
Abjad Documentation

Release 2.2

Víctor Adán, Trevor Bača

August 30, 2011

CONTENTS

1	Abjad?	3
1.1	Abjad extends Python	3
1.2	Abjad extends LilyPond	3
2	Bartók: Mikrokosmos	5
2.1	The score	5
2.2	The measures	5
2.3	The notes	6
2.4	The details	7
3	Ferneyhough: Unsichtbare Farben	11
3.1	The proportions	11
3.2	The transforms	11
3.3	The rhythms	12
3.4	The score	12
4	Ligeti: Désordre	15
4.1	The cell	16
4.2	The measure	17
4.3	The staff	18
4.4	The score	18
5	Annotations	21
5.1	Creating annotations	21
5.2	Attaching annotations to a component	21
5.3	Getting the annotations attached to a component	21
5.4	Detaching annotations from a component one at a time	22
5.5	Detaching all annotations attached to a component at once	22
5.6	Inspecting the component to which an annotation is attached	22
5.7	Inspecting annotation name	22
5.8	Inspecting annotation value	22
6	Articulations	23
6.1	Creating articulations	23
6.2	Attaching articulations to leaves	23
6.3	Getting the articulations attached to a leaf	23
6.4	Detaching articulations from a leaf one at a time	24
6.5	Detaching all articulations attached to a leaf at once	24
6.6	Inspecting the leaf to which an articulation is attached	24
6.7	Controlling whether an articulation appears above or below the staff	25

6.8	Getting and setting articulation name	25
6.9	Copying articulations	26
6.10	Comparing articulations	26
7	Chords	27
7.1	Making chords from a LilyPond input string	27
7.2	Making chords from chromatic pitch numbers and duration	27
7.3	Getting all the written pitches of a chord at once	27
7.4	Getting the written pitches of a chord one at a time	27
7.5	Adding one pitch to a chord at a time	28
7.6	Adding many pitches to a chord at once	28
7.7	Deleting pitches from a chord	29
7.8	Formatting chords	29
7.9	Working with note heads	29
7.10	Working with empty chords	30
8	Containers	31
8.1	Creating containers	31
8.2	Inspecting music	31
8.3	Inspecting length	31
8.4	Inspecting duration	32
8.5	Adding one component to the end of a container	32
8.6	Adding many components to the end of a container	32
8.7	Finding the index of a component	32
8.8	Inserting a component by index	32
8.9	Removing a component by index	33
8.10	Removing a component by reference	33
8.11	Naming containers	33
8.12	Understanding { } and << >> in LilyPond	34
8.13	Understanding sequential and parallel containers	35
8.14	Changing sequential and parallel containers	36
8.15	Overriding containers	36
8.16	Overriding containers' contents	37
8.17	Removing container overrides	38
9	Instrument marks	39
9.1	Creating instrument marks	39
9.2	Attaching instrument marks to a component	39
9.3	Getting the instrument mark attached to a component	39
9.4	Getting the instrument in effect for a component	40
9.5	Detaching instrument marks from a component one at a time	40
9.6	Detaching all instrument marks attached to a component at once	40
9.7	Inspecting the component to which an instrument mark is attached	41
9.8	Inspecting the instrument name of an instrument mark	41
9.9	Inspecting the short instrument name of an instrument mark	41
10	LilyPond comments	43
10.1	Creating LilyPond comments	43
10.2	Attaching LilyPond comments to leaves	43
10.3	Attaching LilyPond comments to containers	43
10.4	Getting the LilyPond comments attached to a component	44
10.5	Detaching LilyPond comments from a component one at a time	44
10.6	Detaching all LilyPond comments attached to a component at once	45
10.7	Inspecting the component to which a LilyPond comment is attached	45
10.8	Inspecting contents string of a LilyPond comment	45

11 LilyPond files	47
11.1 Making LilyPond files	47
11.2 Inspecting file output	47
11.3 Setting default paper size	47
11.4 Setting global staff size	48
12 Measures	49
12.1 Understanding measures in LilyPond	49
12.2 Understanding measures in Abjad	49
12.3 Creating measures	50
12.4 Working with dynamic measures	50
12.5 Adding music to dynamic measures	50
12.6 Removing music from dynamic measures	51
12.7 Setting the denominator of dynamic measures	51
12.8 Suppressing the meter of dynamic measures	51
12.9 Working with anonymous measures	51
12.10 Adding music to anonymous measures	52
12.11 Removing music from anonymous measures	52
13 Notes	53
13.1 Making notes from a string	53
13.2 Making notes from chromatic pitch number and duration	53
13.3 Getting the written pitch of notes	53
13.4 Changing the written pitch of notes	53
13.5 Getting the duration attributes of notes	54
13.6 Changing the written duration of notes	54
13.7 Overriding notes	55
13.8 Removing note overrides	56
14 Pitches	57
14.1 Creation	57
14.2 Name inspection	57
14.3 Octave inspection	57
14.4 Sorting	57
14.5 Pitch comparison	58
14.6 Pitch conversion	58
14.7 Pitch-class conversion	58
14.8 Copying	59
15 Rests	61
15.1 Making rests from strings	61
15.2 Making rests from durations	61
15.3 Getting the duration attributes of rests	61
15.4 Changing the written duration of rests	62
16 Scores	63
16.1 Creating scores	63
16.2 Inspecting score music	63
16.3 Inspecting score length	63
16.4 Inspecting score duration	63
16.5 Adding one component to the bottom of a score	64
16.6 Finding the index of a score component	64
16.7 Removing a score component by index	64
16.8 Removing a score component by reference	65
16.9 Testing score containment	65

16.10 Naming scores	65
17 Spanners	67
17.1 Overriding spanners	67
17.2 Overriding the components to which spanners attach	68
17.3 Removing spanner overrides	68
18 Staves	71
18.1 Creating staves	71
18.2 Inspecting staff music	71
18.3 Inspecting staff length	71
18.4 Inspecting staff duration	71
18.5 Adding one component to the end of a staff	72
18.6 Adding many components to the end of a staff	72
18.7 Finding the index of a staff component	72
18.8 Removing a staff component by index	72
18.9 Removing a staff component by reference	73
18.10 Naming staves	73
18.11 Forcing context	73
19 Tuplets	75
19.1 Making a tuplet from a LilyPond input string	75
19.2 Making a tuplet from a list of other Abjad components	75
19.3 Understanding the interpreter display of a tuplet	75
19.4 Understanding the string representation of a tuplet	76
19.5 Inspecting the LilyPond format of a tuplet	76
19.6 Inspecting the music in a tuplet	76
19.7 Inspecting a tuplet's leaves	76
19.8 Getting the length of a tuplet	77
19.9 Getting the duration attributes of a tuplet	77
19.10 Understanding rhythmic augmentation and diminution	77
19.11 Understanding binary and nonbinary tuplets	77
19.12 Adding one component to the end of a tuplet	78
19.13 Adding many components to the end of a tuplet	78
19.14 Finding the index of a component in a tuplet	78
19.15 Removing a tuplet component by index	78
19.16 Removing a tuplet component by reference	79
19.17 Overriding attributes of the LilyPond tuplet number grob	79
19.18 Overriding attributes of the LilyPond tuplet bracket grob	79
20 Voices	81
20.1 Making a voice from a LilyPond input string	81
20.2 Making a voice from a list of other Abjad components	81
20.3 Understanding the <code>repr</code> of a voice	81
20.4 Inspecting the LilyPond format of a voice	82
20.5 Inspecting the music in a voice	82
20.6 Inspecting a voice's leaves	82
20.7 Getting the length of a voice	82
20.8 Getting the duration attributes of a voice	82
20.9 Adding one component to the end of a voice	83
20.10 Adding many components to the end of a voice	83
20.11 Finding the index of a component in a voice	83
20.12 Removing a voice component by index	84
20.13 Removing a voice component by reference	84
20.14 Naming voices	84

20.15	Changing the context of a voice	85
21	Time signature marks by example	87
22	Leaf, Container, Spanner	97
22.1	Example 1	98
22.2	Example 2	99
23	Working with component parentage	101
23.1	Improper parentage	101
23.2	Proper parentage	101
23.3	Parentage attributes	102
24	Working with threads	103
24.1	What is a thread?	103
24.2	What are threads for?	104
24.3	Coda	106
25	Understanding LilyPond grobs	109
25.1	Grobs control typography	109
25.2	Grobs can be overridden	109
25.3	Check the LilyPond docs	110
26	Understanding Abjad overrides	111
26.1	Grob-override component plug-ins	111
26.2	Grob proxies	111
26.3	Dot-chained override syntax	112
27	Codebase	113
27.1	How the Abjad codebase is laid out	113
27.2	Removing prebuilt versions of Abjad before you check out	113
27.3	Installing the development version	114
28	Docs	117
28.1	How the Abjad docs are laid out	117
28.2	Installing Sphinx	117
28.3	Removing old builds of the docs	118
28.4	Generating the Abjad API	118
28.5	Building the HTML docs	118
28.6	Building a PDF of the docs	119
28.7	Building a coverage report	120
28.8	Building other versions of the docs	121
28.9	Inserting images with <code>abjad-book</code>	121
28.10	Updating Sphinx	121
29	Tests	123
29.1	Automated regression?	123
29.2	Running the battery	123
29.3	Reading test output	124
29.4	Writing tests	124
29.5	Test files start with <code>test_</code>	124
29.6	Avoiding name conflicts	124
29.7	Updating <code>py.test</code>	124
29.8	Running <code>doctest</code> on the <code>tools</code> directory	125

30 Scripts	127
30.1 Searching the Abjad codebase with <code>abj-grep</code>	127
30.2 Removing old <code>*.pyc</code> files with <code>abj-rmpycs</code>	128
30.3 Updating your development copy of Abjad with <code>abj-update</code>	128
30.4 Counting lines of code with <code>count-source-lines</code>	128
30.5 Global search-and-replace with <code>replace-in-files</code>	128
30.6 Adding new development scripts	129
31 Timing code	131
32 Profiling code	133
33 Memory consumption	135
34 Class attributes	137
35 Slots	139
36 To-do	141
37 From Trevor and Víctor	145
38 Why LilyPond is right for Abjad	147
38.1 Nested tuplets works out of the box	147
38.2 Broken tuplets work out of the box	147
38.3 Nonbinary meters work out of the box	148
38.4 Lilypond models the musical measure correctly	148
39 Why MIDI is not enough	151
39.1 A very brief overview of midi	151
39.2 Limitations of midi from the point of view of score modeling	151
39.3 Written note durations vs. midi delta-times	152
39.4 Written note pitch vs. midi note-on	152
39.5 Conclusion	152
40 Configuration	153
41 Recalling output	155
41.1 Reopening Abjad PDFs	155
41.2 Looking at LilyPond output	155
41.3 Looking at the LilyPond log	156
42 Working with LilyPond multipliers	157
43 LilyPond equivalencies in Abjad	159
43.1 Turning on proportional notation	159
44 Coding standards	161
45 Working with lists of numbers	165
46 Pitch conventions	167
46.1 Accidental abbreviations	167
46.2 Chromatic pitch numbers	167
46.3 Diatonic pitch numbers	168
46.4 Octave designation	169
46.5 Accidental spelling	169

47	Setting pitch deviation	171
48	Duration conventions	173
48.1	Introduction	173
48.2	Assignability	173
48.3	Prolation	174
48.4	Duration types	175
48.5	Duration initialization	178
48.6	LilyPond multipliers	179
48.7	Duration interfaces compared	180
49	Template gallery	181
49.1	Default LilyPond layout	181
49.2	lagos.ly	181
49.3	oedo.ly	182
49.4	tangiers.ly	182
49.5	tirnaveni.ly	183
50	Text alignment	185
50.1	Default alignment	185
50.2	TextScript #'self-alignment-X	185
50.3	TextScript #'X-offset	186
51	abjad-book	187
51.1	HTML with embedded Abjad	187
51.2	LaTeX with embedded Abjad	188
51.3	Using abjad-book on ReST documents	190
51.4	Using [hide = True]	190
52	X11 color names	191
53	Bibliography	193
54	Version history	195
54.1	Abjad 1.1.1	195
54.2	Abjad 1.1.0	195
54.3	Abjad 1.0.1055	195
54.4	Abjad 1.0.1022	196
55	Installation	197
55.1	Abjad depends on Python	197
55.2	Abjad depends on LilyPond	197
55.3	Installing the current packaged version of Abjad with <code>easy_install</code>	197
55.4	Installing the current packaged version of Abjad from the Python Package Index	198
55.5	Note for Linux users	198
56	What next?	199
56.1	Get in touch!	199
57	Abjad API	201
57.1	Abjad API	201
	Bibliography	737
	Index	739

Abjad helps composers build up complex pieces of music notation in an iterative and incremental way. Use Abjad to create a symbolic representation of all the notes, rests, staves, tuplets, beams and slurs in any score.

Note: The Abjad documentation is a work in progress.

[Start here](#)

ABJAD?

Abjad is an interactive software system designed to help composers build up complex pieces of music notation in an iterative and incremental way. Use Abjad to create a symbolic representation of all the notes, rests, staves, tuplets, beams and slurs in any score. Because Abjad extends the Python programming language, you can use Abjad to make systematic changes to your music as you work. And because Abjad wraps the powerful LilyPond music notation package, you can use Abjad to control the typographic details of the symbols on the page.

1.1 Abjad extends Python

[Python](#) is an open-source programming language invented by Guido van Rossum and further developed by a team of programmers working in many countries around the world. Python is used for everything from scripting to the development of complex distributed systems. The dynamic language and interpreter features of Python are similar to Ruby while the syntax of Python resembles C, C++ and Java. Code written in Python scales well, tests well and develops quickly.

1.2 Abjad extends LilyPond


[LilyPond](#) is an open-source music notation package invented by Han-Wen Nienhuys and Jan Niewenhuizen and extended by an international team of developers and musicians. LilyPond differs from other music engraving programs in a number of ways. LilyPond separates musical content from page layout. LilyPond affords typographic control over almost everything. And LilyPond implements the rhythmic model of score correctly: barline-crossing durations, broken tuplets and nonbinary meters all work correctly out of the box. For more, see [Why LilyPond is right for Abjad](#).

Examples

BARTÓK: MIKROKOSMOS

This example reconstructs the last five measures of Bartók's "Wandering" from *Mikrokosmos*, volume III. The end result is just a few measures long but covers the basic features you'll use most often in Abjad.

Here is what we want to end up with:



2.1 The score

We'll construct the fragment top-down from containers to notes. We could have done it the other way around but it will be easier to keep the big picture in mind this way. Later, you can rebuild the example bottom-up as an exercise.

First let's create an empty score with a pair of staves connected by a brace:

```
abjad> score = Score([ ])
abjad> piano_staff = scoretools.PianoStaff([ ])
abjad> upper_staff = Staff([ ])
abjad> lower_staff = Staff([ ])

abjad> piano_staff.append(upper_staff)
abjad> piano_staff.append(lower_staff)
abjad> score.append(piano_staff)
```

Here we create an empty score and assign it to the `score` variable. Then we create an empty piano staff assigned to the `piano_staff` variable and two empty staves assigned to the `upper_staff` and `lower_staff` variables. Finally, we append the two staves to the piano staff and the piano staff to the score.

2.2 The measures

Now let's add some measures to our score:

```

abjad> m1 = Measure((2, 4), [ ])
abjad> m2 = Measure((3, 4), [ ])
abjad> m3 = Measure((2, 4), [ ])
abjad> m4 = Measure((2, 4), [ ])
abjad> m5 = Measure((2, 4), [ ])

abjad> upper_measures = [m1, m2, m3, m4, m5]
abjad> lower_measures = componenttools.copy_components_and_covered_spanners(upper_measures)

abjad> upper_staff.extend(upper_measures)
abjad> lower_staff.extend(lower_measures)

```

The lower measures are copies of the upper measures.

Note that we add lists of measures to staves with `extend()`. This is because `extend()` is used for adding many objects to an iterable at once while `append()` is used to add only one object at a time.

2.3 The notes

Now let's add some notes. We begin with the upper staff:

```

abjad> upper_measures[0].extend([Note(i, (1, 8)) for i in [9, 7, 5, 4]])

abjad> upper_measures[1].extend(notetools.make_notes([2, 7, 5, 4, 2], [(1, 4)] + [(1, 8)] * 4))

abjad> notes = notetools.make_notes([0, 2, 4, 5, 4], [(1, 8), (1, 16), (1, 16), (1, 8), (1, 8)])
abjad> upper_measures[2].extend(notes)

abjad> upper_measures[3].append(Note("d'2"))

abjad> upper_measures[4].append(Note("d'2"))

```

Now let's add notes to the lower staff. This will be a more intricate process than that needed for the upper staff. We added notes directly to the measures of the upper staff. But this will not be possible for the lower staff because of the simultaneous voices the lower staff contains.

We add notes to the lower staff measure by measure:

```

abjad> main_voice_m1 = Voice("b4 d'8 c'8")
abjad> main_voice_m1.name = 'main_voice'
abjad> lower_measures[0].append(main_voice_m1)

abjad> main_voice_m2 = Voice("b8 a8 af4 c'8 bf8")
abjad> main_voice_m2.name = 'main_voice'
abjad> lower_measures[1].append(main_voice_m2)

abjad> main_voice_m3 = Voice("a8 g8 fs8 gl6 a16")
abjad> main_voice_m3.name = 'main_voice'
abjad> lower_measures[2].append(main_voice_m3)

```

Notice that we give the same name to the three voices contained in the first three measures of the lower staff.

It is in the last two measures of the lower staff where Bartók writes two voices at once. We'll name the second of these two voices the *appendix_voice*:


```

abjad> appendix_voice_m4 = Voice([Note("b2")])
abjad> appendix_voice_m4.name = 'appendix_voice'
abjad> lilypond_command_mark = marktools.LilyPondCommandMark('voiceOne')
abjad> lilypond_command_mark.attach_mark(appendix_voice_m4)

abjad> main_voice_m4 = Voice("b4 a4")
abjad> main_voice_m4.name = 'main_voice'
abjad> lilypond_command_mark = marktools.LilyPondCommandMark('voiceTwo')
abjad> lilypond_command_mark.attach_mark(main_voice_m4)

abjad> container = Container([appendix_voice_m4, main_voice_m4])
abjad> container.is_parallel = True
abjad> lower_measures[3].append(container)

```

The LilyPond `\voiceOne` and `\voiceTwo` commands determine the direction of the stems in different voices.

Note that we must put both voices in a parallel container because they occur at the same time in the score. We do this by creating an Abjad container and then setting the `is_parallel` attribute of the container to true.

We now do a similar thing for the last measure:

```

abjad> appendix_voice_m5 = Voice("b2")
abjad> appendix_voice_m5.name = 'appendix_voice'
abjad> lilypond_command_mark = marktools.LilyPondCommandMark('voiceOne')
abjad> lilypond_command_mark.attach_mark(appendix_voice_m5)

abjad> main_voice_m5 = Voice("g2")
abjad> main_voice_m5.name = 'main_voice'
abjad> lilypond_command_mark = marktools.LilyPondCommandMark('voiceTwo')
abjad> lilypond_command_mark.attach_mark(main_voice_m5)

abjad> container = Container([appendix_voice_m5, main_voice_m5])
abjad> container.is_parallel = True
abjad> lower_measures[4].append(container)

```

Here's our work so far:

```
abjad> show(score)
```



2.4 The details

Ok, let's add the details. First, notice that the bottom staff has a treble clef just like the top staff. Let's change that:

```
abjad> contexttools.ClefMark('bass')(lower_staff)
```

Now let's add dynamic marks. For the top staff, we'll add them to the first note of the first measure and the second note of the second measure. For the bottom staff, we'll add dynamic markings to the second note of the first measure and the fourth note of the second measure.

```
abjad> contexttools.DynamicMark('pp')(upper_measures[0][0])
abjad> contexttools.DynamicMark('mp')(upper_measures[1][1])
abjad> contexttools.DynamicMark('pp')(lower_measures[0][0][1])
abjad> contexttools.DynamicMark('mp')(lower_measures[1][0][3])
```

Let's add a double bar to the end of the piece:

```
lilypond_command_mark = marktools.LilyPondCommandMark('bar "|.",', format_slot = 'closing')
abjad> lilypond_command_mark.attach_mark(lower_staff.leaves[-1])
```

And see how things are coming out:

```
abjad> show(score)
```



Notice that the beams of the eighth and sixteenth notes appear as you would usually expect: grouped by beat. We get this for free thanks to LilyPond's default beaming algorithm. But this is not the way Bartók notated the beams. Let's set the beams as Bartók did with some crossing the bar lines:

```
abjad> spannertools.BeamSpanner(upper_measures[0])
abjad> spannertools.BeamSpanner(lower_staff.leaves[1:5])
abjad> spannertools.BeamSpanner(lower_staff.leaves[6:10])

abjad> show(score)
```



Now some slurs:

```
abjad> spannertools.SlurSpanner(upper_staff.leaves[0:5])
abjad> spannertools.SlurSpanner(upper_staff.leaves[5:])
abjad> spannertools.SlurSpanner(lower_staff.leaves[1:6])
abjad> spannertools.SlurSpanner(lower_staff.leaves[6:13] + (main_voice_m4, main_voice_m5))
```

Hairpins:

```
abjad> spannertools.CrescendoSpanner(upper_staff.leaves[-7:-2])
abjad> spannertools.DecrescendoSpanner(upper_staff.leaves[-2:])
```

A ritardando marking above the last seven notes of the upper staff:


```
abjad> text_spanner = spannertools.TextSpanner(upper_staff.leaves[-7:])
abjad> text_spanner.override.text_spanner.bound_details__left__text = markuptools.Markup('ritard.')
```

And ties connecting the last two notes in each staff:

```
abjad> tietools.TieSpanner(upper_staff[-2:])  
abjad> tietools.TieSpanner([appendix_voice_m4[0], appendix_voice_m5[0]])
```

The final result:

```
abjad> show(score)
```



FERNEYHOUGH: UNSICHTBARE FARBEN

Mikhail Malt analyzes the rhythmic materials of Ferneyhough’s *Unsichtbare Farben* in *The OM Composer’s Book 2*.

Malt explains that Ferneyhough used OpenMusic to create an “exhaustive catalogue of rhythmic cells” such that:

1. They are subdivided into two pulses, with proportions from 1/1 to 1/11.
2. The second pulse is subdivided successively by 1, 2, 3, 4, 5 and 6.

Let’s recreate Malt’s results in Abjad.

3.1 The proportions

First we define proportions:

```
abjad> proportions = [(1, n) for n in range(1, 11 + 1)]

abjad> proportions
[(1, 1), (1, 2), (1, 3), (1, 4), (1, 5), (1, 6), (1, 7), (1, 8), (1, 9), (1, 10), (1, 11)]
```

3.2 The transforms

Then we make aliases to give shorter names to two functions with long names:

```
abjad> make_tuplet = tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_encourage_c
abjad> tie_chain_to_tuplet = tietools.tie_chain_to_diminished_tuplet_with_proportions_and_encourage_c
```

And then define a helper function:

```
def divide_tuplet(tuplet, n):
    last_tie_chain = tietools.get_tie_chain(tuplet[-1])
    proportions = n * [1]
    new = tie_chain_to_tuplet(last_tie_chain, proportions)
    return new
```

3.3 The rhythms

We set the duration of each tuplet equal to a quarter note:

```
abjad> duration = Fraction(1, 4)
```

And then we make the rhythms:

```
for proportion in proportions:
    tuplets = [ ]
    for n in range(1, 6 + 1):
        tuplet = make_tuplet(duration, proportion)
        divide_tuplet(tuplet, n)
        tuplets.append(tuplet)
    staff.extend(tuplets)
```

3.4 The score

Finally we make the score:

```
abjad> staff = stafftools.RhythmicStaff(music)
abjad> score = Score([staff])
abjad> lily_file = lilyfiletools.make_basic_lily_file(score)
```

Configure containers:

```
abjad> contexttools.TimeSignatureMark((1, 4))(staff)
abjad> score.override.bar_number.transparent = True
abjad> score.set.proportional_notation_duration = schemetools.SchemeMoment(1, 56)
abjad> score.set.tuplet_full_length = True
abjad> score.override.spacing_spanner.uniform_stretching = True
abjad> score.override.spacing_spanner.strict_note_spacing = True
abjad> score.override.tuplet_bracket.padding = 2
abjad> score.override.tuplet_bracket.staff_padding = 4
abjad> score.override.tuplet_number.text = schemetools.SchemeFunction('tuplet-number::calc-fraction-t')
abjad> score.override.time_signature.stencil = False
abjad> score.override.bar_line.stencil = False
```

Configure the LilyPond file:

```
abjad> lily_file.default_paper_size = '11x17', 'portrait'
abjad> lily_file.global_staff_size = 12
abjad> lily_file.layout_block.indent = 0
abjad> lily_file.layout_block.ragged_right = True
abjad> lily_file.paper_block.ragged_bottom = True
abjad> space = schemetools.SchemePair('space', 18)
abjad> stretchability = schemetools.SchemePair('stretchability', 0)
abjad> vector = schemetools.SchemeVector(space, stretchability)
abjad> lily_file.paper_block.between_system_spacing = vector
```

And show the result:

```
abjad> show(lily_file)
```


LIGETI: DÉSORDRE

This example demonstrates the power of exploiting redundancy to model musical structure. The piece that concerns us here is Ligeti’s *Désordre*: the first piano study from Book I. Specifically, we will focus on modeling the first section of the piece:

[illegible]

The redundancy is immediately evident in the repeating pattern found in both staves. The pattern is hierarchical. At the smallest level we have what we will here call a *cell*:

There are two of these cells per measure. Notice that the cells are strictly contained within the measure (i.e., there are no cells crossing a bar line). So, the next level in the hierarchy is the measure. Notice that the measure sizes (the meters) change and that these changes occur independently for each staff, so that each staff carries it's own sequence of measures. Thus, the staff is the next level in the hierarchy. Finally there's the piano staff, which is composed of the right hand and left hand staves.

In what follows we will model this structure in this order (*cell*, *measure*, *staff*, *piano staff*), from bottom to top.

4.1 The cell

Before plunging into the code, observe the following characteristic of the *cell*:

1. It is composed of two layers: the top one which is an octave “chord” and the bottom one which is a straight eighth note run.
2. The total duration of the *cell* can vary, and is always the sum of the eight note runs.
3. The eight note runs are always stem down while the octave “chord” is always stem up.
4. The eight note runs are always beamed together and slurred, and the first two notes always have the dynamic markings ‘f’ ‘p’.

The two “layers” of the *cell* we will model with two Voices inside a parallel Container. The top Voice will hold the octave “chord” while the lower Voice will hold the eighth note run. First the eighth notes:

```
abjad> pitches = [1, 2, 3]
abjad> notes = notetools.make_notes(pitches, [(1, 8)])
abjad> spannertools.BeamSpanner(notes)
abjad> spannertools.SlurSpanner(notes)
abjad> contexttools.DynamicMark('f')(notes[0])
abjad> contexttools.DynamicMark('p')(notes[1])

abjad> voice_lower = Voice(notes)
abjad> voice_lower.name = 'rh_lower'
abjad> marktools.LilyPondCommandMark('voiceTwo')(voice_lower)
```

The notes belonging to the eighth note run are first beamed and slurred. Then we add the dynamic marks to the first two notes, and finally we put them inside a Voice. After naming the voice we number it 2 so that the stems of the notes point down.

Now we construct the octave:

```
abjad> import math
abjad> n = int(math.ceil(len(pitches) / 2.))
abjad> chord = Chord([pitches[0], pitches[0] + 12], (n, 8))
abjad> marktools.Articulation('>')(chord)

abjad> voice_higher = Voice([chord])
abjad> voice_higher.name = 'rh_higher'
abjad> marktools.LilyPondCommandMark('voiceOne')(voice_higher)
```

The duration of the chord is half the duration of the running eighth notes if the duration of the running notes is divisible by two. Otherwise the duration of the chord is the next integer greater than this half. We add the articulation marking and finally add the Chord to a Voice, to which we set the number to 1, forcing the stem to always point up.

Finally we combine the two voices in a parallel Container:

```
abjad> p = Container([voice_lower, voice_higher])
abjad> p.is_parallel = True
```

This results in the complete *Désordre cell*:



Because this *cell* appears over and over again, we want to reuse this code to generate any number of these *cells*. We here encapsulate it in a function that will take only a list of pitches:

```
def desordre_cell(pitches):
    '''The function constructs and returns a *Désordre cell*.
       - 'pitches' is a list of numbers or, more generally, pitch tokens.
    '''
    notes = [Note(p, (1, 8)) for p in pitches]
    spannertools.BeamSpanner(notes)
    spannertools.SlurSpanner(notes)
    contextttools.DynamicMark('f')(notes[0])
    contextttools.DynamicMark('p')(notes[1])
    v_lower = Voice(notes)
    v_lower.name = 'rh_lower'
    marktools.LilyPondCommandMark('voiceTwo')(v_lower)

    n = int(math.ceil(len(pitches) / 2.))
    chord = Chord([pitches[0], pitches[0] + 12], (n, 8))
    marktools.Articulation('>')(chord)
    v_higher = Voice([chord])
    v_higher.name = 'rh_higher'
    marktools.LilyPondCommandMark('voiceOne')(v_higher)
    p = Container([v_lower, v_higher])
    p.is_parallel = True
    ### make all 1/8 beats breakable
    for n in v_lower.leaves[:-1]:
        n.bar_line.kind = ''
    return p
```

Now we can call this function to create any number of *cells*. That was actually the hardest part of reconstructing the opening of Ligeti's *Désordre*. Because the repetition of patterns occurs also at the level of measures and staves, we will now define functions to create these other higher level constructs.

4.2 The measure

We define a function to create a measure from a list of lists of numbers:

```
def measure_build(pitches):
    '''Constructs a measure composed of *Désordre cells*.
       - 'pitches' is a list of lists of number (e.g., [[1, 2, 3], [2, 3, 4]])
       The function returns a DynamicMeasure.
    '''
    result = DynamicMeasure([ ])
    for seq in pitches:
        result.append(desordre_cell(seq))
```

The function is very simple. It simply creates a *DynamicMeasure* and then populates it with *cells* that are created internally with the function previously defined. The function takes a list *pitches* which is actually a list of lists of pitches (e.g., `[[1, 2, 3], [2, 3, 4]]`). The list of lists of pitches is iterated to create each of the *cells* to be appended to the *DynamicMeasures*. We could have defined the function to take ready made *cells* directly, but we are building the hierarchy of functions so that we can pass simple lists of lists of numbers to generate the full structure. To construct a Ligeti measure we would call the function like so:

```
abjad> measure = measure_build([[0, 4, 7], [0, 4, 7, 9], [4, 7, 9, 11]])
abjad> show(Staff([measure]))
```



4.3 The staff

Now we move up to the next level, the staff:

```
def staff_build(pitches):
    '''Returns a Staff containing DynamicMeasures.'''
    result = Staff([ ])
    for seq in pitches:
        measure = measure_build(seq)
        result.append(measure)
    return result
```

The function again takes a plain list as argument. The list must be a list of lists (for measures) of lists (for cells) of pitches. The function simply constructs the Ligeti measures internally by calling our previously defined function and puts them inside a Staff. As with measures, we can now create full measure sequences with this new function:

```
abjad> pitches = [[[-1, 4, 5], [-1, 4, 5, 7, 9]], [[0, 7, 9], [-1, 4, 5, 7, 9]]]
abjad> staff = staff_build(pitches)
abjad> show(staff)
```



4.4 The score

Finally a function that will generate the whole opening section of the piece *Désordre*:

```
def desordre_build(pitches):
    '''Returns a complete PianoStaff with Ligeti music!'''
    assert len(pitches) == 2
    piano = PianoStaff([ ])
    ### build the music...
    for hand in pitches:
        seq = staff_build(hand)
        piano.append(seq)
    ### set clef and key signature to left hand staff...
    piano[1].clef.forced = stafftools.Clef('bass')
    piano[1].key_signature.forced = tonalitytools.KeySignature('b', 'major')
    return piano
```

The function creates a PianoStaff, constructs Staves with Ligeti music and appends these to the empty PianoStaff. Finally it sets the clef and key signature of the lower staff to match the original score. The argument of the function is

a list of length 2, depth 3. The first element in the list corresponds to the upper staff, the second to the lower staff.

The final result:

```
abjad> top = [[[-1, 4, 5], [-1, 4, 5, 7, 9]], [[0, 7, 9], [-1, 4, 5, 7, 9]], [[2, 4, 5, 7, 9], [0, 5, 7, 9]],
abjad> bottom = [[[-9, -4, -2], [-9, -4, -2, 1, 3]], [[-6, -2, 1], [-9, -4, -2, 1, 3]], [[-4, -2, 1, 3], [-2, 1, 3, 5, 7, 9]],
abjad>
abjad> desordre = desordre_build([top, bottom])
abjad> show(desordre)
```



Now that we have the redundant aspect of the piece compactly expressed and encapsulated, we can play around with it by changing the sequence of pitches.

Note: In order for each staff to carry its own sequence of independent measure changes, LilyPond requires some special setting up prior to rendering. Specifically, one must move the *Timing_translator* from the score level to the level of staves. In this example we used the ‘tirnaveni’ template, which is configured to do just that. You may want to study this template (in the “templates” directory of the abjad distribution). Refer to the LilyPond documentation on [Polymetric notation](#) to learn all about how this works.

Reference manual

ANNOTATIONS

Annotate components with user-specific information for future use.

Annotations do not impact formatting.

5.1 Creating annotations

Use mark tools to create annotations:

```
abjad> annotation = marktools.Annotation('special pitch', pitchtools.NamedChromaticPitch('bs'))

abjad> annotation
Annotation('special pitch', NamedChromaticPitch('bs'))
```

5.2 Attaching annotations to a component

Attach annotations to any component with `attach_mark()`:

```
abjad> note = Note("c'4")
abjad> annotation.attach_mark(note)

abjad> annotation
Annotation('special pitch', NamedChromaticPitch('bs'))(c'4)

abjad> another_annotation = marktools.Annotation('special pitch', pitchtools.NamedChromaticPitch('bs'))
abjad> another_annotation.attach_mark(note)

abjad> another_annotation
Annotation('special pitch', NamedChromaticPitch('bs'))(c'4)
```

5.3 Getting the annotations attached to a component

Use mark tools to get all the annotations attached to a component:

```
abjad> marktools.get_annotations_attached_to_component(note)
(Annotation('special pitch', NamedChromaticPitch('bs'))(c'4), Annotation('special pitch', NamedChromaticPitch('bs'))(c'4))
```

5.4 Detaching annotations from a component one at a time

Use `detach_mark()` to detach annotations from a component one at a time:

```
abjad> annotation.detach_mark()

abjad> annotation
Annotation('special pitch', NamedChromaticPitch('bs'))
```

5.5 Detaching all annotations attached to a component at once

Or use mark tools to detach all annotations attached to a component at once:

```
abjad> print marktools.detach_annotations_attached_to_component(note)
(Annotation('special pitch', NamedChromaticPitch('bs')),)

abjad> marktools.get_annotations_attached_to_component(note)
()
```

5.6 Inspecting the component to which an annotation is attached

Use `start_component` to inspect the component to which an annotation is attached:

```
abjad> annotation.attach_mark(note)

abjad> annotation.start_component
Note("c'4")
```

5.7 Inspecting annotation name

Use `name` to get the name of any annotation:

```
abjad> annotation.name
'special pitch'
```

5.8 Inspecting annotation value

And use `value` to get the value of any annotation:

```
abjad> annotation.value
NamedChromaticPitch('bs')
```


ARTICULATIONS

Articulations model staccati, marcati, tenuti and other symbols. Articulations attach notes, rests or chords.

6.1 Creating articulations

Use `marktools` to create articulations:

```
articulation = marktools.Articulation('marcato')  
  
abjad> articulation  
Articulation('marcato', '-')
```

6.2 Attaching articulations to leaves

Use `attach_mark()` to attach any articulation to a leaf:

```
abjad> staff = Staff("c'4 d'4 e'4 f'4")  
  
abjad> articulation.attach_mark(staff[0])  
  
abjad> show(staff)
```



6.3 Getting the articulations attached to a leaf

Use `marktools` to get the articulations attached to a leaf:

```
abjad> marktools.get_articulations_attached_to_component(staff[0])  
(Articulation('marcato', '-') (c'4),)
```

6.4 Detaching articulations from a leaf one at a time

Detach articulations by hand with `detach_mark()`:

```
abjad> articulation.detach_mark()
```

```
abjad> articulation
-\marcato
```

```
abjad> show(staff)
```



6.5 Detaching all articulations attached to a leaf at once

Use `marktools` to detach all articulations attached to a leaf at once:

```
abjad> articulation_1 = marktools.Articulation('marcato')
abjad> articulation_1.attach_mark(staff[0])
```

```
abjad> articulation_2 = marktools.Articulation('staccato')
abjad> articulation_2.attach_mark(staff[0])
```

```
abjad> show(staff)
```



```
abjad> marktools.detach_articulations_attached_to_component(staff[0])
```

```
abjad> show(staff)
```



6.6 Inspecting the leaf to which an articulation is attached

Use `start_component` to inspect the component to which an articulation is attached:

```
abjad> articulation = marktools.Articulation('marcato')
abjad> articulation.attach_mark(staff[0])
```

```
abjad> show(staff)
```



```
abjad> articulation.start_component
Note("c'4")
```

6.7 Controlling whether an articulation appears above or below the staff

Set `direction_string` to `'^'` to force an articulation to appear above the staff:

```
abjad> articulation.direction_string = '^'
```

```
abjad> show(staff)
```



Set `direction_string` to `'_'` to force an articulation to appear below the staff:

```
abjad> articulation.direction_string = '_'
```

```
abjad> show(staff)
```



Set `direction_string` to `'-'` to allow LilyPond to position an articulation automatically:

```
abjad> articulation.direction_string = '-'
```

```
abjad> show(staff)
```



6.8 Getting and setting articulation name

Set the `name_string` of an articulation to change the symbol an articulation prints:

```
abjad> articulation.name_string = 'staccatissimo'
```

```
abjad> show(staff)
```



6.9 Copying articulations

Use `copy.copy()` to copy an articulation:

```
abjad> import copy

abjad> articulation_copy_1 = copy.copy(articulation)

abjad> articulation_copy_1
Articulation('staccatissimo', '-')

abjad> articulation_copy_1.attach_mark(staff[1])

abjad> show(staff)
```



Or use `copy.deepcopy()` to do the same thing:

```
abjad> articulation_copy_2 = copy.deepcopy(articulation)

abjad> articulation_copy_2
Articulation('staccatissimo', '-')

abjad> articulation_copy_2.attach_mark(staff[2])

abjad> show(staff)
```



6.10 Comparing articulations

Articulations compare equal with equal direction name strings and direction strings:

```
abjad> articulation.name_string
'staccatissimo'
abjad> articulation.direction_string
'-'

abjad> articulation_copy_1.name_string
'staccatissimo'
abjad> articulation_copy_1.direction_string
'-'

abjad> articulation == articulation_copy_1
True
```

Otherwise articulations do not compare equal.

CHORDS

7.1 Making chords from a LilyPond input string

You can make chords from a LilyPond input string:

```
abjad> chord = Chord("<c' d' bf'>4")
```

```
abjad> show(chord)
```



7.2 Making chords from chromatic pitch numbers and duration

You can also make chords from chromatic pitch numbers and duration:

```
abjad> chord = Chord([0, 2, 10], Duration(1, 4))
```

```
abjad> show(chord)
```



7.3 Getting all the written pitches of a chord at once

You can get all the written pitches of a chord at one time:

```
abjad> chord.written_pitches  
(NamedChromaticPitch("c'"), NamedChromaticPitch("d'"), NamedChromaticPitch("bf'"))
```

Abjad returns a read-only tuple of named chromatic pitches.

7.4 Getting the written pitches of a chord one at a time

You can get the written pitches of a chord one at a time:

```
abjad> chord.written_pitches[0]
NamedChromaticPitch("c' ")
```

Chords index the pitch they contain starting from 0 (just like tuples and lists).

7.5 Adding one pitch to a chord at a time

Use `append()` to add one note to a chord.

You can add a pitch to a chord with a chromatic pitch number:

```
abjad> chord.append(9)
```

```
abjad> show(chord)
```



Or you can add a pitch to a chord with a chromatic pitch name:

```
abjad> chord.append("df' ")
```

```
abjad> show(chord)
```



Chords sort their pitches every time you add a new one.

This means you can add pitches to your chord in any order.

7.6 Adding many pitches to a chord at once

Use `extend()` to add many pitches to a chord.

You can use chromatic pitch numbers:

```
abjad> chord.extend([3, 4, 14])
```

```
abjad> show(chord)
```



Or you can chromatic pitch names:

```
abjad> chord.extend(["g' ", "af' "])
```

```
abjad> show(chord)
```




7.7 Deleting pitches from a chord

Delete pitches from a chord with `del()`:

```
abjad> del(chord[0])
```

```
abjad> show(chord)
```



```
abjad> del(chord[0])
```

```
abjad> show(chord)
```



Negative indices work too:

```
abjad> del(chord[-1])
```

```
abjad> show(chord)
```



7.8 Formatting chords

Get the LilyPond input format of any Abjad object with `format`:

```
abjad> chord.format
<ef' e' a' bf' df'' d'' g''>4
```

Use `f()` as a short-cut to print the LilyPond input format of any Abjad object:

```
abjad> f(chord)
<ef' e' a' bf' df'' d'' g''>4
```

7.9 Working with note heads

Most of the time you will work with the pitches of a chord. But you can get the note heads of a chord, too:


```
abjad> chord.note_heads
(NoteHead("ef'"), NoteHead("e'"), NoteHead("a'"), NoteHead("bf'"), NoteHead("df''"), NoteHead("d''"))
```

This is useful when you want to apply LilyPond overrides to note heads in a chord one at a time:

```
abjad> chord[2].tweak.color = 'red'
abjad> chord[3].tweak.color = 'blue'
abjad> chord[4].tweak.color = 'green'
```

```
abjad> f(chord)
<
    ef'
    e'
    \tweak #'color #red
    a'
    \tweak #'color #blue
    bf'
    \tweak #'color #green
    df''
    d''
    g''
>4
```

```
abjad> show(chord)
```



7.10 Working with empty chords

Abjad allows empty chords:

```
abjad> chord = Chord([ ], Duration(1, 4))
Chord('<>4')
```

Abjad formats empty chords, too:

```
abjad> f(chord)
<>4
```

But if you pass empty chords to `show()` LilyPond will complain because empty chords don't constitute valid LilyPond input.

When you are done working with an empty chord you can add pitches back into it chord in any of the ways described above:

```
abjad> chord.extend(["gf'", "df''", "g''"])
```

```
abjad> show(chord)
```



CONTAINERS

8.1 Creating containers

Create a container with components:

```
abjad> container = Container([Note("ds'16"), Note("cs'16"), Note("e'16"), Note("c'16")])  
abjad> show(container)
```



Or with a note-entry string:

```
abjad> container = Container("ds'16 cs'16 e'16 c'16 d'2 ~ d'8")  
abjad> show(container)
```



8.2 Inspecting music

Return the components in a container with `music`:

```
abjad> container.music  
(Note("ds'16"), Note("cs'16"), Note("e'16"), Note("c'16"), Note("d'2"), Note("d'8"))
```

Or with a special call to `__getslice__`:

```
abjad> container[:]  
[Note("ds'16"), Note("cs'16"), Note("e'16"), Note("c'16"), Note("d'2"), Note("d'8")]
```

8.3 Inspecting length

Get the length of a container with `len()`:

```
abjad> len(container)
6
```

8.4 Inspecting duration

Contents duration equals the sum of the duration of everything inside the container:

```
abjad> container.contents_duration
Duration(7, 8)
```

8.5 Adding one component to the end of a container

Add one component to the end of a container with `append`:

```
abjad> container.append(Note("af' 32"))

abjad> show(container)
```



8.6 Adding many components to the end of a container

Add many components to the end of a container with `extend`:

```
abjad> container.extend([Note("c' ' 32"), Note("a' 32")])

abjad> show(container)
```



8.7 Finding the index of a component

Find the index of a component with `index`:

```
abjad> note = container[7]

abjad> container.index(note)
7
```

8.8 Inserting a component by index

Insert a component by index with `insert`:

```
abjad> container.insert(-3, Note("g'32"))
```

```
abjad> show(container)
```



8.9 Removing a component by index

Remove a component by index with `pop`:

```
abjad> container.pop(-1)
```

```
abjad> show(container)
```



8.10 Removing a component by reference

Remove a component by reference with `remove`:

```
abjad> container.remove(container[-1])
```

```
abjad> show(container)
```



Note: `__getslice__`, `__setslice__` and `__delslice__` remain to be documented.

8.11 Naming containers

You can name Abjad containers:

```
abjad> flute_staff = Staff("c'8 d'8 e'8 f'8")
abjad> flute_staff.name = 'Flute'
abjad> violin_staff = Staff("c'8 d'8 e'8 f'8")
abjad> violin_staff.name = 'Violin'
abjad> staff_group = scoretools.StaffGroup([flute_staff, violin_staff])
abjad> score = Score([staff_group])
```

Container names appear in LilyPond input:

```
abjad> f(score)
\new Score <<
  \new StaffGroup <<
    \context Staff = "Flute" {
      c'8
      d'8
      e'8
      f'8
    }
    \context Staff = "Violin" {
      c'8
      d'8
      e'8
      f'8
    }
  >>
>>
```

And make it easy to retrieve containers later:

```
abjad> componenttools.get_first_component_in_expr_with_name(score, 'Flute')
Staff-"Flute">{4}
```

But container names do not appear in notational output:

```
abjad> show(score)
```



8.12 Understanding { } and << >> in LilyPond

LilyPond uses curly { } braces to wrap a stream of musical events that are to be engraved one after the other:

```
\new Voice {
  e''4
  f''4
  g''4
  g''4
  f''4
  e''4
  d''4
  d''4 \fermata
}
```



LilyPond uses skeleton << >> braces to wrap two or more musical expressions that are to be played at the same time:

```

\new Staff <<
  \new Voice {
    \voiceOne
    e''4
    f''4
    g''4
    g''4
    f''4
    e''4
    d''4
    d''4 \fermata
  }
  \new Voice {
    \voiceTwo
    c''4
    c''4
    b'4
    c''4
    c''8
    b'8
    c''4
    b'4
    b'4 \fermata
  }
>>

```



The examples above are both LilyPond input.

The most common use of LilyPond { } is to group a potentially long stream of notes and rests into a single expression.

The most common use of LilyPond << >> is to group a relatively smaller number of note lists together polyphonically.

8.13 Understanding sequential and parallel containers

Abjad implements LilyPond { } and << >> in the container `is_parallel` attribute.

Some containers set `is_parallel` to false at initialization:

```

staff = Staff([ ])
staff.is_parallel
False

```

Other containers set `is_parallel` to true:

```

score = Score([ ])
score.is_parallel
True

```

8.14 Changing sequential and parallel containers

Set `is_parallel` by hand as necessary:

```
voice_1 = Voice(r"e''4 f''4 g''4 g''4 f''4 e''4 d''4 d''4  ermata")
voice_2 = Voice(r"c''4 c''4 b'4 c''4 c''8 b'8 c''4 b'4 b'4  ermata")
abjad> staff = Staff([voice_1, voice_2])
abjad> staff.is_parallel = True
abjad> marktools.LilyPondCommandMark('voiceOne')(voice_1)
abjad> marktools.LilyPondCommandMark('voiceTwo')(voice_2)
abjad> show(staff)
```



The staff in the example above is set to parallel after initialization to create a type of polyphonic staff:

```
abjad> f(staff)
\new Staff <<
  \new Voice {
    \voiceOne
    e''4
    f''4
    g''4
    g''4
    f''4
    e''4
    d''4
    d''4 -\fermata
  }
  \new Voice {
    \voiceTwo
    c''4
    c''4
    b'4
    c''4
    c''8
    b'8
    c''4
    b'4
    b'4 -\fermata
  }
>>
```

8.15 Overriding containers

The symbols below are black with fixed thickness and predetermined spacing:

```
abjad> staff = Staff("c'4 d'4 e'4 f'4 g'4 a'4 g'2")
abjad> slur_1 = spannertools.SlurSpanner(staff[:2])
abjad> slur_2 = spannertools.SlurSpanner(staff[2:4])
abjad> slur_3 = spannertools.SlurSpanner(staff[4:6])
```

```
abjad> f(staff)
\new Staff {
    c'4 (
    d'4 )
    e'4 (
    f'4 )
    g'4 (
    a'4 )
    g'2
}
```

```
abjad> show(staff)
```



But you can override LilyPond grobs to change the look of Abjad containers:

```
abjad> staff.override.staff_symbol.color = 'blue'
```

```
abjad> f(staff)
\new Staff \with {
    \override StaffSymbol #'color = #blue
} {
    c'4 (
    d'4 )
    e'4 (
    f'4 )
    g'4 (
    a'4 )
    g'2
}
```

```
abjad> show(staff)
```



8.16 Overriding containers' contents

You can override LilyPond grobs to change the look of containers' contents, too:

```
abjad> staff.override.note_head.color = 'red'
abjad> staff.override.stem.color = 'red'
```

```
abjad> f(staff)
\new Staff \with {
    \override NoteHead #'color = #red
    \override StaffSymbol #'color = #blue
    \override Stem #'color = #red
} {
    c'4 (
    d'4 )
}
```

```

    e'4 (
    f'4 )
    g'4 (
    a'4 )
    g'2
}

```

```
abjad> show(staff)
```



8.17 Removing container overrides

Delete grob overrides you no longer want:

```
abjad> del(staff.override.staff_symbol)
```

```

abjad> f(staff)
\new Staff \with {
    \override NoteHead #'color = #red
    \override Stem #'color = #red
} {
    c'4 (
    d'4 )
    e'4 (
    f'4 )
    g'4 (
    a'4 )
    g'2
}

```

```
abjad> show(staff)
```



INSTRUMENT MARKS

Instrument marks appear as markup in the left margin of your score.

9.1 Creating instrument marks

Use `contexttools` to create instrument marks:

```
abjad> instrument_mark = contexttools.InstrumentMark('Violin ', 'Vn. ')

abjad> instrument_mark
InstrumentMark('Violin ', 'Vn. ')
```

9.2 Attaching instrument marks to a component

Use `attach_mark()` to attach any mark to a component:

```
abjad> staff = Staff("c'4 d'4 e'4 f'4")

abjad> instrument_mark.attach_mark(staff)

abjad> show(staff)
```



9.3 Getting the instrument mark attached to a component

Use `contexttools` to get the instrument mark attached to a component:

```
abjad> contexttools.get_instrument_mark_attached_to_component(staff)
InstrumentMark('Violin ', 'Vn. ')(Staff{4})
```

9.4 Getting the instrument in effect for a component

Or to get the instrument currently in effect for a component:

```
abjad> contexttools.get_effective_instrument(staff[1])
InstrumentMark('Violin ', 'Vn. ') (Staff{4})
```

9.5 Detaching instrument marks from a component one at a time

Use `detach_mark()` to detach instrument marks from a component one at a time:

```
abjad> instrument_mark.detach_mark()
```

```
abjad> instrument_mark
InstrumentMark('Violin ', 'Vn. ')
```

```
abjad> show(staff)
```



9.6 Detaching all instrument marks attached to a component at once

Or use `contexttools` to detach instrument marks all at once:

```
abjad> instrument_mark = contexttools.InstrumentMark('Violin ', 'Vn. ')
abjad> instrument_mark.attach_mark(staff)
```

```
abjad> instrument_mark
InstrumentMark('Violin ', 'Vn. ') (Staff{4})
```

```
abjad> show(staff)
```



```
abjad> contexttools.detach_instrument_mark_attached_to_component(staff)
```

```
abjad> instrument_mark
InstrumentMark('Violin ', 'Vn. ')
```

```
abjad> show(staff)
```



9.7 Inspecting the component to which an instrument mark is attached

Use `start_component` to inspect the component to which an instrument mark is attached:

```
abjad> instrument_mark = contexttools.InstrumentMark('Flute ', 'Fl. ')
abjad> instrument_mark.attach_mark(staff)

abjad> show(staff)
```



```
abjad> instrument_mark.start_component
Staff{4}
```

9.8 Inspecting the instrument name of an instrument mark

Use `instrument_name` to get the instrument name of any instrument mark:

```
abjad> instrument_mark.instrument_name
Markup('Flute ')
```

9.9 Inspecting the short instrument name of an instrument mark

And use `short_instrument_name` to get the short instrument name of any instrument mark:

```
abjad> instrument_mark.short_instrument_name
Markup('Fl. ')
```


LILYPOND COMMENTS

LilyPond comments begin with the % sign. Abjad models LilyPond comments as marks.

10.1 Creating LilyPond comments

Use `marktools` to create LilyPond comments:

```
abjad> comment_1 = marktools.Comment('This is a LilyPond comment before a note.', 'before')

abjad> comment_1
Comment('This is a LilyPond comment before a note.')
```

10.2 Attaching LilyPond comments to leaves

Attach LilyPond comments to a note, rest or chord with `attach_mark()`:

```
abjad> note = Note("cs''4")
abjad> show(note)
```



```
abjad> comment_1.attach_mark(note)

abjad> f(note)
% This is a LilyPond comment before a note.
cs''4
```

You can add LilyPond comments before, after or to the right of any leaf.

10.3 Attaching LilyPond comments to containers

Use `attach_mark()` to attach LilyPond comments to a container:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> show(staff)
```



```
abjad> staff_comment_1 = marktools.Comment('Here is a LilyPond comment before the staff.', 'before')
abjad> staff_comment_2 = marktools.Comment('Here is a LilyPond comment in the staff opening.', 'opening')
abjad> staff_comment_3 = marktools.Comment('Here is another LilyPond comment in the staff opening.', 'opening')
abjad> staff_comment_4 = marktools.Comment('LilyPond comment in the staff closing.', 'closing')
abjad> staff_comment_5 = marktools.Comment('LilyPond comment after the staff.', 'after')
```

```
abjad> staff_comment_1.attach_mark(staff)
abjad> staff_comment_2.attach_mark(staff)
abjad> staff_comment_3.attach_mark(staff)
abjad> staff_comment_4.attach_mark(staff)
abjad> staff_comment_5.attach_mark(staff)
```

```
abjad> f(staff)
% Here is a LilyPond comment before the staff.
\new Staff {
    % Here is a LilyPond comment in the staff opening.
    % Here is another LilyPond comment in the staff opening.
    c'8
    d'8
    e'8
    f'8
    % LilyPond comment in the staff closing.
}
% LilyPond comment after the staff.
```

You can add LilyPond comments before, after, in the opening or in the closing of any container.

10.4 Getting the LilyPond comments attached to a component

Use `marktools` to get all the LilyPond comments attached to a component:

```
abjad> marktools.get_comments_attached_to_component(note)
(Comment('This is a LilyPond comment before a note.')(cs''4),)
```

Abjad returns a tuple of zero or more LilyPond comments.

10.5 Detaching LilyPond comments from a component one at a time

Use `detach_mark()` to detach LilyPond comments from a component one at a time:

```
abjad> comment_1 = marktools.get_comments_attached_to_component(note)[0]

abjad> comment_1.detach_mark()
Comment('This is a LilyPond comment before a note.')

abjad> f(note)
cs''4
```

10.6 Detaching all LilyPond comments attached to a component at once

Or use `marktools` to detach all LilyPond comments attached to a component at once:

```
abjad> for comment in marktools.get_comments_attached_to_component(staff): print comment
Comment('Here is a LilyPond comment before the staff.')(Staff{4})
Comment('Here is a LilyPond comment in the staff opening.')(Staff{4})
Comment('Here is another LilyPond comment in the staff opening.')(Staff{4})
Comment('LilyPond comment in the staff closing.')(Staff{4})
Comment('LilyPond comment after the staff.')(Staff{4})
```

```
abjad> marktools.detach_comments_attached_to_component(staff)
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
}
```

10.7 Inspecting the component to which a LilyPond comment is attached

Use `start_component` to inspect the component to which a LilyPond comment is attached:

```
abjad> comment_1.attach_mark(note)
```

```
abjad> comment_1.start_component
Note("cs' '4")
```

10.8 Inspecting contents string of a LilyPond comment

Use `contents_string` to inspect the written contents of a LilyPond comment:

```
abjad> comment_1.contents_string
'This is a LilyPond comment before a note.'
```


LILYPOND FILES

11.1 Making LilyPond files

Make a basic LilyPond input file with the `lilyfiletools` package:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> lily_file = lilyfiletools.make_basic_lily_file(staff)

abjad> lily_file
LilyFile(Staff{4})
```

11.2 Inspecting file output

LilyPond input files that you create this way come equipped with many attributes that appear in file output:

```
abjad> f(lily_file)
% Abjad revision 4651
% 2011-08-21 13:58

\version "2.15.8"
\include "english.ly"
\include "/Users/trevorbaca/Documents/abjad/trunk/abjad/cfg/abjad.scm"

\score {
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
}
```

11.3 Setting default paper size

Set default LilyPond paper size like this:

```
abjad> lily_file.default_paper_size = '11x17', 'landscape'
```

```
abjad> f(lily_file)
% Abjad revision 4651
% 2011-08-21 13:58

\version "2.15.8"
\include "english.ly"
\include "/Users/trevorbaca/Documents/abjad/trunk/abjad/cfg/abjad.scm"

#(set-default-paper-size "11x17" 'landscape)

\score {
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
}
```

11.4 Setting global staff size

Set global staff size like this:

```
abjad> lily_file.global_staff_size = 16

abjad> f(lily_file)
% Abjad revision 4651
% 2011-08-21 13:58

\version "2.15.8"
\include "english.ly"
\include "/Users/trevorbaca/Documents/abjad/trunk/abjad/cfg/abjad.scm"

#(set-default-paper-size "11x17" 'landscape)
#(set-global-staff-size 16)

\score {
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
}
```

MEASURES

12.1 Understanding measures in LilyPond

In LilyPond you specify time signatures by hand and LilyPond creates measures automatically:

```
\new Staff {  
  \time 3/8  
  c'8  
  d'8  
  e'8  
  d'8  
  e'8  
  f'8  
  \time 2/4  
  g'4  
  e'4  
  f'4  
  d'4  
  c'2  
}
```



Here LilyPond creates five measures from two time signatures. This happens because behind-the-scenes LilyPond time-keeping tells the program when measures start and stop and how to draw the barlines that come between them.

12.2 Understanding measures in Abjad

Measures are optional in Abjad, too, and you may omit them in favor of time signatures:

```
abjad> staff = Staff("c'8 d'8 e'8 d'8 e'8 f'8 g'4 e'4 f'4 d'4 c'2")  
  
abjad> contexttools.TimeSignatureMark((3, 8))(staff)  
abjad> contexttools.TimeSignatureMark((2, 4))(staff[6])  
  
abjad> show(staff)
```



But you may also include explicit measures in the Abjad scores you build. The following sections explain how.

12.3 Creating measures

Create a measure with a meter and music:

```
abjad> measure = Measure((3, 8), "c'8 d'8 e'8")
```

```
abjad> f(measure)
{
    \time 3/8
    c'8
    d'8
    e'8
}
```

```
abjad> show(measure)
```



12.4 Working with dynamic measures

Dynamic measures adjust their time signatures on the fly as you add and remove music.

Create dynamic measures without a time signature:

```
abjad> measure = measuretools.DynamicMeasure("c'8 d'8 e'8")
```

```
abjad> show(measure)
```



12.5 Adding music to dynamic measures

Add music to dynamic measures the same as to all containers:

```
abjad> measure.extend([Note("fs'8"), Note("gs'8")])
```

```
abjad> show(measure)
```



12.6 Removing music from dynamic measures

Remove music from dynamic measures the same as with other containers:

```
abjad> del(measure[1:3])
```

```
abjad> show(measure)
```



12.7 Setting the denominator of dynamic measures

You can set the denominator of dynamic measures to any integer power of 2:

```
abjad> measure.denominator = 32
```

```
abjad> show(measure)
```



12.8 Suppressing the meter of dynamic measures

You can temporarily suppress the meter of dynamic measures:

```
abjad> measure.suppress_meter = True
```

```
abjad> f(measure)
```

```
{
    c' 8
    fs' 8
    gs' 8
}
```

LilyPond will engrave the last active meter.

12.9 Working with anonymous measures

Anonymous determine their time signatures on the fly and then hide them at format time.

Create anonymous measures without a time signature:

```
abjad> measure = measuretools.AnonymousMeasure("c' 8 d' 8 e' 8")
```

```
abjad> show(measure)
```



12.10 Adding music to anonymous measures

Add music to anonymous measures the same as to other containers:

```
abjad> measure.extend([Note("fs'8"), Note("gs'8")])
```

```
abjad> show(measure)
```



12.11 Removing music from anonymous measures

Remove music from anonymous measure the same as from other containers:

```
abjad> del(measure[1:3])
```

```
abjad> show(measure)
```



NOTES

13.1 Making notes from a string

You can make notes from string:

```
abjad> note = Note("c' 4")
```

```
abjad> show(note)
```



13.2 Making notes from chromatic pitch number and duration

You can also make notes from chromatic pitch number and duration:

```
abjad> note = Note(0, Duration(1, 4))
```

```
abjad> show(note)
```



(You even use `Note("c' 4")` to create notes with numbers alone.)

13.3 Getting the written pitch of notes

You can get the written pitch of notes:

```
abjad> note.written_pitch  
NamedChromaticPitch("c' ")
```

13.4 Changing the written pitch of notes

And you can change the written pitch of notes:

```
abjad> note.written_pitch = "cs' "
```



(You can use `note.written_pitch = 1` to change pitch with numbers, too.)

13.5 Getting the duration attributes of notes

Get the written duration of notes like this:

```
abjad> note.written_duration
Duration(1, 4)
```

Which is usually the same as preprolated duration:

```
abjad> note.preprolated_duration
Duration(1, 4)
```

And prolated duration:

```
abjad> note.prolated_duration
Duration(1, 4)
```

Except for notes inside a tuplet:

```
abjad> tuplet = Tuplet(Fraction(2, 3), [Note("c'4"), Note("d'4"), Note("e'4")])
```

```
abjad> show(tuplet)
```



```
abjad> note = tuplet[0]
```

Tupletted notes carry written duration:

```
abjad> note.written_duration
Duration(1, 4)
```

Prolation:

```
abjad> note.prolation
Fraction(2, 3)
```

And prolated duration that is the product of the two:

```
abjad> note.prolated_duration
Duration(1, 6)
```

13.6 Changing the written duration of notes

You can change the written duration of notes:


```
abjad> tuplet[0].written_duration = Duration(1, 8)
abjad> tuplet[1].written_duration = Duration(1, 8)
abjad> tuplet[2].written_duration = Duration(1, 8)
```

```
abjad> show(tuplet)
```



Other duration attributes are read-only.

13.7 Overriding notes

The notes below are black with fixed thickness and predetermined spacing:

```
abjad> staff = Staff("c'4 d'4 e'4 f'4 g'4 a'4 g'2")
abjad> slur_1 = spannertools.SlurSpanner(staff[:2])
abjad> slur_2 = spannertools.SlurSpanner(staff[2:4])
abjad> slur_3 = spannertools.SlurSpanner(staff[4:6])
```

```
abjad> f(staff)
```

```
\new Staff {
    c'4 (
    d'4 )
    e'4 (
    f'4 )
    g'4 (
    a'4 )
    g'2
}
```

```
abjad> show(staff)
```



But you can override LilyPond grobs to change the look of notes, rests and chords:

```
abjad> staff[-1].override.note_head.color = 'red'
abjad> staff[-1].override.stem.color = 'red'
```

```
abjad> f(staff)
```

```
\new Staff {
    c'4 (
    d'4 )
    e'4 (
    f'4 )
    g'4 (
    a'4 )
    \once \override NoteHead #'color = #red
    \once \override Stem #'color = #red
    g'2
}
```

```
abjad> show(staff)
```



13.8 Removing note overrides

Delete grob overrides you no longer want:

```
abjad> del(staff[-1].override.stem)
```

```
abjad> f(staff)
\new Staff {
    c'4 (
    d'4 )
    e'4 (
    f'4 )
    g'4 (
    a'4 )
    \once \override NoteHead #'color = #red
    g'2
}
```

```
abjad> show(staff)
```



PITCHES

Named chromatic pitches are the everyday pitches attached to notes and chords:

```
abjad> note = Note("cs' '8")

abjad> note.written_pitch
NamedChromaticPitch("cs' ' ")
```

14.1 Creation

Use pitch tools to create named chromatic pitches:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs' ' ")

abjad> named_chromatic_pitch
NamedChromaticPitch("cs' ' ")
```

14.2 Name inspection

Use `str()` to get the name of named chromatic pitches:

```
abjad> str(named_chromatic_pitch)
cs''
```

14.3 Octave inspection

Get the octave number of named chromatic pitches with `octave_number`:

```
abjad> named_chromatic_pitch.octave_number
5
```

14.4 Sorting

Named chromatic pitches sort by octave, diatonic pitch-class and accidental, in that order:

```
abjad> pitchtools.NamedChromaticPitch('es') < pitchtools.NamedChromaticPitch('ff')
True
```

14.5 Pitch comparison

Compare named chromatic pitches to each other:

```
abjad> named_chromatic_pitch_1 = pitchtools.NamedChromaticPitch("c'")
abjad> named_chromatic_pitch_2 = pitchtools.NamedChromaticPitch("d'")
```

```
abjad> named_chromatic_pitch_1 == named_chromatic_pitch_2
False
```

```
abjad> named_chromatic_pitch_1 != named_chromatic_pitch_2
True
```

```
abjad> named_chromatic_pitch_1 > named_chromatic_pitch_2
False
```

```
abjad> named_chromatic_pitch_1 < named_chromatic_pitch_2
True
```

```
abjad> named_chromatic_pitch_1 >= named_chromatic_pitch_2
False
```

```
abjad> named_chromatic_pitch_1 <= named_chromatic_pitch_2
True
```

14.6 Pitch conversion

Convert any named chromatic pitch to a named diatonic pitch:

```
abjad> named_chromatic_pitch.named_diatonic_pitch
NamedDiatonicPitch("c'")
```

To a numbered chromatic pitch:

```
abjad> named_chromatic_pitch.numbered_chromatic_pitch
NumberedChromaticPitch(13)
```

Or to a numbered diatonic pitch:

```
abjad> named_chromatic_pitch.numbered_diatonic_pitch
NumberedDiatonicPitch(7)
```

14.7 Pitch-class conversion

Convert any named chromatic pitch to a named chromatic pitch-class:

```
abjad> named_chromatic_pitch.named_chromatic_pitch_class
NamedChromaticPitchClass('cs')
```

To a named diatonic pitch-class:

```
abjad> named_chromatic_pitch.named_diatonic_pitch_class
NamedDiatonicPitchClass('c')
```

To a numbered chromatic pitch-class:

```
abjad> named_chromatic_pitch.numbered_chromatic_pitch_class
NumberedChromaticPitchClass(1)
```

Or to a numbered diatonic pitch-class:

```
abjad> named_chromatic_pitch.numbered_diatonic_pitch_class
NumberedDiatonicPitchClass(0)
```

14.8 Copying

Use `copy.copy()` to copy named chromatic pitches:

```
abjad> import copy

abjad> copy.copy(named_chromatic_pitch)
NamedChromaticPitch("cs' ")
```

Or use `copy.deepcopy()` to do the same thing:

```
abjad> copy.deepcopy(named_chromatic_pitch)
NamedChromaticPitch("cs' ")
```


RESTS

15.1 Making rests from strings

You can make rests from a string:

```
abjad> rest = Rest('r8')
```

```
abjad> show(rest)
```



15.2 Making rests from durations

You can also make rests from a duration:

```
abjad> rest = Rest(Duration(1, 4))
```

```
abjad> show(rest)
```



(You can even use `Rest((1, 8))` to make rests from a duration pair.)

15.3 Getting the duration attributes of rests

Get the written duration of rests like this:

```
abjad> rest.written_duration  
Duration(1, 4)
```

Which is usually the same as preprolated duration:

```
abjad> rest.preprolated_duration  
Duration(1, 4)
```

And prolated duration:

```
abjad> rest.prolated_duration
Duration(1, 4)
```

Except for rests inside a tuplet:

```
abjad> tuplet = Tuplet(Fraction(2, 3), [Note("c'4"), Rest('r4'), Note("e'4")])

abjad> show(tuplet)
```



```
abjad> rest = tuplet[1]
```

Tupletted rests carry written duration:

```
abjad> rest.written_duration
Duration(1, 4)
```

Prolation:

```
abjad> rest.prolation
Fraction(2, 3)
```

And prolated duration that is the product of the two:

```
abjad> rest.prolated_duration
Duration(1, 6)
```

15.4 Changing the written duration of rests

You can change the written duration of notes and rests:

```
abjad> tuplet[0].written_duration = Duration(1, 8)
abjad> tuplet[1].written_duration = Duration(1, 8)
abjad> tuplet[2].written_duration = Duration(1, 8)

abjad> show(tuplet)
```



Other duration attributes are read-only.

SCORES

16.1 Creating scores

Create a score like this:

```
abjad> treble_staff_1 = Staff("e'4 d'4 e'4 f'4 g'1")
abjad> treble_staff_2 = Staff("c'2. b8 a8 b1")

abjad> score = Score([treble_staff_1, treble_staff_2])

abjad> show(score)
```



16.2 Inspecting score music

Return score components with `music`:

```
abjad> score.music
(Staff{5}, Staff{4})
```

16.3 Inspecting score length

Get score length with `len()`:

```
abjad> len(score)
2
```

16.4 Inspecting score duration

Score contents duration is equal to the duration of the longest component in score:

```
abjad> score.contents_duration
Duration(2, 1)
```

16.5 Adding one component to the bottom of a score

Add one component to the bottom of a score with `append`:

```
abjad> bass_staff = Staff("g4 f4 e4 d4 d1")
abjad> contexttools.ClefMark('bass')(bass_staff)
```

```
abjad> score.append(bass_staff)
```

```
abjad> show(score)
```



16.6 Finding the index of a score component

Find the index of a score component with `index`:

```
abjad> score.index(treble_staff_1)
0
```

16.7 Removing a score component by index

Use `pop` to remove a score component by index:

```
abjad> score.pop(1)
```

```
abjad> show(score)
```



16.8 Removing a score component by reference

Remove a score component by reference with `remove`:

```
abjad> score.remove(treble_staff_1)
```

```
abjad> show(score)
```



16.9 Testing score containment

Use `in` to find out whether a score contains a given component:

```
abjad> treble_staff_1 in score
False
```

```
abjad> treble_staff_2 in score
False
```

```
abjad> bass_staff in score
True
```

16.10 Naming scores

You can name Abjad scores:

```
abjad> score.name = 'Example Score'
```

Score names appear in LilyPond input:

```
abjad> f(score)
\context Score = "Example Score" <<
  \new Staff {
    \clef "bass"
    g4
    f4
    e4
    d4
    d1
  }
>>
```

But do not appear in notational output:

```
abjad> show(score)
```



SPANNERS

17.1 Overriding spanners

The symbols below are black with fixed thickness and predetermined spacing:

```
abjad> staff = Staff("c'4 d'4 e'4 f'4 g'4 a'4 g'2")
abjad> slur_1 = spannertools.SlurSpanner(staff[:2])
abjad> slur_2 = spannertools.SlurSpanner(staff[2:4])
abjad> slur_3 = spannertools.SlurSpanner(staff[4:6])
```

```
abjad> f(staff)
\new Staff {
    c'4 (
    d'4 )
    e'4 (
    f'4 )
    g'4 (
    a'4 )
    g'2
}
```

```
abjad> show(staff)
```



But you can override LilyPond grobs to change the look of spanners:

```
abjad> slur_1.override.slur.color = 'red'
abjad> slur_3.override.slur.color = 'red'
```

```
abjad> f(staff)
\new Staff {
    \override Slur #'color = #red
    c'4 (
    d'4 )
    \revert Slur #'color
    e'4 (
    f'4 )
    \override Slur #'color = #red
    g'4 (
    a'4 )
}
```

```
\revert Slur #'color
g'2
}
```

```
abjad> show(staff)
```



17.2 Overriding the components to which spanners attach

You can override LilyPond grobs to change spanners' contents:

```
abjad> slur_2.override.slur.color = 'blue'
abjad> slur_2.override.note_head.color = 'blue'
abjad> slur_2.override.stem.color = 'blue'
```

```
abjad> f(staff)
\new Staff {
  \override Slur #'color = #red
  c'4 (
  d'4 )
  \revert Slur #'color
  \override NoteHead #'color = #blue
  \override Slur #'color = #blue
  \override Stem #'color = #blue
  e'4 (
  f'4 )
  \revert NoteHead #'color
  \revert Slur #'color
  \revert Stem #'color
  \override Slur #'color = #red
  g'4 (
  a'4 )
  \revert Slur #'color
  g'2
}
```

```
abjad> show(staff)
```



17.3 Removing spanner overrides

Delete grob overrides you no longer want:

```
abjad> del(slur_1.override.slur)
abjad> del(slur_3.override.slur)
```

```
abjad> f(staff)
\new Staff {
  c'4 (
  d'4 )
  \override NoteHead #'color = #blue
  \override Slur #'color = #blue
  \override Stem #'color = #blue
  e'4 (
  f'4 )
  \revert NoteHead #'color
  \revert Slur #'color
  \revert Stem #'color
  g'4 (
  a'4 )
  g'2
}
```

```
abjad> show(staff)
```



STAVES

18.1 Creating staves

Create staves like this:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'4 c''1")
```

```
abjad> show(staff)
```



18.2 Inspecting staff music

Return staff components with `music`:

```
abjad> staff.music  
(Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8"), Note("g'8"), Note("a'8"), Note("b'4"), Note("c''1"))
```

18.3 Inspecting staff length

Get staff length with `len()`:

```
abjad> len(staff)  
8
```

18.4 Inspecting staff duration

Staff contents durations equals the sum of staff components' duration:

```
abjad> staff.contents_duration  
Duration(2, 1)
```

18.5 Adding one component to the end of a staff

Add one component to the end of a staff with `append`:

```
abjad> staff.append(Note("d' '2"))
```

```
abjad> show(staff)
```



18.6 Adding many components to the end of a staff

Add many components to the end of a staff with `extend`:

```
abjad> notes = [Note("e' '8"), Note("d' '8"), Note("c' '4")]
abjad> staff.extend(notes)
```

```
abjad> show(staff)
```



18.7 Finding the index of a staff component

Find staff component index with `index`:

```
abjad> notes[0]
Note("e' '8")
```

```
abjad> staff.index(notes[0])
9
```

18.8 Removing a staff component by index

Use `pop` to remove a staff component by index:

```
abjad> staff[8]
Note("d' '2")
```

```
abjad> staff.pop(8)
```

```
abjad> show(staff)
```




```
abjad> staff.context
'CustomUserStaff'

abjad> f(staff)
\context CustomUserStaff = "Example Staff" {
    c' 8
    d' 8
    e' 8
    f' 8
    g' 8
    a' 8
    b' 4
    c'' 1
    e'' 8
    d'' 8
}
```

Force context when you have defined a new LilyPond context.

TUPLETS

19.1 Making a tuplet from a LilyPond input string

You can make an Abjad tuplet from a multiplier and a LilyPond input string:

```
abjad> tuplet = Tuplet(Fraction(2, 3), "c'8 d'8 e'8")
```

```
abjad> show(tuplet)
```



19.2 Making a tuplet from a list of other Abjad components

You can also make a tuplet from a multiplier and a list of other Abjad components:

```
abjad> leaves = [Note("fs'8"), Note("g'8"), Rest('r8')]
```

```
abjad> tuplet = Tuplet(Fraction(2, 3), leaves)
```

```
abjad> show(tuplet)
```



19.3 Understanding the interpreter display of a tuplet

The interpreter display of an Abjad tuplet contains three parts:

```
abjad> tuplet
Tuplet(2/3, [fs'8, g'8, r8])
```

`Tuplet` tells you the tuplet's class.

`2/3` tells you the tuplet's multiplier.

The list `[fs'8, g'8, r8]` shows the top-level components the tuplet contains.

19.4 Understanding the string representation of a tuplet

The string representation of a tuplet contains four parts:

```
abjad> print tuplet
{* 3:2 fs'8, g'8, r8 *}
```

Curly braces { and } indicate that the tuplet's music is interpreted sequentially instead of in parallel.

The asterisks * denote a fixed-multiplier tuplet.

3 : 2 tells you the tuplet's ratio.

The remaining arguments show the top-level components of tuplet.

19.5 Inspecting the LilyPond format of a tuplet

Get the LilyPond input format of any Abjad object with `format`:

```
abjad> tuplet.format
"\times 2/3 {\n\tfs'8\n\tg'8\n\tr8\n}"
```

Use `f()` as a short-cut to print the LilyPond format of any Abjad object:

```
abjad> f(tuplet)
\times 2/3 {
    fs'8
    g'8
    r8
}
```

19.6 Inspecting the music in a tuplet

Get the music in any Abjad container with `music`:

```
abjad> tuplet.music
(Note("fs'8"), Note("g'8"), Rest('r8'))
```

Abjad returns a read-only tuple of components.

19.7 Inspecting a tuplet's leaves

Get the leaves in any Abjad container with `leaves`:

```
abjad> tuplet.leaves
(Note("fs'8"), Note("g'8"), Rest('r8'))
```

Abjad returns a read-only tuple of leaves.

19.8 Getting the length of a tuplet

Get the length of any Abjad container with `len()`:

```
abjad> len(tuplet)
3
```

The length of every Abjad container is defined equal to the number of top-level components present in the container.

19.9 Getting the duration attributes of a tuplet

You set the multiplier of a tuplet at initialization:

```
abjad> tuplet.multiplier
Fraction(2, 3)
```

The contents durations of a tuplet equals the sum of written durations of the components in the tuplet:

```
abjad> tuplet.contents_duration
Duration(3, 8)
```

The multiplied duration of a tuplet equals the product of the tuplet's multiplier and the tuplet's contents duration:

```
abjad> tuplet.multiplied_duration
Duration(1, 4)
```

19.10 Understanding rhythmic augmentation and diminution

A tuplet with a multiplier less than 1 constitutes a type of rhythmic diminution:

```
abjad> tuplet.multiplier
Fraction(2, 3)

abjad> tuplet.is_diminution
True
```

A tuplet with a multiplier greater than 1 is a type of rhythmic augmentation:

```
abjad> tuplet.is_augmentation
False
```

19.11 Understanding binary and nonbinary tuplets

A tuplet is considered binary if the numerator of the tuplet multiplier is an integer power of 2:

```
abjad> tuplet.multiplier
Fraction(2, 3)

abjad> tuplet.is_binary
True
```

Other tuplets are nonbinary:

```
abjad> tuplet.is_nonbinary
False
```

19.12 Adding one component to the end of a tuplet

Add one component to the end of a tuplet with `append`:

```
abjad> tuplet.append(Note("e'4."))
```

```
abjad> show(tuplet)
```



19.13 Adding many components to the end of a tuplet

Add many components to the end of a tuplet with `extend`:

```
abjad> notes = [Note("fs'8"), Note("e'8"), Note("d'8"), Note("c'4.")]
abjad> tuplet.extend(notes)
```

```
abjad> show(tuplet)
```



19.14 Finding the index of a component in a tuplet

Find the index of a component in a tuplet with `index()`:

```
abjad> notes[1]
Note("e'8")
```

```
abjad> tuplet.index(notes[1])
5
```

19.15 Removing a tuplet component by index

Use `pop()` to remove a tuplet component by index:

```
abjad> tuplet[7]
Note("c'4.")
```

```
abjad> tuplet.pop(7)
```

```
abjad> show(tuplet)
```




19.16 Removing a tuplet component by reference

Remove tuplet components by reference with `remove()`:

```
abjad> tuplet.remove(tuplet[3])
```

```
abjad> show(tuplet)
```



19.17 Overriding attributes of the LilyPond tuplet number grob

Override attributes of the LilyPond tuplet number grob like this:

```
abjad> tuplet.override.tuplet_number.text = schemetools.SchemeFunction('tuplet-number::calc-fraction')
abjad> tuplet.override.tuplet_number.color = 'red'
```

```
abjad> f(tuplet)
\override TupletNumber #'color = #red
\override TupletNumber #'text = #tuplet-number::calc-fraction-text
\times 2/3 {
  fs'8
  g'8
  r8
  fs'8 [
  e'8
  d'8 ]
}
\revert TupletNumber #'color
\revert TupletNumber #'text
```

```
abjad> show(tuplet)
```



See the LilyPond docs for lists of grob attributes available.

19.18 Overriding attributes of the LilyPond tuplet bracket grob

Override attributes of the LilyPond tuplet bracket grob like this:

```
abjad> tuplet.override.tuplet_bracket.color = 'red'
```

```
abjad> f(tuplet)
\override TupletBracket #'color = #red
\override TupletNumber #'color = #red
\override TupletNumber #'text = #tuplet-number::calc-fraction-text
\times 2/3 {
    fs'8
    g'8
    r8
    fs'8 [
    e'8
    d'8 ]
}
\revert TupletBracket #'color
\revert TupletNumber #'color
\revert TupletNumber #'text
```

```
abjad> show(tuplet)
```



See the LilyPond docs for lists of grob attributes available.

VOICES

20.1 Making a voice from a LilyPond input string

You can make an Abjad voice from a LilyPond input string:

```
abjad> voice = Voice("c'8 d'8 e'8 f'8 g'8 a'8 b'4 c''1")
```

```
abjad> show(voice)
```



20.2 Making a voice from a list of other Abjad components

You can also make a voice from a list of other Abjad components:

```
abjad> components = [Tuplet(Fraction(2, 3), "c'4 d'4 e'4"), Note("f'2"), Note("g'1")]
```

```
abjad> voice = Voice(components)
```

```
abjad> show(voice)
```



20.3 Understanding the repr of a voice

The repr of an Abjad voice contains three parts:

```
abjad> voice  
Voice{3}
```

Voice tells you the voice's class.

3 tells you the voice's length (which is the number of top-level components the voice contains).

Curly braces { and } tell you that the music inside the voice is interpreted sequentially rather than in parallel.

20.4 Inspecting the LilyPond format of a voice

Get the LilyPond input format of any Abjad object with `format`:

```
abjad> voice.format
"\new Voice {\n\t\times 2/3 {\n\t\t\tc'4\n\t\t\td'4\n\t\t\te'4\n\t\t}\n\t\tf'2\n\t\tg'1\n}"
```

Use `f()` as a short-cut to print the LilyPond format of any Abjad object:

```
abjad> f(voice)
\nnew Voice {
  \times 2/3 {
    c'4
    d'4
    e'4
  }
  f'2
  g'1
}
```

20.5 Inspecting the music in a voice

Get voice components with `music`:

```
abjad> voice.music
(Tuplet(2/3, [c'4, d'4, e'4]), Note("f'2"), Note("g'1"))
```

Abjad returns a read-only tuple of components.

20.6 Inspecting a voice's leaves

Get the leaves in a voice with `leaves`:

```
abjad> voice.leaves
(Note("c'4"), Note("d'4"), Note("e'4"), Note("f'2"), Note("g'1"))
```

Abjad returns a read-only tuple of leaves.

20.7 Getting the length of a voice

Get voice length with `len()`:

```
abjad> len(voice)
3
```

The length of a voice is defined equal to the number of top-level components the voice contains.

20.8 Getting the duration attributes of a voice

The contents durations of a voice equals the sum of durations of the components in the voice:

```
abjad> voice.contents_duration
Duration(2, 1)
```

The preprolated duration of a voice is usually equal to the voice's contents duration:

```
abjad> voice.preprolated_duration
Duration(2, 1)
```

The prolated duration of a voice is usually equal to the voice's contents duration, too:

```
abjad> voice.preprolated_duration
Duration(2, 1)
```

Only when you nest a very small voice inside a tuplet will the prolated and preprolated duration of a voice differ.

Voices that are not nested inside a tuplet carry a prolation of 1:

```
abjad> voice.prolation
Fraction(1, 1)
```

All voice duration attributes are read-only.

20.9 Adding one component to the end of a voice

Add one component to the end of a voice with `append`:

```
abjad> voice.append(Note("af'2"))

abjad> show(voice)
```



20.10 Adding many components to the end of a voice

Add many components to the end of a voice with `extend`:

```
abjad> notes = [Note("g'4"), Note("f'4")]
abjad> voice.extend(notes)

abjad> show(voice)
```



20.11 Finding the index of a component in a voice

Find the index of a component in a voice with `index()`:

```
abjad> notes[0]
Note("g'4")
```

```
abjad> voice.index(notes[0])  
4
```

20.12 Removing a voice component by index

Use `pop()` to remove a voice component by index:

```
abjad> voice[5]  
Note("f'4")  
  
abjad> voice.pop(5)  
  
abjad> show(voice)
```



20.13 Removing a voice component by reference

Remove voice components by reference with `remove()`:

```
abjad> voice.remove(voice[-1])  
  
abjad> show(voice)
```



20.14 Naming voices

You can name Abjad voices:

```
abjad> voice.name = 'Upper Voice'
```

Voice names appear in LilyPond input:

```
abjad> f(voice)  
\context Voice = "Upper Voice" {  
  \times 2/3 {  
    c'4  
    d'4  
    e'4  
  }  
  f'2  
  g'1  
  af'2  
}
```

But not in notational output:

```
abjad> show(voice)
```



20.15 Changing the context of a voice

The context of a voice is set to 'Voice' by default:

```
abjad> voice.context
'Voice'
```

But you can change the context of a voice if you want:

```
abjad> voice.context = 'SpeciallyDefinedVoice'
```

```
abjad> voice.context
'SpeciallyDefinedVoice'
```

```
abjad> f(voice)
\context SpeciallyDefinedVoice = "Upper Voice" {
    \times 2/3 {
        c' 4
        d' 4
        e' 4
    }
    f' 2
    g' 1
    af' 2
}
```

Change the context of a voice when you have defined a new LilyPond context based on a LilyPond voice.

Tutorials

TIME SIGNATURE MARKS BY EXAMPLE

In this tutorial is to take a deeper look at what happens when we attach time signature marks to staves and other score components. To work through the tutorial, enter each of the examples into the Abjad interpreter and study what comes back. At the end of the tutorial you'll understand how time signature marks are created. You'll also understand how the states of different objects change when time signature marks are attached and detached.

First we start by creating a staff full of notes:

```
abjad> staff = Staff("c'4 d'4 e'4 f'4 g'2")
```

If we ask the Abjad interpreter about our staff reference Abjad will respond with the interpreter display of the object:

```
abjad> staff
Staff{5}
```

The 5 in `Staff{5}` shows that the staff contains 5 top-level components. The curly braces in `Staff{5}` show that the contents of the staff are to be read sequentially through time rather than in parallel.

Before we get to time signature marks let's take a moment and examine the state of the staff we've created. We can motivate this a bit by asking two questions:

1. what time signature is currently in effect for the staff we have just created?
2. **what is the time signature currently in effect for** the five notes contained within the staff we have just created?

The answer to both questions is the same: there is no time signature currently in effect for either our staff or for the five notes it contains.

We can see that this is the case with tools from the API:

```
abjad> contexttools.get_effective_time_signature(staff) is None
True
```

And:

```
abjad> for leaf in staff:
...     contexttools.get_effective_time_signature(leaf) is None
...
True
True
True
True
True
```

If we want, we can iterate both the staff and its leaves at one and the same time like this:

```
abjad> for component in componenttools.iterate_components_forward_in_expr(staff):
...     component, contexttools.get_effective_time_signature(component)
...
(Staff{5}, None)
(Note("c'4"), None)
(Note("d'4"), None)
(Note("e'4"), None)
(Note("f'4"), None)
(Note("g'2"), None)
```

This confirms the answer to our questions that there is not yet any time signature in effect for any component in our staff because we have not yet attached a time signature mark to any component in our staff.

So what happens if we format our staff and send it off to LilyPond to render as a PDF? Will LilyPond render the staff with a time signature? Without a time signature? Will LilyPond refuse to render the example at all?

We find out like this:

```
abjad> show(staff)
```



It turns out LilyPond defaults to a time signature of 4/4.

What's important to note here is that because we have not yet attached a time signature mark any component in our staff Abjad says “no effective time signature here” while LilyPond says “OK, I'll default to 4/4 so we can get on with rendering your music.”

We can further confirm that this is the case by asking Abjad for the LilyPond format of our staff:

```
abjad> f(staff)
\new Staff {
    c'4
    d'4
    e'4
    f'4
    g'2
}
```

The LilyPond format of our staff contains no LilyPond `\time` command. This is, again, because we have not yet attached a time signature mark to any component in our staff.

We can now practice attaching and detaching time signature marks to different components in our staff and study what happens as we do.

We'll start with 3/4.

The easiest thing to do is to attach a time signature mark to the staff itself.

We'll do this in two separate steps and study each step to understand exactly what's going on.

First, we create a 3/4 time signature mark:

```
abjad> time_signature_mark = contexttools.TimeSignatureMark(3, 4)
```

If we ask the Abjad interpreter for the interpreter display of our time signature mark we get the following:

```
abjad> time_signature_mark
TimeSignatureMark(3, 4)
```

All this tells us is that we have in fact created a 3/4 time signature mark. Nothing too exciting yet. At this point our 3/4 time signature is not yet attached to anything. We could say that the “state” of our time signature mark is “unattached.” And we can see this like so:

```
abjad> time_signature_mark.start_component is None
True
```

What does it mean for a time signature mark to have ‘start_component’ equal to none? It means that the time signature isn’t yet attached to any score component anywhere.

So now we attach our time signature mark to our staff:

```
abjad> time_signature_mark.attach_mark(staff)
TimeSignatureMark(3, 4)(Staff{5})
```

Abjad responds immediately by returning the time signature mark we have just attached.

Notice that our time signature mark’s repr has changed. The repr of our 3/4 time signature mark now includes the repr of the staff to which we have just attached the time signature mark. That is to say that the repr of our time signature mark is `statal`.

Our time signature mark has transitioned from an “unattached” state to an “attached” state. We can see this like so:

```
abjad> time_signature_mark.start_component
Staff{5}
```

And our staff has likewise transitioned from a state of having no effective time signature to a state of having an effective time signature:

```
abjad> contexttools.get_effective_time_signature(staff)
TimeSignatureMark(3, 4)(Staff{5})
```

And what about the leaves inside our staff? Do the leaves now “know” that they are governed by a 3/4 time signature?

Indeed they do:

```
abjad> for leaf in staff.leaves:
...     leaf, contexttools.get_effective_time_signature(leaf)
...
(Note("c'4"), TimeSignatureMark(3, 4)(Staff{5}))
(Note("d'4"), TimeSignatureMark(3, 4)(Staff{5}))
(Note("e'4"), TimeSignatureMark(3, 4)(Staff{5}))
(Note("f'4"), TimeSignatureMark(3, 4)(Staff{5}))
(Note("g'2"), TimeSignatureMark(3, 4)(Staff{5}))
```

So to briefly resume:

What we just did was to:

1. create a time signature mark
2. attach the time signature to a score component

This 2-step pattern is always the same when dealing with context marks: create then attach.

(We will find out later that there are short-cuts for different parts of this process. Right now we’ve chosen to create in a first step and attach in a second step so that we can examine the changing states of the objects involved.)

Before moving on let’s look at the PDF corresponding to our staff:

```
abjad> show(staff)
```



And let's confirm what we see in the PDF in the staff's format:

```
abjad> f(staff)
\new Staff {
    \time 3/4
    c'4
    d'4
    e'4
    f'4
    g'2
}
```

The staff's format now contains a LilyPond `\time` command because we have attached an Abjad time signature mark to the staff.

What we've just been through above will cover over 80% of what you'll ever wind up doing with time signature marks: creating them and attaching them directly to staves. But what if we wanna get rid of a time signature mark? Or what if the time signature will be changing all over the place? We cover those cases next.

Detaching a time signature mark is easy:

```
abjad> time_signature_mark.detach_mark()
TimeSignatureMark(3, 4)
```

The Abjad returns the mark we have just detached. And, observing the repr of the time signature mark, we see that the time signature mark has again changed state: the time signature mark has transitioned from attached to unattached. We confirm this like so:

```
abjad> time_signature_mark.start_component is None
True
```

And also like so:

```
abjad> contexttools.get_effective_time_signature(staff) is None
True
```

Yup: our time signature mark knows nothing about our staff. And vice versa. This is good.

So now what if we want to set up a time signature of 2/4? That fits our music, too.

We have a couple of options.

We can simply create and attach a new time signature mark:

```
abjad> duple_time_signature_mark = contexttools.TimeSignatureMark(2, 4)
abjad> duple_time_signature_mark.attach_mark(staff)
TimeSignatureMark(2, 4)(Staff{5})
```

```
abjad> f(staff)
\new Staff {
    \time 2/4
    c'4
    d'4
    e'4
    f'4
}
```

```

        g' 2
    }

```

```
abjad> show(staff)
```



Yup. That works.

On the other hand, we could simply reuse our previous 3/4 time signature mark.

To do this we'll first detach our 2/4 time signature mark ...

```
abjad> duple_time_signature_mark.detach_mark()
```

```
abjad> duple_time_signature_mark.detach_mark()
TimeSignatureMark(2, 4)
```

... confirm that our staff is now time signatureless ...

```
abjad> contexttools.get_effective_time_signature(staff) is None
True
```

```
abjad> f(staff)
\new Staff {
    c' 4
    d' 4
    e' 4
    f' 4
    g' 2
}
```

... reattach our previous 3/4 time signature ...

```
abjad> time_signature_mark.attach_mark(staff)
```

```
abjad> time_signature_mark.attach_mark(staff)
TimeSignatureMark(4, 4) (Staff{5})
```

... change the numerator of our time signature mark ...

```
abjad> time_signature_mark.numerator = 2
```

... and check to make sure that everything is as it should be:

```
abjad> contexttools.get_effective_time_signature(staff)
TimeSignatureMark(2, 4) (Staff{5})
abjad> time_signature_mark.start_component
Staff{5}
```

```
abjad> f(staff)
\new Staff {
    \time 2/4
    c' 4
    d' 4
    e' 4
    f' 4
    g' 2
}
```

```
abjad> show(staff)
```



And everything works as it should.

To change to, for example, 4/4 we change just change the time signature mark's numerator again:

```
abjad> time_signature_mark.numerator = 4
```

```
abjad> f(staff)
\new Staff {
  \time 4/4
  c'4
  d'4
  e'4
  f'4
  g'2
}
```

But what if our time signature has a 2/4 pick-up?

The LilyPond command for pick-ups is `\partial`. Abjad time signature marks implement this as a read / write attribute:

```
abjad> time_signature_mark.partial = Duration(2, 4)
```

```
abjad> f(staff)
\new Staff {
  \partial 2
  \time 4/4
  c'4
  d'4
  e'4
  f'4
  g'2
}
```

```
abjad> show(staff)
```



And what if time signature changes all over the place?

We'll use the trivial example of a measure in 4/4 followed by a measure in 2/4.

To do this we will need two time signature marks.

We've already got a 4/4 time signature mark attached to our staff:

```
abjad> f(staff)
\new Staff {
  \partial 2
  \time 4/4
  c'4
  d'4
}
```

```

        e' 4
        f' 4
        g' 2
    }

```

Let's get rid of the pick-up:

```
abjad> time_signature_mark.partial = None
```

```

abjad> f(staff)
\new Staff {
    \time 4/4
    c' 4
    d' 4
    e' 4
    f' 4
    g' 2
}

```

Now what about the 2/4 time signature mark?

We create it in the usual way:

```

abjad> duple_time_signature_mark = contexttools.TimeSignatureMark(2, 4)
abjad> duple_time_signature_mark
TimeSignatureMark(2, 4)

```

But should we attach it? We can't attach our 2/4 time signature to our staff because we've already attached our 4/4 time signature to our staff. And it only makes sense to attach one time signature to any given score component.

Observe that we've built our score in a very straightforward way: we have a single staff that contains a (flat) sequence of notes. This means that we have only one choice for where to attach the new 2/4 time signature mark. And that is one the $g' 2$ that comes on the downbeat of the second measure. We do that like this:

```

abjad> duple_time_signature_mark.attach_mark(staff[4])

abjad> duple_time_signature_mark.attach_mark(staff[4])
TimeSignatureMark(2, 4) (g' 2)

abjad> f(staff)
\new Staff {
    \time 4/4
    c' 4
    d' 4
    e' 4
    f' 4
    \time 2/4
    g' 2
}

```

```
abjad> show(staff)
```



And everything works as we would like.

Incidentally, `staff[4]` means the component sitting at index 4 inside our staff. Using the interpreter we can verify that this is $g' 2$:

```
abjad> staff[4]
Note("g' 2")
```

Depending on how we had chosen to build our staff we would have had more options for where to attach our 2/4 time signature mark. If, for example, we had chosen to populate our staff with a series of measures then it's possible we could have attached our 2/4 time signature to a measure instead of a note.

That covers the vast majority of things you'll do with time signature marks.

But before we stop we should mention another useful API function and then talk about some short-cuts.

First an API function to detach ALL context marks attaching to a component:

We call the function a first time:

```
abjad> contexttools.detach_all_context_marks_attached_to_component(staff)
(TimeSignatureMark(4, 4),)
```

```
abjad> f(staff)
\new Staff {
    c' 4
    d' 4
    e' 4
    f' 4
    \time 2/4
    g' 2
}
```

And then a second time:

```
:: abjad> contexttools.detach_all_context_marks_attached_to_component(staff[4]) (TimeSignatureMark(2, 4),)
```

```
abjad> f(staff)
\new Staff {
    c' 4
    d' 4
    e' 4
    f' 4
    g' 2
}
```

Now there are now context marks of any sort attached to our staff or to the notes in our staff.

Be careful with this function, though: it removes *all* context marks. So even though we just used the function to remove time signature marks, it also would have removed any clef marks or tempo marks if we had had those attached to our score, too.

And now for the short-cuts:

Our staff currently has no time signature marks attached:

```
abjad> f(staff)
\new Staff {
    c' 4
    d' 4
    e' 4
    f' 4
    g' 2
}
```

So to recreate our 3/4 time signature we can do this ...


```
abjad> time_signature_mark = contexttools.TimeSignatureMark(3, 4)
```

... and then use a short-cut to avoid calling `time_signature_mark.attach_mark()` like this:

```
abjad> time_signature_mark(staff)
TimeSignatureMark(3, 4)(Staff{5})
```

```
abjad> f(staff)
\new Staff {
    \time 3/4
    c'4
    d'4
    e'4
    f'4
    g'2
}
```

What's going on here is that all context marks implement the special `__call__()` method as a short-cut for `attach_mark()`. What is the special `__call__()` method? The `__call__()` method is what makes a function, class or any other Python object callable. The statement `time_signature_mark(staff)` has parentheses in it because the time signature mark is callable; and the time signature mark is callable because all context marks implement the special `__call__()` method.

Note too that all context marks understand an *empty call* as a short-cut for `detach_mark()`. Like this:

```
abjad> time_signature_mark()
TimeSignatureMark(3, 4)
```

```
abjad> f(staff)
\new Staff {
    c'4
    d'4
    e'4
    f'4
    g'2
}
```

The empty call made against the time signature mark causes the time signature mark to detach from its start component.

The fact that context marks implement the special `__call__()` method as a short-cut for `attach_mark()` means that context marks can be created and attached in a single line:

```
abjad> contexttools.TimeSignatureMark(2, 4)(staff)
TimeSignatureMark(2, 4)(Staff{5})
```

```
abjad> f(staff)
\new Staff {
    \time 2/4
    c'4
    d'4
    e'4
    f'4
    g'2
}
```

What's going on here?

What's going on is that `contexttools.TimeSignatureMark(2, 4)` creates a time signature mark in the usual way and that – immediately after this – the newly created time signature mark is available for us to call it against our staff.

This last short-cut form of ...


```
abjad> contexttools.TimeSignatureMark(2, 4)(staff)
```

... is the usual way that you will see context marks of all sorts presented in the docs.

LEAF, CONTAINER, SPANNER

At the heart of Abjad's Symbolic Score-Control lies a powerful model that we call the Leaf Container Spanner, or LCS, model of the musical score.

The LCS model can be schematically visualized as a superposition of two complementary and completely independent layers of structure: a *tree* that includes the Containers and the Leaves, and a layer of free floating *connectors* or Spanners.



There can be any number of Spanners, they may overlap, and they may connect to different levels of the tree hierarchy. The spanner attach to the elements of the tree, so a tree structure must exist for spanners to be made manifest.

22.1 Example 1

To understand the whys and hows of the LCS model implemented in Abjad, it is probably easier to base the discussion on concrete musical examples. Let's begin with a simple and rather abstract musical fragment: a measure with nested tuplets.



What we see in this little fragment is a measure with 4/4 meter, 14 notes and four tuplet brackets prolating the notes. The three bottom tuplets (with ratios 5:4, 3:2, 5:4) prolates all but the last note. The topmost tuplet prolates all the notes in the measure and combines with the bottom three tuplets to doubly prolates all but the last note. The topmost tuplet as thus prolates three tuplets, each of which in turn prolates a group of notes. We can think of a tuplet as *containing* notes or other tuplets or both. Thus, in our example, the topmost tuplet contains three tuplets and a half note. Each of the tuplets contained by the topmost tuplet in turn contains five, three, and five notes respectively. If we add the measure, then we have a measure that contains a tuplet that contains tuplets that contain notes. The structure of the measure with nested tuplets as we have just described it has two important properties:

1. It is a *hierarchical* structure.
2. It follows *exclusive membership*, meaning that each element in the hierarchy (a note, a tuplet or a measure) has one and only one *parent*. In other words a single note is not contained in more than one tuplet simultaneously, and no one tuplet is contained in more than one other tuplet at the same time.

What we are describing here is a tree, and it is the structure of Abjad *containers*.

While this tree structure seem like the right way to represent the relationships between the elements of a score, it is not enough. Consider the tuplet example again with the following beaming alternatives:

Beaming alternative 1:



Beaming alternative 2:




Beaming alternative 3:



Clearly the beaming of notes can be totally independent from the tuplet groupings. Beaming across tuplet groups implies beaming across nodes in the tree structure, which means that the beams do not adhere to the *exclusive (parent-hood) membership* characteristic of the tree. Beams must then be modeled independently as a separate and complementary structure. These are the Abjad *spanners*.

Below we have the score of our tuplet example with alternative beaming and its the Leaf-Container-Spanner graph. Notice that the colored blocks represent spanners.

Beaming alternative 3 (graph):



22.2 Example 2


As a second example let's look at the last five measures of Bartók's *Wandering* from *Mikrokosmos* vol. III. As simple as it may seem, these five measures carry with them a lot of information pertaining to musical notation.



Note: Please refer to the [Bartok example](#) for a step by step construction of the musical fragment and its full Abjad code.

There are many musical signs of different types on the pages: notes, dynamic markings, clefs, staves, slurs, etc. These signs are structurally related to each other in different ways. Let's start by looking at the larger picture. The piano piece is written in two staves. As is customary, the staves are graphically grouped with a large curly brace attaching to them at the beginning of each system. Notice that each staff has a variety of signs associated with it. There are notes printed on the staff lines as well as meter indications and bar lines. Each note, for example, is in one and only one staff. A note is never in two staves at the same time. This is also true for measures. A measure in the top staff is not simultaneously drawn on the top staff and the bottom staff. It is better to think of each staff as having its own set of measures. Notice also that the notes in each staff fall within the region of one and only one measure, i.e. measures seem to contain notes. There is not one note that is at once in two measures (this is standard practice in musical notation, but it need not always be the case.)

As we continue describing the relationships between the musical signs in the page, we begin to discover a certain structure, or a convenient way of structuring the score for conceptualization and manipulation. All the music in a piano score seems to be written in what we might call a *staff group*. The staff group is *composed of* two staves. Each staff in turn appears to be composed of a series or measures, and each measure is composed of a series of notes. So again we find that the score structure can be organized hierarchically as a tree. This tree structure looks like this:




Notice again though that there are elements in the score that imply and require a different kind of grouping. The two four eighth-note runs in the lower staff are beamed together across the bar line and, based on our tree structure, across tree nodes. So do the slurs, the dynamics markings and the ritardando indication at the top of the score. As we have seen in the tuplets example, all these groups running across the tree structure can be defined with *spanners*.

WORKING WITH COMPONENT PARENTAGE

Many score objects contain other score objects.

```
abjad> tuplet = Tuplet(Fraction(2, 3), "c'4 d'4 e'4")
abjad> staff = Staff(2 * tuplet)
abjad> score = Score([staff])
abjad> show(score)
```



Abjad uses the idea of parentage to model the way objects contain each other.

23.1 Improper parentage

The improper parentage of the first note in score begins with the note itself:

```
abjad> note = score.leaves[0]
Note("c'4")

abjad> componenttools.get_improper_parentage_of_component(note)
(Note("c'4"), Tuplet(2/3, [c'4, d'4, e'4]), Staff{2}, Score<<1>>)
```

23.2 Proper parentage

The proper parentage of the note begins with only the immediate parent of the note:

```
abjad> componenttools.get_proper_parentage_of_component(note)
(Tuplet(2/3, [c'4, d'4, e'4]), Staff{2}, Score<<1>>)
```

Note: the length of the improper parentage of any component equals the length of the proper parentage of the component plus 1.

23.3 Parentage attributes

Use component tools to find score depth:

```
abjad> componenttools.component_to_score_depth(note)
3
```

Or score root:

```
abjad> componenttools.component_to_score_root(note)
Score<<1>>
```

Or to find whether a component has no (proper) parentage at all:

```
abjad> componenttools.is_orphan_component(note)
False
```


WORKING WITH THREADS

24.1 What is a thread?

A thread is a structural relationship binding a set of strictly sequential voice-level components.

Threads may be explicitly defined via voice instances:

```
abjad> v = Voice()
```

Or they may exist implicitly in certain score constructs in the absence of voice containers:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
```

Two contiguous voices must have the same name in order to be part of the same thread.

Here a thread does **not** exist between notes in different voices:

```
abjad> v_one = Voice("c'16 d'16 e'16 f'16")
abjad> v_two = Voice("c'8 d'8")
abjad> staff = Staff([v_one, v_two])
abjad> f(staff)
\new Staff {
    \new Voice {
        c'16
        d'16
        e'16
        f'16
    }
    \new Voice {
        c'8
        d'8
    }
}
```

Here a thread does exist:

```
abjad> v_one.name = 'flute'
abjad> v_two.name = 'flute'
abjad> f(staff)
\new Staff {
    \context Voice = "flute" {
        c'16
        d'16
        e'16
        f'16
    }
}
```

```
}
\context Voice = "flute" {
  c'8
  d'8
}
}
```

24.2 What are threads for?

Consider the following situation:



Are the two eighth notes in the second half of the measure the continuation of the ascending line in the first half, or is it the quarter note? Is the very last C the continuation of the top melodic line or is it the A? The stems might suggest an answer, but for Abjad, stem direction is not structural. What path should Abjad take to traverse this little score from the first note to the last A? This same problem appears when trying to apply spanners to parallel structures. Thus, threads are important in both score navigation and the application of spanners. In fact, threads are a requirement for spanner application.

In Abjad, the ambiguity is resolved through the explicit use of named voices.

The musical fragment above is constructed with the following code:

```
abjad> vA = Voice(notetools.make_notes([5, 7, 9, 11], [(1, 8)] * 4))
abjad> vB = Voice(notetools.make_notes([12, 11, 9], [(1, 8), (1, 8), (1, 4)]))
abjad> vC = Voice(Note(12, (1, 4)) * 2)
abjad> marktools.LilyPondCommandMark('voiceOne')(vA[0])
abjad> marktools.LilyPondCommandMark('voiceOne')(vB[0])
abjad> marktools.LilyPondCommandMark('voiceTwo')(vC[0])
abjad> p = Container([vB, vC])
abjad> p.is_parallel = True
abjad> staff = Staff([vA, p])
```



There's a staff that sequentially contains a voice and a parallel container. The container in turn holds two voices running simultaneously.

It is now clear from the code that the last A belongs with the two descending eighth notes. But there's still no indication about a relationship of continuity between the first voice in the sequence (vA) and any of the two following voices. Note that, while the LilyPond voice number commands setting may suggest that vA and vB belong together, this is not the case. The LilyPond voice number commands simply set the direction of stems in printed output.

To see this more clearly, suppose we want to add a slur spanner starting on the first note and ending on one of the last simultaneous notes. To attach the slur spanner to the voices we could try either:

```
abjad> spannertools.SlurSpanner([vA, vB])
```

or

```
abjad> spannertools.SlurSpanner([vA, vC])
```

But both raise a contiguity error. Abjad needs to see an explicit connection between either vA and vB or between vA and vC .

Observe the behavior of the `iterate_thread_forward_in_expr()` iterator on the *staff*:

```
::
```

```
abjad> from abjad.tools import threadtools abjad> vA_thread_signature
= threadtools.component_to_thread_signature(vA) abjad> notes = thread-
tools.iterate_thread_forward_in_expr(staff, Note, vA_thread_signature) abjad> print list(notes)
[Note("f'8"), Note("g'8"), Note("a'8"), Note("b'8")]

abjad> vB_thread_signature = threadtools.component_to_thread_signature(vB)
abjad> notes = threadtools.iterate_thread_forward_in_expr(staff, Note, vB_thread_signature)
abjad> print list(notes)
[Note("c'8"), Note("b'8"), Note("a'4")]

abjad> vC_thread_signature = threadtools.component_to_thread_signature(vC)
abjad> notes = threadtools.iterate_thread_forward_in_expr(staff, Note, vC_thread_signature)
abjad> print list(notes)
[Note("c'4"), Note("c'4")]
```

In each case we are passing a different **thread signature** to the `iterate_thread_forward_in_expr()` iterator, so each case returns a different list of notes.

We can see that the thread signature of each voice is indeed different by printing it:

```
abjad> vA_thread_signature = threadtools.component_to_thread_signature(vA)
abjad> vA_thread_signature
<      root: Staff-4324984432 (4324984432) *      score: * staffgroup: *      staff: Staff-4324984432

abjad> vB_thread_signature = threadtools.component_to_thread_signature(vB)
abjad> vB_thread_signature
<      root: Staff-4477851248 (4477851248) *      score: * staffgroup: *      staff: Staff-4477851248

abjad> vC_thread_signature = threadtools.component_to_thread_signature(vC)
abjad> vC_thread_signature
<      root: Staff-4517791344 (4517791344) *      score: * staffgroup: *      staff: Staff-4517791344
```

And by comparing them with the binary equality operator:

```
abjad> vA_thread_signature == vB_thread_signature
False
abjad> vA_thread_signature == vC_thread_signature
False
abjad> vB_thread_signature == vC_thread_signature
False
```

To allow Abjad to treat the content of, say, voices vA and vB as belonging together, we explicitly define a thread between them. To do this all we need to do is give both voices the same name:

```
abjad> vA.name = 'piccolo'
abjad> vB.name = 'piccolo'
```

Now vA and vB and all their content belong to the same thread:

```
abjad> vA_thread_signature == vB_thread_signature
False
```

Note how the thread signatures have changed:

```

abjad> vA_thread_signature = threadtools.component_to_thread_signature(vA)
abjad> print vA_thread_signature
      root: Staff-4495328880 (4495328880)
      score:
staffgroup:
  staff: Staff-4495328880
  voice: Voice-piccolo
  self: Voice-piccolo

abjad> vB_thread_signature = threadtools.component_to_thread_signature(vB)
abjad> print vB_thread_signature
      root: Staff-4546553456 (4546553456)
      score:
staffgroup:
  staff: Staff-4546553456
  voice: Voice-piccolo
  self: Voice-piccolo

abjad> vC_thread_signature = threadtools.component_to_thread_signature(vC)
abjad> print vC_thread_signature
      root: Staff-4440991344 (4440991344)
      score:
staffgroup:
  staff: Staff-4440991344
  voice: Voice-4440991120
  self: Voice-4440991120

```

And how the `threadtools.iterate_thread_forward_in_expr()` function returns all the notes belonging to both `vA` and `vB` when passing it the full staff and the thread signature of `vA`:

```

abjad> notes = threadtools.iterate_thread_forward_in_expr(staff, Note, vA_thread_signature)
abjad> print list(notes)
[Note("f'8"), Note("g'8"), Note("a'8"), Note("b'8"), Note("c'8"), Note("b'8"), Note("a'4")]

```

Now the slur spanner can be applied to voices `vA` and `vB`:

```

abjad> spannertools.SlurSpanner([vA, vB])

```

or directly to the notes returned by the `iterate_thread_forward_in_expr()` iteration tool, which are the notes belonging to both `vA` and `vB`:

```

abjad> notes = threadtools.iterate_thread_forward_in_expr(staff, Note, vA_thread_signature)
abjad> spannertools.SlurSpanner(list(notes))

```

```

abjad> show(staff)

```



24.3 Coda

We could have constructed this score in a simpler way with only two voices, one of them starting with a LilyPond skip:

```
abjad> vX = Voice(notetools.make_notes([5, 7, 9, 11, 12, 11, 9], [(1, 8)] * 6 + [(1, 4)]))
abjad> vY = Voice([skiptools.Skip((2, 4))] + Note(12, (1, 4)) * 2)
abjad> marktools.LilyPondCommandMark('voiceOne')(vX[0])
abjad> marktools.LilyPondCommandMark('voiceTwo')(vY[0])
abjad> staff = Staff([vX, vY])
abjad> staff.is_parallel = True
```



UNDERSTANDING LILYPOND GROBS

LilyPond models music notation as a collection of graphic objects or grobs.

25.1 Grobs control typography

LilyPond grobs control the typographic details of the score:

```
\new Staff {  
  c'4 (  
  d'4 )  
  e'4 (  
  f'4 )  
  g'4 (  
  a'4 )  
  g'2  
}
```



In the example above LilyPond creates a grob for every printed glyph. This includes the clef and time signature as well as the note heads, stems and slurs. If the example included beams, articulations or an explicit key signature then LilyPond would create grobs for those as well.

25.2 Grobs can be overridden

You can change the appearance of LilyPond grobs with grob overrides:

```
\new Staff \with {  
  \override NoteHead #'color = #red  
  \override StaffSymbol #'color = #blue  
  \override Stem #'color = #red  
} {  
  c'4 (  
  d'4 )  
  e'4 (  
  f'4 )  
  g'4 (  
  a'4 )  
}
```



25.3 Check the LilyPond docs

New grobs are added to LilyPond from time to time.

For a complete list of LilyPond grobs see the [LilyPond documentation](#).

UNDERSTANDING ABJAD OVERRIDES

26.1 Grob-override component plug-ins

All Abjad containers have a grob-override plug-in:

```
abjad> staff = Staff("c'4 d'4 e'4 f'4 g'4 a'4 g'2")

abjad> staff.override.staff_symbol.color = 'blue'

abjad> staff.override
LilyPondGrobOverrideComponentPlugIn(staff_symbol__color = 'blue')
```

All Abjad leaves have a grob-override plug-in, too:

```
abjad> leaf = staff[-1]

abjad> leaf.override.note_head.color = 'red'
abjad> leaf.override.stem.color = 'red'

abjad> leaf.override
LilyPondGrobOverrideComponentPlugIn(note_head__color = 'red', stem__color = 'red')
```

And so do Abjad spanners:

```
abjad> slur = spannertools.SlurSpanner(staff[:])

abjad> slur.override.slur.color = 'red'

abjad> slur.override
LilyPondGrobOverrideComponentPlugIn(slur__color = 'red')
```

26.2 Grob proxies

Grob-override plug-ins contain grob proxies:

```
abjad> leaf.override.note_head
LilyPondGrobProxy(color = 'red')

abjad> leaf.override.stem
LilyPondGrobProxy(color = 'red')
```

26.3 Dot-chained override syntax

The's dot-chained grob override syntax shown here results from the special way that the Abjad grob-override plug-in and grob proxy set and get their attributes.

[Developer documentation](#)

CODEBASE

27.1 How the Abjad codebase is laid out

The Abjad codebase comprises twelve top-level directories.

```
abjad$ ls
__init__.py  cfg          core          docs          interfaces  scr          tools
book         checks       demos         exceptions    opt         templates
```

Of these, it is in the `tools` directory that the bulk of the musical reasoning implemented in Abjad resides.

```
abjad$ ls tools/
__init__.py      importtools      markuptools      quantizationtools  stafftools
cfgtools         instrumenttools  mathtools        resttools          tempotools
chordtools       intervaltreertools  measuretools     schemetools        threadtools
componenttools   iotools          metertools       scoretools         tietools
containertools  layouttools      musicxmltools    seqtools           tonalitytools
contexttools     leaftools        notetools        sievetools         tuplettools
durtools         lilyfiletools    pitcharraytools  skiptools          verticalitytools
gracetools       marktools        pitchtools       spannertools       voicetools
```

The remaining sections of this chapter cover the topics necessary to familiarize developers coming to the project for the first time.

27.2 Removing prebuilt versions of Abjad before you check out

If you'd like to be at the cutting edge of the Abjad development then you should check out from Google Code and tell Python and your operating system about Abjad. You can do this by following the steps below.

But before you do this you should realize that there are two ways to get Abjad up and running on your computer. The first way is by downloading a compressed version of Abjad from the [Python Package Index](#). You probably did this when you first discovered Abjad and started to use the system. The second way is by following the steps below to check out a copy of the most recent version of the Abjad repository hosted on Google Code. If you already have a version of Abjad running on your computer but you haven't yet followed the steps below to check out from Google Code, then you probably downloaded a compressed version of Abjad from the Python Package Index.

Before you check out from Google Code you should remove all prebuilt versions of Abjad from your machine. The reason you need to do this is that having both a prebuilt version of Abjad and a Subversion-managed version of Abjad on your machine can confuse your operating system and lead to weird results when you try to start Abjad.

You remove prebuilt versions of Abjad resident on your computer by finding your site packages directory and removing the so-called Abjad 'egg' that Python has installed there. After you remove the Abjad egg from your site packages

directory you will also need to remove the `abj`, `abjad` and `abjad-book` scripts from `/usr/local/bin` or from the directory that is equivalent to `/usr/local/bin` under your operating system.

First note the version of Python you're currently running.

```
$ python --version
Python 2.6.1
```

This is important because you may have more than one version of Python installed on your machine. (Which tends especially to be the case if you're running a Apple's OS X.)

Then note that the site packages directory is a part of your filesystem into which Python installs third-party Python packages like Abjad. The location of the site packages directory varies from one operating system to the next and you may have to Google to find the exact location of the site packages directory on your machine. Under OS X you can check `/Library/Python/2.x/site-packages/`. Under Linux the site packages directory is usually `/usr/lib/python2.x/site-packages`.

Once you've found your site packages directory you can list its contents to see if Python has installed an Abjad egg in it.

```
site-packages$ ls
Abjad-2.0-py2.6.egg      Sphinx-1.0.7-py2.6.egg  py-1.3.4-py2.6.egg
Jinja2-2.5-py2.6.egg    docutils-0.7-py2.6.egg  py-1.4.0-py2.6.egg
Pygments-1.3.1-py2.6.egg easy-install.pth        py-1.4.4-py2.6.egg
README                  guppy                   pytest-2.0.0-py2.6.egg
Sphinx-1.0.1-py2.6.egg  guppy-0.1.9-py2.6.egg-info pytest-2.1.0-py2.6.egg
Sphinx-1.0.4-py2.6.egg  py-1.3.1-py2.6.egg
```

Remove any Abjad eggs Python has installed in your site packages directory.

After you've done this you should check `/usr/local/bin` or equivalent to see if the `abj`, `abjad` or `abjad-book` scripts are installed there.

```
bin$ ls
abj      abjad    abjad-book
```

Remove any of the three scripts you find installed there so that you can use the new versions of the scripts you will download from Google Code instead.

```
bin$ sudo rm abj*
```

Now proceed to the steps below to check out from Google Code.

27.3 Installing the development version

Follow the steps listed above to remove prebuilt versions of Abjad from your machine. Then follow the steps below to check out from Google Code.

1. Make sure Subversion is installed on your machine.

```
svn --version
```

If Subversion responds then it is already installed. Otherwise visit the [Subversion](http://subversion.apache.org/) website.

2. Check out a copy of the main line of the Abjad codebase.

```
svn checkout http://abjad.googlecode.com/svn/abjad/trunk abjad-trunk
```

3. Add the abjad trunk directory to your `PYTHONPATH` environment variable.

```
export PYTHONPATH="/path/to/abjad-trunk:$PYTHONPATH
```

4. Alternatively you may symlink your Python site packages directory to the abjad trunk directory.

```
ln -s /path/to/abjad-trunk /path/to/site-package/abjad
```

5. Finally, add `abjad-trunk/scr/` to your `PATH` environment variable.

```
export PATH="/path/to/abjad-trunk/scr:$PATH
```

You will then be able to run Abjad with the ```abjad``` command.

You now have a copy of the main line of the most recent version of the Abjad repository checked out to your machine.

DOCS

The reST-based sources for the Abjad documentation are included in their entirety in every installation of Abjad. You may add to and edit these reST-based sources as soon as you install Abjad. However, to build human-readable HTML or PDF versions of the docs you will first need to download and install Sphinx.

The remaining sections of this chapter describe how the Abjad docs are laid out and how to build the docs with Sphinx.

28.1 How the Abjad docs are laid out

The source files for the Abjad docs are included in the `docs` directory of every Abjad install. The `docs` directory contains everything required to build HTML, PDF and other versions of the Abjad docs.

```
abjad$ ls docs/
Makefile      _templates  chapters    index.rst   scr
_static       _themes    conf.py     make.bat
```

The bulk of the Abjad docs live in `docs/chapters`. The chapter directories mirror the main sections on Abjad documentation. What you'll find as you inspect the chapter directories are a collection of `.rst` files organized into groups. The `.rst` extension identifies files written in restructured text.

One example:

```
abjad$ ls docs/chapters/appendices/glossary
index.rst
```

28.2 Installing Sphinx

Sphinx is the automated documentation system used by Python, Abjad and [other projects](#) implemented in Python. Because Sphinx is not included in the Python standard library you will probably need to download and install it.

First check to see if Sphinx is already installed on your machine.

```
$ sphinx-build --version
```

If Sphinx responds then the program is already installed on your machine. Otherwise visit the [Sphinx](#) website.

28.3 Removing old builds of the docs

After installing Sphinx, change to the Abjad `docs` directory and use the Sphinx makefile to remove any existing `docs/_build` directory prior to making a new build of the docs.

```
abjad$ cd docs

docs$ make clean
rm -rf _build/*
```

28.4 Generating the Abjad API

The `docs/scr` directory includes a script to generate the Abjad API. Run this script before building the Abjad docs for the first time.

```
docs$ scr/make-abjad-api
Building TOC tree ...
Now making Sphinx TOC ...

... Done.

Now building the HTML docs ...

sphinx-build -b html -d _build/doctrees . _build/html
Running Sphinx v1.0.7
loading pickled environment... done

... (many lines omitted) ...

Build finished. The HTML pages are in _build/html.
```

Rerun `make-abjad-api` any time you add or remove a public class, method or function from the codebase.

28.5 Building the HTML docs

Change to the Abjad `docs` directory and run `make html`.

```
abjad$ cd docs

docs$ make html
sphinx-build -b html -d _build/doctrees . _build/html
Running Sphinx v1.0.7
loading pickled environment... not found
building [html]: targets for 568 source files that are out of date
updating environment: 568 added, 0 changed, 0 removed
reading sources... [ 13%] chapters/api/debug/debugghandlertoregators
reading sources... [ 37%] chapters/api/tools/clonewp/by_leaf_counts_with_parenta
reading sources... [ 38%] chapters/api/tools/clonewp/by_leaf_range_with_parentag
reading sources... [ 38%] chapters/api/tools/componenttools/get_duration_crosser
reading sources... [ 38%] chapters/api/tools/componenttools/get_duration_preprol
reading sources... [ 39%] chapters/api/tools/componenttools/get_le_duration_prol

... (many more lines omitted) ...
```



```
writing output... [ 85%] chapters/api/tools/spannertools/give_attached_to_childr
writing output... [ 95%] chapters/fundamentals/duration/interfaces_compared/inde
writing output... [100%] index /indexdexexexng/indexxxdexindex
writing additional files... genindex modindex search
copying images... done
copying static files... done
dumping search index... done
dumping object inventory... done
build succeeded.
```

Build finished. The HTML pages are in `_build/html`.

You will then find the complete HTML version of the docs in `docs/_build/html`.

```
docs$ ls _build/
doctrees html
```

The output from Sphinx is verbose the first time you build the docs. On sequent builds, Sphinx reports changes only.

```
docs$ make html
sphinx-build -b html -d _build/doctrees . _build/html
Running Sphinx v1.0.7
loading pickled environment... done
building [html]: targets for 1 source files that are out of date
updating environment: 0 added, 1 changed, 0 removed
reading sources... [100%] chapters/devel/documentation/index
looking for now-outdated files... none found
pickling environment... done
checking consistency... done
preparing documents... done
writing output... [100%] index ation/index
writing additional files... genindex modindex search
copying static files... done
dumping search index... done
dumping object inventory... done
build succeeded.
```

Build finished. The HTML pages are in `_build/html`.

28.6 Building a PDF of the docs

Building a PDF of the docs is a two-step process. First you build a LaTeX version of the docs. Then you typeset the LaTeX docs as a PDF.

First change to the Abjad docs directory.

```
abjad$ docs
```

Then make LaTeX sources of the docs.

```
docs$ make latex
sphinx-build -b latex -d _build/doctrees . _build/latex
Running Sphinx v1.0.7
loading pickled environment... done
building [latex]: all documents
updating environment: 0 added, 0 changed, 0 removed
looking for now-outdated files... none found
```

```
processing Abjad.tex... index chapters/start_here/abjad/index chapters/examples/bartok...
(... many lines omitted ...)
...ndices/pitch_conventions/images/example-3.png chapters/examples/ligeti/images/desordre.jpg
copying TeX support files... done
build succeeded.
```

Build finished; the LaTeX files are in `_build/latex`.
Run `'make all-pdf'` or `'make all-ps'` in that directory to run these through `(pdf)latex`.

Now follow the instructions provided by Sphinx and change to the LaTeX build directory.

```
docs$ cd _build/latex/
```

Then make a PDF version of the docs from the LaTeX sources.

```
latex$ make all-pdf

pdflatex 'Abjad.tex'
This is pdfTeXk, Version 3.141592-1.40.3 (Web2C 7.5.6)
  %&-line parsing enabled.
entering extended mode
(./Abjad.tex
LaTeX2e <2005/12/01>
Babel <v3.8h> and hyphenation patterns for english, usenglishmax, dumylang, noh
ypheation, arabic, basque, bulgarian, coptic, welsh, czech, slovak, german, ng
erman, danish, esperanto, spanish, catalan, galician, estonian, farsi, finnish,

(... many lines omitted ...)
```

The resulting docs will appear as `Abjad.pdf` in the LaTeX build directory you're currently in.

28.7 Building a coverage report

Change to the Abjad docs directory and call `sphinx-build` explicitly with the coverage builder, source directory and target directory.

```
docs$ sphinx-build -b coverage . _build/coverage
Making output directory...
Running Sphinx v1.0.7
loading pickled environment... not found
building [coverage]: coverage overview
updating environment: 568 added, 0 changed, 0 removed
reading sources... [ 37%] chapters/api/tools/clonewp/by_leaf_counts_with_parenta
reading sources... [ 38%] chapters/api/tools/clonewp/by_leaf_range_with_parentag
reading sources... [ 38%] chapters/api/tools/componenttools/get_duration_crosser

... (many lines omitted) ...

reading sources... [ 85%] chapters/api/tools/spannertools/withdraw_from_containe
reading sources... [ 95%] chapters/fundamentals/duration/interfaces_compared/ind
reading sources... [100%] index t/indexdexexexng/indexxxdexindex
looking for now-outdated files... none found
pickling environment... done
checking consistency... done
build succeeded.
```

The coverage report is now available in the `docs/_build/coverage` directory.

```
docs$ ls _build/  
coverage doctrees html
```

28.8 Building other versions of the docs

Examine the Sphinx makefile in the Abjad `docs/` directory or change to the `docs/` directory and type `make` with no arguments to see a list of the other versions of the Abjad docs that are available to build.

```
docs$ make  
Please use 'make <target>' where <target> is one of  
  html          to make standalone HTML files  
  dirhtml       to make HTML files named index.html in directories  
  pickle        to make pickle files  
  json          to make JSON files  
  htmlhelp      to make HTML files and a HTML help project  
  qthelp        to make HTML files and a qthelp project  
  latex         to make LaTeX files, you can set PAPER=a4 or PAPER=letter  
  changes       to make an overview of all changed/added/deprecated items  
  linkcheck     to check all external links for integrity  
  doctest       to run all doctests embedded in the documentation (if enabled)
```

28.9 Inserting images with `abjad-book`

Use *abjad-book* to insert snippets of notation in the docs you write in reST.

Embed Abjad code between open and close `<abjad>` `</abjad>` tags in your `.rst.raw` sourcefile and then call `abjad-book` to create a pure `.rst` file.

```
abjad-book foo.rst.raw foo.rst
```

```
Parsing file ...  
Rendering "example-1.ly" ...  
Rendering "example-2.ly" ...
```

You will need to build the HTML docs again to see your work.

```
make html
```

28.10 Updating Sphinx

It is important periodically to update your version of Sphinx. If you used `easy_install` to install Sphinx then the usual command to update Sphinx is this:

```
$ sudo easy_install -U Sphinx
```

This will usually work. But if Sphinx fails to update then it may be because you have multiple versions of Python installed on your computer. (This tends especially to be the case under Apple's OS X.)

To get around this first note the version of Python you're currently running:

```
$ python --version  
Python 2.6.1
```

Then use a version-explicit form of `easy_install` to update Sphinx:

```
$ sudo easy_install-2.6 -U Sphinx
```

TESTS

Abjad includes an extensive battery of tests. Abjad is in a state of rapid development and extension. Major refactoring efforts are common every six to eight months and are likely to remain so for several years. And yet Abjad continues to allow the creation of complex pieces of fully notated score in the midst of these changes. We believe this is due to the extensive coverage provided by the automated regression battery described in the following sections.

29.1 Automated regression?

A battery is any collection of tests. Regression tests differ from other types of test in that they are designed to be run again and again during many different stages of the development process. Regression tests help ensure that the system continues to function correctly as developers make changes to it. An automated regression battery is one that can be run automatically by some sort of driver with minimal manual intervention.

Several different test drivers are now in use in the Python community. Abjad uses `py.test`. The `py.test` distribution is not included in the Python standard library, so one of the first thing new contributors to Abjad should do is download and install `py.test`, and then run the existing battery.

29.2 Running the battery

Change to the directory where you have Abjad installed. Then run `py.test`.

```
abjad$ py.test
===== test session starts =====
platform darwin -- Python 2.6.1 -- pytest-2.1.0
collected 4235 items

core/LilyPondContextProxy/test/test_LilypondContextProxy__eq__.py .
core/LilyPondContextProxy/test/test_LilypondContextProxy__repr__.py .
core/LilyPondContextProxy/test/test_LilypondContextProxy__setattr__.py ..

... (many lines omitted) ...

tools/voicetools/test/test_voicetools_iterate_semantic_voices_forward_in_expr.py .
tools/voicetools/test/test_voicetools_iterate_voices_backward_in_expr.py .
tools/voicetools/test/test_voicetools_iterate_voices_forward_in_expr.py .

===== 4235 passed in 127.06 seconds =====
```

Abjad r4629 includes 4235 tests.

29.3 Reading test output

`py.test` crawls the entire directory structure from which you call it, running tests in alphabetical order. `py.test` prints the total number of tests per file in square brackets and prints test results as a single `.` dot for success or else an `F` for failure.

29.4 Writing tests

Project check-in standards ask that tests accompany all code committed to the Abjad repository. If you add a new function, class or method to Abjad, you should add a new test file for that function, class or method. If you fix or extend an existing function, class or method, you should find the existing test file that covers that code and then either add a completely new test to the test file or else update an existing test already present in the test file.

29.5 Test files start with `test_`

When `py.test` first starts up it crawls the entire directory structure from which you call it prior to running a single test. As `py.test` executes this preflight work, it looks for any files beginning or ending with the string `test` and then collects and alphabetizes these. Only after making such a catalog of tests does `py.test` begin execution. This collect-and-cache behavior leads to the important point about naming, below.

29.6 Avoiding name conflicts

Note that the names of **test functions** must be absolutely unique across the entire directory structure on which you call `py.test`. You must never share names between test functions. For example, you must not have two tests named `test_grob_handling_01()` **even if both tests live in different test files**. That is, a test named `test_grob_handling_01()` living in the file `test_accidental_grob_handling.py` and a second test named `test_grob_handling_01()` living in the file `test_notehead_grob_handling.py` will conflict with the each other when `py.test` runs. And, unfortunately, **“py.test is silent about such conflicts when it runs**. That is, should you run `py.test` with the duplicate naming situation described here, what will happen is that `py.test` will correctly run and report results for the **first** such test it finds. However, when `py.test` encounters the second like-named test, `py.test` will incorrectly report cached results for the **first** test rather than the second. The take-away is to include some sort of namespacing indicators in every test name and not to be afraid of long test names. The `test_grob_handling_01()` example given here fixes easily when the two tests rename to `test_accidental_grob_handling_01()` and `test_notehead_grob_handling_01()`.

29.7 Updating `py.test`

It is important periodically to update `py.test`.

The usual command to do this is:

```
$ sudo easy_install -U pytest
```

Note that `pytest` is here spelled without the intervening period.

29.8 Running doctest on the tools directory

The Python standard library includes the `doctest` module as way of checking the correctness of examples included in Python docstrings. The module searches for instances of the Python interpreter prompt `'>>>'` and executes any code that follows. Abjad docs display the Abjad prompt `'abjad>'` instead of the Python prompt. This means that all instances of the Abjad prompt must be changed to Python prompts before running `doctest` on the Abjad codebase. Three scripts in `abjad/scr/devel` help do this.

First change to the subdirectory of the Abjad source tree on which you'd like to run `doctest`. Then run these scripts:

```
replace-abjad-prompts-with-python-prompts
```

```
run-doctest-on-all-modules-in-tree
```

```
replace-python-prompts-with-abjad-prompts
```

After running `run-doctest-on-all-modules-in-tree` you can inspect the results that come back from `doctest` and make any fixes as required.

SCRIPTS

The `abjad/scr/devel` directory contains scripts for Abjad developers. Add `abjad/scr/devel` to your `PATH` to use the scripts described below.

```
abjad$ ls scr/devel
abj-grep
abj-grp
abj-rmpycs
abj-src-grp
abj-test-grp
abj-update
capitalize-test-file-names
conjoin-multiline-import-statements
count-source-lines
count-tools
duplicate-test-file
find-and-fix-manual-class-package-initializers
find-duplicate-module-names
find-duplicate-tool-module-names
find-import-as-statements
find-local-import-statements
find-lower-camel-case-definitions
find-lower-camel-case-modules
find-manual-class-loads-in-initializers
find-misnamed-private-modules
find-missing-test-modules
find-module-headers
find-modules-with-chevrons
find-multifunction-modules
find-multiline-import-statements
find-nonalphabetized-module-headers
find-nontrivial-subdirectories
find-public-helpers-without-docstrings
find-undocumented-tools
fix-nonalphabetized-module-headers
fix-test-case-block-comments
fix-test-case-names
fix-test-case-numbers
format-lilypond-context-names-with-underscores
list-private-modules
rebuild-docs
reindent-3-spaces-as-4
reindent-4-spaces-as-3
reindent-spaces-variably
remove-tmp-out-directories
rename-public-helper
replace-abjad-prompts-with-python-prompts
replace-in-files
replace-python-prompts-with-abjad-prompts
run-doctest-on-all-modules-in-tree
```

30.1 Searching the Abjad codebase with `abj-grep`

Abjad provides a wrapper around UNIX `grep` in the form of `abj-grep`. Use this script to recursively search the entire Abjad codebase, leaving out non-human-readable files, files located in special `.svn` Subversion subdirectories, and all files in the `abjad/documentation` directories. You can run `abj-grep` from any directory on your system; you needn't be in the Abjad source directories when you call `abj-grep`.

```
$ abj-grep 'is_assignable('
leaf/duration.py:111:         if not durtools.is_assignable(rational):
tempo/indication.py:67:         assert durtools.is_assignable(arg)
tools/check/are_scalable.py:12:         if not durtools.is_assignable(candidate_duration):
tools/durtools/is_assignable.py:5: def is_assignable(duration):
tools/durtools/prolated_to_written.py:2: from abjad.tools.durtools.is_assignable import is_assignable
```

```
tools/durtools/prolated_to_written.py:15:    if is_assignable(prolated_duration):
tools/tietools/duration_change.py:28:    if durtools.is_assignable(new_written_duration):
tools/tupletttools/contents_scale.py:30:    if durtools.is_assignable(multiplier):
```

30.2 Removing old *.pyc files with abj-rmpycs

See the section on `abj-update` below for the reasons that it is a good idea to periodically remove the byte-compiled *.pyc files that Python generates for its own use behind the scenes. Abjad supplies `abj-rmpycs` to delete all the *.pyc in the Abjad codebase, leaving other *.pyc on your system untouched.

30.3 Updating your development copy of Abjad with abj-update

The normal way of updating your working copy of a Subversion repository is with the `svn update` or `svn up` command. You can update your working copy of Abjad in the usual way with `svn up`. But Abjad supplies an `abj-update` script as a wrapper around the usual Subversion update commands. In addition to updating your working copy of Abjad, `abj-update` populates the `abjad/.version` file with the most recent revision number of the system, and then removes all *.pyc files from your Abjad install. The benefits here are twofold. First, Abjad adds the most recent revision number of the system to all .ly files that you generate when working with Abjad. If you do not update the Abjad version file on a regular basis, the headers in your Abjad-generated .ly files will list the wrong version of the system. Second, as is the case in working with any substantial Python codebase, it is a good idea to periodically remove the byte-compiled *.pyc files that Python creates for its own use. The reason for this is inadvertant name aliasing. That is, if there was previously a module named `foo.py` somewhere in the system and if Python had at some point imported the module and created `foo.pyc` as a byproduct, this .pyc file will remain on the filesystem even if you later decide to remove, or rename, the source `foo.py` module. This lead to confusion because days or weeks after `foo.py` has been removed, Python will still find `foo.pyc` and seem to make the contents of `foo.py` available from beyond the grave. Updating with `abj-update` takes care of these two situations.

30.4 Counting lines of code with count-source-lines

Run `count-source-lines` for a count of lines of count divided between source and test files.

```
abjad$ count-source-lines

source_modules: 1703
test_modules:   1812

source_lines:   73942
test_lines:     76636

total lines:    150578
test-to-source ratio is 1 : 1
```

The script is directory-dependent so you can run it any the entire Abjad codebase or any subdirectory of the codebase.

30.5 Global search-and-replace with replace-in-files

You probably won't need to use `replace-in-files` very often. But if you are making changes to Abjad that will cause some name, such as `FooBar`, to be globally changed everywhere in the Abjad codebase to, say to `foo_bar`,

then you can use `replace-in-files` to save lots of time.

```
$ replace-in-files --help
```

Usage:

```
replace-in-files DIR OLD_TEXT NEW_TEXT [CONFIRM=true/false]
```

Crawl directory DIR and read every file in it recursively.
Replace OLD_TEXT with NEW_TEXT in each file.

Set CONFIRM to 'false' to replace without prompting.

30.6 Adding new development scripts

If you write and then find yourself using a certain script over and over again when you're developing new code for Abjad, consider contributing back to the project so we can include your script in the next public release of Abjad. Scripts in the the Abjad script directories end with no file extension and try to be as OS-portable as possible, which usually means writing the script in Python, rather than your operating system's shell, and relying heavily on Python's `os` module.

TIMING CODE

You can time code with Python's built-in `timeit` module:

```
from abjad import *
import timeit

timer = timeit.Timer('Note(0, (1, 4))', 'from __main__ import Note')
print timer.timeit(1000)

0.225436925888
```

These results show that 1000 notes take 0.23 seconds to create.

Other Python timing modules are available for download on the public Internet.

PROFILING CODE

Profile code with `profile_expr()` in the `iotools` package:

```
abjad> iotools.profile_expr('Note(0, (1, 4))')
Sun Aug 14 16:50:36 2011      _tmp_abj_profile

      327 function calls (312 primitive calls) in 0.001 CPU seconds

Ordered by: cumulative time
List reduced from 96 to 12 due to restriction <12>

ncalls  tottime  percall  cumtime  percall filename:lineno(function)
      1   0.000    0.000    0.001    0.001 <string>:1(<module>)
      1   0.000    0.000    0.001    0.001 Note.py:18(__init__)
      1   0.000    0.000    0.001    0.001 Note.py:133(fset)
      1   0.000    0.000    0.001    0.001 NoteHead.py:18(__init__)
      1   0.000    0.000    0.001    0.001 NoteHead.py:121(fset)
      1   0.000    0.000    0.001    0.001 NamedChromaticPitch.py:28(__new__)
      1   0.000    0.000    0.000    0.000 _Leaf.py:18(__init__)
      1   0.000    0.000    0.000    0.000 chromatic_pitch_name_to_diatonic_pitch_numbe
      1   0.000    0.000    0.000    0.000 octave_tick_string_to_octave_number.py:4(oct
      1   0.000    0.000    0.000    0.000 re.py:134(match)
      1   0.000    0.000    0.000    0.000 re.py:227(_compile)
      1   0.000    0.000    0.000    0.000 sre_compile.py:501(compile)
```

These results show 327 function calls to create a note.

The `profile_expr()` function wraps the Python `cProfile` and `pstats` modules.

MEMORY CONSUMPTION

You can examine memory consumption with tools included in the `guppy` module:

```
from guppy import hpy
hp = hpy()
hp.setrelheap()
notes = [Note(0, (1, 4)) for x in range(1000)]
h = hp.heap()
print h
```

Partition of a set of 11024 objects. Total size = 586364 bytes.

Index	Count	%	Size	% Cumulative	% Kind (class / dict of class)
0	1000	9	124000	21	124000 21 abjad.tools.notetools.Note.Note.Note
1	1004	9	116464	20	240464 41 __builtin__.set
2	2003	18	76300	13	316764 54 list
3	1000	9	52000	9	368764 63 abjad.tools.pitchtools.NamedChromaticPitch.NamedChromaticPitch.NamedChromaticPitch
4	1000	9	44000	8	412764 70 abjad.interfaces._OffsetInterface._OffsetInterface._OffsetInterface
5	1000	9	44000	8	456764 78 abjad.tools.notetools.NoteHead.NoteHead.NoteHead
6	1000	9	40000	7	496764 85 0x23add0
7	1000	9	32000	5	528764 90 abjad.interfaces.ParentageInterface.ParentageInterface.ParentageInterface
8	1011	9	28568	5	557332 95 str
9	1000	9	28000	5	585332 100 abjad.interfaces._NavigationInterface._NavigationInterface._NavigationInterface

<6 more rows. Type e.g. `'_.more'` to view.>

These results show 586K for 1000 notes.

You must download `guppy` from the public Internet because the module is not included in the Python standard library.

CLASS ATTRIBUTES

Consider the definition of this class:

```
class FooWithInstanceAttribute(object):

    def __init__(self):
        self.constants = (
            'red', 'orange', 'yellow', 'green',
            'blue', 'indigo', 'violet',
        )
```

1000 objects consume 176k:

```
from guppy import hpy
hp = hpy()
hp.setrelheap()
objects = [FooWithInstanceAttribute() for x in range(1000)]
h = hp.heap()
print h
```

Partition of a set of 2004 objects. Total size = 176536 bytes.

Index	Count	%	Size	% Cumulative	% Kind (class / dict of class)
0	1000	50	140000	79	140000 79 dict of __main__.FooWithInstanceAttribute
1	1000	50	32000	18	172000 97 __main__.FooWithInstanceAttribute
2	1	0	4132	2	176132 100 list
3	1	0	348	0	176480 100 types.FrameType
4	1	0	44	0	176524 100 __builtin__.weakref
5	1	0	12	0	176536 100 int

But consider the definition of this class:

```
class FooWithSharedClassAttribute(object):

    def __init__(self):
        pass

    self.constants = (
        'red', 'orange', 'yellow', 'green',
        'blue', 'indigo', 'violet',
    )
```

1000 objects consume only 36k:

```
from guppy import hpy
hp = hpy()
hp.setrelheap()
```

```
objects = [FooWithClassAttribute() for x in range(1000)]
h = hp.heap()
print h
```

Partition of a set of 1004 objects. Total size = 36536 bytes.

Index	Count	%	Size	% Cumulative	% Kind (class / dict of class)
0	1000	100	32000	88	32000 88 __main__.FooWithClassAttribute
1	1	0	4132	11	36132 99 list
2	1	0	348	1	36480 100 types.FrameType
3	1	0	44	0	36524 100 __builtin__.weakref
4	1	0	12	0	36536 100 int

Objects that share class attributes between them can consume less memory than objects that don't. But consider the usual provisions between class attributes and instance attributes when implementing custom classes. Class attributes make sense when objects will never modify the attribute in question. Class attributes also make sense when objects will modify the attribute in question and will desire to change the attribute in question for all other like objects at the same time. Probably best to use instance attributes in most other cases.

SLOTS

Consider the definition of this class:

```
class Foo(object)

    def __init__(self, a, b, c):
        self.a = a
        self.b = b
        self.c = c
```

1000 objects consume 176k:

```
from guppy import hpy
hp = hpy()
hp.setrelheap()
objects = [Foo(1, 2, 3) for x in range(1000)]
h = hp.heap()
print h
```

Partition of a set of 2004 objects. Total size = 176536 bytes.

Index	Count	%	Size	% Cumulative	% Kind (class / dict of class)
0	1000	50	140000	79	140000 79 dict of __main__.FooWithInstanceAttribute
1	1000	50	32000	18	172000 97 __main__.FooWithInstanceAttribute
2	1	0	4132	2	176132 100 list
3	1	0	348	0	176480 100 types.FrameType
4	1	0	44	0	176524 100 __builtin__.weakref
5	1	0	12	0	176536 100 int

But consider the definition of this class:

```
class FooWithSlots(object):

    __slots__ = ('a', 'b', 'c')
    def __init__(self, a, b, c):
        self.a = a
        self.b = b
        self.c = c
```

1000 objects consume only 40k:

```
from guppy import hpy
hp = hpy()
hp.setrelheap()
objects = [FooWithSlots(1, 2, 3) for x in range(1000)]
h = hp.heap()
print h
```

Partition of a set of 1004 objects. Total size = 40536 bytes.

Index	Count	%	Size	% Cumulative	% Kind (class / dict of class)
0	1000	100	36000	89	36000 89 <code>__main__.Bar</code>
1	1	0	4132	10	40132 99 <code>list</code>
2	1	0	348	1	40480 100 <code>types.FrameType</code>
3	1	0	44	0	40524 100 <code>__builtin__.weakref</code>
4	1	0	12	0	40536 100 <code>int</code>

The example here confirms the Python Reference Manual 3.4.2.4: “By default, instances of both old and new-style classes have a dictionary for attribute storage. This wastes space for objects having very few instance variables. The space consumption can become acute when creating large numbers of instances.”

TO-DO

Once you're comfortable making changes to Abjad, check out the open to-do items listed below:

Todo

this function should (but does not) copy marks that attach to *components* and to the immediate parent of the first component; extend function to do so.

(The *original entry* is located in `chapters/api/tools/componenttools/copy_components_and_immediate_parent_of_first_component.rst`, line 68.)

Todo

Add usage examples.

(The *original entry* is located in `chapters/api/tools/componenttools/iterate_components_depth_first.rst`, line 9.)

Todo

optimize to avoid behind-the-scenes full-score traversal.

(The *original entry* is located in `chapters/api/tools/componenttools/iterate_timeline_backward_from_component.rst`, line 40.)

Todo

optimize to avoid behind-the-scenes full-score traversal.

(The *original entry* is located in `chapters/api/tools/componenttools/iterate_timeline_backward_in_expr.rst`, line 42.)

Todo

optimize to avoid behind-the-scenes full-score traversal.

(The *original entry* is located in `chapters/api/tools/componenttools/iterate_timeline_forward_from_component.rst`, line 38.)

Todo

optimize to avoid behind-the-scenes full-score traversal.

(The *original entry* is located in chapters/api/tools/componenttools/iterate_timeline_forward_in_expr.rst, line 42.)

Todo

implement `componenttools.list_leftmost_components_with_prolated_duration_at_least()`.

(The *original entry* is located in chapters/api/tools/componenttools/list_leftmost_components_with_prolated_duration_at_most.rst, line 20.)

Todo

implement `componenttools.list_rightmost_components_with_prolated_duration_at_most()`.

(The *original entry* is located in chapters/api/tools/componenttools/list_leftmost_components_with_prolated_duration_at_most.rst, line 23.)

Todo

implement `componenttools.list_rightmost_components_with_prolated_duration_at_least()`.

(The *original entry* is located in chapters/api/tools/componenttools/list_leftmost_components_with_prolated_duration_at_most.rst, line 26.)

Todo

add `n = 1` keyword to generalize flipped distance.

(The *original entry* is located in chapters/api/tools/componenttools/move_component_subtree_to_right_in_immediate_parent_of_component.rst, line 35.)

Todo

make `componenttools.move_component_subtree_to_right_in_immediate_parent_of_component()` work when spanners attach to children of component:

(The *original entry* is located in chapters/api/tools/componenttools/move_component_subtree_to_right_in_immediate_parent_of_component.rst, line 37.)

Todo

regularize return value of function.

(The *original entry* is located in chapters/api/tools/componenttools/remove_component_subtree_from_score_and_spanners.rst, line 95.)

Todo

Write a documentation chapter on quantization.

(The *original entry* is located in chapters/api/tools/quantizationtools/QGridQuantizer/QGridQuantizer.rst, line 83.)

Todo

Implement multiprocessing-based QGrid comparison

(The *original entry* is located in chapters/api/tools/quantizationtools/QGridQuantizer/QGridQuantizer.rst, line 84.)

Todo

Implement an optional *wrap* keyword to specify whether this function should wrap around the end of *sequence* whenever `len(sequence) < start + length` or not.

(The *original entry* is located in chapters/api/tools/seqtools/repeat_runs_in_sequence_to_count.rst, line 57.)

Todo

Reimplement this function to return a generator.

(The *original entry* is located in chapters/api/tools/seqtools/repeat_runs_in_sequence_to_count.rst, line 59.)

Todo

Return (immutable) tuple instead of (mutable) list.

(The *original entry* is located in chapters/api/tools/spannertools/Spanner/Spanner.rst, line 219.)

Todo

write `tietools.get_preprolated_tie_chain_duration()` tests.

(The *original entry* is located in chapters/api/tools/tietools/get_preprolated_tie_chain_duration.rst, line 7.)

Todo

Write `tietools.get_prolated_tie_chain_duration()` tests.

(The *original entry* is located in chapters/api/tools/tietools/get_prolated_tie_chain_duration.rst, line 7.)

Todo

Write `tietools.get_tie_chain_duration_in_seconds()` tests.

(The *original entry* is located in chapters/api/tools/tietools/get_tie_chain_duration_in_seconds.rst, line 7.)

Todo

Implement `diatonic_interval_class_set_to_chord_quality_string()`.

(The *original entry* is located in chapters/api/tools/tonalitytools/diatonic_interval_class_segment_to_chord_quality_string.rst, line 19.)

Todo

make work with nested tuplets.

(The *original entry* is located in chapters/api/tools/tuplettools/change_augmented_tuplets_in_expr_to_diminished.rst, line 16.)

Todo

make work with nested tuplets.

(The *original entry* is located in chapters/api/tools/tuplettools/change_diminished_tuplets_in_expr_to_augmented.rst, line 16.)

Todo

optimize without full-component traversal.

(The *original entry* is located in chapters/api/tools/verticalitytools/get_vertical_moment_at_prolated_offset_in_expr.rst, line 49.)

Todo

optimize without full-component traversal.

(The *original entry* is located in chapters/api/tools/verticalitytools/get_vertical_moment_starting_with_component.rst, line 55.)

Todo

optimize without multiple full-component traversal.

(The *original entry* is located in chapters/api/tools/verticalitytools/iterate_vertical_moments_backward_in_expr.rst, line 62.)

Todo

optimize without multiple full-component traversal.

(The *original entry* is located in chapters/api/tools/verticalitytools/iterate_vertical_moments_forward_in_expr.rst, line 62.)

Appendices

FROM TREVOR AND VÍCTOR

We are composers Trevor Bača and Víctor Adán, creators of Abjad, and our earliest collaborative work dates back to shared undergraduate years in Austin. It was the mid- to late-90s and we found ourselves interested in ways of building up ever larger sets of musical materials in our scores, with ever greater amounts of musical information.

Our work then began with pitch formalization, creating materials in C and then writing the results as MIDI to hear what we'd created. Turns out that this is a fairly common gateway into materials generation for many composers, and so it was for us. Probably this was, and is, due to the ever present availability of MIDI and, to a lesser extent, CSound. But even back then it was clear to us to finding ways to embody other aspects of the musical score – from nested rhythms to the different approaches to the musical measure to the arbitrarily complex structures possible with overlapping musical voices – would require a wholly different level of consideration, and different development techniques as well.

As an example, consider flat lists of floating-point values. This basic data structure, together with the constant need some type of quantification or rounding, feeds much of most composers' work with CSound, pd and the like. It is a good thing, therefore, that essentially all modern programming languages include tools for manipulating flat lists of floats out of the box, or in the standard library. But what happens when you want to think of pitch as something much more than integers for core values with, perhaps, floats for microtones? What if you want to work with pitches as fully-fledged objects? Objects capable of carrying arbitrarily large sets of attributes and values? Objects that might group together, first into sets, and then into larger assemblages, and then into still larger complexes of pitch information loaded, or even overloaded, with cross-relationships or textural implications? Carrying this surplus of information about pitch, or the potential uses of pitch, in data structures limited to, or centered around, the list-of-floats paradigm then becomes a burden.

And what of working with rhythms not only as offset values, as implied by the list-of-floats approach, but as arbitrarily nested, stretched, compressed and stacked sets of values, as allowed by the tupleting and measure structures of conventional score? A different approach is needed.

There was, and still is, no reason to believe that general purpose programming languages and development tools should come readily supplied with the objects and methods most suitable for composerly applications. And this means that the attributes of a domain-specific language that will best meet the needs of composers interested in working formally with the full complement of capabilities in traditional score remains an open question.

We continued our work in score formalization independently until 2005, Trevor in a system that would come to be called Lascaux, and Víctor in a system dubbed Cuepatlahto. We experimented with C, Mathematica and Matlab as the core programming languages driving our systems before settling independently on Python, Víctor out of experience at MIT, where he was working on his masters at the Media Lab with Berry Vercoe, and Trevor out of the working necessities of a professional developer and engineer.

We passed through independent experiences using Finale, Sibelius, Leland Smith's SCORE, and even Adobe Illustrator as the notational rendering engines for Lascaux and Cuepatlahto. Through all of this, both systems were designed to tackle a shared set of problems. These included:

1. The difficulty involved in transcribing larger scale and highly parameterized gestures and textures into traditional Western notation.

2. The general inflexibility of closed, commercial music notation software packages.
3. The relative inability of objects on the printed page in conventional score to point to each other — or, indeed, to other objects or ideas outside the printed page — in ways rich enough to help capture, model and develop long-range, nonlocal relationships throughout our scores.

After collaborating on a joint paper describing the two systems, and after discussing collaborative design and implementation at length, both online and in weekends' long review of our respective codebases, we decided to combine our efforts into a single, unified project. That project is now Abjad.

In our work on Abjad we strive to develop a powerful and flexible symbolic system. We picked the phrase 'formalized score control', or FSC, as a nod to Xenakis, who was so far ahead in so many ways, and also to highlight our primary project goal: to bring the full power of modern programming languages, and tools in mathematics, text processing, pattern recognition, and modular, iterative and incremental development to bear on all parts of the compositional process.

WHY LILYPOND IS RIGHT FOR ABJAD

Early versions of Abjad wrote MIDI files for input to Finale and Sibelius. Later versions of Abjad wrote .pbx files for input into Leland Smith's SCORE. Over time we found LilyPond superior to Finale, Sibelius and SCORE.

38.1 Nested tuplets works out of the box

LilyPond uses a single construct to nest tuplets arbitrarily:

```
\new stafftools.RhythmicStaff {  
  \time 7/8  
  \times 7/8 {  
    c8.  
    \times 7/5 { c16 c16 c16 c16 c16 }  
    \times 3/5 { c8 c8 c8 c8 c8 }  
  }  
}
```

```
abjad> staff = stafftools.RhythmicStaff([Measure((7, 8), [ ])])  
abjad> measure = staff[0]  
abjad> measure.append(Note('c8.'))  
abjad> measure.append(Tuplet(Fraction(7, 5), 5 * Note('c16')))  
abjad> spannertools.BeamSpanner(measure[-1])  
abjad> measure.append(Tuplet(Fraction(3, 5), 5 * Note('c8')))  
abjad> spannertools.BeamSpanner(measure[-1])  
abjad> Tuplet(Fraction(7, 8), measure.music)  
abjad> staff.override.tuplet_bracket.bracket_visibility = True  
abjad> staff.override.tuplet_bracket.padding = 1.6  
abjad> show(staff)
```




LilyPond's tuplet input syntax works the same as any other recursive construct.

38.2 Broken tuplets work out of the box

LilyPond engraves tupletted notes interrupted by nontupletted notes correctly:

```
\new Staff {
  \times 4/7 { c'16 c'16 c'16 c'16 }
  c'8 c'8
  \times 4/7 { c'16 c'16 c'16 }
}

abjad> t = Tuplet(Fraction(4, 7), Note(0, (1, 16)) * 4)
abjad> notes = Note(0, (1, 8)) * 2
abjad> u = Tuplet(Fraction(4, 7), Note(0, (1, 16)) * 3)
abjad> spannertools.BeamSpanner(t)
abjad> spannertools.BeamSpanner(notes)
abjad> spannertools.BeamSpanner(u)
abjad> measure = Measure((4, 8), [t] + notes + [u])
abjad> staff = stafftools.RhythmicStaff([measure])
abjad> show(staff)
```



38.3 Nonbinary meters work out of the box

The rhythm above rewrites with time signatures in place of tuplets:

```
\new Staff {
  \time 4/28 c'16 c'16 c'16 c'16 |
  \time 2/8 c'8 c'8 |
  \time 3/28 c'16 c'16 c'16 |
}

abjad> t = Measure((4, 28), Note(0, (1, 16)) * 4)
abjad> u = Measure((2, 8), Note(0, (1, 8)) * 2)
abjad> v = Measure((3, 28), Note(0, (1, 16)) * 3)
abjad> spannertools.BeamSpanner(t)
abjad> spannertools.BeamSpanner(u)
abjad> spannertools.BeamSpanner(v)
abjad> staff = stafftools.RhythmicStaff([t, u, v])
abjad> show(staff)
```



The time signatures 4/28 and 3/28 here have a denominator not equal to 4, 8, 16 or any other nonnegative integer power of two. Abjad calls such time signatures **nonbinary meters** and LilyPond engraves them correctly.

38.4 Lilypond models the musical measure correctly

Most engraving packages make the concept of the measure out to be more important than it should. We see evidence of this wherever an engraving package makes it difficult for either a long note or the notes of a tuplet to cross a barline. These difficulties come from working the idea of measure-as-container deep into object model of the package.

There is a competing way to model the musical measure that we might call the measure-as-background way of thinking about things. Western notation practice started absent any concept of the barline, introduced the idea gradually, and

has since retreated from the necessity of the convention. Engraving packages that pick out an understanding of the barline from the 18th or 19th centuries subscribe to the measure-as-container view of things and oversimplify the problem. One result of this is to render certain barline-crossing rhythmic figures either an inelegant hack or an outright impossibility. LilyPond eschews the measure-as-container model in favor of the measure-as-background model better able to handle both earlier and later notation practice.

WHY MIDI IS NOT ENOUGH

Given that Abjad models written musical score, it might seem odd for MIDI to be even mentioned in this manual. Yet, until fairly recently, MIDI has played a role (sometimes tangential, other times fundamental) in a variety of software tools related to music notation and engraving.

39.1 A very brief overview of midi

MIDI (Musical Instrument Digital Interface) was first introduced in 1981 by Dave Smith, the founder of Sequential Circuits. The original purpose of MIDI was to allow the communication between different electronic musical instruments; more specifically, to allow one device to send **control** data to another device. Typical messages might be “note On” (play a *note*) “note Off” (turn off a *note*). A MIDI “note” message, for example, is composed of three bytes: the first byte (the Status byte) tells the device what kind of message this is (e.g. a Note On message). The second byte encodes key number (which key was pressed) and the third byte, velocity (how hard the key was pressed). It should be clear that a *Note* in this context means something very different than *Note* in the context of a traditional printed score. While the bias towards keyboard interfaces is clear in the definition of the MIDI Note control message, one can still give the MIDI note a more general use by reinterpreting “key number” as pitch and “velocity” as loudness, the usual perceptual correlates of these control changes as well as the most meaningful musical parameters in western music.

With the subsequent proliferation of music production software, the SMF (Standard Midi File) was introduced to allow the recording and storage of the control data from a MIDI stream. The SMF required a time stamp to keep track of when control messages took place. These are called “delta-times” in the SMF specification.

“The MTrk chunk type is where actual song data is stored. It is simply a stream of MIDI events (and non-MIDI events), preceded by delta-time values.”

In combination with the MIDI Note message, the addition of duration now allowed one to have a minimal but sufficient **machine** representation—a machine score—of music requiring only these parameters: duration, pitch and loudness. Such is the case of most piano music.

39.2 Limitations of midi from the point of view of score modeling

But, alas, there is much more information in a printed score that can not be practically encoded in a SMF. Common musical notions such as meter, clef, key signature, articulation, to name only a few, are ignored. A desire to include some of these concepts in MIDI is evident in the inclusion of some so called *meta-events*. From the SMF specification: “specifies non-MIDI information useful to this format or to sequencers.” Examples of *meta-events* are *Time Signature* and *Key Signature*. In addition to the semantic elements just mentioned, there are also the typographical elements (such as line thickness, spacing, color, fonts, etc.) that all printed scores carry. This extra layer of information is completely absent in a SMF. However, from the point of view of encoding a printed score, the main limitation of MIDI is not the lack musical features or the absence of typographical data, but the assumption that musical durations, pitches

and loudnesses can be each fully and efficiently encoded with integers or even fractions. In a printed score, this is not the case for any of them. MIDI encodes only *magnitudes*: time interval magnitudes, pitch interval magnitudes, velocity magnitudes. While these may be sufficient attributes for an automated piano performance, they are not all the attributes of notes in a printed score.

39.3 Written note durations vs. midi delta-times

Assume a fixed tempo has been set. Assume that all magnitudes are represented with (and limited to) rational numbers. A time interval magnitude $d = 1/4$ has an infinity of equivalent representations in terms of magnitude: $d = 1/4 = 1/8 * 2 = 1/8 + 1/16 * 2 \dots$ etc. So, for example, while equivalent in magnitude, these are not the same notated durations:

```
abjad> m1 = measuretools.AnonymousMeasure([Note("c'4")])
abjad> m2 = measuretools.AnonymousMeasure(Note(0, (1, 8)) * 2)
abjad> tietools.TieSpanner(m2)
abjad> m3 = measuretools.AnonymousMeasure([Note(0, (1, 8)) + Note(0, (1, 16)) * 2)
abjad> tietools.TieSpanner(m3)
abjad> r = stafftools.RhythmicStaff([m1, m2, m3])
abjad> iotools.write_expr_to_ly(r, 'midi-1')
```



39.4 Written note pitch vs. midi note-on

A similar thing happens with pitches. In MIDI, key (pitch) number 61 is a half tone above middle C. But how is this pitch to be notated? As a C sharp or a B flat?

```
abjad> m1 = measuretools.AnonymousMeasure([Note(1, (1, 4))])
abjad> m2 = measuretools.AnonymousMeasure([Note('df', 4), (1, 4)])
abjad> r = Staff([m1, m2])
abjad> iotools.write_expr_to_ly(r, 'midi-2')
```



39.5 Conclusion

MIDI was not designed for score representation. MIDI is a simple communication protocol intended for real-time control. As such, it naturally lacks the adequate model to represent the full range of information found in printed scores.

CONFIGURATION

When first run, Abjad creates an `.abjad` directory in your own `$HOME` directory. In `$HOME/.abjad` you will find the Abjad configuration file: `config.py`. Here you can tell Abjad about your preferred PDF file viewer, MIDI player, your preferred LilyPond language, etc. All relevant variables have defaults that you can change to suit your needs. In Linux, for example, you might want to set your `pdfviewer` to `evince` and your `midplayer` to `timidity`.

`config.py` is a regular Python file, so you should make sure the file follows Python syntax.

RECALLING OUTPUT

41.1 Reopening Abjad PDFs

After you build a piece of notation and open with `show()` you will usually close the resulting PDF and continue working, changing your output notation in an iterative and incremental way.

```
abjad> staff = Staff(construct.scale(8))
abjad> show(staff)
```

But what if you need to go back and open the resulting PDF again? Abjad provides `pdf()` for precisely this purpose. Type the following at the Abjad prompt to open the most recent PDF written by Abjad.

```
abjad> pdf()
```

If you want to open not the next-to-most recent PDF generated by Abjad, pass in a `-1`. And for the next-to-next-to-most recent, pass in a `-2`, and so on.

41.2 Looking at LilyPond output

Abjad generates a LilyPond `.ly` file for every Abjad expression that you build and `show()`. To look at these LilyPond `.ly` files that Abjad builds behind the scenes, use `ly()`.

```
abjad> ly()

% Abjad revision 2362
% 2009-06-25 10:30

\version "2.12.2"
\include "english.ly"
\include "/Users/trevorbaca/Documents/abjad/trunk/abjad/scm/abjad.scm"

\new Staff {
  c'8
  d'8
  e'8
  f'8
  g'8
  a'8
  b'8
  c''8
}
```

Abjad opens the LilyPond `.ly` file in your favorite text editor.

These LilyPond `.ly` files that Abjad generates all have the same basic structure. The current version of Abjad and the date appear first, followed by the mandatory LilyPond version string and LilyPond directives for English note names and the default Abjad `.scm` file. The remainder of the file is reserved for the LilyPond input code corresponding to the expression you just built in Abjad.

When you are done looking at the LilyPond `.ly` file quit your text editor to return to the Abjad interpreter.

41.3 Looking at the LilyPond log

If things go wrong when you call `show()` or one of the other Abjad functions that call LilyPond behind the scenes, it may be helpful to examine the output that LilyPond writes to the LilyPond log.

```
abjad> log()
```

```
GNU LilyPond 2.12.2
Processing '1420.ly'
Parsing...
Interpreting music...
Preprocessing graphical objects...
Finding the ideal number of pages...
Fitting music on 1 page...
Drawing systems...
Layout output to '1420.ps'...
Converting to './1420.pdf'...
```

This is the normal output that LilyPond generates every time you call the program behind. When you are done looking at the LilyPond log, quit your text editor to return to the Abjad interpreter.

WORKING WITH LILYPOND MULTIPLIERS

The LilyPond `*` operator allows the creation of duration multipliers against notes, rests, chords and skips.

You can assign LilyPond multipliers in Abjad:

```
abjad> note = Note("c'4")  
abjad> note.duration_multiplier = Fraction(1, 6)
```

LilyPond multipliers change the multiplied duration of notes, rests, chords and skips:

```
abjad> note.multiplied_duration  
Duration(1, 24)
```

LilyPond multipliers leave written duration unchanged:

```
abjad> note.written_duration  
Duration(1, 4)
```


LILYPOND EQUIVALENCIES IN ABJAD

43.1 Turning on proportional notation

Turn on proportional notation like this:

```
abjad> score = Score([ ])
abjad> score.set.proportional_notation_duration = schemetools.SchemeMoment(1, 24)
abjad> score.override.spacing_spanner.uniform_stretching = True
abjad> score.override.spacing_spanner.strict_note_spacing = True
```

To produce LilyPond input that looks like this:

```
abjad> f(score)
\new Score \with {
  \override SpacingSpanner #'strict-note-spacing = ##t
  \override SpacingSpanner #'uniform-stretching = ##t
  proportionalNotationDuration = #(ly:make-moment 1 24)
} <<
>>
```


CODING STANDARDS

Indent with spaces, not with tabs. Use four spaces at a time:

```
def foo(x, y):  
    return x + y
```

Introduce comments with three pound signs and a single space:

```
### comment before foo  
def foo(x, y):  
    return x + y
```

Favor early imports at the head of each module. Only one `import` per line:

```
from foo import x  
from foo import y  
from foo import z
```

Include two blank lines after `import` statements before the rest of the module:

```
from foo import x  
from foo import y  
from foo import z
```

```
class Foo(object):  
    ...  
    ...
```

Wrap docstrings with triple apostrophes and align like this:

```
def foo(x, y):  
    '''This is the first line of the foo docstring.  
       This is the second line of the foo docstring.  
       And this is the last line of the foo docstring.  
    '''
```

Use paired apostrophes to delimit strings:

```
s = 'foo'
```

Use paired quotation marks to delimit strings within a string:

```
s = 'foo and "bar"'
```

Name classes in upper camelcase:

```
def FooBar(object):  
    ...  
    ...
```

Name bound methods in underscore-delimited lowercase:

```
def Foo(object):  
  
    def bar_blah(self):  
        ...  
  
    def bar_baz(self):  
        ...
```

Name module-level functions in underscore-delimited lowercase:

```
def foo_bar():  
    ...  
  
def foo_blah():  
    ...
```

Separate bound method definitions with a single empty line:

```
class FooBar(object):  
  
    def __init__(self, x, y):  
        ...  
  
    def bar_blah(self):  
        ...  
  
    def bar_baz(self):  
        ...
```

Organize the definitions of core classes into the five following major sections plus initialization:

```
class FooBar(object):  
  
    def __init__(self, x, y):  
        ...  
  
    ### OVERLOADS ###  
  
    def __repr__(self):  
        ...  
  
    def __str__(self):  
        ...  
  
    ### PRIVATE ATTRIBUTES ###  
  
    @property  
    def _foo(self):  
        ...  
  
    ### PUBLIC ATTRIBUTES ###  
  
    @property  
    def bar(self):
```

```

...

### PRIVATE METHODS ###

def _blah(self, x, y):
    ...

### PUBLIC METHODS ###

def baz(self, z):
    ...

```

Precede private class attributes with a single underscore:

```

class FooBar(object):

    ### PRIVATE ATTRIBUTES ###

    @property
    def _foo(self):
        ...

    ### PRIVATE METHODS ###

    def _blah(self, x, y):
        ...

```

Use < less-than signs in preference to greater-than signs:

```

if x < y < z:
    ...

```

Limit lines to 110 characters and use \ to break lines where necessary.

Eliminate trivial slice indices. Use `s[:4]` instead of `s[0:4]`.

Do not abbreviate variable names.

Name variables that represent a list or other collection of objects in the plural.

Implement only one class per module.

Implement only one function per module.

Author one `py.test` test file for every module-level function.

Author one `py.test` test file for every bound method in the public interface of a class.

WORKING WITH LISTS OF NUMBERS

Python provides a built-in `list` class that you can use to carry around almost anything. The examples here show how to create a list of numbers and then do things with the numbers in the list.

Create a list with square brackets.

```
abjad> my_list = [23, 7, 10, 18, 13, 20, 3, 2, 18, 9, 14, 3]
abjad> my_list
[23, 7, 10, 18, 13, 20, 3, 2, 18, 9, 14, 3]
```

Use `len()` to find the number of elements in any list.

```
abjad> len(my_list)
12
```

Use `append()` to add one element to a list.

```
abjad> my_list.append(5)
abjad> my_list
[23, 7, 10, 18, 13, 20, 3, 2, 18, 9, 14, 3, 5]
```

Use `extend()` to extend one list with the contents of another.

```
abjad> my_other_list = [19, 11, 4, 10, 12]
abjad> my_list.extend(my_other_list)
abjad> my_list
[23, 7, 10, 18, 13, 20, 3, 2, 18, 9, 14, 3, 5, 19, 11, 4, 10, 12]
```

Use `reverse()` to reverse the elements in a list.

```
abjad> my_list.reverse()
abjad> my_list
[12, 10, 4, 11, 19, 5, 3, 14, 9, 18, 2, 3, 20, 13, 18, 10, 7, 23]
```

You can return a single value from a list with a numeric index.

```
abjad> my_list[0]
12
abjad> my_list[1]
10
abjad> my_list[2]
4
```

You can return many values from a list with slice notation.

```
abjad> my_list[:4]
[12, 10, 4, 11]
```

More information on these and all other operations defined on the built-in Python `list` is available in the [Python tutorial](#).

PITCH CONVENTIONS


46.1 Accidental abbreviations

Abjad abbreviates accidentals according to the LilyPond `english.ly` module:

accidental name	abbreviation
quarter sharp	‘qs’
quarter flat	‘qf’
sharp	‘s’
flat	‘f’
three-quarters sharp	‘tqs’
three-quarters flat	‘tqf’
double sharp	‘ss’
double flat	‘ff’

46.2 Chromatic pitch numbers

Abjad numbers chromatic pitches by semitone with middle C set equal to 0:



The code to generate this table is as follows:

```
score, treble_staff, bass_staff = scoretools.make_empty_piano_score()
duration = Fraction(1, 32)

treble = measuretools.AnonymousMeasure([ ])
bass = measuretools.AnonymousMeasure([ ])

treble_staff.append(treble)
bass_staff.append(bass)

pitches = range(-12, 12 + 1)

cfgtools.set_default_accidental_spelling('sharps')
```

```

for i in pitches:
    note = Note(i, duration)
    rest = Rest(duration)
    clef = pitchtools.suggest_clef_for_named_chromatic_pitches([note.pitch])
    if clef == contexttools.ClefMark('treble'):
        treble.append(note)
        bass.append(rest)
    else:
        treble.append(rest)
        bass.append(note)
    diatonic_pitch_number = str(note.pitch.numbered_chromatic_pitch)
    markuptools.Markup(diatonic_pitch_number, 'down')(bass[-1])

score.override.rest.transparent = True
score.override.stem.stencil = False

show(score, 'paris.ly')

```

46.3 Diatonic pitch numbers

Abjad numbers diatonic pitches by staff space with middle C set equal to 0:



The code to generate this table is as follows:

```

score, treble_staff, bass_staff = scoretools.make_empty_piano_score()
duration = Fraction(1, 32)

treble = measuretools.AnonymousMeasure([])
bass = measuretools.AnonymousMeasure([])

treble_staff.append(treble)
bass_staff.append(bass)

pitches = []
diatonic_pitches = [0, 2, 4, 5, 7, 9, 11]

pitches.extend([-24 + x for x in diatonic_pitches])
pitches.extend([-12 + x for x in diatonic_pitches])
pitches.extend([0 + x for x in diatonic_pitches])
pitches.extend([12 + x for x in diatonic_pitches])
pitches.append(24)
cfgtools.set_default_accidental_spelling('sharps')

for i in pitches:
    note = Note(i, duration)
    rest = Rest(duration)
    clef = pitchtools.suggest_clef_for_named_chromatic_pitches([note.pitch])
    if clef == contexttools.ClefMark('treble'):

```

```
treble.append(note)
bass.append(rest)
else:
    treble.append(rest)
    bass.append(note)
diatonic_pitch_number = abs(note.pitch.numbered_diatonic_pitch)
markuptools.Markup(diatonic_pitch_number, 'down')(bass[-1])

score.override.rest.transparent = True
score.override.stem.stencil = False

show(score, 'paris.ly')
```

46.4 Octave designation

Abjad designates octaves with both numbers and ticks:

Octave notation	Tick notation
C7	c''''
C6	c'''
C5	c''
C4	c'
C3	c
C2	c,
C1	c,,

46.5 Accidental spelling

Abjad chooses between enharmonic spellings at pitch-initialization according to the following table:

Chromatic pitch-class number	Chromatic pitch-class name (default)
0	C
1	C#
2	D
3	Eb
4	E
5	F
6	F#
7	G
8	Gb
9	A
10	Bb
11	B

```
abjad> staff = Staff([Note(n, (1, 8)) for n in range(12)])
abjad> show(staff)
```



Use pitch tools to respell with sharps:

```
abjad> pitchtools.respell_named_chromatic_pitches_in_expr_with_sharps(staff)
abjad> show(staff)
```



Or flats:

```
abjad> pitchtools.respell_named_chromatic_pitches_in_expr_with_flats(staff)
abjad> show(staff)
```



SETTING PITCH DEVIATION

Use deviation to model the fact that two pitches differ by a fraction of a semitone:

```
abjad> note_1 = Note(24, (1, 2))  
abjad> note_2 = Note(24, (1, 2))  
abjad> staff = Staff([note_1, note_2])
```

```
abjad> show(staff)
```



```
abjad> note_2.written_pitch = pitchtools.NamedChromaticPitch(24, deviation = -31)
```

The pitch of the the first note is greater than the pitch of the second:

```
abjad> note_1.written_pitch > note_2.written_pitch  
True
```

Use markup to include indications of pitch deviation in your score:

```
abjad> markuptools.Markup(note_2.written_pitch.deviation_in_cents, 'up')(note_2)
```




DURATION CONVENTIONS

48.1 Introduction

Abjad publishes information about many durated score objects.

Notes, rests, chords and skips carry some duration attributes:

```
abjad> note = Note(0, (3, 16))
abjad> measure = Measure((3, 16), [note])
abjad> staff = stafftools.RhythmicStaff([measure])
abjad> note.written_duration
Duration(3, 16)
```



Tuplets, measures, voices, staves and the other containers carry duration attributes, too:

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(3, 16), Note(0, (1, 16)) * 5)
abjad> measure = Measure((3, 16), [tuplet])
abjad> staff = stafftools.RhythmicStaff([measure])
abjad> tuplet.multiplier
Duration(3, 5)
```



The next chapters document core duration concepts in Abjad.

48.2 Assignability

Western notation readily admits rational values like $1/4$. But values like $1/5$ notate only with tuplet brackets or special time signatures. Abjad formalizes the difference between rationals like $1/4$ and $1/5$ in the definition of rational assignability.

Rational values n/d are assignable when and only when numerator n is of the form $k(2^{**u}-j)$ and denominator d is of the form 2^{**v} . In this definition u and v must be nonnegative integers, k must be a positive integer, and j must be either 0 or 1.

Abjad initializes notes, rests and chords with assignable durations only.

48.3 Prolation

Abjad uses **prolation** as a cover term for rhythmic augmentation and diminution. Augmentation increases the duration of notes, rests and chords. Diminution does the opposite. Western notation employs tuplet brackets and special types of time signature to effect prolation.

48.3.1 Tuplet prolation

Tuplets prolate their contents:

```
abjad> tuplet = Tuplet(Fraction(5, 4), 4 * Note("c'8"))
abjad> staff = stafftools.RhythmicStaff([Measure((5, 8), [tuplet])])
abjad> spannertools.BeamSpanner(tuplet)
abjad> show(staff)
```



```
abjad> note = tuplet[0]
abjad> note.written_duration
Duration(1, 8)

abjad> note.prolation
Fraction(5, 4)

abjad> note.prolated_duration
Duration(5, 32)
```

Notes here with written duration 1/8 carry prolation factor 5/4 and prolated duration 5/32.

48.3.2 Meter prolation

Time signatures in western notation usually carry a denominator equal to a nonnegative integer power of 2. Abjad calls these conventional meters **binary meters**. Denominators equal to integers other than integer powers of 2 are also possible. Such **nonbinary meters** rhythmically diminish the contents of the measures they govern:

```
abjad> measure = Measure((4, 10), Note(0, (1, 8)) * 4)
abjad> spannertools.BeamSpanner(measure)
abjad> staff = stafftools.RhythmicStaff([measure])
```



```
abjad> note = staff.leaves[0]
abjad> note.prolation
Fraction(4, 5)

abjad> note.prolated_duration
Duration(1, 8)

abjad> note.prolation
Fraction(4, 5)
```



```
abjad> note.prolated_duration
Duration(1, 10)
```

Notes here with written duration $1/8$ carry prolation factor $4/5$ and prolated duration $1/10$.

48.3.3 The prolation chain

Tuplets nest and combine freely with different types of meter. When two or more **prolation donors** conspire, the prolation factor they collectively bestow on leaf-level music equals the cumulative product of all prolation factors in the **prolation chain**. All durated components carry a prolation chain:

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(4, 8), Note(0, (1, 16)) * 7)
abjad> spannertools.BeamSpanner(tuplet)
abjad> measure = Measure((4, 10), [tuplet])
abjad> staff = stafftools.RhythmicStaff([measure])
```



```
abjad> measure.multiplier
Fraction(4, 5)

abjad> note = measure.leaves[0]
abjad> note.prolation
Duration(32, 35)

abjad> note.prolated_duration
Duration(2, 35)
```

Notes here with written duration $1/16$ carry prolated duration $2/35$.

Note: Western notation does not recognize tuplet brackets carrying one-to-one ratios. Such **trivial tuplets** may, however, be useful during different stages of composition, and Abjad allows them for that reason. Trivial tuplets carry **zero prolation**. Zero-prolated tuplets neither augment nor diminish the music they contain.

Note: Abjad implements one of two competing nonbinary **meter-interpretation schemes**. The first, **implicit meter-interpretation** given here, follows, for example, Ferneyhough, in that nonbinary meters prolate the contents of the measures they govern implicitly, ie, without recourse to tuplet brackets. The second, **explicit meter-interpretation**, which we find in, for example, Sciarrino, insists instead on the presence of some tuplet bracket, usually engraved in some broken or incomplete way. The implicit meter-interpretation that Abjad implements differs from the explicit meter-interpretation native to LilyPond. Abjad will eventually implement both implicit and explicit meter-interpretation, settable on a container-by-container basis.

Note: Nonbinary meter n/d rhythmically diminishes the contents of the measure it governs by a factor j/k , with $k=d$, and with j equal to the greatest integer power of 2 less than d . That is, $j=2^{**int(\log_2(d))}$.

48.4 Duration types

Abjad publishes duration information about all score components.

48.4.1 Written duration

Abjad uses **written duration** to refer to the face value of notes, rests and chords prior to prolation. Abjad written duration corresponds to the informal names most frequently used when talking about note duration.

These sixteenth notes are worth a sixteenth of a whole note:

```
abjad> measure = Measure((5, 16), Note(0, (1, 16)) * 5)
abjad> spannertools.BeamSpanner(measure)
abjad> staff = stafftools.RhythmicStaff([measure])
abjad> note = measure[0]
abjad> note.written_duration
Duration(1, 16)
```



These sixteenth notes are worth more than a sixteenth of a whole note:

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(5, 16), Note(0, (1, 16)) * 4)
abjad> spannertools.BeamSpanner(tuplet)
abjad> measure = Measure((5, 16), [tuplet])
abjad> staff = stafftools.RhythmicStaff([measure])
abjad> note = tuplet[0]
abjad> note.written_duration
Duration(1, 16)
```



The notes in these examples are ‘sixteenth notes’ that carry different prolated durations. Abjad written duration captures the fact that the note heads and flag counts of the two examples match.

Written duration is a user-assignable rational number. Users can assign and reassign the written duration of notes, rests and chords at initialization and at any time during the life of the note, rest or chord. Written durations must be assignable; see the chapter on *assignability* for details. Note that Abjad containers do not carry written duration.

48.4.2 Prolated duration

Prolation refers to the duration-scaling effects of tuplets and special types of time signature. Prolation is a way of thinking about the contribution that musical structure makes to the duration of score objects. All durated Abjad objects carry a prolated duration. Prolated duration is an emergent property of notes, tuplets and other durated objects. The prolated duration of notes, rests and chords equals the product of the written duration and prolation of those objects. The prolated duration of tuplets, measures and other containers equals the the container’s duration interface multiplied by the container’s prolation.

48.4.3 Contents duration

Abjad defines the **contents duration** of tuplets, measures, voices, staves and other containers equal to the sum of the **preprolated duration** of each of the elements in the container.

The measure here contains two eighth notes and tuplet. These elements carry preprolated durations equal to 1/8, 1/8 and 2/8, respectively:

```
abjad> notes = Note(0, (1, 8)) * 2
abjad> spannertools.BeamSpanner(notes)
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), Note(0, (1, 8)) * 3)
abjad> spannertools.BeamSpanner(tuplet)
abjad> measure = Measure((4, 8), notes + [tuplet])
abjad> staff = stafftools.RhythmicStaff([measure])
abjad> measure.contents_duration
Duration(1, 2)
```



The contents duration of the measure here equals $1/8 + 1/8 + 2/8 = 4/8$.

48.4.4 Target duration

Abjad defines the target duration of fixed-duration tuplets equal to composer-settable duration to which the tuplet prolates its contents.

This fixed-duration tuplet carries a target duration equal to $4/8$:

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(4, 8), Note(0, (1, 8)) * 5)
abjad> spannertools.BeamSpanner(tuplet)
abjad> measure = Measure((4, 8), [tuplet])
abjad> staff = stafftools.RhythmicStaff([measure])
abjad> print tuplet.contents_duration
5/8
abjad> tuplet.target_duration
Duration(1, 2)
```



The tuplet contents sum to $5/8$. But tuplet target duration always equals $4/8$.

48.4.5 Multiplied duration

Abjad defines the multiplied duration of notes, rests and chords equal to the product of written duration and leaf multiplier.

The first two notes below carry leaf multipliers equal to $2/1$:

```
abjad> notes = Note(0, (1, 16)) * 4
abjad> notes[0].duration_multiplier = Fraction(2, 1)
abjad> notes[1].duration_multiplier = Fraction(2, 1)
abjad> measure = Measure((3, 8), notes)
abjad> spannertools.BeamSpanner(measure)
abjad> staff = stafftools.RhythmicStaff([measure])
abjad> note = measure[0]
abjad> note.written_duration
Duration(1, 16)
```



```
abjad> note.duration_multiplier
Fraction(2, 1)
```

```
abjad> note.written_duration * note.duration_multiplier
Duration(1, 8)
abjad> note.multiplied_duration
Duration(1, 8)
```

The written duration of these first two notes equals 1/16 and so the multiplied duration of these first two notes equals $1/16 * 2/1 = 1/8$.

48.5 Duration initialization

Durated Abjad classes initialize duration from arguments in the form (n, d) with numerator n and denominator d .

```
abjad> note = Note(0, (3, 16))
```



Durated classes include notes, rests, chords, skips, tuplets and measures.

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), Note(0, (1, 8)) * 3)
abjad> spannertools.BeamSpanner(tuplet)
```



Abjad restricts notes, rests, chords and skips to durations like 3/16 that can be written with dots, beams and flags without ties or brackets. Abjad allows arbitrary positive durations like 5/8 for tuplets and measures.

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(5, 8), Note(0, (1, 8)) * 4)
abjad> spannertools.BeamSpanner(tuplet)
```



Abjad supports breves.

```
abjad> note = Note(0, (2, 1))
```



And longas.

```
abjad> note = Note(0, (4, 1))
```



Note: The restriction that the written durations of notes, rests, chords and skips be expressible with some combination of dots, flags and beams without recourse to ties and brackets generalizes to the condition of `note_head` assignability. Values (n, d) are `note_head`-assignable when and only when (1) d is a nonnegative integer power of 2; (2) n is either a nonnegative integer power of 2 or is a nonnegative integer power of 2, minus 1; and (3) n/d is less than or equal to 8. Condition (3) captures the fact that LilyPond provides no glyph with greater duration than the maxima (equal to eight whole notes).

Note: Integer forms like 4 as a substitute for $(4, 1)$ in `Note(0, (4, 1))` are undocumented but allowed.

Note: Abjad allows maxima `note_heads` as in `Note(0, (8, 1))`. LilyPond implements a *maxima* command but does not supply a corresponding glyph for the `note_head`.

48.6 LilyPond multipliers

LilyPond provides an asterisk `*` operator to scale the durations of notes, rests and chords by arbitrarily positive rational values. LilyPond multipliers are invisible and generate no typographic output of their own. However, while independent from the typographic output, LilyPond multipliers do factor in in calculations of duration and time.

Abjad implements LilyPond multipliers as the settable `duration.multiplier` attribute of notes, rests and chords.

```
abjad> note = Note("c' 4")
abjad> note.duration_multiplier = Fraction(1, 2)
abjad> note.duration_multiplier
Fraction(1, 2)
```


```
abjad> f(note)
c' 4 * 1/2
```

Abjad also implements a `duration.multiplied` attribute to examine the duration of a note, rest or chord as affected by the multiplier.

```
abjad> note.multiplied_duration
Duration(1, 8)
```

LilyPond multipliers give the half notes here multiplied durations equal to a quarter note.

```
abjad> notes = Note("c' 4") * 4
abjad> multiplied_note = Note(0, (1, 2))
abjad> multiplied_note.duration_multiplier = Fraction(1, 2)
abjad> multiplied_notes = multiplied_note * 4
abjad> top = stafftools.RhythmicStaff(notes)
abjad> bottom = stafftools.RhythmicStaff(multiplied_notes)
abjad> staves = scoretools.StaffGroup([top, bottom])
```



Note: Abjad models multiplication fundamentally differently than prolation. See the chapter on *Prolation* for more information.

Note: The LilyPond multiplication * operator differs from the Abjad multiplication * operator. LilyPond multiplication scales duration of LilyPond notes, rests and chords. Abjad multiplication copies Abjad containers and leaves.

48.7 Duration interfaces compared

type	core	leaf	container	measure	tuplet	fd tuple	fm tuple
contents	–	–	R	R	R	R	R
multiplied	–	R	–	–	–	R	R
multiplier	–	RW	–	R	R	R	RW
preprolated	R	R	R	R	R	R	R
prolated	R	R	R	R	R	R	R
prolation	R	R	R	R	R	R	R
target	–	–	–	–	–	RW	–
written	–	RW	–	–	–	–	–

The table contains a total of only four settable duration attributes, divided among only three classes. Durated Abjad classes offer up many read-only duration attributes but very few read-write duration attributes.

All classes carry all three prolation-related attributes because all classes can nest inside containers. It is possible, for example, to nest an entire voice within a fixed-duration tuple.

Note: Leaf multipliers and tuple multipliers differ.

TEMPLATE GALLERY

Abjad provides a number of score templates in the `abjad/templates` directory:

```
abjad> from abjad.tools import cfgtools
abjad> cfgtools.list_abjad_templates()
('coventry.ly', 'lagos.ly', 'oedo.ly', 'paris.ly', 'tangiers.ly', 'thebes.ly', 'tirnaveni.ly')
```

Templates provide header, layout, paper and grob settings for different types of score.

49.1 Default LilyPond layout

```
abjad> import random
abjad> pitches = [random.randrange(0, 25) for x in range(32)]
abjad> staff_1 = Staff([ ])
abjad> staff_2 = Staff([ ])
abjad> score = Score([staff_1, staff_2])
abjad> staff_1.extend([Note(x, (1, 8)) for x in pitches[:16]])
abjad> staff_2.extend([Note(x, (1, 8)) for x in pitches[16:]])
abjad> show(score)
```



49.2 `lagos.ly`

```
abjad> pitches = [random.randrange(0, 25) for x in range(32)]
abjad> staff_1 = Staff([ ])
abjad> staff_2 = Staff([ ])
abjad> score = Score([staff_1, staff_2])
abjad> staff_1.extend([Note(x, (1, 8)) for x in pitches[:16]])
abjad> staff_2.extend([Note(x, (1, 8)) for x in pitches[16:]])
abjad> show(score, template = 'lagos')
```



49.3 oedo.ly

```
abjad> pitches = [random.randrange(0, 25) for x in range(32)]
abjad> staff_1 = Staff([ ])
abjad> staff_2 = Staff([ ])
abjad> score = Score([staff_1, staff_2])
abjad> staff_1.extend([Note(x, (1, 8)) for x in pitches[:16]])
abjad> staff_2.extend([Note(x, (1, 8)) for x in pitches[16:]])
abjad> show(score, template = 'oedo')
```



49.4 tangiers.ly

```
abjad> pitches = [random.randrange(0, 25) for x in range(32)]
abjad> staff_1 = Staff([ ])
abjad> staff_2 = Staff([ ])
abjad> score = Score([staff_1, staff_2])
abjad> staff_1.extend([Note(x, (1, 8)) for x in pitches[:16]])
abjad> staff_2.extend([Note(x, (1, 8)) for x in pitches[16:]])
abjad> show(score, template = 'tangiers')
```




49.5 tirnaveni.ly

```
abjad> pitches = [random.randrange(0, 25) for x in range(32)]
abjad> staff_1 = Staff([ ])
abjad> staff_2 = Staff([ ])
abjad> score = Score([staff_1, staff_2])
abjad> staff_1.extend([Note(x, (1, 8)) for x in pitches[:16]])
abjad> staff_2.extend([Note(x, (1, 8)) for x in pitches[16:]])
abjad> show(score, template = 'tirnaveni')
```



TEXT ALIGNMENT

LilyPond provides many ways to position text.

50.1 Default alignment

LilyPond left-aligns markup relative to the left edge of note head by default.

```
abjad> notes = notetools.make_repeated_notes(1, Fraction(1, 4))
abjad> staff = stafftools.RhythmicStaff(notes)
abjad> leaves = staff.leaves
abjad> markuptools.Markup('XX', 'up')(leaves[0])
abjad> show(staff, 'thebes')
```



50.2 TextScript #'self-alignment-X

Use #'self-alignment-X to left-, center- or right-align markup relative to the left edge of note head.

Note: changes to #'self-alignment-X do not change the fact that markup positioning is by default relative to the LEFT edge of note head.

```
abjad> notes = notetools.make_repeated_notes(3, Fraction(1, 4))
abjad> staff = stafftools.RhythmicStaff(notes)
abjad> leaves = staff.leaves
abjad> markuptools.Markup('XX', 'up')(leaves[0])
abjad> leaves[0].override.text_script.self_alignment_X = 'left'
abjad> markuptools.Markup('XX', 'up')(leaves[1])
abjad> leaves[1].override.text_script.self_alignment_X = 'center'
abjad> markuptools.Markup('XX', 'up')(leaves[2])
abjad> leaves[2].override.text_script.self_alignment_X = 'right'
abjad> show(staff, 'thebes')
```



50.3 TextScript #'X-offset

Use #'X-offset to offset markup by some number of magic units in the horizontal direction.

Note: Specify #'X-offset arguments as numbers like #2.5. Do not specify #'X-offset arguments as direction constants like #right.

Note: changes to #'X-offset do not change the fact that markup positioning is by default relative to the LEFT edge of note head.

```
abjad> notes = notetools.make_repeated_notes(4, Fraction(1, 4))
abjad> staff = stafftools.RhythmicStaff(notes)
abjad> leaves = staff.leaves
abjad> markuptools.Markup('XX', 'up')(leaves[0])
abjad> leaves[0].override.text_script.X_offset = 0
abjad> markuptools.Markup('XX', 'up')(leaves[1])
abjad> leaves[1].override.text_script.X_offset = 2
abjad> markuptools.Markup('XX', 'up')(leaves[2])
abjad> leaves[2].override.text_script.X_offset = 4
abjad> markuptools.Markup('XX', 'up')(leaves[3])
abjad> leaves[3].override.text_script.X_offset = 6
abjad> show(staff, 'thebes')
```



ABJAD-BOOK

`abjad-book` is an independent application included in every installation of Abjad. `abjad-book` allows you to write Abjad code in the middle of documents written in HTML, LaTeX or ReST. We created `abjad-book` to help us document Abjad. Our work on `abjad-book` was inspired by `lilypond-book`, which does for LilyPond much what `abjad-book` does for Abjad.

51.1 HTML with embedded Abjad

To see `abjad-book` in action, open a file and write some HTML by hand. Add some Abjad code to your HTML between open and close `<abjad>` `</abjad>` tags.

```
<html>

<p>This is an <b>HTML</b> document.</p>

<p>The code is standard hypertext mark-up.</p>

<p>Here is some music notation generated automatically by Abjad:</p>

<abjad>
v = Voice(construct.scale(8))
Beam(v)
write_ly(v, 'abjad-book-1') <hide
show(v)
</abjad>

<p>And here is more ordinary <b>HTML</b>.</p>

</html>
```

Save your the file with the name `example.html.raw`. You now have an HTML file with embedded Abjad code.


In the terminal, call `abjad-book` on `example.html.raw`.

```
$ abjad-book example.html.raw example.html
```

```
Parsing file...
Rendering "abjad-book-1.ly"...
```

The application opens `example.html.raw`, finds all Abjad code between `<abjad>` `</abjad>` tags, executes it, and then creates and inserts image files of music notation accordingly.

Open `example.html` with your browser.



That’s all there is to it. `abjad-book` lets you open a file and type HTML by hand with Abjad sandwiched between the special `<abjad>` `</abjad>` tags described here. Run `abjad-book` on such a hybrid file to create pure HTML with images of music notation created by Abjad.

Note: `abjad-book` makes use of ImageMagick’s `convert` application to crop and scale PNG images generated for HTML and ReST documents. For LaTeX documents, `abjad-book` uses `pdfcrop` for cropping PDFs.

51.2 LaTeX with embedded Abjad

You can use `abjad-book` to insert Abjad code and score excerpts into any LaTeX you create. Type the sample code below into a file.

```
\documentclass{article}
\usepackage{graphicx}
\usepackage{listings}
\begin{document}
```

This is a standard LaTeX document with embedded Abjad.

The code below creates an Abjad measure and then prints the measure format string.

```
<abjad>
measure = RigidMeasure((5, 8), construct.scale(5))
print measure.format
</abjad>
```

This next bit of code knows about the measure we defined earlier. This code renders the measure as a PDF using a template suitable for inclusion in LaTeX documents.

```
<abjad>
write_ly(measure, 'abjad-book-1', 'oedo') <hide
</abjad>
```

And this is the end of the our sample LaTeX document.

```
\end{document}
```

Save your file with the name `example.tex.raw`. You now have a LaTeX file with embedded Abjad code.

In the terminal, call `abjad-book` on `example.tex.raw`.

```
$ abjad-book example.tex.raw example.tex
```

```
Processing 'example.tex.raw'. Will write output to 'example.tex'...
Parsing file...
Rendering "abjad-book-1.ly"...
```

The application open `example.tex.raw`, finds all code between Abjad tags, executes it, and then creates and inserts Abjad interpreter output and PDF files of music notation. You can view the contents of the next LaTeX file `abjad-book` has created.

```
\documentclass{article}
\usepackage{graphicx}
\usepackage{listings}
\begin{document}
```

This is a standard LaTeX document with embedded Abjad.

The code below creates an Abjad measure and then prints the measure format string.

```
\begin{lstlisting}[basicstyle=\footnotesize, tabsize=4, showtabs=false, showspace=false]
  abjad> measure = RigidMeasure((5, 8), construct.scale(5))
  abjad> print measure.format
  {
    \time 5/8
    c'8
    d'8
    e'8
    f'8
    g'8
  }
\end{lstlisting}
```

This next bit of code knows about the measure we defined earlier. This code renders the measure as a PDF using a template suitable for inclusion in LaTeX documents.

```
\includegraphics{images/abjad-book-1.pdf}
```

And this is the end of the our sample LaTeX document.

```
\end{document}
```

You can now process the file `example.tex` just like any other LaTeX file, using `pdflatex` or `TexShop` or whatever LaTeX compilation program you normally use on your computer.

```
$ pdflatex example.tex
```

```
This is pdfTeX, Version 3.141592-1.40.3 (Web2C 7.5.6)
 %&-line parsing enabled.
entering extended mode
...
```

And then open the resulting PDF.

51.3 Using abjad-book on ReST documents

You can call `abjad-book` on ReST documents, too. Follow the examples given here for HTML and LaTeX documents and modify accordingly.

51.4 Using `[hide = True]`

You can add `[hide = True]` to any `abjad-book` example to show only music notation.

```
<abjad>[hide = True]
staff = Staff(construct.scale(8))
write_ly(staff, 'staff-example', 'oedo')
</abjad>
```


X11 COLOR NAMES

Abjad supports the [X11 color names](#) available in LilyPond

BIBLIOGRAPHY

VERSION HISTORY

54.1 Abjad 1.1.1

Abjad 1.1.1.tar.gz

- More complete documentation.
- The configuration file `config` changed to pure Python `config.py`. The file now supports more settings previously read as environment variables. All user settings are now found in this file. Users no longer need to set environment variables.
- Some new classes
 - `_HistoryInterface`. Use the `_HistoryInterface` to apply attributes to any component in score that will be completely ignored by Abjad. Think of the `_HistoryInterface` as a private user namespace.
 - `_NoteColumnInterface` to handle the LilyPond `NoteColumn` grob.
 - `_SpanBarInterface`. See API for details.
 - `InvisibleStaff()` staff.
 - `Moment` utility class to model the Abjad representation of the LilyPond moment.
- New Spanners
 - `TempoProportional` spanner.
- More than a dozen new tools added.

54.2 Abjad 1.1.0

- Many structure transform tools added. See the `abjad.tools.*` in the *Abjad API* package.
- Construction, transformation, manipulation and all other tools now grouped cleanly into packages.
- New `abjad-book` application available. Use `abjad-book` to interpret Abjad code blocks embedded in HTML, LaTeX and reST documents.

54.3 Abjad 1.0.1055

Changes to the public interface:

- Abjad now models ties exclusively with the Tie spanner. The old `_TieInterface._set` attribute is now deprecated.
- You can no longer say `t.tie = True` or `t.tie = False`, for leaf `t`. You must structurally span `t` as `Tie(t)` instead.
- New public properties in `_SpannerReceptor`: `chain`, `parented`, `count`.
- New public helpers:
 - `construct.notes_curve()`
 - `durtools.rationalize()`
 - `iterate.tie_chains()`
 - `list_helpers()`
 - `mathtools.interpolate_divide()`
 - `measuretools.concentrate()`
 - `measuretools.scale_and_remeter()`
 - `measuretools.spin()`
 - `play()`
- Grace note `append()` and `extend()` no longer throw errors.

54.4 Abjad 1.0.1022

- First public release of Abjad.

INSTALLATION

55.1 Abjad depends on Python

You must have Python 2.5, 2.6 or 2.7 installed to run Abjad.

Abjad does not yet support the Python 3.x series of releases.

To check the version of Python installed on your computer type the following:

```
python --version
```

You can download different versions of Python at <http://www.python.org>.

55.2 Abjad depends on LilyPond

You must have LilyPond 2.12 or greater installed for Abjad to work properly.

You can download LilyPond at <http://www.lilypond.org>.

After you have installed LilyPond you should type the following to see if LilyPond is callable from your commandline:

```
lilypond --version
```

If LilyPond is not callable from your commandline you should add the location of the LilyPond executable to your PATH environment variable.

If you are new to working with the commandline you should use Google to get a basic introduction to editing your profile and setting environment variables.

55.3 Installing the current packaged version of Abjad with easy_install

There are different ways to install Python packages on your computer. One of the most direct ways is with `easy_install`.

If you have `easy_install` installed on your computer then you can install Abjad with this command:

```
sudo easy_install -U abjad
```

Python will install Abjad in the site packages directory on your computer and you'll be ready to start using the system.

If you do not have `easy_install` installed on your computer then you should follow the instructions below to install the current packaged version of Abjad from the Python Package Index.

55.4 Installing the current packaged version of Abjad from the Python Package Index

If you do not have `easy_install` installed on your computer you should follow these steps to install the current packaged version of Abjad from the Python Package Index:

1. Download the current release of Abjad from <http://pypi.python.org/pypi/Abjad>.
2. Unarchive the downloaded file. Under MacOS and Windows you can double click the archived file.
Under Linux execute the following command with `x.y` replaced by the current release of Abjad:

```
tar xzvf Abjad-x.y.tar.gz
```

3. Change into the directory created in step 2:

```
cd Abjad-x.y
```

4. Run the following under MacOS or Linux:

```
sudo python setup.py install
```

5. Or run this command under Windows after starting up a command shell with administrator privileges:

```
setup.py install
```

These commands will cause Python to install Abjad in your site packages directory. You'll then be ready to start using Abjad.

55.5 Note for Linux users

Abjad defaults to `xdg-open` to display PDF files using your default PDF viewer. Most Linux distributions now come with `xdg-utils` installed.

If you do not have `xdg-utils` installed, you can download it from <http://www.portland.freedsektop.org>.

Alternatively you can set the `pdfviewer` variable in `$HOME/.abjad/config` to your favorite PDF viewer.

WHAT NEXT?

The most powerful features of Abjad are the set of interlocking objects that structure the system. Find out how Abjad models pitch, duration, leaves, containers and spanners in the chapters on Abjad fundamentals. These chapters explain how to work with the basic Abjad components.

Read some of the chapters concerning materials generation to figure out how to create starting materials.

And then read about structure traversal and manipulation to learn how to move around in large pieces of notation and change them while you go.

When you get stuck, check out the public interface in the *Abjad API*.

When you start to extend Abjad with custom code that you write for your own scores, read the chapters on developing with Abjad. These chapters describe how the codebase is laid out, how to add documentation and tests to the system, and how to contribute code that you write back to the public release of Abjad. We love contributions from composers working in many different ways. So get in touch and consider contributing to the project when the time feels right.

56.1 Get in touch!

Please join our two new mailing lists:

Questions or comments? Join the [abjad-user](#) list.

Want to contribute? Join the [abjad-devel](#) list.

ABJAD API

57.1 Abjad API

57.1.1 Abjad composition packages

chordtools

chordtools.Chord

```
class abjad.tools.chordtools.Chord(*args, **kwargs)
    Bases: abjad.tools.leaftools._Leaf._Leaf._Leaf
```

Abjad model of a chord:

```
abjad> Chord([4, 13, 17], (1, 4))
Chord("<e' cs' ' f' '>4")
```

Return chord instance.

append (*note_head_token*)

Append *note_head_token* to chord:

```
abjad> chord = Chord([4, 13, 17], (1, 4))
abjad> chord
Chord("<e' cs' ' f' '>4")
```

```
abjad> chord.append(19)
abjad> chord
Chord("<e' cs' ' f' ' g' '>4")
```

Sort chord note heads automatically after append and return none.

clear ()

Clear chord:

```
abjad> chord = Chord("<e' cs' ' f' '>4")
abjad> chord
Chord("<e' cs' ' f' '>4")
```

```
abjad> chord.clear()
abjad> chord
Chord('<>4')
```

Return none.

extend (*note_head_tokens*)

Extend chord with *note_head_tokens*:

```
abjad> chord = Chord([4, 13, 17], (1, 4))
abjad> chord
Chord("<e' cs'' f''>4")

abjad> chord.extend([2, 12, 18])
abjad> chord
Chord("<d' e' c'' cs'' f'' fs''>4")
```

Sort chord note heads automatically after extend and return none.

fingered_pitches

Read-only fingered pitches:

```
abjad> staff = Staff("<c''' e'''>4 <d''' fs'''>4")
abjad> glockenspiel = instrumenttools.Glockenspiel()(staff)
abjad> instrumenttools.transpose_notes_and_chords_in_expr_from_sounding_pitch_to_fingered_pi

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Glockenspiel }
  \set Staff.shortInstrumentName = \markup { Gkspl. }
  <c' e'>4
  <d' fs'>4
}

abjad> staff[0].fingered_pitches
(NamedChromaticPitch("c'"), NamedChromaticPitch("e'"))
```

Return tuple of named chromatic pitches.

note_heads

Get read-only tuple of note heads in chord:

```
abjad> chord = Chord([7, 12, 16], (1, 4))
abjad> chord.note_heads
(NoteHead("g'"), NoteHead("c'"), NoteHead("e'"))
```

Set chord note heads from any iterable:

```
abjad> chord = Chord([7, 12, 16], (1, 4))
abjad> chord.note_heads = [0, 2, 6]
abjad> chord
Chord("<c' d' fs'>4")
```

pop (*i=-1*)

Remove note head at index *i* in chord:

```
abjad> chord = Chord([4, 13, 17], (1, 4))
abjad> chord
Chord("<e' cs'' f''>4")

abjad> chord.pop(1)
NoteHead("cs'")

abjad> chord
Chord("<e' f''>4")
```

Return note head.

remove (*note_head*)

Remove *note_head* from chord:

```
abjad> chord = Chord([4, 13, 17], (1, 4))
abjad> chord
Chord("<e' cs' f'>4")
```

```
abjad> chord.remove(chord[1])
abjad> chord
Chord("<e' f'>4")
```

Return none.

sounding_pitches

Read-only sounding pitches:

```
abjad> staff = Staff("<c' e'>4 <d' fs'>4")
abjad> glockenspiel = instrumenttools.Glockenspiel()(staff)
abjad> instrumenttools.transpose_notes_and_chords_in_expr_from_sounding_pitch_to_fingered_pi
```

```
abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Glockenspiel }
  \set Staff.shortInstrumentName = \markup { Gkspl. }
  <c' e'>4
  <d' fs'>4
}
```

```
abjad> staff[0].sounding_pitches
(NamedChromaticPitch("c'"), NamedChromaticPitch("e'"))
```

Return tuple of named chromatic pitches.

written_pitches

Get read-only tuple of pitches in chord:

```
abjad> chord = Chord([7, 12, 16], (1, 4))
abjad> chord.written_pitches
(NamedChromaticPitch("g'"), NamedChromaticPitch("c'"), NamedChromaticPitch("e'))
```

Set chord pitches from any iterable:

```
abjad> chord = Chord([7, 12, 16], (1, 4))
abjad> chord.written_pitches = [0, 2, 6]
abjad> chord
Chord("<c' d' fs'>4")
```

chordtools.arpeggiate_chord

`abjad.tools.chordtools.arpeggiate_chord` (*chord*)

New in version 1.1. Arpeggiate *chord*:

```
abjad> chord = Chord("<c' d' ef'>8")

abjad> chordtools.arpeggiate_chord(chord)
[Note("c'8"), Note("d'8"), Note("ef'8")]
```

Arpeggiated notes inherit *chord* written duration.

Arpeggiated notes do not inherit other *chord* attributes.

Return list of newly constructed notes. Changed in version 2.0: renamed `chordtools.arpeggiate()` to `chordtools.arpeggiate_chord()`.

chordtools.change_defective_chord_to_note_or_rest

`abjad.tools.chordtools.change_defective_chord_to_note_or_rest(chord)`

New in version 1.1. Change zero-length *chord* to rest:

```
abjad> chord = Chord([ ], (3, 16))
```

```
abjad> chord
Chord('<>8.')
```

```
abjad> chordtools.change_defective_chord_to_note_or_rest(chord)
Rest('r8.')
```

Change length-one chord to note:

```
abjad> chord = Chord("<cs''>8.")
```

```
abjad> chord
Chord("<cs''>8.")
```

```
abjad> chordtools.change_defective_chord_to_note_or_rest(chord)
Note("cs''8.")
```

Return chords with length greater than one unchanged:

```
abjad> chord = Chord("<c' c'' cs''>8.")
```

```
abjad> chord
Chord("<c' c'' cs''>8.")
```

```
abjad> chordtools.change_defective_chord_to_note_or_rest(chord)
Chord("<c' c'' cs''>8.")
```

Return notes unchanged:

```
abjad> note = Note("c'4")
```

```
abjad> note
Note("c'4")
```

```
abjad> chordtools.change_defective_chord_to_note_or_rest(note)
Note("c'4")
```

Return rests unchanged:

```
abjad> rest = Rest('r4')
```

```
abjad> rest
Rest('r4')
```

```
abjad> chordtools.change_defective_chord_to_note_or_rest(rest)
Rest('r4')
```

Return note, rest, chord or none. Changed in version 2.0: renamed `chordtools.cast_defective()` to `chordtools.change_defective_chord_to_note_or_rest()`.

chordtools.color_chord_note_heads_by_pitch_class_color_map

abjad.tools.chordtools.**color_chord_note_heads_by_pitch_class_color_map**(*chord*,
color_map)

New in version 2.0. Color *chord* note heads by pitch-class *color_map*:

```
abjad> chord = Chord([12, 14, 18, 21, 23], (1, 4))

abjad> pitches = [[-12, -10, 4], [-2, 8, 11, 17], [19, 27, 30, 33, 37]]
abjad> colors = ['red', 'blue', 'green']
abjad> color_map = pitchtools.NumberedChromaticPitchClassColorMap(pitches, colors)

abjad> chordtools.color_chord_note_heads_by_pitch_class_color_map(chord, color_map)
Chord("<c'' d'' fs'' a'' b''>4")

abjad> f(chord)
<
    \tweak #'color #red
    c''
    \tweak #'color #red
    d''
    \tweak #'color #green
    fs''
    \tweak #'color #green
    a''
    \tweak #'color #blue
    b''
>4
```

Also works on notes:

```
abjad> note = Note("c'4")

abjad> chordtools.color_chord_note_heads_by_pitch_class_color_map(note, color_map)
Note("c'4")

abjad> f(note)
\once \override NoteHead #'color = #red
c'4
```

When *chord* is neither a chord nor note return *chord* unchanged:

```
abjad> staff = Staff([ ])

abjad> chordtools.color_chord_note_heads_by_pitch_class_color_map(staff, color_map)
Staff{}
```

Return *chord*. Changed in version 2.0: renamed `chordtools.color_note_heads_by_pc()` to `chordtools.color_chord_note_heads_by_pitch_class_color_map()`.

chordtools.divide_chord_by_chromatic_pitch_number

abjad.tools.chordtools.**divide_chord_by_chromatic_pitch_number**(*chord*,
pitch=NamedChromaticPitch('b'))

New in version 1.1. Divide *chord* by chromatic *pitch* number:

```
abjad> chord = Chord(range(12), Duration(1, 4))
```

```
abjad> chord
Chord("<c' cs' d' ef' e' f' fs' g' af' a' bf' b'>4")
```

```
abjad> chordtools.divide_chord_by_chromatic_pitch_number(chord, pitchtools.NamedChromaticPitch(6)
(Chord("<fs' g' af' a' bf' b'>4"), Chord("<c' cs' d' ef' e' f'>4")))
```

Input *chord* may be a note, rest or chord but not a skip.

Zero-length parts return rests, length-one parts return notes and other parts return chords.

Return pair of newly constructed leaves. Changed in version 2.0: renamed `chordtools.split_by_pitch_number()` to `chordtools.divide_chord_by_chromatic_pitch_number()`

chordtools.divide_chord_by_diatonic_pitch_number

```
abjad.tools.chordtools.divide_chord_by_diatonic_pitch_number(chord,
pitch=NamedChromaticPitch('b'))
```

New in version 1.1. Divide *chord* by diatonic *pitch* number:

```
abjad> chord = Chord(range(12), Duration(1, 4))
```

```
abjad> chord
Chord("<c' cs' d' ef' e' f' fs' g' af' a' bf' b'>4")
```

```
abjad> chordtools.divide_chord_by_diatonic_pitch_number(chord, pitchtools.NamedChromaticPitch(6)
(Chord("<f' fs' g' af' a' bf' b'>4"), Chord("<c' cs' d' ef' e'>4")))
```

Input *chord* may be a note, rest or chord but not a skip.

Zero-length parts return as rests, length-one parts return as notes and other parts return as chords.

Return pair of newly constructed leaves. Changed in version 2.0: renamed `chordtools.split_by_altitude()` to `chordtools.divide_chord_by_diatonic_pitch_number()`.

chordtools.get_arithmetic_mean_of_chord

```
abjad.tools.chordtools.get_arithmetic_mean_of_chord(chord)
New in version 2.0. Get arithmetic mean of chromatic pitch number of pitches in chord:
```

```
abjad> chord = Chord("<g' c' ' e' ' >4")
```

```
abjad> chordtools.get_arithmetic_mean_of_chord(chord)
11.666666666666666
```

Return none when *chord* is empty:

```
abjad> chord = Chord("< >4")
```

```
abjad> chordtools.get_arithmetic_mean_of_chord(chord) is None
True
```

Return number or none.

chordtools.get_note_head_from_chord_by_pitch

```
abjad.tools.chordtools.get_note_head_from_chord_by_pitch(chord, pitch)
New in version 2.0. Get note head from chord by pitch:
```



```
abjad> chord = Chord("<c' d' b'>4")

abjad> chordtools.get_note_head_from_chord_by_pitch(chord, 14)
NoteHead("d' ")
```

Raise missing note head error when *chord* contains no note head with pitch equal to *pitch*.

Raise extra note head error when *chord* contains more than one note head with pitch equal to *pitch*. Changed in version 2.0: renamed `chordtools.get_note_head()` to `chordtools.get_note_head_from_chord_by_pitch()`.

chordtools.iterate_chords_backward_in_expr

`abjad.tools.chordtools.iterate_chords_backward_in_expr(expr, start=0, stop=None)`
New in version 2.0. Iterate chords backward in *expr*:

```
abjad> staff = Staff("<e' g' c'>8 a'8 r8 <d' f' b'>8 r2")

abjad> f(staff)
\new Staff {
  <e' g' c'>8
  a'8
  r8
  <d' f' b'>8
  r2
}

abjad> for chord in chordtools.iterate_chords_backward_in_expr(staff):
...     chord
Chord("<d' f' b'>8")
Chord("<e' g' c'>8")
```

Ignore threads.

Return generator.

chordtools.iterate_chords_forward_in_expr

`abjad.tools.chordtools.iterate_chords_forward_in_expr(expr, start=0, stop=None)`
New in version 2.0. Iterate chords forward in *expr*:

```
abjad> staff = Staff("<e' g' c'>8 a'8 r8 <d' f' b'>8 r2")

abjad> f(staff)
\new Staff {
  <e' g' c'>8
  a'8
  r8
  <d' f' b'>8
  r2
}

abjad> for chord in chordtools.iterate_chords_forward_in_expr(staff):
...     chord
Chord("<e' g' c'>8")
Chord("<d' f' b'>8")
```

Ignore threads.

Return generator.

chordtools.yield_all_subchords_of_chord

`abjad.tools.chordtools.yield_all_subchords_of_chord(chord)`

New in version 2.0. Yield all subchords of *chord* in binary string order:

```
abjad> chord = Chord("<c' d' af' a'>4")

abjad> for subchord in chordtools.yield_all_subchords_of_chord(chord):
...     subchord
...
Rest('r4')
Note("c'4")
Note("d'4")
Chord("<c' d'>4")
Note("af'4")
Chord("<c' af'>4")
Chord("<d' af'>4")
Chord("<c' d' af'>4")
Note("a'4")
Chord("<c' a'>4")
Chord("<d' a'>4")
Chord("<c' d' a'>4")
Chord("<af' a'>4")
Chord("<c' af' a'>4")
Chord("<d' af' a'>4")
Chord("<c' d' af' a'>4")
```

Include empty chord as rest.

Return generator of newly constructed leaves. Changed in version 2.0: renamed `chordtools.subchords()` to `chordtools.yield_all_subchords_of_chord()`.

chordtools.yield_groups_of_chords_in_sequence

`abjad.tools.chordtools.yield_groups_of_chords_in_sequence(sequence)`

New in version 2.0. Yield groups of chords in *sequence*:

```
abjad> staff = Staff("c'8 d'8 r8 r8 <e' g'>8 <f' a'>8 g'8 a'8 r8 r8 <b' d''>8 <c'' e''>8")

abjad> f(staff)
\new Staff {
    c'8
    d'8
    r8
    r8
    <e' g'>8
    <f' a'>8
    g'8
    a'8
    r8
    r8
    <b' d''>8
```

```

        <c' ' e''>8
    }

```

```

abjad> for chord in chordtools.yield_groups_of_chords_in_sequence(staff):
...     chord
...
(Chord("<e' g'>8"), Chord("<f' a'>8"))
(Chord("<b' d''>8"), Chord("<c' ' e''>8"))

```

Return generator.

componenttools

componenttools.all_are_components

abjad.tools.componenttools.**all_are_components** (*expr*, *klasses=None*)

New in version 1.1. True when elements in *expr* are all components:

```

abjad> componenttools.all_are_components(3 * Note("c'4"))
True

```

Otherwise false:

```

abjad> componenttools.all_are_components(['foo', 'bar'])
False

```

True when elements in *expr* are all *klasses*:

```

abjad> componenttools.all_are_components(3 * Note("c'4"), classes = Note)
True

```

Otherwise false:

```

abjad> componenttools.all_are_components(['foo', 'bar'], classes = Note)
False

```

Return boolean.

componenttools.all_are_components_in_same_parent

abjad.tools.componenttools.**all_are_components_in_same_parent** (*expr*,
klasses=None, al-
low_orphans=True)

New in version 1.1. True when elements in *expr* are all components in same parent. Otherwise false:

```

abjad> staff = Staff(notetools.make_notes([12, 14, 16], [(1, 8)]))
abjad> componenttools.all_are_components_in_same_parent(staff.leaves)
True

```

True when elements in *expr* are all *klasses* in same parent. Otherwise false:

```

abjad> staff = Staff(notetools.make_notes([12, 14, 16], [(1, 8)]))
abjad> componenttools.all_are_components_in_same_parent(staff.leaves, classes = (Note, ))
True

```

Return boolean.

componenttools.all_are_components_in_same_score

`abjad.tools.componenttools.all_are_components_in_same_score` (*expr*,
klasses=None, al-
low_orphans=True)

New in version 1.1. True when elements in *expr* are all components in same score. Otherwise false:

```
abjad> score = Score([Staff("c'8 d'8 e'8")])
abjad> componenttools.all_are_components_in_same_score(score.leaves)
True
```

True when elements in *expr* are all *klasses* in same score. Otherwise false:

```
abjad> score = Score([Staff("c'8 d'8 e'8")])
abjad> componenttools.all_are_components_in_same_score(score.leaves, classes = (Note, ))
True
```

Return boolean.

componenttools.all_are_components_in_same_thread

`abjad.tools.componenttools.all_are_components_in_same_thread` (*expr*,
klasses=None, al-
low_orphans=True)

New in version 1.1. True when elements in *expr* are all components in same thread. Otherwise false:

```
abjad> voice = Voice("c'8 d'8 e'8")
abjad> componenttools.all_are_components_in_same_thread(voice.leaves)
True
```

True when elements in *expr* are all *klasses* in same thread. Otherwise false:

```
abjad> voice = Voice("c'8 d'8 e'8")
abjad> componenttools.all_are_components_in_same_thread(voice.leaves, classes = Note)
True
```

Return boolean.

componenttools.all_are_components_scalable_by_multiplier

`abjad.tools.componenttools.all_are_components_scalable_by_multiplier` (*components*,
multi-
plier)

New in version 1.1. True when *components* are all scalable by *multiplier*:

```
abjad> components = [Note(0, (1, 8))]
abjad> componenttools.all_are_components_scalable_by_multiplier(components, Duration(3, 2))
True
```

Otherwise false:

```
abjad> components = [Note(0, (1, 8))]
abjad> componenttools.all_are_components_scalable_by_multiplier(components, Duration(2, 3))
False
```

Return boolean. Changed in version 2.0: renamed `durtools.are_scalable()` to `componenttools.all_are_components_scalable_by_multiplier()`.

componenttools.all_are_contiguous_components

`abjad.tools.componenttools.all_are_contiguous_components` (*expr*, *classes=None*, *allow_orphans=True*)

New in version 1.1. True when elements in *expr* are all contiguous components. Otherwise false:

```
abjad> staff = Staff("c'8 d'8 e'8")
abjad> componenttools.all_are_contiguous_components(staff.leaves)
True
```

True when elements in *expr* are all contiguous *classes*. Otherwise false:

```
abjad> staff = Staff("c'8 d'8 e'8")
abjad> componenttools.all_are_contiguous_components(staff.leaves, classes = Note)
True
```

Return boolean.

componenttools.all_are_contiguous_components_in_same_parent

`abjad.tools.componenttools.all_are_contiguous_components_in_same_parent` (*expr*, *classes=None*, *allow_orphans=True*)

New in version 1.1. True when elements in *expr* are all contiguous components in same parent. Otherwise false:

```
abjad> staff = Staff("c'8 d'8 e'8")
abjad> componenttools.all_are_contiguous_components_in_same_parent(staff.leaves)
True
```

True when elements in *expr* are all contiguous *classes* in same parent. Otherwise false:

```
abjad> staff = Staff("c'8 d'8 e'8")
abjad> componenttools.all_are_contiguous_components_in_same_parent(staff.leaves, classes = Note)
True
```

Return boolean.

componenttools.all_are_contiguous_components_in_same_score

`abjad.tools.componenttools.all_are_contiguous_components_in_same_score` (*expr*, *classes=None*, *allow_orphans=True*)

New in version 1.1. True when elements in *expr* are all contiguous components in same score. Otherwise false:

```
abjad> score = Score([Staff("c'8 d'8 e'8")])
abjad> componenttools.all_are_contiguous_components_in_same_score(score.leaves)
True
```

True when elements in *expr* are all contiguous *classes* in same score. Otherwise false:

```
abjad> score = Score([Staff("c'8 d'8 e'8")])
abjad> componenttools.all_are_contiguous_components_in_same_score(score.leaves, classes = Note)
True
```

Return boolean.

componenttools.all_are_contiguous_components_in_same_thread

`abjad.tools.componenttools.all_are_contiguous_components_in_same_thread(expr,
klassen=None,
al-
low_orphans=True)`

New in version 1.1. True when elements in *expr* are all contiguous components in same thread. Otherwise false:

```
abjad> staff = Staff("c'8 d'8 e'8")
abjad> componenttools.all_are_contiguous_components_in_same_thread(staff.leaves)
True
```

True when elements in *expr* are all contiguous *klassen* in same thread. Otherwise false:

```
abjad> staff = Staff("c'8 d'8 e'8")
abjad> componenttools.all_are_contiguous_components_in_same_thread(staff.leaves, klassen = Note)
True
```

Return boolean.

componenttools.all_are_orphan_components

`abjad.tools.componenttools.all_are_orphan_components(expr)`
 New in version 2.0. True when *expr* is an iterable of zero or more orphan components.
 Otherwise false.

componenttools.all_are_thread_contiguous_components

`abjad.tools.componenttools.all_are_thread_contiguous_components(expr,
klassen=None,
al-
low_orphans=True)`

New in version 1.1. True when elements in *expr* are all thread-contiguous components:

```
t = Voice(notetools.make_repeated_notes(4))
t.insert(2, Voice(notetools.make_repeated_notes(2)))
Container(t[:2])
Container(t[-2:])
pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
```

```
\new Voice {
  {
    c'8
    d'8
  }
  \new Voice {
    e'8
    f'8
  }
  {
    g'8
    a'8
  }
}
```

```
assert _are_thread_contiguous_components(t[0:1] + t[-1:])
```

```
assert _are_thread_contiguous_components(t[0][:] + t[-1:])
assert _are_thread_contiguous_components(t[0:1] + t[-1][:])
assert _are_thread_contiguous_components(t[0][:] + t[-1][:])
```

Return boolean.

Thread-contiguous components are, by definition, spannable.

componenttools.component_to_parentage_signature

abjad.tools.componenttools.**component_to_parentage_signature**(*component*)

New in version 1.1. Change *component* to parentage signature:

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> staff = Staff([tuplet])
abjad> note = staff.leaves[0]
abjad> print componenttools.component_to_parentage_signature(note)
    root: Staff-... (...)
    score:
staffgroup:
    staff: Staff-...
    voice:
    self: Note-...
```

Return parentage signature.

componenttools.component_to_pitch_and_rhythm_skeleton

abjad.tools.componenttools.**component_to_pitch_and_rhythm_skeleton**(*component*)

New in version 2.0. Change *component* to pitch and rhythm skeleton:

```
abjad> tuplet = Tuplet(Fraction(3, 4), "c'8 d'8 e'8 f'8")
abjad> measure = Measure((6, 16), [tuplet])
abjad> staff = Staff([measure])
abjad> score = Score(staff * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)

abjad> skeleton = componenttools.component_to_pitch_and_rhythm_skeleton(score)
abjad> print skeleton
Score([
    Staff([
        Measure((6, 16), [
            Tuplet(Fraction(3, 4), [
                Note(('c', 4), Duration(1, 8)),
                Note(('d', 4), Duration(1, 8)),
                Note(('e', 4), Duration(1, 8)),
                Note(('f', 4), Duration(1, 8))
            ])
        ])
    ]),
    Staff([
        Measure((6, 16), [
            Tuplet(Fraction(3, 4), [
                Note(('g', 4), Duration(1, 8)),
                Note(('a', 4), Duration(1, 8)),
                Note(('b', 4), Duration(1, 8)),
                Note(('c', 5), Duration(1, 8))
            ])
        ])
    ])
])
```

```

    ])
  ])
])

abjad> new = eval(skeleton)
abjad> new
Score<<2>>

abjad> f(new)
\new Score <<
  \new Staff {
    {
      \time 6/16
      \fraction \times 3/4 {
        c'8
        d'8
        e'8
        f'8
      }
    }
  }
  \new Staff {
    {
      \time 6/16
      \fraction \times 3/4 {
        g'8
        a'8
        b'8
        c''8
      }
    }
  }
>>

```

Return string.

componenttools.component_to_score_depth

`abjad.tools.componenttools.component_to_score_depth(component)`

New in version 1.1. Change *component* to score depth:

```

abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> staff = Staff([tuplet])
abjad> componenttools.component_to_score_depth(staff.leaves[0])
2

```

Return nonnegative integer.

componenttools.component_to_score_index

`abjad.tools.componenttools.component_to_score_index(component)`

New in version 2.0. Change *component* to score index:

```

abjad> staff_1 = Staff(tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_repeated_n
abjad> staff_2 = Staff([tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_repeated_
abjad> score = Score([staff_1, staff_2])

```



```

abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)
abjad> f(score)
\new Score <<
  \new Staff {
    \times 2/3 {
      c'8
      d'8
      e'8
    }
    \times 2/3 {
      f'8
      g'8
      a'8
    }
  }
  \new Staff {
    \times 2/3 {
      b'8
      c''8
      d''8
    }
  }
>>

abjad> for leaf in score.leaves:
...     leaf, componenttools.component_to_score_index(leaf)
...
(Note("c'8"), (0, 0, 0))
(Note("d'8"), (0, 0, 1))
(Note("e'8"), (0, 0, 2))
(Note("f'8"), (0, 1, 0))
(Note("g'8"), (0, 1, 1))
(Note("a'8"), (0, 1, 2))
(Note("b'8"), (1, 0, 0))
(Note("c''8"), (1, 0, 1))
(Note("d''8"), (1, 0, 2))

```

Return tuple of zero or more nonnegative integers.

componenttools.component_to_score_root

abjad.tools.componenttools.**component_to_score_root**(*component*)

New in version 1.1. Change *component* to score root:

```

abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> staff = Staff([tuplet])
abjad> note = staff.leaves[0]
abjad> componenttools.component_to_score_root(note)
Staff{1}

```

Return score root.

componenttools.component_to_tuplet_depth

abjad.tools.componenttools.**component_to_tuplet_depth**(*component*)

New in version 1.1. Change *component* to tuplet depth:

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> staff = Staff([tuplet])
abjad> note = staff.leaves[0]
```

```
abjad> componenttools.component_to_tuplet_depth(note)
1
```

```
abjad> componenttools.component_to_tuplet_depth(tuplet)
0
```

```
abjad> componenttools.component_to_tuplet_depth(staff)
0
```

Return nonnegative integer.

componenttools.copy_and_partition_governed_component_subtree_by_leaf_counts

`abjad.tools.componenttools.copy_and_partition_governed_component_subtree_by_leaf_counts` (componenttools) *leaf_counts*

New in version 1.1. Copy *container* and partition copy according to *leaf_counts*:

```
abjad> voice = Voice(tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_repeated_note("c'8 d'8 e'8")))
abjad> spannertools.BeamSpanner(voice[0].leaves)
BeamSpanner(c'8, c'8, c'8)
abjad> spannertools.BeamSpanner(voice[1].leaves)
BeamSpanner(c'8, c'8, c'8)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voice)
abjad> f(voice)
\new Voice {
  \times 2/3 {
    c'8 [
      d'8
      e'8 ]
  }
  \times 2/3 {
    f'8 [
      g'8
      a'8 ]
  }
}
```

```
abjad> first, second, third = componenttools.copy_and_partition_governed_component_subtree_by_leaf_counts(voice)
```

```
abjad> f(first)
\new Voice {
  \times 2/3 {
    c'8 [ ]
  }
}
```

```
abjad> f(second)
\new Voice {
  \times 2/3 {
    d'8 [
      e'8 ]
  }
}
```

```

abjad> f(third)
\new Voice {
  \times 2/3 {
    f'8 [
      g'8
      a'8 ]
  }
}

```

Set *leaf_counts* to an iterable of zero or more positive integers.

Return a list of parts equal in length to that of *leaf_counts*. Changed in version 2.0: renamed `clonewp.by_leaf_counts_with_parentage()` to `componenttools.copy_and_partition_governed_component_subtree_by_leaf_counts()`.

componenttools.copy_components_and_covered_spanners

```

abjad.tools.componenttools.copy_components_and_covered_spanners(components,
                                                                    n=1)

```

New in version 1.1. Clone *components* and covered spanners.

The *components* must be thread-contiguous.

Covered spanners are those spanners that cover *components*.

The steps taken in this function are as follows. Withdraw *components* from crossing spanners. Preserve spanners that *components* cover. Deep copy *components*. Reapply crossing spanners to source *components*. Return copied components with covered spanners.

```

abjad> voice = Voice(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voi
abjad> beam = spannertools.BeamSpanner(voice.leaves[:4])
abjad> f(voice)
\new Voice {
  {
    \time 2/8
    c'8 [
      d'8
    ]
  }
  {
    \time 2/8
    e'8
    f'8 ]
  }
  {
    \time 2/8
    g'8
    a'8
  }
}

```

```

abjad> result = componenttools.copy_components_and_covered_spanners(voice.leaves)
abjad> result
(Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8"), Note("g'8"), Note("a'8"))

```

```

abjad> new_voice = Voice(result)
abjad> f(new_voice)
\new Voice {

```

```

        c'8 [
        d'8
        e'8
        f'8 ]
        g'8
        a'8
    }

```

```

abjad> voice.leaves[0] is new_voice.leaves[0]
False

```

Clone *components* a total of *n* times.

```

abjad> result = componenttools.copy_components_and_covered_spanners(voice.leaves[:2], n = 3)
abjad> result
(Note("c'8"), Note("d'8"), Note("c'8"), Note("d'8"), Note("c'8"), Note("d'8"))

abjad> new_voice = Voice(result)
abjad> f(new_voice)
\new Voice {
    c'8
    d'8
    c'8
    d'8
    c'8
    d'8
}

```

Changed in version 2.0: renamed `clone.covered()` to `componenttools.copy_components_and_covered_spanners()`.
 in version 2.0: renamed `componenttools.clone_components_and_covered_spanners()` to `componenttools.copy_components_and_covered_spanners()`.

componenttools.copy_components_and_fracture_crossing_spanners

abjad.tools.componenttools.**copy_components_and_fracture_crossing_spanners** (*components*, *n=1*)

New in version 1.1. Clone *components* and fracture crossing spanners.

The *components* must be thread-contiguous.

The steps this function takes are as follows. Deep copy *components*. Deep copy spanners that attach to any component in *components*. Fracture spanners that attach to components not in *components*. Return Python list of copied components.

```

abjad> voice = Voice(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voice)
abjad> beam = spannertools.BeamSpanner(voice.leaves[:4])
abjad> f(voice)
\new Voice {
    {
        \time 2/8
        c'8 [
        d'8
    }
    {
        \time 2/8
        e'8
        f'8 ]
    }
}

```

```

    }
    {
        \time 2/8
        g'8
        a'8
    }
}

abjad> result = componenttools.copy_components_and_fracture_crossing_spanners(voice.leaves[2:4])
abjad> result
(Note("e'8"), Note("f'8"))

abjad> new_voice = Voice(result)
abjad> f(new_voice)
\new Voice {
    e'8 [
    f'8 ]
}

abjad> voice.leaves[2] is new_voice.leaves[0]
False

```

Clone *components* a total of *n* times.

```

abjad> result = componenttools.copy_components_and_fracture_crossing_spanners(voice.leaves[2:4],
abjad> result
(Note("e'8"), Note("f'8"), Note("e'8"), Note("f'8"), Note("e'8"), Note("f'8"))

abjad> new_voice = Voice(result)
abjad> f(new_voice)
\new Voice {
    e'8 [
    f'8 ]
    e'8 [
    f'8 ]
    e'8 [
    f'8 ]
}

```

Changed in version 2.0: renamed `clone.fracture()` to `componenttools.copy_components_and_fracture_cr`
in version 2.0: renamed `componenttools.clone_components_and_fracture_crossing_spanners()`
to `componenttools.copy_components_and_fracture_crossing_spanners()`.

componenttools.copy_components_and_immediate_parent_of_first_component

`abjad.tools.componenttools.copy_components_and_immediate_parent_of_first_component` (*component*
New in version 1.1. Clone *components* and immediate parent of first component.

The *components* must be thread-contiguous.

Return in newly created container equal to type of first element in *components*.

If the parent of the first element in *components* is a tuplet then insure that the tuplet multiplier of the function output equals the tuplet multiplier of the parent of the first element in *components*.

```

abjad> voice = Voice(tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_repeated_not
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voi
abjad> beam = spannertools.BeamSpanner(voice.leaves[:4])

```

```

abjad> f(voice)
\new Voice {
  \times 2/3 {
    c'8 [
      d'8
      e'8
    ]
  }
  \times 2/3 {
    f'8 ]
    g'8
    a'8
  }
  \times 2/3 {
    b'8
    c''8
    d''8
  }
}
abjad> new_tuplet = componenttools.copy_components_and_immediate_parent_of_first_component(voice)
abjad> new_tuplet
FixedDurationTuplet(1/6, [c'8, d'8])
abjad> f(new_tuplet)
\times 2/3 {
  c'8 [
    d'8 ]
}

```

Parent-contiguity is not required. Thread-contiguous *components* suffice.

```

abjad> new_tuplet = componenttools.copy_components_and_immediate_parent_of_first_component(voice)
abjad> new_tuplet
FixedDurationTuplet(5/12, [c'8, d'8, e'8, f'8, g'8])
abjad> f(new_tuplet)
\times 2/3 {
  c'8 [
    d'8
    e'8
    f'8 ]
  g'8
}

```

Note: this function copies only the *immediate parent* of the first element in *components*. This function ignores any further parentage of *components* above the immediate parent of *components*.

Todo

this function should (but does not) copy marks that attach to *components* and to the immediate parent of the first component; extend function to do so.

Changed in version 2.0: renamed `clonewp.with_parent()` to `componenttools.copy_components_and_immediate_parent_of_first_component()`. Changed in version 2.0: renamed `componenttools.clone_components_and_immediate_parent_of_first_component()` to `componenttools.copy_components_and_immediate_parent_of_first_component()`.

componenttools.copy_components_and_remove_all_spanners

`abjad.tools.componenttools.copy_components_and_remove_all_spanners` (*components*,
n=1)

New in version 1.1. Clone *components* and remove all spanners.

The *components* must be thread-contiguous.

The steps taken by this function are as follows. Withdraw all components at any level in *components* from spanners. Deep copy unspanned components in *components*. Reapply spanners to all components at any level in *components*.

```
abjad> voice = Voice(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voi
abjad> beam = spannertools.BeamSpanner(voice.leaves[:4])
abjad> f(voice)
\new Voice {
  {
    \time 2/8
    c'8 [
    d'8
  }
  {
    \time 2/8
    e'8
    f'8 ]
  }
  {
    \time 2/8
    g'8
    a'8
  }
}

abjad> result = componenttools.copy_components_and_remove_all_spanners(voice.leaves[2:4])
abjad> result
(Note("e'8"), Note("f'8"))

abjad> new_voice = Voice(result)
abjad> f(new_voice)
\new Voice {
  e'8
  f'8
}

abjad> voice.leaves[2] is new_voice.leaves[0]
False

Clone components a total of n times.

abjad> result = componenttools.copy_components_and_remove_all_spanners(voice.leaves[2:4], n = 3)
abjad> result
(Note("e'8"), Note("f'8"), Note("e'8"), Note("f'8"), Note("e'8"), Note("f'8"))

abjad> new_voice = Voice(result)
abjad> f(new_voice)
\new Voice {
  e'8
  f'8
  e'8
```

```
f'8
e'8
f'8
}
```

Changed in version 2.0: renamed `clone.unspan()` to `componenttools.copy_components_and_remove_all_sp`
in version 2.0: renamed `componenttools.clone_components_and_remove_all_spanners()`
to `componenttools.copy_components_and_remove_all_spanners()`.

componenttools.copy_governed_component_subtree_by_leaf_range

`abjad.tools.componenttools.copy_governed_component_subtree_by_leaf_range` (*component*,
start=0,
stop=None)

New in version 1.1. Clone governed *component* subtree by leaf range.

Governed subtree means *component* together with children of *component*.

Leaf range refers to the sequential parentage of *component* from *start* leaf index to *stop* leaf index:

```
abjad> t = Staff([Voice(tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_repeated_
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> f(t)
\new Staff {
  \new Voice {
    \times 2/3 {
      c'8
      d'8
      e'8
    }
    \times 2/3 {
      f'8
      g'8
      a'8
    }
  }
}
```

```
abjad> u = componenttools.copy_governed_component_subtree_by_leaf_range(t, 1, 5)
abjad> f(u)
\new Staff {
  \new Voice {
    \times 2/3 {
      d'8
      e'8
    }
    \times 2/3 {
      f'8
      g'8
    }
  }
}
```

Clone sequential containers in leaves' parentage up to the first parallel container in leaves' parentage.

Trim and shrink cloned containers as necessary.

When *stop* is none copy all leaves from *start* forward. Changed in ver-
sion 2.0: renamed `clonewp.by_leaf_range_with_parentage()` to

`componenttools.copy_governed_component_subtree_by_leaf_range()`. Changed in version 2.0: renamed `componenttools.clone_governed_component_subtree_by_leaf_range()` to `componenttools.copy_governed_component_subtree_by_leaf_range()`.

`componenttools.copy_governed_component_subtree_from_prolated_offset_to`

`abjad.tools.componenttools.copy_governed_component_subtree_from_prolated_offset_to(component, start=0, stop=None)`

New in version 1.1. Clone governed *component* subtree from *start* prolated duration to *stop* prolated duration.

Governed subtree refers to *component* together with the children of *component*:

```
abjad> voice = Voice(notetools.make_repeated_notes(2))
abjad> voice.append(tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_repeated_note(2)))
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voice)
abjad> f(voice)
\new Voice {
  c'8
  d'8
  \times 2/3 {
    e'8
    f'8
    g'8
  }
}

abjad> new = componenttools.copy_governed_component_subtree_from_prolated_offset_to(voice, (0, 8))
abjad> f(new)
\new Voice {
  c'8
  d'8
  \times 2/3 {
    e'8
    f'16
  }
}
```

Raise contiguity error if asked to slice a parallel container.

```
abjad> staff = Staff(Voice("c'8 d'8") * 2)
abjad> staff.is_parallel = True
abjad> f(staff)
\new Staff <<
\new Voice {
  c'8
  d'8
}
\new Voice {
  c'8
  d'8
}
>>
```

Raise contiguity error when attempting to copy fleaves from parallel container.

But note that cases with 0 = *start* work correctly:

```
abjad> new = componenttools.copy_governed_component_subtree_from_prolated_offset_to(voice, (0, 8))
abjad> f(new)
\new Voice {
    c'8
}
```

Cases with $0 < \text{start}$ do not work correctly:

```
abjad> new = componenttools.copy_governed_component_subtree_from_prolated_offset_to(voice, (1, 8))
abjad> f(new)
\new Voice {
    c'8
    d'8
}
```

Create ad hoc tuplets as required:

```
abjad> voice = Voice([Note("c'4")])
abjad> new = componenttools.copy_governed_component_subtree_from_prolated_offset_to(voice, 0, (1, 8))
abjad> f(new)
\new Voice {
    \times 2/3 {
        c'8
    }
}
```

Function does NOT clone parentage of *component* when *component* is a leaf:

```
abjad> voice = Voice([Note("c'4")])
abjad> new_leaf = componenttools.copy_governed_component_subtree_from_prolated_offset_to(voice[0], 0, (1, 8))
abjad> f(new_leaf)
c'8
abjad> new_leaf._parentage.parent is None
True
```

Return (untrimmed_copy, first_dif, second_dif). Changed in version 2.0: renamed `componenttools.clone_governed_component_subtree_from_prolated_duration_to()` to `componenttools.copy_governed_component_subtree_from_prolated_offset_to()`.

componenttools.cut_component_at_prolated_duration

`abjad.tools.componenttools.cut_component_at_prolated_duration(component, prolated_duration)`

New in version 2.0. Cut *component* at dotted *prolated_duration*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> componenttools.cut_component_at_prolated_duration(staff, Duration(1, 32))
abjad> f(staff)
\new Staff {
    c'16. [
    d'8
    e'8
    f'8 ]
}
```

Cut *component* at tied *prolated_duration*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> componenttools.cut_component_at_prolated_duration(staff, Duration(3, 64))
abjad> f(staff)
\new Staff {
    c'16 [ ~
    c'64
    d'8
    e'8
    f'8 ]
}

```

Cut *component* at nonbinary *prolated_duration*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> componenttools.cut_component_at_prolated_duration(staff, Duration(1, 24))
abjad> f(staff)
\new Staff {
    \times 2/3 {
        c'8 [
    ]
    d'8
    e'8
    f'8 ]
}

```

Return `none`.

`componenttools.extend_in_parent_of_component_and_do_not_grow_spanners`

`abjad.tools.componenttools.extend_in_parent_of_component_and_do_not_grow_spanners` (*component*, *com-*
po-
nents)

New in version 1.1. Extend *components* in parent of *component* and do not grow spanners:

```

abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8")]
abjad> t = Voice("c'8 d'8 e'8")
abjad> spannertools.BeamSpanner(t[:])
BeamSpanner(c'8, d'8, e'8)
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8")]
abjad> componenttools.extend_in_parent_of_component_and_do_not_grow_spanners(t[-1], notes)
[Note("e'8"), Note("c'8"), Note("d'8"), Note("e'8")]

abjad> print t.format
\new Voice {
    c'8 [
    d'8
    e'8 ]
    c'8
    d'8
    e'8
}

```

Return list of *component* and *components*. Changed in version 2.0: renamed `extend_in_parent()` to `extend_in_parent_of_component_and_do_not_grow_spanners()`.

`componenttools.extend_in_parent_of_component_and_grow_spanners`

`abjad.tools.componenttools.extend_in_parent_of_component_and_grow_spanners` (*component*, *new_components*)

New in version 2.0. Extend *new_components* in parent of *component* and grow spanners:

```
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8")]
abjad> voice = Voice(notes)
abjad> spannertools.BeamSpanner(voice[:])
BeamSpanner(c'8, d'8, e'8)

abjad> f(voice)
\new Voice {
  c'8 [
  d'8
  e'8 ]
}

abjad> new_components = [Note("c'8"), Note("d'8"), Note("e'8")]
abjad> componenttools.extend_in_parent_of_component_and_grow_spanners(voice.leaves[-1], new_comp
[Note("e'8"), Note("c'8"), Note("d'8"), Note("e'8")]

abjad> f(voice)
\new Voice {
  c'8 [
  d'8
  e'8
  c'8
  d'8
  e'8 ]
}
```

Return *component* and *new_components* together in list.

`componenttools.extend_left_in_parent_of_component_and_do_not_grow_spanners`

`abjad.tools.componenttools.extend_left_in_parent_of_component_and_do_not_grow_spanners` (*comp*, *com-*, *po-*, *nents*)

New in version 1.1. Extend *components* left in parent of *component* and do not grow spanners:

```
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8")]
abjad> t = Voice(notes)
abjad> spannertools.BeamSpanner(t[:])
BeamSpanner(c'8, d'8, e'8)
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8")]
abjad> componenttools.extend_left_in_parent_of_component_and_do_not_grow_spanners(t[0], notes)
[Note("c'8"), Note("d'8"), Note("e'8"), Note("c'8")]

abjad> print t.format
\new Voice {
  c'8
  d'8
```

```
e'8
c'8 [
d'8
e'8 ]
}
```

Return *components* and *component* together in newly created list. Changed in version 2.0: renamed `extend_left_in_parent()` to `extend_left_in_parent_of_component_and_do_not_grow_spanners()`.

componenttools.extend_left_in_parent_of_component_and_grow_spanners

`abjad.tools.componenttools.extend_left_in_parent_of_component_and_grow_spanners` (*component*, *new_components*)

New in version 2.0. Extend *new_components* left in parent of *component* and grow spanners:

```
abjad> voice = Voice("c'8 d'8 e'8")
abjad> spannertools.BeamSpanner(voice[:])
BeamSpanner(c'8, d'8, e'8)

abjad> f(voice)
\new Voice {
  c'8 [
  d'8
  e'8 ]
}

abjad> new_components = 3 * Note(0, (1, 16))
abjad> componenttools.extend_left_in_parent_of_component_and_grow_spanners(voice[0], new_components)
[Note("c'16"), Note("c'16"), Note("c'16"), Note("c'8")]

abjad> f(voice)
\new Voice {
  c'16 [
  c'16
  c'16
  c'8
  d'8
  e'8 ]
}
```

Return *new_components* and *component* together in newly created list. Changed in version 2.0: renamed `splice_left()` to `componenttools.extend_left_in_parent_of_component_and_grow_spanners()`.

componenttools.get_component_start_offset

`abjad.tools.componenttools.get_component_start_offset` (*component*)

New in version 1.1. Get *component* start offset:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> f(staff)
\new Staff {
  c'8
  d'8
  e'8
  f'8
}
```

```
abjad> componenttools.get_component_start_offset(staff[1])
Offset(1, 8)
```

Return nonnegative fraction.

componenttools.get_component_start_offset_in_seconds

`abjad.tools.componenttools.get_component_start_offset_in_seconds(component)`

New in version 1.1. Get *component* start offset in seconds:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> score = Score([staff])
abjad> contexttools.TempoMark(Duration(1, 4), 52)(score)
TempoMark(4, 52)(Score<<1>>)
abjad> f(score) # doctest: +SKIP
\new Score <<
  \new Staff {
    \tempo 4=52
    c'8
    d'8
    e'8
    f'8
  }
>>

abjad> componenttools.get_component_start_offset_in_seconds(score.leaves[1])
Offset(15, 26)
```

Return nonnegative fraction.

componenttools.get_component_stop_offset

`abjad.tools.componenttools.get_component_stop_offset(component)`

New in version 1.1. Get *component* stop offset:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> f(staff)
\new Staff {
  c'8
  d'8
  e'8
  f'8
}

abjad> componenttools.get_component_stop_offset(staff[1])
Offset(1, 4)
```

Return positive fraction.

componenttools.get_component_stop_offset_in_seconds

`abjad.tools.componenttools.get_component_stop_offset_in_seconds(component)`

New in version 1.1. Get *component* stop offset in seconds:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> score = Score([staff])
abjad> contexttools.TempoMark(Duration(1, 4), 52)(score)
TempoMark(4, 52)(Score<<1>>)
abjad> f(score) # doctest: +SKIP
\new Score <<
  \new Staff {
    \tempo 4=52
    c'8
    d'8
    e'8
    f'8
  }
>>

abjad> componenttools.get_component_stop_offset_in_seconds(score.leaves[1])
Offset(15, 13)

```

Return positive fraction.

componenttools.get_first_component_in_expr_with_name

`abjad.tools.componenttools.get_first_component_in_expr_with_name(expr, name)`
 New in version 1.1. Get first component in *expr* with *name*:

```

abjad> flute_staff = Staff("c'8 d'8 e'8 f'8")
abjad> flute_staff.name = 'Flute'
abjad> violin_staff = Staff("c'8 d'8 e'8 f'8")
abjad> violin_staff.name = 'Violin'
abjad> staff_group = scoretools.StaffGroup([flute_staff, violin_staff])
abjad> score = Score([staff_group])

abjad> componenttools.get_first_component_in_expr_with_name(score, 'Violin')
Staff-"Violin"{4}

```

Changed in version 2.0: Function returns first component found. Function previously returned tuple of all components found. Changed in version 2.0: renamed `scoretools.find()` to `componenttools.get_first_component_in_expr_with_name()`. Changed in version 2.0: Removed *klass* and *context* keywords. Function operates only on component name.

componenttools.get_first_component_with_name_in_improper_parentage_of_component

`abjad.tools.componenttools.get_first_component_with_name_in_improper_parentage_of_component`

New in version 2.0. Get first component with *name* in improper parentage of *component*:

```

abjad> score = Score([Staff("c'4 d'4 e'4 f'4")])
abjad> score.name = 'The Score'

abjad> f(score)
\context Score = "The Score" <<
  \new Staff {
    c'4
    d'4
    e'4
    f'4
  }
>>

```

```

    }
>>

abjad> leaf = score.leaves[0]

abjad> componenttools.get_first_component_with_name_in_improper_parentage_of_component(leaf, 'The
Score-"The Score"<<1>>

abjad> componenttools.get_first_component_with_name_in_improper_parentage_of_component(leaf, 'fo
True

```

Return component or none.

componenttools.get_first_component_with_name_in_proper_parentage_of_component

abjad.tools.componenttools.get_first_component_with_name_in_proper_parentage_of_component(*component*, *name*)

New in version 2.0. Get first component with *name* in proper parentage of *component*:

```

abjad> score = Score([Staff("c'4 d'4 e'4 f'4")])
abjad> score.name = 'The Score'

abjad> f(score)
\context Score = "The Score" <<
  \new Staff {
    c'4
    d'4
    e'4
    f'4
  }
>>

abjad> leaf = score.leaves[0]

abjad> componenttools.get_first_component_with_name_in_proper_parentage_of_component(leaf, 'The
Score-"The Score"<<1>>

abjad> componenttools.get_first_component_with_name_in_proper_parentage_of_component(leaf, 'foo'
True

```

Return component or none.

componenttools.get_first_instance_of_class_in_improper_parentage_of_component

abjad.tools.componenttools.get_first_instance_of_class_in_improper_parentage_of_component(*component*, *klass*)

New in version 2.0. Get first instance of *klass* in improper parentage of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> componenttools.get_first_instance_of_klass_in_improper_parentage_of_component(staff[0], N
Note("c'8")

```

Return component or none.

componenttools.get_first_instance_of_klass_in_proper_parentage_of_component

`abjad.tools.componenttools.get_first_instance_of_klass_in_proper_parentage_of_component` (*component*, *klass*)

New in version 1.1. Get first instance of *klass* in proper parentage of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> componenttools.get_first_instance_of_klass_in_proper_parentage_of_component(staff[0], Staff)
Staff{4}
```

Return component or none. Changed in version 2.0: renamed `componenttools.get_first()` to `componenttools.get_first_instance_of_klass_in_proper_parentage_of_component()`.

componenttools.get_improper_parentage_of_component

`abjad.tools.componenttools.get_improper_parentage_of_component` (*component*)

New in version 1.1. Get improper parentage of *component*:

```
abjad> tuplet = Tuplet(Fraction(2, 3), "c'8 d'8 e'8")
abjad> staff = Staff([tuplet])
abjad> note = staff.leaves[0]

abjad> componenttools.get_improper_parentage_of_component(note)
(Note("c'8"), Tuplet(2/3, [c'8, d'8, e'8]), Staff{1})
```

Return tuple of zero or more components.

componenttools.get_likely_multiplier_of_components

`abjad.tools.componenttools.get_likely_multiplier_of_components` (*components*)

New in version 2.0. Get likely multiplier of *components*:

```
abjad> staff = Staff("c'8.. d'8.. e'8.. f'8..")
abjad> f(staff)
\new Staff {
    c'8..
    d'8..
    e'8..
    f'8..
}
abjad> componenttools.get_likely_multiplier_of_components(staff[:])
Duration(7, 4)
```

Return 1 when no multiplier is likely:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
}
abjad> componenttools.get_likely_multiplier_of_components(staff[:])
Duration(1, 1)
```

Return none when more than one multiplier is likely:

```

abjad> staff = Staff(notetools.make_notes([0, 2, 4, 5], [(3, 16), (7, 32)]))
abjad> f(staff)
\new Staff {
    c'8.
    d'8..
    e'8.
    f'8..
}
abjad> componenttools.get_likely_multiplier_of_components(staff[:]) is None
True

```

Return fraction or none.

componenttools.get_nth_component_in_expr

`abjad.tools.componenttools.get_nth_component_in_expr(expr, classes, n=0)`

New in version 1.1. Get component *n* in the *classes* of *expr*:

```

abjad> staff = Staff([ ])
abjad> durations = [Duration(n, 16) for n in range(1, 5)]
abjad> notes = notetools.make_notes([0, 2, 4, 5], durations)
abjad> rests = resttools.make_rests(durations)
abjad> from abjad.tools import seqtools
abjad> leaves = seqtools.interlace_sequences(notes, rests)
abjad> staff.extend(leaves)

abjad> print staff.format
\new Staff {
    c'16
    r16
    d'8
    r8
    e'8.
    r8.
    f'4
    r4
}

abjad> for n in range(4):
...     componenttools.get_nth_component_in_expr(staff, Note, n)
...
Note("c'16")
Note("d'8")
Note("e'8.")
Note("f'4")

abjad> for n in range(4):
...     componenttools.get_nth_component_in_expr(staff, Rest, n)
...
Rest('r16')
Rest('r8')
Rest('r8.')
Rest('r4')

abjad> componenttools.get_nth_component_in_expr(staff, Staff)
Staff{8}

```

Read right-to-left for negative values of *n*:

```

abjad> for n in range(3, -1, -1):
...     componenttools.get_nth_component_in_expr(staff, Rest, n)
...
Rest('r4')
Rest('r8.')
Rest('r8')
Rest('r16')

```

Return component or none. Changed in version 2.0: renamed `iterate.get_nth()` to `componenttools.get_nth_component_in_expr()`.

componenttools.get_nth_namesake_from_component

`abjad.tools.componenttools.get_nth_namesake_from_component(component, n)`

New in version 2.0. For positive *n*, return namesake to the right of *component*:

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> componenttools.get_nth_namesake_from_component(t[1], 1)
Note("e'8")

```

For negative *n*, return namesake to the left of *component*:

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> componenttools.get_nth_namesake_from_component(t[1], -1)
Note("c'8")

```

Return *component* when *n* is zero:

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> componenttools.get_nth_namesake_from_component(t[1], 0)
Note("d'8")

```

Return component or none.

componenttools.get_parent_and_start_stop_indices_of_components

`abjad.tools.componenttools.get_parent_and_start_stop_indices_of_components(components)`

New in version 1.1. Get parent and start / stop indices of *components*:

```

abjad> t = Staff("c'8 d'8 e'8 f'8 g'8 a'8")
abjad> print t.format
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
}

abjad> leaves = t[-2:]
abjad> leaves
[Note("g'8"), Note("a'8")]
abjad> componenttools.get_parent_and_start_stop_indices_of_components(leaves)
(Staff{6}, 4, 5)

```

Return parent / start index / stop index triple. Return parent as component or none. Return nonnegative integer start index and nonnegative index stop index. Changed in version 2.0: renamed `componenttools.get_with_indices()` to `componenttools.get_parent_and_start_stop_indices_of_components()`.

`componenttools.get_proper_parentage_of_component`

`abjad.tools.componenttools.get_proper_parentage_of_component(component)`

New in version 1.1. Get proper parentage of *component*:

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> staff = Staff([tuplet])
abjad> note = staff.leaves[0]
abjad> componenttools.get_proper_parentage_of_component(note)
(FixedDurationTuplet(1/4, [c'8, d'8, e'8]), Staff{1})
```

Return tuple of zero or more components.

`componenttools.is_beamable_component`

`abjad.tools.componenttools.is_beamable_component(expr)`

New in version 1.1. True when *expr* is a beamable component. Otherwise false:

```
abjad> componenttools.is_beamable_component(Note(13, (1, 16)))
True
```

Return boolean.

`componenttools.is_orphan_component`

`abjad.tools.componenttools.is_orphan_component(component)`

New in version 1.1. True when *component* has no parent. Otherwise false:

```
abjad> note = Note("c'4")
abjad> componenttools.is_orphan_component(note)
True
```

Return boolean. Changed in version 2.0: renamed `componenttools.component_is_orphan()` to `componenttools.is_orphan_component()`.

`componenttools.is_well_formed_component`

`abjad.tools.componenttools.is_well_formed_component(expr, allow_empty_containers=True)`

New in version 1.1. True when *component* is well formed:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> componenttools.is_well_formed_component(staff)
True
```

Otherwise false:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> staff[1].written_duration = Duration(1, 4)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, d'4, e'8, f'8)
abjad> componenttools.is_well_formed_component(staff)
False

```

Beamed quarter notes are not well formed.

Return boolean.

componenttools.iterate_components_backward_in_expr

```

abjad.tools.componenttools.iterate_components_backward_in_expr(expr,
                                                              klass=<class
                                                              'ab-
jad.tools.componenttools._Component._
start=0,
stop=None)

```

New in version 1.1. Iterate components backward in *expr*:

```

abjad> staff = Staff(tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_repeated_not
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(sta
abjad> f(staff)
\new Staff {
    \times 2/3 {
        c'8
        d'8
        e'8
    }
    \times 2/3 {
        f'8
        g'8
        a'8
    }
}
abjad> for x in componenttools.iterate_components_backward_in_expr(staff, Note):
...     x
...
Note("a'8")
Note("g'8")
Note("f'8")
Note("e'8")
Note("d'8")
Note("c'8")

```

New in version 2.0: optional *start* and *stop* keyword parameters.

```

abjad> for x in componenttools.iterate_components_backward_in_expr(staff, Note, start = 0, stop
...     x
...
Note("a'8")
Note("g'8")
Note("f'8")
Note("e'8")

abjad> for x in componenttools.iterate_components_backward_in_expr(staff, Note, start = 4):
...     x

```

```
...
Note("d'8")
Note("c'8")
```

```
abjad> for x in componenttools.iterate_components_backward_in_expr(staff, Note, start = 4, stop
...      x
...
Note("d'8")
Note("c'8")
```

This function is thread-agnostic. Changed in version 2.0: renamed `iterate.backwards()` to `componenttools.iterate_components_backward_in_expr()`.

componenttools.iterate_components_depth_first

```
abjad.tools.componenttools.iterate_components_depth_first(component,
                                                           capped=True,
                                                           unique=True,      for-
                                                           bid=None,         direc-
                                                           tion='left')
```

New in version 1.1. Iterate components depth-first from *component*.

Todo

Add usage examples.

Changed in version 2.0: renamed `iterate.depth_first()` to `componenttools.iterate_components_depth_first()`.

componenttools.iterate_components_forward_in_expr

```
abjad.tools.componenttools.iterate_components_forward_in_expr(expr,
                                                               klass=<class 'ab-
                                                               jad.tools.componenttools._Component._Co
                                                               start=0,
                                                               stop=None)
```

New in version 1.1. Iterate components forward in *expr*:

```
abjad> container = Container(Voice(notetools.make_repeated_notes(2)) * 2)
abjad> container.is_parallel = True
abjad> container[0].name = 'voice 1'
abjad> container[1].name = 'vocie 2'
abjad> staff = Staff(container * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(sta
abjad> f(staff)
\new Staff {
  <<
    \context Voice = "voice 1" {
      c'8
      d'8
    }
    \context Voice = "vocie 2" {
      e'8
      f'8
    }
  }
```

```

>>
<<
    \context Voice = "voice 1" {
        g'8
        a'8
    }
    \context Voice = "voice 2" {
        b'8
        c''8
    }
>>
}
abjad> for x in componenttools.iterate_components_forward_in_expr(staff, Note):
...     x
...
Note("c'8")
Note("d'8")
Note("e'8")
Note("f'8")
Note("g'8")
Note("a'8")
Note("b'8")
Note("c''8")

```

New in version 2.0: optional *start* and *stop* keyword parameters.

```

abjad> for x in componenttools.iterate_components_forward_in_expr(staff, Note, start = 0, stop = 4):
...     x
...
Note("c'8")
Note("d'8")
Note("e'8")
Note("f'8")

abjad> for x in componenttools.iterate_components_forward_in_expr(staff, Note, start = 4):
...     x
...
Note("g'8")
Note("a'8")
Note("b'8")
Note("c''8")

abjad> for x in componenttools.iterate_components_forward_in_expr(staff, Note, start = 4, stop = 6):
...     x
...
Note("g'8")
Note("a'8")

```

This function is thread-agnostic. Changed in version 2.0: renamed `iterate.naive()` to `componenttools.iterate_components_forward_in_expr()`. Changed in version 2.0: *klass* now defaults to `_Component`.

`componenttools.iterate_namesakes_backward_from_component`

```

abjad.tools.componenttools.iterate_namesakes_backward_from_component(component,
                                                                    start=0,
                                                                    stop=None)

```

New in version 2.0. Iterate namesakes backward from *component*:

```

abjad> container = Container(Staff(notetools.make_repeated_notes(2)) * 2)
abjad> container.is_parallel = True
abjad> container[0].name = 'staff 1'
abjad> container[1].name = 'staff 2'
abjad> score = Score([ ])
abjad> score.is_parallel = False
abjad> score.extend(container * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)
abjad> print score.format
\new Score {
  <<
    \context Staff = "staff 1" {
      c'8
      d'8
    }
    \context Staff = "staff 2" {
      e'8
      f'8
    }
  >>
  <<
    \context Staff = "staff 1" {
      g'8
      a'8
    }
    \context Staff = "staff 2" {
      b'8
      c''8
    }
  >>
}

abjad> for staff in componenttools.iterate_namesakes_backward_from_component(score[-1][0]):
...     print staff.format
...
\context Staff = "staff 1" {
  g'8
  a'8
}
\context Staff = "staff 1" {
  c'8
  d'8
}

```

Return generator.

componenttools.iterate_namesakes_forward_from_component

`abjad.tools.componenttools.iterate_namesakes_forward_from_component` (*component*,
start=0,
stop=None)

New in version 1.1. Iterate namesakes forward from *component*:

```

abjad> container = Container(Staff(notetools.make_repeated_notes(2)) * 2)
abjad> container.is_parallel = True
abjad> container[0].name = 'staff 1'
abjad> container[1].name = 'staff 2'

```



```

abjad> score = Score([ ])
abjad> score.is_parallel = False
abjad> score.extend(container * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)
abjad> print score.format
\new Score {
  <<
    \context Staff = "staff 1" {
      c'8
      d'8
    }
    \context Staff = "staff 2" {
      e'8
      f'8
    }
  >>
  <<
    \context Staff = "staff 1" {
      g'8
      a'8
    }
    \context Staff = "staff 2" {
      b'8
      c''8
    }
  >>
}

abjad> for staff in componenttools.iterate_namesakes_forward_from_component(score[0][0]):
...     print staff.format
...
\context Staff = "staff 1" {
  c'8
  d'8
}
\context Staff = "staff 1" {
  g'8
  a'8
}

```

Return generator.

componenttools.iterate_timeline_backward_from_component

`abjad.tools.componenttools.iterate_timeline_backward_from_component` (*expr*, *klass=None*)

New in version 2.0. Iterate timeline backward from *component*:

```

abjad> score = Score([ ])
abjad> score.append(Staff(notetools.make_repeated_notes(4, Duration(1, 4))))
abjad> score.append(Staff(notetools.make_repeated_notes(4)))
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)
abjad> f(score)
\new Score <<
  \new Staff {
    c'4
    d'4
    e'4
  }

```

```

        f'4
    }
    \new Staff {
        g'8
        a'8
        b'8
        c''8
    }
>>
abjad> for leaf in componenttools.iterate_timeline_backward_from_component(score[1][2]):
...     leaf
...
Note("b'8")
Note("c'4")
Note("a'8")
Note("g'8")

```

Yield components sorted backward by score offset stop time.

Iterate leaves when *klass* is none.

Todo

optimize to avoid behind-the-scenes full-score traversal.

componenttools.iterate_timeline_backward_in_expr

`abjad.tools.componenttools.iterate_timeline_backward_in_expr(expr, klass=None)`

New in version 2.0. Iterate timeline backward in *expr*:

```

abjad> score = Score([ ])
abjad> score.append(Staff(notetools.make_repeated_notes(4, Duration(1, 4))))
abjad> score.append(Staff(notetools.make_repeated_notes(4)))
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)
abjad> f(score)
\new Score <<
    \new Staff {
        c'4
        d'4
        e'4
        f'4
    }
    \new Staff {
        g'8
        a'8
        b'8
        c''8
    }
>>
abjad> for leaf in componenttools.iterate_timeline_backward_in_expr(score):
...     leaf
...
Note("f'4")
Note("e'4")
Note("d'4")
Note("c''8")
Note("b'8")

```

Iterate leaves when *klass* is none.

optimize to avoid behind-the-scenes full-score traversal.

[illegible]

```
abjad> score = Score([ ])
abjad> score.append(Staff(notetools.make_repeated_notes(4, Duration(1, 4))))
abjad> score.append(Staff(notetools.make_repeated_notes(4)))
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)
abjad> f(score)
\new Score <<
  \new Staff {
    c'4
    d'4
    e'4
    f'4
  }
  \new Staff {
    g'8
    a'8
    b'8
    c''8
  }
>>
abjad> for leaf in componenttools.iterate_timeline_forward_from_component(score[1][2]):
...     leaf
...
Note("b'8")
Note("c''8")
Note("e'4")
Note("f'4")
```

optimize to avoid behind-the-scenes full-score traversal.

57.1. Abjad API

```

abjad> score = Score([ ])
abjad> score.append(Staff(notetools.make_repeated_notes(4, Duration(1, 4))))
abjad> score.append(Staff(notetools.make_repeated_notes(4)))
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)
abjad> f(score)
\new Score <<
  \new Staff {
    c'4
    d'4
    e'4
    f'4
  }
  \new Staff {
    g'8
    a'8
    b'8
    c''8
  }
>>
abjad> for leaf in componenttools.iterate_timeline_forward_in_expr(score):
...     leaf
...
Note("c'4")
Note("g'8")
Note("a'8")
Note("d'4")
Note("b'8")
Note("c''8")
Note("e'4")
Note("f'4")

```

Iterate leaves when *klass* is none.

Todo

optimize to avoid behind-the-scenes full-score traversal.

componenttools.list_badly_formed_components_in_expr

abjad.tools.componenttools.**list_badly_formed_components_in_expr**(*expr*, *allow_empty_containers=True*)

New in version 1.1. List badly formed components in *expr*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> staff[1].written_duration = Duration(1, 4)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, d'4, e'8, f'8)
abjad> f(staff)
\new Staff {
  c'8 [
  d'4
  e'8
  f'8 ]
}
abjad> componenttools.list_badly_formed_components_in_expr(staff)
[Note("d'4")]

```

Beamed quarter notes are not well formed.

Return newly created list of zero or more components.

`componenttools.list_improper_contents_of_component_that_cross_prolated_offset`

`abjad.tools.componenttools.list_improper_contents_of_component_that_cross_prolated_offset (`

New in version 2.0. List improper contents of *component* that cross *prolated_offset*:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
}
```

Examples refer to the score above.

No components cross prolated offset 0:

```
abjad> componenttools.list_improper_contents_of_component_that_cross_prolated_offset(staff, 0)
[]
```

Staff, measure and leaf cross prolated offset 1/16:

```
abjad> componenttools.list_improper_contents_of_component_that_cross_prolated_offset(staff, Duration(1/16))
[Staff{2}, Measure(2/8, [c'8, d'8]), Note("c'8")]
```

Staff and measure cross prolated offset 1/8:

```
abjad> componenttools.list_improper_contents_of_component_that_cross_prolated_offset(staff, Duration(1/8))
[Staff{2}, Measure(2/8, [c'8, d'8])]
```

Staff crosses prolated offset 1/4:

```
abjad> componenttools.list_improper_contents_of_component_that_cross_prolated_offset(staff, Duration(1/4))
[Staff{2}]
```

No components cross prolated offset 99:

```
abjad> componenttools.list_improper_contents_of_component_that_cross_prolated_offset(staff, 99)
[]
```

Return list.

componenttools.list_leftmost_components_with_prolated_duration_at_most

abjad.tools.componenttools.**list_leftmost_components_with_prolated_duration_at_most** (*component*, *pro-
lated_duration*)

New in version 2.0. List leftmost components in *component* with prolated duration at most *prolated_duration*.

Return tuple of components[:i] together with the prolated duration of components[:i]:

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> componenttools.list_leftmost_components_with_prolated_duration_at_most(voice[:], Duration(
([Note("c'8"), Note("d'8")], Duration(1, 4))
```

Maximize i such that the prolated duration of components[:i] is no greater than *prolated_duration*.

Input *components* must be thread-contiguous.

Todo

```
implement componenttools.list_leftmost_components_with_prolated_duration_at_least().
```

Todo

```
implement componenttools.list_rightmost_components_with_prolated_duration_at_most().
```

Todo

```
implement componenttools.list_rightmost_components_with_prolated_duration_at_least().
```

Changed in version 2.0: renamed componenttools.get_le_duration_prolated() to componenttools.list_leftmost_components_with_prolated_duration_at_most().

componenttools.move_component_subtree_to_right_in_immediate_parent_of_component

abjad.tools.componenttools.**move_component_subtree_to_right_in_immediate_parent_of_component** (*component*)

New in version 2.0. Move *component* subtree to right in immediate parent of *component*:

```
abjad> t = Voice("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(t[:2])
BeamSpanner(c'8, d'8)
abjad> spannertools.BeamSpanner(t[2:])
BeamSpanner(e'8, f'8)
abjad> f(t)
\new Voice {
  c'8 [
  d'8 ]
  e'8 [
  f'8 ]
}

abjad> componenttools.move_component_subtree_to_right_in_immediate_parent_of_component(t[1])
abjad> f(t)
\new Voice {
  c'8 [
  e'8 ]
  d'8 [
```

```
f'8 ]
}
```

Return none.

Todo

add `n = 1` keyword to generalize flipped distance.

Todo

make `componenttools.move_component_subtree_to_right_in_immediate_parent_of_component()` work when spanners attach to children of component:

```
abjad> voice = Voice(tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_repeated_not
abjad> spannertools.BeamSpanner(voice.leaves[:4])
BeamSpanner(c'8, c'8, c'8, c'8)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voi
abjad> componenttools.move_component_subtree_to_right_in_immediate_parent_of_component(voice[0])
abjad> f(voice)
\new Voice {
  \times 2/3 {
    f'8 ]
    g'8
    a'8
  }
  \times 2/3 {
    c'8 [
    d'8
    e'8
  }
}
abjad> componenttools.is_well_formed_component(voice)
False
```

Preserve spanners. Changed in version 2.0: renamed `componenttools.flip()` to `componenttools.move_component_subtree_to_right_in_immediate_parent_of_component()`.

componenttools.move_parentage_and_spanners_from_components_to_components

`abjad.tools.componenttools.move_parentage_and_spanners_from_components_to_components` (*donors, re-cip-i-ents*)

New in version 1.1. Move parentage and spanners from *donors* to *recipients*.

Give everything from donors to recipients. Almost exactly the same as container `setitem` logic. This helper works with orphan donors. Container `setitem` logic can not work with orphan donors. Return donors. Changed in version 2.0: renamed `scoretools.bequeath()` to `componenttools.move_parentage_and_spanners_from_components_to_components()`.

`componenttools.number_is_between_prolated_start_and_stop_offsets_of_component`

`abjad.tools.componenttools.number_is_between_prolated_start_and_stop_offsets_of_component` (*component*, *timepoint*)

New in version 2.0. True when *timepoint* is within the prolated duration of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> leaf = staff.leaves[0]
abjad> componenttools.number_is_between_prolated_start_and_stop_offsets_of_component (Duration(1, 2), leaf)
True
abjad> componenttools.number_is_between_prolated_start_and_stop_offsets_of_component (Duration(1, 2), staff)
True
```

Otherwise false:

```
abjad> componenttools.number_is_between_prolated_start_and_stop_offsets_of_component (Duration(1, 2), staff)
False
```

Return boolean.

`componenttools.number_is_between_start_and_stop_offsets_of_component_in_seconds`

`abjad.tools.componenttools.number_is_between_start_and_stop_offsets_of_component_in_seconds` (*component*, *timepoint*)

New in version 2.0. True when *timepoint* is within the duration of *component* in seconds:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.TempoMark(Duration(1, 2), 60, target_context = Staff)(staff)
TempoMark(2, 60)(Staff{4})

abjad> leaf = staff.leaves[0]
abjad> componenttools.number_is_between_start_and_stop_offsets_of_component_in_seconds(0.1, leaf)
True
abjad> componenttools.number_is_between_start_and_stop_offsets_of_component_in_seconds(0.333, leaf)
True
```

Otherwise false:

```
abjad> componenttools.number_is_between_start_and_stop_offsets_of_component_in_seconds(0.5, staff)
False
```

Return boolean.

`componenttools.partition_components_cyclically_by_durations_in_seconds_exactly_with_overhang`

`abjad.tools.componenttools.partition_components_cyclically_by_durations_in_seconds_exactly_with_overhang` (*components*, *durations*, *overhang*)

New in version 1.1. Partition *components* cyclically by *durations_in_seconds* exactly with overhang.

componenttools.partition_components_cyclically_by_durations_in_seconds_exactly_without_overhang

`abjad.tools.componenttools.partition_components_cyclically_by_durations_in_seconds_exactly_`

New in version 1.1. Partition *components* cyclically by *durations_in_seconds* exactly without overhang.

componenttools.partition_components_cyclically_by_durations_in_seconds_ge_with_overhang

`abjad.tools.componenttools.partition_components_cyclically_by_durations_in_seconds_ge_with_`

New in version 1.1. Partition *components* cyclically by durations in seconds greater than or equal to *durations_in_seconds*, with overhang.

componenttools.partition_components_cyclically_by_durations_in_seconds_ge_without_overhang

`abjad.tools.componenttools.partition_components_cyclically_by_durations_in_seconds_ge_with_`

New in version 1.1. Partition *components* cyclically by durations in seconds that are equal to or just greater than *durations_in_seconds*, without overhang.

componenttools.partition_components_cyclically_by_durations_in_seconds_le_with_overhang

`abjad.tools.componenttools.partition_components_cyclically_by_durations_in_seconds_le_with_`

New in version 1.1. Partition *components* cyclically by durations in seconds equal to or just less than *durations_in_seconds*, with overhang.

componenttools.partition_components_cyclically_by_durations_in_seconds_le_without_overhang

`abjad.tools.componenttools.partition_components_cyclically_by_durations_in_seconds_le_with_`

New in version 1.1. Partition *components* cyclically by durations in seconds that equal or are just less than *durations_in_seconds*, without overhang

componenttools.partition_components_cyclically_by_prolated_durations_exactly_with_overhang

`abjad.tools.componenttools.partition_components_cyclically_by_prolated_durations_exactly_w_`

New in version 1.1. Partition *components* cyclically by *prolated_durations* exactly, with overhang.

componenttools.partition_components_cyclically_by_prolated_durations_exactly_without_overhang

```
abjad.tools.componenttools.partition_components_cyclically_by_prolated_durations_exactly_w
```

New in version 1.1. Partition *components* cyclically by *prolated_durations* exactly, without overhang.

componenttools.partition_components_cyclically_by_prolated_durations_ge_with_overhang

```
abjad.tools.componenttools.partition_components_cyclically_by_prolated_durations_ge_with_ov
```

New in version 1.1. Partition *components* cyclically by *prolated_durations* greater than or equal, with overhang:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 4)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> f(staff)
\new Staff {
  {
    \time 2/8
    c'8
    d'8
  }
  {
    \time 2/8
    e'8
    f'8
  }
  {
    \time 2/8
    g'8
    a'8
  }
  {
    \time 2/8
    b'8
    c''8
  }
}
```

```
abjad> groups = componenttools.partition_components_cyclically_by_prolated_durations_ge_with_ov
```

```
abjad> for group in groups:
...     group
...
[Note("c'8"), Note("d'8")]
[Note("e'8")]
[Note("f'8"), Note("g'8")]
[Note("a'8")]
[Note("b'8"), Note("c''8")]
```

Return list of lists.

Note: function works not just on components but on any durated objects including spanners.

componenttools.partition_components_cyclically_by_prolated_durations_ge_without_overhang

```
abjad.tools.componenttools.partition_components_cyclically_by_prolated_durations_ge_without
```

New in version 1.1. Partition *components* cyclically by prolated durations that equal or are just greater than *prolated_durations*, without overhang.

componenttools.partition_components_cyclically_by_prolated_durations_le_with_overhang

```
abjad.tools.componenttools.partition_components_cyclically_by_prolated_durations_le_with_ov
```

New in version 1.1. Partition *components* cyclically by prolated duration that equal or are just less than *prolated_durations*, with overhang.

componenttools.partition_components_cyclically_by_prolated_durations_le_without_overhang

```
abjad.tools.componenttools.partition_components_cyclically_by_prolated_durations_le_without
```

New in version 1.1. Partition *components* cyclically by prolated durations that equal or are just less than *prolated_durations*, without overhang.

componenttools.partition_components_once_by_durations_in_seconds_exactly_with_overhang

```
abjad.tools.componenttools.partition_components_once_by_durations_in_seconds_exactly_with_c
```

New in version 1.1. Partition *components* once by *durations_in_seconds* exactly, with overhang.

componenttools.partition_components_once_by_durations_in_seconds_exactly_without_overhang

```
abjad.tools.componenttools.partition_components_once_by_durations_in_seconds_exactly_witho
```

New in version 1.1. Partition *components* cyclically by *durations_in_seconds* exactly, without overhang.

componenttools.partition_components_once_by_durations_in_seconds_ge_with_overhang

```
abjad.tools.componenttools.partition_components_once_by_durations_in_seconds_ge_with_overha
```

New in version 1.1. Partition *components* once by durations in seconds that equal or are just greater than *durations_in_seconds*, with overhang.

`componenttools.partition_components_once_by_durations_in_seconds_ge_without_overhang`

`abjad.tools.componenttools.partition_components_once_by_durations_in_seconds_ge_without_overhang`

New in version 1.1. Partition *components* once by durations in seconds that equal or are just greater than *durations_in_seconds*, without overhang.

`componenttools.partition_components_once_by_durations_in_seconds_le_with_overhang`

`abjad.tools.componenttools.partition_components_once_by_durations_in_seconds_le_with_overhang`

New in version 1.1. Partition *components* once by durations in seconds that equal or are just less than *durations_in_seconds*, with overhang.

`componenttools.partition_components_once_by_durations_in_seconds_le_without_overhang`

`abjad.tools.componenttools.partition_components_once_by_durations_in_seconds_le_without_overhang`

New in version 1.1. Partition *components* once by durations in seconds that equal or are just less than *durations_in_seconds*, without overhang.

`componenttools.partition_components_once_by_prolated_durations_exactly_with_overhang`

`abjad.tools.componenttools.partition_components_once_by_prolated_durations_exactly_with_overhang`

New in version 1.1. Partition *components* once by *prolated_durations* exactly, with overhang.

`componenttools.partition_components_once_by_prolated_durations_exactly_without_overhang`

`abjad.tools.componenttools.partition_components_once_by_prolated_durations_exactly_without_overhang`

New in version 1.1. Partition *components* once by *prolated_durations* exactly, without overhang.

`componenttools.partition_components_once_by_prolated_durations_ge_with_overhang`

`abjad.tools.componenttools.partition_components_once_by_prolated_durations_ge_with_overhang`

New in version 1.1. Partition *components* cyclically by prolated durations that equal or are just greater than *prolated_durations*, with overhang.

componenttools.partition_components_once_by_prolated_durations_ge_without_overhang

```
abjad.tools.componenttools.partition_components_once_by_prolated_durations_ge_without_overhang
```

New in version 1.1. Partition *components* cyclically by prolated durations that equal or are just greater than *prolated_durations*, without overhang.

componenttools.partition_components_once_by_prolated_durations_le_with_overhang

```
abjad.tools.componenttools.partition_components_once_by_prolated_durations_le_with_overhang
```

New in version 1.1. Partition *components* once by prolated durations that equal or are just less than *prolated_durations*, with overhang.

componenttools.partition_components_once_by_prolated_durations_le_without_overhang

```
abjad.tools.componenttools.partition_components_once_by_prolated_durations_le_without_overhang
```

New in version 1.1. Partition *components* once by prolated durations that equal or are just less than *prolated_durations*, without overhang.

componenttools.remove_component_subtree_from_score_and_spanners

```
abjad.tools.componenttools.remove_component_subtree_from_score_and_spanners(components)
```

New in version 1.1. Remove arbitrary *components* and children of *components* from score and spanners:

```
abjad> score = Voice(notetools.make_repeated_notes(2))
abjad> score.insert(1, Container(notetools.make_repeated_notes(2)))
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)
abjad> spannertools.BeamSpanner(score.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> spannertools.GlissandoSpanner(score.leaves)
GlissandoSpanner(c'8, d'8, e'8, f'8)
```

```
abjad> f(score)
\new Voice {
  c'8 [ \glissando
  {
    d'8 \glissando
    e'8 \glissando
  }
  f'8 ]
}
```

Examples refer to the score above.

Remove one leaf from score:

```
abjad> componenttools.remove_component_subtree_from_score_and_spanners(score.leaves[1:2]) # doct
(Note(d', 8),)
```

```
abjad> f(score) # doctest: +SKIP
\new Voice {
    c'8 [ \glissando
    {
        e'8 \glissando
    }
    f'8 ]
}
```

Remove contiguous leaves from score:

```
abjad> result = componenttools.remove_component_subtree_from_score_and_spanners(score.leaves[:2]
(Note(c', 8), Note(d', 8))
```

```
abjad> f(score) # doctest: +SKIP
\new Voice {
    {
        e'8 [ \glissando
    }
    f'8 ]
}
```

Remove noncontiguous leaves from score:

```
abjad> componenttools.remove_component_subtree_from_score_and_spanners([score.leaves[0], score.l
[Note(c', 8), Note(e', 8)]
```

```
abjad> f(score) # doctest: +SKIP
\new Voice {
    {
        d'8 [ \glissando
    }
    f'8 ]
}
```

Remove container from score:

```
abjad> result = componenttools.remove_component_subtree_from_score_and_spanners(score[1:2])
abjad> result # doctest: +SKIP
[{d'8, e'8}]
```

```
abjad> f(score) # doctest: +SKIP
\new Voice {
    c'8 [ \glissando
    f'8 ]
}
```

Withdraw *components* and children of *components* from spanners.

Return either tuple or list of *components* and children of *components*.

Todo

regularize return value of function.

Note: rename to `componenttools.remove_components_from_score_deep()`.

Changed in version 2.0: renamed `componenttools.detach()` to `componenttools.remove_component_subtree_from_score_and_spanners()`.

`componenttools.replace_components_with_children_of_components`

`abjad.tools.componenttools.replace_components_with_children_of_components(components)`

New in version 1.1. Remove arbitrary *components* from score but retain children of *components* in score:

```
abjad> staff = Staff(Container(notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> spannertools.SlurSpanner(staff[:])
SlurSpanner({c'8, d'8}, {e'8, f'8})
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)

abjad> f(staff)
\new Staff {
    {
        c'8 [ (
        d'8
        ]
    }
    {
        e'8
        f'8 ] )
    }
}

abjad> componenttools.replace_components_with_children_of_components(staff[0:1])
[{}]
```

```
abjad> f(staff)
\new Staff {
    c'8 [ (
    d'8
    {
        e'8
        f'8 ] )
    }
}
```

Return *components*.

Note: should be renamed to `componenttools.remove_components_from_score_shallow()`

Changed in version 2.0: renamed `componenttools.slip()` to `componenttools.replace_components_with_children_of_components()`.

`componenttools.report_component_format_contributions_as_string`

`abjad.tools.componenttools.report_component_format_contributions_as_string(component, verbose=False)`

New in version 1.1. Report *component* format contributions as string.

Set *verbose* to True or False.

componenttools.split_component_at_prolated_duration_and_do_not_fracture_crossing_spanners

abjad.tools.componenttools.split_component_at_prolated_duration_and_do_not_fracture_crossing

New in version 1.1. Split *component* at *prolated_duration* and do not fracture crossing spanners.

Leave spanners untouched.

Return split parts:

```
abjad> t = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> spannertools.BeamSpanner(t[0])
BeamSpanner(|2/8(2)|)
abjad> spannertools.BeamSpanner(t[1])
BeamSpanner(|2/8(2)|)
abjad> spannertools.SlurSpanner(t.leaves)
SlurSpanner(c'8, d'8, e'8, f'8)
abjad> f(t)
\new Staff {
  {
    \time 2/8
    c'8 [ (
    d'8 ]
  }
  {
    \time 2/8
    e'8 [
    f'8 ] )
  }
}

abjad> halves = componenttools.split_component_at_prolated_duration_and_do_not_fracture_crossing
abjad> f(t)
\new Staff {
  {
    \time 2/8
    c'32 [ (
    c'16.
    d'8 ]
  }
  {
    \time 2/8
    e'8 [
    f'8 ] )
  }
}
```

Works on both leaves and containers. Changed in version 2.0: renamed `split.unfractured_at_duration()` to `componenttools.split_component_at_prolated_duration_and_do_not_fracture_crossing`

componenttools.split_component_at_prolated_duration_and_fracture_crossing_spanners

abjad.tools.componenttools.**split_component_at_prolated_duration_and_fracture_crossing_spanners**

New in version 1.1. Split *component* at *prolated_duration* and fracture crossing spanners.

Return split parts:

```
abjad> t = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> spannertools.BeamSpanner(t[0])
BeamSpanner(|2/8(2)|)
abjad> spannertools.BeamSpanner(t[1])
BeamSpanner(|2/8(2)|)
abjad> spannertools.SlurSpanner(t.leaves)
SlurSpanner(c'8, d'8, e'8, f'8)
abjad> f(t)
\new Staff {
  {
    \time 2/8
    c'8 [ (
    d'8 ]
  }
  {
    \time 2/8
    e'8 [
    f'8 ] )
  }
}

halves = componenttools.split_component_at_prolated_duration_and_fracture_crossing_spanners(t.leaves)
\new Staff {
  {
    \time 2/8
    c'32 () [
    c'16. (
    d'8 ]
  }
  {
    \time 2/8
    e'8 [
    f'8 ] )
  }
}
```

Function works on both leaves and containers. Changed in version 2.0: renamed `split.fractured_at_duration()` to `componenttools.split_component_at_prolated_duration_and_fracture_crossing_spanners()`.

componenttools.split_components_cyclically_by_prolated_durations_and_do_not_fracture_crossing_spanners

abjad.tools.componenttools.**split_components_cyclically_by_prolated_durations_and_do_not_fracture_crossing_spanners**

New in version 1.1. Partition *components* cyclically by *prolated durations* and do not fracture spanners:

```

abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> spannertools.BeamSpanner(staff[0])
BeamSpanner(|2/8(2)|)
abjad> spannertools.BeamSpanner(staff[1])
BeamSpanner(|2/8(2)|)
abjad> spannertools.SlurSpanner(staff.leaves)
SlurSpanner(c'8, d'8, e'8, f'8)
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8 [ (
        d'8 ]
    }
    {
        \time 2/8
        e'8 [
        f'8 ] )
    }
}

abjad> durations = [Duration(3, 32)]
abjad> componenttools.split_components_cyclically_by_prolated_durations_and_do_not_fracture_crossings(
[[Note("c'16."), [Note("c'32"), Note("d'16")],
[Note("d'16"), Note("e'32")], [Note("e'16."), [Note("f'16."), [Note("f'32")]]]

abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'16. [ (
        c'32
        d'16
        d'16 ]
    }
    {
        \time 2/8
        e'32 [
        e'16.
        f'16.
        f'32 ] )
    }
}

```

Return list of partitioned components. Changed in version 2.0:
renamed `partition.cyclic_unfractured_by_durations()` to
`componenttools.split_components_cyclically_by_prolated_durations_and_do_not_fracture_crossings()`

componenttools.split_components_cyclically_by_prolated_durations_and_fracture_crossing_spanners

`abjad.tools.componenttools.split_components_cyclically_by_prolated_durations_and_fracture_crossing_spanners`

New in version 1.1. Partition *components* cyclically by prolated *durations* and fracture spanners:

```

abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> spannertools.BeamSpanner(staff[0])
BeamSpanner(|2/8(2)|)
abjad> spannertools.BeamSpanner(staff[1])
BeamSpanner(|2/8(2)|)
abjad> spannertools.SlurSpanner(staff.leaves)
SlurSpanner(c'8, d'8, e'8, f'8)
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8 [ (
        d'8 ]
    }
    {
        \time 2/8
        e'8 [
        f'8 ] )
    }
}

abjad> durations = [Duration(3, 32)]
abjad> componenttools.split_components_cyclically_by_prolated_durations_and_fracture_crossing_spansners(
[[Note("c'16.")], [Note("c'32"), Note("d'16")], [Note("d'16"), Note("e'32")],
[Note("e'16.")], [Note("f'16.")], [Note("f'32")]]

abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'16. ( ) [
        c'32 (
        d'16 )
        d'16 ] (
    }
    {
        \time 2/8
        e'32 ) [
        e'16. (
        f'16. )
        f'32 ] ( )
    }
}

```

Return list of partitioned components. Changed in version 2.0: renamed `partition.cyclic_fractured_by_durations()` to `componenttools.split_components_cyclically_by_durations()`

componenttools.split_components_once_by_prolated_durations_and_do_not_fracture_crossing_spansners

`abjad.tools.componenttools.split_components_once_by_prolated_durations_and_do_not_fracture_crossing_spansners`

New in version 1.1. Split *components* once by prolated *durations* and do not fracture crossing spanners:

```

abjad> t = Staff(Container(notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> spannertools.BeamSpanner(t[0])
BeamSpanner({c'8, d'8})
abjad> spannertools.BeamSpanner(t[1])
BeamSpanner({e'8, f'8})
abjad> spannertools.SlurSpanner(t.leaves)
SlurSpanner(c'8, d'8, e'8, f'8)
abjad> f(t)
\new Staff {
    {
        c'8 [ (
            d'8 ]
        }
    {
        e'8 [
            f'8 ] )
    }
}

abjad> durations = [Duration(1, 32), Duration(3, 32), Duration(5, 32)]
abjad> parts = componenttools.split_components_once_by_prolated_durations_and_do_not_fracture_crossing

abjad> f(t)
\new Staff {
    {
        c'32 [ (
        }
    {
        c'16.
    }
    {
        d'8 ]
    }
    {
        e'8 [
            f'8 ] )
    }
}

```

Changed in version 2.0: renamed `partition.unfractured_by_durations()` to `componenttools.split_components_once_by_prolated_durations_and_do_not_fracture_crossing`

componenttools.split_components_once_by_prolated_durations_and_fracture_crossing

`abjad.tools.componenttools.split_components_once_by_prolated_durations_and_fracture_crossing`

New in version 1.1. Split *components* once by prolated *durations* and fracture crossing spanners:

```

abjad> t = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> spannertools.BeamSpanner(t[0])
BeamSpanner(|2/8(2)|)
abjad> spannertools.BeamSpanner(t[1])

```

```

BeamSpanner(|2/8(2)|)
abjad> spannertools.SlurSpanner(t.leaves)
SlurSpanner(c'8, d'8, e'8, f'8)
abjad> f(t)
\new Staff {
  {
    \time 2/8
    c'8 [ (
    d'8 ]
  }
  {
    \time 2/8
    e'8 [
    f'8 ] )
  }
}

abjad> durations = [Duration(1, 32), Duration(3, 32), Duration(5, 32)]
abjad> parts = componenttools.split_components_once_by_prolated_durations_and_fracture_crossing_
abjad> f(t)
\new Staff {
  {
    \time 1/32
    c'32 [ ] ( )
  }
  {
    \time 3/32
    c'16. [ ] ( )
  }
  {
    \time 4/32
    d'8 [ ] (
  }
  {
    \time 2/8
    e'8 [
    f'8 ] )
  }
}

```

Changed in version 2.0: renamed `partition.fractured_by_durations()` to `componenttools.split_components_once_by_prolated_durations_and_fracture_crossing_spann`

componenttools.sum_duration_of_components_in_seconds

`abjad.tools.componenttools.sum_duration_of_components_in_seconds(components)`

New in version 1.1. Sum duration of *components* in seconds:

```

abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> score = Score([Staff([tuplet])])
abjad> contexttools.TempoMark(Duration(1, 4), 48)(score)
TempoMark(4, 48)(Score<<1>>)
abjad> f(score) # doctest: +SKIP
\new Score <<
  \new Staff {
    \times 2/3 {
      \tempo 4=48

```

```

        c'8
        d'8
        e'8
    }
}
>>

```

```

abjad> componenttools.sum_duration_of_components_in_seconds(tuplet[:])
Duration(5, 4)

```

Changed in version 2.0: renamed `durtools.sum_seconds()` to `componenttools.sum_duration_of_components_in_seconds()`.

componenttools.sum_preprolated_duration_of_components

`abjad.tools.componenttools.sum_preprolated_duration_of_components(components)`
 New in version 1.1. Sum preprolated duration of *components*:

```

abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> componenttools.sum_preprolated_duration_of_components(tuplet[:])
Duration(3, 8)

```

Return zero on empty iterable:

```

abjad> componenttools.sum_preprolated_duration_of_components([ ])
0

```

Raise contiguity error on nonparent-contiguous *components*:

```

abjad> t = Voice(tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_repeated_notes(3
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> f(t)
\new Voice {
  \times 2/3 {
    c'8
    d'8
    e'8
  }
  \times 2/3 {
    f'8
    g'8
    a'8
  }
}
abjad> componenttools.sum_preprolated_duration_of_components(t.leaves)
Duration(3, 4)

```

Changed in version 2.0: renamed `componenttools.get_duration_preprolated()` to `componenttools.sum_preprolated_duration_of_components()`.

componenttools.sum_prolated_duration_of_components

`abjad.tools.componenttools.sum_prolated_duration_of_components(components)`
 New in version 1.1. Sum prolated duration of *components*:

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> f(tuplet)
\times 2/3 {
    c'8
    d'8
    e'8
}
abjad> componenttools.sum_prolated_duration_of_components(tuplet[:])
Duration(1, 4)
```

Changed in version 2.0: renamed `durtools.sum_prolated()` to `componenttools.sum_prolated_duration_of_components()`.

componenttools.tabulate_well_formedness_violations_in_expr

`abjad.tools.componenttools.tabulate_well_formedness_violations_in_expr`(*expr*, *al-*
low_empty_containers=True)

New in version 1.1. Tabulate well-formedness violations in *expr*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> staff[1].written_duration = Duration(1, 4)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, d'4, e'8, f'8)
abjad> f(staff)
\new Staff {
    c'8 [
    d'4
    e'8
    f'8 ]
}

abjad> componenttools.tabulate_well_formedness_violations_in_expr(staff)
1 / 4 beamed quarter note
0 / 1 discontinuous spanner
0 / 5 duplicate i d
0 / 1 empty container
0 / 0 intermarked hairpin
0 / 0 misdurated measure
0 / 0 misfilled measure
0 / 4 mispitched tie
0 / 4 misrepresented flag
0 / 5 missing parent
0 / 0 nested measure
0 / 0 overlapping beam
0 / 0 overlapping glissando
0 / 0 overlapping octavation
0 / 0 short hairpin
```

Beamed quarter notes are not well formed.

componenttools.yield_components_grouped_by_preprolated_duration

`abjad.tools.componenttools.yield_components_grouped_by_preprolated_duration`(*components*)
New in version 2.0. Yield components grouped by preprolated duration:

```
abjad> notes = notetools.make_notes([0], [(1, 4), (1, 4), (1, 8), (1, 16), (1, 16), (1, 16)])
abjad> for x in componenttools.yield_components_grouped_by_preprolated_duration(notes):
...     x
...
(Note("c'4"), Note("c'4"))
(Note("c'8"),)
(Note("c'16"), Note("c'16"), Note("c'16"))
```

Return generator.

componenttools.yield_components_grouped_by_prolated_duration

abjad.tools.componenttools.**yield_components_grouped_by_prolated_duration**(*components*)

New in version 2.0. Yield *component* grouped by prolated duration:

```
abjad> notes = notetools.make_notes([0], [(1, 4), (1, 4), (1, 8), (1, 16), (1, 16), (1, 16)])
abjad> for x in componenttools.yield_components_grouped_by_prolated_duration(notes):
...     x
...
(Note("c'4"), Note("c'4"))
(Note("c'8"),)
(Note("c'16"), Note("c'16"), Note("c'16"))
```

Return generator.

componenttools.yield_groups_of_mixed_klasses_in_sequence

abjad.tools.componenttools.**yield_groups_of_mixed_klasses_in_sequence**(*sequence*,
klasses)

New in version 2.0. Yield groups of mixed *klasses* in *sequence*:

```
abjad> staff = Staff("c'8 d'8 r8 r8 <e' g'>8 <f' a'>8 g'8 a'8 r8 r8 <b' d''>8 <c'' e''>8")

abjad> f(staff)
\new Staff {
    c'8
    d'8
    r8
    r8
    <e' g'>8
    <f' a'>8
    g'8
    a'8
    r8
    r8
    <b' d''>8
    <c'' e''>8
}
```

```
abjad> for group in componenttools.yield_groups_of_mixed_klasses_in_sequence(staff, (Note, Chord)):
...     group
(Note("c'8"), Note("d'8"))
(Chord("<e' g'>8"), Chord("<f' a'>8"), Note("g'8"), Note("a'8"))
(Chord("<b' d''>8"), Chord("<c'' e''>8"))
```

Return generator.

componenttools.yield_topmost_components_grouped_by_type

abjad.tools.componenttools.**yield_topmost_components_grouped_by_type**(*expr*)

New in version 2.0. Yield topmost components in *expr* grouped by type:

```

abjad> staff = Staff(leaftools.make_leaves([0, 2, 4, None, None, 5, 7], [(1, 8)]))
abjad> for x in componenttools.yield_topmost_components_grouped_by_type(staff):
...     x
...
(Note("c'8"), Note("d'8"), Note("e'8"))
(Rest('r8'), Rest('r8'))
(Note("f'8"), Note("g'8"))

```

Return generator.

componenttools.yield_topmost_components_of_klass_grouped_by_type

abjad.tools.componenttools.**yield_topmost_components_of_klass_grouped_by_type**(*expr*,
klass)

New in version 2.0. Yield topmost components of *klass* in *expr* grouped by type:

```

abjad> staff = Staff(leaftools.make_leaves([0, 2, 4, None, None, 5, 7], [(1, 8)]))
abjad> for x in componenttools.yield_topmost_components_of_klass_grouped_by_type(staff, Note):
...     x
...
(Note("c'8"), Note("d'8"), Note("e'8"))
(Note("f'8"), Note("g'8"))

```

Return generator.

containertools

containertools.Cluster

class abjad.tools.containertools.**Cluster**(*music=None*, ***kwargs*)

Bases: abjad.tools.containertools.Container.Container.Container New in version 1.1.

Abjad model of a tone cluster container:

```

abjad> cluster = containertools.Cluster("c'8 d'8 b'8")

abjad> cluster
Cluster(c'8, d'8, b'8)

abjad> f(cluster)
\makeClusters {
    c'8
    d'8
    b'8
}

```

Return cluster object.

containertools.Container

class abjad.tools.containertools.**Container**(*music=None*, ***kwargs*)

Bases: abjad.tools.componenttools._Component._Component._Component

Abjad model of a music container:

```
abjad> container = Container("c'8 d'8 e'8 f'8")
abjad> f(container)
{
    c'8
    d'8
    e'8
    f'8
}
```

Return container object.

append (*component*)

Append *component* to container:

```
abjad> container = Container("c'8 d'8 e'8")
abjad> beam = spannertools.BeamSpanner(container.music)

abjad> f(container)
{
    c'8 [
    d'8
    e'8 ]
}

abjad> container.append(Note("f'8"))

abjad> f(container)
{
    c'8 [
    d'8
    e'8 ]
    f'8
}
```

Return none.

contents_duration

duration_in_seconds

extend (*expr*)

Extend *expr* against container:

```
abjad> container = Container("c'8 d'8 e'8")
abjad> beam = spannertools.BeamSpanner(container.music)

abjad> f(container)
{
    c'8 [
    d'8
    e'8 ]
}

abjad> container.extend([Note("cs'8"), Note("ds'8"), Note("es'8")])

abjad> f(container)
{
    c'8 [
```

```

        d'8
        e'8 ]
        cs'8
        ds'8
        es'8
    }

```

Return none.

index (*component*)

Index *component* in container:

```

abjad> container = Container("c'8 d'8 e'8")

abjad> note = container[-1]
abjad> note
Note("e'8")

abjad> container.index(note)
2

```

Return nonnegative integer.

insert (*i*, *component*)

Insert *component* in container at index *i*:

```

abjad> container = Container("c'8 d'8 e'8")
abjad> beam = spannertools.BeamSpanner(container.music)

abjad> f(container)
{
    c'8 [
    d'8
    e'8 ]
}

abjad> container.insert(1, Note("cs'8"))

abjad> f(container)
{
    c'8 [
    cs'8
    d'8
    e'8 ]
}

```

Return none.

is_parallel

Get parallel container:

```

abjad> container = Container([Voice("c'8 d'8 e'8"), Voice('g4.')]

abjad> f(container)
{
    \new Voice {
        c'8
        d'8
        e'8
    }
}

```

```

        \new Voice {
            g4.
        }
    }

```

```

abjad> container.is_parallel
False

```

Return boolean.

Set parallel container:

```

abjad> container.is_parallel = True

```

```

abjad> f(container)
<<
    \new Voice {
        c'8
        d'8
        e'8
    }
    \new Voice {
        g4.
    }
>>

```

Return none.

leaves

Read-only tuple of leaves in container:

```

abjad> container = Container("c'8 d'8 e'8")

abjad> container.leaves
(Note("c'8"), Note("d'8"), Note("e'8"))

```

Return tuple of zero or more leaves.

music

Read-only tuple of components in container:

```

abjad> container = Container("c'8 d'8 e'8")

abjad> container.music
(Note("c'8"), Note("d'8"), Note("e'8"))

```

Return tuple or zero or more components.

pop (*i*=-1)

Pop component at index *i* from container:

```

abjad> container = Container("c'8 d'8 e'8")
abjad> beam = spannertools.BeamSpanner(container.music)

abjad> f(container)
{
    c'8 [
    d'8
    e'8 ]
}

```

```

abjad> container.pop(-1)
Note("e'8")

abjad> f(container)
{
    c'8 [
    d'8 ]
}

```

Return component.

preprolated_duration

remove (*component*)

Remove *component* from container:

```

abjad> container = Container("c'8 d'8 e'8")
abjad> beam = spannertools.BeamSpanner(container.music)

abjad> f(container)
{
    c'8 [
    d'8
    e'8 ]
}

abjad> note = container[-1]
abjad> note
Note("e'8")

abjad> container.remove(note)

abjad> f(container)
{
    c'8 [
    d'8 ]
}

```

Return none.

containertools.color_contents_of_container

`abjad.tools.containertools.color_contents_of_container` (*container*, *color*)

New in version 2.0. Color contents of *container*:

```

abjad> measure = Measure((2, 8), "c'8 d'8")

abjad> containertools.color_contents_of_container(measure, 'red')
Measure(2/8, [c'8, d'8])

abjad> f(measure)
{
    \override Accidental #'color = #red
    \override Beam #'color = #red
    \override Dots #'color = #red
    \override NoteHead #'color = #red
    \override Rest #'color = #red
    \override Stem #'color = #red
}

```

```

\override TupletBracket #'color = #red
\override TupletNumber #'color = #red
\time 2/8
c'8
d'8
\revert Accidental #'color
\revert Beam #'color
\revert Dots #'color
\revert NoteHead #'color
\revert Rest #'color
\revert Stem #'color
\revert TupletBracket #'color
\revert TupletNumber #'color
}

```

Return *none*. Changed in version 2.0: renamed `containertools.contents_color()` to `containertools.color_contents_of_container()`.

containertools.delete_contents_of_container

`abjad.tools.containertools.delete_contents_of_container(container)`

Delete contents of *container*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)

abjad> f(staff)
\new Staff {
  c'8 [
  d'8
  e'8
  f'8 ]
}

abjad> containertools.delete_contents_of_container(staff)
[Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]

abjad> f(staff)
\new Staff {
}

```

Return *container* contents. Changed in version 2.0: renamed `containertools.contents_delete()` to `containertools.delete_contents_of_container()`.

containertools.delete_contents_of_container_starting_at_or_after_prolated_offset

`abjad.tools.containertools.delete_contents_of_container_starting_at_or_after_prolated_offset`

New in version 2.0. Delete contents of *container* starting at or after *prolated_offset*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)

```

```
abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}
```

```
abjad> containertools.delete_contents_of_container_starting_at_or_after_prolated_offset(staff, D
Staff{1})
```

```
abjad> f(staff)
\new Staff {
    c'8 [ ]
}
```

Return *container*. Changed in version 2.0: renamed `containertools.contents_delete_starting_not_before_prolated_offset` to `containertools.delete_contents_of_container_starting_at_or_after_prolated_offset()`.

containertools.delete_contents_of_container_starting_before_or_at_prolated_offset

```
abjad.tools.containertools.delete_contents_of_container_starting_before_or_at_prolated_offset
```

New in version 2.0. Delete contents of *container* starting before or at *prolated_offset*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
```

```
abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}
```

```
abjad> containertools.delete_contents_of_container_starting_before_or_at_prolated_offset(staff,
Staff{2})
```

```
abjad> f(staff)
\new Staff {
    e'8 [
    f'8 ]
}
```

Return *container*. Changed in version 2.0: renamed `containertools.contents_delete_starting_not_after_prolated_offset` to `containertools.delete_contents_of_container_starting_before_or_at_prolated_offset()`.

containertools.delete_contents_of_container_starting_strictly_after_prolated_offset

```
abjad.tools.containertools.delete_contents_of_container_starting_strictly_after_prolated_offset
```

New in version 2.0. Delete contents of *container* starting strictly after *prolated_offset*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}

abjad> containertools.delete_contents_of_container_starting_strictly_after_prolated_offset(staff,
Staff{2})

abjad> f(staff)
\new Staff {
    c'8 [
    d'8 ]
}

```

Return *container*. Changed in version 2.0: renamed `containertools.contents_delete_starting_after_prolated_offset` to `containertools.delete_contents_of_container_starting_strictly_after_prolated_offset()`

`containertools.delete_contents_of_container_starting_strictly_before_prolated_offset`

`abjad.tools.containertools.delete_contents_of_container_starting_strictly_before_prolated_offset`

New in version 2.0. Delete contents of *container* contents starting strictly before *prolated_offset*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}

abjad> containertools.delete_contents_of_container_starting_strictly_before_prolated_offset(staff,
Staff{3})

abjad> f(staff)
\new Staff {
    d'8 [
    e'8
    f'8 ]
}

```

Return *container*. Changed in version 2.0: renamed `containertools.contents_delete_starting_before_prolated_offset` to `containertools.delete_contents_of_container_starting_strictly_before_prolated_offset`

containertools.eject_contents_of_container

`abjad.tools.containertools.eject_contents_of_container(container)`

New in version 2.0. Eject contents of *container*:

```
abjad> container = Container("c'8 d'8 e'8 f'8")

abjad> f(container)
{
    c'8
    d'8
    e'8
    f'8
}

abjad> containertools.eject_contents_of_container(container)
[Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]

abjad> container
{}

abjad> f(container)
{
}
```

Return list of *container* contents.

containertools.fuse_like_named_contiguous_containers_in_expr

`abjad.tools.containertools.fuse_like_named_contiguous_containers_in_expr(expr)`

Fuse like-named contiguous containers in *expr*:

```
abjad> staff = Staff(Voice("c'8 c'8") * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> staff[0].name = 'soprano'
abjad> staff[1].name = 'soprano'

abjad> f(staff)
\new Staff {
    \context Voice = "soprano" {
        c'8
        d'8
    }
    \context Voice = "soprano" {
        e'8
        f'8
    }
}

abjad> containertools.fuse_like_named_contiguous_containers_in_expr(staff)
Staff{1}

abjad> f(staff)
\new Staff {
    \context Voice = "soprano" {
        c'8
        d'8
    }
```

```

        e'8
        f'8
    }
}

```

Return *expr*. Changed in version 2.0: renamed `fuse.containers_by_reference()` to `containertools.fuse_like_named_contiguous_containers_in_expr()`.

containertools.get_element_starting_at_exactly_prolated_offset

`abjad.tools.containertools.get_element_starting_at_exactly_prolated_offset` (*container*, *prolated_offset*)

New in version 2.0. Get *container* element starting at exactly *prolated_offset*:

```
abjad> voice = Voice("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")
```

```
abjad> containertools.get_element_starting_at_exactly_prolated_offset(voice, Duration(6, 8))
Note("b'8")
```

Raise missing component error when no *container* element starts at exactly *prolated_offset*. Changed in version 2.0: renamed `containertools.get_element_starting_at_prolated_offset()` to `containertools.get_element_starting_at_exactly_prolated_offset()`.

containertools.get_first_container_in_improper_parentage_of_component

`abjad.tools.containertools.get_first_container_in_improper_parentage_of_component` (*component*)

New in version 2.0. Get first container in improper parentage of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
}
```

```
abjad> containertools.get_first_container_in_improper_parentage_of_component(staff[1])
Staff{4}
```

Return container or none.

containertools.get_first_container_in_proper_parentage_of_component

`abjad.tools.containertools.get_first_container_in_proper_parentage_of_component` (*component*)

New in version 2.0. Get first container in proper parentage of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
```

```

    e'8
    f'8
}

```

```

abjad> containertools.get_first_container_in_proper_parentage_of_component(staff[1])
Staff{4}

```

Return container or none.

containertools.get_first_element_starting_at_or_after_prolated_offset

`abjad.tools.containertools.get_first_element_starting_at_or_after_prolated_offset` (*container*, *pro-lated_offset*)

New in version 2.0. Get first *container* element starting at or after *prolated_offset*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

```

```

abjad> containertools.get_first_element_starting_at_or_after_prolated_offset(staff, Duration(1,
Note("d'8"))

```

Return component.

Return none when no *container* element starts at or after *prolated_offset*. Changed in version 2.0: renamed `containertools.get_leftmost_element_starting_not_before_prolated_offset()` to `containertools.get_first_element_starting_at_or_after_prolated_offset()`.

containertools.get_first_element_starting_before_or_at_prolated_offset

`abjad.tools.containertools.get_first_element_starting_before_or_at_prolated_offset` (*container*, *pro-lated_offset*)

New in version 2.0. Get first *container* element starting before or at *prolated_offset*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

```

```

abjad> containertools.get_first_element_starting_before_or_at_prolated_offset(staff, Duration(1,
Note("d'8"))

```

Return component.

Return none when no *container* element starts before or at *prolated_offset*. Changed in version 2.0: renamed `containertools.get_rightmost_element_starting_not_after_prolated_offset()` to `containertools.get_first_element_starting_before_or_at_prolated_offset()`.

containertools.get_first_element_starting_strictly_after_prolated_offset

`abjad.tools.containertools.get_first_element_starting_strictly_after_prolated_offset` (*container*, *pro-lated_offset*)

New in version 2.0. Get first *container* element starting strictly after *prolated_offset*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

```

```
abjad> containertools.get_first_element_starting_strictly_after_prolated_offset(staff, Duration(
Note("e'8")
```

Return component.

Return none when no *container* element starts strictly after *prolated_offset*. Changed in version 2.0: renamed `containertools.get_leftmost_element_starting_after_prolated_offset()` to `containertools.get_first_element_starting_strictly_after_prolated_offset()`.

`containertools.get_first_element_starting_strictly_before_prolated_offset`

```
abjad.tools.containertools.get_first_element_starting_strictly_before_prolated_offset(container,
pro-
lated_offset)
```

New in version 2.0. Get first *container* element starting strictly before *prolated_offset*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> containertools.get_first_element_starting_strictly_before_prolated_offset(staff, Duration(
Note("c'8")
```

Return component.

Return none when *container* element starts strictly before *prolated_offset*. Changed in version 2.0: renamed `containertools.get_rightmost_element_starting_before_prolated_offset()` to `containertools.get_first_element_starting_strictly_before_prolated_offset()`.

`containertools.insert_component_and_do_not_fracture_crossing_spanners`

```
abjad.tools.containertools.insert_component_and_do_not_fracture_crossing_spanners(container,
i,
com-
po-
nent)
```

New in version 2.0. Insert *component* into *container* at index *i* and do not fracture crossing spanners:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)

abjad> f(staff)
\new Staff {
  c'8 [
  d'8
  e'8
  f'8 ]
}

abjad> containertools.insert_component_and_do_not_fracture_crossing_spanners(staff, 1, Note("cs'8"))
Staff{5}

abjad> f(staff)
\new Staff {
  c'8 [
  cs'8
  d'8
  e'8
```

```
f'8 ]
}
```

Return *container*. Changed in version 2.0: renamed `containertools.insert_and_do_not_fracture()` to `containertools.insert_component_and_do_not_fracture_crossing_spanners()`.

`containertools.insert_component_and_fracture_crossing_spanners`

`abjad.tools.containertools.insert_component_and_fracture_crossing_spanners`(*container*, *i*, *compo-*
po-
nent)

Insert *component* into *container* at index *i* and fracture spanners:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
```

```
abjad> f(staff)
\new Staff {
  c'8 [
  d'8
  e'8
  f'8 ]
}
```

```
abjad> containertools.insert_component_and_fracture_crossing_spanners(staff, 1, Rest((1, 8)))
[(BeamSpanner(c'8, d'8, e'8, f'8), BeamSpanner(c'8), BeamSpanner(d'8, e'8, f'8)), (BeamSpanner(d
```

```
abjad> f(staff)
\new Staff {
  c'8 [ ]
  r8
  d'8 [
  e'8
  f'8 ]
}
```

Return list of fractured spanners. Changed in version 2.0: renamed `containertools.insert_and_fracture()` to `containertools.insert_component_and_fracture_crossing_spanners()`.

`containertools.iterate_containers_backward_in_expr`

`abjad.tools.containertools.iterate_containers_backward_in_expr`(*expr*, *start=0*, *stop=None*)

New in version 2.0. Iterate containers backward in *expr*:

```
abjad> staff = Staff([Voice("c'8 d'8"), Voice("e'8 f'8 g'8")])
abjad> Tuplet(Fraction(2, 3), staff[1][:])
Tuplet(2/3, [e'8, f'8, g'8])
abjad> staff.is_parallel = True
```

```
abjad> f(staff)
\new Staff <<
  \new Voice {
```

```

        c'8
        d'8
    }
    \new Voice {
        \times 2/3 {
            e'8
            f'8
            g'8
        }
    }
>>

abjad> for x in containertools.iterate_containers_backward_in_expr(staff):
...     x
Staff<<2>>
Voice{1}
Tuplet(2/3, [e'8, f'8, g'8])
Voice{2}

```

Ignore threads.

Return generator.

containertools.iterate_containers_forward_in_expr

abjad.tools.containertools.**iterate_containers_forward_in_expr**(*expr*, *start=0*, *stop=None*)

New in version 2.0. Iterate containers forward in *expr*:

```

abjad> staff = Staff([Voice("c'8 d'8"), Voice("e'8 f'8 g'8")])
abjad> Tuplet(Fraction(2, 3), staff[1][:])
Tuplet(2/3, [e'8, f'8, g'8])
abjad> staff.is_parallel = True

```

```

abjad> f(staff)
\new Staff <<
    \new Voice {
        c'8
        d'8
    }
    \new Voice {
        \times 2/3 {
            e'8
            f'8
            g'8
        }
    }
>>

```

```

abjad> for x in containertools.iterate_containers_forward_in_expr(staff):
...     x
Staff<<2>>
Voice{2}
Voice{1}
Tuplet(2/3, [e'8, f'8, g'8])

```

Ignore threads.

Return generator.

containertools.move_parentage_children_and_spanners_from_components_to_empty_container

`abjad.tools.containertools.move_parentage_children_and_spanners_from_components_to_empty_container`

Move parentage, children and spanners from *components* to empty *container*:

```
abjad> voice = Voice(Container("c'8 c'8") * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voice)
abjad> spannertools.BeamSpanner(voice.leaves)
BeamSpanner(c'8, d'8, e'8, f'8, g'8, a'8)
```

```
abjad> f(voice)
\new Voice {
  {
    c'8 [
    d'8
  ]
  {
    e'8
    f'8
  ]
  {
    g'8
    a'8 ]
  ]
}
```

```
abjad> tuplet = Tuplet(Fraction(3, 4), [ ])
abjad> containertools.move_parentage_children_and_spanners_from_components_to_empty_container(voice)
```

```
abjad> f(voice)
\new Voice {
  \fraction \times 3/4 {
    c'8 [
    d'8
    e'8
    f'8
  ]
  {
    g'8
    a'8 ]
  ]
}
```

Return `none`. Changed in version 2.0: renamed `scoretools.donate()` to `containertools.move_parentage_children_and_spanners_from_components_to_empty_container`

containertools.remove_empty_containers_in_expr

`abjad.tools.containertools.remove_empty_containers_in_expr(expr)`

Remove empty containers in *expr*:

```
abjad> staff = Staff(Container(notetools.make_repeated_notes(2)) * 4)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
```

```

abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner({c'8, d'8}, {e'8, f'8}, {g'8, a'8}, {b'8, c''8})
abjad> containertools.delete_contents_of_container(staff[1])
[Note("e'8"), Note("f'8")]
abjad> containertools.delete_contents_of_container(staff[-1])
[Note("b'8"), Note("c''8")]

abjad> f(staff)
\new Staff {
    {
        c'8 [
        d'8
    ]
    {
    }
    {
        g'8
        a'8 ]
    }
    {
    }
}

abjad> containertools.remove_empty_containers_in_expr(staff)

abjad> f(staff)
\new Staff {
    {
        c'8 [
        d'8
    ]
    {
        g'8
        a'8 ]
    }
}

```

Return `none`. Changed in version 2.0: renamed `containertools.remove_empty()` to `containertools.remove_empty_containers_in_expr()`.

containertools.repeat_contents_of_container

`abjad.tools.containertools.repeat_contents_of_container(container, total=2)`

New in version 1.1. Repeat contents of *container*:

```

abjad> staff = Staff("c'8 d'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8 ]
}

abjad> containertools.repeat_contents_of_container(staff, 3)
Staff{6}

```



```

abjad> f(staff)
\new Staff {
    c'8 [
    d'8 ]
    c'8 [
    d'8 ]
    c'8 [
    d'8 ]
}

```

Leave *container* unchanged when *total* is 1.

Empty *container* when *total* is 0.

Return *container*. Changed in version 2.0: renamed `containertools.contents_multiply()` to `containertools.repeat_contents_of_container()`.

containertools.repeat_last_n_elements_of_container

```

abjad.tools.containertools.repeat_last_n_elements_of_container(container, n=1,
                                                                total=2)

```

New in version 1.1. Repeat last *n* elements of *container*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)

```

```

abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}

```

```

abjad> containertools.repeat_last_n_elements_of_container(staff, n = 2, total = 3)
Staff{8}

```

```

abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
    e'8 [
    f'8 ]
    e'8 [
    f'8 ]
}

```

Return *container*. Changed in version 2.0: renamed `containertools.extend_cyclic()` to `containertools.repeat_last_n_elements_of_container()`.

containertools.replace_contents_of_target_container_with_contents_of_source_container

```

abjad.tools.containertools.replace_contents_of_target_container_with_contents_of_source_container

```

New in version 2.0. Replace contents of *target_container* with contents of *source_container*:

```

abjad> staff = Staff(Tuplet(Fraction(2, 3), "c'8 d'8 e'8") * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, ... [5] ..., c''8, d''8)

abjad> f(staff)
\new Staff {
  \times 2/3 {
    c'8 [
      d'8
      e'8
    ]
  }
  \times 2/3 {
    f'8
    g'8
    a'8
  }
  \times 2/3 {
    b'8
    c''8
    d''8 ]
  }
}

abjad> container = Container("c'8 d'8 e'8")
abjad> spannertools.SlurSpanner(container.leaves)
SlurSpanner(c'8, d'8, e'8)

abjad> f(container)
{
  c'8 (
    d'8
    e'8 )
}

abjad> containertools.replace_contents_of_target_container_with_contents_of_source_container(staff,
Tuplet(2/3, [c'8, d'8, e'8]))

abjad> f(staff)
\new Staff {
  \times 2/3 {
    c'8 [
      d'8
      e'8
    ]
  }
  \times 2/3 {
    c'8 (
      d'8
      e'8 )
    ]
  }
  \times 2/3 {
    b'8
    c''8
    d''8 ]
  }
}

```

Leave *source_container* empty:

```
abjad> container
{}
```

Return *target_container*.

containertools.replace_larger_left_half_of_elements_in_container_with_big_endian_rests

`abjad.tools.containertools.replace_larger_left_half_of_elements_in_container_with_big_endian_rests`

New in version 2.0. Replace larger left half of elements in *container* with big-endian rests:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8 d''8 e''8")
```

```
abjad> f(staff)
\new Staff {
  c'8
  d'8
  e'8
  f'8
  g'8
  a'8
  b'8
  c''8
  d''8
  e''8
}
```

```
abjad> containertools.replace_larger_left_half_of_elements_in_container_with_big_endian_rests(staff)
Staff{7}
```

```
abjad> f(staff)
\new Staff {
  r2
  r8
  a'8
  b'8
  c''8
  d''8
  e''8
}
```

Return *container*.

containertools.replace_larger_left_half_of_elements_in_container_with_little_endian_rests

`abjad.tools.containertools.replace_larger_left_half_of_elements_in_container_with_little_endian_rests`

New in version 2.0. Replace larger left half of elements in *container* with little-endian rests:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8 d''8 e''8")
```

```
abjad> f(staff)
\new Staff {
  c'8
  d'8
  e'8
  f'8
  g'8
}
```

```

        a'8
        b'8
        c''8
        d''8
        e''8
    }

```

```

abjad> containertools.replace_larger_left_half_of_elements_in_container_with_little_endian_rests(
Staff{7})

```

```

abjad> f(staff)
\new Staff {
    r8
    r2
    a'8
    b'8
    c''8
    d''8
    e''8
}

```

Return *container*.

containertools.replace_larger_right_half_of_elements_in_container_with_big_endian_rests

`abjad.tools.containertools.replace_larger_right_half_of_elements_in_container_with_big_endian_rests(container)`

New in version 2.0. Replace larger right half of elements in *container* with big-endian rests:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8 d''8 e''8")

```

```

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
    b'8
    c''8
    d''8
    e''8
}

```

```

abjad> containertools.replace_larger_right_half_of_elements_in_container_with_big_endian_rests(
Staff{7})

```

```

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    r2
    r8
}

```

Return *container*.

`containertools.replace_larger_right_half_of_elements_in_container_with_little_endian_rests`

`abjad.tools.containertools.replace_larger_right_half_of_elements_in_container_with_little_endian_rests` (new in version 2.0). Replace larger right half of elements in *container* with little-endian rests:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8 d''8 e''8")
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
    b'8
    c''8
    d''8
    e''8
}
```

```
abjad> containertools.replace_larger_right_half_of_elements_in_container_with_little_endian_rests(staff, 7)
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    r8
    r2
}
```

Return *container*.

`containertools.replace_n_edge_elements_in_container_with_big_endian_rests`

`abjad.tools.containertools.replace_n_edge_elements_in_container_with_big_endian_rests` (new in version 2.0). Replace *n* edge elements in *container* with big-endian rests:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8")
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
}
```

```
abjad> containertools.replace_n_edge_elements_in_container_with_big_endian_rests(staff, -5)
Staff{3}
```

```
abjad> f(staff)
\new Staff {
    c'8
    r2
    r8
}
```

Return *container*. Changed in version 2.0: renamed `containertools.replace_first_n_elements_in_container` to `containertools.replace_n_edge_elements_in_container_with_big_endian_rests()`.

`containertools.replace_n_edge_elements_in_container_with_little_endian_rests`

`abjad.tools.containertools.replace_n_edge_elements_in_container_with_little_endian_rests(container, n)`

New in version 2.0. Replace *n* edge elements in *container* with little-endian rests:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8")
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
}
```

```
abjad> containertools.replace_n_edge_elements_in_container_with_little_endian_rests(staff, -5)
Staff{3}
```

```
abjad> f(staff)
\new Staff {
    c'8
    r8
    r2
}
```

Return *container*. Changed in version 2.0: renamed `containertools.replace_first_n_elements_in_container` to `containertools.replace_n_edge_elements_in_container_with_little_endian_rests()`.

`containertools.replace_n_edge_elements_in_container_with_rests`

`abjad.tools.containertools.replace_n_edge_elements_in_container_with_rests(container, n)`

New in version 2.0. Replace first *n* elements in *container* with big-endian rests:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8")
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
```

```

    e'8
    f'8
    g'8
    a'8
}

```

```

abjad> containertools.replace_n_edge_elements_in_container_with_rests(staff, 5)
Staff{3}

```

```

abjad> f(staff)
\new Staff {
    r2
    r8
    a'8
}

```

Replace last n elements in *container* with little-endian rests:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8")

```

```

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
}

```

```

abjad> containertools.replace_n_edge_elements_in_container_with_rests(staff, -5)
Staff{3}

```

```

abjad> f(staff)
\new Staff {
    c'8
    r8
    r2
}

```

Return *container*. Changed in version 2.0: renamed `containertools.replace_first_n_elements_in_container` to `containertools.replace_n_edge_elements_in_container_with_rests()`.

`containertools.replace_smaller_left_half_of_elements_in_container_with_big_endian_rests`

`abjad.tools.containertools.replace_smaller_left_half_of_elements_in_container_with_big_endian_rests`
 New in version 2.0. Replace smaller left half of elements in *container* with big-endian rests:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8 d''8 e''8")

```

```

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8

```

```

        a'8
        b'8
        c''8
        d''8
        e''8
    }

```

```

abjad> containertools.replace_smaller_left_half_of_elements_in_container_with_big_endian_rests(
Staff{7}

```

```

abjad> f(staff)
\new Staff {
    r2
    r8
    a'8
    b'8
    c''8
    d''8
    e''8
}

```

Return *container*.

containertools.replace_smaller_left_half_of_elements_in_container_with_little_endian_rests

abjad.tools.containertools.**replace_smaller_left_half_of_elements_in_container_with_little_endian_rests**

New in version 2.0. Replace smaller left half of elements in *container* with little-endian rests:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8 d''8 e''8")

```

```

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
    b'8
    c''8
    d''8
    e''8
}

```

```

abjad> containertools.replace_smaller_left_half_of_elements_in_container_with_little_endian_rests(
Staff{7}

```

```

abjad> f(staff)
\new Staff {
    r8
    r2
    a'8
    b'8
    c''8
    d''8
    e''8
}

```


Return *container*.

`containertools.replace_smaller_right_half_of_elements_in_container_with_big_endian_rests`

`abjad.tools.containertools.replace_smaller_right_half_of_elements_in_container_with_big_endian_rests`

New in version 2.0. Relace smaller right half of elements in *container* with big-endian rests:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8 d''8 e''8")
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
    b'8
    c''8
    d''8
    e''8
}
```

```
abjad> containertools.replace_smaller_right_half_of_elements_in_container_with_big_endian_rests(
Staff{7})
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    r2
    r8
}
```

Return *container*.

`containertools.replace_smaller_right_half_of_elements_in_container_with_little_endian_rests`

`abjad.tools.containertools.replace_smaller_right_half_of_elements_in_container_with_little_endian_rests`

New in version 2.0. Replace smaller right half of elements in *container* with little-endian rests:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8 d''8 e''8")
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
    b'8
    c''8
    d''8
}
```

```

        e'8
    }

abjad> containertools.replace_smaller_right_half_of_elements_in_container_with_little_endian_res
Staff{7}

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    r8
    r2
}

```

Return *container*.

containertools.report_container_modifications_as_string

`abjad.tools.containertools.report_container_modifications_as_string(container)`

Report *container* modifications as string:

```

abjad> container = Container("c'8 d'8 e'8 f'8")
abjad> container.override.note_head.color = 'red'
abjad> container.override.note_head.style = 'harmonic'

abjad> f(container)
{
    \override NoteHead #'color = #red
    \override NoteHead #'style = #'harmonic
    c'8
    d'8
    e'8
    f'8
    \revert NoteHead #'color
    \revert NoteHead #'style
}

abjad> string = containertools.report_container_modifications_as_string(container)

abjad> print string # doctest: +SKIP
{
    \override NoteHead #'color = #red
    \override NoteHead #'style = #'harmonic

    %%% 4 components omitted %%%

    \revert NoteHead #'color
    \revert NoteHead #'style
}

```

Return string.

containertools.reverse_contents_of_container

`abjad.tools.containertools.reverse_contents_of_container(container)`

New in version 1.1. Reverse contents of *container*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves[:2])
BeamSpanner(c'8, d'8)
abjad> spannertools.SlurSpanner(staff.leaves[2:])
SlurSpanner(e'8, f'8)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8 ]
    e'8 (
    f'8 )
}

abjad> containertools.reverse_contents_of_container(staff)
Staff{4}

abjad> f(staff) # doctest: +SKIP
\new Staff {
    f'8 (
    e'8 )
    d'8 [
    c'8 ]
}
```

Return *container*. Changed in version 2.0: renamed `containertools.contents_reverse()` to `containertools.reverse_contents_of_container()`.

containertools.scale_contents_of_container

`abjad.tools.containertools.scale_contents_of_container(container, multiplier)`

New in version 1.1. Scale contents of *container* by dot *multiplier*:

```
abjad> staff = Staff("c'8 d'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8 ]
}

abjad> containertools.scale_contents_of_container(staff, Duration(3, 2))
Staff{2}

abjad> f(staff)
\new Staff {
    c'8. [
    d'8. ]
}
```

Scale contents of *container* by tie *multiplier*:

```

abjad> staff = Staff("c'8 d'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8 ]
}

abjad> containertools.scale_contents_of_container(staff, Duration(5, 4))
Staff{4}

abjad> f(staff)
\new Staff {
    c'8 [ ~
    c'32
    d'8 ~
    d'32 ]
}

```

Scale contents of *container* by nonbinary *multiplier*:

```

abjad> staff = Staff("c'8 d'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8 ]
}

abjad> containertools.scale_contents_of_container(staff, Duration(4, 3))
Staff{2}

abjad> f(staff)
\new Staff {
    \times 2/3 {
        c'4 [
    }
    \times 2/3 {
        d'4 ]
    }
}

```

Return *container*. Changed in version 2.0: renamed `containertools.contents_scale()` to `containertools.scale_contents_of_container()`.

containertools.set_container_multiplier

`abjad.tools.containertools.set_container_multiplier(container, multiplier)`

Set *container multiplier*:

```

abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")

```

```

abjad> f(tuplet)
\times 2/3 {
    c'8
    d'8
    e'8
}

abjad> containertools.set_container_multiplier(tuplet, Duration(3, 4))

abjad> f(tuplet)
\fraction \times 3/4 {
    c'8
    d'8
    e'8
}

```

Return `none`. Changed in version 2.0: renamed `containertools.multiplier_set()` to `containertools.set_container_multiplier()`.

containertools.split_container_at_index_and_do_not_fracture_crossing_spanners

```
abjad.tools.containertools.split_container_at_index_and_do_not_fracture_crossing_spanners(
```

Split *container* at *index* and do not fracture crossing spanners:

```

abjad> voice = Voice(Measure((3, 8), "c'8 c'8 c'8") * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voi
abjad> beam = spannertools.BeamSpanner(voice[:])

abjad> f(voice)
\new Voice {
    {
        \time 3/8
        c'8 [
        d'8
        e'8
    }
    {
        \time 3/8
        f'8
        g'8
        a'8 ]
    }
}

abjad> containertools.split_container_at_index_and_do_not_fracture_crossing_spanners(voice[1], 1
(Measure(1/8, [f'8]), Measure(2/8, [g'8, a'8]))

abjad> f(voice)
\new Voice {
    {
        \time 3/8
        c'8 [
        d'8
        e'8
    }
}

```

```

    {
        \time 1/8
        f'8
    }
    {
        \time 2/8
        g'8
        a'8 ]
    }
}

```

Leave spanners and leaves untouched.

Resize resizable containers.

Preserve container multiplier.

Preserve meter denominator.

Return split parts. Changed in version 2.0: renamed `split.unfractured_at_index()` to `containertools.split_container_at_index_and_do_not_fracture_crossing_spanners()`.

containertools.split_container_at_index_and_fracture_crossing_spanners

`abjad.tools.containertools.split_container_at_index_and_fracture_crossing_spanners` (*container*, *in-*
dex)

Split *container* at *index* and fracture crossing spanners:

```

abjad> voice = Voice(tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 c'8 c'8") * 2)
abjad> tuplet = voice[1]
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voi
abjad> beam = spannertools.BeamSpanner(voice[:])

abjad> f(voice)
\new Voice {
    \times 2/3 {
        c'8 [
        d'8
        e'8
    ]
    \times 2/3 {
        f'8
        g'8
        a'8 ]
    }
}

abjad> left, right = containertools.split_container_at_index_and_fracture_crossing_spanners(tupl

abjad> f(voice)
\new Voice {
    \times 2/3 {
        c'8 [
        d'8
        e'8
    ]
    \times 2/3 {
        f'8 ]
    }
}

```

```

    }
    \times 2/3 {
      g'8 [
      a'8 ]
    }
  }
}

```

Leave leaves untouched.

Create two new copies of *container*.

Empty *container* of original contents.

Return split parts. Changed in version 2.0: renamed `split.fractured_at_index()` to `containertools.split_container_at_index_and_fracture_crossing_spanners()`.

containertools.split_container_cyclically_by_counts_and_do_not_fracture_crossing_spanners

`abjad.tools.containertools.split_container_cyclically_by_counts_and_do_not_fracture_crossing_spanners`

Split *container* cyclically by *counts* and do not fracture crossing spanners:

```

abjad> container = Container("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")
abjad> voice = Voice([container])
abjad> beam = spannertools.BeamSpanner(voice)
abjad> slur = spannertools.SlurSpanner(container)

```

```

abjad> f(voice)
\new Voice {
  {
    c'8 [ (
    d'8
    e'8
    f'8
    g'8
    a'8
    b'8
    c''8 ] )
  }
}

```

```

abjad> containertools.split_container_cyclically_by_counts_and_do_not_fracture_crossing_spanners
[[{c'8}], [{d'8, e'8, f'8}], [{g'8}], [{a'8, b'8, c''8}]]

```

```

abjad> f(voice)
\new Voice {
  {
    c'8 [ (
  }
  {
    d'8
    e'8
    f'8
  }
  {
    g'8
  }
  {

```

```

        a'8
        b'8
        c''8 ] )
    }
}

```

Return list of list-wrapped container pieces. Changed in version 2.0: renamed `partition.cyclic_unfractured_by_counts()` to `containertools.split_container_cyclically_by_counts_and_do_not_fracture_crossing_spanners`

containertools.split_container_cyclically_by_counts_and_fracture_crossing_spanners

`abjad.tools.containertools.split_container_cyclically_by_counts_and_fracture_crossing_spanners`

Split *container* cyclically by *counts* and fracture crossing spanners:

```

abjad> container = Container("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")
abjad> voice = Voice([container])
abjad> beam = spannertools.BeamSpanner(voice)
abjad> slur = spannertools.SlurSpanner(container)

```

```

abjad> f(voice)
\new Voice {
  {
    c'8 [ (
    d'8
    e'8
    f'8
    g'8
    a'8
    b'8
    c''8 ] )
  }
}

```

```

abjad> containertools.split_container_cyclically_by_counts_and_fracture_crossing_spanners(container,
[[{c'8}], [{d'8, e'8, f'8}], [{g'8}], [{a'8, b'8, c''8}]]

```

```

abjad> f(voice)
\new Voice {
  {
    c'8 ( ) [
  }
  {
    d'8 (
    e'8
    f'8 )
  }
  {
    g'8 ( )
  }
  {
    a'8 (
    b'8
    c''8 ] )
  }
}

```


Return list of list-wrapped container pieces. Changed in version 2.0: renamed `partition.cyclic_fractured_by_counts()` to `containertools.split_container_cyclically_by_counts_and_fracture_crossing_spanners()`.

`containertools.split_container_once_by_counts_and_do_not_fracture_crossing_spanners`

`abjad.tools.containertools.split_container_once_by_counts_and_do_not_fracture_crossing_spanners`

Split *container* once by *counts* and do no fracture crossing spanners:

```
abjad> container = Container("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")
abjad> voice = Voice([container])
abjad> beam = spannertools.BeamSpanner(voice)
abjad> slur = spannertools.SlurSpanner(container)
```

```
abjad> f(voice)
\new Voice {
  {
    c'8 [ (
      d'8
      e'8
      f'8
      g'8
      a'8
      b'8
      c''8 ] )
  }
}
```

```
abjad> containertools.split_container_once_by_counts_and_do_not_fracture_crossing_spanners(container,
[[{c'8}], [{d'8, e'8, f'8}], [{g'8, a'8, b'8, c''8}]]
```

```
abjad> f(voice)
\new Voice {
  {
    c'8 [ (
  }
  {
    d'8
    e'8
    f'8
  }
  {
    g'8
    a'8
    b'8
    c''8 ] )
  }
}
```

Return list of list-wrapped container pieces. Changed in version 2.0: renamed `partition.unfractured_by_counts()` to `containertools.split_container_once_by_counts_and_do_not_fracture_crossing_spanners()`.

containertools.split_container_once_by_counts_and_fracture_crossing_spanners

abjad.tools.containertools.**split_container_once_by_counts_and_fracture_crossing_spanners** (container, counts, fracture_crossing_spanners) *CO*

Split *container* once by *counts* and fracture crossing spanners:

```
abjad> container = Container("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")
abjad> voice = Voice([container])
abjad> beam = spannertools.BeamSpanner(voice)
abjad> slur = spannertools.SlurSpanner(container)
```

```
abjad> f(voice)
\new Voice {
  {
    c'8 [ (
    d'8
    e'8
    f'8
    g'8
    a'8
    b'8
    c''8 ] )
  }
}
```

```
abjad> containertools.split_container_once_by_counts_and_fracture_crossing_spanners(container, [
[[{c'8}], [{d'8, e'8, f'8}], [{g'8, a'8, b'8, c''8}]]
```

```
abjad> f(voice)
\new Voice {
  {
    c'8 ( ) [
  }
  {
    d'8 (
    e'8
    f'8 )
  }
  {
    g'8 (
    a'8
    b'8
    c''8 ] )
  }
}
```

Return list of list-wrapped container pieces. Changed in version 2.0: renamed `partition.fractured_by_counts()` to `containertools.split_container_once_by_counts_and_fracture_crossing_spanners()`

contexttools

contexttools.ClefMark

class abjad.tools.contexttools.**ClefMark** (*arg*, *target_context=None*)

Bases: `abjad.tools.contexttools.ContextMark.ContextMark` `ContextMark` New in version 2.0. Abjad model of a clef:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> contexttools.ClefMark('treble')(staff)
ClefMark('treble')(Staff{4})

abjad> f(staff)
\new Staff {
  \clef "treble"
  c'8
  d'8
  e'8
  f'8
}

```

Clef marks target the staff context by default.

clef_name_string

Get clef name string:

```

abjad> clef = contexttools.ClefMark('treble')
abjad> clef.clef_name_string
'treble'

```

Set clef name string:

```

abjad> clef.clef_name_string = 'alto'
abjad> clef.clef_name_string
'alto'

```

Return string.

format

Read-only LilyPond format of clef:

```

abjad> clef = contexttools.ClefMark('treble')
abjad> clef.format
'\\clef "treble"'

```

Return string.

middle_c_position

Read-only middle-C position of clef:

```

abjad> clef = contexttools.ClefMark('treble')
abjad> clef.middle_c_position
-6

```

Return integer number of stafflines.

contexttools.ContextMark

class abjad.tools.contexttools.**ContextMark** (*target_context=None*)

Bases: abjad.tools.marktools.Mark.Mark.Mark New in version 2.0. Abstract class from which concrete context marks inherit:

```

abjad> note = Note("c'4")

abjad> contexttools.ContextMark()(note)
ContextMark()(c'4)

```

Context marks override `__call__` to attach to Abjad components.

Context marks implement `__slots__`.

attach_mark (*start_component*)

Make sure no context mark of same type is already attached to start component.

detach_mark ()

Detach mark:

```
abjad> note = Note("c'4")
abjad> context_mark = contexttools.ContextMark()(note)
```

```
abjad> context_mark.start_component
Note("c'4")
```

```
abjad> context_mark.detach_mark()
ContextMark()
```

```
abjad> context_mark.start_component is None
True
```

Return context mark.

effective_context

Read-only reference to effective context of context mark:

```
abjad> note = Note("c'4")
abjad> context_mark = contexttools.ContextMark()(note)
```

```
abjad> context_mark.effective_context is None
True
```

Return context mark or none.

target_context

Read-only reference to target context of context mark:

```
abjad> note = Note("c'4")
abjad> context_mark = contexttools.ContextMark()(note)
```

```
abjad> context_mark.target_context is None
True
```

Return context mark or none.

contexttools.DynamicMark

class abjad.tools.contexttools.**DynamicMark** (*dynamic_name_string*, *target_context=None*)

Bases: abjad.tools.contexttools.ContextMark.ContextMark.ContextMark New in version 2.0. Abjad model of a dynamic mark:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> contexttools.DynamicMark('f')(staff[0])
DynamicMark('f')(c'8)

abjad> f(staff)
\new Staff {
  c'8 \f
```

```

d' 8
e' 8
f' 8
}

```

Dynamic marks target the staff context by default.

static composite_dynamic_name_to_steady_state_dynamic_name (*dynamic_name*)

Change composite *dynamic_name* to steady state dynamic name:

```

abjad> contexttools.DynamicMark.composite_dynamic_name_to_steady_state_dynamic_name('sfp')
'p'

```

Return string.

dynamic_name_string

Get dynamic name string:

```

abjad> dynamic = contexttools.DynamicMark('f')
abjad> dynamic.dynamic_name_string
'f'

```

Set dynamic name string:

```

abjad> dynamic.dynamic_name_string = 'p'
abjad> dynamic.dynamic_name_string
'p'

```

Return string.

static dynamic_name_to_dynamic_ordinal (*dynamic_name*)

Change *dynamic_name* to dynamic ordinal:

```

abjad> contexttools.DynamicMark.dynamic_name_to_dynamic_ordinal('fff')
4

```

Return integer.

static dynamic_ordinal_to_dynamic_name (*dynamic_ordinal*)

Change *dynamic_ordinal* to dynamic name:

```

abjad> contexttools.DynamicMark.dynamic_ordinal_to_dynamic_name(-5)
'pppp'

```

Return string.

format

Read-only LilyPond input format of dynamic mark:

```

abjad> dynamic_mark = contexttools.DynamicMark('f')
abjad> dynamic_mark.format
'\f'

```

Return string.

static is_dynamic_name (*arg*)

True when *arg* is dynamic name. False otherwise:

```

abjad> contexttools.DynamicMark.is_dynamic_name('f')
True

```

Return boolean.

contexttools.InstrumentMark

class abjad.tools.contexttools.**InstrumentMark**(*instrument_name*, *short_instrument_name*, *target_context=None*)

Bases: abjad.tools.contexttools.ContextMark.ContextMark.ContextMark New in version 2.0. Abjad model of an instrument change:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> contexttools.InstrumentMark('Flute', 'Fl.')(staff)
InstrumentMark('Flute', 'Fl.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Flute }
  \set Staff.shortInstrumentName = \markup { Fl. }
  c'8
  d'8
  e'8
  f'8
}
```

Instrument marks target staff context by default.

format

Read-only LilyPond input format of instrument mark:

```
abjad> instrument = contexttools.InstrumentMark('Flute', 'Fl.')
abjad> instrument.format
['\set Staff.instrumentName = \markup { Flute }', '\set Staff.shortInstrumentName = \markup
```

Return list.

instrument_name

Get instrument name:

```
abjad> instrument = contexttools.InstrumentMark('Flute', 'Fl.')
abjad> instrument.instrument_name
Markup('Flute')
```

Set instrument name:

```
abjad> instrument.instrument_name = 'Alto Flute'
abjad> instrument.instrument_name
Markup('Alto Flute')
```

Return markup.

short_instrument_name

Get short instrument name:

```
abjad> instrument = contexttools.InstrumentMark('Flute', 'Fl.')
abjad> instrument.short_instrument_name
Markup('Fl.')
```

Set short instrument name:

```
abjad> instrument.short_instrument_name = 'Alto Fl.'
abjad> instrument.short_instrument_name
Markup('Alto Fl.')
```

Return markup.

contexttools.KeySignatureMark

class abjad.tools.contexttools.**KeySignatureMark**(*tonic, mode, target_context=None*)

Bases: abjad.tools.contexttools.ContextMark.ContextMark.ContextMark New in version 2.0. Abjad model of a key signature setting or key signature change:

```
abjad> staff = Staff("e'8 fs'8 gs'8 a'8")

abjad> contexttools.KeySignatureMark('e', 'major')(staff)
KeySignatureMark(NamedChromaticPitchClass('e'), Mode(major))(Staff{4})

abjad> f(staff)
\new Staff {
  \key e \major
  e'8
  fs'8
  gs'8
  a'8
}
```

Key signature marks target staff context by default.

format

Read-only LilyPond format of key signature mark:

```
abjad> key_signature = contexttools.KeySignatureMark('e', 'major')
abjad> key_signature.format
'\key e \major'
```

Return string.

mode

Get mode of key signature:

```
abjad> key_signature = contexttools.KeySignatureMark('e', 'major')
abjad> key_signature.mode
Mode(major)
```

Set mode of key signature:

```
abjad> key_signature.mode = 'minor'
abjad> key_signature.mode
Mode(minor)
```

Return mode.

name

Read-only name of key signature:

```
abjad> key_signature = contexttools.KeySignatureMark('e', 'major')
abjad> key_signature.name
'E major'
```

Return string.

tonic

Get tonic of key signature:

```
abjad> key_signature = contexttools.KeySignatureMark('e', 'major')
abjad> key_signature.tonic
NamedChromaticPitchClass('e')
```

Set tonic of key signature:

```
abjad> key_signature.tonic = 'd'
abjad> key_signature.tonic
NamedChromaticPitchClass('d')
```

Return named chromatic pitch.

contexttools.StaffChangeMark

class abjad.tools.contexttools.**StaffChangeMark** (*staff*, *target_context=None*)

Bases: abjad.tools.contexttools.ContextMark.ContextMark.ContextMark New in version 2.0. Abjad model of a staff change:

```
abjad> piano_staff = scoretools.PianoStaff([ ])
abjad> rh_staff = Staff("c'8 d'8 e'8 f'8")
abjad> rh_staff.name = 'RHStaff'
abjad> lh_staff = Staff("s2")
abjad> lh_staff.name = 'LHStaff'
abjad> piano_staff.extend([rh_staff, lh_staff])

abjad> f(piano_staff)
\new PianoStaff <<
  \context Staff = "RHStaff" {
    c'8
    d'8
    e'8
    f'8
  }
  \context Staff = "LHStaff" {
    s2
  }
>>

abjad> contexttools.StaffChangeMark(lh_staff)(rh_staff[2])
StaffChangeMark(Staff-"LHStaff"{1})(e'8)

abjad> f(piano_staff) # doctest: +SKIP
\new PianoStaff <<
  \context Staff = "RHStaff" {
    c'8
    d'8
    \change Staff = LHStaff
    e'8
    f'8
  }
  \context Staff = "LHStaff" {
    s2
  }
>>
```

Staff change marks target staff context by default.

format

Read-only LilyPond format of staff change mark:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> staff.name = 'RHStaff'
abjad> staff_change = contexttools.StaffChangeMark(staff)
abjad> staff_change.format
'\\change Staff = RHStaff'
```

Return string.

staff

Get staff of staff change mark:

```
abjad> rh_staff = Staff("c'8 d'8 e'8 f'8")
abjad> rh_staff.name = 'RHStaff'
abjad> staff_change = contexttools.StaffChangeMark(rh_staff)
abjad> staff_change.staff
Staff-"RHStaff"{4}
```

Set staff of staff change mark:

```
abjad> lh_staff = Staff("s2")
abjad> lh_staff.name = 'LHStaff'
abjad> staff_change.staff = lh_staff
abjad> staff_change.staff
Staff-"LHStaff"{1}
```

Return staff.

contexttools.TempoMark

class abjad.tools.contexttools.**TempoMark**(*args, **kwargs)

Bases: abjad.tools.contexttools.ContextMark.ContextMark New in version 2.0. Abjad model of a tempo indication:

```
abjad> score = Score([ ])
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> score.append(staff)

abjad> contexttools.TempoMark(Duration(1, 8), 52)(staff[0])
TempoMark(8, 52)(c'8)

abjad> f(score)
\\new Score <<
  \\tempo 8=52
  \\new Staff {
    c'8
    d'8
    e'8
    f'8
  }
>>
```

Tempo marks target **score** context by default.

duration

Get duration of tempo mark:

```
abjad> tempo = contexttools.TempoMark(Duration(1, 8), 52)
abjad> tempo.duration
Duration(1, 8)
```

Set duration of tempo mark:

```
abjad> tempo.duration = Duration(1, 4)
abjad> tempo.duration
Duration(1, 4)
```

Return duration.

format

Read-only LilyPond format of tempo mark:

```
abjad> tempo = contexttools.TempoMark(Duration(1, 8), 52)
abjad> tempo.format
'\\tempo 8=52'
```

Return string.

quarters_per_minute

Read-only quarters per minute of tempo mark:

```
abjad> tempo = contexttools.TempoMark(Duration(1, 8), 52)
abjad> tempo.quarters_per_minute
Duration(104, 1)
```

Return fraction.

units_per_minute

Get units per minute of tempo mark:

```
abjad> tempo = contexttools.TempoMark(Duration(1, 8), 52)
abjad> tempo.units_per_minute
52
```

Set units per minute of tempo mark:

```
abjad> tempo.units_per_minute = 56
abjad> tempo.units_per_minute
56
```

Return number.

contexttools.TimeSignatureMark

class abjad.tools.contexttools.**TimeSignatureMark**(*args, **kwargs)

Bases: abjad.tools.contexttools.ContextMark.ContextMark.ContextMark New in version 2.0. Abjad model of a time signature:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> contexttools.TimeSignatureMark((4, 8))(staff[0])
TimeSignatureMark(4, 8)(c'8)

abjad> f(staff)
\\new Staff {
  \\time 4/8
  c'8
```

```

    d' 8
    e' 8
    f' 8
}

```

Abjad time signature marks target **staff context** by default.

Initialize time signature marks to **score context** like this:

```

abjad> contexttools.TimeSignatureMark((4, 8), target_context = Score)
TimeSignatureMark(4, 8, target_context = Score)

```

Time signatures are immutable.

denominator

Get denominator of time signature mark:

```

abjad> meter = contexttools.TimeSignatureMark(3, 8)
abjad> meter
TimeSignatureMark(3, 8)
abjad> meter.denominator
8

```

Set denominator of time signature mark:

```

abjad> meter.denominator = 16
abjad> meter.denominator
16

```

Return integer.

duration

Read-only duration of time signature mark:

```

abjad> meter = contexttools.TimeSignatureMark(3, 8)
abjad> meter.duration
Duration(3, 8)

```

Return fraction.

format

Read-only LilyPond format of time signature mark:

```

abjad> meter = contexttools.TimeSignatureMark(3, 8)
abjad> meter.format
'\time 3/8'

```

Return string.

is_nonbinary

Read-only indicator true when time signature mark is nonbinary:

```

abjad> meter = contexttools.TimeSignatureMark(3, 8)
abjad> meter.is_nonbinary
False

```

Return boolean.

multiplier

Read-only multiplier of time signature mark:

```
abjad> meter = contexttools.TimeSignatureMark(3, 8)
abjad> meter.multiplier
Fraction(1, 1)
```

Return fraction.

numerator

Get numerator of time signature mark:

```
abjad> meter = contexttools.TimeSignatureMark(3, 8)
abjad> meter.numerator
3
```

Set numerator of time signature mark:

```
abjad> meter.numerator = 4
abjad> meter.numerator
4
```

Set integer.

partial

Get partial measure pick-up of time signature mark:

```
abjad> meter = contexttools.TimeSignatureMark(3, 8, partial = Duration(1, 8))
abjad> meter.partial
Duration(1, 8)
```

Set partial measure pick-up of time signature mark:

```
abjad> meter.partial = Duration(1, 4)
abjad> meter.partial
Duration(1, 4)
```

Set fraction or none.

contexttools.detach_all_context_marks_attached_to_component

```
abjad.tools.contexttools.detach_all_context_marks_attached_to_component(start_component,
                                                                           klaseses=(<class
                                                                           'ab-
                                                                           jad.tools.contexttools.Conte
                                                                           ))
```

New in version 2.0. Detach context marks attached to *start_component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> clef_mark = contexttools.ClefMark('treble')(staff)
abjad> dynamic_mark = contexttools.DynamicMark('p')(staff[0])
abjad> f(staff)
\new Staff {
  \clef "treble"
  c'8 \p
  d'8
  e'8
  f'8
}
```

```
abjad> contexttools.detach_all_context_marks_attached_to_component(staff[0])
(DynamicMark('p'),)
```

```

abjad> f(staff)
\new Staff {
  \clef "treble"
  c'8
  d'8
  e'8
  f'8
}

```

Return tuple of zero or marks. Changed in version 2.0: renamed to
`contexttools.detach_context_marks_attached_to_start_component()`
`contexttools.detach_all_context_marks_attached_to_component()`.

contexttools.detach_instrument_mark_attached_to_component

`abjad.tools.contexttools.detach_instrument_mark_attached_to_component` (*component*)

New in version 2.1. Detach instrument mark attached to *component*:

```

abjad> staff = Staff("c'4 d'4 e'4 f'4")
abjad> instrument_mark = contexttools.InstrumentMark('Violin ', 'Vn. ')
abjad> instrument_mark.attach_mark(staff)
InstrumentMark('Violin ', 'Vn. ') (Staff{4})

```

```

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Violin }
  \set Staff.shortInstrumentName = \markup { Vn. }
  c'4
  d'4
  e'4
  f'4
}

```

```

abjad> contexttools.detach_instrument_mark_attached_to_component(staff)
InstrumentMark('Violin ', 'Vn. ')

```

```

abjad> f(staff)
\new Staff {
  c'4
  d'4
  e'4
  f'4
}

```

Return instrument mark.

Raise missing mark error when no instrument mark attached to *component*.

contexttools.detach_time_signature_mark_attached_to_component

`abjad.tools.contexttools.detach_time_signature_mark_attached_to_component` (*component*)

New in version 2.0. Detach time signature mark attached to *component*:

```

abjad> staff = Staff("c'4 d'4 e'4 f'4")
abjad> contexttools.TimeSignatureMark(4, 4)(staff[0])
TimeSignatureMark(4, 4)(c'4)

```

```

abjad> f(staff)
\new Staff {
    \time 4/4
    c'4
    d'4
    e'4
    f'4
}

abjad> contexttools.detach_time_signature_mark_attached_to_component(staff[0])
TimeSignatureMark(4, 4)

abjad> f(staff)
\new Staff {
    c'4
    d'4
    e'4
    f'4
}

```

Return time signature mark.

Raise missing mark error when no time signature mark attached to *component*.

contexttools.get_context_marks_attached_to_any_improper_parent_of_component

`abjad.tools.contexttools.get_context_marks_attached_to_any_improper_parent_of_component` (*component*)

New in version 2.0. Get all context marks attached to any improper parent of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('treble')(staff)
ClefMark('treble')(Staff{4})
abjad> contexttools.DynamicMark('f')(staff[0])
DynamicMark('f')(c'8)

```

```

abjad> f(staff)
\new Staff {
    \clef "treble"
    c'8 \f
    d'8
    e'8
    f'8
}

```

```

abjad> contexttools.get_context_marks_attached_to_any_improper_parent_of_component(staff[0]) # d
set([DynamicMark('f')(c'8), ClefMark('treble')(Staff{4})])

```

Return unordered set of zero or more context marks. Changed in version 2.0: renamed `contexttools.get_all_context_marks_attached_to_any_improper_parent_of_component()` to `contexttools.get_context_marks_attached_to_any_improper_parent_of_component()`.

contexttools.get_context_marks_attached_to_component

```
abjad.tools.contexttools.get_context_marks_attached_to_component (start_component,
                                                                    classes=( <class
                                                                    'ab-
                                                                    jad.tools.contexttools.ContextMark.Co
                                                                    ))
```

New in version 2.0. Get context marks attached to *start_component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> clef_mark = contexttools.ClefMark('treble')(staff)
abjad> dynamic_mark = contexttools.DynamicMark('p')(staff[0])
```

```
abjad> f(staff)
\new Staff {
    \clef "treble"
    c'8 \p
    d'8
    e'8
    f'8
}
```

```
abjad> contexttools.get_context_marks_attached_to_component(staff[0])
(DynamicMark('p')(c'8),)
```

Return tuple of zero or more context marks. Changed in version 2.0: renamed `contexttools.get_context_marks_attached_to_start_component()` to `contexttools.get_context_marks_attached_to_component()`.

contexttools.get_dynamic_marks_attached_to_component

```
abjad.tools.contexttools.get_dynamic_marks_attached_to_component (component)
```

New in version 2.0. Get dynamic marks attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> clef_mark = contexttools.ClefMark('treble')(staff)
abjad> dynamic_mark = contexttools.DynamicMark('p')(staff[0])
abjad> f(staff)
```

```
\new Staff {
    \clef "treble"
    c'8 \p
    d'8
    e'8
    f'8
}
```

```
abjad> contexttools.get_dynamic_marks_attached_to_component(staff[0])
(DynamicMark('p')(c'8),)
```

Return tuple of zero or more dynamic marks.

contexttools.get_effective_clef

```
abjad.tools.contexttools.get_effective_clef (component)
```

New in version 2.0. Get effective clef of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('treble')(staff)
ClefMark('treble')(Staff{4})

abjad> f(staff)
\new Staff {
    \clef "treble"
    c'8
    d'8
    e'8
    f'8
}

abjad> for note in staff:
...     print note, contexttools.get_effective_clef(note)
...
c'8 ClefMark('treble')(Staff{4})
d'8 ClefMark('treble')(Staff{4})
e'8 ClefMark('treble')(Staff{4})
f'8 ClefMark('treble')(Staff{4})

```

Return clef mark or none.

contexttools.get_effective_context_mark

abjad.tools.contexttools.get_effective_context_mark(*component*, *klass*)

New in version 2.0. Get effective context mark of *klass* from *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.TimeSignatureMark(4, 8)(staff)
TimeSignatureMark(4, 8)(Staff{4})

abjad> f(staff)
\new Staff {
    \time 4/8
    c'8
    d'8
    e'8
    f'8
}

abjad> contexttools.get_effective_context_mark(staff[0], contexttools.TimeSignatureMark)
TimeSignatureMark(4, 8)(Staff{4})

```

Return context mark or none.

contexttools.get_effective_dynamic

abjad.tools.contexttools.get_effective_dynamic(*component*)

New in version 2.0. Get effective dynamic of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.DynamicMark('f')(staff[0])
DynamicMark('f')(c'8)

```



```

abjad> f(staff)
\new Staff {
    c'8 \f
    d'8
    e'8
    f'8
}

abjad> for note in staff:
...     print note, contexttools.get_effective_dynamic(note)
...
c'8 DynamicMark('f')(c'8)
d'8 DynamicMark('f')(c'8)
e'8 DynamicMark('f')(c'8)
f'8 DynamicMark('f')(c'8)

```

Return dynamic mark or none.

contexttools.get_effective_instrument

`abjad.tools.contexttools.get_effective_instrument` (*component*)

New in version 2.0. Get effective instrument of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.InstrumentMark('Flute', 'Fl.')(staff)
InstrumentMark('Flute', 'Fl.')(Staff{4})

abjad> f(staff)
\new Staff {
    \set Staff.instrumentName = \markup { Flute }
    \set Staff.shortInstrumentName = \markup { Fl. }
    c'8
    d'8
    e'8
    f'8
}

abjad> for note in staff:
...     print note, contexttools.get_effective_instrument(note)
...
c'8 InstrumentMark('Flute', 'Fl.')(Staff{4})
d'8 InstrumentMark('Flute', 'Fl.')(Staff{4})
e'8 InstrumentMark('Flute', 'Fl.')(Staff{4})
f'8 InstrumentMark('Flute', 'Fl.')(Staff{4})

```

Return instrument mark or none.

contexttools.get_effective_key_signature

`abjad.tools.contexttools.get_effective_key_signature` (*component*)

New in version 2.0. Get effective key signature of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.KeySignatureMark('c', 'major')(staff)
KeySignatureMark(NamedChromaticPitchClass('c'), Mode(major))(Staff{4})

```

```

abjad> f(staff)
\new Staff {
    \key c \major
    c'8
    d'8
    e'8
    f'8
}

abjad> for note in staff:
...     note, contexttools.get_effective_key_signature(note)
...
(Note("c'8"), KeySignatureMark(NamedChromaticPitchClass('c'), Mode(major))(Staff{4}))
(Note("d'8"), KeySignatureMark(NamedChromaticPitchClass('c'), Mode(major))(Staff{4}))
(Note("e'8"), KeySignatureMark(NamedChromaticPitchClass('c'), Mode(major))(Staff{4}))
(Note("f'8"), KeySignatureMark(NamedChromaticPitchClass('c'), Mode(major))(Staff{4}))

```

Return key signature mark or none.

contexttools.get_effective_staff

`abjad.tools.contexttools.get_effective_staff(component)`

New in version 2.0. Get effective staff of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> staff.name = 'First Staff'

abjad> f(staff)
\context Staff = "First Staff" {
    c'8
    d'8
    e'8
    f'8
}

abjad> for note in staff:
...     print note, contexttools.get_effective_staff(note)
...
c'8 Staff-"First Staff"{4}
d'8 Staff-"First Staff"{4}
e'8 Staff-"First Staff"{4}
f'8 Staff-"First Staff"{4}

```

Return staff or none.

contexttools.get_effective_tempo

`abjad.tools.contexttools.get_effective_tempo(component)`

New in version 2.0. Get effective tempo of *component*:

```

abjad> score = Score([ ])
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> score.append(staff)
abjad> contexttools.TempoMark(Duration(1, 8), 52)(staff[0])
TempoMark(8, 52)(c'8)

```

```

abjad> f(score)
\new Score <<
  \tempo 8=52
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
>>

abjad> for note in staff:
...     print note, contexttools.get_effective_tempo(note)
...
c'8 TempoMark(8, 52) (c'8)
d'8 TempoMark(8, 52) (c'8)
e'8 TempoMark(8, 52) (c'8)
f'8 TempoMark(8, 52) (c'8)

```

Return tempo mark or none.

contexttools.get_effective_time_signature

`abjad.tools.contexttools.get_effective_time_signature` (*component*)

New in version 2.0. Get effective time signature of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.TimeSignatureMark(4, 8)(staff)
TimeSignatureMark(4, 8)(Staff{4})

abjad> f(staff)
\new Staff {
  \time 4/8
  c'8
  d'8
  e'8
  f'8
}

abjad> for note in staff:
...     note, contexttools.get_effective_time_signature(note)
...
(Note("c'8"), TimeSignatureMark(4, 8)(Staff{4}))
(Note("d'8"), TimeSignatureMark(4, 8)(Staff{4}))
(Note("e'8"), TimeSignatureMark(4, 8)(Staff{4}))
(Note("f'8"), TimeSignatureMark(4, 8)(Staff{4}))

```

Return time signature mark or none.

contexttools.get_instrument_mark_attached_to_component

`abjad.tools.contexttools.get_instrument_mark_attached_to_component` (*component*)

New in version 2.1. Get instrument mark attached to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> violin = contexttools.InstrumentMark('Violin ', 'Vn. ')

```

```
abjad> violin.attach_mark(staff)
InstrumentMark('Violin ', 'Vn. ') (Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Violin }
  \set Staff.shortInstrumentName = \markup { Vn. }
  c'8
  d'8
  e'8
  f'8
}

abjad> contexttools.get_instrument_mark_attached_to_component(staff)
InstrumentMark('Violin ', 'Vn. ') (Staff{4})
```

Return instrument mark.

Raise missing mark error when no instrument mark attaches to *component*.

contexttools.get_time_signature_mark_attached_to_component

`abjad.tools.contexttools.get_time_signature_mark_attached_to_component` (*component*)
 New in version 2.0. Get time signature mark attached to *component*:

```
abjad> measure = Measure((4, 8), "c'8 d'8 e'8 f'8")

abjad> f(measure)
{
  \time 4/8
  c'8
  d'8
  e'8
  f'8
}

abjad> contexttools.get_time_signature_mark_attached_to_component(measure)
TimeSignatureMark(4, 8) (|4/8, c'8, d'8, e'8, f'8|)
```

Return time signature mark.

Raise missing mark error when no time signature mark attaches to *component*.

contexttools.is_component_with_context_mark_attached

`abjad.tools.contexttools.is_component_with_context_mark_attached` (*component*,
klases=(*<class*
 'ab-
 jad.tools.contexttools.ContextMark.C
))

New in version 2.0. True when context mark of *klases* attaches to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.TimeSignatureMark(4, 8)(staff[0])
TimeSignatureMark(4, 8) (c'8)
abjad> f(staff)
\new Staff {
```

```

\time 4/8
c'8
d'8
e'8
f'8
}
abjad> contexttools.is_component_with_context_mark_attached(staff[0])
True

```

Otherwise false:

```

abjad> contexttools.is_component_with_context_mark_attached(staff)
False

```

Return boolean.

contexttools.is_component_with_time_signature_mark_attached

`abjad.tools.contexttools.is_component_with_time_signature_mark_attached(component)`
 New in version 2.0. True when time signature mark attaches to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.TimeSignatureMark(4, 8)(staff[0])
TimeSignatureMark(4, 8)(c'8)

abjad> f(staff)
\new Staff {
  \time 4/8
  c'8
  d'8
  e'8
  f'8
}

abjad> contexttools.is_component_with_time_signature_mark_attached(staff[0])
True

```

Otherwise false:

```

abjad> contexttools.is_component_with_time_signature_mark_attached(staff)
False

```

Return boolean.

contexttools.iterate_contexts_backward_in_expr

`abjad.tools.contexttools.iterate_contexts_backward_in_expr(expr, start=0, stop=None)`

New in version 2.0. Iterate contexts backward in *expr*:

```

abjad> staff = Staff([Voice("c'8 d'8"), Voice("e'8 f'8 g'8")])
abjad> Tuplet(Fraction(2, 3), staff[1][:])
Tuplet(2/3, [e'8, f'8, g'8])
abjad> staff.is_parallel = True

abjad> f(staff)
\new Staff <<

```

```

        \new Voice {
            c'8
            d'8
        }
        \new Voice {
            \times 2/3 {
                e'8
                f'8
                g'8
            }
        }
    }
>>

```

```

abjad> for x in contexttools.iterate_contexts_backward_in_expr(staff):
...     x
Staff<<2>>
Voice{1}
Voice{2}

```

Ignore threads.

Return generator.

contexttools.iterate_contexts_forward_in_expr

`abjad.tools.contexttools.iterate_contexts_forward_in_expr(expr, start=0, stop=None)`

New in version 2.0. Iterate contexts forward in *expr*:

```

abjad> staff = Staff([Voice("c'8 d'8"), Voice("e'8 f'8 g'8")])
abjad> Tuplet(Fraction(2, 3), staff[1][:])
Tuplet(2/3, [e'8, f'8, g'8])
abjad> staff.is_parallel = True

```

```

abjad> f(staff)
\new Staff <<
  \new Voice {
    c'8
    d'8
  }
  \new Voice {
    \times 2/3 {
      e'8
      f'8
      g'8
    }
  }
>>

```

```

abjad> for x in contexttools.iterate_contexts_forward_in_expr(staff):
...     x
Staff<<2>>
Voice{2}
Voice{1}

```

Ignore threads.

Return generator.

contexttools.set_accidental_style_on_sequential_contexts_in_expr

```
abjad.tools.contexttools.set_accidental_style_on_sequential_contexts_in_expr(expr,
                                                                            ac-
                                                                            ci-
                                                                            den-
                                                                            tal_style)
```

New in version 2.0. Set *accidental_style* for sequential semantic contexts in *expr*:

```
abjad> score = Score(Staff("c'8 d'8") * 2)
abjad> contexttools.set_accidental_style_on_sequential_contexts_in_expr(score, 'forget')

abjad> f(score)
\new Score <<
  \new Staff {
    # (set-accidental-style 'forget)
    c'8
    d'8
  }
  \new Staff {
    # (set-accidental-style 'forget)
    c'8
    d'8
  }
>>
```

Skip nonsemantic contexts.

Function looks like a hack but isn't. LilyPond uses the dedicated command shown here to set accidental style. This means that it is not possible to set accidental style on a top-level context like *score* with a single override.

gracetools

gracetools.Grace

```
class abjad.tools.gracetools.Grace(music=None, kind='grace', **kwargs)
    Bases: abjad.tools.containertools.Container.Container.Container
```

Abjad model of grace music:

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(voice[:])
BeamSpanner(c'8, d'8, e'8, f'8)

abjad> f(voice)
\new Voice {
  c'8 [
  d'8
  e'8
  f'8 ]
}

abjad> grace_notes = [Note("c'16"), Note("d'16")]
abjad> gracetools.Grace(grace_notes, kind = 'grace')(voice[1])
Note("d'8")

abjad> f(voice)
\new Voice {
```

```

c'8 [
  \grace {
    c'16
    d'16
  }
  d'8
  e'8
  f'8 ]
}

abjad> after_grace_notes = [Note("e'16"), Note("f'16")]
abjad> gracetools.Grace(after_grace_notes, kind = 'after')(voice[1])
Note("d'8")

abjad> f(voice)
\new Voice {
  c'8 [
    \grace {
      c'16
      d'16
    }
    \afterGrace
    d'8
    {
      e'16
      f'16
    }
  ]
  e'8
  f'8 ]
}

```

Grace objects are containers you can fill with notes, rests and chords.

Grace containers override the special `__call__` method.

Use `Grace()` to attach grace containers to nongrace notes, rests and chords.

detach()

Detach grace container from leaf:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> grace_container = gracetools.Grace([Note("cs'16")], kind = 'grace')
abjad> grace_container(staff[1])
Note("d'8")
abjad> f(staff)
\new Staff {
  c'8
  \grace {
    cs'16
  }
  d'8
  e'8
  f'8
}

abjad> grace_container.detach()
Grace()
abjad> f(staff)
\new Staff {
  c'8

```



```

    d'8
    e'8
    f'8
}

```

Return grace container.

kind

Get *kind* of grace container:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> gracetools.Grace([Note("cs'16")], kind = 'grace')(staff[1])
Note("d'8")
abjad> grace_container = staff[1].grace
abjad> grace_container.kind
'grace'

```

Return string.

Set *kind* of grace container:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> gracetools.Grace([Note("cs'16")], kind = 'grace')(staff[1])
Note("d'8")
abjad> grace_container = staff[1].grace
abjad> grace_container.kind = 'acciaccatura'
abjad> grace_container.kind
'acciaccatura'

```

Set string.

Valid options include 'after', 'grace', 'acciaccatura', 'appoggiatura'.

gracetools.detach_grace_containers_attached_to_leaf

`abjad.tools.gracetools.detach_grace_containers_attached_to_leaf(leaf)`

New in version 2.0. Detach grace containers attached to *leaf*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> grace_container = gracetools.Grace([Note("cs'16")], kind = 'grace')
abjad> grace_container(staff[1])
Note("d'8")

abjad> f(staff)
\new Staff {
    c'8
    \grace {
        cs'16
    }
    d'8
    e'8
    f'8
}

abjad> gracetools.get_grace_containers_attached_to_leaf(staff[1])
(Grace(cs'16),)

abjad> gracetools.detach_grace_containers_attached_to_leaf(staff[1])
(Grace(),)

```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
}

abjad> gracetools.get_grace_containers_attached_to_leaf(staff[1])
()
```

Return tuple.

gracetools.get_grace_containers_attached_to_leaf

`abjad.tools.gracetools.get_grace_containers_attached_to_leaf(leaf)`

New in version 2.0. Get grace containers attached to leaf:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> gracetools.Grace([Note("cs'16")], kind = 'grace')(staff[1])
Note("d'8")
abjad> gracetools.Grace([Note("ds'16")], kind = 'after')(staff[1])
Note("d'8")

abjad> f(staff)
\new Staff {
    c'8
    \grace {
        cs'16
    }
    \afterGrace
    d'8
    {
        ds'16
    }
    e'8
    f'8
}

abjad> gracetools.get_grace_containers_attached_to_leaf(staff[1])
(Grace(cs'16), Grace(ds'16))
```

Return tuple.

gracetools.iterate_components_and_grace_containers_forward_in_expr

`abjad.tools.gracetools.iterate_components_and_grace_containers_forward_in_expr(expr, klass)`

Iterate components of *klass* forward in *expr*:

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(voice[:])
BeamSpanner(c'8, d'8, e'8, f'8)

abjad> grace_notes = [Note("c'16"), Note("d'16")]
abjad> gracetools.Grace(grace_notes, kind = 'grace')(voice[1])
Note("d'8")
```

```

abjad> after_grace_notes = [Note("e'16"), Note("f'16")]
abjad> gracetools.Grace(after_grace_notes, kind = 'after')(voice[1])
Note("d'8")

abjad> f(voice)
\new Voice {
  c'8 [
    \grace {
      c'16
      d'16
    }
    \afterGrace
    d'8
    {
      e'16
      f'16
    }
  ]
  e'8
  f'8 ]
}

abjad> for note in gracetools.iterate_components_and_grace_containers_forward_in_expr(voice, Note)
...     note
...
Note("c'8")
Note("c'16")
Note("d'16")
Note("d'8")
Note("e'16")
Note("f'16")
Note("e'8")
Note("f'8")

```

Include grace leaves before main leaves.

Include grace leaves after main leaves. Changed in version 2.0: renamed `iterate.grace()` to `componenttools.iterate_components_and_grace_containers_forward_in_expr()`.

instrumenttools

instrumenttools.Accordion

```

class abjad.tools.instrumenttools.Accordion(instrument_name='Accordion',
                                             short_instrument_name='Acc.',          tar-
                                             get_context=None)

Bases: abjad.tools.instrumenttools._KeyboardInstrument._KeyboardInstrument._KeyboardInst
abjad.tools.instrumenttools._ReedInstrument._ReedInstrument._ReedInstrument

```

Abjad model of the accordion:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Accordion(target_context = Staff)(staff)
Accordion('Accordion', 'Acc.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Accordion }

```

```

        \set Staff.shortInstrumentName = \markup { Acc. }
        c'8
        d'8
        e'8
        f'8
    }

```

The accordion targets piano staff context by default.

instrumenttools.AltoFlute

```

class abjad.tools.instrumenttools.AltoFlute (instrument_name='Alto           Flute',
                                              short_instrument_name='Alt.   Fl.', tar-
                                              get_context=None)
Bases: abjad.tools.instrumenttools.Flute.Flute.Flute

```

Abjad model of the alto flute:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.AltoFlute()(staff)
AltoFlute('Alto Flute', 'Alt. Fl.')(Staff{4})

abjad> f(staff)
\new Staff {
    \set Staff.instrumentName = \markup { Alto Flute }
    \set Staff.shortInstrumentName = \markup { Alt. Fl. }
    c'8
    d'8
    e'8
    f'8
}

```

The alto flute targets staff context by default.

instrumenttools.BassClarinet

```

class abjad.tools.instrumenttools.BassClarinet (instrument_name='Bass           Clarinet',
                                                  short_instrument_name='Bass   Cl.', tar-
                                                  get_context=None)
Bases: abjad.tools.instrumenttools.Clarinet.Clarinet.Clarinet New in version 2.0.

```

Abjad model of the bass clarinet:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.BassClarinet()(staff)
BassClarinet('Bass Clarinet', 'Bass Cl.')(Staff{4})

abjad> f(staff)
\new Staff {
    \set Staff.instrumentName = \markup { Bass Clarinet }
    \set Staff.shortInstrumentName = \markup { Bass Cl. }
    c'8
    d'8
    e'8
    f'8
}

```

The bass clarinet targets staff context by default.

instrumenttools.BassFlute

```
class abjad.tools.instrumenttools.BassFlute(instrument_name='Bass Flute',
                                           short_instrument_name='Bass Fl.',
                                           get_context=None)
    Bases: abjad.tools.instrumenttools.Flute.Flute.Flute
    New in version 2.0. Abjad model of the bass flute:

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.BassFlute()(staff)
BassFlute('Bass Flute', 'Bass Fl.')(Staff{4})

abjad> f(staff)
\new Staff {
    \set Staff.instrumentName = \markup { Bass Flute }
    \set Staff.shortInstrumentName = \markup { Bass Fl. }
    c'8
    d'8
    e'8
    f'8
}
```

The bass flute targets staff context by default.

instrumenttools.Bassoon

```
class abjad.tools.instrumenttools.Bassoon(instrument_name='Bassoon',
                                           short_instrument_name='Bsn.',
                                           get_context=None)
    Bases: abjad.tools.instrumenttools._DoubleReedInstrument._DoubleReedInstrument._DoubleReedInstrument
    New in version 2.0. Abjad model of the bassoon:

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('bass')(staff)
ClefMark('bass')(Staff{4})

abjad> instrumenttools.Bassoon()(staff)
Bassoon('Bassoon', 'Bsn.')(Staff{4})

abjad> f(staff)
\new Staff {
    \clef "bass"
    \set Staff.instrumentName = \markup { Bassoon }
    \set Staff.shortInstrumentName = \markup { Bsn. }
    c'8
    d'8
    e'8
    f'8
}
```

The bassoon targets staff context by default.

instrumenttools.Cello

class abjad.tools.instrumenttools.**Cello** (*instrument_name='Cello',*
short_instrument_name='Vc.', target_context=None)
Bases: abjad.tools.instrumenttools._StringInstrument._StringInstrument._StringInstrument
New in version 2.0. Abjad model of the cello:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('bass')(staff)
ClefMark('bass')(Staff{4})

abjad> instrumenttools.Cello()(staff)
Cello('Cello', 'Vc.')(Staff{4})

abjad> f(staff)
\new Staff {
  \clef "bass"
  \set Staff.instrumentName = \markup { Cello }
  \set Staff.shortInstrumentName = \markup { Vc. }
  c'8
  d'8
  e'8
  f'8
}
```

The cello targets staff context by default.

instrumenttools.Clarinete

class abjad.tools.instrumenttools.**Clarinet** (*instrument_name='Clarinet',*
short_instrument_name='Cl.', target_context=None)
Bases: abjad.tools.instrumenttools._SingleReedInstrument._SingleReedInstrument._SingleReedInstrument
New in version 2.0. Abjad model of the B-flat clarinet:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Clarinete()(staff)
Clarinet('Clarinet', 'Cl.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Clarinete }
  \set Staff.shortInstrumentName = \markup { Cl. }
  c'8
  d'8
  e'8
  f'8
}
```

The clarinete targets staff context by default.

instrumenttools.Contrabass

```

class abjad.tools.instrumenttools.Contrabass (instrument_name='Contrabass',
                                              short_instrument_name='Vb.',      tar-
                                              get_context=None)

Bases: abjad.tools.instrumenttools._StringInstrument._StringInstrument._StringInstrument
New in version 2.0. Abjad model of the contrabass:

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('bass')(staff)
ClefMark('bass')(Staff{4})

abjad> instrumenttools.Contrabass()(staff)
Contrabass('Contrabass', 'Vb.')(Staff{4})

abjad> f(staff)
\new Staff {
  \clef "bass"
  \set Staff.instrumentName = \markup { Contrabass }
  \set Staff.shortInstrumentName = \markup { Vb. }
  c'8
  d'8
  e'8
  f'8
}

```

The contrabass targets staff context by default.

instrumenttools.ContrabassFlute

```

class abjad.tools.instrumenttools.ContrabassFlute (instrument_name='Contrabass Flute',
                                                    short_instrument_name='Cbass Fl.',
                                                    target_context=None)

Bases: abjad.tools.instrumenttools.Flute.Flute.Flute New in version 2.0. Abjad model of
the contrabass flute:

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.ContrabassFlute()(staff)
ContrabassFlute('Contrabass Flute', 'Cbass Fl.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Contrabass Flute }
  \set Staff.shortInstrumentName = \markup { Cbass Fl. }
  c'8
  d'8
  e'8
  f'8
}

```

The contrabass flute targets staff context by default.

instrumenttools.Contrabassoon

```
class abjad.tools.instrumenttools.Contrabassoon(instrument_name='Contrabassoon',
                                              short_instrument_name='Contrabsn.',
                                              target_context=None)
```

Bases: abjad.tools.instrumenttools.Bassoon.Bassoon.Bassoon New in version 2.0. Abjad model of the contrabassoon:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('bass')(staff)
ClefMark('bass')(Staff{4})

abjad> instrumenttools.Contrabassoon()(staff)
Contrabassoon('Contrabassoon', 'Contrabsn.')(Staff{4})

abjad> f(staff)
\new Staff {
  \clef "bass"
  \set Staff.instrumentName = \markup { Contrabassoon }
  \set Staff.shortInstrumentName = \markup { Contrabsn. }
  c'8
  d'8
  e'8
  f'8
}
```

The contrabassoon targets staff context by default.

instrumenttools.EFlatClarinet

```
class abjad.tools.instrumenttools.EFlatClarinet(instrument_name='Clarinet in E-flat',
                                              short_instrument_name='Cl. E-flat',
                                              target_context=None)
```

Bases: abjad.tools.instrumenttools.Clarinet.Clarinet.Clarinet New in version 2.0. Abjad model of the E-flat clarinet:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.EFlatClarinet()(staff)
EFlatClarinet('Clarinet in E-flat', 'Cl. E-flat')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Clarinet in E-flat }
  \set Staff.shortInstrumentName = \markup { Cl. E-flat }
  c'8
  d'8
  e'8
  f'8
}
```

The E-flat clarinet targets staff context by default.

instrumenttools.EnglishHorn

```
class abjad.tools.instrumenttools.EnglishHorn(instrument_name='English      Horn',
                                              short_instrument_name='Eng.  hn.', tar-
                                              get_context=None)
    Bases: abjad.tools.instrumenttools.Oboe.Oboe.Oboe
    New in version 2.0. Abjad model of the English horn:

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.EnglishHorn()(staff)
EnglishHorn('English Horn', 'Eng. hn.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { English Horn }
  \set Staff.shortInstrumentName = \markup { Eng. hn. }
  c'8
  d'8
  e'8
  f'8
}
```

The English horn targets staff context by default.

instrumenttools.Flute

```
class abjad.tools.instrumenttools.Flute(instrument_name='Flute',
                                         short_instrument_name='Fl.', target_context=None)
    Bases: abjad.tools.instrumenttools._WindInstrument._WindInstrument._WindInstrument
    New in version 2.0. Abjad model of the flute:

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Flute()(staff)
Flute('Flute', 'Fl.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Flute }
  \set Staff.shortInstrumentName = \markup { Fl. }
  c'8
  d'8
  e'8
  f'8
}
```

The flute targets staff context by default.

instrumenttools.FrenchHorn

```
class abjad.tools.instrumenttools.FrenchHorn(instrument_name='French      Horn',
                                              short_instrument_name='Fr.  hn.', tar-
                                              get_context=None)
    Bases: abjad.tools.instrumenttools._BrassInstrument._BrassInstrument._BrassInstrument,
            abjad.tools.instrumenttools._WindInstrument._WindInstrument._WindInstrument
    New in version 2.0. Abjad model of the French horn:
```

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.FrenchHorn()(staff)
FrenchHorn('French Horn', 'Fr. hn.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { French Horn }
  \set Staff.shortInstrumentName = \markup { Fr. hn. }
  c'8
  d'8
  e'8
  f'8
}

```

The French horn targets staff context by default.

instrumenttools.Glockenspiel

```

class abjad.tools.instrumenttools.Glockenspiel(instrument_name='Glockenspiel',
                                                short_instrument_name='Gkspl.',      tar-
                                                get_context=None)
Bases: abjad.tools.instrumenttools._PercussionInstrument._PercussionInstrument._PercussionInstrument
New in version 2.0. Abjad model of the glockenspiel:

```

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Glockenspiel()(staff)
Glockenspiel('Glockenspiel', 'Gkspl.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Glockenspiel }
  \set Staff.shortInstrumentName = \markup { Gkspl. }
  c'8
  d'8
  e'8
  f'8
}

```

The glockenspiel targets staff context by default.

instrumenttools.Guitar

```

class abjad.tools.instrumenttools.Guitar(instrument_name='Guitar',
                                           short_instrument_name='Gt.',      tar-
                                           get_context=None)
Bases: abjad.tools.instrumenttools._StringInstrument._StringInstrument._StringInstrument
New in version 2.0. Abjad model of the guitar:

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Guitar()(staff)
Guitar('Guitar', 'Gt.')(Staff{4})

```

```

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Guitar }
  \set Staff.shortInstrumentName = \markup { Gt. }
  c'8
  d'8
  e'8
  f'8
}

```

The guitar targets staff context by default.

instrumenttools.Harp

class abjad.tools.instrumenttools.**Harp** (*instrument_name='Harp',*
short_instrument_name='Hp.', target_context=None)
 Bases: abjad.tools.instrumenttools._StringInstrument._StringInstrument._StringInstrument
 New in version 2.0. Abjad model of the harp:

```

abjad> piano_staff = scoretools.PianoStaff([Staff("c'8 d'8 e'8 f'8"), Staff("c'4 b4")])

abjad> instrumenttools.Harp()(piano_staff)
Harp('Harp', 'Hp.')(PianoStaff<<2>>)

abjad> f(piano_staff)
\new PianoStaff <<
  \set PianoStaff.instrumentName = \markup { Harp }
  \set PianoStaff.shortInstrumentName = \markup { Hp. }
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
  \new Staff {
    c'4
    b4
  }
>>

```

The harp targets piano staff context by default.

instrumenttools.Marimba

class abjad.tools.instrumenttools.**Marimba** (*instrument_name='Marimba',*
short_instrument_name='Mb.', target_context=None)
 Bases: abjad.tools.instrumenttools._PercussionInstrument._PercussionInstrument._PercussionInstrument
 New in version 2.0. Abjad model of the marimba:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Marimba()(staff)
Marimba('Marimba', 'Mb.')(Staff{4})

```

```
abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Marimba }
  \set Staff.shortInstrumentName = \markup { Mb. }
  c'8
  d'8
  e'8
  f'8
}
```

The marimba targets staff context by default.

instrumenttools.Oboe

class abjad.tools.instrumenttools.**Oboe** (*instrument_name='Oboe',*
short_instrument_name='Ob.', target_context=None)
 Bases: abjad.tools.instrumenttools._DoubleReedInstrument._DoubleReedInstrument._DoubleReedInstrument
 New in version 2.0. Abjad model of the oboe:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Oboe()(staff)
Oboe('Oboe', 'Ob.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Oboe }
  \set Staff.shortInstrumentName = \markup { Ob. }
  c'8
  d'8
  e'8
  f'8
}
```

The oboe targets staff context by default.

instrumenttools.Piano

class abjad.tools.instrumenttools.**Piano** (*instrument_name='Piano',*
short_instrument_name='Pf.', target_context=None)
 Bases: abjad.tools.instrumenttools._KeyboardInstrument._KeyboardInstrument._KeyboardInstrument
 New in version 2.0. Abjad model of the piano:

```
abjad> piano_staff = scoretools.PianoStaff([Staff("c'8 d'8 e'8 f'8"), Staff("c'4 b4")])

abjad> instrumenttools.Piano()(piano_staff)
Piano('Piano', 'Pf.')(PianoStaff<<2>>>)

abjad> f(piano_staff)
\new PianoStaff <<
  \set PianoStaff.instrumentName = \markup { Piano }
  \set PianoStaff.shortInstrumentName = \markup { Pf. }
  \new Staff {
    c'8
    d'8
    e'8
```

```

        f'8
    }
    \new Staff {
        c'4
        b4
    }
>>

```

The piano target piano staff context by default.

instrumenttools.Piccolo

class abjad.tools.instrumenttools.**Piccolo** (*instrument_name='Piccolo',*
short_instrument_name='Picc.', *tar-*
get_context=None)
Bases: abjad.tools.instrumenttools.Flute.Flute.Flute New in version 2.0. Abjad model of the piccolo:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Piccolo()(staff)
Piccolo('Piccolo', 'Picc.')(Staff{4})

abjad> f(staff)
\new Staff {
    \set Staff.instrumentName = \markup { Piccolo }
    \set Staff.shortInstrumentName = \markup { Picc. }
    c'8
    d'8
    e'8
    f'8
}

```

The piccolo targets staff context by default.

instrumenttools.Trombone

class abjad.tools.instrumenttools.**Trombone** (*instrument_name='Trombone',*
short_instrument_name='Trb.', *tar-*
get_context=None)
Bases: abjad.tools.instrumenttools._BrassInstrument._BrassInstrument._BrassInstrument New in version 2.0. Abjad model of the trombone:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('bass')(staff)
ClefMark('bass')(Staff{4})

abjad> instrumenttools.Trombone()(staff)
Trombone('Trombone', 'Trb.')(Staff{4})

abjad> f(staff)
\new Staff {
    \clef "bass"
    \set Staff.instrumentName = \markup { Trombone }
    \set Staff.shortInstrumentName = \markup { Trb. }
    c'8

```

```

        d'8
        e'8
        f'8
    }

```

The trombone targets staff context by default.

instrumenttools.Trumpet

```

class abjad.tools.instrumenttools.Trumpet (instrument_name='Trumpet',
                                           short_instrument_name='Tp.',
                                           target_context=None)
    Bases: abjad.tools.instrumenttools._BrassInstrument._BrassInstrument
    New in version 2.0. Abjad model of the trumpet:

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Trumpet()(staff)
Trumpet('Trumpet', 'Tp.')(Staff{4})

abjad> f(staff)
\new Staff {
    \set Staff.instrumentName = \markup { Trumpet }
    \set Staff.shortInstrumentName = \markup { Tp. }
    c'8
    d'8
    e'8
    f'8
}

```

The trumpet targets staff context by default.

instrumenttools.Tuba

```

class abjad.tools.instrumenttools.Tuba (instrument_name='Tuba',
                                         short_instrument_name='Tb.',
                                         target_context=None)
    Bases: abjad.tools.instrumenttools._BrassInstrument._BrassInstrument
    New in version 2.0. Abjad model of the tuba:

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('bass')(staff)
ClefMark('bass')(Staff{4})

abjad> instrumenttools.Tuba()(staff)
Tuba('Tuba', 'Tb.')(Staff{4})

abjad> f(staff)
\new Staff {
    \clef "bass"
    \set Staff.instrumentName = \markup { Tuba }
    \set Staff.shortInstrumentName = \markup { Tb. }
    c'8
    d'8
    e'8
    f'8
}

```

The tuba targets staff context by default.

instrumenttools.UntunedPercussion

```
class abjad.tools.instrumenttools.UntunedPercussion (instrument_name='Percussion',  
                                                    short_instrument_name='Perc.',  
                                                    target_context=None)  
  
Bases: abjad.tools.instrumenttools._PercussionInstrument._PercussionInstrument._PercussionInstrument  
New in version 2.0. Abjad model of untuned percussion:
```

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")  
  
abjad> instrumenttools.UntunedPercussion()(staff)  
UntunedPercussion('Percussion', 'Perc.')(Staff{4})  
  
abjad> f(staff)  
\new Staff {  
  \set Staff.instrumentName = \markup { Percussion }  
  \set Staff.shortInstrumentName = \markup { Perc. }  
  c'8  
  d'8  
  e'8  
  f'8  
}
```

Untuned percussion targets the staff context by default.

instrumenttools.Vibraphone

```
class abjad.tools.instrumenttools.Vibraphone (instrument_name='Vibraphone',  
                                                    short_instrument_name='Vibr.', tar-  
                                                    get_context=None)  
  
Bases: abjad.tools.instrumenttools._PercussionInstrument._PercussionInstrument._PercussionInstrument  
New in version 2.0. Abjad model of the vibraphone:
```

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")  
  
abjad> instrumenttools.Vibraphone()(staff)  
Vibraphone('Vibraphone', 'Vibr.')(Staff{4})  
  
abjad> f(staff)  
\new Staff {  
  \set Staff.instrumentName = \markup { Vibraphone }  
  \set Staff.shortInstrumentName = \markup { Vibr. }  
  c'8  
  d'8  
  e'8  
  f'8  
}
```

The vibraphone targets staff context by default.

instrumenttools.Viola

```
class abjad.tools.instrumenttools.Viola(instrument_name='Viola',
                                         short_instrument_name='Va.', target_context=None)
    Bases: abjad.tools.instrumenttools._StringInstrument._StringInstrument._StringInstrument
    New in version 2.0. Abjad model of the viola:

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('alto')(staff)
ClefMark('alto')(Staff{4})

abjad> instrumenttools.Viola()(staff)
Viola('Viola', 'Va.')(Staff{4})

abjad> f(staff)
\new Staff {
    \clef "alto"
    \set Staff.instrumentName = \markup { Viola }
    \set Staff.shortInstrumentName = \markup { Va. }
    c'8
    d'8
    e'8
    f'8
}
```

The viola targets staff context by default.

instrumenttools.Violin

```
class abjad.tools.instrumenttools.Violin(instrument_name='Violin',
                                          short_instrument_name='Vn.', tar-
                                          get_context=None)
    Bases: abjad.tools.instrumenttools._StringInstrument._StringInstrument._StringInstrument
    New in version 2.0. Abjad model of the violin:

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Violin()(staff)
Violin('Violin', 'Vn.')(Staff{4})

abjad> f(staff)
\new Staff {
    \set Staff.instrumentName = \markup { Violin }
    \set Staff.shortInstrumentName = \markup { Vn. }
    c'8
    d'8
    e'8
    f'8
}
```

The violin targets staff context by default.

instrumenttools.Xylophone

class abjad.tools.instrumenttools.**Xylophone** (*instrument_name='Xylophone',*
short_instrument_name='Xyl.', *target_instrument_name='PercussionInstrument',*
get_context=None)

Bases: abjad.tools.instrumenttools._PercussionInstrument._PercussionInstrument, _PercussionInstrument

New in version 2.0. Abjad model of the xylophone:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> instrumenttools.Xylophone()(staff)
Xylophone('Xylophone', 'Xyl.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Xylophone }
  \set Staff.shortInstrumentName = \markup { Xyl. }
  c'8
  d'8
  e'8
  f'8
}
```

The xylophone targets staff context by default.

instrumenttools.iterate_notes_and_chords_in_expr_outside_traditional_instrument_ranges

abjad.tools.instrumenttools.iterate_notes_and_chords_in_expr_outside_traditional_instrument_ranges (*expr*)
 New in version 2.0. Iterate notes and chords in *expr* outside traditional instrument ranges:

```
abjad> staff = Staff("c'8 r8 <d fs>8 r8")
abjad> instrumenttools.Violin()(staff)
Violin('Violin', 'Vn.')(Staff{4})

abjad> for note_or_chord in instrumenttools.iterate_notes_and_chords_in_expr_outside_traditional_instrument_ranges(staff):
...     note_or_chord
Chord('<d fs>8')
```

Return generator.

instrumenttools.notes_and_chords_in_expr_are_on_expected_clefs

abjad.tools.instrumenttools.notes_and_chords_in_expr_are_on_expected_clefs (*expr*, *percussion_clef_is_allowed*)
 New in version 2.0. True when notes and chords in *expr* are on expected clefs:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('treble')(staff)
ClefMark('treble')(Staff{4})
abjad> instrumenttools.Violin()(staff)
Violin('Violin', 'Vn.')(Staff{4})

abjad> instrumenttools.notes_and_chords_in_expr_are_on_expected_clefs(staff)
True
```

False otherwise:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('alto')(staff)
ClefMark('alto')(Staff{4})
abjad> instrumenttools.Violin()(staff)
Violin('Violin', 'Vn.')(Staff{4})

abjad> instrumenttools.notes_and_chords_in_expr_are_on_expected_clefs(staff)
False
```

Allow percussion clef when *percussion_clef_is_allowed* is true:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.ClefMark('percussion')(staff)
ClefMark('percussion')(Staff{4})
abjad> instrumenttools.Violin()(staff)
Violin('Violin', 'Vn.')(Staff{4})

abjad> f(staff)
\new Staff {
  \clef "percussion"
  \set Staff.instrumentName = \markup { Violin }
  \set Staff.shortInstrumentName = \markup { Vn. }
  c'8
  d'8
  e'8
  f'8
}

abjad> instrumenttools.notes_and_chords_in_expr_are_on_expected_clefs(staff, percussion_clef_is_
True
```

Disallow percussion clef when *percussion_clef_is_allowed* is false:

```
abjad> instrumenttools.notes_and_chords_in_expr_are_on_expected_clefs(staff, percussion_clef_is_
False
```

Return boolean.

instrumenttools.notes_and_chords_in_expr_are_within_traditional_instrument_ranges

`abjad.tools.instrumenttools.notes_and_chords_in_expr_are_within_traditional_instrument_ranges`

New in version 2.0. True when notes and chords in *expr* are within traditional instrument ranges:

```
abjad> staff = Staff("c'8 r8 <d' fs'>8 r8")
abjad> instrumenttools.Violin()(staff)
Violin('Violin', 'Vn.')(Staff{4})

abjad> instrumenttools.notes_and_chords_in_expr_are_within_traditional_instrument_ranges(staff)
True
```

False otherwise:

```
abjad> staff = Staff("c'8 r8 <d fs>8 r8")
abjad> instrumenttools.Violin()(staff)
Violin('Violin', 'Vn.')(Staff{4})
```

```
abjad> instrumenttools.notes_and_chords_in_expr_are_within_traditional_instrument_ranges(staff)
False
```

Return boolean.

instrumenttools.transpose_notes_and_chords_in_expr_from_fingered_pitch_to_sounding_pitch

abjad.tools.instrumenttools.transpose_notes_and_chords_in_expr_from_fingered_pitch_to_sounding_pitch

New in version 2.0. Transpose notes and chords in *expr* from sounding pitch to fingered pitch:

```
abjad> staff = Staff("<c' e' g'>4 d'4 r4 e'4")
abjad> instrumenttools.Clarinet()(staff)
Clarinet('Clarinet', 'Cl.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Clarinet }
  \set Staff.shortInstrumentName = \markup { Cl. }
  <c' e' g'>4
  d'4
  r4
  e'4
}

abjad> for leaf in staff.leaves:
...   leaf.written_pitch_indication_is_at_sounding_pitch = False

abjad> instrumenttools.transpose_notes_and_chords_in_expr_from_fingered_pitch_to_sounding_pitch(staff)

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Clarinet }
  \set Staff.shortInstrumentName = \markup { Cl. }
  <bf d' f'>4
  c'4
  r4
  d'4
}
```

Return none.

instrumenttools.transpose_notes_and_chords_in_expr_from_sounding_pitch_to_fingered_pitch

abjad.tools.instrumenttools.transpose_notes_and_chords_in_expr_from_sounding_pitch_to_fingered_pitch

New in version 2.0. Transpose notes and chords in *expr* from sounding pitch to fingered pitch:

```
abjad> staff = Staff("<c' e' g'>4 d'4 r4 e'4")
abjad> instrumenttools.Clarinet()(staff)
Clarinet('Clarinet', 'Cl.')(Staff{4})

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Clarinet }
  \set Staff.shortInstrumentName = \markup { Cl. }
  <c' e' g'>4
  d'4
```

```

        r4
        e'4
    }

```

```
abjad> instrumenttools.transpose_notes_and_chords_in_expr_from_sounding_pitch_to_fingered_pitch(
```

```

abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Clarinet }
  \set Staff.shortInstrumentName = \markup { Cl. }
  <d' fs' a'>4
  e'4
  r4
  fs'4
}

```

Return none.

leaftools

leaftools.change_written_leaf_duration_and_preserve_preprolated_leaf_duration

```
abjad.tools.leaftools.change_written_leaf_duration_and_preserve_preprolated_leaf_duration(
```

New in version 1.1. Change *leaf* written duration to *written_duration* and preserve preprolated *leaf* duration:

```

abjad> note = Note("c'4")
abjad> note.written_duration
Duration(1, 4)
abjad> note.preprolated_duration
Duration(1, 4)

```

```

abjad> leaftools.change_written_leaf_duration_and_preserve_preprolated_leaf_duration(note, Durat
Note("c'8. * 4/3")

```

```

abjad> note.written_duration
Duration(3, 16)
abjad> note.preprolated_duration
Duration(1, 4)

```

Add LilyPond multiplier where necessary.

Return *leaf*. Changed in version 2.0: Renamed from `leaftools.duration_rewrite()`.
`leaftools.change_written_leaf_duration_and_preserve_preprolated_leaf_duration()`.

leaftools.color_leaf

```
abjad.tools.leaftools.color_leaf(leaf, color)
```

New in version 2.0. Color note:

```

abjad> note = Note("c'4")

abjad> leaftools.color_leaf(note, 'red')
Note("c'4")

```

```

abjad> f(note)
\once \override Accidental #'color = #red
\once \override Dots #'color = #red
\once \override NoteHead #'color = #red
c'4

```

Color rest:

```

abjad> rest = Rest('r4')

abjad> leaftools.color_leaf(rest, 'red')
Rest('r4')

abjad> f(rest)
\once \override Dots #'color = #red
\once \override Rest #'color = #red
r4

```

Color chord:

```

abjad> chord = Chord("<c' e' bf'>4")

abjad> leaftools.color_leaf(chord, 'red')
Chord("<c' e' bf'>4")

abjad> f(chord)
\once \override Accidental #'color = #red
\once \override Dots #'color = #red
\once \override NoteHead #'color = #red
<c' e' bf'>4

```

Return *leaf*.

leaftools.color_leaves_in_expr

`abjad.tools.leaftools.color_leaves_in_expr(expr, color)`

New in version 2.0. Color leaves in *expr*:

```

abjad> staff = Staff([Note(1, (3, 16)), Rest((3, 16)), skiptools.Skip((3, 16)), Chord([0, 1, 9],
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(cs'8., r8., s8., <c' cs' a'>8.)
abjad> f(staff)
\new Staff {
  cs'8. [
  r8.
  s8.
  <c' cs' a'>8. ]
}

abjad> leaftools.color_leaves_in_expr(staff, 'red')

abjad> f(staff)
\new Staff {
  \once \override Accidental #'color = #red
  \once \override Dots #'color = #red
  \once \override NoteHead #'color = #red
  cs'8. [
  \once \override Dots #'color = #red

```

```

\once \override Rest #'color = #red
r8.
s8.
\once \override Accidental #'color = #red
\once \override Dots #'color = #red
\once \override NoteHead #'color = #red
<c' cs' a'>8. ]
}

```

Return `none`.

leaftools.copy_written_duration_and_multiplier_from_leaf_to_leaf

`abjad.tools.leaftools.copy_written_duration_and_multiplier_from_leaf_to_leaf`(*source_leaf*, *target_leaf*)

New in version 2.0. Copy written duration and multiplier from *source_leaf* to *target_leaf*:

```

abjad> note = Note("c'4")
abjad> note.duration_multiplier = Duration(1, 2)
abjad> rest = Rest((1, 64))
abjad> leaftools.copy_written_duration_and_multiplier_from_leaf_to_leaf(note, rest)
Rest('r4 * 1/2')

```

Return *target_leaf*.

leaftools.divide_leaf_meiotically

`abjad.tools.leaftools.divide_leaf_meiotically`(*leaf*, *n*=2)

New in version 1.1. Divide *leaf* meiotically *n* times:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}

abjad> leaftools.divide_leaf_meiotically(staff[0], n = 4)

abjad> f(staff)
\new Staff {
    c'32 [
    c'32
    c'32
    c'32
    d'8
    e'8
    f'8 ]
}

```

Replace *leaf* with *n* new leaves.

Preserve parentage and spanners.

Allow divisions into only 1, 2, 4, 8, 16, ... and other nonnegative integer powers of 2.

Produce only leaves and never tuplets or other containers.

Return none.

leaftools.divide_leaves_in_expr_meiotically

`abjad.tools.leaftools.divide_leaves_in_expr_meiotically(expr, n=2)`

New in version 1.1. Divide leaves meiotically in *expr* *n* times:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}

abjad> leaftools.divide_leaves_in_expr_meiotically(staff[2:], n = 4)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'32
    e'32
    e'32
    e'32
    f'32
    f'32
    f'32
    f'32 ]
}
```

Replace every leaf in *expr* with *n* new leaves.

Preserve parentage and spanners.

Allow divisions into only 1, 2, 4, 8, 16, ... and other nonnegative integer powers of 2.

Produce only leaves and never tuplets or other containers.

Return none. Changed in version 2.0: renamed `leaftools.meiose()` to `leaftools.divide_leaves_in_expr_meiotically()`.

leaftools.expr_has_leaf_with_dotted_written_duration

`abjad.tools.leaftools.expr_has_leaf_with_dotted_written_duration(expr)`

New in version 2.0. True when *expr* has at least one leaf with dotted writtern duration:

```
abjad> notes = notetools.make_notes([0], [(1, 16), (2, 16), (3, 16)])
abjad> leaftools.expr_has_leaf_with_dotted_written_duration(notes)
True
```

False otherwise:

```
abjad> notes = notetools.make_notes([0], [(1, 16), (2, 16), (4, 16)])
abjad> leaftools.expr_has_leaf_with_dotted_written_duration(notes)
False
```

Return boolean.

leaftools.fuse_leaves_big_endian

`abjad.tools.leaftools.fuse_leaves_big_endian(leaves)`

New in version 1.1. Fuse thread-contiguous *leaves*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> leaftools.fuse_leaves_big_endian(staff[1:])
[Note("d'4.")]
abjad> f(staff)
\new Staff {
    c'8
    d'4.
}
```

Rewrite duration of first leaf in *leaves*.

Detach all leaves in *leaves* other than first leaf from score.

Return list of first leaf in *leaves*. Changed in version 2.0: renamed `fuse.leaves_by_reference()` to `leaftools.fuse_leaves_big_endian()`.

leaftools.fuse_leaves_in_container_once_by_counts_into_big_endian_notes

`abjad.tools.leaftools.fuse_leaves_in_container_once_by_counts_into_big_endian_notes(container, counts)`

New in version 1.1. Fuse leaves in *container* once by *counts* into big-endian notes.

leaftools.fuse_leaves_in_container_once_by_counts_into_big_endian_rests

`abjad.tools.leaftools.fuse_leaves_in_container_once_by_counts_into_big_endian_rests(container, counts)`

New in version 1.1. Fuse leaves in *container* once by *counts* into big-endian rests.

leaftools.fuse_leaves_in_container_once_by_counts_into_little_endian_notes

`abjad.tools.leaftools.fuse_leaves_in_container_once_by_counts_into_little_endian_notes(container, counts)`

New in version 1.1. Fuse leaves in *container* once by *counts* into little-endian notes.

leaftools.fuse_leaves_in_container_once_by_counts_into_little_endian_rests

`abjad.tools.leaftools.fuse_leaves_in_container_once_by_counts_into_little_endian_rests(container, counts)`

New in version 1.1. Fuse leaves in *container* once by *counts* into little-endian rests.

leaftools.fuse_leaves_in_tie_chain_by_immediate_parent_big_endian

`abjad.tools.leaftools.fuse_leaves_in_tie_chain_by_immediate_parent_big_endian(tie_chain)`
 New in version 1.1. Fuse leaves in *tie_chain* by immediate parent:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> tietools.TieSpanner(staff.leaves)
TieSpanner(c'8, c'8, c'8, c'8)
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8 ~
        c'8 ~
    }
    {
        \time 2/8
        c'8 ~
        c'8
    }
}

abjad> tie_chain = tietools.get_tie_chain(staff.leaves[0])
abjad> leaftools.fuse_leaves_in_tie_chain_by_immediate_parent_big_endian(tie_chain)
[[Note("c'4")], [Note("c'4")]]

abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'4 ~
    }
    {
        \time 2/8
        c'4
    }
}
```

Return list of fused notes by parent. Changed in version 2.0: renamed `fuse_leaves_in_tie_chain()` to `leaftools.fuse_leaves_in_tie_chain_by_immediate_parent_big_endian()`.

leaftools.fuse_tied_leaves_in_components_once_by_prolated_durations_without_overhang

`abjad.tools.leaftools.fuse_tied_leaves_in_components_once_by_prolated_durations_without_overhang`

New in version 1.1. Fuse tied leaves in *components* once by *prolated_durations* without overhang:

```
abjad> staff = Staff(notetools.make_repeated_notes(8))
abjad> tietools.TieSpanner(staff.leaves)
TieSpanner(c'8, c'8, c'8, c'8, c'8, c'8, c'8, c'8)
abjad> f(staff)
\new Staff {
    c'8 ~
    c'8 ~
    c'8 ~
    c'8 ~
    c'8 ~
}
```

```

        c'8 ~
        c'8 ~
        c'8
    }

```

```
abjad> leaftools.fuse_tied_leaves_in_components_once_by_prolated_durations_without_overhang(staff)
```

```

abjad> f(staff)
\new Staff {
    c'4. ~
    c'4. ~
    c'8 ~
    c'8
}

```

Return none. Changed in version 2.0: renamed `fuse.tied_leaves_by_prolated_durations()` to `leaftools.fuse_tied_leaves_in_components_once_by_prolated_durations_without_overhang()`.

leaftools.get_composite_offset_difference_series_from_leaves_in_expr

`abjad.tools.leaftools.get_composite_offset_difference_series_from_leaves_in_expr(expr)`

New in version 2.0. Get composite offset difference series from leaves in *expr*:

```

abjad> staff_1 = Staff([tuplettools.FixedDurationTuplet(Duration(4, 8), notetools.make_repeated_
abjad> staff_2 = Staff(notetools.make_repeated_notes(4))
abjad> score = Score([staff_1, staff_2])
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)
abjad> f(score)
\new Score <<
    \new Staff {
        \fraction \times 4/3 {
            c'8
            d'8
            e'8
        }
    }
    \new Staff {
        f'8
        g'8
        a'8
        b'8
    }
>>
abjad> leaftools.get_composite_offset_difference_series_from_leaves_in_expr(score)
[Offset(1, 8), Offset(1, 24), Offset(1, 12), Offset(1, 12), Offset(1, 24), Offset(1, 8)]

```

Composite offset difference series defined equal to time intervals between unique start and stop offsets of leaves in *expr*.

Return list of fractions.

leaftools.get_composite_offset_series_from_leaves_in_expr

`abjad.tools.leaftools.get_composite_offset_series_from_leaves_in_expr(expr)`

New in version 2.0. Get composite offset series from leaves in *expr*:

```

abjad> staff_1 = Staff([tuplettools.FixedDurationTuplet(Duration(4, 8), notetools.make_repeated_
abjad> staff_2 = Staff(notetools.make_repeated_notes(4))
abjad> score = Score([staff_1, staff_2])
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(score)
abjad> f(score)
\new Score <<
  \new Staff {
    \fraction \times 4/3 {
      c'8
      d'8
      e'8
    }
  }
  \new Staff {
    f'8
    g'8
    a'8
    b'8
  }
>>
abjad> leaftools.get_composite_offset_series_from_leaves_in_expr(score)
[Offset(0, 1), Offset(1, 8), Offset(1, 6), Offset(1, 4), Offset(1, 3), Offset(3, 8), Offset(1, 2)]

```

Equal to list of unique start and stop offsets of leaves in *expr*.

Return list of fractions.

leaftools.get_leaf_at_index_in_measure_number_in_expr

```

abjad.tools.leaftools.get_leaf_at_index_in_measure_number_in_expr(expr, measure_number,
                                                                    leaf_index)

```

New in version 2.0. Get leaf at *leaf_index* in *measure_number* in *expr*:

```

abjad> t = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> f(t)
\new Staff {
  {
    \time 2/8
    c'8
    d'8
  }
  {
    \time 2/8
    e'8
    f'8
  }
  {
    \time 2/8
    g'8
    a'8
  }
}

abjad> leaftools.get_leaf_at_index_in_measure_number_in_expr(t, 2, 0)
Note("e'8")

```

Return leaf or none.

leaftools.get_nth_leaf_in_expr

abjad.tools.leaftools.get_nth_leaf_in_expr(expr, n=0)

New in version 2.0. Get n th leaf in *expr*:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
    {
        \time 2/8
        g'8
        a'8
    }
}

abjad> for n in range(6):
...     leaftools.get_nth_leaf_in_expr(staff, n)
...
Note("c'8")
Note("d'8")
Note("e'8")
Note("f'8")
Note("g'8")
Note("a'8")
```

Read backwards for negative values of n .

```
abjad> leaftools.get_nth_leaf_in_expr(staff, -1)
Note("a'8")
```

Note: Because this function returns as soon as it finds instance n of *klases*, it is more efficient to call `leaftools.get_nth_leaf_in_expr(expr, 0)` than `expr.leaves[0]`. It is likewise more efficient to call `leaftools.get_nth_leaf_in_expr(expr, -1)` than `expr.leaves[-1]`.

Return leaf of none.

leaftools.get_nth_leaf_in_thread_from_leaf

abjad.tools.leaftools.get_nth_leaf_in_thread_from_leaf(leaf, n=0)

New in version 2.0. Get n th leaf in thread from *leaf*:

```

abjad> staff = Staff(2 * Voice("c'8 d'8 e'8 f'8"))
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> f(staff)
\new Staff {
  \new Voice {
    c'8
    d'8
    e'8
    f'8
  }
  \new Voice {
    g'8
    a'8
    b'8
    c''8
  }
}

abjad> for n in range(8):
...     print n, leaftools.get_nth_leaf_in_thread_from_leaf(staff[0][0], n)
...
0 c'8
1 d'8
2 e'8
3 f'8
4 None
5 None
6 None
7 None

```

Return leaf or none.

leaftools.is_bar_line_crossing_leaf

abjad.tools.leaftools.**is_bar_line_crossing_leaf**(*leaf*)

New in version 2.0. True when *leaf* crosses bar line:

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> t[2].written_duration *= 2
abjad> contexttools.TimeSignatureMark(2, 8, partial = Duration(1, 8))(t[2])
TimeSignatureMark(2, 8, partial = Duration(1, 8))(e'4)
abjad> f(t)
\new Staff {
  c'8
  d'8
  \partial 8
  \time 2/8
  e'4
  f'8
}
abjad> leaftools.is_bar_line_crossing_leaf(t.leaves[2])
True

```

Otherwise false:

```

abjad> leaftools.is_bar_line_crossing_leaf(t.leaves[3])
False

```

Return boolean.

leaftools.iterate_leaf_pairs_forward_in_expr

abjad.tools.leaftools.**iterate_leaf_pairs_forward_in_expr**(*expr*)

New in version 2.0. Iterate leaf pairs forward in *expr*:

```
abjad> score = Score([ ])
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8"), Note("g'4")]
abjad> score.append(Staff(notes))
abjad> notes = [Note(x, (1, 4)) for x in [-12, -15, -17]]
abjad> score.append(Staff(notes))
abjad> contexttools.ClefMark('bass')(score[1])
ClefMark('bass')(Staff{3})

abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8
    e'8
    f'8
    g'4
  }
  \new Staff {
    \clef "bass"
    c4
    a,4
    g,4
  }
>>

abjad> for pair in leaftools.iterate_leaf_pairs_forward_in_expr(score):
...     pair
(Note("c'8"), Note('c4'))
(Note("c'8"), Note("d'8"))
(Note('c4'), Note("d'8"))
(Note("d'8"), Note("e'8"))
(Note("d'8"), Note('a,4'))
(Note('c4'), Note("e'8"))
(Note('c4'), Note('a,4'))
(Note("e'8"), Note('a,4'))
(Note("e'8"), Note("f'8"))
(Note('a,4'), Note("f'8"))
(Note("f'8"), Note("g'4"))
(Note("f'8"), Note('g,4'))
(Note('a,4'), Note("g'4"))
(Note('a,4'), Note('g,4'))
(Note("g'4"), Note('g,4'))
```

Iterate leaf pairs left-to-right and top-to-bottom.

Return generator.

leaftools.iterate_leaves_backward_in_expr

abjad.tools.leaftools.**iterate_leaves_backward_in_expr**(*expr*, *start*=0, *stop*=None)

New in version 2.0. Iterate leaves backward in *expr*:

```

abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
    {
        \time 2/8
        g'8
        a'8
    }
}

```

```

abjad> for leaf in leaftools.iterate_leaves_backward_in_expr(staff):
...     leaf
...
Note("a'8")
Note("g'8")
Note("f'8")
Note("e'8")
Note("d'8")
Note("c'8")

```

Use the optional *start* and *stop* keyword parameters to control the indices of iteration.

```

abjad> for leaf in leaftools.iterate_leaves_backward_in_expr(staff, start = 3):
...     leaf
...
Note("e'8")
Note("d'8")
Note("c'8")

```

```

abjad> for leaf in leaftools.iterate_leaves_backward_in_expr(staff, start = 0, stop = 3):
...     leaf
...
Note("a'8")
Note("g'8")
Note("f'8")

```

```

abjad> for leaf in leaftools.iterate_leaves_backward_in_expr(staff, start = 2, stop = 4):
...     leaf
...
Note("f'8")
Note("e'8")

```

Ignore threads.

Return generator.

leaftools.iterate_leaves_forward_in_expr

abjad.tools.leaftools.**iterate_leaves_forward_in_expr**(*expr*, *start*=0, *stop*=None)

New in version 2.0. Iterate leaves forward in *expr*:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
    {
        \time 2/8
        g'8
        a'8
    }
}

abjad> for leaf in leaftools.iterate_leaves_forward_in_expr(staff):
...     leaf
...
Note("c'8")
Note("d'8")
Note("e'8")
Note("f'8")
Note("g'8")
Note("a'8")
```

Use the optional *start* and *stop* keyword parameters to control the start and stop indices of iteration.

```
abjad> for leaf in leaftools.iterate_leaves_forward_in_expr(staff, start = 3):
...     leaf
...
Note("f'8")
Note("g'8")
Note("a'8")

abjad> for leaf in leaftools.iterate_leaves_forward_in_expr(staff, start = 0, stop = 3):
...     leaf
...
Note("c'8")
Note("d'8")
Note("e'8")

abjad> for leaf in leaftools.iterate_leaves_forward_in_expr(staff, start = 2, stop = 4):
...     leaf
...
```



```
Note("e'8")
Note("f'8")
```

Ignore threads.

Return generator.

leaftools.iterate_notes_and_chords_backward_in_expr

abjad.tools.leaftools.**iterate_notes_and_chords_backward_in_expr**(*expr*, *start*=0, *stop*=None)

New in version 2.0. Iterate notes and chords backward in *expr*:

```
abjad> staff = Staff("<e' g' c''>8 a'8 r8 <d' f' b'>8 r2")

abjad> f(staff)
\new Staff {
    <e' g' c''>8
    a'8
    r8
    <d' f' b'>8
    r2
}

abjad> for leaf in leaftools.iterate_notes_and_chords_backward_in_expr(staff):
...     leaf
Chord("<d' f' b'>8")
Note("a'8")
Chord("<e' g' c''>8")
```

Ignore threads.

Return generator. Changed in version 2.0: renamed `pitchtools.iterate_notes_and_chords_backward_in_expr` to `leaftools.iterate_notes_and_chords_backward_in_expr()`.

leaftools.iterate_notes_and_chords_forward_in_expr

abjad.tools.leaftools.**iterate_notes_and_chords_forward_in_expr**(*expr*, *start*=0, *stop*=None)

New in version 2.0. Iterate notes and chords forward in *expr*:

```
abjad> staff = Staff("<e' g' c''>8 a'8 r8 <d' f' b'>8 r2")

abjad> f(staff)
\new Staff {
    <e' g' c''>8
    a'8
    r8
    <d' f' b'>8
    r2
}

abjad> for leaf in leaftools.iterate_notes_and_chords_forward_in_expr(staff):
...     leaf
Chord("<e' g' c''>8")
Note("a'8")
Chord("<d' f' b'>8")
```

Ignore threads.

Return generator. Changed in version 2.0: renamed `pitchtools.iterate_notes_and_chords_forward_in_expr()` to `leaftools.iterate_notes_and_chords_forward_in_expr()`.

`leaftools.label_leaves_in_expr_with_inversion_equivalent_chromatic_interval_classes`

`abjad.tools.leaftools.label_leaves_in_expr_with_inversion_equivalent_chromatic_interval_classes`

New in version 2.0. Label leaves in *expr* with inversion-equivalent chromatic interval classes:

```
abjad> staff = Staff(notetools.make_notes([0, 25, 11, -4, -14, -13, 9, 10, 6, 5], [Duration(1, 8)]))
abjad> leaftools.label_leaves_in_expr_with_inversion_equivalent_chromatic_interval_classes(staff)
abjad> f(staff)
\new Staff {
    c'8 ^ \markup { 1 }
    cs''8 ^ \markup { 2 }
    b'8 ^ \markup { 2 }
    af8 ^ \markup { 2 }
    bf,8 ^ \markup { 1 }
    b,8 ^ \markup { 2 }
    a'8 ^ \markup { 1 }
    bf'8 ^ \markup { 4 }
    fs'8 ^ \markup { 1 }
    f'8
}
```

Return none.

`leaftools.label_leaves_in_expr_with_leaf_depth`

`abjad.tools.leaftools.label_leaves_in_expr_with_leaf_depth`(*expr*,
markup_direction='down')

New in version 1.1. Label leaves in *expr* with leaf depth:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8")
abjad> tuplettools.FixedDurationTuplet(Duration(2, 8), staff[-3:])
FixedDurationTuplet(1/4, [e'8, f'8, g'8])
abjad> leaftools.label_leaves_in_expr_with_leaf_depth(staff)
abjad> f(staff)
\new Staff {
    c'8 _ \markup { \small 1 }
    d'8 _ \markup { \small 1 }
    \times 2/3 {
        e'8 _ \markup { \small 2 }
        f'8 _ \markup { \small 2 }
        g'8 _ \markup { \small 2 }
    }
}
```

Changed in version 2.0: renamed `label.leaf_depth()` to `leaftools.label_leaves_in_expr_with_leaf_depth()`.
Return none.

leaftools.label_leaves_in_expr_with_leaf_durations

`abjad.tools.leaftools.label_leaves_in_expr_with_leaf_durations` (*expr*,
markup_direction='down')

New in version 1.1. Label leaves in *expr* with leaf durations:

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(1, 4), "c'8 d'8 e'8")
abjad> leaftools.label_leaves_in_expr_with_leaf_durations(tuplet)
abjad> f(tuplet)
\times 2/3 {
    c'8 _ \markup { \column { \small 1/8 \small 1/12 } }
    d'8 _ \markup { \column { \small 1/8 \small 1/12 } }
    e'8 _ \markup { \column { \small 1/8 \small 1/12 } }
}
```

Label both written duration and prolated duration.

Return none.

leaftools.label_leaves_in_expr_with_leaf_indices

`abjad.tools.leaftools.label_leaves_in_expr_with_leaf_indices` (*expr*,
markup_direction='down')

New in version 2.0. Label leaves in *expr* with leaf indices:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> leaftools.label_leaves_in_expr_with_leaf_indices(staff)
abjad> f(staff)
\new Staff {
    c'8 _ \markup { \small 0 }
    d'8 _ \markup { \small 1 }
    e'8 _ \markup { \small 2 }
    f'8 _ \markup { \small 3 }
}
```

Return none.

leaftools.label_leaves_in_expr_with_leaf_numbers

`abjad.tools.leaftools.label_leaves_in_expr_with_leaf_numbers` (*expr*,
markup_direction='down')

New in version 1.1. Label leaves in *expr* with leaf numbers:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> leaftools.label_leaves_in_expr_with_leaf_numbers(staff)
abjad> f(staff)
\new Staff {
    c'8 _ \markup { \small 1 }
    d'8 _ \markup { \small 2 }
    e'8 _ \markup { \small 3 }
    f'8 _ \markup { \small 4 }
}
```

Number leaves starting from 1. Changed in version 2.0: renamed `label.leaf_numbers()` to `leaftools.label_leaves_in_expr_with_leaf_numbers()`. Return none.

leaftools.label_leaves_in_expr_with_melodic_chromatic_interval_classes

abjad.tools.leaftools.**label_leaves_in_expr_with_melodic_chromatic_interval_classes**(*expr*, *markup_direction*)

New in version 2.0. Label leaves in *expr* with melodic chromatic interval classes:

```
abjad> staff = Staff(notetools.make_notes([0, 25, 11, -4, -14, -13, 9, 10, 6, 5], [Duration(1, 8)
abjad> leaftools.label_leaves_in_expr_with_melodic_chromatic_interval_classes(staff)
abjad> f(staff)
\new Staff {
    c'8 ^ \markup { +1 }
    cs'''8 ^ \markup { -2 }
    b'8 ^ \markup { -2 }
    af8 ^ \markup { -10 }
    bf,8 ^ \markup { +1 }
    b,8 ^ \markup { +10 }
    a'8 ^ \markup { +1 }
    bf'8 ^ \markup { -4 }
    fs'8 ^ \markup { -1 }
    f'8
}
```

Return none.

leaftools.label_leaves_in_expr_with_melodic_chromatic_intervals

abjad.tools.leaftools.**label_leaves_in_expr_with_melodic_chromatic_intervals**(*expr*, *markup_direction*)

New in version 2.0. Label leaves in *expr* with melodic chromatic intervals:

```
abjad> staff = Staff(notetools.make_notes([0, 25, 11, -4, -14, -13, 9, 10, 6, 5], [Duration(1, 8)
abjad> leaftools.label_leaves_in_expr_with_melodic_chromatic_intervals(staff)
abjad> f(staff)
\new Staff {
    c'8 ^ \markup { +25 }
    cs'''8 ^ \markup { -14 }
    b'8 ^ \markup { -15 }
    af8 ^ \markup { -10 }
    bf,8 ^ \markup { +1 }
    b,8 ^ \markup { +22 }
    a'8 ^ \markup { +1 }
    bf'8 ^ \markup { -4 }
    fs'8 ^ \markup { -1 }
    f'8
}
```

Return none.

leaftools.label_leaves_in_expr_with_melodic_counterpoint_interval_classes

abjad.tools.leaftools.**label_leaves_in_expr_with_melodic_counterpoint_interval_classes**(*expr*, *markup_direction*)

New in version 2.0. Label leaves in *expr* with melodic counterpoint interval classes:

```
abjad> staff = Staff(notetools.make_notes([0, 25, 11, -4, -14, -13, 9, 10, 6, 5], [Duration(1, 8)
abjad> leaftools.label_leaves_in_expr_with_melodic_counterpoint_interval_classes(staff)
abjad> f(staff)
```

```

\new Staff {
  c'8 ^ \markup { +8 }
  cs'''8 ^ \markup { -2 }
  b'8 ^ \markup { -2 }
  af8 ^ \markup { -7 }
  bf,8 ^ \markup { +1 }
  b,8 ^ \markup { +7 }
  a'8 ^ \markup { +2 }
  bf'8 ^ \markup { -4 }
  fs'8 ^ \markup { +1 }
  f'8
}

```

Return none.

leaftools.label_leaves_in_expr_with_melodic_counterpoint_intervals

`abjad.tools.leaftools.label_leaves_in_expr_with_melodic_counterpoint_intervals`(*expr*, *markup_direction*)

New in version 2.0. Label leaves in *expr* with melodic counterpoint intervals:

```

abjad> staff = Staff(notetools.make_notes([0, 25, 11, -4, -14, -13, 9, 10, 6, 5], [Duration(1, 8)
abjad> leaftools.label_leaves_in_expr_with_melodic_counterpoint_intervals(staff)
abjad> f(staff)
\new Staff {
  c'8 ^ \markup { +15 }
  cs'''8 ^ \markup { -9 }
  b'8 ^ \markup { -9 }
  af8 ^ \markup { -7 }
  bf,8 ^ \markup { 1 }
  b,8 ^ \markup { +14 }
  a'8 ^ \markup { +2 }
  bf'8 ^ \markup { -4 }
  fs'8 ^ \markup { 1 }
  f'8
}

```

Return none.

leaftools.label_leaves_in_expr_with_melodic_diatonic_interval_classes

`abjad.tools.leaftools.label_leaves_in_expr_with_melodic_diatonic_interval_classes`(*expr*, *markup_direction*)

New in version 2.0. Label leaves in *expr* with melodic diatonic interval classes:

```

abjad> staff = Staff(notetools.make_notes([0, 25, 11, -4, -14, -13, 9, 10, 6, 5], [Duration(1, 8)
abjad> leaftools.label_leaves_in_expr_with_melodic_diatonic_interval_classes(staff)
abjad> f(staff)
\new Staff {
  c'8 ^ \markup { +aug8 }
  cs'''8 ^ \markup { -M2 }
  b'8 ^ \markup { -aug2 }
  af8 ^ \markup { -m7 }
  bf,8 ^ \markup { aug1 }
  b,8 ^ \markup { +m7 }
  a'8 ^ \markup { +m2 }
  bf'8 ^ \markup { -dim4 }
}

```

```

    fs'8 ^ \markup { aug1 }
    f'8
}

```

Return none.

leaftools.label_leaves_in_expr_with_melodic_diatonic_intervals

abjad.tools.leaftools.**label_leaves_in_expr_with_melodic_diatonic_intervals**(*expr*,
markup_direction='up'

New in version 2.0. Label leaves in *expr* with melodic diatonic intervals:

```

abjad> staff = Staff(notetools.make_notes([0, 25, 11, -4, -14, -13, 9, 10, 6, 5], [Duration(1, 8)
abjad> leaftools.label_leaves_in_expr_with_melodic_diatonic_intervals(staff)
abjad> f(staff)
\new Staff {
    c'8 ^ \markup { +aug15 }
    cs''8 ^ \markup { -M9 }
    b'8 ^ \markup { -aug9 }
    af8 ^ \markup { -m7 }
    bf,8 ^ \markup { +aug1 }
    b,8 ^ \markup { +m14 }
    a'8 ^ \markup { +m2 }
    bf'8 ^ \markup { -dim4 }
    fs'8 ^ \markup { -aug1 }
    f'8
}

```

Return none.

leaftools.label_leaves_in_expr_with_pitch_class_numbers

abjad.tools.leaftools.**label_leaves_in_expr_with_pitch_class_numbers**(*expr*,
num-
ber=True,
color=False,
markup_direction='down'

New in version 1.1. Label leaves in *expr* with pitch-class numbers:

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> leaftools.label_leaves_in_expr_with_pitch_class_numbers(t)
abjad> print t.format
\new Staff {
    c'8 _ \markup { \small 0 }
    d'8 _ \markup { \small 2 }
    e'8 _ \markup { \small 4 }
    f'8 _ \markup { \small 5 }
}

```

When `color = True` call `color_note_head_by_numbered_chromatic_pitch_class_color_map()`.

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> leaftools.label_leaves_in_expr_with_pitch_class_numbers(t, color = True, number = False)
abjad> print t.format
\new Staff {
    \once \override NoteHead #'color = #(x11-color 'red)
    c'8
}

```

```

\once \override NoteHead #'color = #(x11-color 'orange)
d'8
\once \override NoteHead #'color = #(x11-color 'ForestGreen)
e'8
\once \override NoteHead #'color = #(x11-color 'MediumOrchid)
f'8
}

```

You can set *number* and *color* at the same time. Changed in version 2.0: renamed `label.leaf_pcs()` to `leaftools.label_leaves_in_expr_with_pitch_class_numbers()`. Return `none`.

leaftools.label_leaves_in_expr_with_pitch_numbers

`abjad.tools.leaftools.label_leaves_in_expr_with_pitch_numbers`(*expr*,
markup_direction='down')

New in version 1.1. Label leaves in *expr* with pitch numbers:

```

abjad> staff = Staff(leaftools.make_leaves([None, 12, [13, 14, 15], None], [(1, 4)]))
abjad> leaftools.label_leaves_in_expr_with_pitch_numbers(staff)
abjad> f(staff)
\new Staff {
    r4
    c''4 _ \markup { \small 12 }
    <cs'' d'' ef''>4 _ \markup { \column { \small 15 \small 14 \small 13 } }
    r4
}

```

Return `none`. Changed in version 2.0: renamed `label.leaf_pitch_numbers()` to `leaftools.label_leaves_in_expr_with_pitch_numbers()`.

leaftools.label_leaves_in_expr_with_prolated_leaf_duration

`abjad.tools.leaftools.label_leaves_in_expr_with_prolated_leaf_duration`(*expr*,
markup_direction='down')

New in version 1.1. Label leaves in *expr* with prolated leaf duration:

```

abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(1, 4), "c'8 d'8 e'8")
abjad> leaftools.label_leaves_in_expr_with_prolated_leaf_duration(tuplet)
abjad> f(tuplet)
\times 2/3 {
    c'8 _ \markup { \small 1/12 }
    d'8 _ \markup { \small 1/12 }
    e'8 _ \markup { \small 1/12 }
}

```

Return `none`.

leaftools.label_leaves_in_expr_with_tuplet_depth

`abjad.tools.leaftools.label_leaves_in_expr_with_tuplet_depth`(*expr*,
markup_direction='down')

New in version 1.1. Label leaves in *expr* with tuplet depth:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8")
abjad> tuplettools.FixedDurationTuplet(Duration(2, 8), staff[-3:])
FixedDurationTuplet(1/4, [e'8, f'8, g'8])

```

```
abjad> leaftools.label_leaves_in_expr_with_tuplet_depth(staff)
abjad> f(staff)
\new Staff {
  c'8 _ \markup { \small 0 }
  d'8 _ \markup { \small 0 }
  \times 2/3 {
    e'8 _ \markup { \small 1 }
    f'8 _ \markup { \small 1 }
    g'8 _ \markup { \small 1 }
  }
}
```

Return `none`. Changed in version 2.0: renamed `label.leaf_depth_tuplet()` to `leaftools.label_leaves_in_expr_with_tuplet_depth()`.

leaftools.label_leaves_in_expr_with_written_leaf_duration

`abjad.tools.leaftools.label_leaves_in_expr_with_written_leaf_duration(expr, markup_direction='down')`

New in version 1.1. Label leaves in *expr* with written leaf duration:

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(1, 4), "c'8 d'8 e'8")
abjad> leaftools.label_leaves_in_expr_with_leaf_durations(tuplet)
abjad> f(tuplet)
\times 2/3 {
  c'8 _ \markup { \column { \small 1/8 \small 1/12 } }
  d'8 _ \markup { \column { \small 1/8 \small 1/12 } }
  e'8 _ \markup { \column { \small 1/8 \small 1/12 } }
}
```

Return `none`.

leaftools.leaf_to_augmented_tuplet_with_n_notes_of_equal_written_duration

`abjad.tools.leaftools.leaf_to_augmented_tuplet_with_n_notes_of_equal_written_duration(leaf, n)`

New in version 2.0. Change *leaf* to augmented tuplet with *n* notes of equal written duration:

```
abjad> for n in range(1, 11):
...     note = Note(0, (3, 16))
...     tuplet = leaftools.leaf_to_augmented_tuplet_with_n_notes_of_equal_written_duration(note,
...     print tuplet
...
{@ 1:1 c'8. @}
{@ 1:1 c'16., c'16. @}
{@ 1:1 c'16, c'16, c'16 @}
{@ 1:1 c'32., c'32., c'32., c'32. @}
{@ 5:8 c'64., c'64., c'64., c'64., c'64. @}
{@ 1:1 c'32, c'32, c'32, c'32, c'32, c'32 @}
{@ 7:8 c'64., c'64., c'64., c'64., c'64., c'64., c'64. @}
{@ 1:1 c'64., c'64., c'64., c'64., c'64., c'64., c'64., c'64. @}
{@ 3:4 c'64, c'64, c'64, c'64, c'64, c'64, c'64, c'64 @}
{@ 5:8 c'128., c'128., c'128., c'128., c'128., c'128., c'128., c'128. @}
```

Return augmented fixed-duration tuplet.

leaftools.leaf_to_augmented_tuplet_with_proportions

abjad.tools.leaftools.leaf_to_augmented_tuplet_with_proportions(*leaf*, *proportions*)

New in version 2.0. Change *leaf* to augmented tuplet with *proportions*:

```
abjad> note = Note(0, (3, 16))
abjad> print leaftools.leaf_to_augmented_tuplet_with_proportions(note, [1])
{@ 1:1 c'8. @}
abjad> print leaftools.leaf_to_augmented_tuplet_with_proportions(note, [1, 2])
{@ 1:1 c'16, c'8 @}
abjad> print leaftools.leaf_to_augmented_tuplet_with_proportions(note, [1, 2, 2])
{@ 5:8 c'64., c'32., c'32. @}
abjad> print leaftools.leaf_to_augmented_tuplet_with_proportions(note, [1, 2, 2, 3])
{@ 2:3 c'64, c'32, c'32, c'32. @}
abjad> print leaftools.leaf_to_augmented_tuplet_with_proportions(note, [1, 2, 2, 3, 3])
{@ 11:12 c'64, c'32, c'32, c'32., c'32. @}
abjad> print leaftools.leaf_to_augmented_tuplet_with_proportions(note, [1, 2, 2, 3, 3, 4])
{@ 5:8 c'128, c'64, c'64, c'64., c'64., c'32 @}

```

Return augmented fixed-duration tuplet.

leaftools.leaf_to_diminished_tuplet_with_n_notes_of_equal_written_duration

abjad.tools.leaftools.leaf_to_diminished_tuplet_with_n_notes_of_equal_written_duration(*leaf*, *n*)

New in version 2.0. Change *leaf* to diminished tuplet with *n* notes of equal written duration:

```
abjad> for n in range(1, 11):
...     note = Note(0, (3, 16))
...     tuplet = leaftools.leaf_to_diminished_tuplet_with_n_notes_of_equal_written_duration(note, n)
...     print tuplet
...
{@ 1:1 c'8. @}
{@ 1:1 c'16., c'16. @}
{@ 1:1 c'16, c'16, c'16 @}
{@ 1:1 c'32., c'32., c'32., c'32. @}
{@ 5:4 c'32., c'32., c'32., c'32. @}
{@ 1:1 c'32, c'32, c'32, c'32, c'32, c'32 @}
{@ 7:4 c'32., c'32., c'32., c'32., c'32., c'32., c'32. @}
{@ 1:1 c'64., c'64., c'64., c'64., c'64., c'64., c'64., c'64. @}
{@ 3:2 c'32, c'32, c'32, c'32, c'32, c'32, c'32, c'32 @}
{@ 5:4 c'64., c'64., c'64., c'64., c'64., c'64., c'64., c'64., c'64., c'64. @}

```

Return diminished fixed-duration tuplet.

leaftools.leaf_to_diminished_tuplet_with_proportions

abjad.tools.leaftools.leaf_to_diminished_tuplet_with_proportions(*leaf*, *proportions*)

New in version 2.0. Change *leaf* to diminished tuplet with *proportions*:

```
abjad> note = Note(0, (3, 16))
abjad> print leaftools.leaf_to_diminished_tuplet_with_proportions(note, [1])
{@ 1:1 c'8. @}
abjad> print leaftools.leaf_to_diminished_tuplet_with_proportions(note, [1, 2])
{@ 1:1 c'16, c'8 @}

```

```
abjad> print leaftools.leaf_to_diminished_tuplet_with_proportions(note, [1, 2, 2])
{@ 5:4 c'32., c'16., c'16. @}
abjad> print leaftools.leaf_to_diminished_tuplet_with_proportions(note, [1, 2, 2, 3])
{@ 4:3 c'32, c'16, c'16, c'16. @}
abjad> print leaftools.leaf_to_diminished_tuplet_with_proportions(note, [1, 2, 2, 3, 3])
{@ 11:6 c'32, c'16, c'16, c'16., c'16. @}
abjad> print leaftools.leaf_to_diminished_tuplet_with_proportions(note, [1, 2, 2, 3, 3, 4])
{@ 5:4 c'64, c'32, c'32, c'32., c'32., c'16 @}

```

Return diminished fixed-duration tuplet.

leaftools.list_prolated_durations_of_leaves_in_expr

`abjad.tools.leaftools.list_prolated_durations_of_leaves_in_expr(expr)`

New in version 2.0. List prolated durations of leaves in *expr*:

```
abjad> staff = Staff(tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8") * 2)
abjad> leaftools.list_prolated_durations_of_leaves_in_expr(staff)
[Duration(1, 12), Duration(1, 12), Duration(1, 12), Duration(1, 12), Duration(1, 12), Duration(1, 12)]

```

Return list of fractions.

leaftools.list_written_durations_of_leaves_in_expr

`abjad.tools.leaftools.list_written_durations_of_leaves_in_expr(expr)`

New in version 2.0. List the written durations of leaves in *expr*:

```
abjad> staff = Staff(tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8") * 2)
abjad> leaftools.list_written_durations_of_leaves_in_expr(staff)
[Duration(1, 8), Duration(1, 8), Duration(1, 8), Duration(1, 8), Duration(1, 8), Duration(1, 8)]

```

Return list of fractions.

leaftools.make_leaves

`abjad.tools.leaftools.make_leaves(pitches, durations, direction='big-endian', tied_rests=False)`

New in version 1.1. Construct a list of notes, rests or chords.

Set *pitches* is a single pitch, or a list of pitches, or a tuple of pitches.

Integer pitches create notes.

```
abjad> leaftools.make_leaves([2, 4, 19], [(1, 4)])
[Note("d'4"), Note("e'4"), Note("g''4")]

```

Tuple pitches create chords.

```
abjad> leaftools.make_leaves([(0, 1, 2), (3, 4, 5), (6, 7, 8)], [(1, 4)])
[Chord("<c' cs' d'>4"), Chord("<ef' e' f'>4"), Chord("<fs' g' af'>4")]

```

Set *pitches* to a list of none to create rests.

```
abjad> leaftools.make_leaves([None, None, None, None], [(1, 8)])
[Rest('r8'), Rest('r8'), Rest('r8'), Rest('r8')]

```

You can mix and match pitch values.

```
abjad> leaftools.make_leaves([12, (1, 2, 3), None, 12], [(1, 4)])
[Note("c''4"), Chord("<cs' d' ef'>4"), Rest('r4'), Note("c''4")]
```

If the length of *pitches* is less than the length of *durations*, the function reads *durations* cyclically.

```
abjad> leaftools.make_leaves([13], [(1, 8), (1, 8), (1, 4), (1, 4)])
[Note("cs''8"), Note("cs''8"), Note("cs''4"), Note("cs''4")]
```

Set *durations* to a single duration, a list of duration, or a tuple of durations.

If the length of *durations* is less than the length of *pitches*, the function reads *pitches* cyclically.

```
abjad> leaftools.make_leaves([13, 14, 15, 16], [(1, 8)])
[Note("cs''8"), Note("d''8"), Note("ef''8"), Note("e''8")]
```

Duration values not of the form $m / 2 ** n$ return leaves nested inside a fixed-multiplier tuplet.

```
abjad> leaftools.make_leaves([14], [(1, 12), (1, 12), (1, 12)])
[Tuplet(2/3, [d''8, d''8, d''8])]
```

Set *direction* to 'little-endian' to return tied leaf durations from least to greatest.

```
abjad> staff = Staff(leaftools.make_leaves([15], [(13, 16)], direction = 'little-endian'))
abjad> f(staff)
\new Staff {
    ef''16 ~
    ef''2.
}
```

Set *tied_rests* to true to return tied rests for durations like 5/16 and 9/16.

```
abjad> staff = Staff(leaftools.make_leaves([None], [(5, 16)], tied_rests = True))
abjad> f(staff)
\new Staff {
    r4 ~
    r16
}
```

Return list of leaves. Changed in version 2.0: renamed `construct.leaves()` to `leaftools.make_leaves()`.

leaftools.make_leaves_from_note_value_signal

`abjad.tools.leaftools.make_leaves_from_note_value_signal` (*note_value_signal*, *denominator_of_signal*, *tied_rests=False*)

New in version 2.0. Make leaves from *note_value_signal* and *denominator_of_signal*:

```
abjad> leaves = leaftools.make_leaves_from_note_value_signal([3, -3, 5, -5], 8)
abjad> staff = Staff(leaves)
```

```
abjad> f(staff)
\new Staff {
    c'4.
    r4.
    c'2 ~
    c'8
    r2
    r8
}
```

Interpret positive elements in *note_value_signal* as notes.

Interpret negative elements in *note_value_signal* as rests.

Set the pitch of all notes to middle C.

Return list of notes and / or rests.

leaftools.remove_initial_rests_from_sequence

`abjad.tools.leaftools.remove_initial_rests_from_sequence(sequence)`

New in version 2.0. Remove initial rests from *sequence*:

```
abjad> staff = Staff("r8 r8 c'8 d'8 r4 r4")

abjad> f(staff)
\new Staff {
    r8
    r8
    c'8
    d'8
    r4
    r4
}

abjad> leaftools.remove_initial_rests_from_sequence(staff)
[Note("c'8"), Note("d'8"), Rest('r4'), Rest('r4')]

abjad> f(staff)
\new Staff {
    r8
    r8
    c'8
    d'8
    r4
    r4
}
```

Return list.

leaftools.remove_leaf_and_shrink_durated_parent_containers

`abjad.tools.leaftools.remove_leaf_and_shrink_durated_parent_containers(leaf)`

New in version 1.1. Remove *leaf* and shrink durated parent containers:

```
abjad> measure = Measure((4, 8), tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(measure)
abjad> spannertools.BeamSpanner(measure.leaves)
BeamSpanner(c'8, d'8, e'8, f'8, g'8, a'8)
abjad> f(measure)
{
    \time 4/8
    \times 2/3 {
        c'8 [
        d'8
        e'8
    ]
    \times 2/3 {
```

```

        f'8
        g'8
        a'8 ]
    }
}

abjad> leaftools.remove_leaf_and_shrink_durated_parent_containers(measure.leaves[0])

abjad> f(measure)
{
    \time 5/12
    \scaleDurations #'(2 . 3) {
        {
            d'8 [
            e'8
            ]
        }
        {
            f'8
            g'8
            a'8 ]
        }
    }
}

```

Return none.

leaftools.remove_outer_rests_from_sequence

`abjad.tools.leaftools.remove_outer_rests_from_sequence(sequence)`

New in version 2.0. Remove outer rests from *sequence*:

```

abjad> staff = Staff("r8 r8 c'8 d'8 r4 r4")

abjad> f(staff)
\new Staff {
    r8
    r8
    c'8
    d'8
    r4
    r4
}

abjad> leaftools.remove_outer_rests_from_sequence(staff)
[Note("c'8"), Note("d'8")]

abjad> f(staff)
\new Staff {
    r8
    r8
    c'8
    d'8
    r4
    r4
}

```

Return list.

leaftools.remove_terminal_rests_from_sequence

`abjad.tools.leaftools.remove_terminal_rests_from_sequence(sequence)`

New in version 2.0. Remove terminal rests from *sequence*:

```
abjad> staff = Staff("r8 r8 c'8 d'8 r4 r4")

abjad> f(staff)
\new Staff {
    r8
    r8
    c'8
    d'8
    r4
    r4
}

abjad> leaftools.remove_terminal_rests_from_sequence(staff)
[Rest('r8'), Rest('r8'), Note("c'8"), Note("d'8")]

abjad> f(staff)
\new Staff {
    r8
    r8
    c'8
    d'8
    r4
    r4
}
```

Return list.

leaftools.repeat_leaf_and_extend_spanners

`abjad.tools.leaftools.repeat_leaf_and_extend_spanners(leaf, total=1)`

New in version 1.1. Repeat *leaf* and extend spanners:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}

abjad> leaftools.repeat_leaf_and_extend_spanners(staff[0], total = 3)

abjad> f(staff)
\new Staff {
    c'8 [
    c'8
    c'8
    d'8
    e'8
```

```
f'8 ]
}
```

Preserve *leaf* written duration.

Preserve parentage and spanners.

Return none. Changed in version 2.0: renamed `leaftools.clone_and_splice_leaf()` to `leaftools.repeat_leaf_and_extend_spanners()`.

leaftools.repeat_leaves_in_expr_and_extend_spanners

`abjad.tools.leaftools.repeat_leaves_in_expr_and_extend_spanners(expr, total=1)`

New in version 1.1. Repeat leaves in *expr* and extend spanners:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}

abjad> result = leaftools.repeat_leaves_in_expr_and_extend_spanners(staff[2:], total = 3)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    e'8
    e'8
    f'8
    f'8
    f'8 ]
}
```

Preserve leaf written durations.

Preserve parentage and spanners.

Return none. Changed in version 2.0: renamed `leaftools.multiply()` to `leaftools.repeat_leaves_in_expr_and_extend_spanners()`.

leaftools.scale_preprolated_leaf_duration

`abjad.tools.leaftools.scale_preprolated_leaf_duration(leaf, multiplier)`

New in version 1.1. Scale preprolated *leaf* leaf duration by dotted *multiplier*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> leaftools.scale_preprolated_leaf_duration(staff[1], Duration(3, 2))
[Note("d'8.") ]
abjad> f(staff)
```

```
\new Staff {
  c'8 [
  d'8.
  e'8
  f'8 ]
}
```

Scale preprolated *leaf* duration by tied *multiplier*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> leaftools.scale_preprolated_leaf_duration(staff[1], Duration(5, 4))
[Note("d'8"), Note("d'32")]
abjad> f(staff)
\new Staff {
  c'8 [
  d'8 ~
  d'32
  e'8
  f'8 ]
}
```

Scale preprolated *leaf* duration by nonbinary *multiplier*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> leaftools.scale_preprolated_leaf_duration(staff[1], Duration(2, 3))
[Note("d'8")]
abjad> f(staff)
\new Staff {
  c'8 [
  \times 2/3 {
    d'8
  }
  e'8
  f'8 ]
}
```

Scale preprolated *leaf* duration by tied nonbinary *multiplier*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> leaftools.scale_preprolated_leaf_duration(staff[1], Duration(5, 6))
[Note("d'8"), Note("d'32")]
abjad> f(staff)
\new Staff {
  c'8 [
  \times 2/3 {
    d'8 ~
    d'32
  }
  e'8
  f'8 ]
}
```

Return *leaf*. Changed in version 2.0: renamed from `leaftools.duration_scale()`.
`leaftools.scale_preprolated_leaf_duration()`.

leaftools.set_preprolated_leaf_duration

`abjad.tools.leaftools.set_preprolated_leaf_duration(leaf, new_preprolated_duration)`

New in version 1.1. Set preprolated *leaf* duration:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> leaftools.set_preprolated_leaf_duration(staff[1], Duration(3, 16))
[Note("d'8.")]
abjad> f(staff)
\new Staff {
    c'8 [
    d'8.
    e'8
    f'8 ]
}

```

Set tied preprolated *leaf* duration:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> leaftools.set_preprolated_leaf_duration(staff[1], Duration(5, 32))
[Note("d'8"), Note("d'32")]
abjad> f(staff)
\new Staff {
    c'8 [
    d'8 ~
    d'32
    e'8
    f'8 ]
}

```

Set nonbinary preprolated *leaf* duration:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> leaftools.set_preprolated_leaf_duration(staff[1], Duration(1, 12))
[Note("d'8")]
abjad> f(staff)
\new Staff {
    c'8 [
    \times 2/3 {
        d'8
    }
    e'8
    f'8 ]
}

```

Set tied nonbinary preprolated *leaf* duration:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'8, d'8, e'8, f'8)
abjad> leaftools.set_preprolated_leaf_duration(staff[1], Duration(5, 48))
[Note("d'8"), Note("d'32")]
abjad> f(staff)
\new Staff {

```

```

c'8 [
\times 2/3 {
    d'8 ~
    d'32
}
e'8
f'8 ]
}

```

Set preprolated *leaf* duration with LilyPond multiplier:

```

abjad> note = Note(0, (1, 8))
abjad> note.duration_multiplier = Duration(1, 2)
abjad> leaftools.set_preprolated_leaf_duration(note, Duration(5, 48))
[Note("c'8 * 5/6")]
abjad> f(note)
c'8 * 5/6

```

Return list of *leaf* and leaves newly tied to *leaf*. Changed in version 2.0: renamed `leaftools.change_leaf_preprolated_duration()` to `leaftools.set_preprolated_leaf_duration()`.

leaftools.show_leaves

`abjad.tools.leaftools.show_leaves` (*leaves*, *template=None*, *suppress_pdf=False*)

New in version 2.0. Show *leaves* in temporary piano staff score:

```

abjad> leaves = leaftools.make_leaves([None, 1, (-24, -22, 7, 21), None], (1, 4))
abjad> score = leaftools.show_leaves(leaves) # doctest: +SKIP
\new Score <<
  \new PianoStaff <<
    \context Staff = "treble" {
      \clef "treble"
      r4
      cs'4
      <g' a''>4
      r4
    }
    \context Staff = "bass" {
      \clef "bass"
      r4
      r4
      <c, d,>4
      r4
    }
  >>
>>

```

Useful when working with notes, rests, chords not yet added to score.

Return temporary piano staff score.

leaftools.split_leaf_at_prolated_duration_and_rest_right_half

abjad.tools.leaftools.**split_leaf_at_prolated_duration_and_rest_right_half**(*leaf*,
*pro-
lated_duration*)

New in version 1.1. Split *leaf* at *prolated_duration* and rest right half:

```
abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.SlurSpanner(t[:])
SlurSpanner(c'8, d'8, e'8, f'8)
abjad> f(t)
\new Staff {
    c'8 (
    d'8
    e'8
    f'8 )
}

abjad> leaftools.split_leaf_at_prolated_duration_and_rest_right_half(t.leaves[1], (1, 32))
([Note("d'32")], [Note("d'16.")])

abjad> f(t)
\new Staff {
    c'8 (
    d'32
    r16.
    e'8
    f'8 )
}
```

Return list of leaves to left of *prolated_duration* together with list of leaves to right of *prolated_duration*. Changed in version 2.0: renamed `leaftools.shorten()` to `leaftools.split_leaf_at_prolated_duration_and_rest_right_half()`.

leaftools.yield_groups_of_mixed_notes_and_chords_in_sequence

abjad.tools.leaftools.**yield_groups_of_mixed_notes_and_chords_in_sequence**(*sequence*)

New in version 2.0. Yield groups of mixed notes and chords in *sequence*:

```
abjad> staff = Staff("c'8 d'8 r8 r8 <e' g'>8 <f' a'>8 g'8 a'8 r8 r8 <b' d''>8 <c'' e''>8")

abjad> f(staff)
\new Staff {
    c'8
    d'8
    r8
    r8
    <e' g'>8
    <f' a'>8
    g'8
    a'8
    r8
    r8
    <b' d''>8
    <c'' e''>8
}
```

```
abjad> for group in leaftools.yield_groups_of_mixed_notes_and_chords_in_sequence(staff):
...     group
...
(Note("c'8"), Note("d'8"))
(Chord("<e' g'>8"), Chord("<f' a'>8"), Note("g'8"), Note("a'8"))
(Chord("<b' d'>8"), Chord("<c' e'>8"))
```

Return generator.

`lilyfiletools`

`lilyfiletools.AbjadRevisionToken`

class `abjad.tools.lilyfiletools.AbjadRevisionToken`

Bases: `abjad.core._Immutable._Immutable._Immutable` New in version 2.0. Abjad version token:

```
abjad> lilyfiletools.AbjadRevisionToken()
AbjadRevisionToken(Abjad revision ...)
```

Return Abjad version token.

format

Format contribution of Abjad version token:

```
abjad> lilyfiletools.AbjadRevisionToken().format
'Abjad revision ...'
```

Return string.

`lilyfiletools.BookBlock`

class `abjad.tools.lilyfiletools.BookBlock`

Bases: `abjad.tools.lilyfiletools._BlockNonattributed._BlockNonattributed._BlockNonattributed`
New in version 2.0. Abjad model of LilyPond input file book block.

`lilyfiletools.BookpartBlock`

class `abjad.tools.lilyfiletools.BookpartBlock`

Bases: `abjad.tools.lilyfiletools._BlockNonattributed._BlockNonattributed._BlockNonattributed`
New in version 2.0. Abjad model of LilyPond input file bookpart block.

`lilyfiletools.DateTimeToken`

class `abjad.tools.lilyfiletools.DateTimeToken`

Bases: `abjad.core._Immutable._Immutable._Immutable` New in version 2.0. Date time token:

```
abjad> lilyfiletools.DateTimeToken()
DateTimeToken(...)
```

Return date / time token.

format

Format contribution of date time token:

```
abjad> lilyfiletools.DateTimeToken().format
'...'
```

Return string.

`lilyfiletools.HeaderBlock`

class `abjad.tools.lilyfiletools.HeaderBlock`

Bases: `abjad.tools.lilyfiletools._BlockAttributed._BlockAttributed._BlockAttributed`
 New in version 2.0. Abjad model of LilyPond input file header block:

```
abjad> header_block = lilyfiletools.HeaderBlock()
abjad> header_block.composer = markuptools.Markup('Josquin')
abjad> header_block.title = markuptools.Markup('Missa sexti tonus')

abjad> f(header_block)
\header {
  composer = \markup { Josquin }
  title = \markup { Missa sexti tonus }
}
```

Return header block.

`lilyfiletools.LayoutBlock`

class `abjad.tools.lilyfiletools.LayoutBlock`

Bases: `abjad.tools.lilyfiletools._BlockAttributed._BlockAttributed._BlockAttributed`
 New in version 2.0. Abjad model of LilyPond input file layout block.

contexts

`lilyfiletools.LilyFile`

class `abjad.tools.lilyfiletools.LilyFile`

Bases: `list` New in version 2.0. Abjad model of LilyPond input file:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> lily_file = lilyfiletools.make_basic_lily_file(staff)
abjad> lily_file.file_initial_user_comments.append('File construct as an example.')
abjad> lily_file.file_initial_user_comments.append('Parts shown here for positioning.')
abjad> lily_file.file_initial_user_includes.append('external-settings-file-1.ly')
abjad> lily_file.file_initial_user_includes.append('external-settings-file-2.ly')
abjad> lily_file.default_paper_size = 'letter', 'portrait'
abjad> lily_file.global_staff_size = 16
abjad> lily_file.header_block.composer = markuptools.Markup('Josquin')
abjad> lily_file.header_block.title = markuptools.Markup('Missa sexti tonus')
abjad> lily_file.layout_block.indent = 0
abjad> lily_file.layout_block.left_margin = 15
abjad> lily_file.paper_block.oddFooterMarkup = markuptools.Markup('The odd-page footer')
abjad> lily_file.paper_block.evenFooterMarkup = markuptools.Markup('The even-page footer')

abjad> f(lily_file) # doctest: +SKIP
% Abjad revision 3719
% 2010-09-24 09:01
```

```
% File construct as an example.
% Parts shown here for positioning.

\version "2.13.32"
\include "english.ly"
\include "/Users/trevorbaca/Documents/abjad/trunk/abjad/cfg/abjad.scm"

\include "external-settings-file-1.ly"
\include "external-settings-file-2.ly"

#(set-default-paper-size "letter" 'portrait)
#(set-global-staff-size 16)

\header {
  composer = \markup { Josquin }
  title = \markup { Missa sexti tonus }
}

\layout {
  indent = #0
  left-margin = #15
}

\paper {
  evenFooterMarkup = \markup { The even-page footer }
  oddFooterMarkup = \markup { The odd-page footer }
}

\new Staff {
  c'8
  d'8
  e'8
  f'8
}
```

default_paper_size

LilyPond default paper size.

file_initial_system_comments

Read-only list of file-initial system comments.

file_initial_system_includes

List of file-initial system include commands.

file_initial_user_comments

Read-only list of file-initial user comments.

file_initial_user_includes

List of file-initial user include commands.

format

Format-time contribution of LilyPond file.

global_staff_size

LilyPond global staff size.

lilyfiletools.LilyPondLanguageToken

class abjad.tools.lilyfiletools.**LilyPondLanguageToken**

Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. LilyPond language token:

```
abjad> lilyfiletools.LilyPondLanguageToken()  
LilyPondLanguageToken(\include "english.ly")
```

Return LilyPond language token.

format

Format contribution of LilyPond language token:

```
abjad> lilyfiletools.LilyPondLanguageToken().format  
'\\include "english.ly"'
```

Return string.

lilyfiletools.LilyPondVersionToken

class abjad.tools.lilyfiletools.**LilyPondVersionToken**

Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. LilyPond version token:

```
abjad> lilyfiletools.LilyPondVersionToken()  
LilyPondVersionToken(\version "...")
```

Return LilyPond version token.

format

Format contribution of LilyPond version token:

```
abjad> lilyfiletools.LilyPondVersionToken().format  
'\\version "..."
```

Return string.

lilyfiletools.MidiBlock

class abjad.tools.lilyfiletools.**MidiBlock**

Bases: abjad.tools.lilyfiletools._BlockAttributed._BlockAttributed._BlockAttributed
New in version 2.0. Abjad model of LilyPond input file midi block.

lilyfiletools.PaperBlock

class abjad.tools.lilyfiletools.**PaperBlock**

Bases: abjad.tools.lilyfiletools._BlockAttributed._BlockAttributed._BlockAttributed
New in version 2.0. Abjad model of LilyPond input file paper block.

minimal_page_breaking

`lilyfiletools.ScoreBlock`

class `abjad.tools.lilyfiletools.ScoreBlock`

Bases: `abjad.tools.lilyfiletools._BlockNonattributed._BlockNonattributed._BlockNonattributed`

New in version 2.0. Abjad model of LilyPond input file score block.

`lilyfiletools.make_basic_lily_file`

`abjad.tools.lilyfiletools.make_basic_lily_file` (*music=None*)

New in version 2.0. Make basic LilyPond file with *music*:

```
abjad> score = Score([Staff("c'8 d'8 e'8 f'8")])
abjad> lily_file = lilyfiletools.make_basic_lily_file(score)
abjad> lily_file.header_block.composer = markuptools.Markup('Josquin')
abjad> lily_file.layout_block.indent = 0
abjad> lily_file.paper_block.top_margin = 15
abjad> lily_file.paper_block.left_margin = 15

abjad> f(lily_file) # doctest: +SKIP
\header {
  composer = \markup { Josquin }
}

\layout {
  indent = #0
}

\paper {
  left-margin = #15
  top-margin = #15
}

\new Score <<
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
>>
```

Equip LilyPond file with header, layout and paper blocks.

Return LilyPond file.

marktools

`marktools.Annotation`

class `abjad.tools.marktools.Annotation` (*name, value=None*)

Bases: `abjad.tools.marktools.Mark.Mark.Mark` New in version 2.0. User-defined annotation:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> f(staff)
\new Staff {
  c'8
```



```

        d' 8
        e' 8
        f' 8
    }

abjad> marktools.Annotation('special pitch', pitchtools.NamedChromaticPitch('ds'))(staff[0])
Annotation('special pitch', NamedChromaticPitch('ds'))(c' 8)

abjad> f(staff)
\new Staff {
    c' 8
    d' 8
    e' 8
    f' 8
}

```

Annotations contribute no formatting.

Annotations implement `__slots__`.

name

Get name of annotation:

```

abjad> annotation = marktools.Annotation('special_pitch', pitchtools.NamedChromaticPitch('ds'))
abjad> annotation.name
'special_pitch'

```

Set name of annotation:

```

abjad> annotation.name = 'revised special pitch'
abjad> annotation.name
'revised special pitch'

```

Set string.

value

Get value of annotation:

```

abjad> annotation = marktools.Annotation('special_pitch', pitchtools.NamedChromaticPitch('ds'))
abjad> annotation.value
NamedChromaticPitch('ds')

```

Set value of annotation:

```

abjad> annotation.value = pitchtools.NamedChromaticPitch('e')
abjad> annotation.value
NamedChromaticPitch('e')

```

Set arbitrary object.

marktools.Articulation

```

class abjad.tools.marktools.Articulation(*args)
    Bases: abjad.tools.marktools.Mark.Mark.Mark

```

Abjad model of musical articulation:

```

abjad> note = Note("c' 4")

```

```
abjad> marktools.Articulation('staccato')(note)
Articulation('staccato', '-') (c'4)
```

```
abjad> f(note)
c'4 -\staccato
```

Articulations implement `__slots__`.

direction_string

Get direction string of articulation:

```
abjad> articulation = marktools.Articulation('staccato')
abjad> articulation.direction_string
'-'
```

Set direction string of articulation:

```
abjad> articulation.direction_string = '^'
abjad> articulation.direction_string
'^'
```

Set string.

format

Read-only LilyPond format string of articulation:

```
abjad> articulation = marktools.Articulation('staccato', 'up')
abjad> articulation.format
'^\staccato'
```

Return string.

name_string

Get name string of articulation:

```
abjad> articulation = marktools.Articulation('staccato', 'up')
abjad> articulation.name_string
'staccato'
```

Set name string of articulation:

```
abjad> articulation.name_string = 'marcato'
abjad> articulation.name_string
'marcato'
```

Set string.

marktools.Comment

class `abjad.tools.marktools.Comment` (*comment_name_string*, *format_slot='opening'*)

Bases: `abjad.tools.marktools.Mark.Mark` New in version 2.0. User-defined comment:

```
abjad> note = Note("c'4")
```

```
abjad> marktools.Comment('this is a comment')(note)
Comment('this is a comment') (c'4)
```

```
abjad> f(note)
% this is a comment
c'4
```

Comments implement `__slots__`.

contents_string

Get contents string of comment:

```
abjad> comment = marktools.Comment('comment contents string')
abjad> comment.contents_string
'comment contents string'
```

Set contents string of comment:

```
abjad> comment.contents_string = 'new comment contents string'
abjad> comment.contents_string
'new comment contents string'
```

Set string.

format

Read-only LilyPond input format of comment:

```
abjad> comment = marktools.Comment('this is a comment.')
abjad> comment.format
'% this is a comment.'
```

Return string.

marktools.LilyPondCommandMark

class abjad.tools.marktools.**LilyPondCommandMark**(*command_name_string*, *for-*
mat_slot='opening')

Bases: abjad.tools.marktools.Mark.Mark New in version 2.0. LilyPond command mark:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff.leaves)

abjad> lilypond_command = marktools.LilyPondCommandMark('slurDotted')(staff[0])

abjad> f(staff)
\new Staff {
  \slurDotted
  c'8 (
  d'8
  e'8
  f'8 )
}
```

LilyPond command marks implement `__slots__`.

command_name_string

Get command name string of LilyPond command mark:

```
abjad> lilypond_command = marktools.LilyPondCommandMark('slurDotted')
abjad> lilypond_command.command_name_string
'slurDotted'
```

Set command name string of LilyPond command mark:

```
abjad> lilypond_command.command_name_string = 'slurDashed'
abjad> lilypond_command.command_name_string
'slurDashed'
```

Set string.

format

Read-only LilyPond input format of LilyPond command mark:

```
abjad> note = Note("c'4")
abjad> lilypond_command = marktools.LilyPondCommandMark('slurDotted')(note)
abjad> lilypond_command.format
'\slurDotted'
```

Return string.

marktools.Mark**class** `abjad.tools.marktools.Mark`

Bases: object New in version 2.0. Abstract class from which concrete marks inherit:

```
abjad> note = Note("c'4")
```

```
abjad> marktools.Mark()(note)
Mark()(c'4)
```

Marks override `__call__` to attach to a note, rest or chord.

Marks implement `__slots__`.

attach_mark (*start_component*)

Attach mark to *start_component*:

```
abjad> note = Note("c'4")
abjad> mark = marktools.Mark()
```

```
abjad> mark.attach_mark(note)
Mark()(c'4)
```

```
abjad> mark.start_component
Note("c'4")
```

Return mark.

detach_mark ()

Detach mark:

```
abjad> note = Note("c'4")
abjad> mark = marktools.Mark()(note)
```

```
abjad> mark.start_component
Note("c'4")
```

```
abjad> mark.detach_mark()
Mark()
```

```
abjad> mark.start_component is None
True
```

Return mark.

start_component

Read-only reference to mark start component:

```

abjad> note = Note("c'4")
abjad> mark = marktools.Mark()(note)

abjad> mark.start_component
Note("c'4")

```

Return component or none.

marktools.StemTremolo

class abjad.tools.marktools.**StemTremolo**(*tremolo_flags*)

Bases: abjad.tools.marktools.Mark.Mark.Mark New in version 2.0. Abjad model of stem tremolo:

```

abjad> note = Note("c'4")

abjad> marktools.StemTremolo(16)(note)
StemTremolo(16)(c'4)

abjad> f(note)
c'4 :16

```

Stem tremolos implement `__slots__`.

format

Read-only LilyPond format string:

```

abjad> stem_tremolo = marktools.StemTremolo(16)
abjad> stem_tremolo.format
':16'

```

Return string.

tremolo_flags

Get tremolo flags:

```

abjad> stem_tremolo = marktools.StemTremolo(16)
abjad> stem_tremolo.tremolo_flags
16

```

Set tremolo flags:

```

abjad> stem_tremolo.tremolo_flags = 32
abjad> stem_tremolo.tremolo_flags
32

```

Set integer.

marktools.apply_articulations_to_notes_and_chords_in_expr

abjad.tools.marktools.**apply_articulations_to_notes_and_chords_in_expr**(*expr*,
articulations)

New in version 2.0. Apply *articulations* to notes and chords in *expr*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> marktools.apply_articulations_to_notes_and_chords_in_expr(staff, list('^.'))

```

```
abjad> f(staff)
\new Staff {
    c'8 -\marcato -\staccato
    d'8 -\marcato -\staccato
    e'8 -\marcato -\staccato
    f'8 -\marcato -\staccato
}
```

Return none.

marktools.detach_annotations_attached_to_component

abjad.tools.marktools.**detach_annotations_attached_to_component** (*component*)

New in version 2.0. Detach annotations attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> marktools.Annotation('annotation 1')(staff[0])
Annotation('annotation 1')(c'8)
abjad> marktools.Annotation('annotation 2')(staff[0])
Annotation('annotation 2')(c'8)
```

```
abjad> f(staff)
\new Staff {
    c'8 (
    d'8
    e'8
    f'8 )
}
```

```
abjad> marktools.get_annotations_attached_to_component(staff[0])
(Annotation('annotation 1')(c'8), Annotation('annotation 2')(c'8))
```

```
abjad> marktools.detach_annotations_attached_to_component(staff[0])
(Annotation('annotation 1'), Annotation('annotation 2'))
```

```
abjad> marktools.get_annotations_attached_to_component(staff[0])
()
```

Return tuple or zero or more annotations detached.

marktools.detach_articulations_attached_to_component

abjad.tools.marktools.**detach_articulations_attached_to_component** (*component*)

New in version 2.0. Detach articulations attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> marktools.Articulation('^')(staff[0])
Articulation('^', '-')(c'8)
abjad> marktools.Articulation('.') (staff[0])
Articulation('.', '-')(c'8)
```

```
abjad> f(staff)
\new Staff {
    c'8 -\marcato -\staccato (
```

```

        d'8
        e'8
        f'8 )
    }

abjad> marktools.get_articulations_attached_to_component(staff[0])
(Articulation('^', '-')(c'8), Articulation('.', '-')(c'8))

abjad> marktools.detach_articulations_attached_to_component(staff[0])
(Articulation('^', '-'), Articulation('.', '-'))

abjad> marktools.get_articulations_attached_to_component(staff[0])
()
```

Return tuple or zero or more articulations detached.

marktools.detach_comments_attached_to_component

`abjad.tools.marktools.detach_comments_attached_to_component` (*component*)

New in version 2.0. Detach comments attached to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> marktools.Comment('comment 1')(staff[0])
Comment('comment 1')(c'8)
abjad> marktools.Comment('comment 2')(staff[0])
Comment('comment 2')(c'8)

abjad> f(staff)
\new Staff {
    % comment 1
    % comment 2
    c'8 (
    d'8
    e'8
    f'8 )
}

abjad> marktools.detach_comments_attached_to_component(staff[0])
(Comment('comment 1'), Comment('comment 2'))

abjad> f(staff)
\new Staff {
    c'8 (
    d'8
    e'8
    f'8 )
}

abjad> marktools.get_comments_attached_to_component(staff[0])
()
```

Return tuple or zero or more comments.

marktools.detach_lilypond_command_marks_attached_to_component

abjad.tools.marktools.**detach_lilypond_command_marks_attached_to_component** (*component*, *com-*
mand_name_string=Non

New in version 2.0. Detach LilyPond command marks attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> marktools.LilyPondCommandMark('slurDotted')(staff[0])
LilyPondCommandMark('slurDotted')(c'8)
abjad> marktools.LilyPondCommandMark('slurUp')(staff[0])
LilyPondCommandMark('slurUp')(c'8)

abjad> f(staff)
\new Staff {
  \slurDotted
  \slurUp
  c'8 (
  d'8
  e'8
  f'8 )
}

abjad> marktools.detach_lilypond_command_marks_attached_to_component(staff[0])
(LilyPondCommandMark('slurDotted'), LilyPondCommandMark('slurUp'))

abjad> f(staff)
\new Staff {
  c'8 (
  d'8
  e'8
  f'8 )
}
```

Return tuple of zero or more marks detached.

marktools.detach_marks_attached_to_component

abjad.tools.marktools.**detach_marks_attached_to_component** (*component*)

New in version 2.0. Detach marks attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> marktools.Articulation('^')(staff[0])
Articulation('^', '-')(c'8)
abjad> marktools.Comment('comment 1')(staff[0])
Comment('comment 1')(c'8)
abjad> marktools.LilyPondCommandMark('slurUp')(staff[0])
LilyPondCommandMark('slurUp')(c'8)

abjad> f(staff)
\new Staff {
  % comment 1
  \slurUp
  c'8 -\marcato (
  d'8
```



```

    e'8
    f'8 )
}

abjad> marktools.get_marks_attached_to_component(staff[0])
(Articulation('^', '-') (c'8), Comment('comment 1') (c'8), LilyPondCommandMark('slurUp') (c'8))

abjad> marktools.detach_marks_attached_to_component(staff[0])
(Articulation('^', '-'), Comment('comment 1'), LilyPondCommandMark('slurUp'))

abjad> marktools.get_marks_attached_to_component(staff[0])
()
```

Return tuple or zero or more marks detached.

marktools.detach_stem_tremolos_attached_to_component

`abjad.tools.marktools.detach_stem_tremolos_attached_to_component` (*component*)

New in version 2.0. Detach stem tremolos attached to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> marktools.StemTremolo(16) (staff[0])
StemTremolo(16) (c'8)

abjad> f(staff)
\new Staff {
    c'8 :16
    d'8
    e'8
    f'8
}

abjad> marktools.get_stem_tremolos_attached_to_component(staff[0])
(StemTremolo(16) (c'8),)

abjad> marktools.detach_stem_tremolos_attached_to_component(staff[0])
(StemTremolo(16),)

abjad> marktools.get_stem_tremolos_attached_to_component(staff[0])
()
```

Return tuple or zero or more stem tremolos detached.

marktools.get_annotation_attached_to_component

`abjad.tools.marktools.get_annotation_attached_to_component` (*component*)

New in version 2.0. Get exactly one annotation attached to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> marktools.Annotation('special information') (staff[0])
Annotation('special information') (c'8)

abjad> f(staff)
\new Staff {
    c'8
    d'8
```

```

        e'8
        f'8
    }

```

```

abjad> marktools.get_annotation_attached_to_component(staff[0])
Annotation('special information')(c'8)

```

Return one annotation.

Raise missing mark error when no annotation is attached.

Raise extra mark error when more than one annotation is attached.

marktools.get_annotations_attached_to_component

`abjad.tools.marktools.get_annotations_attached_to_component` (*component*)

New in version 2.0. Get annotations attached to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> marktools.Annotation('annotation 1')(staff[0])
Annotation('annotation 1')(c'8)
abjad> marktools.Annotation('annotation 2')(staff[0])
Annotation('annotation 2')(c'8)

```

```

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
}

```

```

abjad> marktools.get_annotations_attached_to_component(staff[0])
(Annotation('annotation 1')(c'8), Annotation('annotation 2')(c'8))

```

Return tuple of zero or more annotations.

marktools.get_articulations_attached_to_component

`abjad.tools.marktools.get_articulations_attached_to_component` (*component*)

New in version 2.0. Get articulations attached to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> marktools.Articulation('staccato')(staff[0])
Articulation('staccato', '-')(c'8)
abjad> marktools.Articulation('marcato')(staff[0])
Articulation('marcato', '-')(c'8)

```

```

abjad> f(staff)
\new Staff {
    c'8 -\marcato -\staccato
    d'8
    e'8
    f'8
}

```

```
abjad> marktools.get_articulations_attached_to_component(staff[0])
(Articulation('staccato', '-') (c'8), Articulation('marcato', '-') (c'8))
```

Return tuple of zero or more articulations.

marktools.get_comments_attached_to_component

abjad.tools.marktools.get_comments_attached_to_component(*component*)

New in version 2.0. Get comments attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> marktools.Comment('comment 1')(staff[0])
Comment('comment 1')(c'8)
abjad> marktools.Comment('comment 2')(staff[0])
Comment('comment 2')(c'8)
```

```
abjad> f(staff)
\new Staff {
    % comment 1
    % comment 2
    c'8 (
    d'8
    e'8
    f'8 )
}
```

```
abjad> marktools.get_comments_attached_to_component(staff[0])
(Comment('comment 1')(c'8), Comment('comment 2')(c'8))
```

Return tuple of zero or more comments.

marktools.get_lilypond_command_marks_attached_to_component

abjad.tools.marktools.get_lilypond_command_marks_attached_to_component(*component*,
com-
mand_name_string=None)

New in version 2.0. Get LilyPond command marks attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> marktools.LilyPondCommandMark('slurDotted')(staff[0])
LilyPondCommandMark('slurDotted')(c'8)
abjad> marktools.LilyPondCommandMark('slurUp')(staff[0])
LilyPondCommandMark('slurUp')(c'8)
```

```
abjad> f(staff)
\new Staff {
    \slurDotted
    \slurUp
    c'8 (
    d'8
    e'8
    f'8 )
}
```

```
abjad> marktools.get_lilypond_command_marks_attached_to_component(staff[0])
(LilyPondCommandMark('slurDotted')(c'8), LilyPondCommandMark('slurUp')(c'8))
```

Return tuple of zero or more marks.

marktools.get_marks_attached_to_component

`abjad.tools.marktools.get_marks_attached_to_component(component)`

New in version 2.0. Get all marks attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> comment_mark = marktools.Comment('beginning of note content')(staff[0])
abjad> marktools.LilyPondCommandMark('slurDotted')(staff[0])
LilyPondCommandMark('slurDotted')(c'8)

abjad> f(staff)
\new Staff {
    % beginning of note content
    \slurDotted
    c'8 (
    d'8
    e'8
    f'8 )
}

abjad> marktools.get_marks_attached_to_component(staff[0])
(Comment('beginning of note content')(c'8), LilyPondCommandMark('slurDotted')(c'8))
```

Return tuple of zero or more marks. Changed in version 2.0: re-named `marktools.get_all_marks_attached_to_component()` to `marktools.get_marks_attached_to_component()`.

marktools.get_noncontext_marks_attached_to_component

`abjad.tools.marktools.get_noncontext_marks_attached_to_component(component)`

New in version 2.0. Get noncontext marks attached to component:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> contexttools.TimeSignatureMark((2, 4))(staff[0])
TimeSignatureMark(2, 4)(c'8)
abjad> marktools.Articulation('staccato')(staff[0])
Articulation('staccato', '-')(c'8)

abjad> f(staff)
\new Staff {
    \time 2/4
    c'8 -\staccato
    d'8
    e'8
    f'8
}

abjad> marktools.get_noncontext_marks_attached_to_component(staff[0])
(Articulation('staccato', '-')(c'8),)
```

Return tuple of zero or more marks.

marktools.get_stem_tremolos_attached_to_component

abjad.tools.marktools.get_stem_tremolos_attached_to_component(*component*)

New in version 2.0. Get stem tremolos attached to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> marktools.StemTremolo(16)(staff[0])
StemTremolo(16)(c'8)

abjad> f(staff)
\new Staff {
  c'8 :16
  d'8
  e'8
  f'8
}

abjad> marktools.get_stem_tremolos_attached_to_component(staff[0])
(StemTremolo(16)(c'8),)

```

Return tuple of zero or more stem tremolos.

marktools.get_value_of_annotation_attached_to_component

abjad.tools.marktools.get_value_of_annotation_attached_to_component(*component*,
name,
de-
fault_value=None)

New in version 2.0. Get value of annotation with *name* attached to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> marktools.Annotation('special dictionary', {})(staff[0])
Annotation('special dictionary', {})(c'8)

abjad> f(staff)
\new Staff {
  c'8
  d'8
  e'8
  f'8
}

abjad> marktools.get_value_of_annotation_attached_to_component(staff[0], 'special dictionary')
{}

```

Return arbitrary value of annotation.

Return *default_value* when no annotation with *name* is attached.

Raise extra mark error when more than one annotation with *name* is attached.

marktools.is_component_with_lilypond_command_mark_attached

abjad.tools.marktools.is_component_with_lilypond_command_mark_attached(*expr*,
com-
mand_name_string=None)

True when *expr* is component with LilyPond command mark attached:

```
abjad> note = Note("c'4")
abjad> marktools.LilyPondCommandMark('stemUp')(note)
LilyPondCommandMark('stemUp')(c'4)
```

```
abjad> marktools.is_component_with_lilypond_command_mark_attached(note)
True
```

False otherwise:

```
abjad> note = Note("c'4")

abjad> marktools.is_component_with_lilypond_command_mark_attached(note)
False
```

Return boolean.

markuptools

markuptools.Markup

class abjad.tools.markuptools.**Markup**(arg, direction_string=None, style_string='backslash')
 Bases: abjad.tools.markuptools.Mark.Mark.Mark

Abjad model of backslash-style LilyPond markup or Scheme-style LilyPond markup.

Initialize backslash-style markup from string:

```
abjad> markup = markuptools.Markup(r'\bold { "This is markup text." }')

abjad> markup
Markup('\bold { "This is markup text." }')

abjad> f(markup)
\markup { \bold { "This is markup text." } }
```

Initialize Scheme-style markup from string:

```
abjad> markup = markuptools.Markup("(markup #:draw-line '(0 . -1))", style_string = 'scheme')

abjad> markup
Markup("(markup #:draw-line '(0 . -1))")

abjad> f(markup)
#(markup #:draw-line '(0 . -1))
```

Initialize any markup from existing markup:

```
abjad> markup_1 = markuptools.Markup('foo', direction_string = 'up')
abjad> markup_2 = markuptools.Markup(markup_1, direction_string = 'down')

abjad> f(markup_1)
^ \markup { foo }

abjad> f(markup_2)
_ \markup { foo }
```

Attach markup to score components like this:

```

abjad> note = Note("c'4")

abjad> markup = markuptools.Markup(r'\bold { "This is markup text." }')

abjad> markup(note)
Markup('\bold { "This is markup text." }')

abjad> f(note)
c'4 \markup { \bold { "This is markup text." } }

```

Set *direction_string* to 'up', 'down', 'neutral' or none.

Set *style_string* to 'backslash' or 'scheme'.

Markup objects are immutable.

format

Read-only LilyPond format of markup:

```

abjad> markup = markuptools.Markup(r'\bold { "This is markup text." }')
abjad> markup.format
'\markup { \bold { "This is markup text." } }'

```

Return string.

markuptools.MarkupCommand

class abjad.tools.markuptools.**MarkupCommand** (*command, args, markup, is_braced=True*)

Bases: abjad.core._Immutable._Immutable._Immutable

Abjad model of a LilyPond markup command:

```

abjad> circle = markuptools.MarkupCommand('draw-circle', ['#2.5', '#0.1', '##f'], None)
abjad> square = markuptools.MarkupCommand('rounded-box', None, ['hello?'])
abjad> line = markuptools.MarkupCommand('line', None, [square, 'wow!'])
abjad> rotate = markuptools.MarkupCommand('rotate', ['#60'], [line])
abjad> combine = markuptools.MarkupCommand('combine', None, [rotate, circle], is_braced = False)

abjad> print combine
\combine \rotate #60 \line { \rounded-box hello? wow! } \draw-circle #2.5 #0.1 ##f

```

Insert markup command in markup to attach to score components:

```

abjad> note = Note("c'4")

abjad> markup = markuptools.Markup(combine)

abjad> markup(note)
Markup('\combine \rotate #60 \line { \rounded-box hello? wow! } \draw-circle #2.5 #0.1 ##f')

abjad> f(note)
c'4 \markup { \combine \rotate #60 \line { \rounded-box hello? wow! } \draw-circle #2.5 #0.1 ##f'

```

Markup commands are immutable.

args

Read-only tuple of markup command arguments.

command

Read-only string of markup command command-name.

format

Read-only format of markup command:

```
abjad> markup_command = markuptools.MarkupCommand('draw-circle', ['#2.5', '#0.1', '##f'], None)
abjad> markup_command.format
'\\draw-circle #2.5 #0.1 ##f'
```

Return list of strings.

is_braced

Read-only boolean of markup command bracing.

markup

Read-only tuple of markup command's child markup.

report (*output='screen'*)

Report, in an indented human-readable format, the structure of a formatted MarkupCommand.

markuptools.combine_markup_commands

`abjad.tools.markuptools.combine_markup_commands(*commands)`

Combine MarkupCommand and/or string objects.

LilyPond's 'combine' markup command can only take two arguments, so in order to combine more than two stencils, a cascade of 'combine' commands must be employed. `combine_markup_commands` simplifies this process.

```
abjad> from abjad.tools.markuptools import combine_markup_commands
abjad> from abjad.tools.markuptools import MarkupCommand

abjad> markup_a = MarkupCommand('draw-circle', ["#4", '#0.4', '##f'], None)
abjad> markup_b = MarkupCommand('filled-box', ["#'(-4 . 4)", "#'(-0.5 . 0.5)", '#1'], None)
abjad> markup_c = "some text"
abjad> combine_markup_commands(markup_a, markup_b, markup_c).report()
\combine
  \combine
    \draw-circle #4 #0.4 ##f
    \filled-box #'(-4 . 4) #'(-0.5 . 0.5) #1
    "some text"
```

Returns a MarkupCommand instance, or a string if that was the only argument.

markuptools.get_down_markup_attached_to_component

`abjad.tools.markuptools.get_down_markup_attached_to_component(component)`

New in version 2.0. Get down-markup attached to component:

```
abjad> chord = Chord([-11, 2, 5], (1, 4))
abjad> markuptools.Markup('UP', 'up')(chord)
Markup('UP', 'up')
abjad> markuptools.Markup('DOWN', 'down')(chord)
Markup('DOWN', 'down')

abjad> markuptools.get_down_markup_attached_to_component(chord)
(Markup('DOWN', 'down'),)
```

Return tuple of zero or more markup objects.

markuptools.get_markup_attached_to_component

abjad.tools.markuptools.get_markup_attached_to_component(*component*)

New in version 2.0. Get markup attached to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff[:])
abjad> markuptools.Markup('foo')(staff[0])
Markup('foo')
abjad> markuptools.Markup('bar')(staff[0])
Markup('bar')

abjad> f(staff)
\new Staff {
  c'8 - \markup { \column { foo bar } } (
  d'8
  e'8
  f'8 )
}

abjad> markuptools.get_markup_attached_to_component(staff[0])
(Markup('foo'), Markup('bar'))

```

Return tuple of zero or more markup objects.

markuptools.get_up_markup_attached_to_component

abjad.tools.markuptools.get_up_markup_attached_to_component(*component*)

New in version 2.0. Get up-markup attached to component:

```

abjad> chord = Chord([-11, 2, 5], (1, 4))
abjad> markuptools.Markup('UP', 'up')(chord)
Markup('UP', 'up')
abjad> markuptools.Markup('DOWN', 'down')(chord)
Markup('DOWN', 'down')

abjad> markuptools.get_up_markup_attached_to_component(chord)
(Markup('UP', 'up'),)

```

Return tuple of zero or more markup objects.

markuptools.make_big_centered_page_number_markup

abjad.tools.markuptools.make_big_centered_page_number_markup(*text=None*)

New in version 1.1. Make big centered page number markup:

```

abjad> markup = markuptools.make_big_centered_page_number_markup()

abjad> f(markup)
\markup {
  \fill-line {
    \bold \fontsize #3 \concat {
      \on-the-fly #print-page-number-check-first
      \fromproperty #'page:page-number-string } } }

```

Return markup. Changed in version 2.0: renamed `markuptools.big_centered_page_number()` to `markuptools.make_big_centered_page_number_markup()`.

markuptools.remove_markup_attached_to_component

abjad.tools.markuptools.**remove_markup_attached_to_component** (*component*)

New in version 2.0. Remove markup attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> slur = spannertools.SlurSpanner(staff[:])
abjad> markuptools.Markup('foo')(staff[0])
Markup('foo')
abjad> markuptools.Markup('bar')(staff[0])
Markup('bar')

abjad> f(staff)
\new Staff {
  c'8 - \markup { \column { foo bar } } (
  d'8
  e'8
  f'8 )
}

abjad> markuptools.remove_markup_attached_to_component(staff[0])
(Markup('foo'), Markup('bar'))

abjad> f(staff)
\new Staff {
  c'8 (
  d'8
  e'8
  f'8 )
}
```

Return tuple of zero or more markup objects.

markuptools.remove_markup_from_leaves_in_expr

abjad.tools.markuptools.**remove_markup_from_leaves_in_expr** (*expr*)

New in version 1.1. Remove markup from leaves in *expr*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> leaftools.label_leaves_in_expr_with_pitch_class_numbers(staff)
abjad> f(staff)
\new Staff {
  c'8 _ \markup { \small 0 }
  d'8 _ \markup { \small 2 }
  e'8 _ \markup { \small 4 }
  f'8 _ \markup { \small 5 }
}

abjad> markuptools.remove_markup_from_leaves_in_expr(staff)
abjad> f(staff)
\new Staff {
  c'8
  d'8
  e'8
  f'8
}
```

Return `None`. Changed in version 2.0: renamed `label.clear_leaves()` to `markuptools.remove_markup_from_leaves_in_expr()`.

measuretools

measuretools.AnonymousMeasure

class `abjad.tools.measuretools.AnonymousMeasure` (*music=None, **kwargs*)

Bases: `abjad.tools.measuretools.DynamicMeasure`. `DynamicMeasure`
New in version 1.1. Dynamic measure with no time signature:

```
abjad> measure = measuretools.AnonymousMeasure("c'8 d'8 e'8 f'8")
```

```
abjad> f(measure)
{
    \override Staff.TimeSignature #'stencil = ##f
    \time 1/2
    c'8
    d'8
    e'8
    f'8
    \revert Staff.TimeSignature #'stencil
}
```

```
abjad> notes = [Note("c'8"), Note("d'8")]
abjad> measure.extend(notes)
```

```
abjad> f(measure)
{
    \override Staff.TimeSignature #'stencil = ##f
    \time 3/4
    c'8
    d'8
    e'8
    f'8
    c'8
    d'8
    \revert Staff.TimeSignature #'stencil
}
```

Return anonymous measure.

measuretools.DynamicMeasure

class `abjad.tools.measuretools.DynamicMeasure` (*music=None, **kwargs*)

Bases: `abjad.tools.measuretools.Measure`. `Measure` New in version 1.1. Measure sets meter dynamically to exactly equal contents duration:

```
abjad> measure = measuretools.DynamicMeasure("c'8 d'8 e'8")
```

```
abjad> measure
DynamicMeasure(3/8, [c'8, d'8, e'8])
```

```
abjad> f(measure)
{
    \time 3/8
    c'8
```

```

    d'8
    e'8
}

```

Return dynamic measure.

denominator

Get explicit denominator of dynamic measure:

```
abjad> measure = measuretools.DynamicMeasure("c'8 d'8 e'8 f'8")
```

```
abjad> measure.denominator is None
True
```

Set explicit denominator of dynamic measure:

```
abjad> measure.denominator = 8
```

```
abjad> f(measure)
{
    \time 4/8
    c'8
    d'8
    e'8
    f'8
}
```

Set positive integer or none.

extend (*expr*)

Extend dynamic measure:

```
abjad> measure = measuretools.DynamicMeasure("c'8 d'8 e'8")
```

```
abjad> f(measure)
{
    \time 3/8
    c'8
    d'8
    e'8
}
```

```
abjad> measure.extend([Note("f'8"), Note("g'8")])
```

```
abjad> f(measure)
{
    \time 5/8
    c'8
    d'8
    e'8
    f'8
    g'8
}
```

Return none.

preprolated_duration

suppress_meter

Get meter suppression indicator:

```
abjad> measure = measuretools.DynamicMeasure("c'8 d'8 e'8 f'8")
```

```
abjad> f(measure)
{
    \time 1/2
    c'8
    d'8
    e'8
    f'8
}
```

```
abjad> measure.suppress_meter
False
```

Set meter suppression indicator:

```
abjad> measure.suppress_meter = True
```

```
abjad> measure.suppress_meter
True
```

```
abjad> f(measure)
{
    c'8
    d'8
    e'8
    f'8
}
```

Set boolean.

measuretools.Measure

class abjad.tools.measuretools.**Measure** (*meter*, *music=None*, ***kwargs*)

Bases: abjad.tools.containertools.Container.Container New in version 1.1.

Abjad model of a measure:

```
abjad> measure = Measure((4, 8), "c'8 d'8 e'8 f'8")
```

```
abjad> measure
Measure(4/8, [c'8, d'8, e'8, f'8])
```

```
abjad> f(measure)
{
    \time 4/8
    c'8
    d'8
    e'8
    f'8
}
```

Return measure object.

is_binary

is_full

True when meter matches duration of measure:

```
abjad> measure = Measure((4, 8), "c'8 d'8 e'8 f'8")
```

```
abjad> measure.is_full
True
```

False otherwise:

```
abjad> measure = Measure((4, 8), "c'8 d'8 e'8")
```

```
abjad> measure.is_full
False
```

Return boolean.

is_nonbinary

is_overfull

New in version 1.1. True when prolated duration is greater than effective meter duration.

is_underfull

New in version 1.1. True when prolated duration is less than effective meter duration.

measure_number

multiplier

preprolated_duration

Measure contents duration times effective meter multiplier.

measuretools.append_spacer_skip_to_underfull_measure

abjad.tools.measuretools.**append_spacer_skip_to_underfull_measure** (*rigid_measure*)

New in version 1.1. Append spacer skip to underfull *measure*:

```
abjad> measure = Measure((4, 12), "c'8 d'8 e'8 f'8")
abjad> contexttools.detach_time_signature_mark_attached_to_component(measure)
TimeSignatureMark(4, 12)
abjad> contexttools.TimeSignatureMark(5, 12)(measure)
TimeSignatureMark(5, 12)(|5/12, c'8, d'8, e'8, f'8|)
abjad> measure.is_underfull
True
```

```
abjad> measuretools.append_spacer_skip_to_underfull_measure(measure)
Measure(5/12, [c'8, d'8, e'8, f'8, s1 * 1/8])
```

```
abjad> f(measure)
{
  \time 5/12
  \scaleDurations #'(2 . 3) {
    c'8
    d'8
    e'8
    f'8
    s1 * 1/8
  }
}
```

Append nothing to nonunderfull *measure*.

Return *measure*. Changed in version 2.0: renamed `measuretools.make_measures_with_full_measure_spacer_skip` to `measuretools.append_spacer_skip_to_underfull_measure()`.

measuretools.append_spacer_skips_to_underfull_measures_in_expr

`abjad.tools.measuretools.append_spacer_skips_to_underfull_measures_in_expr(expr)`

New in version 1.1. Append spacer skips to underfull measures in *expr*:

```
abjad> staff = Staff(Measure((3, 8), "c'8 d'8 e'8") * 3)
abjad> contexttools.detach_time_signature_mark_attached_to_component(staff[1])
TimeSignatureMark(3, 8)
abjad> contexttools.TimeSignatureMark(4, 8)(staff[1])
TimeSignatureMark(4, 8)(|4/8, c'8, d'8, e'8|)
abjad> contexttools.detach_time_signature_mark_attached_to_component(staff[2])
TimeSignatureMark(3, 8)
abjad> contexttools.TimeSignatureMark(5, 8)(staff[2])
TimeSignatureMark(5, 8)(|5/8, c'8, d'8, e'8|)
abjad> staff[1].is_underfull
True
abjad> staff[2].is_underfull
True
```

```
abjad> measuretools.append_spacer_skips_to_underfull_measures_in_expr(staff)
[Measure(4/8, [c'8, d'8, e'8, s1 * 1/8]), Measure(5/8, [c'8, d'8, e'8, s1 * 1/4])]
```

```
abjad> f(staff)
\new Staff {
    {
        \time 3/8
        c'8
        d'8
        e'8
    }
    {
        \time 4/8
        c'8
        d'8
        e'8
        s1 * 1/8
    }
    {
        \time 5/8
        c'8
        d'8
        e'8
        s1 * 1/4
    }
}
```

Return measures treated. Changed in version 2.0: renamed `measuretools.remedy_underfull_measures()` to `measuretools.append_spacer_skips_to_underfull_measures_in_expr()`.

measuretools.apply_beam_spanner_to_measure

`abjad.tools.measuretools.apply_beam_spanner_to_measure(measure)`

New in version 2.0. Apply beam spanner to *measure*:

```
abjad> measure = Measure((2, 8), "c'8 d'8")
```

```

abjad> f(measure)
{
    \time 2/8
    c'8
    d'8
}

abjad> measuretools.apply_beam_spanner_to_measure(measure)
BeamSpanner(|2/8(2)|)

abjad> f(measure)
{
    \time 2/8
    c'8 [
    d'8 ]
}

```

Return beam spanner.

measuretools.apply_beam_spanners_to_measures_in_expr

abjad.tools.measuretools.**apply_beam_spanners_to_measures_in_expr**(*expr*)

New in version 1.1. Apply beam spanners to measures in *expr*:

```

abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)

abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
}

abjad> measuretools.apply_beam_spanners_to_measures_in_expr(staff)
[BeamSpanner(|2/8(2)|), BeamSpanner(|2/8(2)|)]

abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8 [
        d'8 ]
    }
    {
        \time 2/8
        e'8 [
        f'8 ]
    }
}

```


Return list of beams created. Changed in version 2.0: renamed `measuretools.beam()` to `measuretools.apply_beam_spanners_to_measures_in_expr()`.

measuretools.apply_complex_beam_spanner_to_measure

`abjad.tools.measuretools.apply_complex_beam_spanner_to_measure(measure)`

New in version 2.0. Apply complex beam spanner to *measure*:

```
abjad> measure = Measure((2, 8), "c'8 d'8")
```

```
abjad> f(measure)
```

```
{
    \time 2/8
    c'8
    d'8
}
```

```
abjad> measuretools.apply_complex_beam_spanner_to_measure(measure)
```

```
DuratedComplexBeamSpanner(|2/8(2)|)
```

```
abjad> f(measure)
```

```
{
    \time 2/8
    \set stemLeftBeamCount = #0
    \set stemRightBeamCount = #1
    c'8 [
    \set stemLeftBeamCount = #1
    \set stemRightBeamCount = #0
    d'8 ]
}
```

Return complex beam spanner.

measuretools.apply_complex_beam_spanners_to_measures_in_expr

`abjad.tools.measuretools.apply_complex_beam_spanners_to_measures_in_expr(expr)`

New in version 2.0. Apply complex beam spanners to measures in *expr*:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
```

```
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
```

```
abjad> f(staff)
```

```
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
}
```

```
abjad> measuretools.apply_complex_beam_spanners_to_measures_in_expr(staff)
[DuratedComplexBeamSpanner(|2/8(2)|), DuratedComplexBeamSpanner(|2/8(2)|)]
```

```
abjad> f(staff)
\new Staff {
  {
    \time 2/8
    \set stemLeftBeamCount = #0
    \set stemRightBeamCount = #1
    c'8 [
    \set stemLeftBeamCount = #1
    \set stemRightBeamCount = #0
    d'8 ]
  }
  {
    \time 2/8
    \set stemLeftBeamCount = #0
    \set stemRightBeamCount = #1
    e'8 [
    \set stemLeftBeamCount = #1
    \set stemRightBeamCount = #0
    f'8 ]
  }
}
```

Return list of beams created.

measuretools.apply_durated_complex_beam_spanner_to_measures

`abjad.tools.measuretools.apply_durated_complex_beam_spanner_to_measures` (*measures*)

New in version 1.1. Apply durated complex beam spanner to *measures*:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
```

```
abjad> f(staff)
\new Staff {
  {
    \time 2/8
    c'8
    d'8
  }
  {
    \time 2/8
    e'8
    f'8
  }
}
```

```
abjad> measures = staff[:]
abjad> measuretools.apply_durated_complex_beam_spanner_to_measures(measures)
DuratedComplexBeamSpanner(|2/8(2)|, |2/8(2)|)
```

```
abjad> f(staff)
\new Staff {
  {
    \time 2/8
```

```

        \set stemLeftBeamCount = #0
        \set stemRightBeamCount = #1
        c'8 [
        \set stemLeftBeamCount = #1
        \set stemRightBeamCount = #1
        d'8
    ]
}
{
    \time 2/8
    \set stemLeftBeamCount = #1
    \set stemRightBeamCount = #1
    e'8
    \set stemLeftBeamCount = #1
    \set stemRightBeamCount = #0
    f'8 ]
}
}

```

Set beam spanner durations to preprolated measure durations.

Return beam spanner created. Changed in version 2.0: renamed `measuretools.beam_together()`.

measuretools.apply_full_measure_tuplets_to_contents_of_measures_in_expr

`abjad.tools.measuretools.apply_full_measure_tuplets_to_contents_of_measures_in_expr(expr)`

New in version 2.0. Apply full-measure tuplets to contents of measures in *expr*:

```

abjad> staff = Staff([Measure((2, 8), "c'8 d'8"), Measure((3, 8), "e'8 f'8 g'8")])

abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 3/8
        e'8
        f'8
        g'8
    }
}

abjad> measuretools.apply_full_measure_tuplets_to_contents_of_measures_in_expr(staff)

abjad> f(staff)
\new Staff {
    {
        \time 2/8
        {
            c'8
            d'8
        }
    }
    {
        \time 3/8
        {

```

```

        e'8
        f'8
        g'8
    }
}

```

Return none.

measuretools.color_measure

`abjad.tools.measuretools.color_measure(measure, color='red')`

New in version 2.0. Color *measure* with *color*:

```

abjad> measure = Measure((2, 8), "c'8 d'8")

abjad> f(measure)
{
    \time 2/8
    c'8
    d'8
}

abjad> measuretools.color_measure(measure, 'red')
Measure(2/8, [c'8, d'8])

abjad> f(measure)
{
    \override Beam #'color = #red
    \override Dots #'color = #red
    \override NoteHead #'color = #red
    \override Staff.TimeSignature #'color = #red
    \override Stem #'color = #red
    \time 2/8
    c'8
    d'8
    \revert Beam #'color
    \revert Dots #'color
    \revert NoteHead #'color
    \revert Staff.TimeSignature #'color
    \revert Stem #'color
}

```

Return colored *measure*.

Color names appear in LilyPond Learning Manual appendix B.5.

measuretools.color_nonbinary_measures_in_expr

`abjad.tools.measuretools.color_nonbinary_measures_in_expr(expr, color='red')`

New in version 2.0. Color nonbinary measures in *expr* with *color*:

```

abjad> staff = Staff(Measure((2, 8), "c'8 d'8") * 2)
abjad> measuretools.scale_measure_denominator_and_adjust_measure_contents(staff[1], 3)
Measure(3/12, [c'8., d'8.])

```

```

abjad> f(staff)
\new Staff {
  {
    \time 2/8
    c'8
    d'8
  }
  {
    \time 3/12
    \scaleDurations #'(2 . 3) {
      c'8.
      d'8.
    }
  }
}

abjad> measuretools.color_nonbinary_measures_in_expr(staff, 'red')
[Measure(3/12, [c'8., d'8.])]

abjad> f(staff)
\new Staff {
  {
    \time 2/8
    c'8
    d'8
  }
  {
    \override Beam #'color = #red
    \override Dots #'color = #red
    \override NoteHead #'color = #red
    \override Staff.TimeSignature #'color = #red
    \override Stem #'color = #red
    \time 3/12
    \scaleDurations #'(2 . 3) {
      c'8.
      d'8.
    }
    \revert Beam #'color
    \revert Dots #'color
    \revert NoteHead #'color
    \revert Staff.TimeSignature #'color
    \revert Stem #'color
  }
}

```

Return list of measures colored.

Color names appear in LilyPond Learning Manual appendix B.5.

measuretools.comment_measures_in_container_with_measure_numbers

`abjad.tools.measuretools.comment_measures_in_container_with_measure_numbers` (*container*)

New in version 1.1. Comment measures in *container* with measure numbers:

```

abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(sta

```

```
abjad> measuretools.comment_measures_in_container_with_measure_numbers(staff)
```

```
abjad> f(staff)
\new Staff {
    % start measure 1
    {
        \time 2/8
        c'8
        d'8
    }
    % stop measure 1
    % start measure 2
    {
        \time 2/8
        e'8
        f'8
    }
    % stop measure 2
    % start measure 3
    {
        \time 2/8
        g'8
        a'8
    }
    % stop measure 3
}
```

Changed in version 2.0: renamed `label.measure_numbers()` to `measuretools.comment_measures_in_container_with_measure_numbers()`.

measuretools.extend_measures_in_expr_and_apply_full_measure_tuplets_to_measure_contents

```
abjad.tools.measuretools.extend_measures_in_expr_and_apply_full_measure_tuplets_to_measure
```

New in version 2.0. Extend measures in *expr* with *supplement* and apply full-measure tuplets to contents of measures:

```
abjad> staff = Staff([Measure((2, 8), "c'8 d'8"), Measure((3, 8), "e'8 f'8 g'8")])
```

```
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 3/8
        e'8
        f'8
        g'8
    }
}
```

```

abjad> supplement = [Rest((1, 16))]
abjad> measuretools.extend_measures_in_expr_and_apply_full_measure_tuplets_to_measure_contents(s

abjad> f(staff)
\new Staff {
  {
    \time 2/8
    \times 4/5 {
      c'8
      d'8
      r16
    }
  }
  {
    \time 3/8
    \fraction \times 6/7 {
      e'8
      f'8
      g'8
      r16
    }
  }
}

```

Return none.

measuretools.fill_measures_in_expr_with_big_endian_notes

```

abjad.tools.measuretools.fill_measures_in_expr_with_big_endian_notes(expr,
                                                                    iterc-
                                                                    trl=None)

```

New in version 1.1. Fill measures in *expr* with big-endian notes.

measuretools.fill_measures_in_expr_with_full_measure_spacer_skips

```

abjad.tools.measuretools.fill_measures_in_expr_with_full_measure_spacer_skips(expr,
                                                                    iter-
                                                                    c-
                                                                    trl=None)

```

New in version 1.1. Fill measures in *expr* with full-measure spacer skips.

measuretools.fill_measures_in_expr_with_little_endian_notes

```

abjad.tools.measuretools.fill_measures_in_expr_with_little_endian_notes(expr,
                                                                    iter-
                                                                    c-
                                                                    trl=None)

```

New in version 1.1. Fill measures in *expr* with little-endian notes.

measuretools.fill_measures_in_expr_with_meter_denominator_notes

abjad.tools.measuretools.**fill_measures_in_expr_with_meter_denominator_notes**(*expr*,
iter-
c-
trl=None)

New in version 1.1. Fill measures in *expr* with meter denominator notes:

```
abjad> staff = Staff([Measure((3, 4), [ ]), Measure((3, 16), [ ]), Measure((3, 8), [ ])])
abjad> measuretools.fill_measures_in_expr_with_meter_denominator_notes(staff)
```

```
abjad> f(staff)
\new Staff {
  {
    \time 3/4
    c'4
    c'4
    c'4
  }
  {
    \time 3/16
    c'16
    c'16
    c'16
  }
  {
    \time 3/8
    c'8
    c'8
    c'8
  }
}
```

Delete existing contents of measures in *expr*.

Return none.

measuretools.fill_measures_in_expr_with_repeated_notes

abjad.tools.measuretools.**fill_measures_in_expr_with_repeated_notes**(*expr*, *writ-*
ten_duration,
iterc-
trl=None)

New in version 1.1. Fill measures in *expr* with repeated notes.

measuretools.fuse_contiguous_measures_in_container_cyclically_by_counts

abjad.tools.measuretools.**fuse_contiguous_measures_in_container_cyclically_by_counts**(*container*,
counts,
mark=Fa)

New in version 1.1. Fuse contiguous measures in *container* cyclically by *counts*:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 5)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
```



```

abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
    {
        \time 2/8
        g'8
        a'8
    }
    {
        \time 2/8
        b'8
        c''8
    }
    {
        \time 2/8
        d''8
        e''8
    }
}

abjad> counts = (2, 1)
abjad> measuretools.fuse_contiguous_measures_in_container_cyclically_by_counts(staff, counts)

abjad> f(staff)
\new Staff {
    {
        \time 4/8
        c'8
        d'8
        e'8
        f'8
    }
    {
        \time 2/8
        g'8
        a'8
    }
    {
        \time 4/8
        b'8
        c''8
        d''8
        e''8
    }
}

```

Return none.

Set *mark* to true to mark fused measures for later reference. Changed
in version 2.0: renamed `fuse_measures_by_counts_cyclic()` to

```
measuretools.fuse_contiguous_measures_in_container_cyclically_by_counts().
```

measuretools.fuse_measures

abjad.tools.measuretools.**fuse_measures** (*measures*)

New in version 1.1. Fuse *measures*:

```
abjad> staff = Staff(measuretools.make_measures_with_full_measure_spacer_skips([(1, 8), (2, 16)]))
abjad> measuretools.fill_measures_in_expr_with_repeated_notes(staff, Duration(1, 16))
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> spannertools.BeamSpanner(staff.leaves)
BeamSpanner(c'16, d'16, e'16, f'16)
```

```
abjad> f(staff)
\new Staff {
  {
    \time 1/8
    c'16 [
    d'16
  ]
  {
    \time 2/16
    e'16
    f'16 ]
  }
}
```

```
abjad> measuretools.fuse_measures(staff[:])
Measure(2/8, [c'16, d'16, e'16, f'16])
```

```
abjad> f(staff)
\new Staff {
  {
    \time 2/8
    c'16 [
    d'16
    e'16
    f'16 ]
  }
}
```

Return new measure.

Allow parent-contiguous *measures*.

Allow outside-of-score *measures*.

Do not define measure fusion across intervening container boundaries.

Calculate best new time signature.

Instantiate new measure.

Give *measures* contents to new measure.

Give *measures* dominant spanners to new measure.

Give *measures* parentage to new measure.

Leave *measures* empty, unspanned and outside-of-score. Changed in version 2.0: renamed `fuse_measures_by_reference()` to `measuretools.fuse_measures()`.

measuretools.get_first_measure_in_improper_parentage_of_component

`abjad.tools.measuretools.get_first_measure_in_improper_parentage_of_component` (*component*)
 New in version 2.0. Get first measure in improper parentage of *component*:

```
abjad> measure = Measure((2, 4), "c'8 d'8 e'8 f'8")
abjad> staff = Staff([measure])

abjad> f(staff)
\new Staff {
    {
        \time 2/4
        c'8
        d'8
        e'8
        f'8
    }
}

abjad> measuretools.get_first_measure_in_improper_parentage_of_component(staff.leaves[0])
Measure(2/4, [c'8, d'8, e'8, f'8])
```

Return measure or none.

measuretools.get_first_measure_in_proper_parentage_of_component

`abjad.tools.measuretools.get_first_measure_in_proper_parentage_of_component` (*component*)
 New in version 2.0. Get first measure in proper parentage of *component*:

```
abjad> measure = Measure((2, 4), "c'8 d'8 e'8 f'8")
abjad> staff = Staff([measure])

abjad> f(staff)
\new Staff {
    {
        \time 2/4
        c'8
        d'8
        e'8
        f'8
    }
}

abjad> measuretools.get_first_measure_in_proper_parentage_of_component(staff.leaves[0])
Measure(2/4, [c'8, d'8, e'8, f'8])
```

Return measure or none.

measuretools.get_next_measure_from_component

`abjad.tools.measuretools.get_next_measure_from_component` (*component*)
 New in version 1.1. Get next measure from *component*.

When *component* is voice, staff or other sequential context, and when *component* contains a measure, return first measure in *component*. This starts the process of forwards measure iteration.

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> measuretools.get_next_measure_from_component(staff)
Measure(2/8, [c'8, d'8])
```

When *component* is voice, staff or other sequential context, and when *component* contains no measure, raise missing measure error.

When *component* is a measure and there is a measure immediately following *component*, return measure immediately following component.

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> measuretools.get_prev_measure_from_component(staff[0]) is None
True
```

When *component* is a measure and there is no measure immediately following *component*, return None.

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> measuretools.get_prev_measure_from_component(staff[-1])
Measure(2/8, [c'8, d'8])
```

When *component* is a leaf and there is a measure in the parentage of *component*, return the measure in the parentage of *component*.

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> measuretools.get_prev_measure_from_component(staff.leaves[0])
Measure(2/8, [c'8, d'8])
```

When *component* is a leaf and there is no measure in the parentage of *component*, raise missing measure error. Changed in version 2.0: renamed `iterate.measure_next()` to `measuretools.get_next_measure_from_component()`.

measuretools.get_nth_measure_in_expr

`abjad.tools.measuretools.get_nth_measure_in_expr(expr, n=0)`

New in version 2.0. Get nth measure in *expr*:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)

abjad> f(staff)
\new Staff {
  {
    \time 2/8
    c'8
    d'8
  }
  {
    \time 2/8
    e'8
    f'8
  }
  {
    \time 2/8
    g'8
  }
}
```

```

        a'8
    }
}

```

Read forward for positive values of n .

```

abjad> for n in range(3):
...     measuretools.get_nth_measure_in_expr(staff, n)
...
Measure(2/8, [c'8, d'8])
Measure(2/8, [e'8, f'8])
Measure(2/8, [g'8, a'8])

```

Read backward for negative values of n .

```

abjad> for n in range(3, -1, -1):
...     measuretools.get_nth_measure_in_expr(staff, n)
...
Measure(2/8, [g'8, a'8])
Measure(2/8, [e'8, f'8])
Measure(2/8, [c'8, d'8])

```

Changed in version 2.0: renamed `iterate.get_nth_measure()` to `measuretools.get_nth_measure_in_expr()`.

`measuretools.get_one_indexed_measure_number_in_expr`

`abjad.tools.measuretools.get_one_indexed_measure_number_in_expr(expr, measure_number)`

New in version 2.0. Get one-indexed *measure_number* in *expr*:

```

abjad> t = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)

abjad> f(t)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
    {
        \time 2/8
        g'8
        a'8
    }
}
abjad> measuretools.get_one_indexed_measure_number_in_expr(t, 3)
Measure(2/8, [g'8, a'8])

```

Note that measures number from 1.

measuretools.get_prev_measure_from_component

`abjad.tools.measuretools.get_prev_measure_from_component(component)`

New in version 1.1. Get previous measure from *component*.

When *component* is voice, staff or other sequential context, and when *component* contains a measure, return last measure in *component*. This starts the process of backwards measure iteration.

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> measuretools.get_prev_measure_from_component(staff)
Measure(2/8, [e'8, f'8])
```

When *component* is voice, staff or other sequential context, and when *component* contains no measure, raise missing measure error.

When *component* is a measure and there is a measure immediately preceeding *component*, return measure immediately preceeding component.

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> measuretools.get_prev_measure_from_component(staff[-1])
Measure(2/8, [c'8, d'8])
```

When *component* is a measure and there is no measure immediately preceeding *component*, return None.

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> measuretools.get_prev_measure_from_component(staff[0]) is None
True
```

When *component* is a leaf and there is a measure in the parentage of *component*, return the measure in the parentage of *component*.

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> measuretools.get_prev_measure_from_component(staff.leaves[0])
Measure(2/8, [c'8, d'8])
```

When *component* is a leaf and there is no measure in the parentage of *component*, raise missing measure error. Changed in version 2.0: renamed `iterate.measure_prev()` to `measuretools.get_prev_measure_from_component()`.

measuretools.iterate_measures_backward_in_expr

`abjad.tools.measuretools.iterate_measures_backward_in_expr(expr, start=0, stop=None)`

New in version 2.0. Iterate measures backward in *expr*:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)

abjad> f(staff)
\new Staff {
  {
    \time 2/8
    c'8
    d'8
  }
}
```

```

    {
        \time 2/8
        e'8
        f'8
    }
    {
        \time 2/8
        g'8
        a'8
    }
}

abjad> for measure in measuretools.iterate_measures_backward_in_expr(staff):
...     measure
...
Measure(2/8, [g'8, a'8])
Measure(2/8, [e'8, f'8])
Measure(2/8, [c'8, d'8])

```

Use the optional *start* and *stop* keyword parameters to control indices of iteration.

```

abjad> for measure in measuretools.iterate_measures_backward_in_expr(staff, start = 1):
...     measure
...
Measure(2/8, [e'8, f'8])
Measure(2/8, [c'8, d'8])

abjad> for measure in measuretools.iterate_measures_backward_in_expr(staff, start = 0, stop = 2):
...     measure
...
Measure(2/8, [g'8, a'8])
Measure(2/8, [e'8, f'8])

```

Changed in version 2.0: renamed `iterate_measures_backward_in()` to `measuretools.iterate_measures_backward_in_expr()`.

measuretools.iterate_measures_forward_in_expr

`abjad.tools.measuretools.iterate_measures_forward_in_expr(expr, start=0, stop=None)`

New in version 2.0. Iterate measures forward in *expr*:

```

abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)

abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
}

```

```

        \time 2/8
        g'8
        a'8
    }
}

abjad> for measure in measuretools.iterate_measures_forward_in_expr(staff):
...     measure
...
Measure(2/8, [c'8, d'8])
Measure(2/8, [e'8, f'8])
Measure(2/8, [g'8, a'8])

```

Use the optional *start* and *stop* keyword parameters to control the start and stop indices of iteration.

```

abjad> for measure in measuretools.iterate_measures_forward_in_expr(staff, start = 1):
...     measure
...
Measure(2/8, [e'8, f'8])
Measure(2/8, [g'8, a'8])

abjad> for measure in measuretools.iterate_measures_forward_in_expr(staff, start = 0, stop = 2):
...     measure
...
Measure(2/8, [c'8, d'8])
Measure(2/8, [e'8, f'8])

```

Changed in version 2.0: renamed `iterate.measures_forward_in()` to `measuretools.iterate_measures_forward_in_expr()`.

measuretools.list_time_signatures_of_measures_in_expr

`abjad.tools.measuretools.list_time_signatures_of_measures_in_expr(components)`

New in version 2.0. List time signatures of measures in *expr*:

```

abjad> from abjad.tools import metertools

abjad> staff = Staff([Measure((2, 8), "c8 d8"), Measure((3, 8), "c8 d8 e8"), Measure((4, 8), "c8

abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c8
        d8
    }
    {
        \time 3/8
        c8
        d8
        e8
    }
    {
        \time 4/8
        c8
        d8
        e8
    }
}

```



```

        f8
    }
}

abjad> measuretools.list_time_signatures_of_measures_in_expr(staff)
[TimeSignatureMark(2, 8)(|2/8, c8, d8|), TimeSignatureMark(3, 8)(|3/8, c8, d8, e8|), TimeSignatureMark(4, 8)(|4/8, c8, d8, e8, f8|)]

Return list of zero or more time signatures.      Changed in version 2.0:      re-
named      measuretools.list_time_signatures_of_mesures_in_expr()      to
measuretools.list_time_signatures_of_measures_in_expr().

```

measuretools.make_measures_with_full_measure_spacer_skips

`abjad.tools.measuretools.make_measures_with_full_measure_spacer_skips(meters)`

New in version 1.1. Make measures with full-measure spacer skips from *meters*:

```

abjad> measures = measuretools.make_measures_with_full_measure_spacer_skips([(1, 8), (5, 16), (5, 16)])

abjad> staff = Staff(measures)

abjad> f(staff)
\new Staff {
    {
        \time 1/8
        s1 * 1/8
    }
    {
        \time 5/16
        s1 * 5/16
    }
    {
        \time 5/16
        s1 * 5/16
    }
}

```

Return list of rigid measures. Changed in version 2.0: renamed `measuretools.make()` to `measuretools.make_measures_with_full_measure_spacer_skips()`.

measuretools.move_measure_prolation_to_full_measure_tuplet

`abjad.tools.measuretools.move_measure_prolation_to_full_measure_tuplet(expr)`

New in version 2.0. Move measure prolotion to full-measure tuplet.

Turn nonbinary measures into binary measures containing a single fixed-duration tuplet.

This is the inverse of `measuretools.move_prolation_of_full_measure_tuplet_to_meter_of_measure()`.

Note that not all nonbinary measures can be made binary.

Returns `None` because processes potentially many measures. Changed in version 2.0: renamed `measuretools.project()` to `measuretools.move_measure_prolation_to_full_measure_tuplet()`.

measuretools.move_prolation_of_full_measure_tuplet_to_meter_of_measure

`abjad.tools.measuretools.move_prolation_of_full_measure_tuplet_to_meter_of_measure(expr)`
 New in version 1.1. Move prolotion of full-measure tuplet to meter of measure.

Measures usually become nonbinary as as result:

```
abjad> t = Measure((2, 8), [tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")])
abjad> measuretools.move_prolation_of_full_measure_tuplet_to_meter_of_measure(t)
```

```
abjad> f(t)
{
    \time 3/12
    \scaleDurations #'(2 . 3) {
        c'8
        d'8
        e'8
    }
}
```

Return `none`. Changed in version 2.0: renamed `measuretools.subsume()` to `measuretools.move_prolation_of_full_measure_tuplet_to_meter_of_measure()`.

measuretools.multiply_contents_of_measures_in_expr

`abjad.tools.measuretools.multiply_contents_of_measures_in_expr(expr, n)`
 New in version 1.1. Multiply contents $n - 1$ times and adjust meter of every measure in *expr*:

```
abjad> measure = Measure((3, 8), "c'8 d'8 e'8")
abjad> spannertools.BeamSpanner(measure.leaves)
BeamSpanner(c'8, d'8, e'8)
```

```
abjad> f(measure)
{
    \time 3/8
    c'8 [
    d'8
    e'8 ]
}
```

```
abjad> measuretools.multiply_contents_of_measures_in_expr(measure, 3)
```

```
abjad> f(measure)
{
    \time 9/8
    c'8 [
    d'8
    e'8 ]
    c'8 [
    d'8
    e'8 ]
    c'8 [
    d'8
    e'8 ]
}
```

Changed in version 2.0: renamed `measuretools.spin()` to `measuretools.multiply_contents_of_measures_in_expr()`.

measuretools.multiply_contents_of_measures_in_expr_and_scale_meter_denominators

abjad.tools.measuretools.multiply_contents_of_measures_in_expr_and_scale_meter_denominators

New in version 1.1. Multiply contents of measures in *expr* and scale meter denominators.

Expr may be any Abjad expression. Concentration_pairs a Python list of pairs, each of the form (spin_count, scalar_denominator). Both spin_count and scalar_denominator must be positive integers.

Iterate *expr*. For every measure in *expr*, spin measure by the spin_count element in concentration_pair and scale measure by 1/scalar_denominator element in concentration_pair.

Return Python list of transformed measures:

```
abjad> t = Measure((3, 16), notetools.make_repeated_notes(3, Duration(1, 16)))
abjad> print(measuretools.multiply_contents_of_measures_in_expr_and_scale_meter_denominators(t,
|9/48, c'32, c'32, c'32, c'32, c'32, c'32, c'32, c'32, c'32|)
```

```
abjad> t = Measure((3, 16), notetools.make_repeated_notes(3, Duration(1, 16)))
abjad> print(measuretools.multiply_contents_of_measures_in_expr_and_scale_meter_denominators(t,
|9/32, c'32, c'32, c'32, c'32, c'32, c'32, c'32, c'32, c'32|)
```

```
abjad> t = Measure((3, 16), notetools.make_repeated_notes(3, Duration(1, 16)))
abjad> print(measuretools.multiply_contents_of_measures_in_expr_and_scale_meter_denominators(t,
|9/16, c'16, c'16, c'16, c'16, c'16, c'16, c'16, c'16, c'16|)
```

Changed in version 2.0: renamed measuretools.concentrate() to measuretools.multiply_contents_of_measures_in_expr_and_scale_meter_denominators().

measuretools.pad_measures_in_expr_with_rests

abjad.tools.measuretools.pad_measures_in_expr_with_rests(*expr*, *front*, *back*, *splice=False*)

New in version 1.1. Pad measures in *expr* with rests.

Iterate all measures in *expr*. Insert rest with duration equal to *front* at beginning of each measure. Insert rest with duration equal to *back* at end of each measure.

Set *front* to a positive rational or none. Set *back* to a positive rational or none.

Note that this function is designed to help create regularly spaced charts and tables of musical materials. This function makes most sense when used on anonymous measures or dynamic measures.

```
abjad> t = Staff(measuretools.AnonymousMeasure("c'8 d'8") * 2)
abjad> front, back = Duration(1, 32), Duration(1, 64)
abjad> measuretools.pad_measures_in_expr_with_rests(t, front, back)
```

```
abjad> f(t)
\new Staff {
    {
        \override Staff.TimeSignature #'stencil = ##f
        \time 19/64
        r32
        c'8
        d'8
        r64
    }
}
```

```

        \revert Staff.TimeSignature #'stencil
    }
    {
        \override Staff.TimeSignature #'stencil = ##f
        \time 19/64
        r32
        c'8
        d'8
        r64
        \revert Staff.TimeSignature #'stencil
    }
}

```

Works when measures contain stacked voices:

```

abjad> measure = measuretools.DynamicMeasure(Voice(notetools.make_repeated_notes(2)) * 2)
abjad> measure.is_parallel = True
abjad> t = Staff(measure * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> measuretools.pad_measures_in_expr_with_rests(t, Duration(1, 32), Duration(1, 64))

abjad> f(t)
\new Staff {
    <<
        \time 19/64
        \new Voice {
            r32
            c'8
            d'8
            r64
        }
        \new Voice {
            r32
            e'8
            f'8
            r64
        }
    >>
    <<
        \time 19/64
        \new Voice {
            r32
            g'8
            a'8
            r64
        }
        \new Voice {
            r32
            b'8
            c''8
            r64
        }
    >>
}

```

Set the optional *splice* keyword to `True` to extend edge spanners over newly inserted rests:

```

abjad> t = measuretools.DynamicMeasure("c'8 d'8")
abjad> spannertools.BeamSpanner(t[:])

```

```

BeamSpanner(c'8, d'8)
abjad> measuretools.pad_measures_in_expr_with_rests(t, Duration(1, 32), Duration(1, 64), splice

abjad> f(t)
{
    \time 19/64
    r32 [
        c'8
        d'8
        r64 ]
}

```

Return none.

Raise value when *front* is neither a positive rational nor none.

Raise value when *back* is neither a positive rational nor none. Changed in version 2.0: renamed `layout.insert_measure_padding_rest()` to `measuretools.pad_measures_in_expr_with_rests()`.

measuretools.pad_measures_in_expr_with_skips

```

abjad.tools.measuretools.pad_measures_in_expr_with_skips(expr, front, back,
                                                         splice=False)

```

New in version 2.0. Pad measures in *expr* with skips.

Iterate all measures in *expr*. Insert skip with duration equal to *front* at beginning of each measure. Insert skip with duration equal to *back* at end of each measure.

Set *front* to a positive rational or none. Set *back* to a positive rational or none.

Note that this function is designed to help create regularly spaced charts and tables of musical materials. This function makes most sense when used on anonymous measures and dynamic measures.

```

abjad> t = Staff(measuretools.AnonymousMeasure("c'8 d'8") * 2)
abjad> front, back = Duration(1, 32), Duration(1, 64)
abjad> measuretools.pad_measures_in_expr_with_skips(t, front, back)

abjad> f(t)
\new Staff {
    {
        \override Staff.TimeSignature #'stencil = ##f
        \time 19/64
        s32
        c'8
        d'8
        s64
        \revert Staff.TimeSignature #'stencil
    }
    {
        \override Staff.TimeSignature #'stencil = ##f
        \time 19/64
        s32
        c'8
        d'8
        s64
        \revert Staff.TimeSignature #'stencil
    }
}

```

Works when measures contain stacked voices.

```
abjad> measure = measuretools.DynamicMeasure(Voice(notetools.make_repeated_notes(2)) * 2)
abjad> measure.is_parallel = True
abjad> t = Staff(measure * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> measuretools.pad_measures_in_expr_with_skips(t, Duration(1, 32), Duration(1, 64))

abjad> f(t)
\new Staff {
  <<
    \time 19/64
    \new Voice {
      s32
      c'8
      d'8
      s64
    }
    \new Voice {
      s32
      e'8
      f'8
      s64
    }
  >>
  <<
    \time 19/64
    \new Voice {
      s32
      g'8
      a'8
      s64
    }
    \new Voice {
      s32
      b'8
      c''8
      s64
    }
  >>
}
```

Set the optional *splice* keyword to True to extend edge spanners over newly inserted skips:

```
abjad> t = measuretools.DynamicMeasure("c'8 d'8")
abjad> spannertools.BeamSpanner(t[:])
BeamSpanner(c'8, d'8)
abjad> measuretools.pad_measures_in_expr_with_skips(t, Duration(1, 32), Duration(1, 64), splice

abjad> f(t)
{
  \time 19/64
  s32 [
  c'8
  d'8
  s64 ]
}
```

Return none.

Raise value error when *front* is neither a positive rational nor none.

Raise value error when *back* is neither a positive rational nor none. Changed in version 2.0: renamed `layout.insert_measure_padding_skip()` to `measuretools.pad_measures_in_expr_with_skips()`.

measuretools.pitch_array_row_to_measure

`abjad.tools.measuretools.pitch_array_row_to_measure` (*pitch_array_row*,
cell_duration_denominator=8)

New in version 2.0. Change *pitch_array_row* to measure with meter *pitch_array_row.width* over *cell_duration_denominator*:

```
abjad> from abjad.tools import pitcharraytools
abjad> array = pitcharraytools.PitchArray([
...     [1, (2, 1), ([-2, -1.5], 2)],
...     [(7, 2), (6, 1), 1]])

abjad> print array
[ ] [d'] [bf bqf  ]
[g'    ] [fs'   ] [ ]

abjad> measure = measuretools.pitch_array_row_to_measure(array.rows[0])

abjad> f(measure)
{
    \time 4/8
    r8
    d'8
    <bf bqf>4
}
```

Return measure.

measuretools.pitch_array_to_measures

`abjad.tools.measuretools.pitch_array_to_measures` (*pitch_array*,
cell_duration_denominator=8)

New in version 2.0. Change *pitch_array* to measures with meters *row.width* over *cell_duration_denominator* for each row in *pitch_array*:

```
abjad> from abjad.tools import pitcharraytools
abjad> array = pitcharraytools.PitchArray([
...     [1, (2, 1), ([-2, -1.5], 2)],
...     [(7, 2), (6, 1), 1]])

abjad> print array
[ ] [d'] [bf bqf  ]
[g'    ] [fs'   ] [ ]

abjad> measuretools.pitch_array_to_measures(array)
[Measure(4/8, [r8, d'8, <bf bqf>4]), Measure(4/8, [g'4, fs'8, r8])]
abjad> for measure in _:
...     f(measure)
...
{
    \time 4/8
```

```

        r8
        d'8
        <bf bqf>4
    }
    {
        \time 4/8
        g'4
        fs'8
        r8
    }

```

Return list of measures.

measuretools.replace_contents_of_measures_in_expr

abjad.tools.measuretools.**replace_contents_of_measures_in_expr**(*expr*,
new_contents)

New in version 1.1. Replace contents of measures in *expr* with *new_contents*:

```
abjad> staff = Staff(measuretools.make_measures_with_full_measure_spacer_skips([(1, 8), (3, 16)]))
```

```
abjad> f(staff)
\new Staff {
    {
        \time 1/8
        s1 * 1/8
    }
    {
        \time 3/16
        s1 * 3/16
    }
}

```

```
abjad> notes = [Note("c'16"), Note("d'16"), Note("e'16"), Note("f'16")]
abjad> measuretools.replace_contents_of_measures_in_expr(staff, notes)
[Measure(1/8, [c'16, d'16]), Measure(3/16, [e'16, f'16, s1 * 1/16])]
```

```
abjad> f(staff)
\new Staff {
    {
        \time 1/8
        c'16
        d'16
    }
    {
        \time 3/16
        e'16
        f'16
        s1 * 1/16
    }
}

```

Preserve duration of all measures.

Skip measures that are too small.

Pad extra space at end of measures with spacer skip.

If not enough measures raise stop iteration.

Return measures iterated. Changed in version 2.0: renamed `measuretools.override_contents()` to `measuretools.replace_contents_of_measures_in_expr()`.

`measuretools.report_meter_distribution_as_string`

`abjad.tools.measuretools.report_meter_distribution_as_string(expr)`

New in version 2.0. Report meter distribution of *expr* as string:

```
abjad> measuretools.report_meter_distribution_as_string(t) # doctest: +SKIP
'\t3/80\t2\n\t2/16\t73\n\t7/40\t1\n\t3/16\t20\n\t16/80\t1\n\t17/80\t1\n\t19/80\t1\n\t4/16\t73\n\t5/16\t62\n\t13/40\t1\n\t27/80\t1\n\t6/16\t12\n\t7/16\t16\n\t8/16\t13\n\t9/16\t15\n\t10/16\t4\n'
```

Return string.

`measuretools.scale_contents_of_measures_in_expr`

`abjad.tools.measuretools.scale_contents_of_measures_in_expr(expr, multiplier=1)`

New in version 2.0. Scale contents of measures in *expr* by *multiplier*.

Iterate *expr*. For every measure in *expr* first multiply the measure meter by *multiplier* and then scale measure contents to fit the new meter.

Extend `containertools.scale_contents_of_container()`.

Return none.

`measuretools.scale_measure_by_multiplier_and_adjust_meter`

`abjad.tools.measuretools.scale_measure_by_multiplier_and_adjust_meter(measure, multiplier=1)`

New in version 2.0. Scale *measure* by *multiplier* and adjust meter:

```
abjad> t = Measure((3, 8), "c'8 d'8 e'8")
abjad> measuretools.scale_measure_by_multiplier_and_adjust_meter(t, Duration(2, 3))
Measure(3/12, [c'8, d'8, e'8])
```

```
abjad> f(t)
{
  \time 3/12
  \scaleDurations #'(2 . 3) {
    c'8
    d'8
    e'8
  }
}
```

Return *measure*.

`measuretools.scale_measure_denominator_and_adjust_measure_contents`

`abjad.tools.measuretools.scale_measure_denominator_and_adjust_measure_contents(measure, new_denominator_factor)`

New in version 1.1. Change binary *measure* to nonbinary measure with *new_denominator_factor*:

```

abjad> measure = Measure((2, 8), "c'8 d'8")
abjad> spannertools.BeamSpanner(measure.leaves)
BeamSpanner(c'8, d'8)

abjad> f(measure)
{
    \time 2/8
    c'8 [
    d'8 ]
}

abjad> measuretools.scale_measure_denominator_and_adjust_measure_contents(measure, 3)
Measure(3/12, [c'8., d'8.])

abjad> f(measure)
{
    \time 3/12
    \scaleDurations #'(2 . 3) {
        c'8. [
        d'8. ]
    }
}

```

Treat *new_denominator_factor* like clever form of 1: 3/3 or 5/5 or 7/7, etc.

Preserve *measure* prolated duration.

Derive new *measure* multiplier.

Scale *measure* contents.

Pick best new meter. Changed in version 2.0: renamed `measuretools.change_binary_measure_to_nonbinary()` to `measuretools.scale_measure_denominator_and_adjust_measure_contents()`.

`measuretools.set_measure_denominator_and_adjust_numerator`

```

abjad.tools.measuretools.set_measure_denominator_and_adjust_numerator(measure,
                                                                    de-
                                                                    nom-
                                                                    ina-
                                                                    tor)

```

New in version 1.1. Set *measure* meter *denominator* and multiply meter numerator accordingly:

```

abjad> measure = Measure((3, 8), "c'8 d'8 e'8")
abjad> spannertools.BeamSpanner(measure.leaves)
BeamSpanner(c'8, d'8, e'8)

abjad> f(measure)
{
    \time 3/8
    c'8 [
    d'8
    e'8 ]
}

abjad> measuretools.set_measure_denominator_and_adjust_numerator(measure, 16)
Measure(6/16, [c'8, d'8, e'8])

```

```

abjad> f(measure)
{
    \time 6/16
    c'8 [
    d'8
    e'8 ]
}

```

Leave *measure* contents unchanged.

Return *measure*. Changed in version 2.0: renamed `measuretools.set_measure_denominator_and_multiply_num` to `measuretools.set_measure_denominator_and_adjust_numerator()`.

notetools

notetools.NaturalHarmonic

class `abjad.tools.notetools.NaturalHarmonic(*args)`

Bases: `abjad.tools.notetools.Note.Note`, `abjad.tools.notetools._Flageolet._Flageolet`

Abjad model of natural harmonic.

Initialize natural harmonic by hand:

```

abjad> notetools.NaturalHarmonic("cs'8.")
NaturalHarmonic(cs', 8.)

```

Initialize natural harmonic from note:

```

abjad> note = Note("cs'8.")

abjad> notetools.NaturalHarmonic(note)
NaturalHarmonic(cs', 8.)

```

Natural harmonics are immutable.

notetools.Note

class `abjad.tools.notetools.Note(*args, **kwargs)`

Bases: `abjad.tools.leaftools._Leaf._Leaf`

Abjad model of a note:

```

abjad> Note(13, (3, 16))
Note("cs''8.")

```

fingered_pitch

Read-only fingered pitch of note:

```

abjad> staff = Staff("d''8 e''8 f''8 g''8")
abjad> piccolo = instrumenttools.Piccolo()(staff)
abjad> instrumenttools.transpose_notes_and_chords_in_expr_from_sounding_pitch_to_fingered_pi

abjad> f(staff)
\new Staff {
    \set Staff.instrumentName = \markup { Piccolo }
    \set Staff.shortInstrumentName = \markup { Picc. }
    d'8
    e'8

```

```
f'8
g'8
}
```

```
abjad> staff[0].fingered_pitch
NamedChromaticPitch("d'")
```

Return named chromatic pitch.

note_head

Get note head of note:

```
abjad> note = Note(13, (3, 16))
abjad> note.note_head
NoteHead("cs'")
```

Set note head of note:

```
abjad> note = Note(13, (3, 16))
abjad> note.note_head = 14
abjad> note
Note("d''8.")
```

sounding_pitch

Read-only sounding pitch of note:

```
abjad> staff = Staff("d''8 e''8 f''8 g''8")
abjad> piccolo = instrumenttools.Piccolo()(staff)
```

```
abjad> instrumenttools.transpose_notes_and_chords_in_expr_from_sounding_pitch_to_fingered_pi
```

```
abjad> f(staff)
\new Staff {
  \set Staff.instrumentName = \markup { Piccolo }
  \set Staff.shortInstrumentName = \markup { Picc. }
  d'8
  e'8
  f'8
  g'8
}
abjad> staff[0].sounding_pitch
NamedChromaticPitch("d'")
```

Return named chromatic pitch.

written_pitch

Get named pitch of note:

```
abjad> note = Note(13, (3, 16))
abjad> note.written_pitch
NamedChromaticPitch("cs'")
```

Set named pitch of note:

```
abjad> note = Note(13, (3, 16))
abjad> note.written_pitch = 14
abjad> note
Note("d''8.")
```

notetools.NoteHead

```
class abjad.tools.notetools.NoteHead(*args)
    Bases: abjad.core._UnaryComparator._UnaryComparator._UnaryComparator
```

Abjad model of a note head:

```
abjad> notetools.NoteHead(13)
NoteHead("cs' ' ")
```

Note heads are immutable.

format

Read-only LilyPond input format of note head:

```
abjad> note_head = notetools.NoteHead("cs' ' ")
abjad> note_head.format
"cs' ' "
```

Return string.

named_chromatic_pitch

Read-only named chromatic pitch equal to note head:

```
abjad> note_head = notetools.NoteHead("cs' ' ")
abjad> note_head.named_chromatic_pitch
NamedChromaticPitch("cs' ' ")
```

Return named chromatic pitch.

tweak

Read-only LilyPond tweak reservoir:

```
abjad> note_head = notetools.NoteHead("cs' ' ")
abjad> note_head.tweak
LilyPondTweakReservoir()
```

Return LilyPond tweak reservoir.

written_pitch

Get named pitch of note head:

```
abjad> note_head = notetools.NoteHead("cs' ' ")
abjad> note_head.written_pitch
NamedChromaticPitch("cs' ' ")
```

Set named pitch of note head:

```
abjad> note_head = notetools.NoteHead("cs' ' ")
abjad> note_head.written_pitch = "d' ' "
abjad> note_head.written_pitch
NamedChromaticPitch("d' ' ")
```

Set pitch token.

notetools.add_artificial_harmonic_to_note

```
abjad.tools.notetools.add_artificial_harmonic_to_note(note,
                                                         melodic_diatonic_interval=MelodicDiatonicInterval('
    Add artifical harmonic to note at melodic_diatonic_interval:
```

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, d'8, e'8, f'8)

abjad> f(staff)
\new Staff {
  c'8 [
  d'8
  e'8
  f'8 ]
}

abjad> notetools.add_artificial_harmonic_to_note(staff[0])
Chord("<c' f'>8")

abjad> f(staff)
\new Staff {
  <
    c'
    \tweak #'style #'harmonic
    f'
  >8 [
  d'8
  e'8
  f'8 ]
}

```

Create new artificial harmonic chord from *note*.

Move parentage and spanners from *note* to artificial harmonic chord.

Return artificial harmonic chord. Changed in version 2.0: renamed `harmonictools.add_artificial()` to `notetools.add_artificial_harmonic_to_note()`.

notetools.color_note_head_by_numbered_chromatic_pitch_class_color_map

`abjad.tools.notetools.color_note_head_by_numbered_chromatic_pitch_class_color_map(pitch_carrier)`
 Color *pitch_carrier* note head:

```

abjad> note = Note("c'4")

abjad> notetools.color_note_head_by_numbered_chromatic_pitch_class_color_map(note)
Note("c'4")

abjad> f(note)
\once \override NoteHead #'color = #(x11-color 'red)
c'4

```

Numbered chromatic pitch-class color map:

```

0: red
1: MediumBlue
2: orange
3: LightSlateBlue
4: ForestGreen
5: MediumOrchid
6: firebrick
7: DeepPink

```

```

8: DarkOrange
9: IndianRed
10: CadetBlue
11: SeaGreen
12: LimeGreen

```

Numbered chromatic pitch-class color map can not be changed.

Raise type error when *pitch_carrier* is not a pitch carrier.

Raise extra pitch error when *pitch_carrier* carries more than 1 note head.

Raise missing pitch error when *pitch_carrier* carries no note head.

Return *pitch_carrier*. Changed in version 2.0: renamed `pitchtools.color_by_pc()` to `notetools.color_note_head_by_numbered_chromatic_pitch_class_color_map()`. Changed in version 2.0: renamed `notetools.color_note_head_by_numeric_chromatic_pitch_class_color_map()` to `notetools.color_note_head_by_numbered_chromatic_pitch_class_color_map()`.

notetools.iterate_notes_backward_in_expr

`abjad.tools.notetools.iterate_notes_backward_in_expr(expr, start=0, stop=None)`

New in version 2.0. Yield right-to-left notes in *expr*:

```

abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
    {
        \time 2/8
        g'8
        a'8
    }
}

abjad> for leaf in notetools.iterate_notes_backward_in_expr(staff):
...     leaf
...
Note("a'8")
Note("g'8")
Note("f'8")
Note("e'8")
Note("d'8")
Note("c'8")

```

Use optional *start* and *stop* keyword parameters to control indices of iteration:

```

abjad> for leaf in notetools.iterate_notes_backward_in_expr(staff, start = 3):
...     leaf

```

```
...
Note("e'8")
Note("d'8")
Note("c'8")

abjad> for leaf in notetools.iterate_notes_backward_in_expr(staff, start = 0, stop = 3):
...     leaf
...
Note("a'8")
Note("g'8")
Note("f'8")

abjad> for leaf in notetools.iterate_notes_backward_in_expr(staff, start = 2, stop = 4):
...     leaf
...
Note("f'8")
Note("e'8")
```

Return note generator. Changed in version 2.0: renamed `iterate.notes_backward_in()` to `notetools.iterate_notes_backward_in_expr()`.

notetools.iterate_notes_forward_in_expr

`abjad.tools.notetools.iterate_notes_forward_in_expr(expr, start=0, stop=None)`

New in version 2.0. Yield left-to-right notes in *expr*:

```
abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 3)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
    {
        \time 2/8
        g'8
        a'8
    }
}

abjad> for leaf in notetools.iterate_notes_forward_in_expr(staff):
...     leaf
...
Note("c'8")
Note("d'8")
Note("e'8")
Note("f'8")
Note("g'8")
Note("a'8")
```

Use optional *start* and *stop* keyword parameters to control start and stop indices of iteration:


```

abjad> for leaf in notetools.iterate_notes_forward_in_expr(staff, start = 3):
...     leaf
...
Note("f'8")
Note("g'8")
Note("a'8")

abjad> for leaf in notetools.iterate_notes_forward_in_expr(staff, start = 0, stop = 3):
...     leaf
...
Note("c'8")
Note("d'8")
Note("e'8")

abjad> for leaf in notetools.iterate_notes_forward_in_expr(staff, start = 2, stop = 4):
...     leaf
...
Note("e'8")
Note("f'8")

```

Return generator. Changed in version 2.0: renamed `iterate.notes_forward_in()` to `notetools.iterate_notes_forward_in_expr()`.

notetools.label_notes_in_expr_with_note_indices

`abjad.tools.notetools.label_notes_in_expr_with_note_indices`(*expr*,
markup_direction='down')

New in version 2.0. Label notes in *expr* with note indices:

```

abjad> staff = Staff("c'8 d'8 r8 r8 g'8 a'8 r8 c''8")

abjad> notetools.label_notes_in_expr_with_note_indices(staff)

abjad> f(staff)
\new Staff {
  c'8 _ \markup { \small 0 }
  d'8 _ \markup { \small 1 }
  r8
  r8
  g'8 _ \markup { \small 2 }
  a'8 _ \markup { \small 3 }
  r8
  c''8 _ \markup { \small 4 }
}

```

Return none.

notetools.make_accelerating_notes_with_lilypond_multipliers

```
abjad.tools.notetools.make_accelerating_notes_with_lilypond_multipliers(pitches,  
                                                                           total,  
                                                                           start,  
                                                                           stop,  
                                                                           exp='cosine',  
                                                                           writ-  
                                                                           ten=Duration(1,  
                                                                           8))
```

Make accelerating notes with LilyPond multipliers:

```
abjad> notetools.make_accelerating_notes_with_lilypond_multipliers([1,2], (1, 2), (1, 4), (1, 8)  
[Note("cs'8 * 113/64"), Note("d'8 * 169/128"), Note("cs'8 * 117/128")]  
  
abjad> voice = Voice(_)  
abjad> voice.prolated_duration  
Duration(1, 2)
```

Set note pitches cyclically from *pitches*.

Return as many interpolation values as necessary to fill the *total* duration requested.

Interpolate durations from *start* to *stop*.

Set note durations to *written* duration times computed interpolated multipliers.

Return list of notes. Changed in version 2.0: renamed `construct.notes_curve()` to `notetools.make_accelerating_notes_with_lilypond_multipliers()`.

notetools.make_notes

```
abjad.tools.notetools.make_notes(pitches, durations, direction='big-endian')
```

Make notes according to *pitches* and *durations*.

Cycle through *pitches* when the length of *pitches* is less than the length of *durations*:

```
abjad> notetools.make_notes([0], [(1, 16), (1, 8), (1, 8)])  
[Note("c'16"), Note("c'8"), Note("c'8")]
```

Cycle through *durations* when the length of *durations* is less than the length of *pitches*:

```
abjad> notetools.make_notes([0, 2, 4, 5, 7], [(1, 16), (1, 8), (1, 8)])  
[Note("c'16"), Note("d'8"), Note("e'8"), Note("f'16"), Note("g'8")]
```

Create ad hoc tuplets for nonassignable durations:

```
abjad> notetools.make_notes([0], [(1, 16), (1, 12), (1, 8)])  
[Note("c'16"), Tuplet(2/3, [c'8]), Note("c'8")]
```

Set *direction* to 'big-endian' to express tied values in decreasing duration:

```
abjad> notetools.make_notes([0], [(13, 16)], direction = 'big-endian')  
[Note("c'2."), Note("c'16")]
```

Set *direction* to 'little-endian' to express tied values in increasing duration:

```
abjad> notetools.make_notes([0], [(13, 16)], direction = 'little-endian')  
[Note("c'16"), Note("c'2.")]
```

Set *pitches* to a single pitch or a sequence of pitches.

Set *durations* to a single duration or a list of durations.

Return list of newly constructed notes. Changed in version 2.0: renamed `construct.notes()` to `notetools.make_notes()`.

notetools.make_notes_with_multiplied_durations

`abjad.tools.notetools.make_notes_with_multiplied_durations` (*pitch*, *written_duration*, *multiplied_durations*)

New in version 2.0. Make *written_duration* notes with *pitch* and *multiplied_durations*:

```
abjad> notetools.make_notes_with_multiplied_durations(0, Duration(1, 4), [(1, 2), (1, 3), (1, 4)]
[Note("c'4 * 2"), Note("c'4 * 4/3"), Note("c'4 * 1"), Note("c'4 * 4/5")]
```

Useful for making spatially positioned notes.

Return list of notes.

notetools.make_percussion_note

`abjad.tools.notetools.make_percussion_note` (*pitch*, *total_duration*, *max_note_duration*=(1, 8))

Make percussion note:

```
abjad> notetools.make_percussion_note(2, (1, 4), (1, 8))
[Note("d'8"), Rest('r8')]
```

```
abjad> notetools.make_percussion_note(2, (1, 64), (1, 8))
[Note("d'64")]
```

```
abjad> notetools.make_percussion_note(2, (5, 64), (1, 8))
[Note("d'16"), Rest('r64')]
```

```
abjad> notetools.make_percussion_note(2, (5, 4), (1, 8))
[Note("d'8"), Rest('r1'), Rest('r8')]
```

Return list of newly constructed note followed by zero or more newly constructed rests.

Durations of note and rests returned will sum to *total_duration*.

Duration of note returned will be no greater than *max_note_duration*.

Duration of rests returned will sum to note duration taken from *total_duration*.

Useful for percussion music where attack duration is negligible and tied notes undesirable. Changed in version 2.0: renamed `construct.percussion_note()` to `notetools.make_percussion_note()`.

notetools.make_quarter_notes_with_lilypond_multipliers

`abjad.tools.notetools.make_quarter_notes_with_lilypond_multipliers` (*pitches*, *multiplied_durations*)

New in version 2.0. Make quarter notes with *pitches* and *multiplied_durations*:

```
abjad> notetools.make_quarter_notes_with_lilypond_multipliers([0, 2, 4, 5], [(1, 4), (1, 5), (1, 6)],
[Note("c'4 * 1"), Note("d'4 * 4/5"), Note("e'4 * 2/3"), Note("f'4 * 4/7")])
```

Read *pitches* cyclically where the length of *pitches* is less than the length of *multiplied_durations*:

```
abjad> notetools.make_quarter_notes_with_lilypond_multipliers([0], [(1, 4), (1, 5), (1, 6), (1, 7)],
[Note("c'4 * 1"), Note("c'4 * 4/5"), Note("c'4 * 2/3"), Note("c'4 * 4/7")])
```

Read *multiplied_durations* cyclically where the length of *multiplied_durations* is less than the length of *pitches*:

```
abjad> notetools.make_quarter_notes_with_lilypond_multipliers([0, 2, 4, 5], [(1, 5)])
[Note("c'4 * 4/5"), Note("d'4 * 4/5"), Note("e'4 * 4/5"), Note("f'4 * 4/5")]
```

Return list of zero or more newly constructed notes. Changed in version 2.0: renamed `construct.quarter_notes_with_multipliers()` to `notetools.make_quarter_notes_with_lilypond_multipliers()`.

notetools.make_repeated_notes

`abjad.tools.notetools.make_repeated_notes(count, duration=Duration(1, 8))`

Make *count* repeated notes with note head-assignable *duration*:

```
abjad> notetools.make_repeated_notes(4)
[Note("c'8"), Note("c'8"), Note("c'8"), Note("c'8")]
```

Make *count* repeated tie chains with tied *duration*:

```
abjad> notes = notetools.make_repeated_notes(2, (5, 16))
abjad> voice = Voice(notes)

abjad> f(voice)
\new Voice {
  c'4 ~
  c'16
  c'4 ~
  c'16
}
```

Make ad hoc tuplet holding *count* repeated notes with nonbinary *duration*:

```
abjad> notetools.make_repeated_notes(3, (1, 12))
[Tuplet(2/3, [c'8, c'8, c'8])]
```

Set pitch of all notes created to middle C.

Return list of zero or more newly constructed notes or list of one newly constructed tuplet. Changed in version 2.0: renamed `construct.run()` to `notetools.make_repeated_notes()`.

notetools.make_repeated_notes_from_time_signature

`abjad.tools.notetools.make_repeated_notes_from_time_signature(time_signature, pitch="c")`

New in version 2.0. Make repeated notes from *time_signature*:

```
abjad> notetools.make_repeated_notes_from_time_signature((5, 32))
[Note("c'32"), Note("c'32"), Note("c'32"), Note("c'32"), Note("c'32")]
```

Make repeated notes with *pitch* from *time_signature*:

```
abjad> notetools.make_repeated_notes_from_time_signature((5, 32), pitch = "d'")
[Note("d' 32"), Note("d' 32"), Note("d' 32"), Note("d' 32"), Note("d' 32")]
```

Return list of notes.

notetools.make_repeated_notes_from_time_signatures

```
abjad.tools.notetools.make_repeated_notes_from_time_signatures(time_signatures,
                                                                pitch="c")
```

Make repeated notes from *time_signatures*:

```
notetools.make_repeated_notes_from_time_signatures([(2, 8), (3, 32)])
[[Note("c' 8"), Note("c' 8")], [Note("c' 32"), Note("c' 32"), Note("c' 32")]]
```

Make repeated notes with *pitch* from *time_signatures*:

```
abjad> notetools.make_repeated_notes_from_time_signatures([(2, 8), (3, 32)], pitch = "d'")
[[Note("d' 8"), Note("d' 8")], [Note("d' 32"), Note("d' 32"), Note("d' 32")]]
```

Return two-dimensional list of note lists.

Use `seqtools.flatten_sequence()` to flatten output if required.

notetools.make_repeated_notes_with_shorter_notes_at_end

```
abjad.tools.notetools.make_repeated_notes_with_shorter_notes_at_end(pitch,
                                                                    written_duration,
                                                                    total_duration,
                                                                    prolation=Duration(1,
                                                                    1))
```

Make repeated notes with *pitch* and *written_duration* summing to *total_duration* under *prolation*:

```
abjad> voice = Voice(notetools.make_repeated_notes_with_shorter_notes_at_end(0, Duration(1, 16),
                                                                              1, 16))

abjad> f(voice)
\new Voice {
    c'16
    c'16
    c'16
    c'16
}
```

Fill binary remaining duration with binary notes of lesser written duration:

```
abjad> voice = Voice(notetools.make_repeated_notes_with_shorter_notes_at_end(0, Duration(1, 16),
                                                                              1, 16))

abjad> f(voice)
\new Voice {
    c'16
    c'16
    c'16
    c'16
    c'32
}
```

Fill nonbinary remaining duration with ad hoc tuplet:

```
abjad> voice = Voice(notetools.make_repeated_notes_with_shorter_notes_at_end(0, Duration(1, 16),

abjad> f(voice)
\new Voice {
  c'16
  c'16
  c'16
  c'16
  c'16
  c'16
  \times 4/5 {
    c'32
  }
}
```

Set *prolation* when constructing notes in a nonbinary measure.

Return list of newly constructed components. Changed in version 2.0: renamed `construct.note_train()` to `notetools.make_repeated_notes_with_shorter_notes_at_end()`.

notetools.yield_groups_of_notes_in_sequence

`abjad.tools.notetools.yield_groups_of_notes_in_sequence(sequence)`

New in version 2.0. Yield groups of notes in *sequence*:

```
abjad> staff = Staff("c'8 d'8 r8 r8 <e' g'>8 <f' a'>8 g'8 a'8 r8 r8 <b' d''>8 <c'' e''>8")

abjad> f(staff)
\new Staff {
  c'8
  d'8
  r8
  r8
  <e' g'>8
  <f' a'>8
  g'8
  a'8
  r8
  r8
  <b' d''>8
  <c'' e''>8
}

abjad> for note in notetools.yield_groups_of_notes_in_sequence(staff):
...     note
...
(Note("c'8"), Note("d'8"))
(Note("g'8"), Note("a'8"))
```

Return generator.

pitchtools

pitchtools.Accidental**class** abjad.tools.pitchtools.**Accidental**

Bases: abjad.core._StrictComparator._StrictComparator._StrictComparator, abjad.core._Immutable._Immutable._Immutable New in version 2.0. Abjad model of the accidental:

```
abjad> pitchtools.Accidental('s')
Accidental('s')
```

Accidentals are immutable.

alphabetic_string

Read-only alphabetic string:

```
abjad> accidental = pitchtools.Accidental('s')
abjad> accidental.alphabetic_string
's'
```

Return string.

format

Read-only LilyPond input format of accidental:

```
abjad> accidental = pitchtools.Accidental('s')
abjad> accidental.format
's'
```

Return string.

is_adjusted

True for all accidentals equal to a nonzero number of semitones. False otherwise:

```
abjad> accidental = pitchtools.Accidental('s')
abjad> accidental.is_adjusted
True
```

Return boolean.

name_string

Read-only name string of accidental:

```
abjad> accidental = pitchtools.Accidental('s')
abjad> accidental.name_string
'sharp'
```

Return string.

semitones

Read-only semitones of accidental:

```
abjad> accidental = pitchtools.Accidental('s')
abjad> accidental.semitones
1
```

Return number.

symbolic_string

Read-only symbolic string of accidental:

```
abjad> accidental = pitchtools.Accidental('s')
abjad> accidental.symbolic_string
'#'
```

Return string.

pitchtools.HarmonicChromaticInterval

class abjad.tools.pitchtools.**HarmonicChromaticInterval**

Bases: abjad.tools.pitchtools._ChromaticInterval._ChromaticInterval._ChromaticInterval, abjad.tools.pitchtools._HarmonicInterval._HarmonicInterval._HarmonicInterval

New in version 2.0. Abjad model of harmonic chromatic interval:

```
abjad> pitchtools.HarmonicChromaticInterval(-14)
HarmonicChromaticInterval(14)
```

Harmonic chromatic intervals are immutable.

harmonic_chromatic_interval_class

Read-only harmonic chromatic interval-class:

```
abjad> harmonic_chromatic_interval = pitchtools.HarmonicChromaticInterval(14)
abjad> harmonic_chromatic_interval.harmonic_chromatic_interval_class
HarmonicChromaticIntervalClass(2)
```

Return harmonic chromatic interval-class.

pitchtools.HarmonicChromaticIntervalClass

class abjad.tools.pitchtools.**HarmonicChromaticIntervalClass**

Bases: abjad.tools.pitchtools._ChromaticIntervalClass._ChromaticIntervalClass._ChromaticIntervalClass, abjad.tools.pitchtools._HarmonicIntervalClass._HarmonicIntervalClass._HarmonicIntervalClass

New in version 2.0. Abjad model of harmonic chromatic interval-class:

```
abjad> pitchtools.HarmonicChromaticIntervalClass(-14)
HarmonicChromaticIntervalClass(2)
```

Harmonic chromatic interval-classes are immutable.

pitchtools.HarmonicChromaticIntervalClassVector

class abjad.tools.pitchtools.**HarmonicChromaticIntervalClassVector** (*expr*)

Bases: abjad.tools.pitchtools._Vector._Vector._Vector New in version 2.0. Abjad model of harmonic chromatic interval-class vector:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8")
abjad> hcicv = pitchtools.HarmonicChromaticIntervalClassVector(staff)
abjad> print hcicv
0 1 3 2 1 2 0 1 0 0 0 0
```

Harmonic chromatic interval-class vector is quartertone-aware:

```
abjad> staff.append(Note(1.5, (1, 4)))
abjad> hcicv = pitchtools.HarmonicChromaticIntervalClassVector(staff)
abjad> print hcicv
0 1 3 2 1 2 0 1 0 0 0 0
1 1 1 1 0 1 0 0 0 0 0 0
```

Harmonic chromatic interval-class vectors are immutable.

has_none_of (*chromatic_interval_numbers*)

True when harmonic chromatic interval-class vector contains none of *chromatic_interval_numbers*. Otherwise false:

```
abjad> hcicv = pitchtools.HarmonicChromaticIntervalClassVector(Staff("c'8 d'8 e'8 f'8 g'8"))
abjad> hcicv.has_none_of([9, 10, 11])
True
```

Return boolean.

pitchtools.HarmonicChromaticIntervalSegment

class abjad.tools.pitchtools.**HarmonicChromaticIntervalSegment**

Bases: abjad.tools.pitchtools._IntervalSegment._IntervalSegment._IntervalSegment

New in version 2.0. Abjad model of harmonic chromatic interval segment:

```
abjad> pitchtools.HarmonicChromaticIntervalSegment([10, -12, -13, -13.5])
HarmonicChromaticIntervalSegment(10, 12, 13, 13.5)
```

Harmonic chromatic interval segments are immutable.

pitchtools.HarmonicChromaticIntervalSet

class abjad.tools.pitchtools.**HarmonicChromaticIntervalSet**

Bases: abjad.tools.pitchtools._IntervalSet._IntervalSet._IntervalSet New in version 2.0. Abjad model of harmonic chromatic interval set:

```
abjad> pitchtools.HarmonicChromaticIntervalSet([10, -12, -13, -13, -13.5])
HarmonicChromaticIntervalSet(10, 12, 13, 13.5)
```

Harmonic chromatic interval sets are immutable.

harmonic_chromatic_interval_numbers

harmonic_chromatic_intervals

pitchtools.HarmonicCounterpointInterval

class abjad.tools.pitchtools.**HarmonicCounterpointInterval**

Bases: abjad.tools.pitchtools._CounterpointInterval._CounterpointInterval._CounterpointInterval

abjad.tools.pitchtools._HarmonicInterval._HarmonicInterval._HarmonicInterval

New in version 2.0. Abjad model of harmonic counterpoint interval:

```
abjad> pitchtools.HarmonicCounterpointInterval(-9)
HarmonicCounterpointInterval(9)
```

Harmonic counterpoint intervals are immutable.

harmonic_counterpoint_interval_class

pitchtools.HarmonicCounterpointIntervalClass

class abjad.tools.pitchtools.**HarmonicCounterpointIntervalClass**

Bases: abjad.tools.pitchtools._CounterpointIntervalClass._CounterpointIntervalClass._CounterpointIntervalClass

abjad.tools.pitchtools._HarmonicIntervalClass._HarmonicIntervalClass._HarmonicIntervalClass

New in version 2.0. Abjad model of harmonic counterpoint interval-class:

```
abjad> pitchtools.HarmonicCounterpointIntervalClass(-9)
HarmonicCounterpointIntervalClass(2)
```

Harmonic counterpoint interval-classes are immutable.

pitchtools.HarmonicDiatonicInterval

class abjad.tools.pitchtools.**HarmonicDiatonicInterval**
 Bases: abjad.tools.pitchtools._DiatonicInterval._DiatonicInterval, abjad.tools.pitchtools._HarmonicInterval._HarmonicInterval
 New in version 2.0. Abjad model harmonic diatonic interval:

```
abjad> pitchtools.HarmonicDiatonicInterval('M9')
HarmonicDiatonicInterval('M9')
```

Harmonic diatonic intervals are immutable.

```
harmonic_counterpoint_interval
harmonic_diatonic_interval_class
melodic_diatonic_interval_ascending
melodic_diatonic_interval_descending
semitones
staff_spaces
```

pitchtools.HarmonicDiatonicIntervalClass

class abjad.tools.pitchtools.**HarmonicDiatonicIntervalClass**
 Bases: abjad.tools.pitchtools._DiatonicIntervalClass._DiatonicIntervalClass, abjad.tools.pitchtools._HarmonicIntervalClass._HarmonicIntervalClass
 New in version 2.0. Abjad model harmonic diatonic interval-class:

```
abjad> pitchtools.HarmonicDiatonicIntervalClass('-M9')
HarmonicDiatonicIntervalClass('M2')
```

Harmonic diatonic interval-classes are immutable.

```
invert()
    Read-only inversion of harmonic diatonic interval-class:

    abjad> hdic = pitchtools.HarmonicDiatonicIntervalClass('major', -9)
    abjad> hdic.invert()
    HarmonicDiatonicIntervalClass('m7')
```

Return harmonic diatonic interval-class.

pitchtools.HarmonicDiatonicIntervalClassSet

class abjad.tools.pitchtools.**HarmonicDiatonicIntervalClassSet**
 Bases: abjad.tools.pitchtools._IntervalClassSet._IntervalClassSet
 New in version 2.0. Abjad model of harmonic diatonic interval-class set:

```
abjad> pitchtools.HarmonicDiatonicIntervalClassSet('m2 M2 m3 M3') # doctest: +SKIP
HarmonicDiatonicIntervalClassSet('m2 M2 m3 M3')
```

Harmonic diatonic interval-class sets are immutable.

harmonic_diatonic_interval_classes

pitchtools.HarmonicDiatonicIntervalSegment

class abjad.tools.pitchtools.**HarmonicDiatonicIntervalSegment**

Bases: abjad.tools.pitchtools._IntervalSegment._IntervalSegment._IntervalSegment

New in version 2.0. Abjad model of harmonic diatonic interval segment:

```
abjad> pitchtools.HarmonicDiatonicIntervalSegment('m2 M9 m3 M3')
HarmonicDiatonicIntervalSegment('m2 M9 m3 M3')
```

Harmonic diatonic interval segments are immutable.

harmonic_chromatic_interval_segment

melodic_chromatic_interval_segment

melodic_diatonic_interval_segment

pitchtools.HarmonicDiatonicIntervalSet

class abjad.tools.pitchtools.**HarmonicDiatonicIntervalSet**

Bases: abjad.tools.pitchtools._IntervalSet._IntervalSet._IntervalSet New in version 2.0. Abjad model of harmonic diatonic interval set:

```
abjad> pitchtools.HarmonicDiatonicIntervalSet('m2 m2 M2 M9')
HarmonicDiatonicIntervalSet('m2 M2 M9')
```

Harmonic diatonic interval sets are immutable.

harmonic_chromatic_interval_set

harmonic_diatonic_interval_numbers

harmonic_diatonic_intervals

pitchtools.InversionEquivalentChromaticIntervalClass

class abjad.tools.pitchtools.**InversionEquivalentChromaticIntervalClass**

Bases: abjad.tools.pitchtools._IntervalClass._IntervalClass._IntervalClass

New in version 2.0. Abjad model of inversion-equivalent chromatic interval-class:

```
abjad> pitchtools.InversionEquivalentChromaticIntervalClass(1)
InversionEquivalentChromaticIntervalClass(1)
```

Inversion-equivalent chromatic interval-classes are immutable.

inversion_equivalent_chromatic_interval_number

pitchtools.InversionEquivalentChromaticIntervalClassSegment

class abjad.tools.pitchtools.**InversionEquivalentChromaticIntervalClassSegment**

Bases: abjad.tools.pitchtools._IntervalClassSegment._IntervalClassSegment._IntervalClassSegment

New in version 2.0. Abjad model of inversion-equivalent chromatic interval-class segment:

```
abjad> pitchtools.InversionEquivalentChromaticIntervalClassSegment([2, 1, 0, 5.5, 6])
InversionEquivalentChromaticIntervalClassSegment(2, 1, 0, 5.5, 6)
```

Inversion-equivalent chromatic interval-class segments are immutable.

pitchtools.InversionEquivalentChromaticIntervalClassSet

class abjad.tools.pitchtools.**InversionEquivalentChromaticIntervalClassSet**
 Bases: abjad.tools.pitchtools._IntervalClassSet._IntervalClassSet._IntervalClassSet
 New in version 2.0. Abjad model of inversion-equivalent chromatic interval-class set:

```
abjad> pitchtools.InversionEquivalentChromaticIntervalClassSet([1, 1, 6, 2, 2])
InversionEquivalentChromaticIntervalClassSet(1, 2, 6)
```

Inversion-equivalent chromatic interval-class sets are immutable.

inversion_equivalent_chromatic_interval_class_numbers

inversion_equivalent_chromatic_interval_classes

pitchtools.InversionEquivalentChromaticIntervalClassVector

class abjad.tools.pitchtools.**InversionEquivalentChromaticIntervalClassVector**(*args, **kwargs)
 Bases: abjad.tools.pitchtools._Vector._Vector._Vector New in version 2.0. Abjad model
 of inversion-equivalent chromatic interval-class vector:

```
abjad> pitchtools.InversionEquivalentChromaticIntervalClassVector([1, 1, 6, 2, 2, 2])
InversionEquivalentChromaticIntervalClassVector(0 | 2 3 0 0 0 1)
```

Initialize by inversion-equivalent chromatic interval-class counts:

```
abjad> pitchtools.InversionEquivalentChromaticIntervalClassVector(counts = [2, 3, 0, 0, 0, 1])
InversionEquivalentChromaticIntervalClassVector(0 | 2 3 0 0 0 1)
```

Inversion-equivalent chromatic interval-class vectors are immutable.

pitchtools.InversionEquivalentDiatonicIntervalClass

class abjad.tools.pitchtools.**InversionEquivalentDiatonicIntervalClass**
 Bases: abjad.tools.pitchtools._DiatonicIntervalClass._DiatonicIntervalClass._DiatonicIntervalClass
 New in version 2.0. Abjad model of inversion-equivalent diatonic interval-class:

```
abjad> pitchtools.InversionEquivalentDiatonicIntervalClass('-m14')
InversionEquivalentDiatonicIntervalClass('M2')
```

Inversion-equivalent diatonic interval-classes are immutable.

pitchtools.InversionEquivalentDiatonicIntervalClassSegment

class abjad.tools.pitchtools.**InversionEquivalentDiatonicIntervalClassSegment**
 Bases: abjad.tools.pitchtools._IntervalSegment._IntervalSegment._IntervalSegment
 New in version 2.0. Abjad model of inversion-equivalent diatonic interval-class segment:

```
abjad> pitchtools.InversionEquivalentDiatonicIntervalClassSegment([('major', 2), ('major', 9), ('mi', 1)],
InversionEquivalentDiatonicIntervalClassSegment(M2, M2, m2, m2)
```

Inversion-equivalent diatonic interval-class segments are immutable.

is_tertian

True when all diatonic interval-classes in segment are tertian. Otherwise false:

```
abjad> dics = pitchtools.InversionEquivalentDiatonicIntervalClassSegment([('major', 3), ('mi', 1)],
abjad> dics.is_tertian
True
```

Return boolean.

pitchtools.InversionEquivalentDiatonicIntervalClassVector

class abjad.tools.pitchtools.**InversionEquivalentDiatonicIntervalClassVector**(*expr*)

Bases: abjad.tools.pitchtools._Vector._Vector._Vector New in version 2.0. Abjad model of inversion-equivalent diatonic interval-class vector:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8")
abjad> pitchtools.InversionEquivalentDiatonicIntervalClassVector(staff)
InversionEquivalentDiatonicIntervalClassVector(P1: 0, aug1: 0, m2: 1, M2: 3, aug2: 0, dim3: 0, m
```

Inversion-equivalent diatonic interval-class vector are not quartertone-aware.

Inversion-equivalent diatonic interval-class vectors are immutable.

pitchtools.MelodicChromaticInterval

class abjad.tools.pitchtools.**MelodicChromaticInterval**

Bases: abjad.tools.pitchtools._ChromaticInterval._ChromaticInterval._ChromaticInterval, abjad.tools.pitchtools._MelodicInterval._MelodicInterval._MelodicInterval New in version 2.0. Abjad model of melodic chromatic interval:

```
abjad> pitchtools.MelodicChromaticInterval(-14)
MelodicChromaticInterval(-14)
```

Melodic chromatic intervals are immutable.

chromatic_interval_number

Read-only chromatic interval number:

```
abjad> pitchtools.MelodicChromaticInterval(-14).chromatic_interval_number
-14
```

Return integer or float.

direction_number

Read-only numeric sign:

```
abjad> pitchtools.MelodicChromaticInterval(-14).direction_number
-1
```

Return integer.

harmonic_chromatic_interval

Read-only harmonic chromatic interval:

```
abjad> pitchtools.MelodicChromaticInterval(-14).harmonic_chromatic_interval
HarmonicChromaticInterval(14)
```

Return harmonic chromatic interval.

melodic_chromatic_interval_class

Read-only melodic chromatic interval-class:

```
abjad> pitchtools.MelodicChromaticInterval(-14).melodic_chromatic_interval_class
MelodicChromaticIntervalClass(-2)
```

Return melodic chromatic interval-class.

pitchtools.MelodicChromaticIntervalClass

class abjad.tools.pitchtools.**MelodicChromaticIntervalClass**

Bases: abjad.tools.pitchtools._ChromaticIntervalClass._ChromaticIntervalClass._ChromaticIntervalClass

abjad.tools.pitchtools._MelodicIntervalClass._MelodicIntervalClass._MelodicIntervalClass

New in version 2.0. Abjad model of melodic chromatic interval-class:

```
abjad> pitchtools.MelodicChromaticIntervalClass(-14)
MelodicChromaticIntervalClass(-2)
```

Melodic chromatic interval-classes are immutable.

pitchtools.MelodicChromaticIntervalClassSegment

class abjad.tools.pitchtools.**MelodicChromaticIntervalClassSegment**

Bases: abjad.tools.pitchtools._IntervalClassSegment._IntervalClassSegment._IntervalClassSegment

New in version 2.0. Abjad model of melodic chromatic interval-class segment:

```
abjad> pitchtools.MelodicChromaticIntervalClassSegment([-2, -14, 3, 5.5, 6.5])
MelodicChromaticIntervalClassSegment(-2, -2, +3, +5.5, +6.5)
```

Melodic chromatic interval-class segments are immutable.

pitchtools.MelodicChromaticIntervalClassVector

class abjad.tools.pitchtools.**MelodicChromaticIntervalClassVector** (*mcic_tokens*)

Bases: abjad.tools.pitchtools._Vector._Vector._Vector New in version 2.0. Abjad model of melodic chromatic interval-class vector:

```
abjad> print pitchtools.MelodicChromaticIntervalClassVector([-2, -14, 3, 5.5, 6.5])
. | . . 1 . . . | . . . . .
  | . 2 . . . . | . . . . .
  | . . . . . 1 | 1 . . . .
  | . . . . . . | . . . . .
```

Melodic chromatic interval-class vectors are immutable.

pitchtools.MelodicChromaticIntervalSegment

class abjad.tools.pitchtools.**MelodicChromaticIntervalSegment**

Bases: abjad.tools.pitchtools._IntervalSegment._IntervalSegment._IntervalSegment

New in version 2.0. Abjad model of melodic chromatic interval segment:

```
abjad> pitchtools.MelodicChromaticIntervalSegment([11, 13, 13.5, -2, 2.5])
MelodicChromaticIntervalSegment(+11, +13, +13.5, -2, +2.5)
```

Melodic chromatic interval segments are immutable.

harmonic_chromatic_interval_segment

melodic_chromatic_interval_class_segment

melodic_chromatic_interval_class_vector

melodic_chromatic_interval_numbers

slope

The slope of a melodic interval segment is the sum of its intervals divided by its length:

```
abjad> pitchtools.MelodicChromaticIntervalSegment([1, 2]).slope
Fraction(3, 2)
```

Return fraction.

spread

The maximum harmonic interval spanned by any combination of the intervals within a harmonic chromatic interval segment:

```
abjad> pitchtools.MelodicChromaticIntervalSegment([1, 2, -3, 1, -2, 1]).spread
HarmonicChromaticInterval(4)
abjad> pitchtools.MelodicChromaticIntervalSegment([1, 1, 1, 2, -3, -2]).spread
HarmonicChromaticInterval(5)
```

Return harmonic chromatic interval.

pitchtools.MelodicChromaticIntervalSet

class abjad.tools.pitchtools.**MelodicChromaticIntervalSet**

Bases: abjad.tools.pitchtools._IntervalSet._IntervalSet._IntervalSet New in version 2.0. Abjad model of melodic chromatic interval set:

```
abjad> pitchtools.MelodicChromaticIntervalSet([11, 11, 13.5, 13.5])
MelodicChromaticIntervalSet(+11, +13.5)
```

Melodic chromatic interval sets are immutable.

harmonic_chromatic_interval_set

melodic_chromatic_interval_numbers

melodic_chromatic_intervals

pitchtools.MelodicCounterpointInterval

class abjad.tools.pitchtools.**MelodicCounterpointInterval**

Bases: abjad.tools.pitchtools._CounterpointInterval._CounterpointInterval._CounterpointInterval
abjad.tools.pitchtools._MelodicInterval._MelodicInterval._MelodicInterval

New in version 2.0. Abjad model of melodic counterpoint interval:

```
abjad> pitchtools.MelodicCounterpointInterval(-9)
MelodicCounterpointInterval(-9)
```

Melodic counterpoint intervals are immutable.

```
direction_number
melodic_counterpoint_interval_class
```

pitchtools.MelodicCounterpointIntervalClass

class abjad.tools.pitchtools.**MelodicCounterpointIntervalClass**

Bases: abjad.tools.pitchtools._CounterpointIntervalClass._CounterpointIntervalClass._CounterpointIntervalClass

abjad.tools.pitchtools._MelodicIntervalClass._MelodicIntervalClass._MelodicIntervalClass

New in version 2.0. Abjad model of melodic counterpoint interval-class:

```
abjad> pitchtools.MelodicCounterpointIntervalClass(-9)
MelodicCounterpointIntervalClass(-2)
```

Melodic counterpoint interval-classes are immutable.

pitchtools.MelodicDiatonicInterval

class abjad.tools.pitchtools.**MelodicDiatonicInterval**

Bases: abjad.tools.pitchtools._DiatonicInterval._DiatonicInterval._DiatonicInterval,

abjad.tools.pitchtools._MelodicInterval._MelodicInterval._MelodicInterval

New in version 2.0. Abjad model of melodic diatonic interval:

```
abjad> pitchtools.MelodicDiatonicInterval('+M9')
MelodicDiatonicInterval('+M9')
```

Melodic diatonic intervals are immutable.

```
direction_number
direction_string
harmonic_chromatic_interval
harmonic_counterpoint_interval
harmonic_diatonic_interval
inversion_equivalent_chromatic_interval_class
melodic_chromatic_interval
melodic_counterpoint_interval
melodic_diatonic_interval_class
semitones
staff_spaces
```

pitchtools.MelodicDiatonicIntervalClass

class abjad.tools.pitchtools.**MelodicDiatonicIntervalClass**

Bases: abjad.tools.pitchtools._DiatonicIntervalClass._DiatonicIntervalClass._DiatonicIntervalClass

abjad.tools.pitchtools._MelodicIntervalClass._MelodicIntervalClass._MelodicIntervalClass

New in version 2.0. Abjad model of melodic diatonic interval-class:

```
abjad> pitchtools.MelodicDiatonicIntervalClass('-M9')
MelodicDiatonicIntervalClass('-M2')
```


Melodic diatonic interval-classes are immutable.

direction_number
direction_symbol
direction_word

pitchtools.MelodicDiatonicIntervalSegment

class abjad.tools.pitchtools.**MelodicDiatonicIntervalSegment**

Bases: abjad.tools.pitchtools._IntervalSegment._IntervalSegment._IntervalSegment
 New in version 2.0. Abjad model of melodic diatonic interval segment:

```
abjad> pitchtools.MelodicDiatonicIntervalSegment('M2 M9 -m3 -P4')
MelodicDiatonicIntervalSegment('+M2 +M9 -m3 -P4')
```

Melodic diatonic interval segments are immutable.

harmonic_chromatic_interval_segment
harmonic_diatonic_interval_segment
melodic_chromatic_interval_segment

pitchtools.MelodicDiatonicIntervalSet

class abjad.tools.pitchtools.**MelodicDiatonicIntervalSet**

Bases: abjad.tools.pitchtools._IntervalSet._IntervalSet._IntervalSet New in version 2.0. Abjad model of melodic diatonic interval set:

```
abjad> pitchtools.MelodicDiatonicIntervalSet('M2 M2 -m3 -P4')
MelodicDiatonicIntervalSet('-P4 -m3 +M2')
```

Melodic diatonic interval sets are immutable.

harmonic_chromatic_interval_set
harmonic_diatonic_interval_set
melodic_chromatic_interval_set
melodic_diatonic_interval_numbers
melodic_diatonic_intervals

pitchtools.NamedChromaticPitch

class abjad.tools.pitchtools.**NamedChromaticPitch**

Bases: abjad.tools.pitchtools._Pitch._Pitch._Pitch New in version 1.1. Abjad model of named chromatic pitch:

```
abjad> pitchtools.NamedChromaticPitch("cs' ' ")
NamedChromaticPitch("cs' ' ")
```

Named chromatic pitches are immutable.

chromatic_pitch_class_name
 Read-only chromatic pitch-class name:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_chromatic_pitch.chromatic_pitch_class_name
'cs'
```

Return string.

chromatic_pitch_class_number

Read-only chromatic pitch-class number:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_chromatic_pitch.chromatic_pitch_class_number
1
```

Return integer or float.

chromatic_pitch_name

Read-only chromatic pitch name:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_chromatic_pitch.chromatic_pitch_name
"cs' "
```

Return string.

chromatic_pitch_number

Read-only chromatic pitch-class number:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_chromatic_pitch.chromatic_pitch_number
13
```

Return integer or float.

deviation_in_cents

Read-only deviation of named chromatic pitch in cents:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_chromatic_pitch.deviation_in_cents is None
True
```

Return integer or none.

diatonic_pitch_class_name

Read-only diatonic pitch-class name:

```
abjad> named_diatonic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_diatonic_pitch.diatonic_pitch_class_name
'C'
```

Return string.

diatonic_pitch_class_number

Read-only diatonic pitch-class number:

```
abjad> named_diatonic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_diatonic_pitch.diatonic_pitch_class_number
0
```

Return integer.

diatonic_pitch_name

Read-only diatonic pitch name:

```
abjad> named_diatonic_pitch = pitchtools.NamedChromaticPitch("cs' ' ")
abjad> named_diatonic_pitch.diatonic_pitch_name
"c' ' "
```

Return string.

diatonic_pitch_number

Read-only diatonic pitch number:

```
abjad> named_diatonic_pitch = pitchtools.NamedChromaticPitch("cs' ' ")
abjad> named_diatonic_pitch.diatonic_pitch_number
7
```

Return integer.

format

Read-only LilyPond input format of named chromatic pitch:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs' ' ")
abjad> named_chromatic_pitch.format
"cs' ' "
```

Return string.

named_chromatic_pitch_class

Read-only named pitch-class:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs' ' ")
abjad> named_chromatic_pitch.named_chromatic_pitch_class
NamedChromaticPitchClass('cs')
```

Return named chromatic pitch-class.

named_diatonic_pitch

Read-only named diatonic pitch:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs' ' ")
abjad> named_chromatic_pitch.named_diatonic_pitch
NamedDiatonicPitch("c' ' ")
```

Return named diatonic pitch.

named_diatonic_pitch_class

Read-only named diatonic pitch-class:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs' ' ")
abjad> named_chromatic_pitch.named_diatonic_pitch_class
NamedDiatonicPitchClass('c')
```

Return named diatonic pitch-class.

numbered_chromatic_pitch

Read-only numbered chromatic pitch from named chromatic pitch:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs' ' ")
abjad> named_chromatic_pitch.numbered_chromatic_pitch_class
NumberedChromaticPitchClass(1)
```

Return numbered chromatic pitch-class.

numbered_chromatic_pitch_class

Read-only numbered pitch-class:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_chromatic_pitch.numbered_chromatic_pitch_class
NumberedChromaticPitchClass(1)
```

Return numbered chromatic pitch-class.

numbered_diatonic_pitch

Read-only numbered diatonic pitch:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_chromatic_pitch.numbered_diatonic_pitch
NumberedDiatonicPitch(7)
```

Return numbered diatonic pitch.

numbered_diatonic_pitch_class

Read-only numbered diatonic pitch:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_chromatic_pitch.numbered_diatonic_pitch_class
NumberedDiatonicPitchClass(0)
```

Return numbered diatonic pitch-class.

octave_number

Read-only integer octave number:

```
abjad> named_chromatic_pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> named_chromatic_pitch.octave_number
5
```

Return integer.

pitchtools.NamedChromaticPitchClass

class abjad.tools.pitchtools.**NamedChromaticPitchClass**

Bases: abjad.tools.pitchtools._PitchClass._PitchClass._PitchClass New in version 2.0. Abjad model of named chromatic pitch-class:

```
abjad> pitchtools.NamedChromaticPitchClass('cs')
NamedChromaticPitchClass('cs')
```

Named chromatic pitch-classes are immutable.

apply_accidental (*accidental*)

Apply *accidental*:

```
abjad> named_chromatic_pitch_class = pitchtools.NamedChromaticPitchClass('cs')
abjad> named_chromatic_pitch_class.apply_accidental('qs')
NamedChromaticPitchClass('ctqs')
```

Return named chromatic pitch-class.

numbered_chromatic_pitch_class

Read-only numbered chromatic pitch-class:

```
abjad> named_chromatic_pitch_class = pitchtools.NamedChromaticPitchClass('cs')
abjad> named_chromatic_pitch_class.numbered_chromatic_pitch_class
NumberedChromaticPitchClass(1)
```

Return numbered chromatic pitch-class.

transpose (*melodic_diatonic_interval*)

Transpose named chromatic pitch-class by *melodic_diatonic_interval*:

```
abjad> named_chromatic_pitch_class = pitchtools.NamedChromaticPitchClass('cs')
abjad> named_chromatic_pitch_class.transpose(pitchtools.MelodicDiatonicInterval('major', 2))
NamedChromaticPitchClass('ds')
```

Return named chromatic pitch-class.

pitchtools.NamedChromaticPitchClassSegment

class abjad.tools.pitchtools.**NamedChromaticPitchClassSegment**

Bases: abjad.tools.pitchtools._PitchClassSegment._PitchClassSegment._PitchClassSegment

New in version 2.0. Abjad model of named chromatic pitch-class segment:

```
abjad> pitchtools.NamedChromaticPitchClassSegment(['gs', 'a', 'as', 'c', 'cs'])
NamedChromaticPitchClassSegment(['gs', 'a', 'as', 'c', 'cs'])
```

Named chromatic pitch-class segments are immutable.

inversion_equivalent_diatonic_interval_class_segment

is_equivalent_under_transposition (*arg*)

named_chromatic_pitch_class_set

named_chromatic_pitch_classes

numbered_chromatic_pitch_class_segment

numbered_chromatic_pitch_class_set

numbered_chromatic_pitch_classes

retrograde ()

rotate (*n*)

transpose (*melodic_diatonic_interval*)

pitchtools.NamedChromaticPitchClassSet

class abjad.tools.pitchtools.**NamedChromaticPitchClassSet**

Bases: abjad.tools.pitchtools._PitchClassSet._PitchClassSet._PitchClassSet

New in version 2.0. Abjad model of a named chromatic pitch-class set:

```
abjad> named_chromatic_pitch_class_set = pitchtools.NamedChromaticPitchClassSet(['gs', 'g', 'as'])
```

```
abjad> named_chromatic_pitch_class_set
NamedChromaticPitchClassSet(['as', 'c', 'cs', 'g', 'gs'])
```

```
abjad> print named_chromatic_pitch_class_set
{as, c, cs, g, gs}
```

Named chromatic pitch-class sets are immutable.

inversion_equivalent_diatonic_interval_class_vector

named_chromatic_pitch_classes

Read-only named chromatic pitch-classes:

```
abjad> named_chromatic_pitch_class_set = pitchtools.NamedChromaticPitchClassSet(['gs', 'g',
abjad> named_chromatic_pitch_class_set.named_chromatic_pitch_classes # doctest: +SKIP
(NamedChromaticPitchClass('c'), NamedChromaticPitchClass('cs'), NamedChromaticPitchClass('g'
```

Return tuple.

numbered_chromatic_pitch_class_set

order_by (*npc_seg*)

transpose (*melodic_diatonic_interval*)

Transpose all npcs in self by melodic diatonic interval.

pitchtools.NamedChromaticPitchSegment

class abjad.tools.pitchtools.**NamedChromaticPitchSegment**

Bases: abjad.tools.pitchtools._PitchSegment._PitchSegment._PitchSegment New in version 2.0. Abjad model of a named chromatic pitch segment:

```
abjad> pitchtools.NamedChromaticPitchSegment(['bf', 'bqf', "fs'", "g'", 'bqf', "g'"])
NamedChromaticPitchSegment("bf bqf fs' g' bqf g'")
```

Named chromtic pitch segments are immutable.

chromatic_pitch_numbers

harmonic_chromatic_interval_class_segment

harmonic_chromatic_interval_segment

harmonic_diatonic_interval_class_segment

harmonic_diatonic_interval_segment

inflection_point_count

inversion_equivalent_chromatic_interval_class_segment

inversion_equivalent_chromatic_interval_class_set

inversion_equivalent_chromatic_interval_class_vector

local_maxima

local_minima

melodic_chromatic_interval_class_segment

melodic_chromatic_interval_segment

melodic_diatonic_interval_class_segment

melodic_diatonic_interval_segment

named_chromatic_pitch_class_vector

named_chromatic_pitch_set

named_chromatic_pitch_vector

named_chromatic_pitches

numbered_chromatic_pitch_class_segment

numbered_chromatic_pitch_class_set

transpose (*melodic_interval*)

Transpose pitches in pitch segment by melodic interval and emit new pitch segment.

pitchtools.NamedChromaticPitchSet

class abjad.tools.pitchtools.**NamedChromaticPitchSet**

Bases: abjad.tools.pitchtools._PitchSet._PitchSet._PitchSet New in version 2.0. Abjad model of a named chromatic pitch set:

```
abjad> pitchtools.NamedChromaticPitchSet(['bf', 'bqf', "fs'", "g'", 'bqf', "g'"])
NamedChromaticPitchSet(['bf', 'bqf', "fs'", "g'"])
```

Named chromatic pitch sets are immutable.

chromatic_pitch_numbers

duplicate_pitch_classes

is_pitch_class_unique

named_chromatic_pitches

numbered_chromatic_pitch_class_set

numbered_chromatic_pitch_classes

transpose (*n*)

Transpose all pcs in self by n.

pitchtools.NamedChromaticPitchVector

class abjad.tools.pitchtools.**NamedChromaticPitchVector** (*pitch_tokens*)

Bases: abjad.tools.pitchtools._Vector._Vector._Vector New in version 2.0. Abjad model of named chromatic pitch vector:

```
abjad> named_chromatic_pitch_vector = pitchtools.NamedChromaticPitchVector(["c'", "c'", "cs'"])
```

```
abjad> named_chromatic_pitch_vector
NamedChromaticPitchVector(c': 2, cs': 3)
```

```
abjad> print named_chromatic_pitch_vector
NamedChromaticPitchVector(c': 2, cs': 3)
```

Named chromatic pitch vectors are immutable.

chromatic_pitch_numbers

named_chromatic_pitches

pitchtools.NamedDiatonicPitch

class abjad.tools.pitchtools.**NamedDiatonicPitch**

Bases: abjad.tools.pitchtools._DiatonicPitch._DiatonicPitch._DiatonicPitch New in version 2.0. Abjad model of a named diatonic pitch:

```
abjad> named_diatonic_pitch = pitchtools.NamedDiatonicPitch("c'")
```

```
abjad> named_diatonic_pitch
NamedDiatonicPitch("c' ")

abjad> print named_diatonic_pitch
c'
```

Named diatonic pitches are immutable.

chromatic_pitch_class_name

Read-only chromatic pitch-class name:

```
abjad> pitchtools.NamedDiatonicPitch("c' ").chromatic_pitch_class_name
'c'
```

Return string.

chromatic_pitch_class_number

Read-only chromatic pitch-class number:

```
abjad> pitchtools.NamedDiatonicPitch("c' ").chromatic_pitch_class_number
0
```

Return integer.

chromatic_pitch_name

Read-only chromatic pitch name:

```
abjad> pitchtools.NamedDiatonicPitch("c' ").chromatic_pitch_name
"c' "
```

Return string.

chromatic_pitch_number

Read-only chromatic pitch number:

```
abjad> pitchtools.NamedDiatonicPitch("c' ").chromatic_pitch_number
12
```

Return integer.

diatonic_pitch_class_name

Read-only diatonic pitch-class name:

```
abjad> pitchtools.NamedDiatonicPitch("c' ").diatonic_pitch_class_name
'c'
```

Return string.

diatonic_pitch_class_number

Read-only diatonic pitch-class number:

```
abjad> pitchtools.NamedDiatonicPitch("c' ").diatonic_pitch_class_number
0
```

Return integer.

diatonic_pitch_name

Read-only diatonic pitch name:

```
abjad> pitchtools.NamedDiatonicPitch("c' ").diatonic_pitch_name
"c' "
```

Return string.

diatonic_pitch_number

Read-only diatonic pitch number:

```
abjad> pitchtools.NamedDiatonicPitch("c'").diatonic_pitch_number
7
```

Return integer.

format

Read-only LilyPond input format of named diatonic pitch:

```
abjad> pitchtools.NamedDiatonicPitch("c'").format
"c' "
```

Return string.

named_chromatic_pitch

Read-only named chromatic pitch:

```
abjad> pitchtools.NamedDiatonicPitch("c'").named_chromatic_pitch
NamedChromaticPitch("c' ")
```

Return named chromatic pitch.

named_chromatic_pitch_class

Read-only named chromatic pitch-class:

```
abjad> pitchtools.NamedDiatonicPitch("c'").named_chromatic_pitch_class
NamedChromaticPitchClass('c')
```

Return named chromatic pitch-class.

named_diatonic_pitch_class

Read-only named diatonic pitch-class:

```
abjad> pitchtools.NamedDiatonicPitch("c'").named_diatonic_pitch_class
NamedDiatonicPitchClass('c')
```

Return named diatonic pitch-class.

numbered_chromatic_pitch

Read-only numbered chromatic pitch:

```
abjad> pitchtools.NamedDiatonicPitch("c'").numbered_chromatic_pitch
NumberedChromaticPitch(12)
```

Return numbered chromatic pitch.

numbered_chromatic_pitch_class

Read-only numbered chromatic pitch-class:

```
abjad> pitchtools.NamedDiatonicPitch("c'").numbered_chromatic_pitch_class
NumberedChromaticPitchClass(0)
```

Return numbered chromatic pitch-class.

numbered_diatonic_pitch

Read-only numbered diatonic pitch:

```
abjad> pitchtools.NamedDiatonicPitch("c'").numbered_diatonic_pitch
NumberedDiatonicPitch(7)
```

Return numbered diatonic pitch.

numbered_diatonic_pitch_class

Read-only numbered diatonic pitch-class:

```
abjad> pitchtools.NamedDiatonicPitch("c'").numbered_diatonic_pitch_class
NumberedDiatonicPitchClass(0)
```

Return numbered diatonic pitch-class.

pitchtools.NamedDiatonicPitchClass

class abjad.tools.pitchtools.**NamedDiatonicPitchClass**

Bases: abjad.tools.pitchtools._DiatonicPitchClass._DiatonicPitchClass._DiatonicPitchClass

New in version 2.0. Abjad model of a named diatonic pitch-class:

```
abjad> pitchtools.NamedDiatonicPitchClass('c')
NamedDiatonicPitchClass('c')
```

Named diatonic pitch-classes are immutable.

numbered_diatonic_pitch_class

Read-only numbered diatonic pitch-class from named diatonic pitch-class:

```
abjad> named_diatonic_pitch_class = pitchtools.NamedDiatonicPitchClass('c')
abjad> named_diatonic_pitch_class.numbered_diatonic_pitch_class
NumberedDiatonicPitchClass(0)
```

Return numbered diatonic pitch-class.

pitchtools.NumberedChromaticPitch

class abjad.tools.pitchtools.**NumberedChromaticPitch**

Bases: abjad.tools.pitchtools._ChromaticPitch._ChromaticPitch._ChromaticPitch, abjad.tools.pitchtools._NumberedPitch._NumberedPitch._NumberedPitch New in version 2.0. Abjad model of a numbered chromatic pitch:

```
abjad> pitchtools.NumberedChromaticPitch(13)
NumberedChromaticPitch(13)
```

Numbered chromatic pitches are immutable.

apply_accidental (*accidental=None*)

Apply *accidental*:

```
abjad> pitchtools.NumberedChromaticPitch(13).apply_accidental('flat')
NumberedChromaticPitch(12)
```

Return numbered chromatic pitch.

chromatic_pitch_number

Read-only chromatic pitch-class number:

```
abjad> pitchtools.NumberedChromaticPitch(13).chromatic_pitch_number
13
```

Return integer or float.

diatonic_pitch_class_number

Read-only diatonic pitch-class number:

```
abjad> pitchtools.NumberedChromaticPitch(13).diatonic_pitch_class_number
0
```

Return integer.

diatonic_pitch_number

Read-only diatonic pitch-class number:

```
abjad> pitchtools.NumberedChromaticPitch(13).diatonic_pitch_number
7
```

Return integer.

transpose (*n=0*)

Transpose by *n* semitones:

```
abjad> pitchtools.NumberedChromaticPitch(13).transpose(1)
NumberedChromaticPitch(14)
```

Return numbered chromatic pitch.

pitchtools.NumberedChromaticPitchClass

class abjad.tools.pitchtools.**NumberedChromaticPitchClass**

Bases: abjad.tools.pitchtools._PitchClass._PitchClass._PitchClass New in version 2.0. Abjad model of a numbered chromatic pitch-class:

```
abjad> pitchtools.NumberedChromaticPitchClass(13)
NumberedChromaticPitchClass(1)
```

Numbered chromatic pitch-classes are immutable.

apply_accidental (*accidental=None*)

Emit new numbered chromatic pitch-class as sum of self and accidental.

invert ()

Invert pitch-class.

multiply (*n*)

Multiply pitch-class by *n*.

transpose (*n*)

Transpose pitch-class by *n*.

pitchtools.NumberedChromaticPitchClassColorMap

class abjad.tools.pitchtools.**NumberedChromaticPitchClassColorMap**

Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Abjad model of a numbered chromatic pitch-class color map:

```
abjad> chromatic_pitch_class_numbers = [[-8, 2, 10, 21], [0, 11, 32, 41], [15, 25, 42, 43]]
abjad> colors = ['red', 'green', 'blue']
abjad> pitchtools.NumberedChromaticPitchClassColorMap(chromatic_pitch_class_numbers, colors)
NumberedChromaticPitchClassColorMap([[-8, 2, 10, 21], [0, 11, 32, 41], [15, 25, 42, 43]], ['red', 'green', 'blue'])
```

Numbered chromatic pitch-class color maps are immutable.

colors

get (*key, alternative=None*)

`pairs`
`pitch_iterables`
`twelve_tone_complete`
`twenty_four_tone_complete`

`pitchtools.NumberedChromaticPitchClassSegment`

class `abjad.tools.pitchtools.NumberedChromaticPitchClassSegment`

Bases: `abjad.tools.pitchtools._PitchClassSegment._PitchClassSegment._PitchClassSegment`

New in version 2.0. Abjad model of a numbered chromatic pitch-class segment:

```
abjad> pitchtools.NumberedChromaticPitchClassSegment([-2, -1.5, 6, 7, -1.5, 7])
NumberedChromaticPitchClassSegment([10, 10.5, 6, 7, 10.5, 7])
```

Numbered chromatic pitch-class segments are immutable.

alpha()

Morris alpha transform of numbered chromatic pitch-class segment:

```
numbered_chromatic_pitch_class_segment = pitchtools.NumberedChromaticPitchClassSegment([10,
numbered_chromatic_pitch_class_segment.alpha()
NumberedChromaticPitchClassSegment([11, 11.5, 7, 6, 11.5, 6])
```

Return numbered chromatic pitch-class segment.

inversion_equivalent_chromatic_interval_class_segment

Read-only inversion-equivalent chromatic interval-class segment:

```
numbered_chromatic_pitch_class_segment = pitchtools.NumberedChromaticPitchClassSegment([10,
numbered_chromatic_pitch_class_segment.inversion_equivalent_chromatic_interval_class_segment
InversionEquivalentChromaticIntervalClassSegment(0.5, 4.5, 1, 3.5, 3.5)
```

Return inversion-equivalent chromatic interval-class segment.

invert()

Invert numbered chromatic pitch-class segment:

```
numbered_chromatic_pitch_class_segment = pitchtools.NumberedChromaticPitchClassSegment([10,
numbered_chromatic_pitch_class_segment.invert()
NumberedChromaticPitchClassSegment([2, 1.5, 6, 5, 1.5, 5])
```

Return numbered chromatic pitch-class segment.

multiply(*n*)

Multiply numbered chromatic pitch-class segment by *n*:

```
numbered_chromatic_pitch_class_segment = pitchtools.NumberedChromaticPitchClassSegment([10,
numbered_chromatic_pitch_class_segment.multiply(5)
NumberedChromaticPitchClassSegment([2, 4.5, 6, 11, 4.5, 11])
```

Return numbered chromatic pitch-class segment.

numbered_chromatic_pitch_class_set

Read-only numbered chromatic pitch-class set from numbered chromatic pitch-class segment:

```
numbered_chromatic_pitch_class_segment = pitchtools.NumberedChromaticPitchClassSegment([10,
numbered_chromatic_pitch_class_segment.numbered_chromatic_pitch_class_set
NumberedChromaticPitchClassSet([6, 7, 10, 10.5])
```

Return numbered chromatic pitch-class set.

retrograde()

Retrograde of numbered chromatic pitch-class segment:

```
numbered_chromatic_pitch_class_segment = pitchtools.NumberedChromaticPitchClassSegment([10,
numbered_chromatic_pitch_class_segment.retrograde()
NumberedChromaticPitchClassSegment([7, 10.5, 7, 6, 10.5, 10])
```

Return numbered chromatic pitch-class segment.

rotate(*n*)

Rotate numbered chromatic pitch-class segment:

```
numbered_chromatic_pitch_class_segment = pitchtools.NumberedChromaticPitchClassSegment([10,
numbered_chromatic_pitch_class_segment.rotate(1)
NumberedChromaticPitchClassSegment([7, 10, 10.5, 6, 7, 10.5])
```

Return numbered chromatic pitch-class segment.

transpose(*n*)

Transpose numbered chromatic pitch-class segment:

```
numbered_chromatic_pitch_class_segment = pitchtools.NumberedChromaticPitchClassSegment([10,
numbered_chromatic_pitch_class_segment.transpose(10)
NumberedChromaticPitchClassSegment([8, 8.5, 4, 5, 8.5, 5])
```

Return numbered chromatic pitch-class segment.

pitchtools.NumberedChromaticPitchClassSet

class abjad.tools.pitchtools.**NumberedChromaticPitchClassSet**

Bases: abjad.tools.pitchtools._PitchClassSet._PitchClassSet._PitchClassSet

New in version 2.0. Abjad model of a numbered chromatic pitch-class set:

```
abjad> numbered_chromatic_pitch_class_set = pitchtools.NumberedChromaticPitchClassSet([-2, -1.5,
abjad> numbered_chromatic_pitch_class_set
NumberedChromaticPitchClassSet([6, 7, 10, 10.5])

abjad> print numbered_chromatic_pitch_class_set
{6, 7, 10, 10.5}
```

Numbered chromatic pitch-class sets are immutable.

inversion_equivalent_chromatic_interval_class_set

Read-only inversion-equivalent chromatic interval-class set:

```
abjad> numbered_chromatic_pitch_class_set = pitchtools.NumberedChromaticPitchClassSet([-2, -
abjad> numbered_chromatic_pitch_class_set.inversion_equivalent_chromatic_interval_class_set
InversionEquivalentChromaticIntervalClassSet(0.5, 1, 3, 3.5, 4, 4.5)
```

Return inversion-equivalent chromatic interval-class set.

inversion_equivalent_chromatic_interval_class_vector

Read-only inversion-equivalent chromatic interval-class vector:

```
abjad> numbered_chromatic_pitch_class_set = pitchtools.NumberedChromaticPitchClassSet([-2, -
abjad> numbered_chromatic_pitch_class_set.inversion_equivalent_chromatic_interval_class_vect
InversionEquivalentChromaticIntervalClassVector(0 | 1 0 1 1 0 0 1 0 0 1 1 0)
```

Return inversion-equivalent chromatic interval-class vector.

invert ()

Invert numbered chromatic pitch-class set:

```
abjad> numbered_chromatic_pitch_class_set = pitchtools.NumberedChromaticPitchClassSet([-2, -1.5, 6, 7, -1.5, 7])
abjad> numbered_chromatic_pitch_class_set.invert()
NumberedChromaticPitchClassSet([1.5, 2, 5, 6])
```

Return numbered chromatic pitch-class set.

is_transposed_subset (*pcset*)

True when self is transposed subset of *pcset*. False otherwise:

```
abjad> pcset_1 = pitchtools.NumberedChromaticPitchClassSet([-2, -1.5, 6, 7, -1.5, 7])
abjad> pcset_2 = pitchtools.NumberedChromaticPitchClassSet([-2, -1.5, 6, 7, -1.5, 7, 7.5, 8])

abjad> pcset_1.is_transposed_subset(pcset_2)
True
```

Return boolean.

is_transposed_superset (*pcset*)

True when self is transposed superset of *pcset*. False otherwise:

```
abjad> pcset_1 = pitchtools.NumberedChromaticPitchClassSet([-2, -1.5, 6, 7, -1.5, 7])
abjad> pcset_2 = pitchtools.NumberedChromaticPitchClassSet([-2, -1.5, 6, 7, -1.5, 7, 7.5, 8])

abjad> pcset_2.is_transposed_superset(pcset_1)
True
```

Return boolean.

multiply (*n*)

Multiply numbered chromatic pitch-class set by *n*:

```
abjad> numbered_chromatic_pitch_class_set = pitchtools.NumberedChromaticPitchClassSet([-2, -1.5, 6, 7, -1.5, 7])
abjad> numbered_chromatic_pitch_class_set.multiply(5)
NumberedChromaticPitchClassSet([2, 4.5, 6, 11])
```

Return numbered chromatic pitch-class set.

numbered_chromatic_pitch_classes

Read-only numbered chromatic pitch-classes:

```
abjad> numbered_chromatic_pitch_class_set = pitchtools.NumberedChromaticPitchClassSet([-2, -1.5, 6, 7, -1.5, 7])
abjad> numbered_chromatic_pitch_class_set.numbered_chromatic_pitch_classes
(NumberedChromaticPitchClass(6), NumberedChromaticPitchClass(7), NumberedChromaticPitchClass(7.5), NumberedChromaticPitchClass(8))
```

Return tuple.

prime_form

To be implemented.

transpose (*n*)

Transpose numbered chromatic pitch-class set by *n*:

```
abjad> numbered_chromatic_pitch_class_set = pitchtools.NumberedChromaticPitchClassSet([-2, -1.5, 6, 7, -1.5, 7])
abjad> numbered_chromatic_pitch_class_set.multiply(5)
NumberedChromaticPitchClassSet([2, 4.5, 6, 11])
```

Return numbered chromatic pitch-class set.

pitchtools.NumberedChromaticPitchClassVector

class abjad.tools.pitchtools.**NumberedChromaticPitchClassVector** (*pitch_class_tokens*)

Bases: abjad.tools.pitchtools._Vector._Vector._Vector New in version 2.0. Abjad model of numbered chromatic pitch-class vector:

```
abjad> numbered_chromatic_pitch_class_vector = pitchtools.NumberedChromaticPitchClassVector([13,

abjad> numbered_chromatic_pitch_class_vector
NumberedChromaticPitchClassVector(0 2 0 0 0 0 | 3 0 0 0 0 0 || 0 0 3 0 0 0 | 0 0 0 0 0 0)

abjad> print numbered_chromatic_pitch_class_vector
0 2 0 0 0 0 | 3 0 0 0 0 0
0 0 3 0 0 0 | 0 0 0 0 0 0
```

Numbered chromatic pitch-class vectors are immutable.

chromatic_pitch_class_numbers

Read-only chromatic pitch-class numbers from numbered chromatic pitch-class vector:

```
abjad> numbered_chromatic_pitch_class_vector = pitchtools.NumberedChromaticPitchClassVector(
abjad> numbered_chromatic_pitch_class_vector.chromatic_pitch_class_numbers
[1, 2.5, 6]
```

Return list.

numbered_chromatic_pitch_classes

Read-only numbered chromatic pitch-classes from numbered chromatic pitch-class vector:

```
abjad> numbered_chromatic_pitch_class_vector = pitchtools.NumberedChromaticPitchClassVector(
abjad> numbered_chromatic_pitch_class_vector.numbered_chromatic_pitch_classes
[NumberedChromaticPitchClass(2.5), NumberedChromaticPitchClass(1), NumberedChromaticPitchClass(6)]
```

Return list.

pitchtools.NumberedDiatonicPitch

class abjad.tools.pitchtools.**NumberedDiatonicPitch**

Bases: abjad.tools.pitchtools._DiatonicPitch._DiatonicPitch._DiatonicPitch, abjad.tools.pitchtools._NumberedPitch._NumberedPitch._NumberedPitch New in version 2.0. Abjad model of a numbered diatonic pitch:

```
abjad> pitchtools.NumberedDiatonicPitch(7)
NumberedDiatonicPitch(7)
```

Numbered diatonic pitches are immutable.

chromatic_pitch_number

Read-only chromatic pitch number:

```
abjad> pitchtools.NumberedDiatonicPitch(7).chromatic_pitch_number
12
```

Return integer.

diatonic_pitch_number

Read-only diatonic pitch number:

```
abjad> pitchtools.NumberedDiatonicPitch(7).diatonic_pitch_number
7
```

Return integer.

named_diatonic_pitch

Read-only named diatonic pitch:

```
abjad> pitchtools.NumberedDiatonicPitch(7).named_diatonic_pitch
NamedDiatonicPitch('c'')
```

Return named diatonic pitch.

named_diatonic_pitch_class

Read-only named diatonic pitch-class:

```
abjad> pitchtools.NumberedDiatonicPitch(7).named_diatonic_pitch_class
NamedDiatonicPitchClass('c')
```

Return named diatonic pitch-class.

numbered_diatonic_pitch_class

Read-only numbered diatonic pitch-class:

```
abjad> pitchtools.NumberedDiatonicPitch(7).numbered_diatonic_pitch_class
NumberedDiatonicPitchClass(0)
```

Return numbered diatonic pitch-class.

pitchtools.NumberedDiatonicPitchClass

class abjad.tools.pitchtools.**NumberedDiatonicPitchClass**

Bases: abjad.tools.pitchtools._NumberedPitchClass._NumberedPitchClass._NumberedPitchClass

abjad.tools.pitchtools._DiatonicPitchClass._DiatonicPitchClass._DiatonicPitchClass

New in version 2.0. Abjad model of a numbered diatonic pitch-class:

```
abjad> pitchtools.NumberedDiatonicPitchClass(0)
NumberedDiatonicPitchClass(0)
```

Numbered diatonic pitch-classes are immutable.

named_diatonic_pitch_class

Read-only named diatonic pitch-class from numbered diatonic pitch-class:

```
abjad> numbered_diatonic_pitch_class = pitchtools.NumberedDiatonicPitchClass(0)
abjad> numbered_diatonic_pitch_class.named_diatonic_pitch_class
NamedDiatonicPitchClass('c')
```

Return named diatonic pitch-class.

pitchtools.PitchRange

class abjad.tools.pitchtools.**PitchRange**(*args)

Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Abjad model of pitch range:

```
abjad> pitchtools.PitchRange(-12, 36)
PitchRange((NamedChromaticPitch('c'), 'inclusive'), (NamedChromaticPitch("c'"""), 'inclusive'))
```


Init from pitch numbers, pitch instances or other pitch range objects.

Pitch ranges implement all six Python rich comparators.

Pitch ranges are immutable.

start_pitch

Read-only start pitch of range:

```
abjad> pitch_range = pitchtools.PitchRange(-12, 36)
abjad> pitch_range.start_pitch
NamedChromaticPitch('c')
```

Return pitch.

start_pitch_is_included_in_range

True when start pitch is included in range. Otherwise false:

```
abjad> pitch_range = pitchtools.PitchRange(-12, 36)
abjad> pitch_range.start_pitch_is_included_in_range
True
```

Return boolean.

stop_pitch

Read-only stop pitch of range:

```
abjad> pitch_range = pitchtools.PitchRange(-12, 36)
abjad> pitch_range.stop_pitch
NamedChromaticPitch("c' ' ' ' ")
```

Return pitch.

stop_pitch_is_included_in_range

True when stop pitch is included in range. Otherwise false:

```
abjad> pitch_range = pitchtools.PitchRange(-12, 36)
abjad> pitch_range.stop_pitch_is_included_in_range
True
```

Return boolean.

pitchtools.TwelveToneRow

class abjad.tools.pitchtools.TwelveToneRow

Bases: `abjad.tools.pitchtools.NumberedChromaticPitchClassSegment.NumberedChromaticPitchC`

New in version 2.0. Abjad model of twelve-tone row:

```
abjad> pitchtools.TwelveToneRow([0, 1, 11, 9, 3, 6, 7, 5, 4, 10, 2, 8])
TwelveToneRow([0, 1, 11, 9, 3, 6, 7, 5, 4, 10, 2, 8])
```

Twelve-tone rows validate pitch-classes at initialization.

Twelve-tone rows inherit canonical operators from numbered chromatic pitch-class segment.

Twelve-tone rows return numbered chromatic pitch-class segments on calls to `getslice`.

Twelve-tone rows are immutable.

pitchtools.all_are_chromatic_pitch_class_name_octave_number_pairs

`abjad.tools.pitchtools.all_are_chromatic_pitch_class_name_octave_number_pairs(expr)`
 New in version 1.1. True when all elements of *expr* are pitch tokens. Otherwise false:

```
abjad> pitchtools.all_are_chromatic_pitch_class_name_octave_number_pairs([('c', 4), ('d', 4), ('e', 4)])
True
```

Return boolean. Changed in version 2.0: renamed `pitchtools.is_pitch_token_collection()` to `pitchtools.all_are_chromatic_pitch_class_name_octave_number_pairs()`.

pitchtools.apply_accidental_to_named_chromatic_pitch

`abjad.tools.pitchtools.apply_accidental_to_named_chromatic_pitch(named_chromatic_pitch, accidental=None)`

New in version 2.0. Apply *accidental* to *named_chromatic_pitch*:

```
abjad> pitch = pitchtools.NamedChromaticPitch("cs'")
abjad> pitchtools.apply_accidental_to_named_chromatic_pitch(pitch, 'f')
NamedChromaticPitch("c'")
```

Return new named pitch.

pitchtools.apply_octavation_spanner_to_pitched_components

`abjad.tools.pitchtools.apply_octavation_spanner_to_pitched_components(expr, ottava_numbered_diatonic_pitch_class_name, quintessential_diatonic_pitch_class_name)`

New in version 1.1. Apply octavation spanner to pitched components in *expr*:

```
abjad> t = Measure((4, 8), notetools.make_notes([24, 26, 27, 29], [(1, 8)]))
abjad> pitchtools.apply_octavation_spanner_to_pitched_components(t, ottava_numbered_diatonic_pitch_class_name, quintessential_diatonic_pitch_class_name)
OctavationSpanner(|4/8(4)|)
```

```
abjad> print t.format
{
    \time 4/8
    \ottava #1
    c'''8
    d'''8
    ef'''8
    f'''8
    \ottava #0
}
```

Apply octavation spanner according to the diatonic pitch number of the maximum pitch in *expr*.

Return octavation spanner.

pitchtools.calculate_harmonic_chromatic_interval_class_from_pitch_carrier_to_pitch_carrier

```
abjad.tools.pitchtools.calculate_harmonic_chromatic_interval_class_from_pitch_carrier_to_pitch_carrier
```

New in version 2.0. Calculate harmonic chromatic interval-class from *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_harmonic_chromatic_interval_class_from_pitch_carrier_to_pitch_carrier(pitch_carrier_1, pitch_carrier_2)
HarmonicChromaticIntervalClass(2)
```

Return harmonic chromatic interval-class.

pitchtools.calculate_harmonic_chromatic_interval_from_pitch_carrier_to_pitch_carrier

```
abjad.tools.pitchtools.calculate_harmonic_chromatic_interval_from_pitch_carrier_to_pitch_carrier
```

New in version 2.0. Calculate harmonic chromatic interval from *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_harmonic_chromatic_interval_from_pitch_carrier_to_pitch_carrier(pitch_carrier_1, pitch_carrier_2)
HarmonicChromaticInterval(14)
```

Return harmonic chromatic interval.

pitchtools.calculate_harmonic_counterpoint_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch

```
abjad.tools.pitchtools.calculate_harmonic_counterpoint_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch
```

New in version 2.0. Calculate harmonic counterpoint interval-class from *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_harmonic_counterpoint_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch(named_chromatic_pitch_1, named_chromatic_pitch_2)
HarmonicCounterpointIntervalClass(2)
```

Return harmonic counterpoint interval-class. Changed in version 2.0: renamed `pitchtools.calculate_harmonic_counterpoint_interval_class_from_named_pchromatic_pitch_to_named_pchromatic_pitch` to `pitchtools.calculate_harmonic_counterpoint_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch`.

pitchtools.calculate_harmonic_counterpoint_interval_from_named_chromatic_pitch_to_named_chromatic_pitch

```
abjad.tools.pitchtools.calculate_harmonic_counterpoint_interval_from_named_chromatic_pitch_to_named_chromatic_pitch
```

New in version 2.0. Calculate harmonic counterpoint interval *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_harmonic_counterpoint_interval_from_named_chromatic_pitch_to_named_chromatic_pitch(named_chromatic_pitch_1, named_chromatic_pitch_2)
HarmonicCounterpointInterval(9)
```

Return harmonic counterpoint interval-class.

pitchtools.calculate_harmonic_diatonic_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch

```
abjad.tools.pitchtools.calculate_harmonic_diatonic_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch
```

New in version 2.0. Calculate harmonic diatonic interval-class from *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_harmonic_diatonic_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch(named_chromatic_pitch_1, named_chromatic_pitch_2)
HarmonicDiatonicIntervalClass('M2')
```

Return harmonic diatonic interval-class.

pitchtools.calculate_harmonic_diatonic_interval_from_named_chromatic_pitch_to_named_chromatic_pitch

`abjad.tools.pitchtools.calculate_harmonic_diatonic_interval_from_named_chromatic_pitch_to_named_chromatic_pitch`

New in version 2.0. Calculate harmonic diatonic interval from *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_harmonic_diatonic_interval_from_named_chromatic_pitch_to_named_chromatic_pitch(pitch_carrier_1, pitch_carrier_2)
HarmonicDiatonicInterval('M9')
```

Return harmonic diatonic interval.

pitchtools.calculate_melodic_chromatic_interval_class_from_pitch_carrier_to_pitch_carrier

`abjad.tools.pitchtools.calculate_melodic_chromatic_interval_class_from_pitch_carrier_to_pitch_carrier`

New in version 2.0. Calculate melodic chromatic interval-class from *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_melodic_chromatic_interval_class_from_pitch_carrier_to_pitch_carrier(pitch_carrier_1, pitch_carrier_2)
MelodicChromaticIntervalClass(+2)
```

Return melodic chromatic interval-class.

pitchtools.calculate_melodic_chromatic_interval_from_pitch_carrier_to_pitch_carrier

`abjad.tools.pitchtools.calculate_melodic_chromatic_interval_from_pitch_carrier_to_pitch_carrier`

New in version 2.0. Calculate melodic chromatic interval from *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_melodic_chromatic_interval_from_pitch_carrier_to_pitch_carrier(pitch_carrier_1, pitch_carrier_2)
MelodicChromaticInterval(+14)
```

Return melodic chromatic interval.

pitchtools.calculate_melodic_counterpoint_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch

`abjad.tools.pitchtools.calculate_melodic_counterpoint_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch`

New in version 2.0. Calculate melodic counterpoint interval-class from *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_melodic_counterpoint_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch(pitch_carrier_1, pitch_carrier_2)
MelodicCounterpointIntervalClass(+2)
```

Return melodic counterpoint interval-class.

pitchtools.calculate_melodic_counterpoint_interval_from_named_chromatic_pitch_to_named_chromatic_pitch

`abjad.tools.pitchtools.calculate_melodic_counterpoint_interval_from_named_chromatic_pitch_to_named_chromatic_pitch`

New in version 2.0. Calculate melodic counterpoint interval *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_melodic_counterpoint_interval_from_named_chromatic_pitch_to_named_chromatic_pitch(pitch_carrier_1, pitch_carrier_2)
MelodicCounterpointInterval(+9)
```

Return melodic counterpoint interval.

pitchtools.calculate_melodic_diatonic_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch

```
abjad.tools.pitchtools.calculate_melodic_diatonic_interval_class_from_named_chromatic_pitch
```

New in version 2.0. Calculate melodic diatonic interval-class from *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_melodic_diatonic_interval_class_from_named_chromatic_pitch_to_named_
MelodicDiatonicIntervalClass('+M2')
```

Return melodic diatonic interval-class.

pitchtools.calculate_melodic_diatonic_interval_from_named_chromatic_pitch_to_named_chromatic_pitch

```
abjad.tools.pitchtools.calculate_melodic_diatonic_interval_from_named_chromatic_pitch_to_n
```

New in version 2.0. Calculate melodic diatonic interval from *pitch_carrier_1* to *pitch_carrier_2*:

```
abjad> pitchtools.calculate_melodic_diatonic_interval_from_named_chromatic_pitch_to_named_chroma
MelodicDiatonicInterval('+M9')
```

Return melodic diatonic interval.

pitchtools.chromatic_pitch_class_name_to_chromatic_pitch_class_number

```
abjad.tools.pitchtools.chromatic_pitch_class_name_to_chromatic_pitch_class_number(chromatic_p
```

New in version 2.0. Change *chromatic_pitch_class_name* to chromatic pitch-class number:

```
abjad> pitchtools.chromatic_pitch_class_name_to_chromatic_pitch_class_number('cs')
1
```

Return chromatic pitch-class number.

pitchtools.chromatic_pitch_class_name_to_diatonic_pitch_class_name

```
abjad.tools.pitchtools.chromatic_pitch_class_name_to_diatonic_pitch_class_name(chromatic_pitch
```

New in version 2.0. Change *chromatic_pitch_class_name* to diatonic pitch-class name:

```
abjad> pitchtools.chromatic_pitch_class_name_to_diatonic_pitch_class_name('cs')
'c'
```

Return string.

pitchtools.chromatic_pitch_class_name_to_diatonic_pitch_class_name_alphabetic_accidental_abbreviation_pair

```
abjad.tools.pitchtools.chromatic_pitch_class_name_to_diatonic_pitch_class_name_alphabetic_a
```

New in version 1.1. Change *chromatic_pitch_class_name* to diatonic pitch-class name / alphabetic accidental abbreviation pair:

```
abjad> pitchtools.chromatic_pitch_class_name_to_diatonic_pitch_class_name_alphabetic_accidental_
('c', 's')
```

Return pair of strings. Changed in version 2.0: renamed `pitchtools.name_to_letter_accidental()` to `pitchtools.chromatic_pitch_class_name_to_diatonic_pitch_class_name_alphabetic_accidental()`

pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name

`abjad.tools.pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name` (*chromatic_pitch_class_number*)
New in version 1.1. Change *chromatic_pitch_class_number* to chromatic pitch-class name:

```
abjad> for n in range(0, 13):
...     pc = n / 2.0
...     pitch_name_string = pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name(pc)
...     print '%s    %s' % (pc, pitch_name_string)
...
0.0    c
0.5    cqs
1.0    cs
1.5    dqf
2.0    d
2.5    dqs
3.0    ef
3.5    eqf
4.0    e
4.5    eqs
5.0    f
5.5    fqs
6.0    fs
```

Return string. Changed in version 2.0: renamed `pitchtools.pc_to_pitch_name()` to `pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name()`.

pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name_with_flats

`abjad.tools.pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name_with_flats` (*chromatic_pitch_class_number*)
New in version 1.1. Change chromatic pitch-class number to chromatic pitch-class name with flats:

```
abjad> for n in range(13):
...     pc = n / 2.0
...     name = pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name_with_flats(pc)
...     print '%s    %s' % (pc, name)
...
0.0    c
0.5    dtqf
1.0    df
1.5    dqf
2.0    d
2.5    etqf
3.0    ef
3.5    eqf
4.0    e
4.5    fqf
5.0    f
5.5    gtqf
6.0    gf
```

Return string. Changed in version 2.0: renamed `pitchtools.pc_to_pitch_name_flats()` to `pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name_with_flats()`.

pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name_with_sharps

`abjad.tools.pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name_with_sharps`
 New in version 1.1. Change *chromatic_pitch_class_number* to chromatic pitch-class name with sharps:

```
abjad> for n in range(13):
...     pc = n / 2.0
...     name = pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name_with_sharps(pc)
...     print '%s  %s' % (pc, name)
...
0.0  c
0.5  cqs
1.0  cs
1.5  ctqs
2.0  d
2.5  dqqs
3.0  ds
3.5  dtqs
4.0  e
4.5  eqqs
5.0  f
5.5  fqqs
6.0  fs
```

Return string. Changed in version 2.0: renamed `pitchtools.pc_to_pitch_name_sharps()` to `pitchtools.chromatic_pitch_class_number_to_chromatic_pitch_class_name_with_sharps()`.

pitchtools.chromatic_pitch_class_number_to_diatonic_pitch_class_number

`abjad.tools.pitchtools.chromatic_pitch_class_number_to_diatonic_pitch_class_number` (*chromatic_pitch_class_number*)
 New in version 2.0. Change *chromatic_pitch_class_number* to diatonic pitch-class number:

```
abjad> pitchtools.chromatic_pitch_class_number_to_diatonic_pitch_class_number(1)
0
```

Return integer.

pitchtools.chromatic_pitch_name_to_chromatic_pitch_class_name

`abjad.tools.pitchtools.chromatic_pitch_name_to_chromatic_pitch_class_name` (*chromatic_pitch_name*)
 New in version 2.0. Change *chromatic_pitch_name* to chromatic pitch-class name:

```
abjad> pitchtools.chromatic_pitch_name_to_chromatic_pitch_class_name("cs' ")
'cs'
```

Return string.

pitchtools.chromatic_pitch_name_to_chromatic_pitch_class_number

`abjad.tools.pitchtools.chromatic_pitch_name_to_chromatic_pitch_class_number` (*chromatic_pitch_name*)
 New in version 2.0. Change *chromatic_class_name* to chromatic pitch-class-number:

```
abjad> pitchtools.chromatic_pitch_name_to_chromatic_pitch_class_number("cs' ")
1
```

Return integer or float.

pitchtools.chromatic_pitch_name_to_chromatic_pitch_number

`abjad.tools.pitchtools.chromatic_pitch_name_to_chromatic_pitch_number(chromatic_pitch_name)`
New in version 2.0. Change *chromatic_pitch_name* to chromatic pitch number:

```
abjad> pitchtools.chromatic_pitch_name_to_chromatic_pitch_number("cs' ' ")
13
```

Return integer or float.

pitchtools.chromatic_pitch_name_to_diatonic_pitch_class_name

`abjad.tools.pitchtools.chromatic_pitch_name_to_diatonic_pitch_class_name(chromatic_pitch_name)`
New in version 2.0. Change *chromatic_pitch_name* to diatonic pitch name:

```
abjad> pitchtools.chromatic_pitch_name_to_diatonic_pitch_class_name("cs' ' ")
'c'
```

Return string.

pitchtools.chromatic_pitch_name_to_diatonic_pitch_class_number

`abjad.tools.pitchtools.chromatic_pitch_name_to_diatonic_pitch_class_number(chromatic_pitch_name)`
New in version 2.0. Change *chromatic_pitch_name* to diatonic pitch-class number:

```
abjad> pitchtools.chromatic_pitch_name_to_diatonic_pitch_class_number("cs' ' ")
0
```

Return integer.

pitchtools.chromatic_pitch_name_to_diatonic_pitch_name

`abjad.tools.pitchtools.chromatic_pitch_name_to_diatonic_pitch_name(chromatic_pitch_name)`
New in version 2.0. Change *chromatic_pitch_name* to diatonic pitch name:

```
abjad> pitchtools.chromatic_pitch_name_to_diatonic_pitch_name("cs' ' ")
"c' ' "
```

Return string.

pitchtools.chromatic_pitch_name_to_diatonic_pitch_number

`abjad.tools.pitchtools.chromatic_pitch_name_to_diatonic_pitch_number(chromatic_pitch_name)`
New in version 2.0. Change *chromatic_pitch_name* to diatonic pitch number:

```
abjad> pitchtools.chromatic_pitch_name_to_diatonic_pitch_number("cs' ' ")
7
```

Return integer.

pitchtools.chromatic_pitch_name_to_octave_number

`abjad.tools.pitchtools.chromatic_pitch_name_to_octave_number(chromatic_pitch_name)`
New in version 2.0. Change *chromatic_pitch_name* to octave number:


```
abjad> pitchtools.chromatic_pitch_name_to_octave_number('cs')
3
```

Return integer.

`pitchtools.chromatic_pitch_names_string_to_named_chromatic_pitch_list`

`abjad.tools.pitchtools.chromatic_pitch_names_string_to_named_chromatic_pitch_list` (*chromatic_p*
New in version 2.0. Change *chromatic_pitch_names_string* to named chromatic pitch list:

```
abjad> pitchtools.chromatic_pitch_names_string_to_named_chromatic_pitch_list("cs, cs cs' cs''")
[NamedChromaticPitch('cs,'), NamedChromaticPitch('cs'), NamedChromaticPitch("cs'"), NamedChromaticPitch("cs'')
```

Return list of named chromatic pitches.

`pitchtools.chromatic_pitch_number_and_accidental_semitones_to_octave_number`

`abjad.tools.pitchtools.chromatic_pitch_number_and_accidental_semitones_to_octave_number` (*chr*
ac-
ci-
den
tal_

New in version 1.1. Change *chromatic_pitch_number* and *accidental_semitones* to octave number:

```
abjad> pitchtools.chromatic_pitch_number_and_accidental_semitones_to_octave_number(12, -2)
5
```

Return integer. Changed in version 2.0: renamed `pitchtools.pitch_number_and_accidental_semitones_to_octave_number` to `pitchtools.chromatic_pitch_number_and_accidental_semitones_to_octave_number()`.

`pitchtools.chromatic_pitch_number_diatonic_pitch_class_name_to_alphabetic_accidental_abbreviation_octave_n`

`abjad.tools.pitchtools.chromatic_pitch_number_diatonic_pitch_class_name_to_alphabetic_accidental_abbreviation_octave_n`

New in version 1.1. Change *chromatic_pitch_number* and *diatonic_pitch_class_name* to alphabetic accidental abbreviation / octave number pair:

```
abjad> pitchtools.chromatic_pitch_number_diatonic_pitch_class_name_to_alphabetic_accidental_abbreviation_octave_number('ss', 5)
```

Return pair. Changed in version 2.0: renamed `pitchtools.number_letter_to_accidental_octave()` to `pitchtools.chromatic_pitch_number_diatonic_pitch_class_name_to_alphabetic_accidental_abbreviation_octave_number()`.

`pitchtools.chromatic_pitch_number_to_chromatic_pitch_class_number`

`abjad.tools.pitchtools.chromatic_pitch_number_to_chromatic_pitch_class_number` (*chromatic_pitch_n*
New in version 2.0. Change *chromatic_pitch_number* to chromatic pitch-class number:

```
abjad> pitchtools.chromatic_pitch_number_to_chromatic_pitch_class_number(13)
1
```

Return integer or float.

`pitchtools.chromatic_pitch_number_to_chromatic_pitch_name`

`abjad.tools.pitchtools.chromatic_pitch_number_to_chromatic_pitch_name` (*chromatic_pitch_number*, *accidental_spelling*=*'mixed'*)

New in version 2.0. Change *chromatic_pitch_number* to chromatic pitch name:

```
abjad> pitchtools.chromatic_pitch_number_to_chromatic_pitch_name(13)
"cs' '"
```

Return string.

`pitchtools.chromatic_pitch_number_to_diatonic_pitch_class_name_alphabetic_accidental_abbreviation_octave_number`

`abjad.tools.pitchtools.chromatic_pitch_number_to_diatonic_pitch_class_name_alphabetic_accidental_abbreviation_octave_number` (*chromatic_pitch_number*, *accidental_abbreviation*, *octave_number*)

Change *chromatic_pitch_number* to diatonic pitch-class name / alphabetic accidental abbreviation / octave number triple:

```
abjad> pitchtools.chromatic_pitch_number_to_diatonic_pitch_class_name_alphabetic_accidental_abbreviation_octave_number(13, 'c', 's', 5)
('c', 's', 5)
```

Return tuple. Changed in version 2.0: renamed `pitchtools.number_to_letter_accidental_octave()` to `pitchtools.chromatic_pitch_number_to_diatonic_pitch_class_name_alphabetic_accidental_abbreviation_octave_number()`

`pitchtools.chromatic_pitch_number_to_diatonic_pitch_class_number`

`abjad.tools.pitchtools.chromatic_pitch_number_to_diatonic_pitch_class_number` (*chromatic_pitch_number*)

New in version 2.0. Change *chromatic_pitch_number* to diatonic pitch-class number:

```
abjad> pitchtools.chromatic_pitch_number_to_diatonic_pitch_class_number(13)
0
```

Return integer.

`pitchtools.chromatic_pitch_number_to_diatonic_pitch_number`

`abjad.tools.pitchtools.chromatic_pitch_number_to_diatonic_pitch_number` (*chromatic_pitch_number*)

New in version 2.0. Change *chromatic_pitch_number* to diatonic pitch number:

```
abjad> pitchtools.chromatic_pitch_number_to_diatonic_pitch_number(13)
7
```

Return integer.

`pitchtools.chromatic_pitch_number_to_octave_number`

`abjad.tools.pitchtools.chromatic_pitch_number_to_octave_number` (*chromatic_pitch_number*)

New in version 1.1. Change *chromatic_pitch_number* to octave number:

```
abjad> pitchtools.chromatic_pitch_number_to_octave_number(13)
5
```

Return integer. Changed in version 2.0: renamed `pitchtools.pitch_number_to_octave()` to `pitchtools.chromatic_pitch_number_to_octave_number()`.

pitchtools.clef_and_staff_position_number_to_named_chromatic_pitch

```
abjad.tools.pitchtools.clef_and_staff_position_number_to_named_chromatic_pitch(clef,
                                                                              staff_position_number)
```

New in version 2.0. Change *clef* and *staff_position_number* to named chromatic pitch:

```
abjad> clef = contexttools.ClefMark('treble')
abjad> for n in range(-6, 6):
...     pitch = pitchtools.clef_and_staff_position_number_to_named_chromatic_pitch(clef, n)
...     print '%s\t%s\t%s' % (clef.clef_name_string, n, pitch)
treble    -6  c'
treble    -5  d'
treble    -4  e'
treble    -3  f'
treble    -2  g'
treble    -1  a'
treble     0  b'
treble     1  c''
treble     2  d''
treble     3  e''
treble     4  f''
treble     5  g''
```

Return named chromatic pitch.

pitchtools.diatonic_interval_number_and_chromatic_interval_number_to_melodic_diatonic_interval

```
abjad.tools.pitchtools.diatonic_interval_number_and_chromatic_interval_number_to_melodic_diatonic_interval(diatonic_interval_number, chromatic_interval_number)
```

New in version 2.0. Change *diatonic_interval_number* and *chromatic_interval_number* to melodic diatonic interval:

```
abjad> pitchtools.diatonic_interval_number_and_chromatic_interval_number_to_melodic_diatonic_interval(1, 2)
MelodicDiatonicInterval('+m2')
```

Return melodic diatonic interval.

pitchtools.diatonic_pitch_class_name_to_chromatic_pitch_class_number

```
abjad.tools.pitchtools.diatonic_pitch_class_name_to_chromatic_pitch_class_number(diatonic_pitch_class_name)
```

New in version 1.1. Change *diatonic_pitch_class_name* to chromatic pitch-class number:

```
abjad> pitchtools.diatonic_pitch_class_name_to_chromatic_pitch_class_number('f')
5
```

Return integer.

pitchtools.diatonic_pitch_class_name_to_diatonic_pitch_class_number

`abjad.tools.pitchtools.diatonic_pitch_class_name_to_diatonic_pitch_class_number` (*diatonic_pitch_class_name*)
New in version 2.0. Change *diatonic_pitch_class_name* to diatonic pitch-class number:

```
abjad> pitchtools.diatonic_pitch_class_name_to_diatonic_pitch_class_number('c')
0
```

Return integer.

pitchtools.diatonic_pitch_class_number_to_chromatic_pitch_class_number

`abjad.tools.pitchtools.diatonic_pitch_class_number_to_chromatic_pitch_class_number` (*diatonic_pitch_class_number*)
New in version 2.0. Change *diatonic_pitch_class_number* to chromatic pitch-class number:

```
abjad> pitchtools.diatonic_pitch_class_number_to_chromatic_pitch_class_number(6)
11
```

Return nonnegative integer.

pitchtools.diatonic_pitch_class_number_to_diatonic_pitch_class_name

`abjad.tools.pitchtools.diatonic_pitch_class_number_to_diatonic_pitch_class_name` (*diatonic_pitch_class_number*)
New in version 2.0. Change *diatonic_pitch_class_number* to diatonic pitch-class name:

```
abjad> pitchtools.diatonic_pitch_class_number_to_diatonic_pitch_class_name(0)
'c'
```

Return string.

pitchtools.diatonic_pitch_name_to_chromatic_pitch_class_name

`abjad.tools.pitchtools.diatonic_pitch_name_to_chromatic_pitch_class_name` (*diatonic_pitch_name*)
New in version 2.0. Change *diatonic_pitch_name* to chromatic pitch-class name:

```
abjad> pitchtools.diatonic_pitch_name_to_chromatic_pitch_class_name("c' ")
'c'
```

Return string.

pitchtools.diatonic_pitch_name_to_chromatic_pitch_class_number

`abjad.tools.pitchtools.diatonic_pitch_name_to_chromatic_pitch_class_number` (*diatonic_pitch_name*)
New in version 2.0. Change *diatonic_pitch_name* to chromatic pitch-class number:

```
abjad> pitchtools.diatonic_pitch_name_to_chromatic_pitch_class_number("c' ")
0
```

Return integer.

pitchtools.diatonic_pitch_name_to_chromatic_pitch_name

`abjad.tools.pitchtools.diatonic_pitch_name_to_chromatic_pitch_name` (*diatonic_pitch_name*)
New in version 2.0. Change *diatonic_pitch_name* to chromatic pitch name:

```
abjad> pitchtools.diatonic_pitch_name_to_chromatic_pitch_name("c'")
"c' "
```

Return string.

`pitchtools.diatonic_pitch_name_to_chromatic_pitch_number`

`abjad.tools.pitchtools.diatonic_pitch_name_to_chromatic_pitch_number` (*diatonic_pitch_name*)
New in version 2.0. Change *diatonic_pitch_name* to chromatic pitch number:

```
abjad> pitchtools.diatonic_pitch_name_to_chromatic_pitch_number("c'")
12
```

Return integer.

`pitchtools.diatonic_pitch_name_to_diatonic_pitch_class_name`

`abjad.tools.pitchtools.diatonic_pitch_name_to_diatonic_pitch_class_name` (*diatonic_pitch_name*)
New in version 2.0. Change *diatonic_pitch_name* to diatonic pitch-class name:

```
abjad> pitchtools.diatonic_pitch_name_to_diatonic_pitch_class_name("c'")
'c'
```

Return string.

`pitchtools.diatonic_pitch_name_to_diatonic_pitch_class_number`

`abjad.tools.pitchtools.diatonic_pitch_name_to_diatonic_pitch_class_number` (*diatonic_pitch_name*)
New in version 2.0. Change *diatonic_pitch_name* to diatonic pitch-class number:

```
abjad> pitchtools.diatonic_pitch_name_to_diatonic_pitch_class_number("c'")
0
```

Return integer.

`pitchtools.diatonic_pitch_name_to_diatonic_pitch_number`

`abjad.tools.pitchtools.diatonic_pitch_name_to_diatonic_pitch_number` (*diatonic_pitch_name*)
New in version 2.0. Change *diatonic_pitch_name* to diatonic pitch number:

```
abjad> pitchtools.diatonic_pitch_name_to_diatonic_pitch_number("c'")
7
```

Return integer.

`pitchtools.diatonic_pitch_number_to_chromatic_pitch_number`

`abjad.tools.pitchtools.diatonic_pitch_number_to_chromatic_pitch_number` (*diatonic_pitch_number*)
New in version 2.0. Change *diatonic_pitch_number* to chromatic pitch number:

```
abjad> pitchtools.diatonic_pitch_number_to_chromatic_pitch_number(7)
12
```

Return integer.

`pitchtools.diatonic_pitch_number_to_diatonic_pitch_class_name`

`abjad.tools.pitchtools.diatonic_pitch_number_to_diatonic_pitch_class_name` (*diatonic_pitch_number*)
 New in version 2.0. Change *diatonic_pitch_number* to diatonic pitch-class name:

```
abjad> pitchtools.diatonic_pitch_number_to_diatonic_pitch_class_name(7)
'c'
```

Return string.

`pitchtools.diatonic_pitch_number_to_diatonic_pitch_class_number`

`abjad.tools.pitchtools.diatonic_pitch_number_to_diatonic_pitch_class_number` (*diatonic_pitch_number*)
 New in version 2.0. Change *diatonic_pitch_number* to diatonic pitch-class number:

```
abjad> pitchtools.diatonic_pitch_number_to_diatonic_pitch_class_number(7)
0
```

Return nonnegative integer.

`pitchtools.diatonic_pitch_number_to_diatonic_pitch_name`

`abjad.tools.pitchtools.diatonic_pitch_number_to_diatonic_pitch_name` (*diatonic_pitch_number*)
 New in version 2.0. Change *diatonic_pitch_number* to diatonic pitch name:

```
abjad> pitchtools.diatonic_pitch_number_to_diatonic_pitch_name(7)
'c' ''
```

Return string.

`pitchtools.expr_has_duplicate_named_chromatic_pitch`

`abjad.tools.pitchtools.expr_has_duplicate_named_chromatic_pitch` (*expr*)
 New in version 2.0. True when *expr* has duplicate named chromatic pitch. Otherwise false:

```
abjad> chord = Chord([13, 13, 14], (1, 4))
abjad> pitchtools.expr_has_duplicate_named_chromatic_pitch(chord)
True
```

Return boolean.

`pitchtools.expr_has_duplicate_numbered_chromatic_pitch_class`

`abjad.tools.pitchtools.expr_has_duplicate_numbered_chromatic_pitch_class` (*expr*)
 New in version 2.0. True when *expr* has duplicate numbered chromatic pitch-class. Otherwise false:

```
abjad> chord = Chord([1, 13, 14], (1, 4))
abjad> pitchtools.expr_has_duplicate_numbered_chromatic_pitch_class(chord)
True
```

Return boolean. Changed in version 2.0: renamed `pitchtools.expr_has_duplicate_numeric_chromatic_pitch` to `pitchtools.expr_has_duplicate_numbered_chromatic_pitch_class`().

pitchtools.expr_to_melodic_chromatic_interval_segment

abjad.tools.pitchtools.**expr_to_melodic_chromatic_interval_segment**(*expr*)

New in version 2.0. Change *expr* to melodic chromatic interval segment:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")
abjad> pitchtools.expr_to_melodic_chromatic_interval_segment(staff)
MelodicChromaticIntervalSegment(+2, +2, +1, +2, +2, +2, +1)
```

Return melodic chromatic interval segment.

pitchtools.get_named_chromatic_pitch_from_pitch_carrier

abjad.tools.pitchtools.**get_named_chromatic_pitch_from_pitch_carrier**(*pitch_carrier*)

New in version 1.1. Get named chromatic pitch from *pitch_carrier*:

```
abjad> pitch = pitchtools.NamedChromaticPitch('df', 5)
abjad> pitch
NamedChromaticPitch("df'")
abjad> pitchtools.get_named_chromatic_pitch_from_pitch_carrier(pitch)
NamedChromaticPitch("df'")

abjad> note = Note(('df', 5), (1, 4))
abjad> note
Note("df'4")
abjad> pitchtools.get_named_chromatic_pitch_from_pitch_carrier(note)
NamedChromaticPitch("df'")

abjad> note = Note(('df', 5), (1, 4))
abjad> note.note_head
NoteHead("df'")
abjad> pitchtools.get_named_chromatic_pitch_from_pitch_carrier(note.note_head)
NamedChromaticPitch("df'")

abjad> chord = Chord([('df', 5)], (1, 4))
abjad> chord
Chord("<df'>4")
abjad> pitchtools.get_named_chromatic_pitch_from_pitch_carrier(chord)
NamedChromaticPitch("df'")

abjad> pitchtools.get_named_chromatic_pitch_from_pitch_carrier(13)
NamedChromaticPitch("cs'")
```

Raise missing pitch error when *pitch_carrier* carries no pitch.

Raise extra pitch error when *pitch_carrier* carries more than one pitch.

Return named chromatic pitch. Changed in version 2.0: renamed `pitchtools.get_pitch()` to `pitchtools.get_named_chromatic_pitch_from_pitch_carrier()`.

pitchtools.get_numbered_chromatic_pitch_class_from_pitch_carrier

abjad.tools.pitchtools.**get_numbered_chromatic_pitch_class_from_pitch_carrier**(*pitch_carrier*)

New in version 2.0. Get numbered chromatic pitch-class from *pitch_carrier*:

```
abjad> note = Note("cs'4")
abjad> pitchtools.get_numbered_chromatic_pitch_class_from_pitch_carrier(note)
NumberedChromaticPitchClass(1)
```



```

abjad> for x in pitchtools.instantiate_pitch_and_interval_test_collection(): x
...
HarmonicChromaticInterval(1)
HarmonicChromaticIntervalClass(1)
HarmonicCounterpointInterval(1)
HarmonicCounterpointIntervalClass(1)
HarmonicDiatonicInterval('M2')
HarmonicDiatonicIntervalClass('M2')
InversionEquivalentChromaticIntervalClass(1)
InversionEquivalentDiatonicIntervalClass('M2')
MelodicChromaticInterval(+1)
MelodicChromaticIntervalClass(+1)
MelodicCounterpointInterval(1)
MelodicCounterpointIntervalClass(+1)
MelodicDiatonicInterval('+M2')
MelodicDiatonicIntervalClass('+M2')
NamedChromaticPitch('c')
NamedChromaticPitchClass('c')
NamedDiatonicPitch('c')
NamedDiatonicPitchClass('c')
NumberedChromaticPitch(1)
NumberedChromaticPitchClass(1)
NumberedDiatonicPitch(1)
NumberedDiatonicPitchClass(1)

```

Use to test pitch and interval interface consistency.

Return list.

`pitchtools.inventory_aggregate_subsets`

`abjad.tools.pitchtools.inventory_aggregate_subsets()`

New in version 2.0. Inventory aggregate subsets:

```

abjad> U_star = pitchtools.inventory_aggregate_subsets()
abjad> len(U_star)
4096
abjad> for pcset in U_star[:20]:
...     pcset
NumberedChromaticPitchClassSet([])
NumberedChromaticPitchClassSet([0])
NumberedChromaticPitchClassSet([1])
NumberedChromaticPitchClassSet([0, 1])
NumberedChromaticPitchClassSet([2])
NumberedChromaticPitchClassSet([0, 2])
NumberedChromaticPitchClassSet([1, 2])
NumberedChromaticPitchClassSet([0, 1, 2])
NumberedChromaticPitchClassSet([3])
NumberedChromaticPitchClassSet([0, 3])
NumberedChromaticPitchClassSet([1, 3])
NumberedChromaticPitchClassSet([0, 1, 3])
NumberedChromaticPitchClassSet([2, 3])
NumberedChromaticPitchClassSet([0, 2, 3])
NumberedChromaticPitchClassSet([1, 2, 3])
NumberedChromaticPitchClassSet([0, 1, 2, 3])
NumberedChromaticPitchClassSet([4])
NumberedChromaticPitchClassSet([0, 4])

```

```
NumberedChromaticPitchClassSet([1, 4])
NumberedChromaticPitchClassSet([0, 1, 4])
```

There are 4096 subsets of the aggregate.

This is U^* in [Morris 1987].

Return list of numbered chromatic pitch-class sets.

pitchtools.inventory_inversion_equivalent_diatonic_interval_classes

`abjad.tools.pitchtools.inventory_inversion_equivalent_diatonic_interval_classes()`
 New in version 2.0. Inventory inversion-equivalent diatonic interval-classes:

```
abjad> for dic in pitchtools.inventory_inversion_equivalent_diatonic_interval_classes():
...     dic
...
InversionEquivalentDiatonicIntervalClass('P1')
InversionEquivalentDiatonicIntervalClass('aug1')
InversionEquivalentDiatonicIntervalClass('m2')
InversionEquivalentDiatonicIntervalClass('M2')
InversionEquivalentDiatonicIntervalClass('aug2')
InversionEquivalentDiatonicIntervalClass('dim3')
InversionEquivalentDiatonicIntervalClass('m3')
InversionEquivalentDiatonicIntervalClass('M3')
InversionEquivalentDiatonicIntervalClass('dim4')
InversionEquivalentDiatonicIntervalClass('P4')
InversionEquivalentDiatonicIntervalClass('aug4')
```

There are 11 inversion-equivalent diatonic interval-classes.

It is an open question as to whether octaves should be included.

Return list of inversion-equivalent diatonic interval-classes.

pitchtools.is_alphabetic_accidental_abbreviation

`abjad.tools.pitchtools.is_alphabetic_accidental_abbreviation(expr)`
 New in version 2.0. True when *expr* is an alphabetic accidental abbreviation. Otherwise false:

```
abjad> pitchtools.is_alphabetic_accidental_abbreviation('tqs')
True
```

The regex `^([s]{1,2}|[f]{1,2}|t?q?[fs])!?$` underlies this predicate.

Return boolean.

pitchtools.is_chromatic_pitch_class_name

`abjad.tools.pitchtools.is_chromatic_pitch_class_name(expr)`
 New in version 2.0. True when *expr* is a chromatic pitch-class name. Otherwise false:

```
abjad> pitchtools.is_chromatic_pitch_class_name('fs')
True
```

The regex `^([a-g,A-G])(([s]{1,2}|[f]{1,2}|t?q?[fs])!?)$` underlies this predicate.

Return boolean.

pitchtools.is_chromatic_pitch_class_name_octave_number_pair

`abjad.tools.pitchtools.is_chromatic_pitch_class_name_octave_number_pair(expr)`

New in version 1.1. True when *arg* has the form of a chromatic pitch-class / octave number pair. Otherwise false:

```
abjad> pitchtools.is_chromatic_pitch_class_name_octave_number_pair(('cs', 5))
True
```

Return boolean. Changed in version 2.0: renamed `pitchtools.is_pair()` to `pitchtools.is_chromatic_pitch_class_name_octave_number_pair()`.

pitchtools.is_chromatic_pitch_class_number

`abjad.tools.pitchtools.is_chromatic_pitch_class_number(expr)`

New in version 2.0. True *expr* is a chromatic pitch-class number. Otherwise false:

```
abjad> pitchtools.is_chromatic_pitch_class_number(1)
True
```

The chromatic pitch-class numbers are equal to the set `[0, 0.5, ..., 11, 11.5]`.

Return boolean.

pitchtools.is_chromatic_pitch_name

`abjad.tools.pitchtools.is_chromatic_pitch_name(expr)`

New in version 2.0. True *expr* is a chromatic pitch name. Otherwise false:

```
abjad> pitchtools.is_chromatic_pitch_name('c,')
True
```

The regex `^([a-g,A-G])(([s]{1,2}|[f]{1,2}|t?q?[f,s])!?) (,+|'+|)$` underlies this predicate.

Return boolean.

pitchtools.is_chromatic_pitch_number

`abjad.tools.pitchtools.is_chromatic_pitch_number(expr)`

New in version 2.0. True *expr* is a chromatic pitch number. Otherwise false:

```
abjad> pitchtools.is_chromatic_pitch_number(13)
True
```

The chromatic pitch numbers are equal to the set of all integers in union with the set of all integers plus of minus 0.5.

Return boolean.

pitchtools.is_diatonic_pitch_class_name

`abjad.tools.pitchtools.is_diatonic_pitch_class_name(expr)`

New in version 2.0. True when *expr* is a diatonic pitch-class name. Otherwise false:

```
abjad> pitchtools.is_diatonic_pitch_class_name('c')
True
```

The regex `^[a-g,A-G]$` underlies this predicate.

Return boolean.

`pitchtools.is_diatonic_pitch_class_number`

`abjad.tools.pitchtools.is_diatonic_pitch_class_number(expr)`
New in version 2.0. True when *expr* is a diatonic pitch-class number. Otherwise false:

```
abjad> pitchtools.is_diatonic_pitch_class_number(0)
True
```

The diatonic pitch-class numbers are equal to the set `[0, 1, 2, 3, 4, 5, 6]`.

Return boolean.

`pitchtools.is_diatonic_pitch_name`

`abjad.tools.pitchtools.is_diatonic_pitch_name(expr)`
New in version 2.0. True when *expr* is a diatonic pitch name. Otherwise false:

```
abjad> pitchtools.is_diatonic_pitch_name("c' ")
True
```

The regex `(^[a-g,A-G])(, +|' +|)$` underlies this predicate.

Return boolean.

`pitchtools.is_diatonic_pitch_number`

`abjad.tools.pitchtools.is_diatonic_pitch_number(expr)`
New in version 2.0. True when *expr* is a diatonic pitch number. Otherwise false:

```
abjad> pitchtools.is_diatonic_pitch_number(7)
True
```

The diatonic pitch numbers are equal to the set of integers.

Return boolean.

`pitchtools.is_diatonic_quality_abbreviation`

`abjad.tools.pitchtools.is_diatonic_quality_abbreviation(expr)`
New in version 2.0. True when *expr* is a diatonic quality abbreviation. Otherwise false:

```
abjad> pitchtools.is_diatonic_quality_abbreviation('aug')
True
```

The regex `^M|m|P|aug|dim$` underlies this predicate.

Return boolean.

pitchtools.is_harmonic_diatonic_interval_abbreviation

`abjad.tools.pitchtools.is_harmonic_diatonic_interval_abbreviation(expr)`
 New in version 2.0. True when *expr* is a harmonic diatonic interval abbreviation. Otherwise false:

```
abjad> pitchtools.is_harmonic_diatonic_interval_abbreviation('M9')
True
```

The regex `^(M|m|P|aug|dim)(\d+)$` underlies this predicate.

Return boolean.

pitchtools.is_melodic_diatonic_interval_abbreviation

`abjad.tools.pitchtools.is_melodic_diatonic_interval_abbreviation(expr)`
 New in version 2.0. True when *expr* is a melodic diatonic interval abbreviation. Otherwise false:

```
abjad> pitchtools.is_melodic_diatonic_interval_abbreviation('+M9')
True
```

The regex `^([+,-]?)(M|m|P|aug|dim)(\d+)$` underlies this predicate.

Return boolean.

pitchtools.is_named_chromatic_pitch_token

`abjad.tools.pitchtools.is_named_chromatic_pitch_token(pitch_token)`
 New in version 1.1. True when *pitch_token* has the form of an Abjad pitch token. Otherwise false:

```
abjad> pitchtools.is_named_chromatic_pitch_token('c', 4)
True
```

Return boolean. Changed in version 2.0: renamed `pitchtools.is_pitch_token()` to `pitchtools.is_named_chromatic_pitch_token()`.

pitchtools.is_octave_tick_string

`abjad.tools.pitchtools.is_octave_tick_string(expr)`
 New in version 2.0. True when *expr* is an octave tick string. Otherwise false:

```
abjad> pitchtools.is_octave_tick_string(',,,')
True
```

The regex `^[+,|'++|$` underlies this predicate.

Return boolean.

pitchtools.is_pitch_carrier

`abjad.tools.pitchtools.is_pitch_carrier(expr)`
 New in version 1.1. True when *expr* is an Abjad pitch, note, note-head of chord instance. Otherwise false:

```
abjad> note = Note("c'4")
abjad> pitchtools.is_pitch_carrier(note)
True
```

Return boolean. Changed in version 2.0: renamed `pitchtools.is_carrier()` to `pitchtools.is_pitch_carrier()`.

`pitchtools.iterate_named_chromatic_pitch_pairs_forward_in_expr`

`abjad.tools.pitchtools.iterate_named_chromatic_pitch_pairs_forward_in_expr(expr)`

New in version 2.0. Iterate left-to-right, top-to-bottom named chromatic pitch pairs in *expr*:

```
abjad> score = Score([ ])
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8"), Note("g'4")]
abjad> score.append(Staff(notes))
abjad> notes = [Note(x, (1, 4)) for x in [-12, -15, -17]]
abjad> score.append(Staff(notes))
abjad> contexttools.ClefMark('bass')(score[1])
ClefMark('bass')(Staff{3})

abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8
    e'8
    f'8
    g'4
  }
  \new Staff {
    \clef "bass"
    c4
    a,4
    g,4
  }
>>

abjad> for pair in pitchtools.iterate_named_chromatic_pitch_pairs_forward_in_expr(score):
...     pair
...
(NamedChromaticPitch("c'"), NamedChromaticPitch('c'))
(NamedChromaticPitch("c'"), NamedChromaticPitch("d'"))
(NamedChromaticPitch('c'), NamedChromaticPitch("d'"))
(NamedChromaticPitch("d'"), NamedChromaticPitch("e'"))
(NamedChromaticPitch("d'"), NamedChromaticPitch('a,'))
(NamedChromaticPitch('c'), NamedChromaticPitch("e'"))
(NamedChromaticPitch('c'), NamedChromaticPitch('a,'))
(NamedChromaticPitch("e'"), NamedChromaticPitch('a,'))
(NamedChromaticPitch("e'"), NamedChromaticPitch("f'"))
(NamedChromaticPitch('a,'), NamedChromaticPitch("f'"))
(NamedChromaticPitch("f'"), NamedChromaticPitch("g'"))
(NamedChromaticPitch("f'"), NamedChromaticPitch('g,'))
(NamedChromaticPitch('a,'), NamedChromaticPitch("g'"))
(NamedChromaticPitch('a,'), NamedChromaticPitch('g,'))
(NamedChromaticPitch("g'"), NamedChromaticPitch('g,'))
```

Chords are handled correctly.

```
abjad> chord_1 = Chord([0, 2, 4], (1, 4))
abjad> chord_2 = Chord([17, 19], (1, 4))
abjad> staff = Staff([chord_1, chord_2])
```

```

abjad> f(staff)
\new Staff {
    <c' d' e'>4
    <f'' g''>4
}

abjad> for pair in pitchtools.iterate_named_chromatic_pitch_pairs_forward_in_expr(staff):
...     print pair
(NamedChromaticPitch("c'"), NamedChromaticPitch("d'"))
(NamedChromaticPitch("c'"), NamedChromaticPitch("e'"))
(NamedChromaticPitch("d'"), NamedChromaticPitch("e'"))
(NamedChromaticPitch("c'"), NamedChromaticPitch("f''"))
(NamedChromaticPitch("c'"), NamedChromaticPitch("g''"))
(NamedChromaticPitch("d'"), NamedChromaticPitch("f''"))
(NamedChromaticPitch("d'"), NamedChromaticPitch("g''"))
(NamedChromaticPitch("e'"), NamedChromaticPitch("f''"))
(NamedChromaticPitch("e'"), NamedChromaticPitch("g''"))
(NamedChromaticPitch("f''"), NamedChromaticPitch("g''"))

```

Return generator.

`pitchtools.list_chromatic_pitch_numbers_in_expr`

`abjad.tools.pitchtools.list_chromatic_pitch_numbers_in_expr(expr)`

New in version 2.0. List chromatic pitch numbers in *expr*:

```

abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> pitchtools.list_chromatic_pitch_numbers_in_expr(tuplet)
(0, 2, 4)

```

Return tuple of zero or more numbers.

`pitchtools.list_harmonic_chromatic_intervals_in_expr`

`abjad.tools.pitchtools.list_harmonic_chromatic_intervals_in_expr(expr)`

New in version 2.0. List harmonic chromatic intervals in *expr*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> for interval in sorted(pitchtools.list_harmonic_chromatic_intervals_in_expr(staff)):
...     interval
...
HarmonicChromaticInterval(1)
HarmonicChromaticInterval(2)
HarmonicChromaticInterval(2)
HarmonicChromaticInterval(3)
HarmonicChromaticInterval(4)
HarmonicChromaticInterval(5)

```

Return unordered set.

`pitchtools.list_harmonic_diatonic_intervals_in_expr`

`abjad.tools.pitchtools.list_harmonic_diatonic_intervals_in_expr(expr)`

New in version 2.0. List harmonic diatonic intervals in *expr*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> for interval in sorted(pitchtools.list_harmonic_diatonic_intervals_in_expr(staff)):
...     interval
...
HarmonicDiatonicInterval('m2')
HarmonicDiatonicInterval('M2')
HarmonicDiatonicInterval('M2')
HarmonicDiatonicInterval('m3')
HarmonicDiatonicInterval('M3')
HarmonicDiatonicInterval('P4')
```

Return unordered set.

`pitchtools.list_inversion_equivalent_chromatic_interval_classes_pairwise_between_pitch_carriers`

`abjad.tools.pitchtools.list_inversion_equivalent_chromatic_interval_classes_pairwise_between`

New in version 2.0. List inversion-equivalent chromatic interval-classes pairwise between *pitch_carriers*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
    b'8
    c''8
}

abjad> pitchtools.list_inversion_equivalent_chromatic_interval_classes_pairwise_between_pitch_carriers(staff)
[InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(1)]

abjad> pitchtools.list_inversion_equivalent_chromatic_interval_classes_pairwise_between_pitch_carriers(staff, 1)
[InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(1), InversionEquivalentChromaticIntervalClass(0)]

abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8"), Note("g'8"), Note("a'8"), Note("b'8"), Note("c''8")]
abjad> notes.reverse()
abjad> notes
[Note("c''8"), Note("b'8"), Note("a'8"), Note("g'8"), Note("f'8"), Note("e'8"), Note("d'8"), Note("c'8")]

abjad> pitchtools.list_inversion_equivalent_chromatic_interval_classes_pairwise_between_pitch_carriers(notes)
[InversionEquivalentChromaticIntervalClass(1), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(1), InversionEquivalentChromaticIntervalClass(2)]

abjad> pitchtools.list_inversion_equivalent_chromatic_interval_classes_pairwise_between_pitch_carriers(notes, 1)
[InversionEquivalentChromaticIntervalClass(1), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(1), InversionEquivalentChromaticIntervalClass(2), InversionEquivalentChromaticIntervalClass(0)]
```


When `wrap = False` do not return `pitch_carriers[-1] - pitch_carriers[0]` as last in series.

When `wrap = True` do return `pitch_carriers[-1] - pitch_carriers[0]` as last in series.

Return list.

`pitchtools.list_melodic_chromatic_interval_numbers_pairwise_between_pitch_carriers`

`abjad.tools.pitchtools.list_melodic_chromatic_interval_numbers_pairwise_between_pitch_carriers`

New in version 1.1. List melodic chromatic interval numbers pairwise between *pitch_carriers*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")
abjad> print staff.format
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'8
    a'8
    b'8
    c''8
}

abjad> pitchtools.list_melodic_chromatic_interval_numbers_pairwise_between_pitch_carriers(staff)
[2, 2, 1, 2, 2, 2, 1]

abjad> pitchtools.list_melodic_chromatic_interval_numbers_pairwise_between_pitch_carriers(staff,
[2, 2, 1, 2, 2, 2, 1, -12]

abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8"), Note("g'8"), Note("a'8"), Note("b'8"), Note("c''8")]
abjad> notes.reverse()
abjad> notes
[Note("c''8"), Note("b'8"), Note("a'8"), Note("g'8"), Note("f'8"), Note("e'8"), Note("d'8"), Note("c'8")]

abjad> pitchtools.list_melodic_chromatic_interval_numbers_pairwise_between_pitch_carriers(notes)
[-1, -2, -2, -2, -1, -2, -2]

abjad> pitchtools.list_melodic_chromatic_interval_numbers_pairwise_between_pitch_carriers(notes,
[-1, -2, -2, -2, -1, -2, -2, 12]
```

When `wrap = False` do not return `pitch_carriers[-1] - pitch_carriers[0]` as last in series.

When `wrap = True` do return `pitch_carriers[-1] - pitch_carriers[0]` as last in series.

Return list. Changed in version 2.0: renamed `pitchtools.get_signed_interval_series()` to `pitchtools.list_melodic_chromatic_interval_numbers_pairwise_between_pitch_carriers()`.

`pitchtools.list_named_chromatic_pitch_carriers_in_expr_sorted_by_numbered_chromatic_pitch_class`

`abjad.tools.pitchtools.list_named_chromatic_pitch_carriers_in_expr_sorted_by_numbered_chromatic_pitch_class`

New in version 2.0. List named chromatic pitch carriers in *expr* sorted by numbered chromatic pitch-class:

```
abjad> chord = Chord([9, 11, 12, 14, 16], (1, 4))
abjad> notes = chordtools.arpeggiate_chord(chord)
abjad> pitchtools.list_named_chromatic_pitch_carriers_in_expr_sorted_by_numbered_chromatic_pitch_class(notes)
[Note("c''4"), Note("d''4"), Note("e''4"), Note("a'4"), Note("b'4")]
```

The elements in *pitch_carriers* are not changed in any way.

Return list. Changed in version 2.0: renamed `pitchtools.list_named_chromatic_pitch_carriers_in_expr_sorted_by_numbered_chromatic_pitch_carriers` to `pitchtools.list_named_chromatic_pitch_carriers_in_expr_sorted_by_numbered_chromatic_pitch_carriers`.

`pitchtools.list_named_chromatic_pitches_in_expr`

`abjad.tools.pitchtools.list_named_chromatic_pitches_in_expr(expr)`

New in version 2.0. List named chromatic pitches in *expr*:

```
abjad> t = Staff("c'4 d'4 e'4 f'4")
abjad> beam = spannertools.BeamSpanner(t[:])
abjad> pitchtools.list_named_chromatic_pitches_in_expr(beam)
(NamedChromaticPitch("c'"), NamedChromaticPitch("d'"), NamedChromaticPitch("e'"), NamedChromaticPitch("f'))
```

Return tuple.

`pitchtools.list_numbered_chromatic_pitch_classes_in_expr`

`abjad.tools.pitchtools.list_numbered_chromatic_pitch_classes_in_expr(expr)`

New in version 2.0. List numbered chromatic pitch-classes in *expr*:

```
abjad> chord = Chord([13, 14, 15], (1, 4))
abjad> pitchtools.list_numbered_chromatic_pitch_classes_in_expr(chord)
(NumberedChromaticPitchClass(1), NumberedChromaticPitchClass(2), NumberedChromaticPitchClass(3))
```

Works with notes, chords, defective chords.

Return tuple or zero or more numbered chromatic pitch-classes. Changed in version 2.0: renamed `pitchtools.list_numeric_chromatic_pitch_classes_in_expr()` to `pitchtools.list_numbered_chromatic_pitch_classes_in_expr()`.

`pitchtools.list_octave_transpositions_of_pitch_carrier_within_pitch_range`

`abjad.tools.pitchtools.list_octave_transpositions_of_pitch_carrier_within_pitch_range(pitch_carrier, pitch_range)`

New in version 1.1. List octave transpositions of *pitch_carrier* in *pitch_range*:

```
abjad> chord = Chord([0, 2, 4], (1, 4))
abjad> pitch_range = pitchtools.PitchRange(0, 48)
abjad> pitchtools.list_octave_transpositions_of_pitch_carrier_within_pitch_range(chord, pitch_range)
[Chord("<c' d' e'>4"), Chord("<c'' d'' e''>4"), Chord("<c''' d''' e'''>4"), Chord("<c'''' d'''' e''''>4")]
```

Return list of newly created *pitch_carrier* objects.

`pitchtools.list_ordered_named_chromatic_pitch_pairs_from_expr_1_to_expr_2`

`abjad.tools.pitchtools.list_ordered_named_chromatic_pitch_pairs_from_expr_1_to_expr_2(expr_1, expr_2)`

New in version 2.0. List ordered named chromatic pitch pairs from *expr_1* to *expr_2*:

```
abjad> chord_1 = Chord([0, 1, 2], (1, 4))
abjad> chord_2 = Chord([3, 4], (1, 4))
abjad> for pair in pitchtools.list_ordered_named_chromatic_pitch_pairs_from_expr_1_to_expr_2(chord_1, chord_2):
...     pair
(NamedChromaticPitch("c'"), NamedChromaticPitch("ef'))
```

```
(NamedChromaticPitch("c'"), NamedChromaticPitch("e'"))
(NamedChromaticPitch("cs'"), NamedChromaticPitch("ef'"))
(NamedChromaticPitch("cs'"), NamedChromaticPitch("e'"))
(NamedChromaticPitch("d'"), NamedChromaticPitch("ef'"))
(NamedChromaticPitch("d'"), NamedChromaticPitch("e'"))
```

Return generator.

pitchtools.list_unordered_named_chromatic_pitch_pairs_in_expr

`abjad.tools.pitchtools.list_unordered_named_chromatic_pitch_pairs_in_expr(expr)`

New in version 2.0. List unordered named chromatic pitch pairs in *expr*:

```
abjad> for pair in pitchtools.list_unordered_named_chromatic_pitch_pairs_in_expr(Chord([0, 1, 2,
...     pair
...
(NamedChromaticPitch("c'"), NamedChromaticPitch("cs'"))
(NamedChromaticPitch("c'"), NamedChromaticPitch("d'"))
(NamedChromaticPitch("c'"), NamedChromaticPitch("ef'"))
(NamedChromaticPitch("cs'"), NamedChromaticPitch("d'"))
(NamedChromaticPitch("cs'"), NamedChromaticPitch("ef'"))
(NamedChromaticPitch("d'"), NamedChromaticPitch("ef'"))
```

Return generator.

pitchtools.make_n_middle_c_centered_pitches

`abjad.tools.pitchtools.make_n_middle_c_centered_pitches(n)`

New in version 2.0. Make *n* middle-c centered pitches, where $0 < n$:

```
abjad> for p in pitchtools.make_n_middle_c_centered_pitches(5): p
NamedChromaticPitch('f')
NamedChromaticPitch('a')
NamedChromaticPitch("c'")
NamedChromaticPitch("e'")
NamedChromaticPitch("g'")

abjad> for p in pitchtools.make_n_middle_c_centered_pitches(4): p
NamedChromaticPitch('g')
NamedChromaticPitch('b')
NamedChromaticPitch("d'")
NamedChromaticPitch("f'")
```

Return list of zero or more named chromatic pitches.

pitchtools.named_chromatic_pitch_and_clef_to_staff_position_number

`abjad.tools.pitchtools.named_chromatic_pitch_and_clef_to_staff_position_number(pitch, clef)`

New in version 2.0. Change named chromatic *pitch* and *clef* to staff position number:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")
abjad> clef = contexttools.ClefMark('treble')
abjad> for note in staff:
...     written_pitch = note.written_pitch
...     number = pitchtools.named_chromatic_pitch_and_clef_to_staff_position_number(written_pitch,
```

```
... print '%s\t%s' % (written_pitch, number)
c'    -6
d'    -5
e'    -4
f'    -3
g'    -2
a'    -1
b'     0
c'     1
```

Return integer.

`pitchtools.named_chromatic_pitch_tokens_to_named_chromatic_pitches`

`abjad.tools.pitchtools.named_chromatic_pitch_tokens_to_named_chromatic_pitches` (*pitch_tokens*)
 New in version 2.0. Change named chromatic *pitch_tokens* to named chromatic pitches:

```
abjad> pitchtools.named_chromatic_pitch_tokens_to_named_chromatic_pitches([0, 2, ('ef', 4)])
[NamedChromaticPitch("c'"), NamedChromaticPitch("d'"), NamedChromaticPitch("ef'")]
```

Return list of zero or more named chromatic pitches.

`pitchtools.named_chromatic_pitches_to_harmonic_chromatic_interval_class_number_dictionary`

`abjad.tools.pitchtools.named_chromatic_pitches_to_harmonic_chromatic_interval_class_number_dictionary`
 New in version 1.1. Change named chromatic pitches to harmonic chromatic interval-class number dictionary:

```
abjad> chord = Chord([0, 2, 11], (1, 4))
abjad> vector = pitchtools.named_chromatic_pitches_to_harmonic_chromatic_interval_class_number_dictionary(chord)
abjad> vector
{0: 0, 1: 0, 2: 1, 3: 0, 4: 0, 5: 0, 6: 0, 7: 0, 8: 0, 9: 1, 10: 0, 11: 1}
```

Return dictionary. Changed in version 2.0: renamed `pitchtools.get_interval_vector()` to `pitchtools.named_chromatic_pitches_to_harmonic_chromatic_interval_class_number_dictionary()`

`pitchtools.named_chromatic_pitches_to_inversion_equivalent_chromatic_interval_class_number_dictionary`

`abjad.tools.pitchtools.named_chromatic_pitches_to_inversion_equivalent_chromatic_interval_class_number_dictionary`
 New in version 1.1. Change named chromatic *pitches* to inversion-equivalent chromatic interval-class number dictionary:

```
abjad> chord = Chord([0, 2, 11], (1, 4))
abjad> vector = pitchtools.named_chromatic_pitches_to_inversion_equivalent_chromatic_interval_class_number_dictionary(chord)
abjad> for i in range(7):
...     print '\t%s\t%s' % (i, vector[i])
...
0 0
1 1
2 1
3 1
4 0
5 0
6 0
```

Changed in version 2.0: works with quartertones. Return dictionary. Changed in version 2.0: renamed `pitchtools.get_interval_class_vector()` to `pitchtools.named_chromatic_pitches_to_inversion_equivalent_chromatic_interval_class_numbers`.

`pitchtools.octave_number_to_octave_tick_string`

`abjad.tools.pitchtools.octave_number_to_octave_tick_string(octave_number)`

New in version 2.0. Change *octave_number* to octave tick string:

```
abjad> for octave_number in range(-1, 9):
...     print "%s\t%s" % (octave_number, pitchtools.octave_number_to_octave_tick_string(octave_number))
...
-1  ',,,,'
0   ',,,
1   ',,
2   ',
3
4   '
5   ''
6   ''',
7   ''',,
8   ''',,,
```

Raise type error on noninteger input.

Return string.

`pitchtools.octave_tick_string_to_octave_number`

`abjad.tools.pitchtools.octave_tick_string_to_octave_number(tick_string)`

New in version 2.0. Change *tick_string* to octave number:

```
abjad> pitchtools.octave_tick_string_to_octave_number("'")
4
```

Raise type error on nonstring input.

Raise value error on input not of tick string format.

Return integer.

`pitchtools.ordered_chromatic_pitch_class_numbers_are_within_ordered_chromatic_pitch_numbers`

`abjad.tools.pitchtools.ordered_chromatic_pitch_class_numbers_are_within_ordered_chromatic_pitch_numbers(pitches)`

New in version 1.1. True if ordered *chromatic_pitch_class_numbers* are within ordered *chromatic_pitch_numbers*:

```
abjad> pcs = [2, 7, 10]
abjad> pitches = [6, 9, 12, 13, 14, 19, 22, 27, 28, 29, 32, 35]
abjad> pitchtools.ordered_chromatic_pitch_class_numbers_are_within_ordered_chromatic_pitch_numbers(pitches)
True
```

Return boolean. Changed in version 2.0: renamed `pitchtools.are_in_octave_order()` to `pitchtools.ordered_chromatic_pitch_class_numbers_are_within_ordered_chromatic_pitch_numbers`.

`pitchtools.pentatonic_pitch_number_to_chromatic_pitch_number`

`abjad.tools.pitchtools.pentatonic_pitch_number_to_chromatic_pitch_number` (*pentatonic_scale_degree*, *transpose=1*, *phase=0*)

New in version 1.1. Changed *pentatonic_scale_degree* number to chromatic pitch number:

```
abjad> for pentatonic_scale_degree in range(9): # doctest: +SKIP
...     chromatic_pitch_number = pitchtools.pentatonic_pitch_number_to_chromatic_pitch_number(pe
...     print '%s\t%s' % (pentatonic_scale_degree, chromatic_pitch_number)
...
0 1
1 3
2 6
3 8
4 10
5 13
6 15
7 18
8 20
```

Pentatonic scale degrees may be negative:

```
abjad> for pentatonic_scale_degree in range(-1, -9, -1): # doctest: +SKIP
...     chromatic_pitch_number = pitchtools.pentatonic_pitch_number_to_chromatic_pitch_number(pe
...     print '%s\t%s' % (pentatonic_scale_degree, chromatic_pitch_number)
...
-1 -2
-2 -4
-3 -6
-4 -9
-5 -11
-6 -14
-7 -16
-8 -18
```

Return integer. Changed in version 2.0: renamed `pitchtools.pentatonic_to_chromatic()` to `pitchtools.pentatonic_pitch_number_to_chromatic_pitch_number()`.

`pitchtools.permute_named_chromatic_pitch_carrier_list_by_twelve_tone_row`

`abjad.tools.pitchtools.permute_named_chromatic_pitch_carrier_list_by_twelve_tone_row` (*pitches*, *row*)

New in version 2.0. Permute named chromatic pitch carrier list by twelve-tone *row*:

```
abjad> notes = notetools.make_notes([17, -10, -2, 11], [Duration(1, 4)])
abjad> row = pitchtools.TwelveToneRow([10, 0, 2, 6, 8, 7, 5, 3, 1, 9, 4, 11])
abjad> pitchtools.permute_named_chromatic_pitch_carrier_list_by_twelve_tone_row(notes, row)
[Note('bf4'), Note('d4'), Note("f'4"), Note("b'4")]
```

Function works by reference only. No objects are cloned.

Return list.

`pitchtools.register_chromatic_pitch_class_numbers_by_chromatic_pitch_number_aggregate`

`abjad.tools.pitchtools.register_chromatic_pitch_class_numbers_by_chromatic_pitch_number_aggregate`

New in version 1.1. Register chromatic *pitch_class_numbers* by chromatic pitch-number *aggregate*:

```
abjad> pitchtools.register_chromatic_pitch_class_numbers_by_chromatic_pitch_number_aggregate(
...     [10, 0, 2, 6, 8, 7, 5, 3, 1, 9, 4, 11],
...     [10, 19, 20, 23, 24, 26, 27, 29, 30, 33, 37, 40])
[10, 24, 26, 30, 20, 19, 29, 27, 37, 33, 40, 23]
```

Return list of zero or more chromatic pitch numbers. Changed in version 2.0: renamed `pitchtools.registrate()` to `pitchtools.register_chromatic_pitch_class_numbers_by_chromatic_pitch_number_aggregate()`.

`pitchtools.respell_named_chromatic_pitches_in_expr_with_flats`

`abjad.tools.pitchtools.respell_named_chromatic_pitches_in_expr_with_flats` (*expr*)

New in version 1.1. Respell named chromatic pitches in *expr* with flats:

```
abjad> staff = Staff(notetools.make_repeated_notes(6))
abjad> pitchtools.set_ascending_named_chromatic_pitches_on_nontied_pitched_components_in_expr(staff)

abjad> f(staff)
\new Staff {
    c'8
    cs'8
    d'8
    ef'8
    e'8
    f'8
}

abjad> pitchtools.respell_named_chromatic_pitches_in_expr_with_flats(staff)

abjad> f(staff)
\new Staff {
    c'8
    df'8
    d'8
    ef'8
    e'8
    f'8
}
```

Return `none`. Changed in version 2.0: renamed `pitchtools.make_flat()` to `pitchtools.respell_named_chromatic_pitches_in_expr_with_flats()`.

`pitchtools.respell_named_chromatic_pitches_in_expr_with_sharps`

`abjad.tools.pitchtools.respell_named_chromatic_pitches_in_expr_with_sharps` (*expr*)

New in version 1.1. Respell named chromatic pitches in *expr* with sharps:

```
abjad> staff = Staff(notetools.make_repeated_notes(6))
abjad> pitchtools.set_ascending_named_chromatic_pitches_on_nontied_pitched_components_in_expr(staff)
```

```

abjad> f(staff)
\new Staff {
    c'8
    cs'8
    d'8
    ef'8
    e'8
    f'8
}

abjad> pitchtools.respell_named_chromatic_pitches_in_expr_with_sharps(staff)

abjad> f(staff)
\new Staff {
    c'8
    cs'8
    d'8
    ds'8
    e'8
    f'8
}

```

Return `none`. Changed in version 2.0: renamed `pitchtools.make_sharp()` to `pitchtools.respell_named_chromatic_pitches_in_expr_with_sharps()`.

`pitchtools.set_ascending_named_chromatic_pitches_on_nontied_pitched_components_in_expr`

`abjad.tools.pitchtools.set_ascending_named_chromatic_pitches_on_nontied_pitched_components_in_expr`
 New in version 1.1. Set ascending named chromatic pitches on nontied pitched components in *expr*:

```

abjad> staff = Voice(notetools.make_notes(0, [(5, 32)] * 4))
abjad> pitchtools.set_ascending_named_chromatic_pitches_on_nontied_pitched_components_in_expr(staff)

abjad> f(staff)
\new Voice {
    c'8 ~
    c'32
    cs'8 ~
    cs'32
    d'8 ~
    d'32
    ef'8 ~
    ef'32
}

```

Used primarily in generating test file examples.

Return `none`. Changed in version 2.0: renamed `pitchtools.chromaticize()` to `pitchtools.set_ascending_named_chromatic_pitches_on_nontied_pitched_components_in_expr`

`pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr`

`abjad.tools.pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr`

New in version 1.1. Set ascending named diatonic pitches on nontied pitched components in *expr*:


```

abjad> staff = Staff(notetools.make_notes(0, [(5, 32)] * 4))
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)

abjad> f(staff)
\new Staff {
    c'8 ~
    c'32
    d'8 ~
    d'32
    e'8 ~
    e'32
    f'8 ~
    f'32
}

```

Used primarily in generating test file examples. New in version 2.0: Optional *key_signature* keyword argument. Return none. Changed in version 2.0: renamed `pitchtools.diatonicize()` to `pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr()`

`pitchtools.suggest_clef_for_named_chromatic_pitches`

```

abjad.tools.pitchtools.suggest_clef_for_named_chromatic_pitches(pitches,
                                                                clefs=['treble',
                                                                'bass'])

```

New in version 1.1. Suggest clef for named chromatic *pitches*:

```

abjad> staff = Staff(notetools.make_notes(range(-12, -6), [(1, 4)]))
abjad> pitchtools.suggest_clef_for_named_chromatic_pitches(staff)
ClefMark('bass')

```

Suggest clef based on minimal number of ledger lines.

Return clef mark. Changed in version 2.0: renamed `pitchtools.suggest_clef()` to `pitchtools.suggest_clef_for_named_chromatic_pitches()`.

`pitchtools.transpose_chromatic_pitch_by_melodic_chromatic_interval_segment`

```

abjad.tools.pitchtools.transpose_chromatic_pitch_by_melodic_chromatic_interval_segment(pitch,
                                                                                       segment)

```

New in version 2.0. Transpose chromatic *pitch* by melodic chromatic interval *segment*:

```

abjad> ncp = pitchtools.NumberedChromaticPitch(0)
abjad> mcis = pitchtools.MelodicChromaticIntervalSegment([0, -1, 2])
abjad> pitchtools.transpose_chromatic_pitch_by_melodic_chromatic_interval_segment(ncp, mcis)
[NumberedChromaticPitch(0), NumberedChromaticPitch(-1), NumberedChromaticPitch(1)]

```

Transpose by each interval in *segment* such that each transposition transposes the resulting pitch of the previous transposition.

Return list of numbered chromatic pitches.

pitchtools.transpose_chromatic_pitch_class_number_by_octaves_to_nearest_neighbor_of_chromatic_pitch_number

abjad.tools.pitchtools.transpose_chromatic_pitch_class_number_by_octaves_to_nearest_neighbor_of_chromatic_pitch_number

New in version 1.1. Transpose *chromatic_pitch_class_number* by octaves to nearest neighbor of *chromatic_pitch_number*:

```
abjad> pitchtools.transpose_chromatic_pitch_class_number_by_octaves_to_nearest_neighbor_of_chromatic_pitch_number(16)
```

Resulting chromatic pitch number must be within one tritone of *pitch_number*.

Return integer or float. Changed in version 2.0: renamed `pitchtools.nearest_neighbor()` to `pitchtools.transpose_chromatic_pitch_class_number_by_octaves_to_nearest_neighbor_of_chromatic_pitch_number`.

pitchtools.transpose_chromatic_pitch_number_by_octave_transposition_mapping

abjad.tools.pitchtools.transpose_chromatic_pitch_number_by_octave_transposition_mapping(*chromatic_pitch_number*, *mapping*)

New in version 1.1. Transpose *chromatic_pitch_number* by the some number of octaves up or down. Derive correct number of octaves from *mapping* where *mapping* is a list of (*range_spec*, *octave*) pairs and *range_spec* is, in turn, a (*start*, *stop*) pair suitable to pass to the built-in Python `range()` function:

```
abjad> mapping = [((-39, -13), 0), ((-12, 23), 12), ((24, 48), 24)]
```

The mapping given here comprises three (*range_spec*, *octave*) pairs. The first such pair is `((-39, -13), 0)` and can be read as follows: “any pitches between -39 and -13 should be transposed into the octave rooted at pitch 0.” The octave rooted at pitch 0 equals the twelve pitches `range(0, 0 + 12)` or `[0, 1, ..., 10, 11]`.

The second (*range_spec*, *octave*) pair is `((-12, 23), 12)` and can be read as “any pitches between -12 and 23 should be transposed into the octave rooted at pitch 12,” with the octave rooted at pitch 12 equal to the twelve pitches `range(12, 12 + 12)` or `[12, 13, ..., 22, 23]`.

The third and last (*range_spec*, *octave*) pair is `((24, 48), 24)` and can be read as “any pitches between 24 and 48 should be transposed to the octave rooted at 24,” with the octave rooted at 24 equal to the twelve pitches `range(24, 24, + 12)` or `[24, 25, ..., 34, 35]`.

The mapping given here divides the compass of the piano, from -39 to 48, into three disjunct subranges and then explains how to transpose pitches found in any of those three disjunct subranges. This means that, for example, all the f-sharps within the range of the piano now undergo a known transposition under *mapping* as defined here:

```
abjad> pitchtools.transpose_chromatic_pitch_number_by_octave_transposition_mapping(-30, mapping)
```

6

We verify that pitch -30 should map to pitch 6 by noticing that pitch -30 falls in the first of the three subranges defined by *mapping* from -39 to -13 and then noting that *mapping* sends pitches with that subrange to the octave rooted at pitch 0. The octave transposition of -30 that falls within the octave rooted at 0 is 6:

```
abjad> pitchtools.transpose_chromatic_pitch_number_by_octave_transposition_mapping(-18, mapping)
```

6

Likewise, *mapping* sends pitch -18 to pitch 6 because pitch -18 falls in the same subrange from -39 to -13 as did pitch -39 and so undergoes the same transposition to the octave rooted at 0.

In this way we can map all f-sharps from -39 to 48 according to *mapping*:

```
abjad> pitch_numbers = [-30, -18, -6, 6, 18, 30, 42]
abjad> for n in pitch_numbers:
...     n, pitchtools.transpose_chromatic_pitch_number_by_octave_transposition_mapping(n, mapping)
(-30, 6)
(-18, 6)
(-6, 18)
(6, 18)
(18, 18)
(30, 30)
(42, 30)
```

And so on.

Return chromatic pitch number. Changed in version 2.0: renamed
`pitchtools.send_pitch_number_to_octave()` to `pitchtools.transpose_chromatic_pitch_number_`

`pitchtools.transpose_named_chromatic_pitch_by_melodic_chromatic_interval_and_respell`

`abjad.tools.pitchtools.transpose_named_chromatic_pitch_by_melodic_chromatic_interval_and_respell`

New in version 1.1. Transpose named chromatic pitch by *melodic_chromatic_interval* and respell *staff_spaces* above or below:

```
abjad> pitch = pitchtools.NamedChromaticPitch(0)
abjad> pitchtools.transpose_named_chromatic_pitch_by_melodic_chromatic_interval_and_respell(pitch,
NamedChromaticPitch("dtqf'"))
```

Return new named chromatic pitch. Changed in version 2.0: renamed
`pitchtools.staff_space_transpose()` to `pitchtools.transpose_named_chromatic_pitch_by_melo`

`pitchtools.transpose_pitch_carrier_by_melodic_interval`

`abjad.tools.pitchtools.transpose_pitch_carrier_by_melodic_interval` (*pitch_carrier*,
melodic_interval)

New in version 2.0. Transpose *pitch_carrier* by diatonic *melodic_interval*:

```
abjad> chord = Chord("<c' e' g'>4")

abjad> pitchtools.transpose_pitch_carrier_by_melodic_interval(chord, '+m2')
Chord("<df' f' af'>4")
```

Transpose *pitch_carrier* by chromatic *melodic_interval*:

```
abjad> chord = Chord("<c' e' g'>4")

abjad> pitchtools.transpose_pitch_carrier_by_melodic_interval(chord, 1)
Chord("<cs' f' af'>4")
```

Return non-pitch-carrying input unchanged:

```
abjad> rest = Rest('r4')

abjad> pitchtools.transpose_pitch_carrier_by_melodic_interval(rest, 1)
Rest('r4')
```

Return *pitch_carrier*.

pitchtools.transpose_pitch_expr_into_pitch_range

`abjad.tools.pitchtools.transpose_pitch_expr_into_pitch_range` (*pitch_expr*,
pitch_range)

New in version 2.0. Transpose *pitch_expr* into *pitch_range*:

```
abjad> pitchtools.transpose_pitch_expr_into_pitch_range([-2, -1, 13, 14], pitchtools.PitchRange(
[10, 11, 1, 2])
```

Return new *pitch_expr* object.

resttools

resttools.MultiMeasureRest

class `abjad.tools.resttools.MultiMeasureRest` (*args, **kwargs)

Bases: `abjad.tools.resttools.Rest.Rest.Rest` New in version 2.0. Abjad model of a multi-measure rest:

```
abjad> resttools.MultiMeasureRest((1, 4))
MultiMeasureRest('R4')
```

Multi-measure rests are immutable.

resttools.Rest

class `abjad.tools.resttools.Rest` (*args, **kwargs)

Bases: `abjad.tools.leaftools._Leaf._Leaf._Leaf`

Abjad model of a rest:

```
abjad> Rest((3, 16))
Rest('r8.')
```

resttools.is_lilypond_rest_string

`abjad.tools.resttools.is_lilypond_rest_string` (*expr*)

New in version 2.0. True when *expr* is a LilyPond rest string:

```
abjad> resttools.is_lilypond_rest_string('r4.. * 1/2')
True
```

Otherwise false:

```
abjad> resttools.is_lilypond_rest_string('text')
False
```

The regex `^(r|R)\s*(1|2|4|8|16|32|64|128|\breve|\longa|\maxima)\s*(\.*)\s*(*\s*(\d+(\d+|` underlies this predicate.

Return boolean.

resttools.iterate_rests_backward_in_expr

`abjad.tools.resttools.iterate_rests_backward_in_expr` (*expr*, *start=0*, *stop=None*)

New in version 2.0. Iterate rests backward in *expr*:

```

abjad> staff = Staff("<e' g' c''>8 a'8 r8 <d' f' b'>8 r2")

abjad> f(staff)
\new Staff {
    <e' g' c''>8
    a'8
    r8
    <d' f' b'>8
    r2
}

abjad> for rest in resttools.iterate_rests_backward_in_expr(staff):
...     rest
Rest('r2')
Rest('r8')

```

Ignore threads.

Return generator.

resttools.iterate_rests_forward_in_expr

`abjad.tools.resttools.iterate_rests_forward_in_expr(expr, start=0, stop=None)`
 New in version 2.0. Iterate rests forward in *expr*:

```

abjad> staff = Staff("<e' g' c''>8 a'8 r8 <d' f' b'>8 r2")

abjad> f(staff)
\new Staff {
    <e' g' c''>8
    a'8
    r8
    <d' f' b'>8
    r2
}

abjad> for rest in resttools.iterate_rests_forward_in_expr(staff):
...     rest
Rest('r8')
Rest('r2')

```

Ignore threads.

Return generator.

resttools.make_multi_measure_rests

`abjad.tools.resttools.make_multi_measure_rests(duration_tokens)`
 New in version 2.0. Make multi-measure rests from *duration_tokens*:

```

abjad> resttools.make_multi_measure_rests([(4, 4), (7, 4)])
[MultiMeasureRest('R1'), MultiMeasureRest('R1..')]

```

Return list.

resttools.make_repeated_rests_from_time_signature

`abjad.tools.resttools.make_repeated_rests_from_time_signature` (*time_signature*)
 New in version 2.0. Make repeated rests from *time_signature*:

```
abjad> resttools.make_repeated_rests_from_time_signature((5, 32))
[Rest('r32'), Rest('r32'), Rest('r32'), Rest('r32'), Rest('r32')]
```

Return list of newly constructed rests.

resttools.make_repeated_rests_from_time_signatures

`abjad.tools.resttools.make_repeated_rests_from_time_signatures` (*time_signatures*)
 Make repeated rests from *time_signatures*:

```
resttools.make_repeated_rests_from_time_signatures([(2, 8), (3, 32)])
[[Rest('r8'), Rest('r8')], [Rest('r32'), Rest('r32'), Rest('r32')]]
```

Return two-dimensional list of newly constructed rest lists.

Use `seqtools.flatten_sequence()` to flatten output if required.

resttools.make_rests

`abjad.tools.resttools.make_rests` (*duration_tokens*, *direction*='big-endian', *tied*=False)
 New in version 1.1. Make rests.

Make big-endian rests:

```
abjad> resttools.make_rests([(5, 16), (9, 16)], direction = 'big-endian')
[Rest('r4'), Rest('r16'), Rest('r2'), Rest('r16')]
```

Make little-endian rests:

```
abjad> resttools.make_rests([(5, 16), (9, 16)], direction = 'little-endian')
[Rest('r16'), Rest('r4'), Rest('r16'), Rest('r2')]
```

Make tied rests:

```
abjad> voice = Voice(resttools.make_rests([(5, 16), (9, 16)], tied = True))
```

```
abjad> f(voice)
\new Voice {
    r4 ~
    r16
    r2 ~
    r16
}
```

Return list of rests. Changed in version 2.0: renamed `construct.rests()` to `resttools.make_rests()`.

resttools.set_vertical_positioning_pitch_on_rest

`abjad.tools.resttools.set_vertical_positioning_pitch_on_rest` (*rest*, *pitch*)
 New in version 2.0. Set vertical positioning *pitch* on *rest*:

```

abjad> rest = Rest((1, 4))

abjad> resttools.set_vertical_positioning_pitch_on_rest(rest, "d'")
Rest('r4')

abjad> f(rest)
d''4 \rest

```

Raise type error when *rest* is not a rest.

Return *rest*.

resttools.yield_groups_of_rests_in_sequence

`abjad.tools.resttools.yield_groups_of_rests_in_sequence(sequence)`

New in version 2.0. Yield groups of rests in *sequence*:

```

abjad> staff = Staff("c'8 d'8 r8 r8 <e' g'>8 <f' a'>8 g'8 a'8 r8 r8 <b' d''>8 <c'' e''>8")

abjad> f(staff)
\new Staff {
    c'8
    d'8
    r8
    r8
    <e' g'>8
    <f' a'>8
    g'8
    a'8
    r8
    r8
    <b' d''>8
    <c'' e''>8
}

abjad> for rest in resttools.yield_groups_of_rests_in_sequence(staff):
...     rest
...
(Rest('r8'), Rest('r8'))
(Rest('r8'), Rest('r8'))

```

Return generator.

schemetools

schemetools.SchemeAssociativeList

class `abjad.tools.schemetools.SchemeAssociativeList`

Bases: `tuple`, `abjad.core._Immutable._Immutable._Immutable` New in version 2.0. Abjad model of Scheme associative list:

```

abjad> schemetools.SchemeAssociativeList(('space', 2), ('padding', 0.5))
SchemeAssociativeList(SchemePair('space', 2), SchemePair('padding', 0.5))

```

Scheme associative lists are immutable.

format

LilyPond input format of Scheme associative list:

```
abjad> scheme_associative_list = schemetools.SchemeAssociativeList(('space', 2), ('padding',
abjad> scheme_associative_list.format
"##'((space . 2) (padding . 0.5))"
```

Return string.

schemetools.SchemeBoolean

class abjad.tools.schemetools.**SchemeBoolean**

Bases: abjad.core._Immutable._Immutable._Immutable

Abjad model of Scheme boolean:

```
abjad> schemetools.SchemeBoolean(True)
SchemeBoolean(True)
```

Scheme variables are immutable.

arg

format

LilyPond input format of Scheme boolean:

```
abjad> scheme_boolean = schemetools.SchemeBoolean(True)
abjad> scheme_boolean.format
'##t'
```

Return string.

schemetools.SchemeColor

class abjad.tools.schemetools.**SchemeColor**

Bases: abjad.core._StrictComparator._StrictComparator._StrictComparator,
abjad.core._Immutable._Immutable._Immutable

Abjad model of Scheme color:

```
abjad> schemetools.SchemeColor('ForestGreen')
SchemeColor('ForestGreen')
```

Scheme colors are immutable.

color_name

format

LilyPond input format of Scheme color:

```
abjad> scheme_color = schemetools.SchemeColor('ForestGreen')
abjad> scheme_color.format
"##(x11-color 'ForestGreen)"
```

Return string.

schemetools.SchemeFunction

class abjad.tools.schemetools.**SchemeFunction**

Bases: abjad.core._StrictComparator._StrictComparator._StrictComparator,
abjad.core._Immutable._Immutable._Immutable

Abjad model of Scheme function:

```
abjad> schemetools.SchemeFunction('magstep', -3)
SchemeFunction('magstep', -3)
```

Scheme functions are immutable.

format

LilyPond input format of Scheme function:

```
abjad> scheme_function = schemetools.SchemeFunction('magstep', -3)
abjad> scheme_function.format
'#(magstep -3)'
```

Return string.

schemetools.SchemeMoment

class abjad.tools.schemetools.**SchemeMoment**

Bases: abjad.core._StrictComparator._StrictComparator._StrictComparator,
abjad.core._Immutable._Immutable._Immutable

Abjad model of LilyPond moment:

```
abjad> schemetools.SchemeMoment(1, 68)
SchemeMoment(1, 68)
```

Initialize scheme moments with a single fraction, two integers or another scheme moment.

Scheme moments are immutable.

duration

Duration of scheme moment:

```
abjad> scheme_moment = schemetools.SchemeMoment(1, 68)
abjad> scheme_moment.duration
Fraction(1, 68)
```

Return duration.

format

LilyPond input format of scheme moment:

```
abjad> scheme_moment = schemetools.SchemeMoment(1, 68)
abjad> scheme_moment.format
'#(ly:make-moment 1 68)'
```

Return string.

schemetools.SchemeNumber

class abjad.tools.schemetools.**SchemeNumber**

Bases: abjad.core._Immutable._Immutable._Immutable

Abjad model of Scheme number:

```
abjad> schemetools.SchemeNumber(1.1)
SchemeNumber(1.1...)
```

Scheme numbers are immutable.

format

LilyPond input format of Scheme number:

```
abjad> scheme_number = schemetools.SchemeNumber(1.1)
abjad> scheme_number.format
'#1.1'
```

Return string.

number

schemetools.SchemePair

class abjad.tools.schemetools.**SchemePair**

Bases: tuple, abjad.core._Immutable._Immutable._Immutable

Abjad model of Scheme pair:

```
abjad> schemetools.SchemePair('spacing', 4)
SchemePair('spacing', 4)
```

Initialize Scheme pairs with a tuple, two separate values or another Scheme pair.

Scheme pairs are immutable.

format

LilyPond input format of Scheme pair:

```
abjad> scheme_pair = schemetools.SchemePair('spacing', 4)
abjad> scheme_pair.format
"##(spacing . 4)"
```

Return string.

schemetools.SchemeString

class abjad.tools.schemetools.**SchemeString**

Bases: abjad.core._StrictComparator._StrictComparator._StrictComparator, abjad.core._Immutable._Immutable._Immutable

Abjad model of Scheme string:

```
abjad> schemetools.SchemeString('grace')
SchemeString('grace')
```

Scheme strings are immutable.

format

LilyPond input format of Scheme string:

```
abjad> scheme_string = schemetools.SchemeString('grace')
abjad> scheme_string.format
'#"grace"'
```

Return string.

schemetools.SchemeVariable

class abjad.tools.schemetools.**SchemeVariable**

Bases: abjad.core._StrictComparator._StrictComparator._StrictComparator,
abjad.core._Immutable._Immutable._Immutable

Abjad model of Scheme variable:

```
abjad> schemetools.SchemeVariable('grace')
SchemeVariable('grace')
```

Scheme variables are immutable.

format

LilyPond input format of Scheme variable:

```
abjad> scheme_variable = schemetools.SchemeVariable('UP')
abjad> scheme_variable.format
'#UP'
```

Return string.

schemetools.SchemeVector

class abjad.tools.schemetools.**SchemeVector**

Bases: tuple, abjad.core._Immutable._Immutable._Immutable New in version 2.0. Abjad model of Scheme vector:

```
abjad> schemetools.SchemeVector(True, True, False)
SchemeVector(True, True, False)
```

Scheme vectors and Scheme vector constants differ in only their LilyPond input format.

Scheme vectors are immutable.

format

LilyPond input format of Scheme vector:

```
abjad> scheme_vector = schemetools.SchemeVector(True, True, False)
abjad> scheme_vector.format
"##'(#t #t #f)"
```

Return string.

schemetools.SchemeVectorConstant

class abjad.tools.schemetools.**SchemeVectorConstant**

Bases: tuple, abjad.core._Immutable._Immutable._Immutable New in version 2.0. Abjad model of Scheme vector constant:

```
abjad> schemetools.SchemeVectorConstant(True, True, False)
SchemeVectorConstant(True, True, False)
```

Scheme vectors and Scheme vector constants differ in only their LilyPond input format.

Scheme vector constants are immutable.

format

LilyPond input format of scheme vector constant:

```
abjad> scheme_vector_constant = schemetools.SchemeVectorConstant(True, True, False)
abjad> scheme_vector_constant.format
"#' #(#t #t #f) "
```

Return string.

scoretools

scoretools.GrandStaff

class abjad.tools.scoretools.**GrandStaff** (*music*)

Bases: abjad.tools.scoretools.StaffGroup.StaffGroup.StaffGroup

Abjad model of grand staff:

```
abjad> staff_1 = Staff("c'4 d'4 e'4 f'4 g'1")
abjad> staff_2 = Staff("g2 f2 e1")

abjad> grand_staff = scoretools.GrandStaff([staff_1, staff_2])

abjad> f(grand_staff)
\new GrandStaff <<
  \new Staff {
    c'4
    d'4
    e'4
    f'4
    g'1
  }
  \new Staff {
    g2
    f2
    e1
  }
>>
```

Return grand staff.

scoretools.PianoStaff

class abjad.tools.scoretools.**PianoStaff** (*music*)

Bases: abjad.tools.scoretools.StaffGroup.StaffGroup.StaffGroup

Abjad model of piano staff:

```
abjad> staff_1 = Staff("c'4 d'4 e'4 f'4 g'1")
abjad> staff_2 = Staff("g2 f2 e1")

abjad> piano_staff = scoretools.PianoStaff([staff_1, staff_2])

abjad> f(piano_staff)
\new PianoStaff <<
  \new Staff {
    c'4
    d'4
```

```

        e'4
        f'4
        g'1
    }
    \new Staff {
        g2
        f2
        e1
    }
>>

```

Return piano staff.

scoretools.Score

class abjad.tools.scoretools.**Score**(*music=None, **kwargs*)
 Bases: abjad.tools.contexttools._Context._Context._Context

Abjad model of a score:

```

abjad> staff_1 = Staff("c'8 d'8 e'8 f'8")
abjad> staff_2 = Staff("c'8 d'8 e'8 f'8")
abjad> score = Score([staff_1, staff_2])
abjad> f(score)
\new Score <<
    \new Staff {
        c'8
        d'8
        e'8
        f'8
    }
    \new Staff {
        c'8
        d'8
        e'8
        f'8
    }
>>

```

Return score object.

scoretools.StaffGroup

class abjad.tools.scoretools.**StaffGroup**(*music=[]*, ***kwargs*)
 Bases: abjad.tools.contexttools._Context._Context._Context

Abjad model of staff group:

```

abjad> staff_1 = Staff("c'4 d'4 e'4 f'4 g'1")
abjad> staff_2 = Staff("g2 f2 e1")

abjad> staff_group = scoretools.StaffGroup([staff_1, staff_2])

abjad> f(staff_group)
\new StaffGroup <<
    \new Staff {
        c'4

```

```

        d'4
        e'4
        f'4
        g'1
    }
    \new Staff {
        g2
        f2
        e1
    }
>>

```

Return staff group.

scoretools.add_double_bar_to_end_of_score

`abjad.tools.scoretools.add_double_bar_to_end_of_score(score)`

New in version 2.0. Add double bar to end of *score*:

```

abjad> staff = Staff("c'4 d'4 e'4 f'4")

abjad> scoretools.add_double_bar_to_end_of_score(staff)
LilyPondCommandMark('bar "|."')(f'4)

abjad> f(staff)
\new Staff {
    c'4
    d'4
    e'4
    f'4
    \bar "|."
}

```

Return double bar.

scoretools.add_markup_to_end_of_score

`abjad.tools.scoretools.add_markup_to_end_of_score(score, markup, extra_offset=None)`

New in version 2.0. Add *markup* to end of *score*:

```

abjad> staff = Staff("c'4 d'4 e'4 f'4")
abjad> markup = r'\italic \right-column { "Bremen - Boston - Los Angeles." "Jul 2010 - May 2011." }'
abjad> markup = markuptools.Markup(markup, 'down')
abjad> scoretools.add_markup_to_end_of_score(staff, markup, (4, -2))
Markup('\italic \right-column { "Bremen - Boston - Los Angeles." "Jul 2010 - May 2011." }', 'down')

abjad> f(staff)
\new Staff {
    c'4
    d'4
    e'4
    \once \override TextScript #'extra-offset = #'(4 . -2)
    f'4 _ \markup { \italic \right-column { "Bremen - Boston - Los Angeles." "Jul 2010 - May 2011." } }
}

```

Return *markup*.

scoretools.get_first_score_in_improper_parentage_of_component

`abjad.tools.scoretools.get_first_score_in_improper_parentage_of_component` (*component*)
 New in version 2.0. Get first score in improper parentage of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> score = Score([staff])

abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
>>

abjad> scoretools.get_first_score_in_improper_parentage_of_component(score.leaves[0])
Score<<1>>
```

Return score or none.

scoretools.get_first_score_in_proper_parentage_of_component

`abjad.tools.scoretools.get_first_score_in_proper_parentage_of_component` (*component*)
 New in version 2.0. Get first score in proper parentage of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> score = Score([staff])

abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
>>

abjad> scoretools.get_first_score_in_proper_parentage_of_component(score.leaves[0])
Score<<1>>
```

Return score or none.

scoretools.iterate_scores_backward_in_expr

`abjad.tools.scoretools.iterate_scores_backward_in_expr` (*expr*, *start=0*, *stop=None*)
 New in version 2.0. Iterate scores backward in *expr*:

```
abjad> score_1 = Score([Staff("c'8 d'8 e'8 f'8")])
abjad> score_2 = Score([Staff("c'1"), Staff("g'1")])
abjad> scores = [score_1, score_2]
```

```
abjad> for score in scoretools.iterate_scores_backward_in_expr(scores):
...     score
Score<<2>>
Score<<1>>
```

Ignore threads.

Return generator.

scoretools.iterate_scores_forward_in_expr

`abjad.tools.scoretools.iterate_scores_forward_in_expr(expr, start=0, stop=None)`

New in version 2.0. Iterate scores forward in *expr*:

```
abjad> score_1 = Score([Staff("c'8 d'8 e'8 f'8")])
abjad> score_2 = Score([Staff("c'1"), Staff("g'1")])
abjad> scores = [score_1, score_2]
```

```
abjad> for score in scoretools.iterate_scores_forward_in_expr(scores):
...     score
Score<<1>>
Score<<2>>
```

Ignore threads.

Return generator.

scoretools.make_empty_piano_score

`abjad.tools.scoretools.make_empty_piano_score()`

New in version 1.1. Make empty piano score:

```
abjad> score, treble, bass = scoretools.make_empty_piano_score()
```

```
abjad> f(score)
\new Score <<
  \new PianoStaff <<
    \context Staff = "treble" {
      \clef "treble"
    }
    \context Staff = "bass" {
      \clef "bass"
    }
  >>
>>
```

Return `score`, `treble` staff, `bass` staff. Changed in version 2.0: renamed `scoretools.make_piano_staff()` to `scoretools.make_empty_piano_score()`.

scoretools.make_piano_score_from_leaves

`abjad.tools.scoretools.make_piano_score_from_leaves(leaves, low-est_treble_pitch=NamedChromaticPitch('b'))`

New in version 2.0. Make piano score from *leaves*:


```

abjad> notes = [Note(x, (1, 4)) for x in [-12, 37, -10, 2, 4, 17]]
abjad> score, treble_staff, bass_staff = scoretools.make_piano_score_from_leaves(notes)

abjad> f(score)
\new Score <<
  \new PianoStaff <<
    \context Staff = "treble" {
      \clef "treble"
      r4
      cs''''4
      r4
      d'4
      e'4
      f''4
    }
    \context Staff = "bass" {
      \clef "bass"
      c4
      r4
      d4
      r4
      r4
      r4
    }
  >>
>>

```

Return score, treble staff, bass staff.

scoretools.make_piano_sketch_score_from_leaves

abjad.tools.scoretools.**make_piano_sketch_score_from_leaves**(*leaves*, *low-est_treble_pitch*=*NamedChromaticPitch('b')*)

New in version 2.0. Make piano sketch score from *leaves*:

```

abjad> notes = notetools.make_notes([-12, -10, -8, -7, -5, 0, 2, 4, 5, 7], [(1, 4)])
abjad> score, treble_staff, bass_staff = scoretools.make_piano_sketch_score_from_leaves(notes)

abjad> f(score)
\new Score \with {
  \override BarLine #'stencil = ##f
  \override BarNumber #'transparent = ##t
  \override SpanBar #'stencil = ##f
  \override TimeSignature #'transparent = ##t
} <<
  \new PianoStaff <<
    \context Staff = "treble" {
      \clef "treble"
      #(set-accidental-style 'forget)
      r4
      r4
      r4
      r4
      r4
      c'4
      d'4
      e'4
    }
  >>
>>

```

```

        f'4
        g'4
    }
    \context Staff = "bass" {
        \clef "bass"
        #(set-accidental-style 'forget)
        c4
        d4
        e4
        f4
        g4
        r4
        r4
        r4
        r4
        r4
    }
>>
>>

```

Make time signatures and bar numbers transparent.

Do not print bar lines or span bars.

Set all staff accidental styles to forget.

Return score, treble staff, bass staff.

scoretools.make_pitch_array_score_from_pitch_arrays

abjad.tools.scoretools.**make_pitch_array_score_from_pitch_arrays** (*pitch_arrays*)

New in version 2.0. Make pitch-array score from *pitch_arrays*:

```

abjad> from abjad.tools import pitcharraytools

abjad> array_1 = pitcharraytools.PitchArray([
...     [1, (2, 1), ([-2, -1.5], 2)],
...     [(7, 2), (6, 1), 1]])

abjad> array_2 = pitcharraytools.PitchArray([
...     [1, 1, 1],
...     [1, 1, 1]])

abjad> score = scoretools.make_pitch_array_score_from_pitch_arrays([array_1, array_2])

abjad> f(score)
\new Score <<
  \new StaffGroup <<
    \new Staff {
      {
        \time 4/8
        r8
        d'8
        <bf bqf>4
      }
      {
        \time 3/8
        r8

```

```

        r8
        r8
    }
}
\new Staff {
    {
        \time 4/8
        g'4
        fs'8
        r8
    }
    {
        \time 3/8
        r8
        r8
        r8
    }
}
>>
>>

```

Create one staff per pitch-array row.

Return score.

skiptools

skiptools.Skip

class abjad.tools.skiptools.**Skip**(*args, **kwargs)
 Bases: abjad.tools.leaftools._Leaf._Leaf._Leaf

Abjad model of a LilyPond skip:

```

abjad> skiptools.Skip((3, 16))
Skip('s8.')

```

Return skip.

skiptools.iterate_skips_backward_in_expr

abjad.tools.skiptools.**iterate_skips_backward_in_expr**(expr, start=0, stop=None)

New in version 2.0. Iterate skips backward in *expr*:

```

abjad> staff = Staff("<e' g' c''>8 a'8 s8 <d' f' b'>8 s2")

abjad> f(staff)
\new Staff {
    <e' g' c''>8
    a'8
    s8
    <d' f' b'>8
    s2
}

abjad> for skip in skiptools.iterate_skips_backward_in_expr(staff):
...     skip

```

```
Skip('s2')
Skip('s8')
```

Ignore threads.

Return generator.

skiptools.iterate_skips_forward_in_expr

`abjad.tools.skiptools.iterate_skips_forward_in_expr(expr, start=0, stop=None)`
 New in version 2.0. Iterate skips forward in *expr*:

```
abjad> staff = Staff("<e' g' c''>8 a'8 s8 <d' f' b'>8 s2")

abjad> f(staff)
\new Staff {
    <e' g' c''>8
    a'8
    s8
    <d' f' b'>8
    s2
}

abjad> for skip in skiptools.iterate_skips_forward_in_expr(staff):
...     skip
Skip('s8')
Skip('s2')
```

Ignore threads.

Return generator.

skiptools.make_repeated_skips_from_time_signature

`abjad.tools.skiptools.make_repeated_skips_from_time_signature(time_signature)`
 New in version 2.0. Make repeated skips from *time_signature*:

```
abjad> skiptools.make_repeated_skips_from_time_signature((5, 32))
[Skip('s32'), Skip('s32'), Skip('s32'), Skip('s32'), Skip('s32')]
```

Return list of skips.

skiptools.make_repeated_skips_from_time_signatures

`abjad.tools.skiptools.make_repeated_skips_from_time_signatures(time_signatures)`
 Make repeated skips from *time_signatures*:

```
skiptools.make_repeated_skips_from_time_signatures([(2, 8), (3, 32)])
[[Skip('s8'), Skip('s8')], [Skip('s32'), Skip('s32'), Skip('s32')]]
```

Return list of skip lists.

skiptools.make_skips_with_multiplied_durations

abjad.tools.skiptools.**make_skips_with_multiplied_durations** (*written_duration*, *multiplied_durations*)

New in version 2.0. Make *written_duration* skips with *multiplied_durations*:

```
abjad> skiptools.make_skips_with_multiplied_durations(Duration(1, 4), [(1, 2), (1, 3), (1, 4), (1, 5)],
[Skip('s4 * 2'), Skip('s4 * 4/3'), Skip('s4 * 1'), Skip('s4 * 4/5')])
```

Useful for making invisible layout voices.

Return list of skips. Changed in version 2.0: renamed `construct.skips_with_multipliers()` to `skiptools.make_skips_with_multiplied_durations()`.

skiptools.replace_leaves_in_expr_with_skips

abjad.tools.skiptools.**replace_leaves_in_expr_with_skips** (*expr*)

New in version 1.1. Replace leaves in *expr* with skips:

```
abjad> staff = Staff(Measure((2, 8), "c'8 d'8") * 2)
abjad> skiptools.replace_leaves_in_expr_with_skips(staff[0])
abjad> print staff.format
\new Staff {
  {
    \time 2/8
    s8
    s8
  }
  {
    \time 2/8
    c'8
    d'8
  }
}
```

Return none. Changed in version 2.0: renamed `leaftools.replace_leaves_with_skips_in()` to `skiptools.replace_leaves_in_expr_with_skips()`.

skiptools.yield_groups_of_skips_in_sequence

abjad.tools.skiptools.**yield_groups_of_skips_in_sequence** (*sequence*)

New in version 2.0. Yield groups of skips in *sequence*:

```
abjad> staff = Staff("c'8 d'8 s8 s8 <e' g'>8 <f' a'>8 g'8 a'8 s8 s8 <b' d''>8 <c'' e''>8")

abjad> f(staff)
\new Staff {
  c'8
  d'8
  s8
  s8
  <e' g'>8
  <f' a'>8
  g'8
  a'8
  s8
  s8
}
```

```

        <b' d''>8
        <c'' e''>8
    }

```

```

abjad> for skip in skiptools.yield_groups_of_skips_in_sequence(staff):
...     skip
...
(Skip('s8'), Skip('s8'))
(Skip('s8'), Skip('s8'))

```

Return generator.

spannertools

spannertools.BeamSpanner

class abjad.tools.spannertools.**BeamSpanner** (*components=None*)
 Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad beam spanner:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'2")

```

```

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
    g'2
}

```

```

abjad> spannertools.BeamSpanner(staff[:4])
BeamSpanner(c'8, d'8, e'8, f'8)

```

```

abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
    g'2
}

```

Return beam spanner.

spannertools.BracketSpanner

class abjad.tools.spannertools.**BracketSpanner** (*components=None*)
 Bases: abjad.tools.spannertools.TextSpanner.TextSpanner.TextSpanner

Abjad bracket spanner:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

```

```

abjad> spannertools.BracketSpanner(staff[:])
BracketSpanner(c'8, d'8, e'8, f'8)

```

```

abjad> f(staff)
\new Staff {
  \override TextSpanner #'bound-details #'left #'text = #(markup #:draw-line '(0 . -1))
  \override TextSpanner #'bound-details #'left-broken #'text = ##f
  \override TextSpanner #'bound-details #'right #'text = #(markup #:draw-line '(0 . -1))
  \override TextSpanner #'bound-details #'right-broken #'text = ##f
  \override TextSpanner #'color = #red
  \override TextSpanner #'dash-fraction = #1
  \override TextSpanner #'staff-padding = #2
  \override TextSpanner #'thickness = #1.5
  c'8 \startTextSpan
  d'8
  e'8
  f'8 \stopTextSpan
  \revert TextSpanner #'bound-details #'left #'text
  \revert TextSpanner #'bound-details #'left-broken #'text
  \revert TextSpanner #'bound-details #'right #'text
  \revert TextSpanner #'bound-details #'right-broken #'text
  \revert TextSpanner #'color
  \revert TextSpanner #'dash-fraction
  \revert TextSpanner #'staff-padding
  \revert TextSpanner #'thickness
}

```

Render 1.5-unit thick solid red spanner.

Draw nibs at beginning and end of spanner.

Do not draw nibs at line breaks.

Return bracket spanner.

spannertools.ComplexBeamSpanner

class abjad.tools.spannertools.**ComplexBeamSpanner** (*components=None, lone=False*)

Bases: abjad.tools.spannertools.BeamSpanner.BeamSpanner.BeamSpanner

Abjad complex beam spanner:

```

abjad> staff = Staff("c'16 e'16 r16 f'16 g'2")

abjad> f(staff)
\new Staff {
  c'16
  e'16
  r16
  f'16
  g'2
}

abjad> spannertools.ComplexBeamSpanner(staff[:4])
ComplexBeamSpanner(c'16, e'16, r16, f'16)

abjad> f(staff)
\new Staff {
  \set stemLeftBeamCount = #0
  \set stemRightBeamCount = #2
  c'16 [
  \set stemLeftBeamCount = #2

```

```

\set stemRightBeamCount = #2
e'16 ]
r16
\set stemLeftBeamCount = #2
\set stemRightBeamCount = #0
f'16 [ ]
g'2
}

```

Return complex beam spanner.

lone

Beam lone leaf and force beam nibs to left:

```

abjad> note = Note("c'16")

abjad> beam = spannertools.ComplexBeamSpanner([note], lone = 'left')

abjad> f(note)
\set stemLeftBeamCount = #2
\set stemRightBeamCount = #0
c'16 [ ]

```

Beam lone leaf and force beam nibs to right:

```

abjad> note = Note("c'16")

abjad> beam = spannertools.ComplexBeamSpanner([note], lone = 'right')

abjad> f(note)
\set stemLeftBeamCount = #0
\set stemRightBeamCount = #2
c'16 [ ]

```

Beam lone leaf and force beam nibs to both left and right:

```

abjad> note = Note("c'16")

abjad> beam = spannertools.ComplexBeamSpanner([note], lone = 'both')

abjad> f(note)
\set stemLeftBeamCount = #2
\set stemRightBeamCount = #2
c'16 [ ]

```

Beam lone leaf and accept LilyPond default nibs at both left and right:

```

abjad> note = Note("c'16")

abjad> beam = spannertools.ComplexBeamSpanner([note], lone = True)

abjad> f(note)
\set stemLeftBeamCount = #2
\set stemRightBeamCount = #2
c'16 [ ]

```

Do not beam lone leaf:


```

abjad> note = Note("c'16")

abjad> beam = spannertools.ComplexBeamSpanner([note], lone = False)

abjad> f(note)
c'16

```

Set to 'left', 'right', 'both', true or false as shown above.

Ignore this setting when spanner contains more than one leaf.

spannertools.CrescendoSpanner

class abjad.tools.spannertools.**CrescendoSpanner** (*components=None, include_rests=True*)
 Bases: abjad.tools.spannertools.HairpinSpanner.HairpinSpanner.HairpinSpanner

Abjad crescendo spanner that includes rests:

```

abjad> staff = Staff("r4 c'8 d'8 e'8 f'8 r4")

abjad> f(staff)
\new Staff {
  r4
  c'8
  d'8
  e'8
  f'8
  r4
}

abjad> spannertools.CrescendoSpanner(staff[:], include_rests = True)
CrescendoSpanner(r4, c'8, d'8, e'8, f'8, r4)

abjad> f(staff)
\new Staff {
  r4 \<
  c'8
  d'8
  e'8
  f'8
  r4 \!
}

```

Abjad crescendo spanner that does not include rests:

```

abjad> staff = Staff("r4 c'8 d'8 e'8 f'8 r4")

abjad> f(staff)
\new Staff {
  r4
  c'8
  d'8
  e'8
  f'8
  r4
}

```

```
abjad> spannertools.CrescendoSpanner(staff[:], include_rests = False)
CrescendoSpanner(r4, c'8, d'8, e'8, f'8, r4)
```

```
abjad> f(staff)
\new Staff {
    r4
    c'8 \<
    d'8
    e'8
    f'8 \!
    r4
}
```

Return crescendo spanner.

spannertools.DecrescendoSpanner

class abjad.tools.spannertools.**DecrescendoSpanner** (*components=None*, *include_rests=True*)

Bases: abjad.tools.spannertools.HairpinSpanner.HairpinSpanner.HairpinSpanner

Abjad decrescendo spanner that includes rests:

```
abjad> staff = Staff("r4 c'8 d'8 e'8 f'8 r4")
```

```
abjad> f(staff)
\new Staff {
    r4
    c'8
    d'8
    e'8
    f'8
    r4
}
```

```
abjad> spannertools.DecrescendoSpanner(staff[:], include_rests = True)
DecrescendoSpanner(r4, c'8, d'8, e'8, f'8, r4)
```

```
abjad> f(staff)
\new Staff {
    r4 \>
    c'8
    d'8
    e'8
    f'8
    r4 \!
```

Abjad decrescendo spanner that does not include rests:

```
abjad> staff = Staff("r4 c'8 d'8 e'8 f'8 r4")
```

```
abjad> f(staff)
\new Staff {
    r4
    c'8
    d'8
    e'8
```

```

        f'8
        r4
    }

abjad> spannertools.DecrescendoSpanner(staff[:], include_rests = False)
DecrescendoSpanner(r4, c'8, d'8, e'8, f'8, r4)

abjad> f(staff)
\new Staff {
    r4
    c'8 \>
    d'8
    e'8
    f'8 \!
    r4
}

```

Return decrescendo spanner.

spannertools.DuratedComplexBeamSpanner

```

class abjad.tools.spannertools.DuratedComplexBeamSpanner (components=None,
                                                           durations=None, span=1,
                                                           lone=False)

```

Bases: abjad.tools.spannertools.ComplexBeamSpanner.ComplexBeamSpanner.ComplexBeamSpanner

Abjad durated complex beam spanner:

```

staff = Staff("c'16 d'16 e'16 f'16")

durations = [Duration(1, 8), Duration(1, 8)]
beam = spannertools.DuratedComplexBeamSpanner(staff[:], durations, 1)

f(staff)
\new Staff {
    \set stemLeftBeamCount = #0
    \set stemRightBeamCount = #2
    c'16 [
    \set stemLeftBeamCount = #2
    \set stemRightBeamCount = #1
    d'16
    \set stemLeftBeamCount = #1
    \set stemRightBeamCount = #2
    e'16
    \set stemLeftBeamCount = #2
    \set stemRightBeamCount = #0
    f'16 ]
}

```

Beam all beamable leaves in spanner explicitly.

Group leaves in spanner according to *durations*.

Span leaves between duration groups according to *span*.

Return durated complex beam spanner.

durations

Get spanner leaf group durations:

```
abjad> staff = Staff("c'16 d'16 e'16 f'16")
abjad> durations = [Duration(1, 8), Duration(1, 8)]
abjad> beam = spannertools.DuratedComplexBeamSpanner(staff[:], durations)
abjad> beam.durations
[Duration(1, 8), Duration(1, 8)]
```

Set spanner leaf group durations:

```
abjad> staff = Staff("c'16 d'16 e'16 f'16")
abjad> durations = [Duration(1, 8), Duration(1, 8)]
abjad> beam = spannertools.DuratedComplexBeamSpanner(staff[:], durations)
abjad> beam.durations = [Duration(1, 4)]
abjad> beam.durations
[Duration(1, 4)]
```

Set iterable.

span

Get top-level beam count:

```
abjad> staff = Staff("c'16 d'16 e'16 f'16")
abjad> durations = [Duration(1, 8), Duration(1, 8)]
abjad> beam = spannertools.DuratedComplexBeamSpanner(staff[:], durations, 1)
abjad> beam.span
1
```

Set top-level beam count:

```
abjad> staff = Staff("c'16 d'16 e'16 f'16")
abjad> durations = [Duration(1, 8), Duration(1, 8)]
abjad> beam = spannertools.DuratedComplexBeamSpanner(staff[:], durations, 1)
abjad> beam.span = 2
abjad> beam.span
2
```

Set nonnegative integer.

spannertools.DynamicTextSpanner

class abjad.tools.spannertools.**DynamicTextSpanner** (*components=None, mark=''*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad dynamic text spanner:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> spannertools.DynamicTextSpanner(staff[:], 'f')
DynamicTextSpanner(c'8, d'8, e'8, f'8)

abjad> f(staff)
\new Staff {
    c'8 \f
    d'8
    e'8
    f'8
}
```

Format dynamic *mark* at first leaf in spanner.

Return dynamic text spanner.

mark

Get dynamic string:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> dynamic_text_spanner = spannertools.DynamicTextSpanner(staff[:], 'f')
abjad> dynamic_text_spanner.mark
'f'
```

Set dynamic string:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> dynamic_text_spanner = spannertools.DynamicTextSpanner(staff[:], 'f')
abjad> dynamic_text_spanner.mark = 'p'
abjad> dynamic_text_spanner.mark
'p'
```

Set string.

spannertools.GlissandoSpanner

class abjad.tools.spannertools.**GlissandoSpanner** (*components=None*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad glissando spanner:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> spannertools.GlissandoSpanner(staff[:])
GlissandoSpanner(c'8, d'8, e'8, f'8)

abjad> f(staff)
\new Staff {
    c'8 \glissando
    d'8 \glissando
    e'8 \glissando
    f'8
}
```

Format nonlast leaves in spanner with LilyPond glissando command.

Return glissando spanner.

spannertools.HairpinSpanner

class abjad.tools.spannertools.**HairpinSpanner** (*components=None*, *descriptor='<'*, *include_rests=True*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad hairpin spanner that includes rests:

```
abjad> staff = Staff("r4 c'8 d'8 e'8 f'8 r4")

abjad> f(staff)
\new Staff {
    r4
    c'8
    d'8
    e'8
```

```

        f'8
        r4
    }

abjad> spannertools.HairpinSpanner(staff[:], 'p < f', include_rests = True)
HairpinSpanner(r4, c'8, d'8, e'8, f'8, r4)

abjad> f(staff)
\new Staff {
    r4 \< \p
    c'8
    d'8
    e'8
    f'8
    r4 \f
}

```

Abjad hairpin spanner that does not include rests:

```

abjad> staff = Staff("r4 c'8 d'8 e'8 f'8 r4")

abjad> f(staff)
\new Staff {
    r4
    c'8
    d'8
    e'8
    f'8
    r4
}

abjad> spannertools.HairpinSpanner(staff[:], 'p < f', include_rests = False)
HairpinSpanner(r4, c'8, d'8, e'8, f'8, r4)

abjad> f(staff)
\new Staff {
    r4
    c'8 \< \p
    d'8
    e'8
    f'8 \f
    r4
}

```

Return hairpin spanner.

include_rests

Get boolean hairpin rests setting:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> hairpin = spannertools.HairpinSpanner(staff[:], 'p < f', include_rests = True)
abjad> hairpin.include_rests
True

```

Set boolean hairpin rests setting:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> hairpin = spannertools.HairpinSpanner(staff[:], 'p < f', include_rests = True)
abjad> hairpin.include_rests = False

```

```
abjad> hairpin.include_rests
False
```

Set boolean.

static is_hairpin_shape_string (*arg*)

True when *arg* is a hairpin shape string. Otherwise false:

```
abjad> spannertools.HairpinSpanner.is_hairpin_shape_string('<')
True
```

Return boolean.

shape_string

Get hairpin shape string:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> hairpin = spannertools.HairpinSpanner(staff[:], 'p < f')
abjad> hairpin.shape_string
'<'
```

Set hairpin shape string:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> hairpin = spannertools.HairpinSpanner(staff[:], 'p < f')
abjad> hairpin.shape_string = '>'
abjad> hairpin.shape_string
'>'
```

Set string.

start_dynamic_string

Get hairpin start dynamic string:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> hairpin = spannertools.HairpinSpanner(staff[:], 'p < f')
abjad> hairpin.start_dynamic_string
'p'
```

Set hairpin start dynamic string:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> hairpin = spannertools.HairpinSpanner(staff[:], 'p < f')
abjad> hairpin.start_dynamic_string = 'mf'
abjad> hairpin.start_dynamic_string
'mf'
```

Set string.

stop_dynamic_string

Get hairpin stop dynamic string:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> hairpin = spannertools.HairpinSpanner(staff[:], 'p < f')
abjad> hairpin.stop_dynamic_string
'f'
```

Set hairpin stop dynamic string:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> hairpin = spannertools.HairpinSpanner(staff[:], 'p < f')
abjad> hairpin.stop_dynamic_string = 'mf'
```

```
abjad> hairpin.stop_dynamic_string
'mf'
```

Set string.

spannertools.HiddenStaffSpanner

```
class abjad.tools.spannertools.HiddenStaffSpanner (components=None)
    Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner
```

Abjad hidden staff spanner:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> spannertools.HiddenStaffSpanner(staff[:2])
HiddenStaffSpanner(c'8, d'8)

abjad> f(staff)
\new Staff {
    \stopStaff
    c'8
    d'8
    \startStaff
    e'8
    f'8
}
```

Hide staff behind leaves in spanner.

Return hidden staff spanner.

spannertools.MeasuredComplexBeamSpanner

```
class abjad.tools.spannertools.MeasuredComplexBeamSpanner (components=None,
                                                             lone=False, span=1)
    Bases: abjad.tools.spannertools.ComplexBeamSpanner.ComplexBeamSpanner.ComplexBeamSpanner
```

Abjad measured complex beam spanner:

```
abjad> staff = Staff([Measure((2, 16), "c'16 d'16"), Measure((2, 16), "e'16 f'16")])

abjad> spannertools.MeasuredComplexBeamSpanner(staff.leaves)
MeasuredComplexBeamSpanner(c'16, d'16, e'16, f'16)

abjad> f(staff)
\new Staff {
    {
        \time 2/16
        \set stemLeftBeamCount = #0
        \set stemRightBeamCount = #2
        c'16 [
        \set stemLeftBeamCount = #2
        \set stemRightBeamCount = #1
        d'16
    }
    {
        \time 2/16
```



```

        \set stemLeftBeamCount = #1
        \set stemRightBeamCount = #2
        e'16
        \set stemLeftBeamCount = #2
        \set stemRightBeamCount = #0
        f'16 ]
    }
}

```

Beam leaves in spanner explicitly.

Group leaves by measures.

Format top-level *span* beam between measures.

Return measured complex beam spanner.

span

Get top-level beam count:

```

abjad> staff = Staff([Measure((2, 16), "c'16 d'16"), Measure((2, 16), "e'16 f'16")])
abjad> beam = spannertools.MeasuredComplexBeamSpanner(staff.leaves)
abjad> beam.span
1

```

Set top-level beam count:

```

abjad> staff = Staff([Measure((2, 16), "c'16 d'16"), Measure((2, 16), "e'16 f'16")])
abjad> beam = spannertools.MeasuredComplexBeamSpanner(staff.leaves)
abjad> beam.span = 2
abjad> beam.span
2

```

Set nonnegative integer.

spannertools.MetricGridSpanner

class abjad.tools.spannertools.**MetricGridSpanner** (*components=None, meters=None*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad metric grid spanner:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c'8")

abjad> spannertools.MetricGridSpanner(staff.leaves, meters = [(1, 8), (1, 4)])
MetricGridSpanner(c'8, d'8, e'8, f'8, g'8, a'8, b'8, c'8)

abjad> f(staff)
\new Staff {
  \time 1/8
  c'8
  \time 1/4
  d'8
  e'8
  \time 1/8
  f'8
  \time 1/4
  g'8
  a'8
  \time 1/8

```

```

    b'8
    \time 1/4
    c'8
}

```

Format leaves in spanner cyclically with *meters*.

Return metric grid spanner.

meters

Get metric grid meters:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c'8")
abjad> metric_grid_spanner = spannertools.MetricGridSpanner(staff.leaves, meters = [(1, 8),
abjad> list(metric_grid_spanner.meters)
[(TimeSignatureMark(1, 8), 0, False), (TimeSignatureMark(1, 4), Duration(1, 8), False), (Time

```

Set metric grid meters:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c'8")
abjad> metric_grid_spanner = spannertools.MetricGridSpanner(staff.leaves, meters = [(1, 8),
abjad> metric_grid_spanner.meters = [Duration(1, 4)]
abjad> list(metric_grid_spanner.meters)
[(TimeSignatureMark(1, 4), 0, False), (TimeSignatureMark(1, 4), Duration(1, 4), True), (Time

```

Set iterable.

split_on_bar()

Temporarily unavailable.

splitting_condition (*leaf*)

User-definable boolean function to determine whether leaf should be split:

```

abjad> voice = Voice("c'4 r4 c'4")

abjad> f(voice)
\new Voice {
    c'4
    r4
    c'4
}

abjad> def cond(leaf):
...     if not isinstance(leaf, Rest): return True
...     else: return False
abjad> metric_grid_spanner = spannertools.MetricGridSpanner(voice.leaves, [Duration(1, 8)])
abjad> metric_grid_spanner.splitting_condition = cond

abjad> metric_grid_spanner.split_on_bar()

abjad> f(voice)
\new Voice {
    \time 1/8
    c'8 ~
    c'8
    r4
    c'8 ~
    c'8
}

```

Function defaults to return true.

spannertools.MultipartBeamSpanner

class abjad.tools.spannertools.**MultipartBeamSpanner** (*components=None*)

Bases: abjad.tools.spannertools.BeamSpanner.BeamSpanner.BeamSpanner New in version 2.0. Abjad multipart beam spanner:

```
abjad> staff = Staff("c'8 d'8 e'4 f'8 g'8 r4")

abjad> spannertools.MultipartBeamSpanner(staff[:])
MultipartBeamSpanner(c'8, d'8, e'4, f'8, g'8, r4)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8 ]
    e'4
    f'8 [
    g'8 ]
    r4
}
```

Avoid rests.

Avoid large-duration notes.

Return multipart beam spanner.

spannertools.OctavationSpanner

class abjad.tools.spannertools.**OctavationSpanner** (*components=None, start=0, stop=0*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad octavation spanner:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> spanner = spannertools.OctavationSpanner(staff[:], start = 1)

abjad> f(staff)
\new Staff {
    \ottava #1
    c'8
    d'8
    e'8
    f'8
    \ottava #0
}
```

Return octavation spanner.

start

Get octavation start:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> octavation = spannertools.OctavationSpanner(staff[:], start = 1)
abjad> octavation.start
1
```

Set octavation start:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> octavation = spannertools.OctavationSpanner(staff[:], start = 1)
abjad> octavation.start
1
```

Set integer.

stop

Get octavation stop:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> octavation = spannertools.OctavationSpanner(staff[:], start = 2, stop = 1)
abjad> octavation.stop
1
```

Set octavation stop:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> octavation = spannertools.OctavationSpanner(staff[:], start = 2, stop = 1)
abjad> octavation.stop = 0
abjad> octavation.stop
0
```

Set integer.

spannertools.PhrasingSlurSpanner

class abjad.tools.spannertools.**PhrasingSlurSpanner** (*components=None*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad phrasing slur spanner:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> spannertools.PhrasingSlurSpanner(staff[:])
PhrasingSlurSpanner(c'8, d'8, e'8, f'8)

abjad> f(staff)
\new Staff {
  c'8 \{
  d'8
  e'8
  f'8 \}
}
```

Return phrasing slur spanner.

spannertools.PianoPedalSpanner

class abjad.tools.spannertools.**PianoPedalSpanner** (*components=None*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad piano pedal spanner:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> spannertools.PianoPedalSpanner(staff[:])
PianoPedalSpanner(c'8, d'8, e'8, f'8)
```

```

abjad> f(staff)
\new Staff {
  \set Staff.pedalSustainStyle = #'mixed
  c'8 \sustainOn
  d'8
  e'8
  f'8 \sustainOff
}

```

Return piano pedal spanner.

kind

Get piano pedal spanner kind:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.PianoPedalSpanner(staff[:])
abjad> spanner.kind
'sustain'

```

Set piano pedal spanner kind:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.PianoPedalSpanner(staff[:])
abjad> spanner.kind = 'sostenuto'
abjad> spanner.kind
'sostenuto'

```

Acceptable values 'sustain', 'sostenuto', 'corda'.

style

Get piano pedal spanner style:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.PianoPedalSpanner(staff[:])
abjad> spanner.style
'mixed'

```

Set piano pedal spanner style:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.PianoPedalSpanner(staff[:])
abjad> spanner.style = 'bracket'
abjad> spanner.style
'bracket'

```

Acceptable values 'mixed', 'bracket', 'text'.

spannertools.SlurSpanner

class abjad.tools.spannertools.**SlurSpanner** (*components=None*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad slur spanner:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> spannertools.SlurSpanner(staff[:])
SlurSpanner(c'8, d'8, e'8, f'8)

```

```
abjad> f(staff)
\new Staff {
    c'8 (
    d'8
    e'8
    f'8 )
}
```

Return slur spanner.

spannertools.Spanner

class abjad.tools.spannertools.**Spanner** (*components=None*)
 Bases: abjad.core._StrictComparator._StrictComparator._StrictComparator

Any type of notation object that stretches horizontally and encompasses some number of notes, rest, chords, tuplets, measures, voices or other Abjad components.

Beams, slurs, hairpins, trills, glissandi and piano pedal brackets all stretch horizontally on the page to encompass multiple notes and all implement as Abjad spanners. That is, these spanner all have an obvious graphic reality with definite start-, stop- and midpoints.

Abjad also implements a number of spanners of a different type, such as tempo and instrument spanners, which mark a group of notes, rests, chords or measures as carrying a certain tempo or being played by a certain instrument.

The spanner class described here abstracts the functionality that all such spanners, both graphic and nongraphic, share. This shared functionality includes methods to add, remove, inspect and test components governed by the spanner, as well as basic formatting properties. The other spanner classes, such as beam and glissando, all inherit from this class and receive the functionality implemented here.

append (*component*)

Add *component* to right of spanner.

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[:2])
abjad> spanner
Spanner(c'8, d'8)

abjad> spanner.append(voice[2])
abjad> spanner
Spanner(c'8, d'8, e'8)
```

Return none.

append_left (*component*)

Add *component* to left of spanner.

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[2:])
abjad> spanner
Spanner(e'8, f'8)

abjad> spanner.append_left(voice[1])
abjad> spanner
Spanner(d'8, e'8, f'8)
```

Return none.

clear()

Remove all components from spanner:

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[:])
abjad> spanner
Spanner(c'8, d'8, e'8, f'8)

abjad> spanner.clear()
abjad> spanner
Spanner()
```

Return none.

components

Return read-only tuple of components in spanner.

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[:2])
abjad> spanner.components
(Note("c'8"), Note("d'8"))
```

Changed in version 1.1: Now returns an (immutable) tuple instead of a (mutable) list.

duration_in_seconds

Sum of duration of all leaves in spanner, in seconds.

extend(components)

Add iterable *components* to right of spanner:

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[:2])
abjad> spanner
Spanner(c'8, d'8)

abjad> spanner.extend(voice[2:])
abjad> spanner
Spanner(c'8, d'8, e'8, f'8)
```

Return none.

extend_left(components)

Add iterable *components* to left of spanner:

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[2:])
abjad> spanner
Spanner(e'8, f'8)

abjad> spanner.extend_left(voice[:2])
abjad> spanner
Spanner(c'8, d'8, e'8, f'8)
```

Return none.

fracture(i, direction='both')

Fracture spanner at *direction* of component at index *i*.

Valid values for *direction* are 'left', 'right' and 'both'.

Return original, left and right spanners.

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(voice[:])
abjad> beam
BeamSpanner(c'8, d'8, e'8, f'8)

abjad> beam.fracture(1, direction = 'left')
(BeamSpanner(c'8, d'8, e'8, f'8), BeamSpanner(c'8), BeamSpanner(d'8, e'8, f'8))

abjad> print voice.format
\new Voice {
  c'8 [ ]
  d'8 [
  e'8
  f'8 ]
}
```

Return tuple.

fuse (*spanner*)

Fuse contiguous spanners.

Return new spanner.

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> left_beam = spannertools.BeamSpanner(voice[:2])
abjad> right_beam = spannertools.BeamSpanner(voice[2:])

abjad> print voice.format
\new Voice {
  c'8 [
  d'8 ]
  e'8 [
  f'8 ]
}

abjad> left_beam.fuse(right_beam)
[(BeamSpanner(c'8, d'8), BeamSpanner(e'8, f'8), BeamSpanner(c'8, d'8, e'8, f'8))]
```

```
abjad> print voice.format
\new Voice {
  c'8 [
  d'8
  e'8
  f'8 ]
}
```

Todo

Return (immutable) tuple instead of (mutable) list.

index (*component*)

Return nonnegative integer index of *component* in spanner.

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[2:])
abjad> spanner
Spanner(e'8, f'8)
```



```
abjad> spanner.index(voice[-2])
0
```

Return nonnegative integer.

leaves

Return read-only tuple of leaves in spanner.

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[:2])
abjad> spanner.leaves
(Note("c'8"), Note("d'8"))
```

Changed in version 1.1: Now returns an (immutable) tuple instead of a (mutable) list.

Note: When dealing with large, complex scores accessing this attribute can take some time. Best to make a local copy with `leaves = spanner.leaves` first. Or use spanner- specific iteration tools.

offset

New in version 1.1. Return read-only reference to spanner offset interface.

Spanner offset interface implements `start` and `stop` attributes.

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[2:])
abjad> spanner
Spanner(e'8, f'8)
```

```
abjad> spanner._offset.start
Offset(1, 4)
```

```
abjad> spanner._offset.stop
Offset(1, 2)
```

Return duration.

override

LilyPond grob override component plug-in.

pop()

Remove and return rightmost component in spanner.

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[:])
abjad> spanner
Spanner(c'8, d'8, e'8, f'8)
```

```
abjad> spanner.pop()
Note("f'8")
```

```
abjad> spanner
Spanner(c'8, d'8, e'8)
```

Return component.

pop_left()

Remove and return leftmost component in spanner.

```

abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.Spanner(voice[:])
abjad> spanner
Spanner(c'8, d'8, e'8, f'8)

abjad> spanner.pop_left()
Note("c'8")

abjad> spanner
Spanner(d'8, e'8, f'8)

```

Return component.

preprolated_duration

Sum of preprolated duration of all components in spanner.

prolated_duration

Sum of prolated duration of all components in spanner.

set

LilyPond context setting component plug-in.

written_duration

Sum of written duration of all components in spanner.

spannertools.StaffLinesSpanner

class abjad.tools.spannertools.**StaffLinesSpanner** (*components=None, arg=5*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad staff lines spanner:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> spannertools.StaffLinesSpanner(staff[:2], 1)
StaffLinesSpanner(c'8, d'8)

abjad> f(staff)
\new Staff {
  \stopStaff
  \override Staff.StaffSymbol #'line-count = #1
  \startStaff
  c'8
  d'8
  \stopStaff
  \revert Staff.StaffSymbol #'line-count
  \startStaff
  e'8
  f'8
}

```

Staff lines spanner handles changing either the line-count or the line-positions property of the StaffSymbol grob, as well as automatically stopping and restarting the staff so that the change may take place.

Return staff lines spanner.

lines

Get staff lines spanner line count:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.StaffLinesSpanner(staff[:2], 1)
abjad> spanner.lines
1

```

Set staff lines spanner line count:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> spanner = spannertools.StaffLinesSpanner(staff[:2], 1)
abjad> spanner.lines = 2
abjad> spanner.lines
2

```

Set integer.

spannertools.TextScriptSpanner

class abjad.tools.spannertools.**TextScriptSpanner** (*components=None*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner New in version 2.0. Abjad text script spanner:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> spanner = spannertools.TextScriptSpanner(staff[:])
abjad> spanner.override.text_script.color = 'red'
abjad> markuptools.Markup(r'\italic { espressivo }', 'up')(staff[1])
Markup('\italic { espressivo }', 'up')

abjad> f(staff)
\new Staff {
  \override TextScript #'color = #red
  c'8
  d'8 ^ \markup { \italic { espressivo } }
  e'8
  f'8
  \revert TextScript #'color
}

```

Override LilyPond TextScript grob.

Return text script spanner.

spannertools.TextSpanner

class abjad.tools.spannertools.**TextSpanner** (*components=None*)

Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner New in version 2.0. Abjad text spanner:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> text_spanner = spannertools.TextSpanner(staff[:])

abjad> markup = markuptools.Markup('(markup #:bold #:italic "foo")', style_string = 'scheme')
abjad> text_spanner.override.text_spanner.bound_details__left__text = markup
abjad> markup = markuptools.Markup("(markup #:draw-line '(0 . -1))", style_string = 'scheme')
abjad> text_spanner.override.text_spanner.bound_details__right__text = markup
abjad> text_spanner.override.text_spanner.dash_fraction = 1

```

```

abjad> f(staff)
\new Staff {
  \override TextSpanner #'bound-details #'left #'text = #(markup #:bold #:italic "foo")
  \override TextSpanner #'bound-details #'right #'text = #(markup #:draw-line '(0 . -1))
  \override TextSpanner #'dash-fraction = #1
  c'8 \startTextSpan
  d'8
  e'8
  f'8 \stopTextSpan
  \revert TextSpanner #'bound-details #'left #'text
  \revert TextSpanner #'bound-details #'right #'text
  \revert TextSpanner #'dash-fraction
}

```

Override LilyPond TextSpanner grob.

Return text spanner.

spannertools.TrillSpanner

class abjad.tools.spannertools.**TrillSpanner**(*components=None*)
Bases: abjad.tools.spannertools.Spanner.Spanner.Spanner

Abjad trill spanner:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> spannertools.TrillSpanner(staff[:])
TrillSpanner(c'8, d'8, e'8, f'8)

abjad> f(staff)
\new Staff {
  c'8 \startTrillSpan
  d'8
  e'8
  f'8 \stopTrillSpan
}

```

Override LilyPond TrillSpanner grob.

Return trill spanner.

pitch

Optional read / write pitch for pitched trills.

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> trill = spannertools.TrillSpanner(t[:2])
abjad> trill.pitch = pitchtools.NamedChromaticPitch('cs', 4)

abjad> f(t)
\new Staff {
  \pitchedTrill c'8 \startTrillSpan cs'
  d'8 \stopTrillSpan
  e'8
  f'8
}

```

Set pitch.

written_pitch

spannertools.destroy_all_spanners_attached_to_component

`abjad.tools.spannertools.destroy_all_spanners_attached_to_component` (*component*,
klass=None)

New in version 1.1. Destroy all spanners attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> trill = spannertools.TrillSpanner(staff)
abjad> f(staff)
\new Staff {
    c'8 [ ( \startTrillSpan
    d'8
    e'8
    f'8 ] ) \stopTrillSpan
}

abjad> spannertools.destroy_all_spanners_attached_to_component(staff[0])
abjad> f(staff)
\new Staff {
    c'8 \startTrillSpan
    d'8
    e'8
    f'8 \stopTrillSpan
}
```

Return none.

spannertools.find_index_of_spanner_component_at_score_offset

`abjad.tools.spannertools.find_index_of_spanner_component_at_score_offset` (*spanner*,
score_offset)

Return index of component in ‘spanner’ that begins at exactly ‘score_offset’:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)

abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}

abjad> spannertools.find_index_of_spanner_component_at_score_offset(beam, Duration(3, 8))
3
```

Raise spanner population error when no component in *spanner* begins at exactly *score_offset*.
Changed in version 2.0: renamed `spannertools.find_index_at_score_offset()` to
`spannertools.find_index_of_spanner_component_at_score_offset()`.

spannertools.find_spanner_component_starting_at_exactly_score_offset

`abjad.tools.spannertools.find_spanner_component_starting_at_exactly_score_offset` (*spanner*, *score_offset*)

Find *spanner* component starting at exactly *score_offset*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
```

```
abjad> f(staff)
\new Staff {
  c'8 [
  d'8
  e'8
  f'8 ]
}
```

```
abjad> spannertools.find_spanner_component_starting_at_exactly_score_offset(beam, Duration(3, 8))
Note("f'8")
```

When no *spanner* component starts at exactly *score_offset* return none.

Return *spanner* component or none. Changed in version 2.0: re-named `spannertools.find_component_at_score_offset()` to `spannertools.find_spanner_component_starting_at_exactly_score_offset()`.

spannertools.fracture_all_spanners_attached_to_component

`abjad.tools.spannertools.fracture_all_spanners_attached_to_component` (*component*, *direction*=*'both'*, *klass*=None)

New in version 1.1. Fracture all spanners attached to *component* according to *direction*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> trill = spannertools.TrillSpanner(staff)
abjad> f(staff)
```

```
\new Staff {
  c'8 [ ( \startTrillSpan
  d'8
  e'8
  f'8 ] ) \stopTrillSpan
}
```

```
abjad> spannertools.fracture_all_spanners_attached_to_component(staff[1], 'right')
[(BeamSpanner(c'8, d'8, e'8, f'8), BeamSpanner(c'8, d'8), BeamSpanner(e'8, f'8)), (SlurSpanner(c'8, d'8, e'8, f'8))]
abjad> f(staff)
\new Staff {
  c'8 [ ( \startTrillSpan
  d'8 ] )
  e'8 [ (
  f'8 ] ) \stopTrillSpan
}
```

Set *direction* to left, right or both.

spannertools.fracture_spanners_that_cross_components

abjad.tools.spannertools.**fracture_spanners_that_cross_components** (*components*)

Fracture to the left of the leftmost component. Fracture to the right of the rightmost component. Do not fracture spanners of any components at higher levels of score. Do not fracture spanners of any components at lower levels of score. Return components.

Components must be thread-contiguous. Some spanners may copy during fracture. This helper is public-safe.

Example:

```
t = Staff(Container(notetools.make_repeated_notes(2)) * 3)
pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
spannertools.CrescendoSpanner(t)
spannertools.BeamSpanner(t[:])
spannertools.TrillSpanner(t.leaves)
```

```
\new Staff {
  {
    c'8 [ \< \startTrillSpan
    d'8
  }
  {
    e'8
    f'8
  }
  {
    g'8
    a'8 ] \! \stopTrillSpan
  }
}
```

```
spannertools.fracture_spanners_that_cross_components(t[1:2])
```

```
\new Staff {
  {
    c'8 [ \< \startTrillSpan
    d'8 ]
  }
  {
    e'8 [
    f'8 ]
  }
  {
    g'8 [
    a'8 ] \! \stopTrillSpan
  }
}
```

Changed in version 2.0: renamed `spannertools.fracture_crossing()` to `spannertools.fracture_spanners_that_cross_components()`.

spannertools.get_beam_spanner_attached_to_component

abjad.tools.spannertools.**get_beam_spanner_attached_to_component** (*component*)

New in version 2.0. Get the only beam spanner attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
```

```

abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}

abjad> spannertools.get_beam_spanner_attached_to_component(staff[0])
BeamSpanner(c'8, d'8, e'8, f'8)

abjad> _ is beam
True

```

Return beam spanner.

Raise missing spanner error when no beam spanner attached to *component*.

Raise extra spanner error when more than one beam spanner attached to *component*. Changed in version 2.0: renamed `beamtools.get_beam_spanner()` to `spannertools.get_beam_spanner_attached_to_component()`. Changed in version 2.0: renamed `beamtools.get_beam_spanner_attached_to_component()` to `spannertools.get_beam_spanner_attached_to_component()`.

`spannertools.get_nth_leaf_in_spanner`

`abjad.tools.spannertools.get_nth_leaf_in_spanner(spanner, idx)`
 Get nth leaf in spanner, no matter how complicated the nesting situation. Changed in version 2.0: renamed `spannertools.get_nth_leaf()` to `spannertools.get_nth_leaf_in_spanner()`.

`spannertools.get_spanners_attached_to_any_improper_child_of_component`

`abjad.tools.spannertools.get_spanners_attached_to_any_improper_child_of_component(component, klass=None)`

New in version 2.0. Get all spanners attached to any improper children of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> first_slur = spannertools.SlurSpanner(staff.leaves[:2])
abjad> second_slur = spannertools.SlurSpanner(staff.leaves[2:])
abjad> trill = spannertools.TrillSpanner(staff)

abjad> f(staff)
\new Staff {
    c'8 [ ( \startTrillSpan
    d'8 )
    e'8 (
    f'8 ] ) \stopTrillSpan
}

abjad> len(spannertools.get_spanners_attached_to_any_improper_child_of_component(staff)) == 4
True

```

Get all spanners of *klass* attached to any proper children of *component*:


```
abjad> spanner_klass = spannertools.SlurSpanner
abjad> spannertools.get_spanners_attached_to_any_proper_child_of_component(staff, spanner_klass)
set([SlurSpanner(c'8, d'8), SlurSpanner(e'8, f'8)])
```

Get all spanners of any *klass* attached to any proper children of *component*:

```
abjad> spanner_klasses = (spannertools.SlurSpanner, spannertools.BeamSpanner)
abjad> spannertools.get_spanners_attached_to_any_proper_child_of_component(staff, spanner_klasses)
set([BeamSpanner(c'8, d'8, e'8, f'8), SlurSpanner(c'8, d'8), SlurSpanner(e'8, f'8)])
```

Return unordered set of zero or more spanners. Changed in version 2.0: renamed `spannertools.get_all_spanners_attached_to_any_improper_children_of_component()` to `spannertools.get_spanners_attached_to_any_improper_child_of_component()`.

spannertools.get_spanners_attached_to_any_improper_parent_of_component

`abjad.tools.spannertools.get_spanners_attached_to_any_improper_parent_of_component` (*component*, *klass=None*)

New in version 1.1. Get all spanners attached to improper parentage of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> trill = spannertools.TrillSpanner(staff)
abjad> f(staff)
\new Staff {
  c'8 [ ( \startTrillSpan
  d'8
  e'8
  f'8 ] ) \stopTrillSpan
}

abjad> spannertools.get_spanners_attached_to_any_improper_parent_of_component(staff[0]) # doctest
set([BeamSpanner(c'8, d'8, e'8, f'8), SlurSpanner(c'8, d'8, e'8, f'8), TrillSpanner({c'8, d'8, e'8, f'8})])
```

Return unordered set of zero or more spanners. Changed in version 2.0: renamed `spannertools.get_all_spanners_attached_to_improper_parentage_of_component()` to `spannertools.get_spanners_attached_to_any_improper_parent_of_component()`.

spannertools.get_spanners_attached_to_any_proper_child_of_component

`abjad.tools.spannertools.get_spanners_attached_to_any_proper_child_of_component` (*component*, *klass=None*)

New in version 2.0. Get all spanners attached to any proper children of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> first_slur = spannertools.SlurSpanner(staff.leaves[:2])
abjad> second_slur = spannertools.SlurSpanner(staff.leaves[2:])
abjad> trill = spannertools.TrillSpanner(staff)

abjad> f(staff)
\new Staff {
  c'8 [ ( \startTrillSpan
  d'8 )
  e'8 (
```

```
f'8 ] ) \stopTrillSpan
}
```

```
abjad> len(spannertools.get_spanners_attached_to_any_proper_child_of_component(staff)) == 3
True
```

Get all spanners of *klass* attached to any proper children of *component*:

```
abjad> spanner_klass = spannertools.SlurSpanner
abjad> spannertools.get_spanners_attached_to_any_proper_child_of_component(staff, spanner_klass)
set([SlurSpanner(c'8, d'8), SlurSpanner(e'8, f'8)])
```

Get all spanners of any *klass* attached to any proper children of *component*:

```
abjad> spanner_klasses = (spannertools.SlurSpanner, spannertools.BeamSpanner)
abjad> spannertools.get_spanners_attached_to_any_proper_child_of_component(staff, spanner_klasses)
set([BeamSpanner(c'8, d'8, e'8, f'8), SlurSpanner(c'8, d'8), SlurSpanner(e'8, f'8)])
```

Return unordered set of zero or more spanners. Changed in version 2.0: renamed `spannertools.get_all_spanners_attached_to_any_proper_children_of_component()` to `spannertools.get_spanners_attached_to_any_proper_child_of_component()`.

spannertools.get_spanners_attached_to_any_proper_parent_of_component

`abjad.tools.spannertools.get_spanners_attached_to_any_proper_parent_of_component` (*component*, *klass=None*)

New in version 2.0. Get all spanners attached to any proper parent of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> trill = spannertools.TrillSpanner(staff)
abjad> f(staff)
\new Staff {
    c'8 [ ( \startTrillSpan
    d'8
    e'8
    f'8 ] ) \stopTrillSpan
}
```

```
abjad> spannertools.get_spanners_attached_to_any_proper_parent_of_component(staff[0])
set([TrillSpanner({c'8, d'8, e'8, f'8})])
```

Return unordered set of zero or more spanners. Changed in version 2.0: renamed `spannertools.get_all_spanners_attached_to_any_proper_parent_of_component()` to `spannertools.get_spanners_attached_to_any_proper_parent_of_component()`.

spannertools.get_spanners_attached_to_component

`abjad.tools.spannertools.get_spanners_attached_to_component` (*component*, *klass=None*)

New in version 2.0. Get all spanners attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> first_slur = spannertools.SlurSpanner(staff.leaves[:2])
```

```
abjad> second_slur = spannertools.SlurSpanner(staff.leaves[2:])
abjad> crescendo = spannertools.CrescendoSpanner(staff.leaves
```

```
abjad> f(staff)
\new Staff {
  c'8 [ \< (
  d'8 )
  e'8 (
  f'8 ] \! )
}
```

```
abjad> spannertools.get_spanners_attached_to_component(staff.leaves[0]) # doctest: +SKIP
set([BeamSpanner(c'8, d'8, e'8, f'8), SlurSpanner(c'8, d'8), CrescendoSpanner(c'8, d'8, e'8, f'8)
```

Get spanners of *klass* attached to *component*:

```
abjad> klass = spannertools.BeamSpanner
abjad> spannertools.get_spanners_attached_to_component(staff.leaves[0], klass) # doctest: +SKIP
set([BeamSpanner(c'8, d'8, e'8, f'8)])
```

Get spanners of any *klass* attached to *component*:

```
abjad> classes = (spannertools.BeamSpanner, spannertools.SlurSpanner)
abjad> spannertools.get_spanners_attached_to_component(staff.leaves[0], classes) # doctest: +SKI
set([BeamSpanner(c'8, d'8, e'8, f'8), SlurSpanner(c'8, d'8)])
```

Return unordered set of zero or more spanners. Changed in version 2.0: re-named `spannertools.get_all_spanners_attached_to_component()` to `spannertools.get_spanners_attached_to_component()`.

spannertools.get_spanners_contained_by_components

`abjad.tools.spannertools.get_spanners_contained_by_components(components)`

Return unordered set of spanners contained within any component in list of thread-contiguous components. Getter for `t.spanners.contained` across thread-contiguous components.

Changed in version 2.0: renamed `spannertools.get_contained()` to `spannertools.get_spanners_contained_by_components()`.

spannertools.get_spanners_covered_by_components

`abjad.tools.spannertools.get_spanners_covered_by_components(components)`

Return unordered set of spanners completely contained within the time bounds of thread-contiguous components.

Compare ‘covered’ spanners with ‘contained’ spanners. Compare ‘covered’ spanners with ‘dominant’ spanners.

Changed in version 2.0: renamed `spannertools.get_covered()` to `spannertools.get_spanners_covered_by_components()`.

spannertools.get_spanners_on_components_or_component_children

`abjad.tools.spannertools.get_spanners_on_components_or_component_children(components)`

Return unordered set of all spanners attaching to any component in *compo-*

nents or attaching to any of the children of any of the components in *components*. Changed in version 2.0: renamed `spannertools.get_attached()` to `spannertools.get_spanners_on_components_or_component_children()`.

`spannertools.get_spanners_that_cross_components`

`abjad.tools.spannertools.get_spanners_that_cross_components(components)`

Assert thread-contiguous components. Collect spanners that attach to any component in ‘components’. Return unordered set of crossing spanners. A spanner P crosses a list of thread-contiguous components C when P and C share at least one component and when it is the case that NOT ALL of the components in P are also in C. In other words, there is some intersection – but not total intersection – between the components of P and C.

Compare ‘crossing’ spanners with ‘covered’ spanners. Compare ‘crossing’ spanners with ‘dominant’ spanners. Compare ‘crossing’ spanners with ‘contained’ spanners. Compare ‘crossing’ spanners with ‘attached’ spanners. Changed in version 2.0: renamed `spannertools.get_crossing()` to `spannertools.get_spanners_that_cross_components()`.

`spannertools.get_spanners_that_dominate_component_pair`

`abjad.tools.spannertools.get_spanners_that_dominate_component_pair(left, right)`

Return Python list of (spanner, index) pairs. ‘left’ must be either an Abjad component or None. ‘right’ must be either an Abjad component or None.

If both ‘left’ and ‘right’ are components, then ‘left’ and ‘right’ must be thread-contiguous.

This is a special version of `spannertools.get_spanners_that_dominate_components()`. This version is useful for finding spanners that dominate a zero-length ‘crack’ between components, as in `t[2:2]`. Changed in version 2.0: renamed `spannertools.get_dominant_between()` to `spannertools.get_spanners_that_dominate_component_pair()`.

`spannertools.get_spanners_that_dominate_components`

`abjad.tools.spannertools.get_spanners_that_dominate_components(components)`

Return Python list of (spanner, index) pairs. Each (spanner, index) pair gives a spanner which dominates all components in ‘components’ together with the start-index at which spanner first encounters ‘components’.

Use this helper to ‘lift’ any and all spanners temporarily from ‘components’, perform some action to the underlying score tree, and then reattach all spanners to new score components.

This operation always leaves all expressions in tact. Changed in version 2.0: renamed `spannertools.get_dominant()` to `spannertools.get_spanners_that_dominate_components()`.

`spannertools.get_spanners_that_dominate_container_components_from_to`

`abjad.tools.spannertools.get_spanners_that_dominate_container_components_from_to(container, start, stop)`

Return Python list of (spanner, index) pairs. Each spanner dominates the components specified by slice with start index ‘start’ and stop index ‘stop’. Generalization of dominant spanner-finding functions for slices. This exists for slices like `t[2:2]` that are empty lists.

Changed in version 2.0: renamed `spannertools.get_dominant_slice()` to `spannertools.get_spanners_that_dominate_container_components_from_to()`.

`spannertools.get_the_only_spanner_attached_to_any_improper_parent_of_component`

`abjad.tools.spannertools.get_the_only_spanner_attached_to_any_improper_parent_of_component`

New in version 1.1. Get the only spanner attached to any improper parent *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> trill = spannertools.TrillSpanner(staff)
abjad> f(staff)
\new Staff {
    c'8 [ ( \startTrillSpan
    d'8
    e'8
    f'8 ] ) \stopTrillSpan
}

abjad> print spannertools.get_the_only_spanner_attached_to_component(staff)
TrillSpanner({c'8, d'8, e'8, f'8})

```

Raise missing spanner error when no spanner attached to *component*.

Raise extra spanner error when more than one spanner attached to *component*.

Return a single spanner.

Note: function will usually be called with *klass* specifier set.

`spannertools.get_the_only_spanner_attached_to_component`

`abjad.tools.spannertools.get_the_only_spanner_attached_to_component` (*component*,
klass=None)

New in version 1.1. Get the only spanner attached to *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> trill = spannertools.TrillSpanner(staff)
abjad> f(staff)
\new Staff {
    c'8 [ ( \startTrillSpan
    d'8
    e'8
    f'8 ] ) \stopTrillSpan
}

abjad> print spannertools.get_the_only_spanner_attached_to_component(staff)
TrillSpanner({c'8, d'8, e'8, f'8})

```

Raise missing spanner error when no spanner attached to *component*.

Raise extra spanner error when more than one spanner attached to *component*.

Return a single spanner.

Note: function will usually be called with *klass* specifier set.

`spannertools.is_component_with_beam_spanner_attached`

`abjad.tools.spannertools.is_component_with_beam_spanner_attached(expr)`

New in version 2.0. True when *expr* is component with beam spanner attached:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)

abjad> spannertools.is_component_with_beam_spanner_attached(staff[0])
True
```

Otherwise false:

```
abjad> note = Note("c'8")

abjad> spannertools.is_component_with_beam_spanner_attached(note)
False
```

Return boolean. Changed in version 2.0: renamed `beamtools.is_component_with_beam_spanner_attached()` to `spannertools.is_component_with_beam_spanner_attached()`.

`spannertools.is_component_with_spanner_attached`

`abjad.tools.spannertools.is_component_with_spanner_attached(expr, klass=None)`

New in version 2.0. True when *expr* is a component with spanner attached:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> f(staff)
\new Staff {
    c'8 [
    d'8
    e'8
    f'8 ]
}

abjad> spannertools.is_component_with_spanner_attached(staff[0])
True
```

Otherwise false:

```
abjad> spannertools.is_component_with_spanner_attached(staff)
False
```

When *klass* is not none then true when *expr* is a component with a spanner of *klass* attached.

Return true or false.

`spannertools.iterate_components_backward_in_spanner`

`abjad.tools.spannertools.iterate_components_backward_in_spanner(spanner, klass=<class 'abjad.tools.componenttools._Component...>)`

New in version 2.0. Yield components in *spanner* one at a time from left to right.

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> p = spannertools.BeamSpanner(t[2:])
abjad> notes = spannertools.iterate_components_backward_in_spanner(p, klass = Note)
abjad> for note in notes:
...     note
Note("f'8")
Note("e'8")

```

Changed in version 2.0: renamed `spannertools.iterate_components_backward()` to `spannertools.iterate_components_backward_in_spanner()`.

spannertools.iterate_components_forward_in_spanner

`abjad.tools.spannertools.iterate_components_forward_in_spanner` (*spanner*,
klass=<class
'ab-
jad.tools.componenttools._Component._C

New in version 2.0. Yield components in *spanner* one at a time from left to right.

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> p = spannertools.BeamSpanner(t[2:])
abjad> notes = spannertools.iterate_components_forward_in_spanner(p, klass = Note)
abjad> for note in notes:
...     note
Note("e'8")
Note("f'8")

```

Changed in version 2.0: renamed `spannertools.iterate_components_forward()` to `spannertools.iterate_components_forward_in_spanner()`.

spannertools.make_covered_spanner_schema

`abjad.tools.spannertools.make_covered_spanner_schema` (*components*)

New in version 2.0. Make schema of spanners covered by *components*:

```

abjad> voice = Voice(Measure((2, 8), notetools.make_repeated_notes(2)) * 4)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voice)
abjad> beam = spannertools.BeamSpanner(voice.leaves[:4])
abjad> slur = spannertools.SlurSpanner(voice[-2:])

```

```

abjad> f(voice)
\new Voice {
  {
    \time 2/8
    c'8 [
    d'8
  ]
  {
    \time 2/8
    e'8
    f'8 ]
  }
  {
    \time 2/8
    g'8 (
    a'8
  ]
}

```

```

    }
    {
        \time 2/8
        b'8
        c''8 )
    }
}

abjad> spannertools.make_covered_spanner_schema([voice]) # doctest: +SKIP
{BeamSpanner(c'8, d'8, e'8, f'8): [2, 3, 5, 6], SlurSpanner(|2/8(2)|, |2/8(2)|): [7, 10]}

```

Return dictionary.

spannertools.make_dynamic_spanner_below_with_nib_at_right

abjad.tools.spannertools.**make_dynamic_spanner_below_with_nib_at_right** (*dynamic_text*,
com-
po-
nents=None)

New in version 2.0. Span *components* with text spanner. Position spanner below staff and configure with *dynamic_text*, solid line and upward-pointing nib at right.

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.make_dynamic_spanner_below_with_nib_at_right('mp', t[:])
TextSpanner(c'8, d'8, e'8, f'8)
abjad> f(t)
\new Staff {
    \override TextSpanner #'bound-details #'left #'text = \markup { \dynamic { mp } }
    \override TextSpanner #'bound-details #'right #'text = #(markup #:draw-line ' (0 . 1))
    \override TextSpanner #'bound-details #'right-broken #'text = ##f
    \override TextSpanner #'dash-fraction = #1
    \override TextSpanner #'direction = #down
    c'8 \startTextSpan
    d'8
    e'8
    f'8 \stopTextSpan
    \revert TextSpanner #'bound-details #'left #'text
    \revert TextSpanner #'bound-details #'right #'text
    \revert TextSpanner #'bound-details #'right-broken #'text
    \revert TextSpanner #'dash-fraction
    \revert TextSpanner #'direction
}

```

Changed in version 2.0: renamed `spanners.dynamic_spanner_below_with_nib_at_right()` to `spannertools.make_dynamic_spanner_below_with_nib_at_right()`.

spannertools.make_solid_text_spanner_above_with_nib_at_right

abjad.tools.spannertools.**make_solid_text_spanner_above_with_nib_at_right** (*left_text*,
com-
po-
nents=None)

New in version 2.0. Span *components* with text spanner. Position spanner above staff and configure with *left_text*, solid line and downward-pointing nib at right.


```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.make_solid_text_spanner_above_with_nib_at_right('foo', t[:])
TextSpanner(c'8, d'8, e'8, f'8)
abjad> f(t)
\new Staff {
  \override TextSpanner #'bound-details #'left #'text = \markup { foo }
  \override TextSpanner #'bound-details #'right #'text = #(markup #:draw-line '(0 . -1))
  \override TextSpanner #'bound-details #'right-broken #'text = ##f
  \override TextSpanner #'dash-fraction = #1
  \override TextSpanner #'direction = #up
  c'8 \startTextSpan
  d'8
  e'8
  f'8 \stopTextSpan
  \revert TextSpanner #'bound-details #'left #'text
  \revert TextSpanner #'bound-details #'right #'text
  \revert TextSpanner #'bound-details #'right-broken #'text
  \revert TextSpanner #'dash-fraction
  \revert TextSpanner #'direction
}

```

Changed in version 2.0: renamed `spanners.solid_text_spanner_above_with_nib_at_right()` to `spannertools.make_solid_text_spanner_above_with_nib_at_right()`.

`spannertools.make_solid_text_spanner_below_with_nib_at_right`

`abjad.tools.spannertools.make_solid_text_spanner_below_with_nib_at_right` (*left_text*, *components=None*)

New in version 2.0. Span *components* with text spanner. Position spanner below staff and configure with *left_text*, solid line and upward-pointing nib at right.

```

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> spannertools.make_solid_text_spanner_below_with_nib_at_right('foo', t[:])
TextSpanner(c'8, d'8, e'8, f'8)
abjad> f(t)
\new Staff {
  \override TextSpanner #'bound-details #'left #'text = \markup { foo }
  \override TextSpanner #'bound-details #'right #'text = #(markup #:draw-line '(0 . 1))
  \override TextSpanner #'bound-details #'right-broken #'text = ##f
  \override TextSpanner #'dash-fraction = #1
  \override TextSpanner #'direction = #down
  c'8 \startTextSpan
  d'8
  e'8
  f'8 \stopTextSpan
  \revert TextSpanner #'bound-details #'left #'text
  \revert TextSpanner #'bound-details #'right #'text
  \revert TextSpanner #'bound-details #'right-broken #'text
  \revert TextSpanner #'dash-fraction
  \revert TextSpanner #'direction
}

```

Changed in version 2.0: renamed `spanners.solid_text_spanner_below_with_nib_at_right()` to `spannertools.make_solid_text_spanner_below_with_nib_at_right()`.

spannertools.make_spanner_schema

abjad.tools.spannertools.**make_spanner_schema** (*components*)

New in version 2.0. Make schema of spanners contained by *components*:

```
abjad> voice = Voice(Measure((2, 8), notetools.make_repeated_notes(2)) * 4)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(voice)
abjad> beam = spannertools.BeamSpanner(voice.leaves[:4])
abjad> slur = spannertools.SlurSpanner(voice[-2:])
```

```
abjad> f(voice)
\new Voice {
  {
    \time 2/8
    c'8 [
    d'8
  ]
  {
    \time 2/8
    e'8
    f'8 ]
  ]
  {
    \time 2/8
    g'8 (
    a'8
  ]
  {
    \time 2/8
    b'8
    c''8 )
  ]
}
```

```
abjad> spannertools.make_spanner_schema(voice.leaves[2:4])
{BeamSpanner(c'8, d'8, e'8, f'8): [0, 1]}
```

Return dictionary.

spannertools.move_spanners_from_component_to_children_of_component

abjad.tools.spannertools.**move_spanners_from_component_to_children_of_component** (*donor*)

Give spanners attaching directly to donor to recipients. Usual use is to give attached spanners from parent to children, which is a composer-safe operation. Changed in version 2.0: renamed `spannertools.give_attached_to_children()` to `spannertools.move_spanners_from_component_to_children_of_component()`.

spannertools.report_as_string_format_contributions_of_all_spanners_attached_to_component

abjad.tools.spannertools.**report_as_string_format_contributions_of_all_spanners_attached_to_component** (*component*)

New in version 1.1. Report as string format contributions of all spanners attached to *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> slur = spannertools.SlurSpanner(staff.leaves)
```

```

abjad> trill = spannertools.TrillSpanner(staff)
abjad> f(staff)
\new Staff {
    c'8 [ ( \startTrillSpan
    d'8
    e'8
    f'8 ] ) \stopTrillSpan
}

```

```

abjad> spannertools.report_as_string_format_contributions_of_all_spanners_attached_to_component (
'BeamSpanner\n\t_right\n\t\t[\nSlurSpanner\n\t_right\n\t\t(\n'

```

Return string.

spannertools.report_as_string_format_contributions_of_all_spanners_attached_to_improper_parentage_of_comp

`abjad.tools.spannertools.report_as_string_format_contributions_of_all_spanners_attached_to`

New in version 1.1. Report as string format contributions of all spanners attached to improper parentage of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> beam = spannertools.BeamSpanner(staff.leaves)
abjad> slur = spannertools.SlurSpanner(staff.leaves)
abjad> trill = spannertools.TrillSpanner(staff)
abjad> f(staff)
\new Staff {
    c'8 [ ( \startTrillSpan
    d'8
    e'8
    f'8 ] ) \stopTrillSpan
}

```

```

abjad> spannertools.report_as_string_format_contributions_of_all_spanners_attached_to_component (
'BeamSpanner\n\t_right\n\t\t[\nSlurSpanner\n\t_right\n\t\t(\n'

```

Return string.

spannertools.withdraw_components_from_spanners_covered_by_components

`abjad.tools.spannertools.withdraw_components_from_spanners_covered_by_components` (*components*)

Find every spanner covered by ‘components’. Withdraw all components in ‘components’ from covered spanners. Return ‘components’. The operation always leaves all score trees in tact.

Changed in version 2.0: renamed `spannertools.withdraw_from_covered()` to `spannertools.withdraw_components_from_spanners_covered_by_components()`.

stafftools

stafftools.RhythmicStaff

class `abjad.tools.stafftools.RhythmicStaff` (*music*=[], ***kwargs*)

Bases: `abjad.tools.stafftools.Staff.Staff.Staff`

Abjad model of a rhythmic staff.

stafftools.Staff

class abjad.tools.stafftools.**Staff** (*music=None, **kwargs*)
 Bases: abjad.tools.contexttools._Context._Context._Context

Abjad model of a staff:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
}
```

Return staff object.

stafftools.get_first_staff_in_improper_parentage_of_component

abjad.tools.stafftools.**get_first_staff_in_improper_parentage_of_component** (*component*)
 New in version 2.0. Get first staff in improper parentage of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
}

abjad> stafftools.get_first_staff_in_improper_parentage_of_component(staff[1])
Staff{4}
```

Return staff or none.

stafftools.get_first_staff_in_proper_parentage_of_component

abjad.tools.stafftools.**get_first_staff_in_proper_parentage_of_component** (*component*)
 New in version 2.0. Get first staff in proper parentage of *component*:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")

abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
}

abjad> stafftools.get_first_staff_in_proper_parentage_of_component(staff[1])
Staff{4}
```

Return staff or none.

stafftools.iterate_staves_backward_in_expr

`abjad.tools.stafftools.iterate_staves_backward_in_expr(expr, start=0, stop=None)`

New in version 2.0. Iterate staves backward in *expr*:

```
abjad> score = Score(4 * Staff([ ]))

abjad> f(score)
\new Score <<
  \new Staff {
  }
  \new Staff {
  }
  \new Staff {
  }
  \new Staff {
  }
>>

abjad> for staff in stafftools.iterate_staves_backward_in_expr(score):
...     staff
...
Staff{}
Staff{}
Staff{}
Staff{}

Return generator.
```

stafftools.iterate_staves_forward_in_expr

`abjad.tools.stafftools.iterate_staves_forward_in_expr(expr, start=0, stop=None)`

New in version 2.0. Iterate staves forward in *expr*:

```
abjad> score = Score(4 * Staff([ ]))

abjad> f(score)
\new Score <<
  \new Staff {
  }
  \new Staff {
  }
  \new Staff {
  }
  \new Staff {
  }
>>

abjad> for staff in stafftools.iterate_staves_forward_in_expr(score):
...     staff
...
Staff{}
Staff{}
Staff{}
Staff{}

Return generator.
```

stafftools.make_invisible_staff

`abjad.tools.stafftools.make_invisible_staff(music)`

Staff constructor that hides meter, bar line and staff lines. Changed in version 2.0: Invisible staff class changed to invisible staff function.

stafftools.make_rhythmic_sketch_staff

`abjad.tools.stafftools.make_rhythmic_sketch_staff(music)`

Make rhythmic staff with transparent meter and transparent bar lines.

tietools

tietools.TieSpanner

class `abjad.tools.tietools.TieSpanner(music=None)`

Bases: `abjad.tools.spannertools.Spanner.Spanner.Spanner`

Abjad tie spanner:

```
abjad> staff = Staff(notetools.make_repeated_notes(4))
abjad> tietools.TieSpanner(staff[:])
TieSpanner(c'8, c'8, c'8, c'8)
abjad> f(staff)
\new Staff {
    c'8 ~
    c'8 ~
    c'8 ~
    c'8
}
```

Return tie spanner.

tietools.add_or_remove_tie_chain_notes_to_achieve_scaled_written_duration

`abjad.tools.tietools.add_or_remove_tie_chain_notes_to_achieve_scaled_written_duration(tie_chain, multiplier)`

Scale tie chain by multiplier. Wraps `tie_chain_duration_change`. Returns tie chain.

Changed in version 2.0: renamed `tietools.duration_scale()` to `tietools.add_or_remove_tie_chain_notes_to_achieve_scaled_written_duration()`.

tietools.add_or_remove_tie_chain_notes_to_achieve_written_duration

`abjad.tools.tietools.add_or_remove_tie_chain_notes_to_achieve_written_duration(tie_chain, new_written_duration)`

Change the written duration of tie chain, adding and subtracting notes as necessary.

Return newly modified tie chain. Changed in version 2.0: renamed `tietools.duration_change()` to `tietools.add_or_remove_tie_chain_notes_to_achieve_written_duration()`.

tietools.apply_tie_spanner_to_leaf_pair

abjad.tools.tietools.**apply_tie_spanner_to_leaf_pair**(*left*, *right*)

Apply tie spanner to *left* leaf and *right* leaf:

```

abjad> staff = Staff(notetools.make_repeated_notes(4))
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'8)
abjad> f(staff)
\new Staff {
    c'8 ~
    c'8
    c'8
    c'8
}

abjad> tietools.apply_tie_spanner_to_leaf_pair(staff[1], staff[2])

abjad> f(staff)
\new Staff {
    c'8 ~
    c'8 ~
    c'8
    c'8
}

```

Handle existing tie spanners intelligently.

Return `None`. Changed in version 2.0: renamed `tietools.span_leaf_pair()` to `tietools.apply_tie_spanner_to_leaf_pair()`.

tietools.are_components_in_same_tie_spanner

abjad.tools.tietools.**are_components_in_same_tie_spanner**(*components*)

True if all components in list share same tie spanner, otherwise False.

Changed in version 2.0: renamed `tietools.are_in_same_spanner()` to `tietools.are_components_in_same_tie_spanner()`.

tietools.get_leaves_in_tie_chain

abjad.tools.tietools.**get_leaves_in_tie_chain**(*tie_chain*)

Return Python list of leaves in tie chain.

tietools.get_preprolated_tie_chain_duration

abjad.tools.tietools.**get_preprolated_tie_chain_duration**(*tie_chain*)

Get sum of preprolated duration of all leaves in *tie_chain*.

Todo

write `tietools.get_preprolated_tie_chain_duration()` tests.

Changed in version 2.0: renamed `tietools.get_duration_preprolated()` to `tietools.get_preprolated_tie_chain_duration()`.

tietools.get_prolated_tie_chain_duration

`abjad.tools.tietools.get_prolated_tie_chain_duration(tie_chain)`
 Return sum of prolated duration of all leaves in chain.

Todo

Write `tietools.get_prolated_tie_chain_duration()` tests.

Changed in version 2.0: renamed `tietools.get_duration_prolated()` to `tietools.get_prolated_tie_chain_duration()`. Changed in version 2.0: renamed `tietools.get_tie_chain_prolated_duration()` to `tietools.get_prolated_tie_chain_duration()`.

tietools.get_tie_chain

`abjad.tools.tietools.get_tie_chain(component)`
 New in version 2.0. Get tie chain from *component*.

tietools.get_tie_chain_duration_in_seconds

`abjad.tools.tietools.get_tie_chain_duration_in_seconds(tie_chain)`
 Return sum of seconds duration of all leaves in chain.

Todo

Write `tietools.get_tie_chain_duration_in_seconds()` tests.

Changed in version 2.0: renamed `tietools.get_duration_seconds()` to `tietools.get_tie_chain_duration_in_seconds()`.

tietools.get_tie_chains_in_expr

`abjad.tools.tietools.get_tie_chains_in_expr(components)`
 This function returns all tie chains in components. A tie chain may not encompass all the leaves spanned by its corresponding Tie spanner, but only those found in the given list. i.e. the function returns the intersection between all the leaves spanned by all tie spanners touching the components given and the leaves found in the given components list. Changed in version 2.0: renamed `tietools.get_tie_chains()` to `tietools.get_tie_chains_in_expr()`.

tietools.get_written_tie_chain_duration

`abjad.tools.tietools.get_written_tie_chain_duration(tie_chain)`
 Return sum of written duration of all leaves in chain.

tietools.group_leaves_in_tie_chain_by_immediate_parents

`abjad.tools.tietools.group_leaves_in_tie_chain_by_immediate_parents(tie_chain)`
 Group leaves in *tie_chain* by immediate parent:


```

abjad> staff = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> tietools.TieSpanner(staff.leaves)
TieSpanner(c'8, c'8, c'8, c'8)
abjad> f(staff)
\new Staff {
    {
        \time 2/8
        c'8 ~
        c'8 ~
    }
    {
        \time 2/8
        c'8 ~
        c'8
    }
}

abjad> tie_chain = tietools.get_tie_chain(staff.leaves[0])
abjad> tietools.group_leaves_in_tie_chain_by_immediate_parents(tie_chain)
[[Note("c'8"), Note("c'8")], [Note("c'8"), Note("c'8")]]

```

Return list of leaf group lists. Changed in version 2.0: renamed `tietools.group_by_parent()` to `tietools.group_leaves_in_tie_chain_by_immediate_parents()`.

tietools.is_component_with_tie_spanner_attached

`abjad.tools.tietools.is_component_with_tie_spanner_attached(expr)`

New in version 2.0. True when *expr* is component with tie spanner attached:

```

abjad> staff = Staff(notetools.make_repeated_notes(4))
abjad> tietools.TieSpanner(staff[:])
TieSpanner(c'8, c'8, c'8, c'8)
abjad> f(staff)
\new Staff {
    c'8 ~
    c'8 ~
    c'8 ~
    c'8
}
abjad> tietools.is_component_with_tie_spanner_attached(staff)
False

```

Otherwise false:

```

abjad> staff = Staff(notetools.make_repeated_notes(4))
abjad> tietools.TieSpanner(staff[:])
TieSpanner(c'8, c'8, c'8, c'8)
abjad> f(staff)
\new Staff {
    c'8 ~
    c'8 ~
    c'8 ~
    c'8
}
abjad> tietools.is_component_with_tie_spanner_attached(staff[1])
True

```

Return boolean.

tietools.is_tie_chain

`abjad.tools.tietools.is_tie_chain(expr)`
 True when *expr* is a tie chain, otherwise False.

tietools.is_tie_chain_with_all_leaves_in_same_parent

`abjad.tools.tietools.is_tie_chain_with_all_leaves_in_same_parent(expr)`
 True when *expr* is a tie chain with all leaves in same parent.

That is, True when tie chain crosses no container boundaries, otherwise False.

Example:

```
abjad> t = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 2)
abjad> tietools.TieSpanner(t.leaves[1:3])
TieSpanner(c'8, c'8)

\new Staff {
    \time 2/8
    c'8
    c'8 ~
    \time 2/8
    c'8
    c'8
}

abjad> tie_chain = tietools.get_tie_chain(t.leaves[0])
abjad> assert tietools.is_tie_chain_with_all_leaves_in_same_parent(tie_chain)
abjad> tie_chain = tietools.get_tie_chain(t.leaves[1])
abjad> assert not tietools.is_tie_chain_with_all_leaves_in_same_parent(tie_chain)
abjad> tie_chain = tietools.get_tie_chain(t.leaves[2])
abjad> assert not tietools.is_tie_chain_with_all_leaves_in_same_parent(tie_chain)
abjad> tie_chain = tietools.get_tie_chain(t.leaves[3])
abjad> assert tietools.is_tie_chain_with_all_leaves_in_same_parent(tie_chain)
```

Changed in version 2.0: renamed `tietools.is_in_same_parent()` to `tietools.is_tie_chain_with_all_leaves_in_same_parent()`.

tietools.iterate_tie_chains_backward_in_expr

`abjad.tools.tietools.iterate_tie_chains_backward_in_expr(expr)`
 Yield right-to-left tie chains in *expr*:

```
abjad> notes = notetools.make_notes([0], [(5, 16), (1, 8), (1, 8), (5, 16)])
abjad> staff = Staff(notes)
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 16), staff[1:3])
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> print staff.format

\new Staff {
    c'4 ~
    \times 2/3 {
        c'16
        d'8
    }
    e'8
    f'4 ~
```

```

    f'16
}

abjad> for x in tietools.iterate_tie_chains_backward_in_expr(staff):
...     x
...
(Note("f'4"), Note("f'16"))
(Note("e'8"),)
(Note("d'8"),)
(Note("c'4"), Note("c'16"))

```

Note that one-note tie chains yield the same as other tie chains.

Note also that nested structures are no problem. Changed in version 2.0: renamed `iterate.tie_chains_backward_in()` to `tietools.iterate_tie_chains_backward_in_expr()`. Changed in version 2.0: renamed `iterate.tie_chains_backward_in_expr()` to `tietools.iterate_tie_chains_backward_in_expr()`.

`tietools.iterate_tie_chains_forward_in_expr`

`abjad.tools.tietools.iterate_tie_chains_forward_in_expr(expr)`

Yield left-to-right tie chains in *expr*:

```

abjad> notes = notetools.make_notes([0], [(5, 16), (1, 8), (1, 8), (5, 16)])
abjad> staff = Staff(notes)
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 16), staff[1:3])
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> print staff.format
\new Staff {
    c'4 ~
    \times 2/3 {
        c'16
        d'8
    }
    e'8
    f'4 ~
    f'16
}

abjad> for x in tietools.iterate_tie_chains_forward_in_expr(staff):
...     x
...
(Note("c'4"), Note("c'16"))
(Note("d'8"),)
(Note("e'8"),)
(Note("f'4"), Note("f'16"))

```

Note that one-note tie chains yield the same as other tie chains.

Note also that nested structures are no problem. Changed in version 2.0: renamed `iterate.tie_chains_forward_in()` to `tietools.iterate_tie_chains_forward_in_expr()`. Changed in version 2.0: renamed `iterate.tie_chains_forward_in_expr()` to `tietools.iterate_tie_chains_forward_in_expr()`.

`tietools.iterate_topmost_tie_chains_and_components_forward_in_expr`

`abjad.tools.tietools.iterate_topmost_tie_chains_and_components_forward_in_expr(expr)`
 Yield the left-to-right, top-level contents of *expr* with chain-wrapped leaves.

```
abjad> t = Staff(notetools.make_notes(0, [(5, 32)] * 4))
abjad> t.insert(4, tuplettools.FixedDurationTuplet(Duration(2, 8), notetools.make_repeated_notes(
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> f(t)
\new Staff {
    c'8 ~
    c'32
    d'8 ~
    d'32
    \times 2/3 {
        e'8
        f'8
        g'8
    }
    a'8 ~
    a'32
    b'8 ~
    b'32
}
```

```
abjad> for x in tietools.iterate_topmost_tie_chains_and_components_forward_in_expr(t):
...     x
...
(Note("c'8"), Note("c'32"))
(Note("d'8"), Note("d'32"))
FixedDurationTuplet(1/4, [e'8, f'8, g'8])
(Note("a'8"), Note("a'32"))
(Note("b'8"), Note("b'32"))
```

Crossing ties raise `TieChainError`. Changed in version 2.0: renamed `iterate.chained_contents()` to `tietools.iterate_topmost_tie_chains_and_components_forward_in_expr()` in version 2.0: renamed `iterate.topmost_tie_chains_and_components_forward_in_expr()` to `tietools.iterate_topmost_tie_chains_and_components_forward_in_expr()`.

`tietools.label_tie_chains_in_expr_with_prolated_tie_chain_duration`

`abjad.tools.tietools.label_tie_chains_in_expr_with_prolated_tie_chain_duration(expr, markup_direction)`
 Label tie chains in *expr* with prolated tie chain duration:

```
abjad> staff = Staff(notetools.make_repeated_notes(4))
abjad> tuplettools.FixedDurationTuplet(Duration(2, 8), staff[:3])
FixedDurationTuplet(1/4, [c'8, c'8, c'8])
abjad> tietools.TieSpanner(staff.leaves[:2])
TieSpanner(c'8, c'8)
abjad> tietools.TieSpanner(staff.leaves[2:])
TieSpanner(c'8, c'8)
abjad> tietools.label_tie_chains_in_expr_with_prolated_tie_chain_duration(staff)
abjad> f(staff)
\new Staff {
    \times 2/3 {
        c'8 _ \markup { \small 1/6 } ~
```

```

        c'8
        c'8 _ \markup { \small 5/24 } ~
    }
    c'8
}

```

Return none.

tietools.label_tie_chains_in_expr_with_tie_chain_durations

`abjad.tools.tietools.label_tie_chains_in_expr_with_tie_chain_durations`(*expr*,
markup_direction='down')

Label tie chains in *expr* with both written tie chain duration and prolated tie chain duration:

```

abjad> staff = Staff(notetools.make_repeated_notes(4))
abjad> tuplettools.FixedDurationTuplet(Duration(2, 8), staff[:3])
FixedDurationTuplet(1/4, [c'8, c'8, c'8])
abjad> tietools.TieSpanner(staff.leaves[:2])
TieSpanner(c'8, c'8)
abjad> tietools.TieSpanner(staff.leaves[2:])
TieSpanner(c'8, c'8)
abjad> tietools.label_tie_chains_in_expr_with_tie_chain_durations(staff)
abjad> f(staff)
\new Staff {
    \times 2/3 {
        c'8 _ \markup { \column { \small 1/4 \small 1/6 } } ~
        c'8
        c'8 _ \markup { \column { \small 1/4 \small 5/24 } } ~
    }
    c'8
}

```

Return none.

tietools.label_tie_chains_in_expr_with_written_tie_chain_duration

`abjad.tools.tietools.label_tie_chains_in_expr_with_written_tie_chain_duration`(*expr*,
markup_direction=)

Label tie chains in *expr* with written tie chain duration.:

```

abjad> staff = Staff(notetools.make_repeated_notes(4))
abjad> tuplettools.FixedDurationTuplet(Duration(2, 8), staff[:3])
FixedDurationTuplet(1/4, [c'8, c'8, c'8])
abjad> tietools.TieSpanner(staff.leaves[:2])
TieSpanner(c'8, c'8)
abjad> tietools.TieSpanner(staff.leaves[2:])
TieSpanner(c'8, c'8)
abjad> tietools.label_tie_chains_in_expr_with_written_tie_chain_duration(staff)
abjad> f(staff)
\new Staff {
    \times 2/3 {
        c'8 _ \markup { \small 1/4 } ~
        c'8
        c'8 _ \markup { \small 1/4 } ~
    }
    c'8
}

```

Return none.

tietools.remove_all_leaves_in_tie_chain_except_first

`abjad.tools.tietools.remove_all_leaves_in_tie_chain_except_first(tie_chain)`
 Detach all leaves of tie chain after the first. Unspan and return length-1 tie chain. Changed in version 2.0: renamed `tietools.truncate()` to `tietools.remove_all_leaves_in_tie_chain_except_first()`.

tietools.remove_tie_spanners_from_components_in_expr

`abjad.tools.tietools.remove_tie_spanners_from_components_in_expr(expr)`

Remove tie spanners components in *expr*:

```
abjad> staff = Staff("c'4 ~ c'16 d'4 ~ d'16")
abjad> f(staff)
\new Staff {
    c'4 ~
    c'16
    d'4 ~
    d'16
}

abjad> tietools.remove_tie_spanners_from_components_in_expr(staff[:])
[Note("c'4"), Note("c'16"), Note("d'4"), Note("d'16")]
abjad> f(staff)
\new Staff {
    c'4
    c'16
    d'4
    d'16
}
```

Return *expr*. Changed in version 2.0: renamed `componenttools.untie_shallow()` to `tietools.remove_tie_spanners_from_components_in_expr()`.

tietools.tie_chain_to_augmented_tuplet_with_proportions_and_avoid_dots

`abjad.tools.tietools.tie_chain_to_augmented_tuplet_with_proportions_and_avoid_dots(tie_chain, proportions)`

New in version 2.0. Divide *tie_chain* into fixed-duration tuplet according to arbitrary integer *proportions*.

Interpret *proportions* as a ratio. That is, reduce integers in *proportions* relative to each other.

Return non-trivial tuplet as augmentation.

Where `proportions[i] == 1` for `i < len(proportions)`, do not allow tupletted notes to carry dots.

```
abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
```

```

abjad> tietools.tie_chain_to_augmented_tuplet_with_proportions_and_avoid_dots(tie_chain, [1])
FixedDurationTuplet(3/16, [c'8])
abjad> f(staff)
\new Staff {
    \fraction \times 3/2 {
        c'8 [
    ]
    c'16 ]
}

abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_augmented_tuplet_with_proportions_and_avoid_dots(tie_chain, [1, 2])
FixedDurationTuplet(3/16, [c'16, c'8])
abjad> f(staff)
\new Staff {
    {
        c'16 [
        c'8
    ]
    c'16 ]
}

abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_augmented_tuplet_with_proportions_and_avoid_dots(tie_chain, [1, 2,
FixedDurationTuplet(3/16, [c'32, c'16, c'16])
abjad> f(staff)
\new Staff {
    \fraction \times 6/5 {
        c'32 [
        c'16
        c'16
    ]
    c'16 ]
}

```

Changed in version 2.0: renamed `divide.tie_chain_into_arbitrary_augmentation_undotted()` to `tietools.tie_chain_to_augmented_tuplet_with_proportions_and_avoid_dots()`.

tietools.tie_chain_to_augmented_tuplet_with_proportions_and_encourage_dots

`abjad.tools.tietools.tie_chain_to_augmented_tuplet_with_proportions_and_encourage_dots` (*tie_c*

pro-
por-
tions

New in version 2.0. Divide *tie_chain* into fixed-duration tuplet according to arbitrary integer *proportions*.

Interpret *proportions* as a ratio. That is, reduce integers in *proportions* relative to each other.

Return non-trivial tuplet as augmentation.

Where `proportions[i] == 1` for `i < len(proportions)`, allow tupletted notes to carry dots.

```
abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_augmented_tuplet_with_proportions_and_encourage_dots(tie_chain, [1,
FixedDurationTuplet(3/16, [c'8.])
abjad> f(staff)
\new Staff {
    {
        c'8. [
    ]
    c'16 ]
}

abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_augmented_tuplet_with_proportions_and_encourage_dots(tie_chain, [1,
FixedDurationTuplet(3/16, [c'16, c'8])
abjad> f(staff)
\new Staff {
    {
        c'16 [
        c'8
    ]
    c'16 ]
}

abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_augmented_tuplet_with_proportions_and_encourage_dots(tie_chain, [1,
FixedDurationTuplet(3/16, [c'64., c'32., c'32.])
abjad> f(staff)
\new Staff {
    \fraction \times 8/5 {
        c'64. [
        c'32.
        c'32.
    ]
    c'16 ]
}
```

Changed in version 2.0: renamed `divide.tie_chain_into_arbitrary_augmentation_dotted()` to `tietools.tie_chain_to_augmented_tuplet_with_proportions_and_encourage_dots()`.

tietools.tie_chain_to_diminished_tuplet_with_proportions_and_avoid_dots

abjad.tools.tietools.**tie_chain_to_diminished_tuplet_with_proportions_and_avoid_dots** (*tie_chain*, *proportions*)

New in version 2.0. Divide *tie_chain* into fixed-duration tuplet according to arbitrary integer *proportions*.

Interpret *proportions* as a ratio. That is, reduce integers in *proportions* relative to each other.

Return non-trivial tuplet as diminution.

Where `proportions[i] == 1` for `i < len(proportions)`, do not allow tupletted notes to carry dots.

```
abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_diminished_tuplet_with_proportions_and_avoid_dots(tie_chain, [1])
FixedDurationTuplet(3/16, [c'4])
abjad> f(staff)
\new Staff {
    \fraction \times 3/4 {
        c'4 [
    ]
    c'16 ]
}

abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_augmented_tuplet_with_proportions_and_avoid_dots(tie_chain, [1, 2])
FixedDurationTuplet(3/16, [c'16, c'8])
abjad> f(staff)
\new Staff {
    {
        c'16 [
        c'8
    ]
    c'16 ]
}

abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_diminished_tuplet_with_proportions_and_avoid_dots(tie_chain, [1, 2])
FixedDurationTuplet(3/16, [c'16, c'8, c'8])
abjad> f(staff)
\new Staff {
    \fraction \times 3/5 {
        c'16 [
        c'8
```

```

        c'8
    }
    c'16 ]
}

```

Changed in version 2.0: renamed `divide.tie_chain_into_arbitrary_diminution_undotted()` to `tietools.tie_chain_to_diminished_tuplet_with_proportions_and_avoid_dots()`.

tietools.tie_chain_to_diminished_tuplet_with_proportions_and_encourage_dots

`abjad.tools.tietools.tie_chain_to_diminished_tuplet_with_proportions_and_encourage_dots` (*tie_*

pro
por
tion

New in version 2.0. Divide *tie_chain* into fixed-duration tuplet according to arbitrary integer *proportions*.

Interpret *proportions* as a ratio. That is, reduce integers in *proportions* relative to each other.

Return non-trivial tuplet as diminution.

Where `proportions[i] == 1` for `i < len(proportions)`, allow tupletted notes to carry dots.

```

abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_diminished_tuplet_with_proportions_and_encourage_dots(tie_chain, [1, 1])
FixedDurationTuplet(3/16, [c'8.])
abjad> f(staff)
\new Staff {
    {
        c'8. [
    ]
    c'16 ]
}

abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)
abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_diminished_tuplet_with_proportions_and_encourage_dots(tie_chain, [1, 1])
FixedDurationTuplet(3/16, [c'16, c'8])
abjad> f(staff)
\new Staff {
    {
        c'16 [
        c'8
    ]
    c'16 ]
}

abjad> staff = Staff([Note(0, (1, 8)), Note(0, (1, 16)), Note(0, (1, 16))])
abjad> tietools.TieSpanner(staff[:2])
TieSpanner(c'8, c'16)

```

```

abjad> spannertools.BeamSpanner(staff[:])
BeamSpanner(c'8, c'16, c'16)
abjad> tie_chain = tietools.get_tie_chain(staff[0])
abjad> tietools.tie_chain_to_diminished_tuplet_with_proportions_and_encourage_dots(tie_chain, [1
FixedDurationTuplet(3/16, [c'32., c'16., c'16.])
abjad> f(staff)
\new Staff {
  \times 4/5 {
    c'32. [
    c'16.
    c'16.
  }
  c'16 ]
}

```

Changed in version 2.0: renamed `divide.tie_chain_into_arbitrary_diminution_dotted()` to `tietools.tie_chain_to_diminished_tuplet_with_proportions_and_encourage_dots()`.

tuplettools

tuplettools.FixedDurationTuplet

class abjad.tools.tuplettools.**FixedDurationTuplet** (*duration, music=None, **kwargs*)
 Bases: abjad.tools.tuplettools.Tuplet.Tuplet.Tuplet

Abjad tuplet of fixed duration and variable multiplier:

```

abjad> tuplettools.FixedDurationTuplet(Fraction(2, 8), "c'8 d'8 e'8")
FixedDurationTuplet(1/4, [c'8, d'8, e'8])

```

Return fixed-duration tuplet.

multiplied_duration

multiplier

target_duration

trim (*start, stop='unused'*)

Trim fixed-duration tuplet elements from *start* to *stop*:

```

abjad> tuplet = tuplettools.FixedDurationTuplet(Fraction(2, 8), "c'8 d'8 e'8")
abjad> tuplet
FixedDurationTuplet(1/4, [c'8, d'8, e'8])

```

```
abjad> tuplet.trim(2)
```

```
abjad> tuplet
FixedDurationTuplet(1/6, [c'8, d'8])
```

Preserve fixed-duration tuplet multiplier.

Adjust fixed-duration tuplet duration.

Return none.

tuplettools.Tuplet

class abjad.tools.tuplettools.**Tuplet** (*multiplier, music=None, **kwargs*)
 Bases: abjad.tools.containertools.Container.Container.Container

Abjad model of a tuplet:

```
abjad> tuplet = Tuplet(Fraction(2, 3), "c'8 d'8 e'8")
abjad> f(tuplet)
\times 2/3 {
    c'8
    d'8
    e'8
}
```

Return tuplet object.

force_fraction

Read / write boolean to force n:m fraction.

is_augmentation

True when multiplier is greater than 1. Otherwise false:

```
abjad> t = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> t.is_augmentation
False
```

Return boolean.

is_binary

True when multiplier numerator is power of two, otherwise False.

is_diminution

True when multiplier is less than 1. Otherwise false:

```
abjad> t = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> t.is_diminution
True
```

Return boolean.

is_invisible

Read / write boolean to render tuplet invisible.

is_nonbinary

is_trivial

True when tuplet multiplier is one, otherwise False.

multiplied_duration

multiplier

preferred_denominator

New in version 2.0. Integer denominator in terms of which tuplet fraction should format.

preprolated_duration

Duration prior to prolation:

```
abjad> t = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> t.preprolated_duration
Duration(1, 4)
```

Return duration.

ratio

Tuplet multiplier formatted with colon as ratio.

tuplettools.beam_bottommost_tuplets_in_expr

`abjad.tools.tuplettools.beam_bottommost_tuplets_in_expr(expr)`

Beam bottommost tuplets in *expr*:

```
abjad> staff = Staff(3 * Tuplet(Fraction(2, 3), "c'8 d'8 e'8"))
```

```
f(staff)
\new Staff {
  \times 2/3 {
    c'8
    d'8
    e'8
  }
  \times 2/3 {
    c'8
    d'8
    e'8
  }
  \times 2/3 {
    c'8
    d'8
    e'8
  }
}
```

```
abjad> tuplettools.beam_bottommost_tuplets_in_expr(staff)
```

```
abjad> f(staff)
\new Staff {
  \times 2/3 {
    c'8 [
    d'8
    e'8 ]
  }
  \times 2/3 {
    c'8 [
    d'8
    e'8 ]
  }
  \times 2/3 {
    c'8 [
    d'8
    e'8 ]
  }
}
```

Return none.

tuplettools.change_augmented_tuplets_in_expr_to_diminished

`abjad.tools.tuplettools.change_augmented_tuplets_in_expr_to_diminished(tuplet)`

New in version 2.0. Multiply the written duration of the leaves in *tuplet* by the least power of 2 necessary to diminished *tuplet*.

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 4), "c'8 d'8 e'8")
abjad> tuplet
```

```
FixedDurationTuplet(1/2, [c'8, d'8, e'8])
abjad> tuplettools.change_augmented_tuplets_in_expr_to_diminished(tuplet)
FixedDurationTuplet(1/2, [c'4, d'4, e'4])
```

Todo

make work with nested tuplets.

Changed in version 2.0: renamed `tuplettools.augmentation_to_diminution()` to `tuplettools.change_augmented_tuplets_in_expr_to_diminished()`.

tuplettools.change_diminished_tuplets_in_expr_to_augmented

`abjad.tools.tuplettools.change_diminished_tuplets_in_expr_to_augmented(tuplet)`
New in version 2.0. Divide the written duration of the leaves in *tuplet* by the least power of 2 necessary to augment *tuplet*.

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> tuplet
FixedDurationTuplet(1/4, [c'8, d'8, e'8])
abjad> tuplettools.change_diminished_tuplets_in_expr_to_augmented(tuplet)
FixedDurationTuplet(1/4, [c'16, d'16, e'16])
```

Todo

make work with nested tuplets.

Changed in version 2.0: renamed `tuplettools.diminution_to_augmentation()` to `tuplettools.change_diminished_tuplets_in_expr_to_augmented()`.

tuplettools.fix_contents_of_tuplets_in_expr

`abjad.tools.tuplettools.fix_contents_of_tuplets_in_expr(tuplet)`
Scale *tuplet* contents by power of two if tuplet multiplier less than 1/2 or greater than 2. Return *tuplet*.

```
abjad> tuplet = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'4 d'4 e'4")
abjad> tuplet
FixedDurationTuplet(1/4, [c'4, d'4, e'4])
abjad> tuplettools.fix_contents_of_tuplets_in_expr(tuplet)
FixedDurationTuplet(1/4, [c'8, d'8, e'8])
```

Changed in version 2.0: renamed `tuplettools.contents_fix()` to `tuplettools.fix_contents_of_tuplets_in_expr()`.

tuplettools.fuse_tuplets

`abjad.tools.tuplettools.fuse_tuplets(tuplets)`
Fuse parent-contiguous *tuplets*:

```
abjad> t1 = tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8")
abjad> spannertools.BeamSpanner(t1[:])
BeamSpanner(c'8, d'8, e'8)
abjad> t2 = tuplettools.FixedDurationTuplet(Duration(2, 16), "c'16 d'16 e'16")
```

```

abjad> spannertools.SlurSpanner(t2[:])
SlurSpanner(c'16, d'16, e'16)
abjad> staff = Staff([t1, t2])
abjad> f(staff)
\new Staff {
  \times 2/3 {
    c'8 [
      d'8
      e'8 ]
  }
  \times 2/3 {
    c'16 (
      d'16
      e'16 )
  }
}

abjad> tuplettools.fuse_tuplets(staff[:])
FixedDurationTuplet(3/8, [c'8, d'8, e'8, c'16, d'16, e'16])

abjad> f(staff)
\new Staff {
  \times 2/3 {
    c'8 [
      d'8
      e'8 ]
    c'16 (
      d'16
      e'16 )
  }
}

```

Return new tuplet.

Fuse zero or more parent-contiguous *tuplets*.

Allow in-score *tuplets*.

Allow outside-of-score *tuplets*.

All *tuplets* must carry the same multiplier.

All *tuplets* must be of the same type. Changed in version 2.0: renamed `fuse.tuplets_by_reference()` to `tuplettools.fuse_tuplets()`.

tuplettools.get_first_tuplet_in_improper_parentage_of_component

`abjad.tools.tuplettools.get_first_tuplet_in_improper_parentage_of_component` (*component*)

New in version 2.0. Get first tuplet in improper parentage of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> Tuplet(Fraction(2, 3), staff[:3])
Tuplet(2/3, [c'8, d'8, e'8])

abjad> f(staff)
\new Staff {
  \times 2/3 {
    c'8
    d'8

```

```

        e'8
    }
    f'8
}

```

```

abjad> tuplettools.get_first_tuplet_in_improper_parentage_of_component(staff.leaves[1])
Tuplet(2/3, [c'8, d'8, e'8])

```

Return tuplet or none.

tuplettools.get_first_tuplet_in_proper_parentage_of_component

`abjad.tools.tuplettools.get_first_tuplet_in_proper_parentage_of_component` (*component*)
 New in version 2.0. Get first tuplet in proper parentage of *component*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8")
abjad> Tuplet(Fraction(2, 3), staff[:3])
Tuplet(2/3, [c'8, d'8, e'8])

```

```

abjad> f(staff)
\new Staff {
  \times 2/3 {
    c'8
    d'8
    e'8
  }
  f'8
}

```

```

abjad> tuplettools.get_first_tuplet_in_proper_parentage_of_component(staff.leaves[1])
Tuplet(2/3, [c'8, d'8, e'8])

```

Return tuplet or none.

tuplettools.is_proper_tuplet_multiplier

`abjad.tools.tuplettools.is_proper_tuplet_multiplier` (*multiplier*)
 True when $1/2 < \text{multiplier} < 2$.

```

abjad> for n in range(17):
...     rational = Fraction(n, 8)
...     multiplier = tuplettools.is_proper_tuplet_multiplier(rational)
...     print '%s    %s' % (rational, multiplier)
...
0        False
1/8      False
1/4      False
3/8      False
1/2      False
5/8      True
3/4      True
7/8      True
1        True
9/8      True
5/4      True
11/8     True

```



```

3/2      True
13/8     True
7/4      True
15/8     True
2        False

```

This function models the idea that 4:3, 4:5, 4:6, 4:7 are valid tuplet multipliers while 4:2 and 4:8 aren't. Changed in version 2.0: renamed `durtools.is_tuplet_multiplier()` to `tuplettools.is_proper_tuplet_multiplier()`.

`tuplettools.iterate_tuplets_backward_in_expr`

`abjad.tools.tuplettools.iterate_tuplets_backward_in_expr`(*expr*, *start=0*, *stop=None*)

New in version 2.0. Iterate tuplets backward in *expr*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")
abjad> Tuplet(Fraction(2, 3), staff[:3])
Tuplet(2/3, [c'8, d'8, e'8])
abjad> Tuplet(Fraction(2, 3), staff[-3:])
Tuplet(2/3, [a'8, b'8, c''8])

abjad> f(staff)
\new Staff {
    \times 2/3 {
        c'8
        d'8
        e'8
    }
    f'8
    g'8
    \times 2/3 {
        a'8
        b'8
        c''8
    }
}

abjad> for tuplet in tuplettools.iterate_tuplets_backward_in_expr(staff):
...     tuplet
...
Tuplet(2/3, [a'8, b'8, c''8])
Tuplet(2/3, [c'8, d'8, e'8])

```

Return generator.

`tuplettools.iterate_tuplets_forward_in_expr`

`abjad.tools.tuplettools.iterate_tuplets_forward_in_expr`(*expr*, *start=0*, *stop=None*)

New in version 2.0. Iterate tuplets forward in *expr*:

```

abjad> staff = Staff("c'8 d'8 e'8 f'8 g'8 a'8 b'8 c''8")
abjad> Tuplet(Fraction(2, 3), staff[:3])
Tuplet(2/3, [c'8, d'8, e'8])
abjad> Tuplet(Fraction(2, 3), staff[-3:])
Tuplet(2/3, [a'8, b'8, c''8])

```

```

abjad> f(staff)
\new Staff {
  \times 2/3 {
    c'8
    d'8
    e'8
  }
  f'8
  g'8
  \times 2/3 {
    a'8
    b'8
    c''8
  }
}

abjad> for tuplet in tuplettools.iterate_tuplets_forward_in_expr(staff):
...     tuplet
...
Tuplet(2/3, [c'8, d'8, e'8])
Tuplet(2/3, [a'8, b'8, c''8])

```

Return generator.

tuplettools.make_augmented_tuplet_from_duration_and_proportions_and_avoid_dots

`abjad.tools.tuplettools.make_augmented_tuplet_from_duration_and_proportions_and_avoid_dots`

New in version 2.0. Make augmented tuplet from *duration* and *proportions* and avoid dots.

Return tupletted leaves strictly without dots when all *proportions* equal 1:

```

abjad> print tuplettools.make_augmented_tuplet_from_duration_and_proportions_and_avoid_dots(
... Fraction(3, 16), [1, 1, 1, -1, -1])
{@ 5:6 c'32, c'32, c'32, r32, r32 @}

```

Allow tupletted leaves to return with dots when some *proportions* do not equal 1:

```

abjad> print tuplettools.make_augmented_tuplet_from_duration_and_proportions_and_avoid_dots(
... Fraction(3, 16), [1, -2, -2, 3, 3])
{@ 11:12 c'64, r32, r32, c'32., c'32. @}

```

Interpret nonassignable *proportions* according to *direction*:

```

abjad> print tuplettools.make_augmented_tuplet_from_duration_and_proportions_and_avoid_dots(
... Fraction(3, 16), [5, -1, 5], direction = 'little-endian')
{@ 11:12 c'64, c'16, r64, c'64, c'16 @}

```

Reduce *proportions* relative to each other.

Interpret negative *proportions* as rests.

Return	fixed-duration	tuplet.	Changed	in	version	2.0:	renamed
							to
							<code>tuplettools.make_augmented_tuplet_from_duration_and_proportions_and_avoid_dots()</code> .

tuplettools.make_augmented_tuplet_from_duration_and_proportions_and_encourage_dots

abjad.tools.tuplettools.**make_augmented_tuplet_from_duration_and_proportions_and_encourage_dots**

New in version 2.0. Make augmented tuplet from *duration* and *proportions* and encourage dots:

```
abjad> print tuplettools.make_augmented_tuplet_from_duration_and_proportions_and_encourage_dots(
... Fraction(3, 16), [1, 1, 1, -1, -1])
{@ 5:8 c'64., c'64., c'64., r64., r64. @}
```

Interpret nonassignable *proportions* according to *direction*:

```
abjad> print tuplettools.make_augmented_tuplet_from_duration_and_proportions_and_encourage_dots(
... Fraction(3, 16), [5, -1, 5], direction = 'little-endian')
{@ 11:16 c'32..., r128., c'32... @}
```

Reduce *proportions* relative to each other.

Interpret negative *proportions* as rests.

Return fixed-duration tuplet. Changed in version 2.0: renamed
 divide.duration_into_arbitrary_augmentation_dotted() to
 tuplettools.make_augmented_tuplet_from_duration_and_proportions_and_encourage_dots().

tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_avoid_dots

abjad.tools.tuplettools.**make_diminished_tuplet_from_duration_and_proportions_and_avoid_dots**

New in version 2.0. Make diminished tuplet from *duration* and nonzero integer *proportions*.

Return tupletted leaves strictly without dots when all *proportions* equal 1:

```
abjad> print tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_avoid_dots(
... Fraction(3, 16), [1, 1, 1, -1, -1])
{@ 5:3 c'16, c'16, c'16, r16, r16 @}
```

Allow tupletted leaves to return with dots when some *proportions* do not equal 1:

```
abjad> print tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_avoid_dots(
... Fraction(3, 16), [1, -2, -2, 3, 3])
{@ 11:6 c'32, r16, r16, c'16., c'16. @}
```

Interpret nonassignable *proportions* according to *direction*:

```
abjad> print tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_avoid_dots(
... Fraction(3, 16), [5, -1, 5], direction = 'little-endian')
{@ 11:6 c'32, c'8, r32, c'32, c'8 @}
```

Reduce *proportions* relative to each other.

Interpret negative *proportions* as rests.

Return fixed-duration tuplet. Changed in version 2.0: renamed
`divide.duration_into_arbitrary_diminution_undotted()` to
`tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_avoid_dots()`.

`tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_encourage_dots`

`abjad.tools.tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_encourage_dots`

New in version 2.0. Make diminished tuplet from *duration* and *proportions* and encourage dots:

```
abjad> print tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_encourage_dots(
... Fraction(3, 16), [1, 1, 1, -1, -1])
{@ 5:4 c'32., c'32., c'32., r32., r32. @}
```

Interpret nonassignable *proportions* according to *direction*:

```
abjad> print tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_encourage_dots(
... Fraction(3, 16), [5, -1, 5], direction = 'little-endian')
{@ 11:8 c'16..., r64., c'16... @}
```

Reduce *proportions* relative to each other.

Interpret negative *proportions* as rests.

Return fixed-duration tuplet. Changed in version 2.0: renamed
`divide.duration_into_arbitrary_diminution_dotted()` to
`tuplettools.make_diminished_tuplet_from_duration_and_proportions_and_encourage_dots()`.

`tuplettools.make_tuplet_from_proportions_and_pair`

`abjad.tools.tuplettools.make_tuplet_from_proportions_and_pair`(*l*, (*n*, *d*), *together=False*)

Divide (*n*, *d*) according to *l*.

Where no prololation is necessary, return container.

```
abjad> tuplettools.make_tuplet_from_proportions_and_pair([1], (7, 16))
{c'4..}
```

Where prololation is necessary, return fixed-duration tuplet.

```
abjad> tuplettools.make_tuplet_from_proportions_and_pair([1, 2], (7, 16))
FixedDurationTuplet(7/16, [c'8, c'4])
```

```
abjad> tuplettools.make_tuplet_from_proportions_and_pair([1, 2, 4], (7, 16))
FixedDurationTuplet(7/16, [c'16, c'8, c'4])
```

```
abjad> tuplettools.make_tuplet_from_proportions_and_pair([1, 2, 4, 1], (7, 16))
FixedDurationTuplet(7/16, [c'16, c'8, c'4, c'16])
```

```
abjad> tuplettools.make_tuplet_from_proportions_and_pair([1, 2, 4, 1, 2], (7, 16))
FixedDurationTuplet(7/16, [c'16, c'8, c'4, c'16, c'8])
```

```
abjad> tuplettools.make_tuplet_from_proportions_and_pair([1, 2, 4, 1, 2, 4], (7, 16))
FixedDurationTuplet(7/16, [c'16, c'8, c'4, c'16, c'8, c'4])
```

Note: function accepts a pair rather than a rational.

Note: function interprets *d* as tuplet denominator.

Changed in version 2.0: renamed `divide.pair()` to `tuplettools.make_tuplet_from_proportions_and_pair`

`tuplettools.move_prolation_of_tuplet_to_contents_of_tuplet_and_remove_tuplet`

`abjad.tools.tuplettools.move_prolation_of_tuplet_to_contents_of_tuplet_and_remove_tuplet(tu)`
 Scale tuplet contents and then bequeath in-score position of tuplet to contents.

Return orphaned tuplet emptied of all contents.

```
abjad> t = Staff(tuplettools.FixedDurationTuplet(Duration(3, 8), "c'8 d'8") * 2)
abjad> spannertools.BeamSpanner(t.leaves)
BeamSpanner(c'8, d'8, c'8, d'8)
abjad> print t.format
\new Staff {
  \fraction \times 3/2 {
    c'8 [
      d'8
    ]
  }
  \fraction \times 3/2 {
    c'8
    d'8 ]
  }
}

abjad> tuplettools.move_prolation_of_tuplet_to_contents_of_tuplet_and_remove_tuplet(t[0])
FixedDurationTuplet(3/8, [ ])
abjad> print t.format
\new Staff {
  c'8. [
    d'8.
    \fraction \times 3/2 {
      c'8
      d'8 ]
    }
}
```

Changed in version 2.0: renamed `tuplettools.subsume()` to `tuplettools.move_prolation_of_tuplet_to_contents_of_tuplet_and_remove_tuplet()`.

`tuplettools.remove_trivial_tuplets_in_expr`

`abjad.tools.tuplettools.remove_trivial_tuplets_in_expr(expr)`
 Remove trivial tuplets in *expr*:

```
abjad> t = tuplettools.FixedDurationTuplet(Duration(1, 4), "c'8 d'8 e'8")
abjad> u = tuplettools.FixedDurationTuplet(Duration(1, 4), "c'8 d'8")
abjad> s = Staff([t, u])
```

```

abjad> len(s)
2

abjad> s[0]
FixedDurationTuplet(1/4, [c'8, d'8, e'8])
abjad> s[1]
FixedDurationTuplet(1/4, [c'8, d'8])

abjad> tuplettools.remove_trivial_tuplets_in_expr(s)
abjad> len(s)
3
abjad> s[0]
FixedDurationTuplet(1/4, [c'8, d'8, e'8])
abjad> s[1]
Note("c'8")
abjad> s[2]
Note("d'8")

abjad> f(s)
\new Staff {
  \times 2/3 {
    c'8
    d'8
    e'8
  }
  c'8
  d'8
}

```

Replace trivial tuplets with plain leaves.

Return `none`. Changed in version 2.0: renamed `tuplettools.slip_trivial()` to `tuplettools.remove_trivial_tuplets_in_expr()`.

tuplettools.scale_contents_of_tuplets_in_expr_by_multiplier

```

abjad.tools.tuplettools.scale_contents_of_tuplets_in_expr_by_multiplier(tuplet,
                                                                           multiplier)

```

Scale fixed-duration tuplet by multiplier. Preserve tuplet multiplier. Return tuplet.

tuplettools.set_denominator_of_tuplets_in_expr_to_at_least

```

abjad.tools.tuplettools.set_denominator_of_tuplets_in_expr_to_at_least(expr,
                                                                           n)

```

New in version 2.0. Set denominator of tuplets in *expr* to at least *n*:

```

abjad> tuplet = Tuplet(Fraction(3, 5), "c'4 d'8 e'8 f'4 g'2")

abjad> f(tuplet)
\fraction \times 3/5 {
  c'4
  d'8
  e'8
  f'4
}

```

```

        g' 2
    }

abjad> tuplettools.set_denominator_of_tuplets_in_expr_to_at_least(tuplet, 8)

abjad> f(tuplet)
\fraction \times 6/10 {
    c' 4
    d' 8
    e' 8
    f' 4
    g' 2
}

```

Return none.

voicetools

voicetools.Voice

class abjad.tools.voicetools.**Voice** (*music=None, **kwargs*)
Bases: abjad.tools.contexttools._Context._Context._Context

Abjad model of a voice:

```

abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> f(voice)
\new Voice {
    c' 8
    d' 8
    e' 8
    f' 8
}

```

Return voice object.

voicetools.get_first_voice_in_improper_parentage_of_component

abjad.tools.voicetools.**get_first_voice_in_improper_parentage_of_component** (*component*)
 New in version 2.0. Get first voice in improper parentage of *component*:

```

abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> staff = Staff([voice])

abjad> f(staff)
\new Staff {
    \new Voice {
        c' 8
        d' 8
        e' 8
        f' 8
    }
}

abjad> voicetools.get_first_voice_in_improper_parentage_of_component(staff.leaves[0])
Voice{4}

```

Return voice or none.

voicetools.get_first_voice_in_proper_parentage_of_component

`abjad.tools.voicetools.get_first_voice_in_proper_parentage_of_component` (*component*)

New in version 2.0. Get first voice in proper parentage of *component*:

```
abjad> voice = Voice("c'8 d'8 e'8 f'8")
abjad> staff = Staff([voice])

abjad> f(staff)
\new Staff {
  \new Voice {
    c'8
    d'8
    e'8
    f'8
  }
}

abjad> voicetools.get_first_voice_in_proper_parentage_of_component(staff.leaves[0])
Voice{4}
```

Return voice or none.

voicetools.iterate_semantic_voices_backward_in_expr

`abjad.tools.voicetools.iterate_semantic_voices_backward_in_expr` (*expr*)

New in version 2.0. Iterate semantic voices backward in *expr*:

```
abjad> measures = measuretools.make_measures_with_full_measure_spacer_skips([(3, 8), (5, 16), (5, 16)])
abjad> time_signature_voice = Voice(measures)
abjad> time_signature_voice.name = 'TimeSignatureVoice'
abjad> time_signature_voice.is_nonsemantic = True
abjad> music_voice = Voice("c'4. d'4 e'16 f'4 g'16")
abjad> music_voice.name = 'MusicVoice'
abjad> staff = Staff([time_signature_voice, music_voice])
abjad> staff.is_parallel = True

abjad> f(staff)
\new Staff <<
  \context Voice = "TimeSignatureVoice" {
    {
      \time 3/8
      s1 * 3/8
    }
    {
      \time 5/16
      s1 * 5/16
    }
    {
      \time 5/16
      s1 * 5/16
    }
  }
  \context Voice = "MusicVoice" {
    c'4.
    d'4
    e'16
    f'4
  }
}
```



```

        g'16
    }
>>

abjad> for voice in voicetools.iterate_semantic_voices_backward_in_expr(staff):
...     voice
Voice-"MusicVoice"{5}

```

Return generator.

voicetools.iterate_semantic_voices_forward_in_expr

abjad.tools.voicetools.**iterate_semantic_voices_forward_in_expr**(*expr*)

New in version 2.0. Iterate semantic voices forward in *expr*:

```

abjad> measures = measuretools.make_measures_with_full_measure_spacer_skips([(3, 8), (5, 16), (5, 16)])
abjad> meter_voice = Voice(measures)
abjad> meter_voice.name = 'TimeSignatuerVoice'
abjad> meter_voice.is_nonsemantic = True
abjad> music_voice = Voice("c'4. d'4 e'16 f'4 g'16")
abjad> music_voice.name = 'MusicVoice'
abjad> staff = Staff([meter_voice, music_voice])
abjad> staff.is_parallel = True

abjad> f(staff)
\new Staff <<
  \context Voice = "TimeSignatuerVoice" {
    {
      \time 3/8
      s1 * 3/8
    }
    {
      \time 5/16
      s1 * 5/16
    }
    {
      \time 5/16
      s1 * 5/16
    }
  }
  \context Voice = "MusicVoice" {
    c'4.
    d'4
    e'16
    f'4
    g'16
  }
>>

abjad> for voice in voicetools.iterate_semantic_voices_forward_in_expr(staff):
...     voice
Voice-"MusicVoice"{5}

```

Return generator.

voicetools.iterate_voices_backward_in_expr

abjad.tools.voicetools.**iterate_voices_backward_in_expr**(*expr*)

New in version 2.0. Iterate voices backward in *expr*:

```
abjad> voice_1 = Voice("c'8 d'8 e'8 f'8")
abjad> voice_2 = Voice("c'4 b4")
abjad> staff = Staff([voice_1, voice_2])
abjad> staff.is_parallel = True

abjad> f(staff)
\new Staff <<
  \new Voice {
    c'8
    d'8
    e'8
    f'8
  }
  \new Voice {
    c'4
    b4
  }
>>

abjad> for voice in voicetools.iterate_voices_backward_in_expr(staff):
...     voice
Voice{2}
Voice{4}
```

Return generator.

voicetools.iterate_voices_forward_in_expr

abjad.tools.voicetools.**iterate_voices_forward_in_expr**(*expr*)

New in version 2.0. Iterate voices forward in *expr*:

```
abjad> voice_1 = Voice("c'8 d'8 e'8 f'8")
abjad> voice_2 = Voice("c'4 b4")
abjad> staff = Staff([voice_1, voice_2])
abjad> staff.is_parallel = True

abjad> f(staff)
\new Staff <<
  \new Voice {
    c'8
    d'8
    e'8
    f'8
  }
  \new Voice {
    c'4
    b4
  }
>>

abjad> for voice in voicetools.iterate_voices_forward_in_expr(staff):
...     voice
```

```
Voice{4}
Voice{2}
```

Return generator.

57.1.2 Additional Abjad composition packages (load manually)

cfgtools

cfgtools.get_abjad_revision_string

```
abjad.tools.cfgtools.get_abjad_revision_string()
```

New in version 2.0. Get Abjad revision string:

```
abjad> cfgtools.get_abjad_revision_string() # doctest: +SKIP
'4392'
```

Return string.

cfgtools.get_abjad_version_string

```
abjad.tools.cfgtools.get_abjad_version_string()
```

New in version 2.0. Get Abjad version string:

```
abjad> from abjad.tools import cfgtools
```

```
abjad> cfgtools.get_abjad_version_string()
'2.2'
```

Return string.

cfgtools.get_lilypond_version_string

```
abjad.tools.cfgtools.get_lilypond_version_string()
```

New in version 2.0. Get LilyPond version string:

```
abjad> cfgtools.get_lilypond_version_string() # doctest: +SKIP
'2.13.61'
```

Return string.

cfgtools.get_python_version_string

```
abjad.tools.cfgtools.get_python_version_string()
```

New in version 2.0. Get Python version string:

```
abjad> from abjad.tools import cfgtools
```

```
abjad> cfgtools.get_python_version_string() # doctest: +SKIP
'2.6.1'
```

Return string.

cfgtools.list_abjad_environment_variables

`abjad.tools.cfgtools.list_abjad_environment_variables()`

New in version 1.1. List Abjad environment variables.

Return tuple of zero or more environment variable / setting pairs.

Abjad environment variables are defined in `abjad/cfg/cfg.py`. Changed in version 2.0: renamed `cfgtools.list_settings()` to `cfgtools.list_abjad_environment_variables()`.

cfgtools.list_abjad_templates

`abjad.tools.cfgtools.list_abjad_templates()`

New in version 2.0. List Abjad templates:

```
abjad> from abjad.tools import cfgtools
```

```
abjad> cfgtools.list_abjad_templates()  
('coventry.ly', 'lagos.ly', 'oedo.ly', 'paris.ly', 'tangiers.ly', 'thebes.ly', 'tirnaveni.ly')
```

Return tuple of zero or more strings.

Abjad templates are housed in `abjad/templates`.

cfgtools.set_default_accidental_spelling

`abjad.tools.cfgtools.set_default_accidental_spelling(spelling='mixed')`

New in version 1.1. Set default accidental spelling to sharps:

```
abjad> from abjad.tools import cfgtools
```

```
abjad> cfgtools.set_default_accidental_spelling('sharps')
```

```
abjad> [Note(13, (1, 4)), Note(15, (1, 4))]  
[Note("cs''4"), Note("ds''4")]
```

Set default accidental spelling to flats:

```
abjad> cfgtools.set_default_accidental_spelling('flats')
```

```
abjad> [Note(13, (1, 4)), Note(15, (1, 4))]  
[Note("df''4"), Note("ef''4")]
```

Set default accidental spelling to mixed:

```
abjad> cfgtools.set_default_accidental_spelling()
```

```
abjad> [Note(13, (1, 4)), Note(15, (1, 4))]  
[Note("cs''4"), Note("ef''4")]
```

Mixed is system default.

Mixed test case must appear last here for doc tests to check correctly.

Return none. Changed in version 2.0: renamed `pitchtools.change_default_accidental_spelling()` to `cfgtools.set_default_accidental_spelling()`.

durtools

durtools.Duration

class abjad.tools.durtools.**Duration**

Bases: fractions.Fraction New in version 2.0. Abjad model of musical duration:

```
abjad> Duration(15, 16)
Duration(15, 16)
```

Durations inherit from built-in Fraction.

durtools.Offset

class abjad.tools.durtools.**Offset**

Bases: abjad.tools.durtools.Duration.Duration New in version 2.0. Abjad model of offset value of musical time:

```
abjad> from abjad.tools import durtools

abjad> durtools.Offset(121, 16)
Offset(121, 16)
```

Offset inherits from duration (which inherits from built-in Fraction).

durtools.assignable_rational_to_dot_count

abjad.tools.durtools.**assignable_rational_to_dot_count** (*rational*)

New in version 2.0. Change assignable *rational* to dot count:

```
abjad> from abjad.tools import durtools

abjad> for n in range(1, 9):
...     try:
...         rational = Fraction(n, 16)
...         dot_count = durtools.assignable_rational_to_dot_count(rational)
...         print '%s\t%s' % (rational, dot_count)
...     except AssignabilityError:
...         pass
...
1/16    0
1/8     0
3/16    1
1/4     0
3/8     1
7/16    2
1/2     0
```

Raise assignability error when *rational* not assignable.

Return nonnegative integer.

durtools.assignable_rational_to_lilypond_duration_string

abjad.tools.durtools.**assignable_rational_to_lilypond_duration_string** (*rational*)

New in version 2.0. Change assignable *rational* to LilyPond duration string:

```
abjad> from abjad.tools import durtools

abjad> durtools.assignable_rational_to_lilypond_duration_string(Fraction(3, 16))
'8.'
```

Raise assignability error when *rational* not assignable.

Return string.

`durtools.duration_pair_to_prolation_string`

`abjad.tools.durtools.duration_pair_to_prolation_string(pair)`
 New in version 2.0. Change positive integer duration *pair* to colon-separated prolation string:

```
abjad> from abjad.tools import durtools

abjad> durtools.duration_pair_to_prolation_string((2, 3))
'3:2'
```

Return string.

`durtools.duration_token_to_big_endian_list_of_assignable_duration_pairs`

`abjad.tools.durtools.duration_token_to_big_endian_list_of_assignable_duration_pairs(duration_token)`
 New in version 1.1. Change *duration_token* to big-endian tuple of assignable duration pairs:

```
abjad> from abjad.tools import durtools

abjad> duration_tokens = [(n, 16) for n in range(10, 20)]
abjad> for duration_token in duration_tokens:
...     print duration_token, durtools.duration_token_to_big_endian_list_of_assignable_duration_
...
(10, 16) ((8, 16), (2, 16))
(11, 16) ((8, 16), (3, 16))
(12, 16) ((12, 16),)
(13, 16) ((12, 16), (1, 16))
(14, 16) ((14, 16),)
(15, 16) ((15, 16),)
(16, 16) ((16, 16),)
(17, 16) ((16, 16), (1, 16))
(18, 16) ((16, 16), (2, 16))
(19, 16) ((16, 16), (3, 16))
```

Return tuple of integer pairs. Changed in version 2.0: renamed `durtools.token_decompose()` to `durtools.duration_token_to_big_endian_list_of_assignable_duration_pairs()`.

`durtools.duration_token_to_duration_pair`

`abjad.tools.durtools.duration_token_to_duration_pair(duration_token)`
 New in version 1.1. Change *duration_token* to duration pair:

```
abjad> from abjad.tools import durtools

abjad> durtools.duration_token_to_duration_pair(Fraction(2, 4))
(1, 2)
```

New in version 2.0: Change LilyPond duration string to duration pair:

```
abjad> durtools.duration_token_to_duration_pair('8.')
(3, 16)
```

Return pair. Changed in version 2.0: renamed `durtools.token_unpack()` to `durtools.duration_token_to_duration_pair()`.

`durtools.duration_token_to_rational`

`abjad.tools.durtools.duration_token_to_rational(duration_token)`

New in version 2.0. Change *duration_token* to rational:

```
abjad> from abjad.tools import durtools

abjad> durtools.duration_token_to_rational((4, 16))
Fraction(1, 4)

abjad> durtools.duration_token_to_rational('4.')
Fraction(3, 8)
```

Return fraction.

`durtools.duration_tokens_to_duration_pairs`

`abjad.tools.durtools.duration_tokens_to_duration_pairs(duration_tokens)`

New in version 2.0. Change *duration_tokens* to duration pairs:

```
abjad> from abjad.tools import durtools

abjad> durtools.duration_tokens_to_duration_pairs([Fraction(2, 4), 3, '8.', (5, 16)])
[(1, 2), (3, 1), (3, 16), (5, 16)]
```

Return new object of *duration_tokens* type.

`durtools.duration_tokens_to_duration_pairs_with_least_common_denominator`

`abjad.tools.durtools.duration_tokens_to_duration_pairs_with_least_common_denominator(duration_tokens)`

New in version 2.0. Change *duration_tokens* to duration pairs with least common denominator:

```
abjad> from abjad.tools import durtools

abjad> durtools.duration_tokens_to_duration_pairs_with_least_common_denominator([Fraction(2, 4),
[(8, 16), (48, 16), (3, 16), (5, 16)]
```

Return new object of *duration_tokens* type.

`durtools.duration_tokens_to_least_common_denominator`

`abjad.tools.durtools.duration_tokens_to_least_common_denominator(duration_tokens)`

New in version 2.0. Change *duration_tokens* to least common denominator:

```
abjad> from abjad.tools import durtools
```

```
abjad> durtools.duration_tokens_to_least_common_denominator([Fraction(2, 4), 3, '8.', (5, 16)])
16
```

Return positive integer.

`durtools.duration_tokens_to_rationals`

`abjad.tools.durtools.duration_tokens_to_rationals` (*duration_tokens*)

New in version 2.0. Change *duration_tokens* to rationals:

```
abjad> from abjad.tools import durtools

abjad> durtools.duration_tokens_to_rationals([Fraction(2, 4), 3, '8.', (5, 16)])
[Fraction(1, 2), Fraction(3, 1), Fraction(3, 16), Fraction(5, 16)]
```

Return new object of *duration_tokens* type.

`durtools.group_duration_tokens_by_implied_prolation`

`abjad.tools.durtools.group_duration_tokens_by_implied_prolation` (*durations*)

New in version 1.1. Group *durations* by implied prolation:

```
abjad> from abjad.tools import durtools

abjad> durtools.group_duration_tokens_by_implied_prolation([(1, 4), (1, 8), (1, 3), (1, 6), (1,
[[ (1, 4), (1, 8)], [(1, 3), (1, 6)], [(1, 4)]]
```

Return list of integer pair lists. Changed in version 2.0: renamed `durtools.agglomerate_by_prolation()` to `durtools.group_duration_tokens_by_implied_prolation()`

`durtools.is_assignable_rational`

`abjad.tools.durtools.is_assignable_rational` (*expr*)

New in version 1.1. True when *expr* is assignable rational. Otherwise false:

```
abjad> from abjad.tools import durtools

abjad> for numerator in range(0, 16 + 1):
...     duration = Fraction(numerator, 16)
...     print '%s\t%s' % (duration, durtools.is_assignable_rational(duration))
...
0      False
1/16   True
1/8    True
3/16   True
1/4    True
5/16   False
3/8    True
7/16   True
1/2    True
9/16   False
5/8    False
11/16  False
3/4    True
13/16  False
```



```

7/8    True
15/16  True
1      True

```

Return boolean. Changed in version 2.0: renamed `durtools.is_assignable()` to `durtools.is_assignable_rational()`.

`durtools.is_binary_rational`

`abjad.tools.durtools.is_binary_rational(rational)`

New in version 1.1. True when *rational* is of the form $1/2**n$. Otherwise false:

```

abjad> from abjad.tools import durtools

abjad> for n in range(1, 17): # doctest: +SKIP
...     rational = Fraction(1, n)
...     print '%s\t%s' % (rational, durtools.is_binary_rational(rational))
...
1      True
1/2    True
1/3    False
1/4    True
1/5    False
1/6    False
1/7    False
1/8    True
1/9    False
1/10   False
1/11   False
1/12   False
1/13   False
1/14   False
1/15   False
1/16   True

```

Return boolean.

`durtools.is_duration_pair`

`abjad.tools.durtools.is_duration_pair(arg)`

New in version 1.1. True when *arg* has the form of a pair of integers that initialize a positive rational:

```

abjad> from abjad.tools import durtools

abjad> durtools.is_duration_pair((5, 16))
True

```

Otherwise false:

```

abjad> durtools.is_duration_pair((-5, 16))
False

```

Return boolean. Changed in version 2.0: renamed `durtools.is_pair()` to `durtools.is_duration_pair()`.

`durtools.is_duration_token`

`abjad.tools.durtools.is_duration_token(expr)`

New in version 2.0. True when *expr* has the form of an Abjad duration pair:

```
abjad> from abjad.tools import durtools
```

```
abjad> durtools.is_duration_token('8.')
```

```
True
```

Otherwise false:

```
abjad> durtools.is_duration_token('foo')
```

```
False
```

Return boolean.

`durtools.is_lilypond_duration_name`

`abjad.tools.durtools.is_lilypond_duration_name(expr)`

New in version 2.0. True when *expr* is a LilyPond duration name:

```
abjad> from abjad.tools import durtools
```

```
abjad> durtools.is_lilypond_duration_name('\\breve')
```

```
True
```

Otherwise false:

```
abjad> durtools.is_lilypond_duration_name('foo')
```

```
False
```

The regex `^(\\breve|\\longa|\\maxima)$` underlies this predicate.

Return boolean.

`durtools.is_lilypond_duration_string`

`abjad.tools.durtools.is_lilypond_duration_string(expr)`

New in version 2.0. True when *expr* is a LilyPond duration string:

```
abjad> from abjad.tools import durtools
```

```
abjad> durtools.is_lilypond_duration_string('4.. * 1/2')
```

```
True
```

Otherwise false:

```
abjad> durtools.is_lilypond_duration_string('foo')
```

```
False
```

The regex `^(1|2|4|8|16|32|64|128|\\breve|\\longa|\\maxima)\\s*(\\.*)\\s*(*\\s*(\\d+(/\\d+)?)?)?$` underlies this predicate.

Return boolean.

durtools.lilypond_duration_string_to_rational

`abjad.tools.durtools.lilypond_duration_string_to_rational` (*duration_string*)
 New in version 2.0. Change LilyPond *duration_string* to rational:

```
abjad> from abjad.tools import durtools

abjad> durtools.lilypond_duration_string_to_rational('8.')
Fraction(3, 16)
```

Return fraction.

durtools.lilypond_duration_string_to_rational_list

`abjad.tools.durtools.lilypond_duration_string_to_rational_list` (*duration_string*)
 New in version 2.0. Change LilyPond *duration_string* to rational list:

```
abjad> from abjad.tools import durtools

abjad> durtools.lilypond_duration_string_to_rational_list('8.. 32 8.. 32')
[Fraction(7, 32), Fraction(1, 32), Fraction(7, 32), Fraction(1, 32)]
```

Return list of fractions.

durtools.multiply_duration_pair

`abjad.tools.durtools.multiply_duration_pair` (*pair*, *multiplier*)
 New in version 1.1. Multiply duration *pair* by rational *multiplier*:

```
abjad> from abjad.tools import durtools

abjad> durtools.multiply_duration_pair((4, 8), Fraction(4, 5))
(16, 40)
```

Naive multiplication with no simplification of anything intended for certain types of meter multiplication.

Return integer pair. Changed in version 2.0: renamed `durtools.pair_multiply_naive()` to `durtools.multiply_duration_pair()`.

durtools.multiply_duration_pair_and_reduce_factors

`abjad.tools.durtools.multiply_duration_pair_and_reduce_factors` (*pair*, *multiplier*)
 New in version 1.1. Multiply *pair* by rational *multiplier* and reduce factors:

```
abjad> from abjad.tools import durtools

abjad> durtools.multiply_duration_pair_and_reduce_factors((4, 8), Fraction(2, 3))
(4, 12)
```

Intended for certain types of meter multiplication.

Return integer pair. Changed in version 2.0: renamed `durtools.pair_multiply_reduce_factors()` to `durtools.multiply_duration_pair_and_reduce_factors()`.

`durtools.multiply_duration_pair_and_try_to_preserve_numerator`

`abjad.tools.durtools.multiply_duration_pair_and_try_to_preserve_numerator(pair, multiplier)`

New in version 1.1. Multiply duration *pair* by rational *multiplier* and try to preserve numerator:

```
abjad> from abjad.tools import durtools

abjad> durtools.multiply_duration_pair_and_try_to_preserve_numerator((9, 16), Fraction(2, 3))
(9, 24)
```

Intended for certain types of meter multiplication.

Return integer pair. Changed in version 2.0: renamed `durtools.pair_multiply_constant_numerator()` to `durtools.multiply_duration_pair_and_try_to_preserve_numerator()`.

`durtools.numeric_seconds_to_clock_string`

`abjad.tools.durtools.numeric_seconds_to_clock_string(seconds)`

New in version 2.0. Change numeric *seconds* to clock string:

```
abjad> from abjad.tools import durtools

abjad> durtools.numeric_seconds_to_clock_string(117)
'1\57'
```

Return string.

`durtools.numeric_seconds_to_escaped_clock_string`

`abjad.tools.durtools.numeric_seconds_to_escaped_clock_string(seconds)`

New in version 2.0. Change numeric *seconds* to escaped clock string:

```
abjad> from abjad.tools import durtools

abjad> note = Note("c'4")
abjad> clock_string = durtools.numeric_seconds_to_escaped_clock_string(117)
abjad> markuptools.Markup('%s' % clock_string, 'up')(note)
Markup('"1\57\\', 'up')

abjad> f(note)
c'4 ^ \markup { "1'57\" }
```

Escape seconds indicator for output as LilyPond markup.

Return string.

`durtools.positive_integer_to_implied_prolation_multiplier`

`abjad.tools.durtools.positive_integer_to_implied_prolation_multiplier(n)`

New in version 1.1. Change positive integer *n* to implied porlation multiplier:

```
abjad> from abjad.tools import durtools
```

```

abjad> for denominator in range(1, 17): # doctest: +SKIP
...     multiplier = durtools.positive_integer_to_implied_prolation_multiplier(denominator)
...     print '%s\t%s' % (denominator, multiplier)
...
1         1
2         1
3         2/3
4         1
5         4/5
6         2/3
7         4/7
8         1
9         8/9
10        4/5
11        8/11
12        2/3
13        8/13
14        4/7
15        8/15
16        1

```

Return positive fraction less than or equal to 1. Changed in version 2.0: renamed `durtools.denominator_to_multiplier()` to `durtools.positive_integer_to_implied_prolation_multiplier()`.

`durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator`

`abjad.tools.durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator`

Change *duration* to duration pair with multiple of specified *integer_denominator*:

```

abjad> from abjad.tools import durtools

abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(1, 2))
abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(2, 4))
abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(4, 8))
abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(8, 16))

abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(3, 6))
abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(3, 6))
abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(6, 12))
abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(12, 24))

abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(5, 10))
abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(5, 10))

```

```
abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(
(10, 20)
abjad> durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator(Fraction(
(20, 40)
```

Return integer pair. Changed in version 2.0: renamed `durtools.in_terms_of_binary_multiple()` to `durtools.rational_to_duration_pair_with_multiple_of_specified_integer_denominator()`.

`durtools.rational_to_duration_pair_with_specified_integer_denominator`

`abjad.tools.durtools.rational_to_duration_pair_with_specified_integer_denominator` (*duration*, *integer_denominator*)

New in version 1.1. Change *duration* to duration pair with specified *integer_denominator*:

```
abjad> from abjad.tools import durtools

abjad> for n in range(1, 17):
...     rational = Fraction(n, 16)
...     pair = durtools.rational_to_duration_pair_with_specified_integer_denominator(rational, 16)
...     print '%s\t%s' % (rational, pair)
...
1/16      (1, 16)
1/8       (2, 16)
3/16      (3, 16)
1/4       (4, 16)
5/16      (5, 16)
3/8       (6, 16)
7/16      (7, 16)
1/2       (8, 16)
9/16      (9, 16)
5/8       (10, 16)
11/16     (11, 16)
3/4       (12, 16)
13/16     (13, 16)
7/8       (14, 16)
15/16     (15, 16)
1         (16, 16)
```

Return integer pair. Changed in version 2.0: renamed `durtools.in_terms_of()` to `durtools.rational_to_duration_pair_with_specified_integer_denominator()`.

`durtools.rational_to_equal_or_greater_assignable_rational`

`abjad.tools.durtools.rational_to_equal_or_greater_assignable_rational` (*rational*)

New in version 1.1. Change *rational* to equal or greater assignable rational:

```
abjad> from abjad.tools import durtools

abjad> for n in range(1, 17): # doctest: +SKIP
...     prolated = Fraction(n, 16)
...     written = durtools.rational_to_equal_or_greater_assignable_rational(prolated)
...     print '%s/16\t%s' % (n, written)
...
1/16      1/16
```

2/16	1/8
3/16	3/16
4/16	1/4
5/16	3/8
6/16	3/8
7/16	7/16
8/16	1/2
9/16	3/4
10/16	3/4
11/16	3/4
12/16	3/4
13/16	7/8
14/16	7/8
15/16	15/16
16/16	1

Return fraction.

Function returns dotted and double dotted durations where possible. Changed in version 2.0: Fixed to produce monotonically increasing output in response to monotonically increasing input. Changed in version 2.0: renamed `durtools.prolated_to_written_not_less_than()` to `durtools.rational_to_equal_or_greater_assignable_rational()`.

`durtools.rational_to_equal_or_greater_binary_rational`

`abjad.tools.durtools.rational_to_equal_or_greater_binary_rational(rational)`

New in version 1.1. Change *rational* to equal to greater binary rational:

```
abjad> from abjad.tools import durtools

abjad> for n in range(1, 17): # doctest: +SKIP
...     rational = Fraction(n, 16)
...     written_duration = durtools.rational_to_equal_or_greater_binary_rational(rational)
...     print '%s/16\t%s' % (n, written_duration)
...
1/16    1/16
2/16    1/8
3/16    1/4
4/16    1/4
5/16    1/2
6/16    1/2
7/16    1/2
8/16    1/2
9/16    1
10/16   1
11/16   1
12/16   1
13/16   1
14/16   1
15/16   1
16/16   1

abjad> durtools.rational_to_equal_or_greater_binary_rational(Fraction(1, 80))
Fraction(1, 64)

abjad> durtools.rational_to_equal_or_greater_binary_rational(Fraction(17, 16))
Fraction(2, 1)
```

Use to find written duration of tupletted leaves.

Return fraction. Changed in version 2.0: renamed `durtools.naive_prolated_to_written_not_less_than()` to `durtools.rational_to_equal_or_greater_binary_rational()`.

`durtools.rational_to_equal_or_lesser_assignable_rational`

`abjad.tools.durtools.rational_to_equal_or_lesser_assignable_rational(rational)`

New in version 1.1. Change *rational* to equal or lesser assignable rational:

```
abjad> from abjad.tools import durtools

abjad> for n in range(1, 17): # doctest: +SKIP
...     rational = Fraction(n, 16)
...     written = durtools.rational_to_equal_or_lesser_assignable_rational(rational)
...     print '%s/16\t%s' % (n, written)
...
1/16    1/16
2/16    1/8
3/16    3/16
4/16    1/4
5/16    1/4
6/16    3/8
7/16    7/16
8/16    1/2
9/16    1/2
10/16   1/2
11/16   1/2
12/16   3/4
13/16   3/4
14/16   7/8
15/16   15/16
16/16   1
```

Return fraction.

Function returns dotted and double dotted durations where possible. Changed in version 2.0: Fixed to produce monotonically increasing output in response to monotonically increasing input. Changed in version 2.0: renamed `durtools.prolated_to_written_not_greater_than()` to `durtools.rational_to_equal_or_lesser_assignable_rational()`.

`durtools.rational_to_equal_or_lesser_binary_rational`

`abjad.tools.durtools.rational_to_equal_or_lesser_binary_rational(rational)`

New in version 1.1. Change *rational* to equal or lesser binary rational:

```
abjad> from abjad.tools import durtools

abjad> for n in range(1, 17): # doctest: +SKIP
...     rational = Fraction(n, 16)
...     written_duration = durtools.rational_to_equal_or_lesser_binary_rational(rational)
...     print '%s/16\t%s' % (n, written_duration)
...
1/16    1/16
2/16    1/8
3/16    1/8
4/16    1/4
```


5/16	1/4
6/16	1/4
7/16	1/4
8/16	1/2
9/16	1/2
10/16	1/2
11/16	1/2
12/16	1/2
13/16	1/2
14/16	1/2
15/16	1/2
16/16	1

```
abjad> durtools.rational_to_equal_or_lesser_binary_rational(Fraction(1, 80))
Fraction(1, 128)
```

Return fraction.

Function intended to find written duration of notes inside tuplet. Changed in version 2.0: renamed `durtools.naive_prolated_to_written_not_greater_than()` to `durtools.rational_to_equal_or_lesser_binary_rational()`.

`durtools.rational_to_flag_count`

`abjad.tools.durtools.rational_to_flag_count(rational)`

New in version 2.0. Change *rational* to number of flags required to notate:

```
abjad> from abjad.tools import durtools

abjad> durtools.rational_to_flag_count(Fraction(1, 32))
3
```

Return nonnegative integer.

`durtools.rational_to_fraction_string`

`abjad.tools.durtools.rational_to_fraction_string(rational)`

New in version 1.1. Change *rational* to fraction string:

```
abjad> from abjad.tools import durtools

abjad> durtools.rational_to_fraction_string(Fraction(2, 4))
'1/2'
```

Return string.

`durtools.rational_to_prolation_string`

`abjad.tools.durtools.rational_to_prolation_string(rational)`

New in version 2.0. Change *rational* to prolation string:

```
abjad> from abjad.tools import durtools
```

```

abjad> generator = durtools.yield_all_positive_rationals_in_cantor_diagonalized_order_uniquely()
abjad> for n in range(16): # doctest: +SKIP
...     rational = generator.next()
...     prolation_string = durtools.rational_to_prolation_string(rational)
...     print '%s\\t%s' % (rational, prolation_string)
...
1         1:1
2         1:2
1/2       2:1
1/3       3:1
3         1:3
4         1:4
3/2       2:3
2/3       3:2
1/4       4:1
1/5       5:1
5         1:5
6         1:6
5/2       2:5
4/3       3:4
3/4       4:3
2/5       5:2

```

Return string.

`durtools.rational_to_proper_fraction`

`abjad.tools.durtools.rational_to_proper_fraction(rational)`

New in version 2.0. Change *rational* to proper fraction:

```

abjad> from abjad.tools import durtools

abjad> durtools.rational_to_proper_fraction(Fraction(116, 8))
(14, Fraction(1, 2))

```

Return pair.

`durtools.rewrite_rational_under_new_tempo`

`abjad.tools.durtools.rewrite_rational_under_new_tempo(prolated_duration_1, tempo_mark_1, tempo_mark_2)`

New in version 2.0. Given *prolated_duration_1* governed by *tempo_mark_1*, return *prolated_duration_2* governed by *tempo_mark_2* such that *prolated_duration_1* and *prolated_duration_2* consume exactly the same amount of time in seconds.

Consider the two tempo indications below.

```

abjad> from abjad.tools import durtools

abjad> tempo_mark_1 = contexttools.TempoMark(Duration(1, 4), 60)
abjad> tempo_mark_2 = contexttools.TempoMark(Duration(1, 4), 90)

```

The first tempo indication specifies quarter = 60 MM. The second tempo indication specifies quarter = 90 MM.

The second tempo is 1 1/2 times as fast as the first.

```
abjad> tempo_mark_2 / tempo_mark_1
Duration(3, 2)
```

An triplet eighth note at tempo 1 equals a regular eighth note at tempo 2.

```
abjad> durtools.rewrite_rational_under_new_tempo(Duration(1, 12), tempo_mark_1, tempo_mark_2)
Duration(1, 8)
```

Conversely, a regular eighth note at tempo 1 equals a dotted sixteenth at tempo 2.

```
abjad> durtools.rewrite_rational_under_new_tempo(Duration(1, 8), tempo_mark_1, tempo_mark_2)
Duration(3, 16)
```

Return fraction.

`durtools.yield_all_assignable_rationals_in_cantor_diagonalized_order`

`abjad.tools.durtools.yield_all_assignable_rationals_in_cantor_diagonalized_order()`
 New in version 2.0. Yield all assignable rationals in Cantor diagonalized order:

```
abjad> from abjad.tools import durtools

abjad> generator = durtools.yield_all_assignable_rationals_in_cantor_diagonalized_order()
abjad> for n in range(16):
...     generator.next()
...
Fraction(1, 1)
Fraction(2, 1)
Fraction(1, 2)
Fraction(3, 1)
Fraction(4, 1)
Fraction(3, 2)
Fraction(1, 4)
Fraction(6, 1)
Fraction(3, 4)
Fraction(7, 1)
Fraction(8, 1)
Fraction(7, 2)
Fraction(1, 8)
Fraction(7, 4)
Fraction(3, 8)
Fraction(12, 1)
```

Return fraction generator.

`durtools.yield_all_positive_integer_pairs_in_cantor_diagonalized_order`

`abjad.tools.durtools.yield_all_positive_integer_pairs_in_cantor_diagonalized_order()`
 New in version 2.0. Yield all positive integer pairs in Cantor diagonalized order:

```
abjad> from abjad.tools import durtools

abjad> generator = durtools.yield_all_positive_integer_pairs_in_cantor_diagonalized_order()
abjad> for n in range(16):
...     generator.next()
...
(1, 1)
```

```
(2, 1)
(1, 2)
(1, 3)
(2, 2)
(3, 1)
(4, 1)
(3, 2)
(2, 3)
(1, 4)
(1, 5)
(2, 4)
(3, 3)
(4, 2)
(5, 1)
(6, 1)
```

Return pair generator.

durtools.yield_all_positive_rationals_in_cantor_diagonalized_order

`abjad.tools.durtools.yield_all_positive_rationals_in_cantor_diagonalized_order()`

New in version 2.0. Yield all positive rationals in Cantor diagonalized order:

```
abjad> from abjad.tools import durtools

abjad> generator = durtools.yield_all_positive_rationals_in_cantor_diagonalized_order()
abjad> for n in range(16):
...     generator.next()
...
Fraction(1, 1)
Fraction(2, 1)
Fraction(1, 2)
Fraction(1, 3)
Fraction(1, 1)
Fraction(3, 1)
Fraction(4, 1)
Fraction(3, 2)
Fraction(2, 3)
Fraction(1, 4)
Fraction(1, 5)
Fraction(1, 2)
Fraction(1, 1)
Fraction(2, 1)
Fraction(5, 1)
Fraction(6, 1)
```

Return fraction generator.

durtools.yield_all_positive_rationals_in_cantor_diagonalized_order_uniquely

`abjad.tools.durtools.yield_all_positive_rationals_in_cantor_diagonalized_order_uniquely()`

New in version 2.0. Yield all positive rationals in Cantor diagonalized order uniquely:

```
abjad> from abjad.tools import durtools
```

```

abjad> generator = durtools.yield_all_positive_rationals_in_cantor_diagonalized_order_uniquely()
abjad> for n in range(16):
...     generator.next()
...
Fraction(1, 1)
Fraction(2, 1)
Fraction(1, 2)
Fraction(1, 3)
Fraction(3, 1)
Fraction(4, 1)
Fraction(3, 2)
Fraction(2, 3)
Fraction(1, 4)
Fraction(1, 5)
Fraction(5, 1)
Fraction(6, 1)
Fraction(5, 2)
Fraction(4, 3)
Fraction(3, 4)
Fraction(2, 5)

```

Return fraction generator.

`durtools.yield_all_prolation_rewrite_pairs_of_rational_in_cantor_diagonalized_order`

```
abjad.tools.durtools.yield_all_prolation_rewrite_pairs_of_rational_in_cantor_diagonalized_order
```

New in version 2.0. Yield all prolation rewrite pairs of *prolated_duration* in Cantor diagonalized order.

Ensure written duration never less than *minimum_written_duration*.

The different ways to notate a prolated duration of $1/8$:

```

abjad> from abjad.tools import durtools

abjad> pairs = durtools.yield_all_prolation_rewrite_pairs_of_rational_in_cantor_diagonalized_order(1/8)
abjad> for pair in pairs: pair
...
(Fraction(1, 1), Fraction(1, 8))
(Fraction(2, 3), Fraction(3, 16))
(Fraction(4, 3), Fraction(3, 32))
(Fraction(4, 7), Fraction(7, 32))
(Fraction(8, 7), Fraction(7, 64))
(Fraction(8, 15), Fraction(15, 64))
(Fraction(16, 15), Fraction(15, 128))
(Fraction(16, 31), Fraction(31, 128))

```

The different ways to notate a prolated duration of $1/12$.

```

abjad> pairs = durtools.yield_all_prolation_rewrite_pairs_of_rational_in_cantor_diagonalized_order(1/12)
abjad> for pair in pairs: pair
...
(Fraction(2, 3), Fraction(1, 8))
(Fraction(4, 3), Fraction(1, 16))
(Fraction(8, 9), Fraction(3, 32))

```

```
(Fraction(16, 9), Fraction(3, 64))
(Fraction(16, 21), Fraction(7, 64))
(Fraction(32, 21), Fraction(7, 128))
(Fraction(32, 45), Fraction(15, 128))
```

The different ways to notate a prolated duration of $5/48$.

```
abjad> pairs = durtools.yield_all_prolation_rewrite_pairs_of_rational_in_cantor_diagonalized_order
abjad> for pair in pairs: pair
...
(Fraction(5, 6), Fraction(1, 8))
(Fraction(5, 3), Fraction(1, 16))
(Fraction(5, 9), Fraction(3, 16))
(Fraction(10, 9), Fraction(3, 32))
(Fraction(20, 21), Fraction(7, 64))
(Fraction(40, 21), Fraction(7, 128))
(Fraction(8, 9), Fraction(15, 128))
```

Return generator of paired fractions.

intervaltreertools

intervaltreertools.BoundedInterval

```
class abjad.tools.intervaltreertools.BoundedInterval(*args)
    Bases: dict, abjad.core._Immutable._Immutable._Immutable

    A low / high pair, carrying some metadata.

    centroid
        Center point of low and high bounds.

    get_overlap_with_interval(interval)
        Return amount of overlap with interval.

    high
        High bound.

    is_contained_by_interval(interval)
        True if interval is contained by interval.

    is_container_of_interval(interval)
        True if interval contains interval.

    is_overlapped_by_interval(interval)
        True if interval is overlapped by interval.

    is_tangent_to_interval(interval)
        True if interval is tangent to interval.

    low
        Low bound.

    magnitude
        High bound minus low bound.

    scale_by_rational(rational)

    scale_to_rational(rational)

    shift_by_rational(rational)
```

shift_to_rational (*rational*)

signature

Tuple of low bound and high bound.

split_at_rational (*rational*)

intervaltreetools.IntervalTree

class abjad.tools.intervaltreetools.**IntervalTree** (*intervals=[]*)

Bases: abjad.tools.intervaltreetools._RedBlackTree._RedBlackTree._RedBlackTree

An augmented red-black tree for storing and searching for intervals of time (rather than pitch).

This allows for the arbitrary placement of blocks of material along a time-line. While this functionality could be achieved with Python's built-in collections, this class reduces the complexity of the search process, such as locating overlapping intervals.

IntervalTrees can be instantiated without contents, or from a mixed collection of other IntervalTrees and / or BoundedIntervals. The input will be parsed recursively

```
abjad> from abjad.tools.intervaltreetools import IntervalTree
abjad> from abjad.tools.intervaltreetools import BoundedInterval
abjad> bi = BoundedInterval(0, 10)
abjad> tree = IntervalTree([bi])
```

bounds

The lowest and highest values of the tree returned as a BoundedInterval.

find_intervals_intersecting_or_tangent_to_interval (**args*)

find_intervals_intersecting_or_tangent_to_offset (*offset*)

find_intervals_starting_after_offset (*offset*)

find_intervals_starting_and_stopping_within_interval (**args*)

find_intervals_starting_at_offset (*offset*)

find_intervals_starting_before_offset (*offset*)

find_intervals_starting_or_stopping_at_offset (*offset*)

find_intervals_starting_within_interval (**args*)

find_intervals_stopping_after_offset (*offset*)

find_intervals_stopping_at_offset (*offset*)

find_intervals_stopping_before_offset (*offset*)

find_intervals_stopping_within_interval (**args*)

high

The maximum high value of all intervals in the tree. Alias of high_max.

high_max

The maximum high value of all intervals in the tree.

high_min

The minimum high value of all intervals in the tree.

low

The minimum low value of all intervals in the tree. Alias of low_min.

low_max

The maximum low value of all intervals in the tree.

low_min

The minimum low value of all intervals in the tree.

magnitude

Absolute difference of the high and low values of the tree.

intervaltreertools.all_are_intervals_or_trees_or_empty

`abjad.tools.intervaltreertools.all_are_intervals_or_trees_or_empty(input)`

Recursively test if all elements of *input* are BoundedIntervals or IntervalTrees. An empty result also return as True.

intervaltreertools.all_intervals_are_contiguous

`abjad.tools.intervaltreertools.all_intervals_are_contiguous(intervals)`

True when all intervals in *intervals* are contiguous and non-overlapping.

intervaltreertools.all_intervals_are_nonoverlapping

`abjad.tools.intervaltreertools.all_intervals_are_nonoverlapping(intervals)`

True when all intervals in *intervals* in tree are non-overlapping.

intervaltreertools.calculate_density_of_attacks_in_interval

`abjad.tools.intervaltreertools.calculate_density_of_attacks_in_interval(intervals,
in-
ter-
val)`

Return a Fraction of number of attacks in *interval* over the magnitude of *interval*.

intervaltreertools.calculate_density_of_releases_in_interval

`abjad.tools.intervaltreertools.calculate_density_of_releases_in_interval(intervals,
in-
ter-
val)`

Return a Fraction of the number of releases in *interval* divided by the magnitude of *interval*.

intervaltreertools.calculate_depth_centroid_of_intervals

`abjad.tools.intervaltreertools.calculate_depth_centroid_of_intervals(intervals)`

Return a weighted mean, such that the centroids of each interval in the depth tree of *intervals* are the values, and the depth of each interval in the depth tree of *intervals* are the weights.

intervaltreertools.calculate_depth_centroid_of_intervals_in_interval

`abjad.tools.intervaltreertools.calculate_depth_centroid_of_intervals_in_interval` (*intervals*, *interval*)

Return the weighted mean of the depth tree of *intervals* in *interval*, such that the centroids of each interval of the depth tree are the values, and the weights are the depths at each interval of the depth tree.

intervaltreertools.calculate_depth_density_of_intervals

`abjad.tools.intervaltreertools.calculate_depth_density_of_intervals` (*intervals*)

Return a Fraction, of the magnitude of each interval in the depth tree of *intervals*, multiplied by the depth at that interval, divided by the overall magnitude of *intervals*.

The depth density of a single interval is 1

```
abjad> from abjad.tools import intervaltreertools
abjad> from abjad.tools.intervaltreertools import BoundedInterval
abjad> from abjad.tools.intervaltreertools import IntervalTree

abjad> a = BoundedInterval(0, 1)
abjad> b = BoundedInterval(0, 1)
abjad> c = BoundedInterval(Fraction(1, 2), 1)
abjad> intervaltreertools.calculate_depth_density_of_intervals(a)
Duration(1, 1)
abjad> intervaltreertools.calculate_depth_density_of_intervals([a, b])
Duration(2, 1)
abjad> intervaltreertools.calculate_depth_density_of_intervals([a, c])
Duration(3, 2)
abjad> intervaltreertools.calculate_depth_density_of_intervals([a, b, c])
Duration(5, 2)
```

Return fraction.

intervaltreertools.calculate_depth_density_of_intervals_in_interval

`abjad.tools.intervaltreertools.calculate_depth_density_of_intervals_in_interval` (*intervals*, *interval*)

Return a Fraction, of the magnitude of each interval in the depth tree of *intervals* within *interval*, multiplied by the depth at that interval, divided by the overall magnitude of *intervals*.

intervaltreertools.calculate_mean_attack_of_intervals

`abjad.tools.intervaltreertools.calculate_mean_attack_of_intervals` (*intervals*)

Return Fraction of the average attack offset of *intervals*

intervaltreertools.calculate_mean_release_of_intervals

`abjad.tools.intervaltreertools.calculate_mean_release_of_intervals` (*intervals*)

Return a Fraction of the average release offset of *intervals*.

`intervaltreertools.calculate_min_mean_and_max_depth_of_intervals`

`abjad.tools.intervaltreertools.calculate_min_mean_and_max_depth_of_intervals` (*intervals*)
 Return a 3-tuple of the minimum, mean and maximum depth of *intervals*. If *intervals* is empty, return None.
 “Mean” in this case is a weighted mean, where the magnitudes of the intervals in depth tree of *intervals* are the weights

`intervaltreertools.calculate_min_mean_and_max_magnitude_of_intervals`

`abjad.tools.intervaltreertools.calculate_min_mean_and_max_magnitude_of_intervals` (*intervals*)
 Return a 3-tuple of the minimum, mean and maximum magnitude of all intervals in *intervals*. If *intervals* is empty, return None.

`intervaltreertools.calculate_sustain_centroid_of_intervals`

`abjad.tools.intervaltreertools.calculate_sustain_centroid_of_intervals` (*intervals*)
 Return a weighted mean, such that the centroid of each interval in *intervals* are the values, and the weights are their magnitudes.

`intervaltreertools.clip_interval_magnitudes_to_range`

`abjad.tools.intervaltreertools.clip_interval_magnitudes_to_range` (*intervals*,
min=None,
max=None)

`intervaltreertools.compute_depth_of_intervals`

`abjad.tools.intervaltreertools.compute_depth_of_intervals` (*intervals*)
 Compute a tree whose intervals represent the depth (level of overlap) in each boundary pair of *intervals*:

```
abjad> from abjad.tools.intervaltreertools import *
abjad> a = BoundedInterval(0, 3)
abjad> b = BoundedInterval(6, 12)
abjad> c = BoundedInterval(9, 15)
abjad> tree = IntervalTree([a, b, c])
abjad> compute_depth_of_intervals(tree)
IntervalTree([
    BoundedInterval(Offset(0, 1), Offset(3, 1), {'depth': 1}),
    BoundedInterval(Offset(3, 1), Offset(6, 1), {'depth': 0}),
    BoundedInterval(Offset(6, 1), Offset(9, 1), {'depth': 1}),
    BoundedInterval(Offset(9, 1), Offset(12, 1), {'depth': 2}),
    BoundedInterval(Offset(12, 1), Offset(15, 1), {'depth': 1})
])
```

Return interval tree.

`intervaltreertools.compute_depth_of_intervals_in_interval`

`abjad.tools.intervaltreertools.compute_depth_of_intervals_in_interval` (*intervals*,
inter-
val)
interval)
 Compute a tree whose intervals represent the depth (level of overlap) in each boundary pair of *intervals*, cropped within *interval*:

```

abjad> from abjad.tools.intervaltreetools import *
abjad> a = BoundedInterval(0, 3)
abjad> b = BoundedInterval(6, 12)
abjad> c = BoundedInterval(9, 15)
abjad> tree = IntervalTree([a, b, c])
abjad> d = BoundedInterval(-1, 16)
abjad> compute_depth_of_intervals_in_interval(tree, d)
IntervalTree([
    BoundedInterval(Offset(-1, 1), Offset(0, 1), {'depth': 0}),
    BoundedInterval(Offset(0, 1), Offset(3, 1), {'depth': 1}),
    BoundedInterval(Offset(3, 1), Offset(6, 1), {'depth': 0}),
    BoundedInterval(Offset(6, 1), Offset(9, 1), {'depth': 1}),
    BoundedInterval(Offset(9, 1), Offset(12, 1), {'depth': 2}),
    BoundedInterval(Offset(12, 1), Offset(15, 1), {'depth': 1}),
    BoundedInterval(Offset(15, 1), Offset(16, 1), {'depth': 0})
])

```

Return interval tree.

intervaltreetools.compute_logical_and_of_intervals

`abjad.tools.intervaltreetools.compute_logical_and_of_intervals(intervals)`
 Compute the logical AND of a collection of intervals.

intervaltreetools.compute_logical_and_of_intervals_in_interval

`abjad.tools.intervaltreetools.compute_logical_and_of_intervals_in_interval(intervals, interval)`
 Compute the logical AND of a collection of intervals, cropped within *interval*.

intervaltreetools.compute_logical_not_of_intervals

`abjad.tools.intervaltreetools.compute_logical_not_of_intervals(intervals)`
 Compute the logical NOT of some collection of intervals.

intervaltreetools.compute_logical_not_of_intervals_in_interval

`abjad.tools.intervaltreetools.compute_logical_not_of_intervals_in_interval(intervals, interval)`
 Compute the logical NOT of some collection of intervals, cropped within *interval*.

intervaltreetools.compute_logical_or_of_intervals

`abjad.tools.intervaltreetools.compute_logical_or_of_intervals(intervals)`
 Compute the logical OR of a collection of intervals.

intervaltreertools.compute_logical_or_of_intervals_in_interval

`abjad.tools.intervaltreertools.compute_logical_or_of_intervals_in_interval` (*intervals*,
*in-
 ter-
 val*)

Compute the logical OR of a collection of intervals, cropped within *interval*.

intervaltreertools.compute_logical_xor_of_intervals

`abjad.tools.intervaltreertools.compute_logical_xor_of_intervals` (*intervals*)

Compute the logical XOR of a collections of intervals.

intervaltreertools.compute_logical_xor_of_intervals_in_interval

`abjad.tools.intervaltreertools.compute_logical_xor_of_intervals_in_interval` (*intervals*,
*in-
 ter-
 val*)

Compute the logical XOR of a collections of intervals, cropped within *interval*.

intervaltreertools.concatenate_trees

`abjad.tools.intervaltreertools.concatenate_trees` (*trees*, *padding=0*)

Merge all trees in *trees*, offsetting each subsequent tree to start after the previous.

intervaltreertools.explode_intervals_compactly

`abjad.tools.intervaltreertools.explode_intervals_compactly` (*intervals*)

Explode the intervals in *intervals* into *n* non-overlapping trees, where *n* is the maximum depth of *intervals*.

Returns an array of *IntervalTree* instances.

The algorithm will attempt to insert the exploded intervals into the lowest-indexed resultant tree with free space.

intervaltreertools.explode_intervals_into_n_trees_heuristically

`abjad.tools.intervaltreertools.explode_intervals_into_n_trees_heuristically` (*intervals*,
n)

Explode *intervals* into *n* trees, avoiding overlap when possible, and distributing intervals so as to equalize density across the trees.

intervaltreertools.explode_intervals_uncompactly

`abjad.tools.intervaltreertools.explode_intervals_uncompactly` (*intervals*)

Explode the intervals in *intervals* into *n* non-overlapping trees, where *n* is the maximum depth of *intervals*.

Returns an array of *IntervalTree* instances.

The algorithm will attempt to insert the exploded intervals cyclically, making its insertion attempt at the next resultant tree in the array, rather than always beginning its search from index 0.

intervaltreertools.fuse_overlapping_intervals

`abjad.tools.intervaltreertools.fuse_overlapping_intervals` (*intervals*)

Fuse the overlapping intervals in *intervals* and return an *IntervalTree* of the result

```

abjad> from abjad.tools import intervaltreertools
abjad> from abjad.tools.intervaltreertools import BoundedInterval
abjad> from abjad.tools.intervaltreertools import IntervalTree

abjad> a = BoundedInterval(0, 10)
abjad> b = BoundedInterval(5, 15)
abjad> c = BoundedInterval(15, 25)
abjad> tree = IntervalTree([a, b, c])
abjad> intervaltreertools.fuse_overlapping_intervals(tree)
IntervalTree([
    BoundedInterval(Offset(0, 1), Offset(15, 1), {}),
    BoundedInterval(Offset(15, 1), Offset(25, 1), {})
])

```

Return interval tree.

intervaltreertools.fuse_tangent_or_overlapping_intervals

`abjad.tools.intervaltreertools.fuse_tangent_or_overlapping_intervals` (*intervals*)

Fuse all tangent or overlapping intervals and return an *IntervalTree* of the result

```

abjad> from abjad.tools import intervaltreertools
abjad> from abjad.tools.intervaltreertools import BoundedInterval
abjad> from abjad.tools.intervaltreertools import IntervalTree

abjad> a = BoundedInterval(0, 10)
abjad> b = BoundedInterval(5, 15)
abjad> c = BoundedInterval(15, 25)
abjad> tree = IntervalTree([a, b, c])
abjad> intervaltreertools.fuse_tangent_or_overlapping_intervals(tree)
IntervalTree([
    BoundedInterval(Offset(0, 1), Offset(25, 1), {})
])

```

Return interval tree.

intervaltreertools.get_all_unique_bounds_in_intervals

`abjad.tools.intervaltreertools.get_all_unique_bounds_in_intervals` (*intervals*)

Return all unique starting and ending boundaries in *intervals*.

intervaltreertools.group_overlapping_intervals_and_yield_groups

`abjad.tools.intervaltreertools.group_overlapping_intervals_and_yield_groups` (*intervals*)

Group overlapping intervals in *intervals* and return tuples.

intervaltreertools.group_tangent_or_overlapping_intervals_and_yield_groups

`abjad.tools.intervaltreertools.group_tangent_or_overlapping_intervals_and_yield_groups` (*intervals*)

Group tangent or overlapping intervals in *intervals* and return tuples.

intervaltreertools.make_monophonic_percussion_score_from_nonoverlapping_intervals

`abjad.tools.intervaltreertools.make_monophonic_percussion_score_from_nonoverlapping_intervals`

Create a monophonic percussion score from nonoverlapping interval collection *intervals*.

intervaltreertools.make_polyphonic_percussion_score_from_nonoverlapping_trees

`abjad.tools.intervaltreertools.make_polyphonic_percussion_score_from_nonoverlapping_trees` (*trees*)

Make a polyphonic percussion score from a collections of non-overlapping trees.

intervaltreertools.mask_intervals_with_intervals

`abjad.tools.intervaltreertools.mask_intervals_with_intervals` (*masked_intervals*, *mask_intervals*)

Clip or remove all intervals in *masked_intervals* outside of the bounds defined in *mask_intervals*, while maintaining *masked_intervals*' payload contents

```
abjad> from abjad.tools import intervaltreertools
abjad> from abjad.tools.intervaltreertools import BoundedInterval
abjad> from abjad.tools.intervaltreertools import IntervalTree

abjad> a = BoundedInterval(0, 10, {'a': 1})
abjad> b = BoundedInterval(5, 15, {'b': 2})
abjad> tree = IntervalTree([a, b])
abjad> mask = BoundedInterval(4, 11)
abjad> intervaltreertools.mask_intervals_with_intervals(tree, mask)
IntervalTree([
    BoundedInterval(Offset(4, 1), Offset(10, 1), {'a': 1}),
    BoundedInterval(Offset(5, 1), Offset(11, 1), {'b': 2})
])
```

Return interval tree.

intervaltreertools.resolve_overlaps_between_nonoverlapping_trees

`abjad.tools.intervaltreertools.resolve_overlaps_between_nonoverlapping_trees` (*trees*)

Create a nonoverlapping IntervalTree from *trees*. Intervals in higher-indexed trees in *trees* only appear in part or whole where they do not overlap intervals from lower-indexed trees

```
abjad> from abjad.tools import intervaltreertools
abjad> from abjad.tools.intervaltreertools import BoundedInterval
abjad> from abjad.tools.intervaltreertools import IntervalTree

abjad> a = IntervalTree(BoundedInterval(0, 4, {'a': 1}))
abjad> b = IntervalTree(BoundedInterval(1, 5, {'b': 2}))
abjad> c = IntervalTree(BoundedInterval(2, 6, {'c': 3}))
abjad> d = IntervalTree(BoundedInterval(1, 3, {'d': 4}))
abjad> intervaltreertools.resolve_overlaps_between_nonoverlapping_trees([a, b, c, d])
IntervalTree([
    BoundedInterval(Offset(0, 1), Offset(4, 1), {'a': 1}),
    BoundedInterval(Offset(4, 1), Offset(5, 1), {'b': 2}),
    BoundedInterval(Offset(5, 1), Offset(6, 1), {'c': 3}),
    BoundedInterval(Offset(1, 1), Offset(3, 1), {'d': 4})
])
```

```
BoundedInterval(Offset(5, 1), Offset(6, 1), {'c': 3})
])
```

Return interval tree.

`intervalreetools.resolve_overlaps_between_nonoverlapping_trees_excluding_remainders_less_than_rational`

`abjad.tools.intervalreetools.resolve_overlaps_between_nonoverlapping_trees_excluding_remainders_less_than_rational`

Create a nonoverlapping `IntervalTree` from *trees*. Intervals in higher-indexed trees in *trees* only appear in part or whole where they do not overlap intervals from lower-indexed trees, and then only where their magnitudes are equal to or greater than *rational*

```
abjad> from abjad.tools import intervalreetools
abjad> from abjad.tools.intervalreetools import BoundedInterval
abjad> from abjad.tools.intervalreetools import IntervalTree

abjad> a = IntervalTree(BoundedInterval(0, 1, {'a': 1}))
abjad> b = IntervalTree(BoundedInterval(Fraction(1, 32), Fraction(33, 32), {'b': 2}))
abjad> c = IntervalTree(BoundedInterval(Fraction(1, 16), Fraction(17, 16), {'c': 3}))
abjad> intervalreetools.resolve_overlaps_between_nonoverlapping_trees_excluding_remainders_less_than_rational(
IntervalTree([
    BoundedInterval(Offset(0, 1), Offset(1, 1), {'a': 1}),
    BoundedInterval(Offset(1, 1), Offset(17, 16), {'c': 3})
]))
```

Return interval tree.

`intervalreetools.round_interval_bounds_to_nearest_multiple_of_rational`

`abjad.tools.intervalreetools.round_interval_bounds_to_nearest_multiple_of_rational` (*intervals*, *rational*)

`intervalreetools.scale_aggregate_magnitude_by_rational`

`abjad.tools.intervalreetools.scale_aggregate_magnitude_by_rational` (*intervals*, *rational*)

Scale the aggregate magnitude of all intervals in *intervals* by *rational*, maintaining the original low offset

```
abjad> from abjad.tools import intervalreetools
abjad> from abjad.tools.intervalreetools import BoundedInterval
abjad> from abjad.tools.intervalreetools import IntervalTree

abjad> a = BoundedInterval(-1, 3)
abjad> b = BoundedInterval(6, 12)
abjad> c = BoundedInterval(9, 16)
abjad> tree = IntervalTree([a, b, c])
abjad> intervalreetools.scale_aggregate_magnitude_by_rational(tree, Fraction(1, 3))
IntervalTree([
    BoundedInterval(Offset(-1, 1), Offset(1, 3), {}),
    BoundedInterval(Offset(6, 1), Offset(12, 3), {}),
    BoundedInterval(Offset(9, 1), Offset(16, 3), {}),
])
```

```

        BoundedInterval(Offset(4, 3), Offset(10, 3), {}),
        BoundedInterval(Offset(7, 3), Offset(14, 3), {}))
])

```

Return interval tree.

intervaltreertools.scale_aggregate_magnitude_to_rational

`abjad.tools.intervaltreertools.scale_aggregate_magnitude_to_rational`(*intervals*, *rational*)

Scale the aggregate magnitude of all intervals in *intervals* to *rational*, maintaining the original low offset

```

abjad> from abjad.tools import intervaltreertools
abjad> from abjad.tools.intervaltreertools import BoundedInterval
abjad> from abjad.tools.intervaltreertools import IntervalTree

abjad> a = BoundedInterval(-1, 3)
abjad> b = BoundedInterval(6, 12)
abjad> c = BoundedInterval(9, 16)
abjad> tree = IntervalTree([a, b, c])
abjad> intervaltreertools.scale_aggregate_magnitude_to_rational(tree, Fraction(16, 7))
IntervalTree([
    BoundedInterval(Offset(-1, 1), Offset(-55, 119), {}),
    BoundedInterval(Offset(-1, 17), Offset(89, 119), {}),
    BoundedInterval(Offset(41, 119), Offset(9, 7), {})
])

```

Return interval tree.

intervaltreertools.scale_interval_magnitudes_by_rational

`abjad.tools.intervaltreertools.scale_interval_magnitudes_by_rational`(*intervals*, *rational*)

Scale the magnitude of each interval in *intervals* by *rational*, maintaining their low offsets

```

abjad> from abjad.tools import intervaltreertools
abjad> from abjad.tools.intervaltreertools import BoundedInterval
abjad> from abjad.tools.intervaltreertools import IntervalTree

abjad> a = BoundedInterval(-1, 3)
abjad> b = BoundedInterval(6, 12)
abjad> c = BoundedInterval(9, 16)
abjad> tree = IntervalTree([a, b, c])
abjad> intervaltreertools.scale_interval_magnitudes_by_rational(tree, Fraction(6, 5))
IntervalTree([
    BoundedInterval(Offset(-1, 1), Offset(19, 5), {}),
    BoundedInterval(Offset(6, 1), Offset(66, 5), {}),
    BoundedInterval(Offset(9, 1), Offset(87, 5), {})
])

```

Return interval tree.

intervaltreertools.scale_interval_magnitudes_to_rational

`abjad.tools.intervaltreertools.scale_interval_magnitudes_to_rational` (*intervals*, *rational*)

Scale the magnitude of each interval in *intervals* to *rational*, maintaining their low offsets

```
abjad> from abjad.tools import intervaltreertools
abjad> from abjad.tools.intervaltreertools import BoundedInterval
abjad> from abjad.tools.intervaltreertools import IntervalTree

abjad> a = BoundedInterval(-1, 3)
abjad> b = BoundedInterval(6, 12)
abjad> c = BoundedInterval(9, 16)
abjad> tree = IntervalTree([a, b, c])
abjad> intervaltreertools.scale_interval_magnitudes_to_rational(tree, Fraction(1, 7))
IntervalTree([
    BoundedInterval(Offset(-1, 1), Offset(-6, 7), {}),
    BoundedInterval(Offset(6, 1), Offset(43, 7), {}),
    BoundedInterval(Offset(9, 1), Offset(64, 7), {})
])
```

Return interval tree.

intervaltreertools.scale_interval_offsets_by_rational

`abjad.tools.intervaltreertools.scale_interval_offsets_by_rational` (*intervals*, *rational*)

Scale the offset of each interval in *intervals* by *rational*, maintaining the lowest offset in *intervals*

```
abjad> from abjad.tools import intervaltreertools
abjad> from abjad.tools.intervaltreertools import BoundedInterval
abjad> from abjad.tools.intervaltreertools import IntervalTree

abjad> a = BoundedInterval(-1, 3)
abjad> b = BoundedInterval(6, 12)
abjad> c = BoundedInterval(9, 16)
abjad> tree = IntervalTree([a, b, c])
abjad> intervaltreertools.scale_interval_offsets_by_rational(tree, Fraction(4, 5))
IntervalTree([
    BoundedInterval(Offset(-1, 1), Offset(3, 1), {}),
    BoundedInterval(Offset(23, 5), Offset(53, 5), {}),
    BoundedInterval(Offset(7, 1), Offset(14, 1), {})
])
```

Return interval tree.

intervaltreertools.shift_aggregate_offset_by_rational

`abjad.tools.intervaltreertools.shift_aggregate_offset_by_rational` (*intervals*, *rational*)

Shift the aggregate offset of *intervals* by *rational*

```
abjad> from abjad.tools import intervaltreertools
abjad> from abjad.tools.intervaltreertools import BoundedInterval
abjad> from abjad.tools.intervaltreertools import IntervalTree
```

```

abjad> a = BoundedInterval(-1, 3)
abjad> b = BoundedInterval(6, 12)
abjad> c = BoundedInterval(9, 16)
abjad> tree = IntervalTree([a, b, c])
abjad> intervaltreetools.shift_aggregate_offset_by_rational(tree, Fraction(1, 3))
IntervalTree([
    BoundedInterval(Offset(-2, 3), Offset(10, 3), {}),
    BoundedInterval(Offset(19, 3), Offset(37, 3), {}),
    BoundedInterval(Offset(28, 3), Offset(49, 3), {})
])

```

Return interval tree.

intervaltreetools.shift_aggregate_offset_to_rational

`abjad.tools.intervaltreetools.shift_aggregate_offset_to_rational(intervals, rational)`

Shift the aggregate offset of *intervals* to *rational*

```

abjad> from abjad.tools import intervaltreetools
abjad> from abjad.tools.intervaltreetools import BoundedInterval
abjad> from abjad.tools.intervaltreetools import IntervalTree

abjad> a = BoundedInterval(-1, 3)
abjad> b = BoundedInterval(6, 12)
abjad> c = BoundedInterval(9, 16)
abjad> tree = IntervalTree([a, b, c])
abjad> intervaltreetools.shift_aggregate_offset_to_rational(tree, Fraction(10, 7))
IntervalTree([
    BoundedInterval(Offset(10, 7), Offset(38, 7), {}),
    BoundedInterval(Offset(59, 7), Offset(101, 7), {}),
    BoundedInterval(Offset(80, 7), Offset(129, 7), {})
])

```

Return interval tree.

intervaltreetools.split_intervals_at_rationals

`abjad.tools.intervaltreetools.split_intervals_at_rationals(intervals, rationals)`

Split *intervals* at each rational in *rationals*

```

abjad> from abjad.tools import intervaltreetools
abjad> from abjad.tools.intervaltreetools import BoundedInterval
abjad> from abjad.tools.intervaltreetools import IntervalTree

abjad> a = BoundedInterval(-1, 3)
abjad> b = BoundedInterval(6, 12)
abjad> c = BoundedInterval(9, 16)
abjad> tree = IntervalTree([a, b, c])
abjad> intervaltreetools.split_intervals_at_rationals(tree, [1, Fraction(19, 2)])
IntervalTree([
    BoundedInterval(Offset(-1, 1), Offset(1, 1), {}),
    BoundedInterval(Offset(1, 1), Offset(3, 1), {}),
    BoundedInterval(Offset(6, 1), Offset(19, 2), {}),
    BoundedInterval(Offset(9, 1), Offset(19, 2), {}),
    BoundedInterval(Offset(19, 2), Offset(12, 1), {}),
])

```

```
BoundedInterval(Offset(19, 2), Offset(16, 1), {}))
])
```

Return interval tree.

iotools

iotools.clear_terminal

`abjad.tools.iotools.clear_terminal()`

New in version 2.0. Run `clear` if OS is POSIX-compliant (UNIX / Linux / MacOS).

Run `cls` if OS is not POSIX-compliant (Windows):

```
abjad> iotools.clear_terminal()
```

Return none.

iotools.f

`abjad.tools.iotools.f(expr)`

Format *expr* and print to standard out:

```
abjad> staff = Staff("c'8 d'8 e'8 f'8")
```

```
abjad> f(staff)
\new Staff {
    c'8
    d'8
    e'8
    f'8
}
```

Return none.

iotools.format_input_lines_as_doc_string

`abjad.tools.iotools.format_input_lines_as_doc_string(input_lines, tab_width=3)`

New in version 2.0. Format *input_lines* as doc string.

Format expressions intelligently.

Treat blank lines intelligently.

Capture hash-suffixed line output.

Use when writing docstrings.

Example skipped because docstring goes crazy on example input.

iotools.format_input_lines_as_regression_test

`abjad.tools.iotools.format_input_lines_as_regression_test(input_lines, tab_width=3)`

New in version 2.0. Format *input_lines* as regression test:

```

abjad> input_lines = '''
... staff = Staff("c'8 d'8 e'8 f'8")
... spannertools.BeamSpanner(staff.leaves)
... f(staff)
...
... tuplettools.FixedDurationTuplet(Duration(2, 8), staff[:3])
... f(staff)
... '''
abjad> iotools.format_input_lines_as_regression_test(input_lines) # doctest: +SKIP

    staff = Staff("c'8 d'8 e'8 f'8")
    spannertools.BeamSpanner(staff.leaves)

    r'''
    \new Staff {
      c'8 [
        d'8
        e'8
        f'8 ]
    }
    '''

    tuplettools.FixedDurationTuplet(Duration(2, 8), staff[:3])

    r'''
    \new Staff {
      \times 2/3 {
        c'8 [
          d'8
          e'8
        ]
      }
      f'8 ]
    }

    assert componenttools.is_well_formed_component(staff)
    assert staff.format == "\\new Staff {\\n\\t\\times 2/3 {\\n\\t\\tc'8 [\\n\\t\\td'8\\n\\t\\te'8\\n\\t}\\n\\t\\t
    '''

```

Format expressions intelligently.

Treat blank lines intelligently.

Remove line-final hash characters.

Used when writing tests.

iotools.get_last_output_file_name

`abjad.tools.iotools.get_last_output_file_name()`

Get last output file name like 6222.ly.

Return string.

iotools.get_next_output_file_name

`abjad.tools.iotools.get_next_output_file_name()`

Get next output file name like 6223.ly.

Return string.

iotools.log

`abjad.tools.iotools.log()`

Open the LilyPond log file in operating system-specific text editor:

```
abjad> iotools.log() ### doctest: +SKIP
```

```
GNU LilyPond 2.12.2
Processing `0440.ly'
Parsing...
Interpreting music...
Preprocessing graphical objects...
Finding the ideal number of pages...
Fitting music on 1 page...
Drawing systems...
Layout output to `0440.ps'...
Converting to `./0440.pdf'...
```

Exit text editor in the usual way.

Return none.

iotools.ly

`abjad.tools.iotools.ly(target=-1)`

Open the last LilyPond output file in text editor:

```
abjad> iotools.ly() # doctest: +SKIP
```

```
% Abjad revision 2162
% 2009-05-31 14:29

\version "2.12.2"
\include "english.ly"
\include "/Path/to/abjad/trunk/abjad/cfg/abjad.scm"

{
    c' 4
}
```

Open the next-to-last LilyPond output file in text editor:

```
abjad> iotools.ly(-2) # doctest: +SKIP
```

Exit text editor in the usual way.

Return none.

iotools.parse_lilypond_input_string

`abjad.tools.iotools.parse_lilypond_input_string(note_entry_string)`

New in version 2.0. Parse LilyPond *note_entry_string*:

```
abjad> note_entry_string = "g'2 a'2 g'4. fs'8 e'4 d'4"
abjad> iotools.parse_lilypond_input_string(note_entry_string)
{g'2, a'2, g'4., fs'8, e'4, d'4}
```

Return container of note, rest and chord instances.

Handle simple beaming, slurs and articulations.

Do not parse tuplets, measures or other complex LilyPond input.

iotools.pdf

```
abjad.tools.iotools.pdf(target=-1)
    Open the last PDF generated by Abjad with iotools.pdf().

    Open the next-to-last PDF generated by Abjad with iotools.pdf(-2).

    Return none.

    Abjad writes PDFs to the ~/.abjad/output directory by default.

    You may change this by setting the abjad_output variable in the config.py file.
```

iotools.play

```
abjad.tools.iotools.play(expr)
    Play expr:

    abjad> note = Note("c'4")
    abjad> iotools.play(note) # doctest: +SKIP

    This input renders and then opens a one-note MIDI file.

    Abjad outputs MIDI files of the format filename.mid under Windows.

    Abjad outputs MIDI files of the format filename.midi under other operating systems.
```

iotools.profile_expr

```
abjad.tools.iotools.profile_expr(expr, sort_by='cum', num_lines=12, strip_dirs=True)
    Profile expr:

    abjad> iotools.profile_expr('Staff(notetools.make_repeated_notes(8))') # doctest: +SKIP
    Tue Apr  5 20:32:40 2011      _tmp_abj_profile

        2852 function calls (2829 primitive calls) in 0.006 CPU seconds

    Ordered by: cumulative time
    List reduced from 118 to 12 due to restriction <12>

    ncalls  tottime  percall  cumtime  percall  filename:lineno(function)
         1    0.000    0.000    0.006    0.006  <string>:1(<module>)
         1    0.000    0.000    0.003    0.003  make_repeated_notes.py:5(make_repeated_notes)
         1    0.001    0.001    0.003    0.003  make_notes.py:12(make_notes)
         1    0.000    0.000    0.003    0.003  Staff.py:21(__init__)
         1    0.000    0.000    0.003    0.003  _Context.py:11(__init__)
         1    0.000    0.000    0.003    0.003  Container.py:23(__init__)
         1    0.000    0.000    0.003    0.003  Container.py:271(_initialize_music)
```

2	0.000	0.000	0.002	0.001	all_are_thread_contiguous_components.py:9 (all_are_
52	0.001	0.000	0.002	0.000	component_to_thread_signature.py:5 (component_to_th
1	0.000	0.000	0.002	0.002	_construct_unprolotted_notes.py:4 (_construct_unprol
8	0.000	0.000	0.002	0.000	_construct_tied_note.py:5 (_construct_tied_note)
8	0.000	0.000	0.002	0.000	_construct_tied_leaf.py:5 (_construct_tied_leaf)

Function wraps the built-in Python `cProfile` module.

Set *expr* to any string of Abjad input.

Set *sort_by* to 'cum', 'time' or 'calls'.

Set *num_lines* to any positive integer.

Set *strip_dirs* to `True` to strip directory names from output lines.

Note: This function fails on some Linux distros. Some Linux distributions do not include the Python `pstats` module.

Note: This function creates the file `_tmp_abj_profile` in the directory from which it is run.

Note: For information on reading the output of the different Python profilers, see [the Python docs](#).

Changed in version 2.0: renamed `check.profile()` to `iotools.profile_expr()`.

iotools.redo

`abjad.tools.iotools.redo(target=-1, lily_time=10)`

Rerender the last .ly file created in Abjad and then show the resulting PDF:

```
abjad> iotools.redo() # doctest: +SKIP
```

Rerender the next-to-last .ly file created in Abjad and then show the resulting PDF:

```
abjad> iotools.redo(-2) # doctest: +SKIP
```

Return none.

iotools.remove_abjad_pyc_files

`abjad.tools.iotools.remove_abjad_pyc_files()`

Remove .pyc files from Abjad source tree:

```
abjad> iotools.remove_abjad_pyc_files() # doctest: +SKIP
```

Return none.

iotools.save_last_ly_as

`abjad.tools.iotools.save_last_ly_as(file_name)`

New in version 2.0. Save last ly file as *file_name*:

```
abjad> iotools.save_last_ly_as('/project/output/example-1.ly') # doctest: +SKIP
```

Return none.

iotools.save_last_pdf_as

```
abjad.tools.iotools.save_last_pdf_as(file_name)
```

New in version 2.0. Save last PDF as *file_name*:

```
abjad> iotools.save_last_pdf_as('/project/output/example-1.pdf') # doctest: +SKIP
```

Return none.

iotools.show

```
abjad.tools.iotools.show(expr, template=None, return_timing=False, suppress_pdf=False)
```

Show *expr*:

```
abjad> note = Note("c'4")
abjad> show(note) # doctest: +SKIP
```

Show *expr* with *template*:

```
abjad> note = Note("c'4")
abjad> show(note, template = 'tangiers') # doctest: +SKIP
```

Show *expr* and return both Abjad and LilyPond processing time in seconds:

```
abjad> staff = Staff(Note("c'4") * 200)
abjad> show(note, return_timing = True) # doctest: +SKIP
(0, 3)
```

Return none or timing tuple.

Abjad writes LilyPond input files to the `~/ .abjad/output` directory by default.

You may change this by setting the `abjad_output` variable in the `config.py` file.

iotools.underscore_delimited_lowercase_to_lowercamelcase

```
abjad.tools.iotools.underscore_delimited_lowercase_to_lowercamelcase(string)
```

New in version 2.0. Change underscore-delimited lowercase *string* to lowercamelcase:

```
abjad> string = 'bass_figure_alignment_positioning'
abjad> iotools.underscore_delimited_lowercase_to_lowercamelcase(string)
'bassFigureAlignmentPositioning'
```

Changed in version 2.0: renamed `stringtools.underscore_delimited_lowercase_to_lowercamelcase()` to `iotools.underscore_delimited_lowercase_to_lowercamelcase()`.

iotools.underscore_delimited_lowercase_to_uppercamelcase

```
abjad.tools.iotools.underscore_delimited_lowercase_to_uppercamelcase(string)
```

New in version 2.0. Change underscore-delimited lowercase *string* to uppercamelcase:


```
abjad> string = 'bass_figure_alignment_positioning'
abjad> iotools.underscore_delimited_lowercase_to_uppercamelcase(string)
'BassFigureAlignmentPositioning'
```

Changed in version 2.0: renamed `stringtools.underscore_delimited_lowercase_to_uppercamelcase()` to `iotools.underscore_delimited_lowercase_to_uppercamelcase()`.

iotools.write_expr_to_ly

```
abjad.tools.iotools.write_expr_to_ly(expr, file_name, template=None, print_status=True)
```

Write *expr* to *file_name*:

```
abjad> note = Note("c'4")
abjad> iotools.write_expr_to_ly(note, '/home/user/foo.ly') # doctest: +SKIP
```

Write *expr* to *file_name* with *template*:

```
abjad> note = Note("c'4")
abjad> iotools.write_expr_to_ly(note, '/home/user/foo.ly', 'paris') # doctest: +SKIP
```

Return `None`. Changed in version 2.0: renamed `io.write_ly()` to `io.write_expr_to_ly()`.

iotools.write_expr_to_ly_and_to_pdf_and_show

```
abjad.tools.iotools.write_expr_to_ly_and_to_pdf_and_show(expr, name, tem-
                                                         plate=None,
                                                         write=True)
```

Write *expr* to named `.ly` and to PDF and then open the resulting PDF:

```
abjad> iotools.write_expr_to_ly_and_to_pdf_and_show(Note("c'8"), 'file_name_stem') # doctest: +SKIP
```

Write *expr* to temporary `.ly` and to PDF and then open the resulting PDF:

```
abjad> iotools.write_expr_to_ly_and_to_pdf_and_show(Note("c'8"), 'file_name_stem', write = False)
```

Return `None`.

The purpose of this function is to save named `.ly` and PDF output. Changed in version 2.0: renamed `io.write_and_show()` to `io.write_expr_to_ly_and_to_pdf_and_show()`.

iotools.write_expr_to_pdf

```
abjad.tools.iotools.write_expr_to_pdf(expr, file_name, template=None, print_status=True)
```

Write *expr* to pdf *file_name*:

```
abjad> note = Note("c'4")
abjad> iotools.write_expr_to_pdf(note, 'one_note.pdf') # doctest: +SKIP
```

Write *expr* to pdf *file_name* with *template*:

```
abjad> note = Note("c'4")
abjad> iotools.write_expr_to_pdf(note, 'one_note.pdf', 'paris') # doctest: +SKIP
```

Return `None`.

layouttools

layouttools.SpacingIndication

```
class abjad.tools.layouttools.SpacingIndication(tempo_indication,          propor-
                                                tional_notation_duration)
    Bases:      abjad.core._StrictComparator._StrictComparator._StrictComparator,
                abjad.core._Immutable._Immutable._Immutable

    Spacing indication token.

    LilyPond Score.proportionalNotationDuration will equal proportional_notation_duration
    when tempo equals tempo_indication.

    abjad> from abjad.tools import layouttools

    abjad> tempo = contexttools.TempoMark(Duration(1, 8), 44)
    abjad> spacing_indication = layouttools.SpacingIndication(tempo, Duration(1, 68))
    abjad> spacing_indication
    SpacingIndication(TempoMark(8, 44), 1/68)

    Spacing indications are immutable.

normalized_spacing_duration
    Read-only proportional notation duration at 60 MM.

proportional_notation_duration
    LilyPond proportional notation duration context setting.

tempo_indication
    Abjad tempo indication object.
```

layouttools.make_spacing_vector

```
abjad.tools.layouttools.make_spacing_vector(basic_distance, minimum_distance, padding,
                                                stretchability)

    New in version 2.0. Make spacing vector:

    abjad> from abjad.tools import layouttools

    abjad> layouttools.make_spacing_vector(0, 0, 12, 0)
    SchemeVector((basic_distance . 0), (minimum_distance . 0), (padding . 12), (stretchability . 0))

    Use to set paper block spacing attributes:

    abjad> staff = Staff("c'8 d'8 e'8 f'8")
    abjad> lily_file = lilyfiletools.make_basic_lily_file(staff)
    abjad> lily_file.paper_block.system_system_spacing = layouttools.make_spacing_vector(0, 0, 12, 0)

    abjad> f(lily_file) # doctest: +SKIP
    % Abjad revision 4229
    % 2011-04-07 15:19

    \version "2.13.44"
    \include "english.ly"
    \include "/abjad/trunk/abjad/cfg/abjad.scm"

    \paper {
      system-system-spacing = #'((basic_distance . 0) (minimum_distance . 0) (padding . 12) (stretchability . 0))
    }
```

```
\score {
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
}
```

Return scheme vector.

layouttools.set_line_breaks_cyclically_by_line_duration_ge

```
abjad.tools.layouttools.set_line_breaks_cyclically_by_line_duration_ge(expr,
                                                                    line_duration,
                                                                    klass=<class
                                                                    'ab-
                                                                    jad.tools.measuretools.Measure-
                                                                    ad-
                                                                    just_eol=False,
                                                                    add_empty_bars=False)
```

Iterate *klass* instances in *expr* and accumulate prolated duration. Add line break after every total less than or equal to *line_duration*:

```
abjad> from abjad.tools import layouttools

abjad> t = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 4)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> f(t)
\new Staff {
  {
    \time 2/8
    c'8
    d'8
  }
  {
    \time 2/8
    e'8
    f'8
  }
  {
    \time 2/8
    g'8
    a'8
  }
  {
    \time 2/8
    b'8
    c''8
  }
}

abjad> layouttools.set_line_breaks_cyclically_by_line_duration_ge(t, Duration(4, 8))
abjad> f(t)
\new Staff {
  {
    \time 2/8
```

```

        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
        \break
    }
    {
        \time 2/8
        g'8
        a'8
    }
    {
        \time 2/8
        b'8
        c''8
        \break
    }
}

```

Set `adjust_eol` to `True` to include a magic Scheme incantation to move end-of-line LilyPond TimeSignature and BarLine grobs to the right. Changed in version 2.0: renamed `layout.line_break_every_prolated()` to `layout.set_line_breaks_cyclically_by_line_duration_ge()`.

layouttools.set_line_breaks_cyclically_by_line_duration_in_seconds_ge

```

abjad.tools.layouttools.set_line_breaks_cyclically_by_line_duration_in_seconds_ge(expr,
                                          line_duration,
                                          klass=<class 'abjad.tools.measures.AdjustEndOfLine>,
                                          just_eol=False,
                                          add_empty_line=True)

```

Iterate *klass* instances in *expr* and accumulate duration in seconds. Add line break after every total less than or equal to *line_duration*:

```

abjad> from abjad.tools import layouttools

abjad> t = Staff(Measure((2, 8), notetools.make_repeated_notes(2)) * 4)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(t)
abjad> tempo_mark = contexttools.TempoMark(Duration(1, 8), 44, target_context = Staff)(t)
abjad> f(t)
\new Staff {
    \tempo 8=44
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
    }
}

```

```

    {
        \time 2/8
        g'8
        a'8
    }
    {
        \time 2/8
        b'8
        c''8
    }
}

abjad> layouttools.set_line_breaks_cyclically_by_line_duration_in_seconds_ge(t, Duration(6))
abjad> f(t)
\new Staff {
    \tempo 8=44
    {
        \time 2/8
        c'8
        d'8
    }
    {
        \time 2/8
        e'8
        f'8
        \break
    }
    {
        \time 2/8
        g'8
        a'8
    }
    {
        \time 2/8
        b'8
        c''8
    }
}

```

Set `adjust_eol = True` to include a magic Scheme incantation to move end-of-line LilyPond TimeSignature and BarLine grobs to the right. Changed in version 2.0: renamed `layout.line_break_every_seconds()` to `layout.set_line_breaks_cyclically_by_line_duration_in_seconds_ge()`.

mathtools

mathtools.arithmetic_mean

`abjad.tools.mathtools.arithmetic_mean(sequence)`

New in version 1.1. Arithmetic means of *sequence* as an exact integer:

```

abjad> from abjad.tools import mathtools

abjad> mathtools.arithmetic_mean([1, 2, 2, 20, 30])
11

```

As a rational:

```
abjad> mathtools.arithmetic_mean([1, 2, 20])
Fraction(23, 3)
```

As a float:

```
abjad> mathtools.arithmetic_mean([2, 2, 20.0])
8.0
```

Return number. Changed in version 2.0: renamed `seqtools.arithmetic_mean()` to `mathtools.arithmetic_mean()`.

mathtools.binomial_coefficient

`abjad.tools.mathtools.binomial_coefficient(n, k)`

New in version 2.0. Binomial coefficient of *n* choose *k*:

```
abjad> from abjad.tools import mathtools

abjad> for k in range(8):
...     print k, '\t', mathtools.binomial_coefficient(8, k)
...
0  1
1  8
2  28
3  56
4  70
5  56
6  28
7  8
```

Return positive integer.

mathtools.cumulative_products

`abjad.tools.mathtools.cumulative_products(sequence)`

Cumulative products of *sequence*:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.cumulative_products([1, 2, 3, 4, 5, 6, 7, 8])
[1, 2, 6, 24, 120, 720, 5040, 40320]

abjad> mathtools.cumulative_products([1, -2, 3, -4, 5, -6, 7, -8])
[1, -2, -6, 24, 120, -720, -5040, 40320]
```

Raise type error when *sequence* is neither list nor tuple.

Raise value error on empty *sequence*.

Return list. Changed in version 2.0: renamed `seqtools.cumulative_products()` to `mathtools.cumulative_products()`.

mathtools.cumulative_signed_weights

`abjad.tools.mathtools.cumulative_signed_weights(sequence)`

Cumulative signed weights of *sequence*:

```

abjad> from abjad.tools import mathtools

abjad> l = [1, -2, -3, 4, -5, -6, 7, -8, -9, 10]
abjad> mathtools.cumulative_signed_weights(l)
[1, -3, -6, 10, -15, -21, 28, -36, -45, 55]

```

Raise type error when *sequence* is not a list.

For cumulative (unsigned) weights use `mathtools.cumulative_sums([abs(x) for x in l])`.

Return list. Changed in version 2.0: renamed `seqtools.cumulative_weights_signed()` to `mathtools.cumulative_signed_weights()`.

mathtools.cumulative_sums

`abjad.tools.mathtools.cumulative_sums(sequence)`

Cumulative sums of *sequence*:

```

abjad> from abjad.tools import mathtools

abjad> mathtools.cumulative_sums([1, 2, 3, 4, 5, 6, 7, 8])
[1, 3, 6, 10, 15, 21, 28, 36]

```

Raise type error when *sequence* is neither list nor tuple.

Raise value error on empty *sequence*.

Return list. Changed in version 2.0: renamed `seqtools.cumulative_sums()` to `mathtools.cumulative_sums()`.

mathtools.cumulative_sums_zero

`abjad.tools.mathtools.cumulative_sums_zero(sequence)`

Cumulative sums of *sequence* starting from 0:

```

abjad> from abjad.tools import mathtools

abjad> mathtools.cumulative_sums_zero([1, 2, 3, 4, 5, 6, 7, 8])
[0, 1, 3, 6, 10, 15, 21, 28, 36]

```

Return `[0]` on empty *sequence*:

```

abjad> mathtools.cumulative_sums_zero([ ])
[0]

```

Return list. Changed in version 2.0: renamed `mathtools.cumulative_sums_zero()` to `mathtools.cumulative_sums_zero()`.

mathtools.cumulative_sums_zero_pairwise

`abjad.tools.mathtools.cumulative_sums_zero_pairwise(sequence)`

List pairwise cumulative sums of *sequence* from 0:

```

abjad> from abjad.tools import mathtools

abjad> mathtools.cumulative_sums_zero_pairwise([1, 2, 3, 4, 5, 6])
[(0, 1), (1, 3), (3, 6), (6, 10), (10, 15), (15, 21)]

```

Return list of pairs. Changed in version 2.0: renamed `seqtools.pairwise_cumulative_sums_zero()` to `mathtools.cumulative_sums_zero_pairwise()`.

mathtools.difference_series

`abjad.tools.mathtools.difference_series(sequence)`

Difference series of *sequence*:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.difference_series([1, 1, 2, 3, 5, 5, 6])
[0, 1, 1, 2, 0, 1]
```

Return list. Changed in version 2.0: renamed `seqtools.difference_series()` to `mathtools.difference_series()`.

mathtools.divide_number_by_ratio

`abjad.tools.mathtools.divide_number_by_ratio(number, ratio)`

Divide integer by *ratio*:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.divide_number_by_ratio(1, [1, 1, 3])
[Fraction(1, 5), Fraction(1, 5), Fraction(3, 5)]
```

Divide fraction by *ratio*:

```
abjad> mathtools.divide_number_by_ratio(Fraction(1), [1, 1, 3])
[Fraction(1, 5), Fraction(1, 5), Fraction(3, 5)]
```

Divide float by ratio:

```
abjad> mathtools.divide_number_by_ratio(1.0, [1, 1, 3]) # doctest: +SKIP
[0.20000000000000001, 0.20000000000000001, 0.60000000000000009]
```

Raise type error on nonnumeric *number*.

Raise type error on noninteger in *ratio*.

Return list of fractions or list of floats. Changed in version 2.0: renamed `mathtools.divide_number_by_ratio()` to `mathtools.divide_number_by_ratio()`.

mathtools.divisors

`abjad.tools.mathtools.divisors(n)`

Positive divisors of integer *n* in increasing order:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.divisors(84)
[1, 2, 3, 4, 6, 7, 12, 14, 21, 28, 42, 84]

abjad> for x in range(10, 20):
...     print x, mathtools.divisors(x)
...
10 [1, 2, 5, 10]
```



```

11 [1, 11]
12 [1, 2, 3, 4, 6, 12]
13 [1, 13]
14 [1, 2, 7, 14]
15 [1, 3, 5, 15]
16 [1, 2, 4, 8, 16]
17 [1, 17]
18 [1, 2, 3, 6, 9, 18]
19 [1, 19]

```

Allow nonpositive n :

```

abjad> mathtools.divisors(-27)
[1, 3, 9, 27]

```

Raise type error on noninteger n .

Raise not implemented error on 0.

Return list of positive integers.

mathtools.factors

`abjad.tools.mathtools.factors(n)`

Integer factors of positive integer n in increasing order:

```

abjad> from abjad.tools import mathtools

```

```

abjad> mathtools.factors(84)
[1, 2, 2, 3, 7]

```

```

abjad> for n in range(10, 20):
...     print n, mathtools.factors(n)
...
10 [1, 2, 5]
11 [1, 11]
12 [1, 2, 2, 3]
13 [1, 13]
14 [1, 2, 7]
15 [1, 3, 5]
16 [1, 2, 2, 2, 2]
17 [1, 17]
18 [1, 2, 3, 3]
19 [1, 19]

```

Raise type error on noninteger n .

Raise value error on nonpositive n .

Return list of one or more positive integers.

mathtools.get_shared_numeric_sign

`abjad.tools.mathtools.get_shared_numeric_sign($sequence$)`

Return 1 when all *sequence* elements are positive:

```

abjad> from abjad.tools import mathtools

```

```
abjad> mathtools.get_shared_numeric_sign([1, 2, 3])
1
```

Return -1 when all *sequence* elements are negative:

```
abjad> mathtools.get_shared_numeric_sign([-1, -2, -3])
-1
```

Return 0 on empty *sequence*:

```
abjad> mathtools.get_shared_numeric_sign([ ])
0
```

Otherwise return none:

```
abjad> mathtools.get_shared_numeric_sign([1, 2, -3]) is None
True
```

Return 1, -1, 0 or none. Changed in version 2.0: renamed `seqtools.sign()` to `mathtools.get_shared_numeric_sign()`.

mathtools.greatest_common_divisor

`abjad.tools.mathtools.greatest_common_divisor(*integers)`

New in version 2.0. Greatest common divisor of *integers*:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.greatest_common_divisor(84, -94, -144)
2
```

Allow nonpositive *integers*.

Raise type error on noninteger *integers*.

Raise not implemented error when 0 in *integers*.

Return positive integer.

mathtools.greatest_multiple_less_equal

`abjad.tools.mathtools.greatest_multiple_less_equal(m, n)`

Greatest integer multiple of *m* less than or equal to *n*:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.greatest_multiple_less_equal(10, 47)
40

abjad> for m in range(1, 10):
...     print m, mathtools.greatest_multiple_less_equal(m, 47)
...
1 47
2 46
3 45
4 44
5 45
6 42
7 42
```

```
8 40
9 45

abjad> for n in range(10, 100, 10):
...     print mathtools.greatest_multiple_less_equal(7, n), n
...
7 10
14 20
28 30
35 40
49 50
56 60
70 70
77 80
84 90
```

Raise type error on nonnumeric *m*.

Raise type error on nonnumeric *n*.

Return nonnegative integer.

mathtools.greatest_power_of_two_less_equal

`abjad.tools.mathtools.greatest_power_of_two_less_equal(n, i=0)`

Greatest integer power of two less than or equal to positive *n*:

```
abjad> from abjad.tools import mathtools

abjad> for n in range(10, 20):
...     print '\t%s\t%s' % (n, mathtools.greatest_power_of_two_less_equal(n))
...
    10 8
    11 8
    12 8
    13 8
    14 8
    15 8
    16 16
    17 16
    18 16
    19 16
```

Greatest-but-*i* integer power of 2 less than or equal to positive *n*:

```
abjad> for n in range(10, 20):
...     print '\t%s\t%s' % (n, mathtools.greatest_power_of_two_less_equal(n, i = 1))
...
    10 4
    11 4
    12 4
    13 4
    14 4
    15 4
    16 8
    17 8
    18 8
    19 8
```

Raise type error on nonnumeric n .

Raise value error on nonpositive n .

Return positive integer.

mathtools.integer_equivalent_number_to_integer

`abjad.tools.mathtools.integer_equivalent_number_to_integer(number)`

New in version 2.0. Integer-equivalent $number$ to integer:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.integer_equivalent_number_to_integer(17.0)
17
```

Return noninteger-equivalent number unchanged:

```
abjad> mathtools.integer_equivalent_number_to_integer(17.5)
17.5
```

Raise type error on nonnumber input.

Return number.

mathtools.integer_to_base_k_tuple

`abjad.tools.mathtools.integer_to_base_k_tuple(n, k)`

New in version 2.0. Nonnegative integer n to base- k tuple:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.integer_to_base_k_tuple(1066, 10)
(1, 0, 6, 6)
```

Return tuple of one or more positive integers.

mathtools.integer_to_binary_string

`abjad.tools.mathtools.integer_to_binary_string(n)`

Positive integer n to binary string:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.integer_to_binary_string(5)
'101'
```

```
abjad> for n in range(1, 17):
...     print '\t%s\t%s' % (n, mathtools.integer_to_binary_string(n))
...
1  1
2  10
3  11
4  100
5  101
6  110
7  111
```

```

8 1000
9 1001
10 1010
11 1011
12 1100
13 1101
14 1110
15 1111
16 10000

```

Return string. Changed in version 2.0: renamed `mathtools.binary_string()` to `mathtools.integer_to_binary_string()`.

mathtools.interpolate_cosine

`abjad.tools.mathtools.interpolate_cosine(y1, y2, mu)`

Cosine interpolate *y1* and *y2* with *mu* normalized [0, 1]:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.interpolate_cosine(0, 1, 0.5)
0.49999999999999994
```

Return float. Changed in version 2.0: renamed `interpolate.cosine()` to `mathtools.interpolate_cosine()`.

mathtools.interpolate_divide

`abjad.tools.mathtools.interpolate_divide(total, start_frac, stop_frac, exp='cosine')`

Divide *total* into segments of sizes computed from interpolating between *start_frac* and *stop_frac*:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.interpolate_divide(10, 1, 1, exp=1)
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
abjad> sum(mathtools.interpolate_divide(10, 1, 1, exp=1))
10.0
```

```
abjad> mathtools.interpolate_divide(10, 5, 1) # doctest: +SKIP
[4.7986734489043181, 2.8792040693425909, 1.3263207210948171,
0.99580176065827419]
abjad> sum(mathtools.interpolate_divide(10, 5, 1))
10.0
```

Set `exp='cosine'` for cosine interpolation.

Set *exp* to a numeric value for exponential interpolation with *exp* as the exponent.

Scale resulting segments so that their sum equals exactly *total*.

Return a list of floats. Changed in version 2.0: renamed `interpolate.divide()` to `mathtools.interpolate_divide()`.

mathtools.interpolate_divide_multiple

`abjad.tools.mathtools.interpolate_divide_multiple(totals, key_values, exp='cosine')`

New in version 2.0. Interpolate *key_values* such that the sum of the resulting interpolated values equals the given

totals:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.interpolate_divide_multiple([100, 50], [20, 10, 20]) # doctest: +SKIP
[19.4487, 18.5201, 16.2270, 13.7156, 11.7488, 10.4879,
 9.8515, 9.5130, 10.4213, 13.0736, 16.9918]
```

The operation is the same as `mathtools.interpolate_divide()`. But this function takes multiple *totals* and *key_values* at once.

Precondition: `len(totals) == len(key_values) - 1`.

Set *totals* equal to a list or tuple of the total sum of interpolated values.

Set *key_values* equal to a list or tuple of key values to interpolate.

Set *exp* to *consine* for consine interpolation.

Set *exp* to a number for exponential interpolation.

Returns a list of floats. Changed in version 2.0: renamed `interpolate.divide_multiple()` to `mathtools.interpolate_divide_multiple()`.

mathtools.interpolate_exponential

```
abjad.tools.mathtools.interpolate_exponential(y1, y2, mu, exp=1)
```

Exponential interpolate *y1* and *y2* with *mu* normalized `[0, 1]`:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.interpolate_exponential(0, 1, 0.5, 4)
0.0625
```

Set *exp* equal to the exponent of interpolation.

Return float. Changed in version 2.0: renamed `interpolate.exponential()` to `mathtools.interpolate_exponential()`.

mathtools.interpolate_linear

```
abjad.tools.mathtools.interpolate_linear(y1, y2, mu)
```

Linear interpolate *y1* and *y2* with *mu* normalized `[0, 1]`:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.interpolate_linear(0, 1, 0.5)
0.5
```

Return float. Changed in version 2.0: renamed `interpolate.linear()` to `mathtools.interpolate_linear()`.

mathtools.is_assignable_integer

```
abjad.tools.mathtools.is_assignable_integer(expr)
```

New in version 2.0. True when *expr* is equivalent to an integer and can be written without recourse to ties:

```

abjad> from abjad.tools import mathtools

abjad> for n in range(0, 16 + 1):
...     print '%s\t%s' % (n, mathtools.is_assignable_integer(n))
...
0  False
1  True
2  True
3  True
4  True
5  False
6  True
7  True
8  True
9  False
10 False
11 False
12 True
13 False
14 True
15 True
16 True

```

Otherwise false.

Return boolean. Changed in version 2.0: renamed `mathtools.is_assignable()` to `mathtools.is_assignable_integer()`.

mathtools.is_dotted_integer

`abjad.tools.mathtools.is_dotted_integer(expr)`

New in version 2.0. True when *expr* is equivalent to a positive integer and can be written with zero or more dots:

```

abjad> from abjad.tools import mathtools

abjad> for expr in range(16):
...     print '%s\t%s' % (expr, mathtools.is_dotted_integer(expr))
...
0      False
1      False
2      False
3      True
4      False
5      False
6      True
7      True
8      False
9      False
10     False
11     False
12     True
13     False
14     True
15     True

```

Otherwise false.

Return boolean.

Integer n qualifies as dotted when $\text{abs}(n)$ is of the form $2^{**j} * (2^{**k} - 1)$ with integers $0 \leq j, 2 < k$.

mathtools.is_integer_equivalent_number

`abjad.tools.mathtools.is_integer_equivalent_number(expr)`

New in version 2.0. True *expr* is a number and *expr* is equivalent to an integer:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.is_integer_equivalent_number(12.0)
True
```

Otherwise false:

```
abjad> mathtools.is_integer_equivalent_number(Duration(1, 2))
False
```

Return boolean.

mathtools.is_negative_integer

`abjad.tools.mathtools.is_negative_integer(expr)`

New in version 2.0. True when *expr* equals a negative integer:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.is_negative_integer(-1)
True
```

Otherwise false:

```
abjad> mathtools.is_negative_integer(0)
False
```

```
abjad> mathtools.is_negative_integer(99)
False
```

Return boolean.

mathtools.is_nonnegative_integer

`abjad.tools.mathtools.is_nonnegative_integer(expr)`

New in version 2.0. True when *expr* equals a nonnegative integer:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.is_nonnegative_integer(99)
True
```

```
abjad> mathtools.is_nonnegative_integer(0)
True
```

Otherwise false:

```
abjad> mathtools.is_nonnegative_integer(-1)
False
```


Return boolean.

mathtools.is_nonnegative_integer_equivalent_number

`abjad.tools.mathtools.is_nonnegative_integer_equivalent_number(expr)`
New in version 2.0. True when *expr* is a nonnegative integer-equivalent number. Otherwise false:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.is_nonnegative_integer_equivalent_number(Duration(4, 2))
True
```

Return boolean.

mathtools.is_nonnegative_integer_power_of_two

`abjad.tools.mathtools.is_nonnegative_integer_power_of_two(expr)`
True when *expr* is a nonnegative integer power of 2:

```
abjad> from abjad.tools import mathtools

abjad> for n in range(10):
...     print n, mathtools.is_nonnegative_integer_power_of_two(n)
...
0 True
1 True
2 True
3 False
4 True
5 False
6 False
7 False
8 True
9 False
```

Otherwise false.

Return boolean. Changed in version 2.0: renamed `mathtools.is_power_of_two()` to `mathtools.is_nonnegative_integer_power_of_two()`.

mathtools.is_positive_integer

`abjad.tools.mathtools.is_positive_integer(expr)`
New in version 2.0. True when *expr* equals a positive integer:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.is_positive_integer(99)
True
```

Otherwise false:

```
abjad> mathtools.is_positive_integer(0)
False
```

```
abjad> mathtools.is_positive_integer(-1)
False
```

Return boolean.

mathtools.is_positive_integer_equivalent_number

`abjad.tools.mathtools.is_positive_integer_equivalent_number(expr)`
New in version 2.0. True when *expr* is a positive integer-equivalent number. Otherwise false:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.is_positive_integer_equivalent_number(Duration(4, 2))
True
```

Return boolean.

mathtools.least_common_multiple

`abjad.tools.mathtools.least_common_multiple(*integers)`
Least common multiple of positive *integers*:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.least_common_multiple(2, 4, 5, 10, 20)
20
```

Return positive integer.

mathtools.least_multiple_greater_equal

`abjad.tools.mathtools.least_multiple_greater_equal(m, n)`
Return the least integer multiple of *m* greater than or equal to *n*.

```
abjad> from abjad.tools import mathtools

abjad> mathtools.least_multiple_greater_equal(10, 47)
50

abjad> for m in range(1, 10):
...     print m, mathtools.least_multiple_greater_equal(m, 47)
...
1 47
2 48
3 48
4 48
5 50
6 48
7 49
8 48
9 54

abjad> for n in range(10, 100, 10):
...     print mathtools.least_multiple_greater_equal(7, n), n
...
14 10
```

```
21 20
35 30
42 40
56 50
63 60
70 70
84 80
91 90
```

Return integer.

mathtools.least_power_of_two_greater_equal

`abjad.tools.mathtools.least_power_of_two_greater_equal(n, i=0)`

Return least integer power of two greater than or equal to positive n :

```
abjad> from abjad.tools import mathtools

abjad> for n in range(10, 20):
...     print '\t%s\t%s' % (n, mathtools.least_power_of_two_greater_equal(n))
...
    10 16
    11 16
    12 16
    13 16
    14 16
    15 16
    16 16
    17 32
    18 32
    19 32
```

When $i = 1$, return the first integer power of 2 greater than the least integer power of 2 greater than or equal to n .

```
abjad> for n in range(10, 20):
...     print '\t%s\t%s' % (n, mathtools.least_power_of_two_greater_equal(n, i = 1))
...
    10 32
    11 32
    12 32
    13 32
    14 32
    15 32
    16 32
    17 64
    18 64
    19 64
```

When $i = 2$, return the second integer power of 2 greater than the least integer power of 2 greater than or equal to n , and, in general, return the i th integer power of 2 greater than the least integer power of 2 greater than or equal to n .

Raise type error on nonnumeric n .

Raise value error on nonpositive n .

Return integer.

mathtools.next_integer_partition

`abjad.tools.mathtools.next_integer_partition(integer_partition)`

New in version 2.0. Next integer partition following *integer_partition* in descending lex order:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.next_integer_partition((8, 3))
(8, 2, 1)

abjad> mathtools.next_integer_partition((8, 2, 1))
(8, 1, 1, 1)

abjad> mathtools.next_integer_partition((8, 1, 1, 1))
(7, 4)
```

Input *integer_partition* must be sequence of positive integers.

Return integer partition as tuple of positive integers.

mathtools.partition_integer_by_ratio

`abjad.tools.mathtools.partition_integer_by_ratio(n, ratio)`

Partition positive integer-equivalent *n* by *ratio*:

```
abjad> from abjad.tools import mathtools

abjad> mathtools.partition_integer_by_ratio(10, [1, 2])
[3, 7]
```

Partition positive integer-equivalent *n* by *ratio* with negative parts:

```
abjad> mathtools.partition_integer_by_ratio(10, [1, -2])
[3, -7]
```

Partition negative integer-equivalent *n* by *ratio*:

```
abjad> mathtools.partition_integer_by_ratio(-10, [1, 2])
[-3, -7]
```

Partition negative integer-equivalent *n* by *ratio* with negative parts:

```
abjad> mathtools.partition_integer_by_ratio(-10, [1, -2])
[-3, 7]
```

Return result with weight equal to absolute value of *n*.

Raise type error on noninteger *n*.

Return list of integers.

mathtools.partition_integer_into_canonic_parts

`abjad.tools.mathtools.partition_integer_into_canonic_parts(n, direction='big-endian')`

Partition integer *n* into big-endian or small-endian parts.

Return all parts positive on positive *n*:

```

abjad> from abjad.tools import mathtools

abjad> for n in range(1, 11):
...     print n, mathtools.partition_integer_into_canonic_parts(n)
...
1 (1,)
2 (2,)
3 (3,)
4 (4,)
5 (4, 1)
6 (6,)
7 (7,)
8 (8,)
9 (8, 1)
10 (8, 2)

```

Return all parts negative on negative n :

```

abjad> for n in reversed(range(-20, -10)):
...     print n, mathtools.partition_integer_into_canonic_parts(n)
...
-11 (-8, -3)
-12 (-12,)
-13 (-12, -1)
-14 (-14,)
-15 (-15,)
-16 (-16,)
-17 (-16, -1)
-18 (-16, -2)
-19 (-16, -3)
-20 (-16, -4)

```

Return little-endian tuple When `direction = 'little-endian'`:

```

abjad> for n in range(11, 21):
...     print n, mathtools.partition_integer_into_canonic_parts(n, direction = 'little-endian')
...
11 (3, 8)
12 (12,)
13 (1, 12)
14 (14,)
15 (15,)
16 (16,)
17 (1, 16)
18 (2, 16)
19 (3, 16)
20 (4, 16)

```

Return big-endian tuple $t = (t_0, \dots, t_j)$ such that

- $\text{sum}(t) == n$
- t_i can be written without recourse to ties, and
- $t_{(i + 1)} < t_i$ for every t_i in t .

Raise type error on noninteger n .

Return tuple of one or more integers.

mathtools.partition_integer_into_halves

abjad.tools.mathtools.**partition_integer_into_halves**(*n*, *bigger*='left',
even='allowed')

Write positive integer *n* as the pair *t* = (*left*, *right*) such that *n* == *left* + *right*.

When *n* is odd the greater part of *t* corresponds to the value of *bigger*:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.partition_integer_into_halves(7, bigger = 'left')
(4, 3)
abjad> mathtools.partition_integer_into_halves(7, bigger = 'right')
(3, 4)
```

Likewise when *n* is even and *even* = 'disallowed':

```
abjad> mathtools.partition_integer_into_halves(8, bigger = 'left', even = 'disallowed')
(5, 3)
abjad> mathtools.partition_integer_into_halves(8, bigger = 'right', even = 'disallowed')
(3, 5)
```

But when *n* is even and *even* = 'allowed' then *left* == *right* and *bigger* is ignored:

```
abjad> mathtools.partition_integer_into_halves(8)
(4, 4)
abjad> mathtools.partition_integer_into_halves(8, bigger = 'left')
(4, 4)
abjad> mathtools.partition_integer_into_halves(8, bigger = 'right')
(4, 4)
```

When *n* is 0 return (0, 0):

```
abjad> mathtools.partition_integer_into_halves(0)
(0, 0)
```

When *n* is 0 and *even* = 'disallowed' raise partition error.

Raise type error on noninteger *n*.

Raise value error on negative *n*.

Return pair of positive integers.

mathtools.partition_integer_into_thirds

abjad.tools.mathtools.**partition_integer_into_thirds**(*n*, *smallest*='middle',
biggest='middle')

Partition positive integer *n* into *left*, *middle*, *right* parts.

When *n* % 3 == 0, *left* == *middle* == *right*:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.partition_integer_into_thirds(9)
(3, 3, 3)
```

When *n* % 3 == 1, set biggest part to *biggest*:

```

abjad> mathtools.partition_integer_into_thirds(10, biggest = 'left')
(4, 3, 3)
abjad> mathtools.partition_integer_into_thirds(10, biggest = 'middle')
(3, 4, 3)
abjad> mathtools.partition_integer_into_thirds(10, biggest = 'right')
(3, 3, 4)

```

When $n \% 3 == 2$, set smallest part to *smallest*:

```

abjad> mathtools.partition_integer_into_thirds(11, smallest = 'left')
(3, 4, 4)
abjad> mathtools.partition_integer_into_thirds(11, smallest = 'middle')
(4, 3, 4)
abjad> mathtools.partition_integer_into_thirds(11, smallest = 'right')
(4, 4, 3)

```

Raise type error on noninteger n .

Raise value error on nonpositive n .

Return triple of positive integers.

mathtools.partition_integer_into_units

abjad.tools.mathtools.**partition_integer_into_units**(n)

Partition positive integer into units:

```

abjad> from abjad.tools import mathtools

```

```

abjad> mathtools.partition_integer_into_units(6)
[1, 1, 1, 1, 1, 1]

```

Partition negative integer into units:

```

abjad> mathtools.partition_integer_into_units(-5)
[-1, -1, -1, -1, -1]

```

Partition 0 into units:

```

abjad> mathtools.partition_integer_into_units(0)
[]

```

Return list of zero or more parts with absolute value equal to 1.

mathtools.remove_powers_of_two

abjad.tools.mathtools.**remove_powers_of_two**(n)

Remove powers of 2 from the factors of positive integer n :

```

abjad> from abjad.tools import mathtools

```

```

abjad> for n in range(10, 100, 10):
...     print '\t%s\t%s' % (n, mathtools.remove_powers_of_two(n))
...
    10 5
    20 5
    30 15
    40 5

```

```
50 25
60 15
70 35
80 5
90 45
```

Raise type error on noninteger n .

Raise value error on nonpositive n .

Return positive integer.

mathtools.sign

`abjad.tools.mathtools.sign(n)`

Return -1 on negative n :

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.sign(-96.2)
-1
```

Return 0 when n is 0 :

```
abjad> mathtools.sign(0)
0
```

Return 1 on positive n :

```
abjad> mathtools.sign(Duration(9, 8))
1
```

Return -1 , 0 or 1 .

mathtools.weight

`abjad.tools.mathtools.weight(sequence, start=0)`

Sum of the absolute value of the elements in *sequence*:

```
abjad> from abjad.tools import mathtools
```

```
abjad> mathtools.weight([-1, -2, 3, 4, 5])
15
```

Absolute value of *start*:

```
abjad> mathtools.weight([ ])
0
```

Return nonnegative integer. Changed in version 2.0: renamed `seqtools.weight()` to `mathtools.weight()`.

mathtools.yield_all_compositions_of_integer

`abjad.tools.mathtools.yield_all_compositions_of_integer(n)`

New in version 2.0. Yield all compositions of positive integer n in descending lex order:


```

abjad> from abjad.tools import mathtools

abjad> for integer_composition in mathtools.yield_all_compositions_of_integer(5):
...     integer_composition
...
(5,)
(4, 1)
(3, 2)
(3, 1, 1)
(2, 3)
(2, 2, 1)
(2, 1, 2)
(2, 1, 1, 1)
(1, 4)
(1, 3, 1)
(1, 2, 2)
(1, 2, 1, 1)
(1, 1, 3)
(1, 1, 2, 1)
(1, 1, 1, 2)
(1, 1, 1, 1, 1)

```

Integer compositions are ordered integer partitions.

Return generator of positive integer tuples of length at least 1. Changed in version 2.0: renamed `mathtools.integer_compositions()` to `mathtools.yield_all_compositions_of_integer()`.

mathtools.yield_all_partitions_of_integer

`abjad.tools.mathtools.yield_all_partitions_of_integer(n)`

New in version 2.0. Yield all partitions of positive integer n in descending lex order:

```

abjad> from abjad.tools import mathtools

abjad> for partition in mathtools.yield_all_partitions_of_integer(7):
...     partition
...
(7,)
(6, 1)
(5, 2)
(5, 1, 1)
(4, 3)
(4, 2, 1)
(4, 1, 1, 1)
(3, 3, 1)
(3, 2, 2)
(3, 2, 1, 1)
(3, 1, 1, 1, 1)
(2, 2, 2, 1)
(2, 2, 1, 1, 1)
(2, 1, 1, 1, 1, 1)
(1, 1, 1, 1, 1, 1, 1)

```

Return generator of positive integer tuples of length at least 1. Changed in version 2.0: renamed `mathtools.integer_partitions()` to `mathtools.yield_all_partitions_of_integer()`.

metertools

metertools.duration_and_possible_denominators_to_meter

`abjad.tools.metertools.duration_and_possible_denominators_to_meter` (*duration*,
de-
nomina-
tors=None,
fac-
tor=None)

Make new meter equal to *duration*:

```
abjad> from abjad.tools import metertools
```

```
abjad> metertools.duration_and_possible_denominators_to_meter(Duration(3, 2))
TimeSignatureMark(3, 2)
```

Make new meter equal to *duration* with denominator equal to the first possible element in *denominators*:

```
abjad> metertools.duration_and_possible_denominators_to_meter(Duration(3, 2), denominators = [5,
TimeSignatureMark(9, 6)
```

Make new meter equal to *duration* with denominator divisible by *factor*:

```
abjad> metertools.duration_and_possible_denominators_to_meter(Duration(3, 2), factor = 5)
TimeSignatureMark(15, 10)
```

Return new meter. Changed in version 2.0: renamed `metertools.make_best()` to `metertools.duration_and_possible_denominators_to_meter()`.

metertools.get_nonbinary_factor_from_meter_denominator

`abjad.tools.metertools.get_nonbinary_factor_from_meter_denominator` (*meter*)

Get nonbinary factor from nonbinary *meter* denominator:

```
abjad> from abjad.tools import metertools
```

```
abjad> metertools.get_nonbinary_factor_from_meter_denominator(contexttools.TimeSignatureMark(3,
3
```

```
abjad> metertools.get_nonbinary_factor_from_meter_denominator(contexttools.TimeSignatureMark(3,
13
```

```
abjad> metertools.get_nonbinary_factor_from_meter_denominator(contexttools.TimeSignatureMark(3,
7
```

```
abjad> metertools.get_nonbinary_factor_from_meter_denominator(contexttools.TimeSignatureMark(3,
15
```

Get 1 from binary *meter* denominator:

```
abjad> metertools.get_nonbinary_factor_from_meter_denominator(contexttools.TimeSignatureMark(3,
1
```

Return nonnegative integer.

metertools.is_meter_with_equivalent_binary_representation

`abjad.tools.metertools.is_meter_with_equivalent_binary_representation(expr)`

True when *expr* is a meter with binary-valued duration:

```
abjad> from abjad.tools import metertools
```

```
abjad> metertools.is_meter_with_equivalent_binary_representation(contexttools.TimeSignatureMark(3, 12))
True
```

Otherwise false:

```
abjad> metertools.is_meter_with_equivalent_binary_representation(contexttools.TimeSignatureMark(2, 8))
False
```

```
abjad> metertools.is_meter_with_equivalent_binary_representation('text')
False
```

Return boolean.

metertools.meter_to_binary_meter

`abjad.tools.metertools.meter_to_binary_meter(nonbinary_meter, contents_multiplier=Fraction(1, 1))` *contents_multiplier*=*Fraction(1, 1)*

Change nonbinary *meter* to binary meter:

```
abjad> from abjad.tools import metertools
```

```
abjad> metertools.meter_to_binary_meter(contexttools.TimeSignatureMark(3, 12))
TimeSignatureMark(2, 8)
```

Preserve binary *meter*:

```
abjad> metertools.meter_to_binary_meter(contexttools.TimeSignatureMark(2, 8))
TimeSignatureMark(2, 8)
```

Return newly constructed meter. Changed in version 2.0: renamed `metertools.make_binary()` to `metertools.meter_to_binary_meter()`.

`pitcharraytools`

pitcharraytools.PitchArray

`class abjad.tools.pitcharraytools.PitchArray(*args)`

Bases: `abjad.core._StrictComparator._StrictComparator` New in version 2.0. Two-dimensional array of pitches.

`append_column(column)`

`append_row(row)`

`apply_pitches_by_row(pitch_lists)`

`cell_tokens_by_row`

`cell_widths_by_row`

`cells`

`columns`

```

copy_subarray(upper_left_pair, lower_right_pair)
depth
dimensions
has_spanning_cell_over_index(index)
has_voice_crossing
is_rectangular
pad_to_depth(depth)
pad_to_width(width)
pitches
pitches_by_row
pop_column(column_index)
pop_row(row_index=-1)
remove_row(row)
rows
size
voice_crossing_count
weight
width

```

pitcharraytools.PitchArrayCell

```

class abjad.tools.pitcharraytools.PitchArrayCell(cell_token=None)
    Bases: abjad.core._StrictComparator._StrictComparator._StrictComparator

```

One cell in a pitch array.

```

abjad> from abjad.tools import pitcharraytools

abjad> array = pitcharraytools.PitchArray([[1, 2, 1], [2, 1, 1]])
abjad> print array
[ ] [   ] [ ]
[   ] [ ] [ ]
abjad> cell = array[0][1]
abjad> cell
PitchArrayCell(x2)

abjad> cell.column_indices
(1, 2)

abjad> cell.indices
(0, (1, 2))

abjad> cell.is_first_in_row
False

abjad> cell.is_last_in_row
False

```

```
abjad> cell.next
PitchArrayCell(x1)

abjad> cell.parent_array
PitchArray(PitchArrayRow(x1, x2, x1), PitchArrayRow(x2, x1, x1))

abjad> cell.parent_column
PitchArrayColumn(x2, x2)

abjad> cell.parent_row
PitchArrayRow(x1, x2, x1)

abjad> cell.pitches
[]

abjad> cell.prev
PitchArrayCell(x1)

abjad> cell.row_index
0

abjad> cell.token
2

abjad> cell.width
2
```

Return pitch array cell.

column_indices

Read-only tuple of one or more nonnegative integer indices.

indices

is_first_in_row

is_last_in_row

matches_cell (*arg*)

next

parent_array

parent_column

parent_row

pitches

prev

row_index

token

weight

width

pitcharraytools.PitchArrayColumn

class abjad.tools.pitcharraytools.**PitchArrayColumn** (*cells*)
 Bases: abjad.core._StrictComparator._StrictComparator._StrictComparator New in version 2.0. Column in a pitch array:

```
abjad> from abjad.tools import pitcharraytools
```

```
abjad> array = pitcharraytools.PitchArray([
...     [1, (2, 1), (-1.5, 2)],
...     [(7, 2), (6, 1), 1]])
```

```
abjad> print array
[ ] [d'] [bqf ]
[g'      ] [fs'] [ ]
```

```
abjad> array.columns[0]
PitchArrayColumn(x1, g' x2)
```

```
abjad> print array.columns[0]
[ ]
[g'      ]
```

Return pitch array column.

append (*cell*)

cell_tokens

cell_widths

cells

column_index

depth

dimensions

extend (*cells*)

has_voice_crossing

is_defective

parent_array

pitches

remove_pitches ()

start_cells

start_pitches

stop_cells

stop_pitches

weight

width

pitcharraytools.PitchArrayRow

class abjad.tools.pitcharraytools.**PitchArrayRow**(*cells*)
 Bases: abjad.core._StrictComparator._StrictComparator._StrictComparator New in version 2.0. One row in pitch array.

```
abjad> from abjad.tools import pitcharraytools

abjad> array = pitcharraytools.PitchArray([[1, 2, 1], [2, 1, 1]])
abjad> array[0].cells[0].pitches.append(0)
abjad> array[0].cells[1].pitches.append(2)
abjad> array[1].cells[2].pitches.append(4)
abjad> print array
[c'] [d'   ] [  ]
[      ] [  ] [e']

abjad> array[0]
PitchArrayRow(c', d' x2, x1)

abjad> array[0].cell_widths
(1, 2, 1)

abjad> array[0].dimensions
(1, 4)

abjad> array[0].pitches
(NamedChromaticPitch("c'"), NamedChromaticPitch("d'"))
```

Return pitch array row.

append(*cell_token*)
apply_pitches(*pitch_tokens*)
cell_tokens
cell_widths
cells
copy_subrow(*start=None, stop=None*)
depth
dimensions
empty_pitches()
extend(*cell_tokens*)
has_spanning_cell_over_index(*i*)
index(*cell*)
is_defective
is_in_range
merge(*cells*)
pad_to_width(*width*)
parent_array
pitch_range

pitches
pop (*cell_index*)
remove (*cell*)
row_index
weight
width
withdraw ()

pitcharraytools.concatenate_pitch_arrays

`abjad.tools.pitcharraytools.concatenate_pitch_arrays` (*pitch_arrays*)

New in version 2.0. Concatenate *pitch_arrays*:

```

abjad> from abjad.tools import pitcharraytools

abjad> array_1 = pitcharraytools.PitchArray([[1, 2, 1], [2, 1, 1]])
abjad> print array_1
[ ] [   ] [ ]
[   ] [ ] [ ]

abjad> array_2 = pitcharraytools.PitchArray([[3, 4], [4, 3]])
abjad> print array_2
[   ] [   ]
[   ] [   ]

abjad> array_3 = pitcharraytools.PitchArray([[1, 1], [1, 1]])
abjad> print array_3
[ ] [ ]
[ ] [ ]

abjad> merged_array = pitcharraytools.concatenate_pitch_arrays([array_1, array_2, array_3])
abjad> print merged_array
[ ] [   ] [ ] [   ] [   ] [ ] [ ] [ ]
[   ] [ ] [ ] [   ] [   ] [ ] [ ] [ ]
    
```

Return pitch array.

pitcharraytools.list_nonspanning_subarrays_of_pitch_array

`abjad.tools.pitcharraytools.list_nonspanning_subarrays_of_pitch_array` (*pitch_array*)

New in version 2.0. List nonspanning subarrays of *pitch_array*:

```

abjad> from abjad.tools import pitcharraytools

abjad> array = pitcharraytools.PitchArray([
...     [2, 2, 3, 1],
...     [1, 2, 1, 1, 2, 1],
...     [1, 1, 1, 1, 1, 1, 1, 1]])
abjad> print array
[   ] [   ] [   ] [   ]
[ ] [   ] [ ] [ ] [   ] [ ]
[ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ]
    
```



```

abjad> subarrays = pitcharraytools.list_nonspanning_subarrays_of_pitch_array(array)
abjad> len(subarrays)
3

abjad> print subarrays[0]
[      ] [      ]
[ ] [      ] [ ]
[ ] [ ] [ ] [ ]

abjad> print subarrays[1]
[      ]
[ ] [      ]
[ ] [ ] [ ]

abjad> print subarrays[2]
[ ]
[ ]
[ ]

```

Return list.

pitcharraytools.make_empty_pitch_array_from_list_of_pitch_lists

`abjad.tools.pitcharraytools.make_empty_pitch_array_from_list_of_pitch_lists` (*leaf_iterables*)

New in version 2.0. Make empty pitch array from *leaf_iterables*:

```

abjad> from abjad.tools import pitcharraytools

abjad> score = Score([ ])
abjad> score.append(Staff("c'8 d'8 e'8 f'8"))
abjad> score.append(Staff("c'4 d'4"))
abjad> score.append(Staff(tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8") * 2))
abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
  \new Staff {
    c'4
    d'4
  }
  \new Staff {
    \times 2/3 {
      c'8
      d'8
      e'8
    }
    \times 2/3 {
      c'8
      d'8
      e'8
    }
  }
>>

```

```
abjad> array = pitcharraytools.make_empty_pitch_array_from_list_of_pitch_lists(score)
abjad> print array
[      ] [      ] [      ] [      ]
[      ] [      ] [      ] [      ]
[ ] [      ] [ ] [ ] [      ] [ ]
```

Return pitch array.

`pitcharraytools.make_populated_pitch_array_from_list_of_pitch_lists`

`abjad.tools.pitcharraytools.make_populated_pitch_array_from_list_of_pitch_lists` (*leaf_iterables*)
 New in version 2.0. Make populated pitch array from *leaf_iterables*:

```
abjad> from abjad.tools import pitcharraytools

abjad> score = Score([ ])
abjad> score.append(Staff("c'8 d'8 e'8 f'8"))
abjad> score.append(Staff("c'4 d'4"))
abjad> score.append(Staff(tuplettools.FixedDurationTuplet(Duration(2, 8), "c'8 d'8 e'8") * 2))
abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8
    e'8
    f'8
  }
  \new Staff {
    c'4
    d'4
  }
  \new Staff {
    \times 2/3 {
      c'8
      d'8
      e'8
    }
    \times 2/3 {
      c'8
      d'8
      e'8
    }
  }
>>

abjad> array = pitcharraytools.make_populated_pitch_array_from_list_of_pitch_lists(score)
abjad> print array
[c'      ] [d'      ] [e'      ] [f'      ]
[c'      ] [d'      ] [d'      ]
[c'] [d'      ] [e'] [c'] [d'      ] [e']
```

Return pitch array.

seqtools

seqtools.CyclicList**class** abjad.tools.seqtools.**CyclicList**

Bases: list New in version 2.0. Abjad model of cyclic list:

```

abjad> from abjad.tools import seqtools

abjad> cyclic_list = seqtools.CyclicList('abcd')

abjad> cyclic_list
['a', 'b', 'c', 'd']

abjad> for x in range(8):
...     print x, cyclic_list[x]
...
0 a
1 b
2 c
3 d
4 a
5 b
6 c
7 d

```

Cyclic lists overload the item-getting method of built-in lists.

Cyclic lists return a value for any integer index.

Cyclic lists otherwise behave exactly like built-in lists.

seqtools.CyclicMatrix**class** abjad.tools.seqtools.**CyclicMatrix**(*args, **kwargs)

Bases: abjad.tools.seqtools.Matrix.Matrix New in version 2.0. Abjad model of cyclic matrix.

Initialize from rows:

```

abjad> from abjad.tools import seqtools

abjad> cyclic_matrix = seqtools.CyclicMatrix([[0, 1, 2, 3], [10, 11, 12, 13], [20, 21, 22, 23]])

abjad> cyclic_matrix
CyclicMatrix(3x4)

abjad> cyclic_matrix[2]
(20, 21, 22, 23)

abjad> cyclic_matrix[2][2]
22

abjad> cyclic_matrix[99]
(0, 1, 2, 3)

abjad> cyclic_matrix[99][99]
3

```

Initialize from columns:

```

abjad> cyclic_matrix = seqtools.CyclicMatrix(columns = [[0, 10, 20], [1, 11, 21], [2, 12, 22], [3, 13, 23]])

abjad> cyclic_matrix
CyclicMatrix(3x4)

abjad> cyclic_matrix[2]
(20, 21, 22, 23)

abjad> cyclic_matrix[2][2]
22

abjad> cyclic_matrix[99]
(0, 1, 2, 3)

abjad> cyclic_matrix[99][99]
3

```

CyclicMatrix implements only item retrieval in this revision.

Concatenation and division remain to be implemented.

Standard transforms of linear algebra remain to be implemented.

columns

Read-only columns:

```

abjad> cyclic_matrix = seqtools.CyclicMatrix([[0, 1, 2, 3], [10, 11, 12, 13], [20, 21, 22, 23], [30, 31, 32, 33]])

abjad> cyclic_matrix.columns
((0, 10, 20), (1, 11, 21), (2, 12, 22), (3, 13, 23))

```

Return cyclic tuple.

rows

Read-only rows:

```

abjad> cyclic_matrix = seqtools.CyclicMatrix([[0, 1, 2, 3], [10, 11, 12, 13], [20, 21, 22, 23], [30, 31, 32, 33]])

abjad> cyclic_matrix.rows
((0, 1, 2, 3), (10, 11, 12, 13), (20, 21, 22, 23))

```

Return cyclic tuple.

seqtools.CyclicTuple

class `abjad.tools.seqtools.CyclicTuple`

Bases: `tuple` New in version 2.0. Abjad model of cyclic tuple:

```

abjad> from abjad.tools import seqtools

abjad> cyclic_tuple = seqtools.CyclicTuple('abcd')

abjad> cyclic_tuple
('a', 'b', 'c', 'd')

abjad> for x in range(8):
...     print x, cyclic_tuple[x]
...
0 a

```

```
1 b
2 c
3 d
4 a
5 b
6 c
7 d
```

Cyclic tuples overload the item-getting method of built-in tuples.

Cyclic tuples return a value for any integer index.

Cyclic tuples otherwise behave exactly like built-in tuples.

seqtools.Matrix

class abjad.tools.seqtools.**Matrix**(*args, **kwargs)

Bases: object New in version 2.0. Abjad model of matrix.

Initialize from rows:

```
abjad> from abjad.tools import seqtools
```

```
abjad> matrix = seqtools.Matrix([[0, 1, 2, 3], [10, 11, 12, 13], [20, 21, 22, 23]])
```

```
abjad> matrix
Matrix(3x4)
```

```
abjad> matrix[:]
((0, 1, 2, 3), (10, 11, 12, 13), (20, 21, 22, 23))
```

```
abjad> matrix[2]
(20, 21, 22, 23)
```

```
abjad> matrix[2][0]
20
```

Initialize from columns:

```
abjad> matrix = seqtools.Matrix(columns = [[0, 10, 20], [1, 11, 21], [2, 12, 22], [3, 13, 23]])
```

```
abjad> matrix
Matrix(3x4)
```

```
abjad> matrix[:]
((0, 1, 2, 3), (10, 11, 12, 13), (20, 21, 22, 23))
```

```
abjad> matrix[2]
(20, 21, 22, 23)
```

```
abjad> matrix[2][0]
20
```

Matrix implements only item retrieval in this revision.

Concatenation and division remain to be implemented.

Standard transforms of linear algebra remain to be implemented.

columns

Read-only columns:

```
abjad> matrix = seqtools.Matrix([[0, 1, 2, 3], [10, 11, 12, 13], [20, 21, 22, 23]])

abjad> matrix.columns
((0, 10, 20), (1, 11, 21), (2, 12, 22), (3, 13, 23))
```

Return tuple.

rows

Read-only rows:

```
abjad> matrix = seqtools.Matrix([[0, 1, 2, 3], [10, 11, 12, 13], [20, 21, 22, 23]])

abjad> matrix.rows
((0, 1, 2, 3), (10, 11, 12, 13), (20, 21, 22, 23))
```

Return tuple.

seqtools.all_are_assignable_integers

`abjad.tools.seqtools.all_are_assignable_integers(expr)`

New in version 2.0. True when *expr* is a sequence and all elements in *expr* are notehead-assignable integers:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.all_are_assignable_integers([1, 2, 3, 4, 6, 7, 8, 12, 14, 15, 16])
True
```

True when *expr* is an empty sequence:

```
abjad> seqtools.all_are_assignable_integers([ ])
True
```

False otherwise:

```
abjad> seqtools.all_are_assignable_integers('foo')
False
```

Return boolean.

seqtools.all_are_equal

`abjad.tools.seqtools.all_are_equal(expr)`

New in version 2.0. True when *expr* is a sequence and all elements in *expr* are equal:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.all_are_equal([99, 99, 99, 99, 99, 99])
True
```

True when *expr* is an empty sequence:

```
abjad> seqtools.all_are_equal([ ])
True
```

False otherwise:

```
abjad> seqtools.all_are_equal(17)
False
```

Return boolean.

seqtools.all_are_integer_equivalent_numbers

`abjad.tools.seqtools.all_are_integer_equivalent_numbers(expr)`

New in version 2.0. True when *expr* is a sequence and all elements in *expr* are integer-equivalent numbers:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.all_are_integer_equivalent_numbers([1, 2, 3.0, Fraction(4, 1)])
True
```

Otherwise false:

```
abjad> seqtools.all_are_integer_equivalent_numbers([1, 2, 3.5, 4])
False
```

Return boolean.

seqtools.all_are_nonnegative_integer_equivalent_numbers

`abjad.tools.seqtools.all_are_nonnegative_integer_equivalent_numbers(expr)`

New in version 2.0. True *expr* is a sequence and when all elements in *expr* are nonnegative integer-equivalent numbers. Otherwise false:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.all_are_nonnegative_integer_equivalent_numbers([0, 0.0, Fraction(0), 2, 2.0, Fraction(2, 1)])
True
```

Return boolean.

seqtools.all_are_nonnegative_integer_powers_of_two

`abjad.tools.seqtools.all_are_nonnegative_integer_powers_of_two(expr)`

New in version 2.0. True when *expr* is a sequence and all elements in *expr* are nonnegative integer powers of two:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.all_are_nonnegative_integer_powers_of_two([0, 1, 1, 1, 2, 4, 32, 32])
True
```

True when *expr* is an empty sequence:

```
abjad> seqtools.all_are_nonnegative_integer_powers_of_two([ ])
True
```

False otherwise:

```
abjad> seqtools.all_are_nonnegative_integer_powers_of_two(17)
False
```

Return boolean.

seqtools.all_are_nonnegative_integers

`abjad.tools.seqtools.all_are_nonnegative_integers(expr)`

New in version 2.0. True when *expr* is a sequence and all elements in *expr* are nonnegative integers:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.all_are_nonnegative_integers([0, 1, 2, 99])
True
```

Otherwise false:

```
abjad> seqtools.all_are_nonnegative_integers([0, 1, 2, -99])
False
```

Return boolean.

seqtools.all_are_numbers

`abjad.tools.seqtools.all_are_numbers(expr)`

New in version 1.1. True when *expr* is a sequence and all elements in *expr* are numbers:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.all_are_numbers([1, 2, 3.0, Fraction(13, 8)])
True
```

True when *expr* is an empty sequence:

```
abjad> seqtools.all_are_numbers([ ])
True
```

False otherwise:

```
abjad> seqtools.all_are_numbers(17)
False
```

Return boolean. Changed in version 2.0: renamed `seqtools.is_numeric()` to `seqtools.all_are_numbers()`.

seqtools.all_are_positive_integer_equivalent_numbers

`abjad.tools.seqtools.all_are_positive_integer_equivalent_numbers(expr)`

New in version 2.0. True when *expr* is a sequence and all elements in *expr* are positive integer-equivalent numbers. Otherwise false:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.all_are_positive_integer_equivalent_numbers([Fraction(4, 2), 2.0, 2])
True
```

Return boolean.

seqtools.all_are_positive_integers

`abjad.tools.seqtools.all_are_positive_integers(expr)`

New in version 2.0. True when *expr* is a sequence and all elements in *expr* are positive integers:


```
abjad> from abjad.tools import seqtools

abjad> seqtools.all_are_positive_integers([1, 2, 3, 99])
True
```

Otherwise false:

```
abjad> seqtools.all_are_positive_integers(17)
False
```

Return boolean.

seqtools.all_are_unequal

`abjad.tools.seqtools.all_are_unequal(expr)`

New in version 1.1. True when *expr* is a sequence all elements in *expr* are unequal:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.all_are_unequal([1, 2, 3, 4, 9])
True
```

True when *expr* is an empty sequence:

```
abjad> seqtools.all_are_unequal([ ])
True
```

False otherwise:

```
abjad> seqtools.all_are_unequal(17)
False
```

Return boolean. Changed in version 2.0: renamed `seqtools.is_unique()` to `seqtools.all_are_unequal()`.

seqtools.count_length_two_runs_in_sequence

`abjad.tools.seqtools.count_length_two_runs_in_sequence(sequence)`

New in version 1.1. Count length-2 runs in *sequence*:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.count_length_two_runs_in_sequence([0, 0, 1, 1, 1, 2, 3, 4, 5])
3
```

Return nonnegative integer. Changed in version 2.0: renamed `seqtools.count_repetitions()` to `seqtools.count_length_two_runs_in_sequence()`.

seqtools.divide_sequence_elements_by_greatest_common_divisor

`abjad.tools.seqtools.divide_sequence_elements_by_greatest_common_divisor(sequence)`

New in version 2.0. Divide *sequence* elements by greatest common divisor:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.divide_sequence_elements_by_greatest_common_divisor([2, 2, -8, -16])
[1, 1, -4, -8]
```

Allow negative *sequence* elements.

Raise type error on noninteger *sequence* elements.

Raise not implemented error when 0 in *sequence*.

Return new *sequence* object.

seqtools.flatten_sequence

abjad.tools.seqtools.**flatten_sequence**(*sequence*, *klasses=None*, *depth=-1*)

New in version 1.1. Flatten *sequence*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.flatten_sequence([1, [2, 3, [4]], 5, [6, 7, [8]]])
[1, 2, 3, 4, 5, 6, 7, 8]
```

Flatten *sequence* to depth 1:

```
abjad> seqtools.flatten_sequence([1, [2, 3, [4]], 5, [6, 7, [8]]], depth = 1)
[1, 2, 3, [4], 5, 6, 7, [8]]
```

Flatten *sequence* to depth 2:

```
abjad> seqtools.flatten_sequence([1, [2, 3, [4]], 5, [6, 7, [8]]], depth = 2)
[1, 2, 3, 4, 5, 6, 7, 8]
```

Leave *sequence* unchanged.

Return newly constructed *sequence* object. Changed in version 2.0: renamed `listtools.flatten()` to `seqtools.flatten_sequence()`.

seqtools.flatten_sequence_at_indices

abjad.tools.seqtools.**flatten_sequence_at_indices**(*sequence*, *indices*, *klasses=None*, *depth=-1*)

New in version 2.0. Flatten *sequence* at *indices*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.flatten_sequence_at_indices([0, 1, [2, 3, 4], [5, 6, 7]], [3])
[0, 1, [2, 3, 4], 5, 6, 7]
```

Flatten *sequence* at negative *indices*:

```
abjad> seqtools.flatten_sequence_at_indices([0, 1, [2, 3, 4], [5, 6, 7]], [-1])
[0, 1, [2, 3, 4], 5, 6, 7]
```

Leave *sequence* unchanged.

Return newly constructed *sequence* object.

seqtools.get_indices_of_sequence_elements_equal_to_true

abjad.tools.seqtools.**get_indices_of_sequence_elements_equal_to_true**(*sequence*)

New in version 1.1. Get indices of *sequence* elements equal to true:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.get_indices_of_sequence_elements_equal_to_true([0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1,
(3, 4, 5, 9, 10, 11, 12)
```

Return newly constructed tuple of zero or more nonnegative integers. Changed in version 2.0: renamed `listtools.true_indices()` to `seqtools.get_indices_of_sequence_elements_equal_to_true()`.

seqtools.get_sequence_degree_of_rotational_symmetry

abjad.tools.seqtools.**get_sequence_degree_of_rotational_symmetry**(*sequence*)

New in version 2.0. Change *sequence* to degree of rotational symmetry:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.get_sequence_degree_of_rotational_symmetry([1, 2, 3, 4, 5, 6])
1
```

```
abjad> seqtools.get_sequence_degree_of_rotational_symmetry([1, 2, 3, 1, 2, 3])
2
```

```
abjad> seqtools.get_sequence_degree_of_rotational_symmetry([1, 2, 1, 2, 1, 2])
3
```

```
abjad> seqtools.get_sequence_degree_of_rotational_symmetry([1, 1, 1, 1, 1, 1])
6
```

Return positive integer.

seqtools.get_sequence_element_at_cyclic_index

abjad.tools.seqtools.**get_sequence_element_at_cyclic_index**(*sequence*, *index*)

New in version 2.0. Get *sequence* element at nonnegative cyclic *index*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> for index in range(10):
...     print '%s\t%s' % (index, seqtools.get_sequence_element_at_cyclic_index('string', index))
...
0 s
1 t
2 r
3 i
4 n
5 g
6 s
7 t
8 r
9 i
```

Get *sequence* element at negative cyclic *index*:

```

abjad> for index in range(1, 11):
...     print '%s\t%s' % (-index, seqtools.get_sequence_element_at_cyclic_index('string', -index))
...
-1    g
-2    n
-3    i
-4    r
-5    t
-6    s
-7    g
-8    n
-9    i
-10   r

```

Return reference to *sequence* element.

seqtools.get_sequence_elements_at_indices

abjad.tools.seqtools.get_sequence_elements_at_indices(*sequence*, *indices*)

New in version 2.0. Get *sequence* elements at *indices*:

```

abjad> from abjad.tools import seqtools

abjad> seqtools.get_sequence_elements_at_indices('string of text', (2, 3, 10, 12))
('r', 'i', 't', 'x')

```

Return newly constructed tuple of references to *sequence* elements.

seqtools.get_sequence_elements_frequency_distribution

abjad.tools.seqtools.get_sequence_elements_frequency_distribution(*sequence*)

New in version 2.0. Get *sequence* elements frequency distribution:

```

abjad> from abjad.tools import seqtools

abjad> seqtools.get_sequence_elements_frequency_distribution([1, 3, 3, 3, 2, 1, 1, 2, 3, 3, 1, 2])
[(1, 4), (2, 3), (3, 5)]

```

Return list of element / count pairs.

seqtools.get_sequence_period_of_rotation

abjad.tools.seqtools.get_sequence_period_of_rotation(*sequence*, *n*)

New in version 2.0. Change *sequence* to period of rotation:

```

abjad> from abjad.tools import seqtools

abjad> seqtools.get_sequence_period_of_rotation([1, 2, 3, 1, 2, 3], 1)
3

abjad> seqtools.get_sequence_period_of_rotation([1, 2, 3, 1, 2, 3], 2)
3

abjad> seqtools.get_sequence_period_of_rotation([1, 2, 3, 1, 2, 3], 3)
1

```

Return positive integer.

seqtools.increase_sequence_elements_at_indices_by_addenda

```
abjad.tools.seqtools.increase_sequence_elements_at_indices_by_addenda(sequence,
                                                                    ad-
                                                                    denda,
                                                                    in-
                                                                    dices)
```

New in version 1.1. Increase *sequence* by *addenda* at *indices*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> sequence = [1, 1, 2, 3, 5, 5, 1, 2, 5, 5, 6]
```

```
abjad> seqtools.increase_sequence_elements_at_indices_by_addenda(sequence, [0.5, 0.5], [0, 4, 8]
[1.5, 1.5, 2, 3, 5.5, 5.5, 1, 2, 5.5, 5.5, 6])
```

Return list. Changed in version 2.0: renamed `seqtools.increase_at_indices()` to `seqtools.increase_sequence_elements_at_indices_by_addenda()`.

seqtools.increase_sequence_elements_cyclically_by_addenda

```
abjad.tools.seqtools.increase_sequence_elements_cyclically_by_addenda(sequence,
                                                                    ad-
                                                                    denda,
                                                                    shield=True,
                                                                    trim=True)
```

New in version 1.1.. Increase *sequence* cyclically by *addenda*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.increase_sequence_elements_cyclically_by_addenda(range(10), [10, -10], shield =
[10, -9, 12, -7, 14, -5, 16, -3, 18, -1])
```

Increase *sequence* cyclically by *addenda* and map nonpositive values to 1:

```
abjad> seqtools.increase_sequence_elements_cyclically_by_addenda(range(10), [10, -10], shield =
[10, 1, 12, 1, 14, 1, 16, 1, 18, 1])
```

Return list. Changed in version 2.0: renamed `seqtools.increase_cyclic()` to `seqtools.increase_sequence_elements_cyclically_by_addenda()`.

seqtools.interlace_sequences

```
abjad.tools.seqtools.interlace_sequences(*sequences)
```

New in version 1.1. Interlace *sequences*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> k = range(100, 103)
```

```
abjad> l = range(200, 201)
```

```
abjad> m = range(300, 303)
```

```
abjad> n = range(400, 408)
```

```
abjad> seqtools.interlace_sequences(k, l, m, n)
```

```
[100, 200, 300, 400, 101, 301, 401, 102, 302, 402, 403, 404, 405, 406, 407]
```

Return list. Changed in version 2.0: renamed `seqtools.interlace()` to `seqtools.interlace_sequences()`.

seqtools.is_monotonically_decreasing_sequence

`abjad.tools.seqtools.is_monotonically_decreasing_sequence(expr)`

New in version 2.0. True when *expr* is a sequence and the elements in *expr* decrease monotonically:

```
abjad> from abjad.tools import seqtools

abjad> expr = [9, 8, 7, 6, 5, 4, 3, 2, 1, 0]
abjad> seqtools.is_monotonically_decreasing_sequence(expr)
True

abjad> expr = [3, 3, 3, 3, 3, 3, 3, 2, 1, 0]
abjad> seqtools.is_monotonically_decreasing_sequence(expr)
True

abjad> expr = [3, 3, 3, 3, 3, 3, 3, 3, 3, 3]
abjad> seqtools.is_monotonically_decreasing_sequence(expr)
True
```

False when *expr* is a sequence and the elements in *expr* do not decrease monotonically:

```
abjad> expr = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
abjad> seqtools.is_monotonically_decreasing_sequence(expr)
False

abjad> expr = [0, 1, 2, 3, 3, 3, 3, 3, 3, 3]
abjad> seqtools.is_monotonically_decreasing_sequence(expr)
False
```

True when *expr* is a sequence and *expr* is empty:

```
abjad> expr = [ ]
abjad> seqtools.is_monotonically_decreasing_sequence(expr)
True
```

False when *expr* is not a sequence:

```
abjad> seqtools.is_monotonically_decreasing_sequence(17)
False
```

Return boolean.

seqtools.is_monotonically_increasing_sequence

`abjad.tools.seqtools.is_monotonically_increasing_sequence(expr)`

New in version 2.0. True when *expr* is a sequence and the elements in *expr* increase monotonically:

```
abjad> from abjad.tools import seqtools

abjad> expr = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
abjad> seqtools.is_monotonically_increasing_sequence(expr)
True

abjad> expr = [0, 1, 2, 3, 3, 3, 3, 3, 3, 3]
abjad> seqtools.is_monotonically_increasing_sequence(expr)
True
```

```
abjad> expr = [3, 3, 3, 3, 3, 3, 3, 3, 3, 3]
abjad> seqtools.is_monotonically_increasing_sequence(expr)
True
```

False when *expr* is a sequence and the elements in *expr* do not increase monotonically:

```
abjad> expr = [9, 8, 7, 6, 5, 4, 3, 2, 1, 0]
abjad> seqtools.is_monotonically_increasing_sequence(expr)
False
```

```
abjad> expr = [3, 3, 3, 3, 3, 3, 3, 2, 1, 0]
abjad> seqtools.is_monotonically_increasing_sequence(expr)
False
```

True when *expr* is a sequence and *expr* is empty:

```
abjad> expr = [ ]
abjad> seqtools.is_monotonically_increasing_sequence(expr)
True
```

False when *expr* is not a sequence:

```
abjad> seqtools.is_monotonically_increasing_sequence(17)
False
```

Return boolean.

seqtools.is_permutation

`abjad.tools.seqtools.is_permutation(expr, length=None)`

New in version 2.0. True when *expr* is a permutation:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.is_permutation([4, 5, 0, 3, 2, 1])
True
```

Otherwise false:

```
abjad> seqtools.is_permutation([1, 1, 5, 3, 2, 1])
False
```

True when *expr* is a permutation of first *length* nonnegative integers:

```
abjad> seqtools.is_permutation([4, 5, 0, 3, 2, 1], length = 6)
True
```

Otherwise false:

```
abjad> seqtools.is_permutation([4, 0, 3, 2, 1], length = 6)
False
```

Return boolean.

seqtools.is_repetition_free_sequence

`abjad.tools.seqtools.is_repetition_free_sequence(expr)`

New in version 2.0. True when *expr* is a sequence and *expr* is repetition free:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.is_repetition_free_sequence([0, 1, 2, 6, 7, 8])
True
```

False when *expr* is a sequence and *expr* is not repetition free:

```
abjad> seqtools.is_repetition_free_sequence([0, 1, 2, 2, 7, 8])
False
```

True when *expr* is an empty sequence:

```
abjad> seqtools.is_repetition_free_sequence([ ])
True
```

False *expr* is not a sequence:

```
abjad> seqtools.is_repetition_free_sequence(17)
False
```

Return boolean.

seqtools.is_restricted_growth_function

`abjad.tools.seqtools.is_restricted_growth_function(expr)`

New in version 2.0. True when *expr* is a sequence and *expr* meets the criteria for a restricted growth function:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.is_restricted_growth_function([1, 1, 1, 1])
True
```

```
abjad> seqtools.is_restricted_growth_function([1, 1, 1, 2])
True
```

```
abjad> seqtools.is_restricted_growth_function([1, 1, 2, 1])
True
```

```
abjad> seqtools.is_restricted_growth_function([1, 1, 2, 2])
True
```

Otherwise false:

```
abjad> seqtools.is_restricted_growth_function([1, 1, 1, 3])
False
```

```
abjad> seqtools.is_restricted_growth_function(17)
False
```

A restricted growth function is a sequence *l* such that *l*[0] == 1 and such that *l*[*i*] <= max(*l*[:*i*]) + 1 for 1 <= *i* <= len(*l*).

Return boolean.

seqtools.is_strictly_decreasing_sequence

`abjad.tools.seqtools.is_strictly_decreasing_sequence(expr)`

New in version 2.0. True when *expr* is a sequence and the elements in *expr* decrease strictly:


```

abjad> from abjad.tools import seqtools

abjad> expr = [9, 8, 7, 6, 5, 4, 3, 2, 1, 0]
abjad> seqtools.is_strictly_decreasing_sequence(expr)
True

```

False when *expr* is a sequence and the elements in *expr* do not decrease strictly:

```

abjad> expr = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
abjad> seqtools.is_strictly_decreasing_sequence(expr)
False

abjad> expr = [0, 1, 2, 3, 3, 3, 3, 3, 3, 3]
abjad> seqtools.is_strictly_decreasing_sequence(expr)
False

abjad> expr = [3, 3, 3, 3, 3, 3, 3, 3, 3, 3]
abjad> seqtools.is_strictly_decreasing_sequence(expr)
False

abjad> expr = [3, 3, 3, 3, 3, 3, 3, 2, 1, 0]
abjad> seqtools.is_strictly_decreasing_sequence(expr)
False

```

True when *expr* is an empty sequence:

```

abjad> seqtools.is_strictly_decreasing_sequence([ ])
True

```

False *expr* is not a sequence:

```

abjad> seqtools.is_strictly_decreasing_sequence(17)
False

```

Return boolean.

seqtools.is_strictly_increasing_sequence

`abjad.tools.seqtools.is_strictly_increasing_sequence(expr)`

New in version 2.0. True when *expr* is a sequence and the elements in *expr* increase strictly:

```

abjad> from abjad.tools import seqtools

abjad> expr = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
abjad> seqtools.is_strictly_increasing_sequence(expr)
True

```

False when *expr* is a sequence and the elements in *expr* do not increase strictly:

```

abjad> expr = [9, 8, 7, 6, 5, 4, 3, 2, 1, 0]
abjad> seqtools.is_strictly_increasing_sequence(expr)
False

abjad> expr = [3, 3, 3, 3, 3, 3, 3, 2, 1, 0]
abjad> seqtools.is_strictly_increasing_sequence(expr)
False

abjad> expr = [3, 3, 3, 3, 3, 3, 3, 3, 3, 3]
abjad> seqtools.is_strictly_increasing_sequence(expr)
False

```

```
abjad> expr = [0, 1, 2, 3, 3, 3, 3, 3, 3, 3]
abjad> seqtools.is_strictly_increasing_sequence(expr)
False
```

True when *expr* is an empty sequence:

```
abjad> seqtools.is_strictly_increasing_sequence([ ])
True
```

False when *expr* is not a sequence:

```
abjad> seqtools.is_strictly_increasing_sequence(17)
False
```

Return boolean.

seqtools.iterate_sequence_cyclically

```
abjad.tools.seqtools.iterate_sequence_cyclically(sequence,      step=1,      start=0,
                                                    length='inf')
```

New in version 1.1. Iterate *sequence* cyclically according to *step*, *start* and *length*:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [1, 2, 3, 4, 5, 6, 7]

abjad> list(seqtools.iterate_sequence_cyclically(sequence, length = 20))
[1, 2, 3, 4, 5, 6, 7, 1, 2, 3, 4, 5, 6, 7, 1, 2, 3, 4, 5, 6]

abjad> list(seqtools.iterate_sequence_cyclically(sequence, 2, length = 20))
[1, 3, 5, 7, 2, 4, 6, 1, 3, 5, 7, 2, 4, 6, 1, 3, 5, 7, 2, 4]

abjad> list(seqtools.iterate_sequence_cyclically(sequence, 2, 3, length = 20))
[4, 6, 1, 3, 5, 7, 2, 4, 6, 1, 3, 5, 7, 2, 4, 6, 1, 3, 5, 7]

abjad> list(seqtools.iterate_sequence_cyclically(sequence, -2, 5, length = 20))
[6, 4, 2, 7, 5, 3, 1, 6, 4, 2, 7, 5, 3, 1, 6, 4, 2, 7, 5, 3]
```

Changed in version 2.0: allows generator input.

```
abjad> list(seqtools.iterate_sequence_cyclically(xrange(1, 8), -2, 5, length = 20))
[6, 4, 2, 7, 5, 3, 1, 6, 4, 2, 7, 5, 3, 1, 6, 4, 2, 7, 5, 3]
```

Set *step* to jump size and direction across sequence.

Set *start* to the index of *sequence* where the function begins iterating.

Set *length* to number of elements to return. Set to 'inf' to return infinitely.

Return generator. Changed in version 2.0: renamed `seqtools.phasor()` to `seqtools.iterate_sequence_cyclically()`.

seqtools.iterate_sequence_cyclically_from_start_to_stop

```
abjad.tools.seqtools.iterate_sequence_cyclically_from_start_to_stop(sequence,
                                                                        start,
                                                                        stop)
```

New in version 1.1. Iterate *sequence* cyclically from *start* to *stop*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> list(seqtools.iterate_sequence_cyclically_from_start_to_stop(range(20), 18, 10))
[18, 19, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
```

Return generator of references to *sequence* elements. Changed in version 2.0: renamed `seqtools.get_cyclic()` to `seqtools.iterate_sequence_cyclically_from_start_to_stop()`.

seqtools.iterate_sequence_forward_and_backward_nonoverlapping

`abjad.tools.seqtools.iterate_sequence_forward_and_backward_nonoverlapping(sequence)`
New in version 2.0. Iterate *sequence* first forward and then backward, with first and last elements repeated:

```
abjad> from abjad.tools import seqtools
```

```
abjad> list(seqtools.iterate_sequence_forward_and_backward_nonoverlapping([1, 2, 3, 4, 5]))
[1, 2, 3, 4, 5, 5, 4, 3, 2, 1]
```

Return generator.

seqtools.iterate_sequence_forward_and_backward_overlapping

`abjad.tools.seqtools.iterate_sequence_forward_and_backward_overlapping(sequence)`
New in version 2.0. Iterate *sequence* first forward and then backward, with first and last elements appearing only once:

```
abjad> from abjad.tools import seqtools
```

```
abjad> list(seqtools.iterate_sequence_forward_and_backward_overlapping([1, 2, 3, 4, 5]))
[1, 2, 3, 4, 5, 4, 3, 2]
```

Return generator.

seqtools.iterate_sequence_nwise_cyclic

`abjad.tools.seqtools.iterate_sequence_nwise_cyclic(sequence, n)`
New in version 2.0. Iterate elements in *sequence* cyclically *n* at a time:

```
abjad> from abjad.tools import seqtools
```

```
abjad> g = seqtools.iterate_sequence_nwise_cyclic(range(6), 3)
abjad> for n in range(10):
...     print g.next()
(0, 1, 2)
(1, 2, 3)
(2, 3, 4)
(3, 4, 5)
(4, 5, 0)
(5, 0, 1)
(0, 1, 2)
(1, 2, 3)
(2, 3, 4)
(3, 4, 5)
```

Return generator.

seqtools.iterate_sequence_nwise_strict

`abjad.tools.seqtools.iterate_sequence_nwise_strict(sequence, n)`

New in version 2.0. Iterate elements in *sequence* *n* at a time:

```
abjad> from abjad.tools import seqtools
```

```
abjad> list(seqtools.iterate_sequence_nwise_strict(range(10), 4))
[(0, 1, 2, 3), (1, 2, 3, 4), (2, 3, 4, 5), (3, 4, 5, 6), (4, 5, 6, 7), (5, 6, 7, 8), (6, 7, 8, 9)]
```

Return generator.

seqtools.iterate_sequence_nwise_wrapped

`abjad.tools.seqtools.iterate_sequence_nwise_wrapped(sequence, n)`

New in version 2.0. Iterate elements in *sequence* *n* at a time wrapped to beginning:

```
abjad> from abjad.tools import seqtools
```

```
abjad> list(seqtools.iterate_sequence_nwise_wrapped(range(6), 3))
[(0, 1, 2), (1, 2, 3), (2, 3, 4), (3, 4, 5), (4, 5, 0), (5, 0, 1)]
```

Return generator.

seqtools.iterate_sequence_pairwise_cyclic

`abjad.tools.seqtools.iterate_sequence_pairwise_cyclic(sequence)`

New in version 1.1. Iterate *sequence* pairwise cyclic:

```
abjad> from abjad.tools import seqtools
```

```
abjad> generator = seqtools.iterate_sequence_pairwise_cyclic(range(6))
```

```
abjad> generator.next()
(0, 1)
abjad> generator.next()
(1, 2)
abjad> generator.next()
(2, 3)
abjad> generator.next()
(3, 4)
abjad> generator.next()
(4, 5)
abjad> generator.next()
(5, 0)
abjad> generator.next()
(0, 1)
abjad> generator.next()
(1, 2)
```

Return pair generator.

seqtools.iterate_sequence_pairwise_strict

`abjad.tools.seqtools.iterate_sequence_pairwise_strict(sequence)`

New in version 1.1. Iterate *sequence* pairwise strict:

```
abjad> from abjad.tools import seqtools

abjad> list(seqtools.iterate_sequence_pairwise_strict(range(6)))
[(0, 1), (1, 2), (2, 3), (3, 4), (4, 5)]
```

Return pair generator.

seqtools.iterate_sequence_pairwise_wrapped

`abjad.tools.seqtools.iterate_sequence_pairwise_wrapped(sequence)`
 New in version 1.1. Iterate *sequence* pairwise wrapped:

```
abjad> from abjad.tools import seqtools

abjad> list(seqtools.iterate_sequence_pairwise_wrapped(range(6)))
[(0, 1), (1, 2), (2, 3), (3, 4), (4, 5), (5, 0)]
```

Return pair generator.

seqtools.join_subsequences_by_sign_of_subsequence_elements

`abjad.tools.seqtools.join_subsequences_by_sign_of_subsequence_elements(sequence)`
 New in version 1.1. Join subsequences in *sequence* by sign:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [[1, 2], [3, 4], [-5, -6, -7], [-8, -9, -10], [11, 12]]
abjad> seqtools.join_subsequences_by_sign_of_subsequence_elements(sequence)
[[1, 2, 3, 4], [-5, -6, -7, -8, -9, -10], [11, 12]]

abjad> sequence = [[1, 2], [], [], [3, 4, 5], [6, 7]]
abjad> seqtools.join_subsequences_by_sign_of_subsequence_elements(sequence)
[[1, 2], [], [3, 4, 5, 6, 7]]
```

Return newly constructed list. Changed in version 2.0: renamed `seqtools.join_sublists_by_sign()` to `seqtools.join_subsequences_by_sign_of_subsequence_elements()`

seqtools.map_sequence_elements_to_canonic_tuples

`abjad.tools.seqtools.map_sequence_elements_to_canonic_tuples(sequence, direction='big-endian')`
 New in version 1.1. Partition *sequence* elements into canonic big-endian parts:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.map_sequence_elements_to_canonic_tuples(range(10))
[(0,), (1,), (2,), (3,), (4,), (4, 1), (6,), (7,), (8,), (8, 1)]
```

Partition *sequence* elements into canonic little-endian parts:

```
abjad> seqtools.map_sequence_elements_to_canonic_tuples(range(10), direction='little-endian')
[(0,), (1,), (2,), (3,), (4,), (1, 4), (6,), (7,), (8,), (1, 8)]
```

Raise type error when *sequence* is not a list.

Raise value error on noninteger elements in *sequence*.

Return list of tuples. Changed in version 2.0: renamed `seqtools.partition_elements_into_canonic_parts()` to `seqtools.map_sequence_elements_to_canonic_tuples()`.

seqtools.map_sequence_elements_to_numbered_sublists

`abjad.tools.seqtools.map_sequence_elements_to_numbered_sublists(sequence)`

New in version 1.1. Map *sequence* elements to numbered sublists:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.map_sequence_elements_to_numbered_sublists([1, 2, -3, -4, 5])
[[1], [2, 3], [-4, -5, -6], [-7, -8, -9, -10], [11, 12, 13, 14, 15]]

abjad> seqtools.map_sequence_elements_to_numbered_sublists([1, 0, -3, -4, 5])
[[1], [], [-2, -3, -4], [-5, -6, -7, -8], [9, 10, 11, 12, 13]]
```

Note that numbering starts at 1.

Return newly constructed list of lists. Changed in version 2.0: renamed `seqtools.lengths_to_counts()` to `seqtools.map_sequence_elements_to_numbered_sublists()`.

seqtools.negate_absolute_value_of_sequence_elements_at_indices

`abjad.tools.seqtools.negate_absolute_value_of_sequence_elements_at_indices(sequence, indices)`

New in version 1.1. Negate the absolute value of *sequence* elements at *indices*:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [1, 2, 3, 4, 5, -6, -7, -8, -9, -10]

abjad> seqtools.negate_sequence_elements_at_indices(sequence, [0, 1, 2])
[-1, -2, -3, 4, 5, -6, -7, -8, -9, -10]
```

Return newly constructed list. Changed in version 2.0: renamed `seqtools.negate_elements_at_indices_absolutely()` to `seqtools.negate_absolute_value_of_sequence_elements_at_indices()`.

seqtools.negate_absolute_value_of_sequence_elements_cyclically

`abjad.tools.seqtools.negate_absolute_value_of_sequence_elements_cyclically(sequence, indices, period)`

New in version 2.0. Negate the absolute value of *sequence* elements at *indices* cyclically according to *period*:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [1, 2, 3, 4, 5, -6, -7, -8, -9, -10]
```

```
abjad> seqtools.negate_absolute_value_of_sequence_elements_cyclically(sequence, [0, 1, 2], 5)
[-1, -2, -3, 4, 5, -6, -7, -8, -9, -10]
```

Return newly constructed list.

seqtools.negate_sequence_elements_at_indices

`abjad.tools.seqtools.negate_sequence_elements_at_indices(sequence, indices)`

New in version 1.1. Negate *sequence* elements at *indices*:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [1, 2, 3, 4, 5, -6, -7, -8, -9, -10]

abjad> seqtools.negate_sequence_elements_at_indices(sequence, [0, 1, 2])
[-1, -2, -3, 4, 5, -6, -7, -8, -9, -10]
```

Return newly constructed list. Changed in version 2.0: renamed `seqtools.negate_elements_at_indices()` to `seqtools.negate_sequence_elements_at_indices()`.

seqtools.negate_sequence_elements_cyclically

`abjad.tools.seqtools.negate_sequence_elements_cyclically(sequence, indices, period)`

New in version 2.0. Negate *sequence* elements at *indices* cyclically according to *period*:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [1, 2, 3, 4, 5, -6, -7, -8, -9, -10]

abjad> seqtools.negate_sequence_elements_cyclically(sequence, [0, 1, 2], 5)
[-1, -2, -3, 4, 5, 6, 7, 8, -9, -10]
```

Return newly constructed list.

seqtools.overwrite_sequence_elements_at_indices

`abjad.tools.seqtools.overwrite_sequence_elements_at_indices(sequence, pairs)`

New in version 1.1. Overwrite *sequence* elements at indices according to *pairs*:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.overwrite_sequence_elements_at_indices(range(10), [(0, 3), (5, 3)])
[0, 0, 0, 3, 4, 5, 5, 5, 8, 9]
```

Set *pairs* to a list of (anchor_index, length) pairs.

Return new list. Changed in version 2.0: renamed `seqtools.overwrite_slices_at()` to `seqtools.overwrite_sequence_elements_at_indices()`.

seqtools.partition_sequence_by_ratio_of_lengths

`abjad.tools.seqtools.partition_sequence_by_ratio_of_lengths(sequence, lengths)`

New in version 2.0. Partition *sequence* by ratio of *lengths*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.partition_sequence_by_ratio_of_lengths(tuple(range(10)), [1, 1, 2])
[(0, 1, 2), (3, 4), (5, 6, 7, 8, 9)]
```

Use rounding magic to avoid fractional part lengths.

Return list of *sequence* objects.

seqtools.partition_sequence_by_ratio_of_weights

`abjad.tools.seqtools.partition_sequence_by_ratio_of_weights(sequence, weights)`

New in version 2.0. Partition *sequence* by ratio of *weights*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.partition_sequence_by_ratio_of_weights([1] * 10, [1, 1, 1])
[[1, 1, 1], [1, 1, 1, 1], [1, 1, 1]]
```

```
abjad> seqtools.partition_sequence_by_ratio_of_weights([1] * 10, [1, 1, 1, 1])
[[1, 1, 1], [1, 1], [1, 1, 1], [1, 1]]
```

```
abjad> seqtools.partition_sequence_by_ratio_of_weights([1] * 10, [2, 2, 3])
[[1, 1, 1], [1, 1, 1], [1, 1, 1, 1]]
```

```
abjad> seqtools.partition_sequence_by_ratio_of_weights([1] * 10, [3, 2, 2])
[[1, 1, 1, 1], [1, 1, 1], [1, 1, 1]]
```

```
abjad> seqtools.partition_sequence_by_ratio_of_weights([1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2], [1, 1, 1, 1, 1, 1, 2, 2])
[[1, 1, 1, 1, 1, 1, 2, 2], [2, 2, 2, 2]]
```

```
abjad> seqtools.partition_sequence_by_ratio_of_weights([1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2], [1, 1, 1, 1, 1, 1, 2, 2, 2])
[[1, 1, 1, 1, 1, 1], [2, 2, 2], [2, 2, 2]]
```

Weights of parts of returned list equal *weights_ratio* proportions with some rounding magic.

Return list of lists.

seqtools.partition_sequence_by_restricted_growth_function

`abjad.tools.seqtools.partition_sequence_by_restricted_growth_function(sequence, restricted_growth_function)`

New in version 2.0. Partition *sequence* by *restricted_growth_function*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> l = range(10)
abjad> rgf = [1, 1, 2, 2, 1, 2, 3, 3, 2, 4]
abjad> seqtools.partition_sequence_by_restricted_growth_function(l, rgf)
[[0, 1, 4], [2, 3, 5, 8], [6, 7], [9]]
```

Raise value error when *sequence* length does not equal *restricted_growth_function* length.

Return list of lists.

seqtools.partition_sequence_by_sign_of_elements

abjad.tools.seqtools.**partition_sequence_by_sign_of_elements**(*sequence*, *sign*=[-1, 0, 1])

New in version 1.1. Partition *sequence* elements by sign:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [0, 0, -1, -1, 2, 3, -5, 1, 2, 5, -5, -6]

abjad> list(seqtools.partition_sequence_by_sign_of_elements(sequence))
[[0, 0], [-1, -1], [2, 3], [-5], [1, 2, 5], [-5, -6]]

abjad> list(seqtools.partition_sequence_by_sign_of_elements(sequence, sign = [-1]))
[0, 0, [-1, -1], 2, 3, [-5], 1, 2, 5, [-5, -6]]

abjad> list(seqtools.partition_sequence_by_sign_of_elements(sequence, sign = [0]))
[[0, 0], -1, -1, 2, 3, -5, 1, 2, 5, -5, -6]

abjad> list(seqtools.partition_sequence_by_sign_of_elements(sequence, sign = [1]))
[0, 0, -1, -1, [2, 3], -5, [1, 2, 5], -5, -6]

abjad> list(seqtools.partition_sequence_by_sign_of_elements(sequence, sign = [-1, 0]))
[[0, 0], [-1, -1], 2, 3, [-5], 1, 2, 5, [-5, -6]]

abjad> list(seqtools.partition_sequence_by_sign_of_elements(sequence, sign = [-1, 1]))
[0, 0, [-1, -1], [2, 3], [-5], [1, 2, 5], [-5, -6]]

abjad> list(seqtools.partition_sequence_by_sign_of_elements(sequence, sign = [0, 1]))
[[0, 0], -1, -1, [2, 3], -5, [1, 2, 5], -5, -6]

abjad> list(seqtools.partition_sequence_by_sign_of_elements(sequence, sign = [-1, 0, 1]))
[[0, 0], [-1, -1], [2, 3], [-5], [1, 2, 5], [-5, -6]]
```

When -1 in sign, group negative elements.

When 0 in sign, group 0 elements.

When 1 in sign, group positive elements.

Return list of tuples of *sequence* element references. Changed in version 2.0: renamed `listtools.group_by_sign()` to `seqtools.partition_sequence_by_sign_of_elements()`.

seqtools.partition_sequence_by_value_of_elements

abjad.tools.seqtools.**partition_sequence_by_value_of_elements**(*sequence*)

New in version 1.1. Group *sequence* elements by equality:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.partition_sequence_by_value_of_elements([0, 0, -1, -1, 2, 3, -5, 1, 1, 5, -5])
[(0, 0), (-1, -1), (2,), (3,), (-5,), (1, 1), (5,), (-5,)]
```

Return list of tuples of *sequence* element references. Changed in version 2.0: renamed `seqtools.group_by_equality()` to `seqtools.partition_sequence_by_value_of_elements()`.

seqtools.partition_sequence_cyclically_by_counts_with_overhang

abjad.tools.seqtools.**partition_sequence_cyclically_by_counts_with_overhang**(*sequence*,
counts)

New in version 1.1. Partition *sequence* cyclically by *counts* with overhang:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.partition_sequence_cyclically_by_counts_with_overhang(range(16), [4, 6])
[[0, 1, 2, 3], [4, 5, 6, 7, 8, 9], [10, 11, 12, 13], [14, 15]]
```

Return list of *sequence* objects. Changed in version 2.0: renamed
listtools.partition_sequence_cyclically_by_counts_with_overhang() to
seqtools.partition_sequence_cyclically_by_counts_with_overhang().

seqtools.partition_sequence_cyclically_by_counts_without_overhang

abjad.tools.seqtools.**partition_sequence_cyclically_by_counts_without_overhang**(*sequence*,
counts)

New in version 1.1. Partition *sequence* cyclically by *counts* without overhang:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.partition_sequence_cyclically_by_counts_without_overhang(range(16), [4, 6])
[[0, 1, 2, 3], [4, 5, 6, 7, 8, 9], [10, 11, 12, 13]]
```

Return list of *sequence* objects Changed in version 2.0: renamed
listtools.partition_sequence_cyclically_by_counts_without_overhang() to
seqtools.partition_sequence_cyclically_by_counts_without_overhang().

seqtools.partition_sequence_cyclically_by_weights_at_least_with_overhang

abjad.tools.seqtools.**partition_sequence_cyclically_by_weights_at_least_with_overhang**(*sequence*,
weights)

New in version 1.1. Partition *sequence* elements cyclically by *weights* at least with overhang:

```
abjad> from abjad.tools import seqtools
```

```
abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5, 5]
abjad> seqtools.partition_sequence_cyclically_by_weights_at_least_with_overhang(sequence, [10, 4])
[[3, 3, 3, 3], [4], [4, 4, 4], [5], [5]]
```

Return list *sequence* element reference lists. Changed in version 2.0: renamed
seqtools.group_sequence_elements_cyclically_by_weights_at_least_with_overhang()
to seqtools.partition_sequence_cyclically_by_weights_at_least_with_overhang().

seqtools.partition_sequence_cyclically_by_weights_at_least_without_overhang

abjad.tools.seqtools.**partition_sequence_cyclically_by_weights_at_least_without_overhang**(*sequence*,
weights)

New in version 1.1. Partition *sequence* elements cyclically by *weights* at least without overhang:

```
abjad> from abjad.tools import seqtools
```

```
abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5, 5]
abjad> seqtools.partition_sequence_cyclically_by_weights_at_least_without_overhang(sequence, [10, 5])
[[3, 3, 3, 3], [4], [4, 4, 4], [5]]
```

Return list sequence element reference lists. Changed in version 2.0: renamed `seqtools.group_sequence_elements_cyclically_by_weights_at_least_without_overhang()` to `seqtools.partition_sequence_cyclically_by_weights_at_least_without_overhang()`.

seqtools.partition_sequence_cyclically_by_weights_at_most_with_overhang

`abjad.tools.seqtools.partition_sequence_cyclically_by_weights_at_most_with_overhang(sequence, weights)`

New in version 1.1. Partition *sequence* elements cyclically by *weights* at most with overhang:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5, 5]
abjad> seqtools.partition_sequence_cyclically_by_weights_at_most_with_overhang(sequence, [10, 5])
[[3, 3, 3], [3], [4, 4], [4], [4, 5], [5]]
```

Return list sequence element reference lists. Changed in version 2.0: renamed `seqtools.group_sequence_elements_cyclically_by_weights_at_most_with_overhang()` to `seqtools.partition_sequence_cyclically_by_weights_at_most_with_overhang()`.

seqtools.partition_sequence_cyclically_by_weights_at_most_without_overhang

`abjad.tools.seqtools.partition_sequence_cyclically_by_weights_at_most_without_overhang(sequence, weights)`

New in version 1.1. Partition *sequence* elements cyclically by *weights* at most without overhang:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5]
abjad> seqtools.partition_sequence_cyclically_by_weights_at_most_without_overhang(sequence, [10, 5])
[[3, 3, 3], [3], [4, 4], [4]]
```

Return list sequence element reference lists. Changed in version 2.0: renamed `seqtools.group_sequence_elements_cyclically_by_weights_at_most_without_overhang()` to `seqtools.partition_sequence_cyclically_by_weights_at_most_without_overhang()`.

seqtools.partition_sequence_cyclically_by_weights_exactly_with_overhang

`abjad.tools.seqtools.partition_sequence_cyclically_by_weights_exactly_with_overhang(sequence, weights)`

New in version 1.1. Partition *sequence* elements cyclically by *weights* exactly with overhang:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5]
abjad> seqtools.partition_sequence_cyclically_by_weights_exactly_with_overhang(sequence, [12])
[[3, 3, 3, 3], [4, 4, 4], [4, 5]]
```

Return list of sequence element reference lists. Changed in version 2.0: renamed `seqtools.group_sequence_elements_cyclically_by_weights_exactly_with_overhang()` to `seqtools.partition_sequence_cyclically_by_weights_exactly_with_overhang()`.

seqtools.partition_sequence_cyclically_by_weights_exactly_without_overhang

abjad.tools.seqtools.**partition_sequence_cyclically_by_weights_exactly_without_overhang**(*sequence*, *weights*)

New in version 1.1. Partition *sequence* elements cyclically by *weights* exactly without overhang:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5]
abjad> seqtools.partition_sequence_cyclically_by_weights_exactly_without_overhang(sequence, [12])
[[3, 3, 3, 3], [4, 4, 4]]
```

Return list of sequence element reference lists. Changed in version 2.0: renamed `seqtools.group_sequence_elements_cyclically_by_weights_exactly_without_overhang()` to `seqtools.partition_sequence_cyclically_by_weights_exactly_without_overhang()`.

seqtools.partition_sequence_extended_to_counts_with_overhang

abjad.tools.seqtools.**partition_sequence_extended_to_counts_with_overhang**(*sequence*, *counts*)

New in version 2.0. Partition *sequence* extended to *counts* with overhang:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.partition_sequence_extended_to_counts_with_overhang([1, 2, 3, 4], [6, 6, 6])
[[1, 2, 3, 4, 1, 2], [3, 4, 1, 2, 3, 4], [1, 2, 3, 4, 1, 2], [3, 4]]
```

Return new object of *sequence* type.

seqtools.partition_sequence_extended_to_counts_without_overhang

abjad.tools.seqtools.**partition_sequence_extended_to_counts_without_overhang**(*sequence*, *counts*)

New in version 2.0. Partition *sequence* extended to *counts* without overhang:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.partition_sequence_extended_to_counts_without_overhang([1, 2, 3, 4], [6, 6, 6])
[[1, 2, 3, 4, 1, 2], [3, 4, 1, 2, 3, 4], [1, 2, 3, 4, 1, 2]]
```

Return new object of *sequence* type.

seqtools.partition_sequence_once_by_counts_with_overhang

abjad.tools.seqtools.**partition_sequence_once_by_counts_with_overhang**(*sequence*, *counts*)

New in version 1.1. Partition *sequence* once by *counts* with overhang:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.partition_sequence_once_by_counts_with_overhang(range(16), [4, 6])
[[0, 1, 2, 3], [4, 5, 6, 7, 8, 9], [10, 11, 12, 13, 14, 15]]
```

Return list of *sequence* objects. Changed in version 2.0: renamed `listtools.partition_sequence_once_by_counts_with_overhang()` to `seqtools.partition_sequence_once_by_counts_with_overhang()`.

seqtools.partition_sequence_once_by_counts_without_overhang

abjad.tools.seqtools.**partition_sequence_once_by_counts_without_overhang**(*sequence*,
counts)

New in version 1.1. Partition *sequence* once by *counts* without overhang:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.partition_sequence_once_by_counts_without_overhang(range(16), [4, 6])
[[0, 1, 2, 3], [4, 5, 6, 7, 8, 9]]
```

Return list of *sequence* objects. Changed in version 2.0: renamed
listtools.partition_sequence_once_by_counts_without_overhang() to
seqtools.partition_sequence_once_by_counts_without_overhang().

seqtools.partition_sequence_once_by_weights_at_least_with_overhang

abjad.tools.seqtools.**partition_sequence_once_by_weights_at_least_with_overhang**(*sequence*,
weights)

New in version 1.1. Partition *sequence* elements once by *weights* at least with overhang:

```
abjad> from abjad.tools import seqtools
```

```
abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5, 5]
abjad> seqtools.partition_sequence_once_by_weights_at_least_with_overhang(sequence, [10, 4])
[[3, 3, 3, 3], [4], [4, 4, 4, 4, 5, 5]]
```

Return list sequence element reference lists. Changed in version 2.0: renamed
seqtools.group_sequence_elements_once_by_weights_at_least_with_overhang()
to seqtools.partition_sequence_once_by_weights_at_least_with_overhang().

seqtools.partition_sequence_once_by_weights_at_least_without_overhang

abjad.tools.seqtools.**partition_sequence_once_by_weights_at_least_without_overhang**(*sequence*,
weights)

New in version 1.1. Partition *sequence* elements once by *weights* at least without overhang:

```
abjad> from abjad.tools import seqtools
```

```
abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5, 5]
abjad> seqtools.partition_sequence_once_by_weights_at_least_without_overhang(sequence, [10, 4])
[[3, 3, 3, 3], [4]]
```

Return list sequence element reference lists. Changed in version 2.0: renamed
seqtools.group_sequence_elements_once_by_weights_at_least_without_overhang()
to seqtools.partition_sequence_once_by_weights_at_least_without_overhang().

seqtools.partition_sequence_once_by_weights_at_most_with_overhang

abjad.tools.seqtools.**partition_sequence_once_by_weights_at_most_with_overhang**(*sequence*,
weights)

New in version 1.1. Partition *sequence* elements once by *weights* at most with overhang:

```
abjad> from abjad.tools import seqtools
```

```
abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5, 5]
abjad> seqtools.partition_sequence_once_by_weights_at_most_with_overhang(sequence, [10, 4])
[[3, 3, 3], [3], [4, 4, 4, 4, 5, 5]]
```

Return list sequence element reference lists. Changed in version 2.0: renamed `seqtools.group_sequence_elements_once_by_weights_at_most_with_overhang()` to `seqtools.partition_sequence_once_by_weights_at_most_with_overhang()`.

seqtools.partition_sequence_once_by_weights_at_most_without_overhang

`abjad.tools.seqtools.partition_sequence_once_by_weights_at_most_without_overhang(sequence, weights)`

New in version 1.1. Partition *sequence* elements once by *weights* at most without overhang:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5, 5]
abjad> seqtools.partition_sequence_once_by_weights_at_most_without_overhang(sequence, [10, 4])
[[3, 3, 3], [3]]
```

Return list sequence element reference lists. Changed in version 2.0: renamed `seqtools.group_sequence_elements_once_by_weights_at_most_without_overhang()` to `seqtools.partition_sequence_once_by_weights_at_most_without_overhang()`.

seqtools.partition_sequence_once_by_weights_exactly_with_overhang

`abjad.tools.seqtools.partition_sequence_once_by_weights_exactly_with_overhang(sequence, weights)`

New in version 1.1. Partition *sequence* elements once by *weights* exactly with overhang:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5, 5]
abjad> seqtools.partition_sequence_once_by_weights_exactly_with_overhang(sequence, [3, 9])
[[3], [3, 3, 3], [4, 4, 4, 4, 5, 5]]
```

Return list sequence element reference lists. Changed in version 2.0: renamed `seqtools.group_sequence_elements_once_by_weights_exactly_with_overhang()` to `seqtools.partition_sequence_once_by_weights_exactly_with_overhang()`.

seqtools.partition_sequence_once_by_weights_exactly_without_overhang

`abjad.tools.seqtools.partition_sequence_once_by_weights_exactly_without_overhang(sequence, weights)`

New in version 1.1. Partition *sequence* elements once by *weights* exactly without overhang:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [3, 3, 3, 3, 4, 4, 4, 4, 5, 5]
abjad> seqtools.partition_sequence_once_by_weights_exactly_without_overhang(sequence, [3, 9])
[[3], [3, 3, 3]]
```

Return list sequence element reference lists. Changed in version 2.0: renamed `seqtools.group_sequence_elements_once_by_weights_exactly_without_overhang()` to `seqtools.partition_sequence_once_by_weights_exactly_without_overhang()`.

seqtools.permute_sequence

abjad.tools.seqtools.**permute_sequence**(*sequence*, *permutation*)

New in version 2.0. Permute *sequence* by *permutation*:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.permute_sequence([10, 11, 12, 13, 14, 15], [5, 4, 0, 1, 2, 3])
[15, 14, 10, 11, 12, 13]
```

Return newly constructed *sequence* object.

seqtools.remove_sequence_elements_at_indices

abjad.tools.seqtools.**remove_sequence_elements_at_indices**(*sequence*, *indices*)

New in version 2.0. Remove *sequence* elements at *indices*:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.remove_sequence_elements_at_indices(range(20), [1, 16, 17, 18])
[0, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 19]
```

Ignore negative indices.

Return list.

seqtools.remove_sequence_elements_at_indices_cyclically

abjad.tools.seqtools.**remove_sequence_elements_at_indices_cyclically**(*sequence*,
indices,
period,
off-
set=0)

New in version 2.0. Remove *sequence* elements at *indices* mod *period* plus *offset*:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.remove_sequence_elements_at_indices_cyclically(range(20), [0, 1], 5, 3)
[0, 1, 2, 5, 6, 7, 10, 11, 12, 15, 16, 17]
```

Ignore negative indices.

Return list.

seqtools.remove_subsequence_of_weight_at_index

abjad.tools.seqtools.**remove_subsequence_of_weight_at_index**(*sequence*, *weight*, *in-*
dex)

New in version 1.1. Remove subsequence of *weight* at *index*:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.remove_subsequence_of_weight_at_index((1, 1, 2, 3, 5, 5, 1, 2, 5, 5, 6), 13, 4)
(1, 1, 2, 3, 5, 5, 6)
```

Return newly constructed *sequence* object. Changed in version 2.0: renamed
listtools.remove_weighted_subrun_at() to seqtools.remove_subsequence_of_weight_at_index()

seqtools.repeat_runs_in_sequence_to_count

`abjad.tools.seqtools.repeat_runs_in_sequence_to_count(sequence, indicators)`

New in version 1.1. Repeat subruns in *sequence* according to *indicators*. The *indicators* input parameter must be a list of zero or more (start, length, count) triples. For every (start, length, count) indicator in *indicators*, the function copies `sequence[start:start+length]` and inserts *count* new copies of `sequence[start:start+length]` immediately after `sequence[start:start+length]` in *sequence*.

Note: The function reads the value of *count* in every (start, length, count) triple not as the total number of occurrences of `sequence[start:start+length]` to appear in *sequence* after execution, but rather as the number of new occurrences of `sequence[start:start+length]` to appear in *sequence* after execution.

Note: The function wraps newly created subruns in tuples. That is, this function returns output with one more level of nesting than given in input.

To insert 10 count of `sequence[:2]` at `sequence[2:2]`:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.repeat_runs_in_sequence_to_count(range(20), [(0, 2, 10)])
[0, 1, (0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1),
 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19]
```

To insert 5 count of `sequence[10:12]` at `sequence[12:12]` and then insert 5 count of `sequence[:2]` at `sequence[2:2]`:

```
abjad> sequence = range(20)
```

```
abjad> seqtools.repeat_runs_in_sequence_to_count(sequence, [(0, 2, 5), (10, 2, 5)])
[0, 1, (0, 1, 0, 1, 0, 1, 0, 1, 0, 1), 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, (10, 11, 10, 11, 10, 11,
```

Note: This function wraps around the end of *sequence* whenever `len(sequence) < start + length`.

To insert 2 count of `[18, 19, 0, 1]` at `sequence[2:2]`:

```
abjad> seqtools.repeat_runs_in_sequence_to_count(sequence, [(18, 4, 2)])
[0, 1, (18, 19, 0, 1, 18, 19, 0, 1), 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18,
```

To insert 2 count of `[18, 19, 0, 1, 2, 3, 4]` at `sequence[4:4]`:

```
abjad> seqtools.repeat_runs_in_sequence_to_count(sequence, [(18, 8, 2)])
[0, 1, 2, 3, 4, 5, (18, 19, 0, 1, 2, 3, 4, 5, 18, 19, 0, 1, 2, 3, 4, 5), 6, 7, 8, 9, 10, 11, 12,
```

Todo

Implement an optional *wrap* keyword to specify whether this function should wrap around the end of *sequence* whenever `len(sequence) < start + length` or not.

Todo

Reimplement this function to return a generator.

Generalizations of this function would include functions to repeat subruns in *sequence* to not only a certain count, as implemented here, but to a certain length, weight or sum. That is, `seqtools.repeat_subruns_to_length()`, `seqtools.repeat_subruns_to_weight()` and `seqtools.repeat_subruns_to_sum()`. Changed in version 2.0: renamed `seqtools.repeat_subruns_to_count()` to `seqtools.repeat_runs_in_sequence_to_count()`.

seqtools.repeat_sequence_elements_at_indices

`abjad.tools.seqtools.repeat_sequence_elements_at_indices(sequence, indices, total)`

New in version 2.0. Repeat *sequence* elements at *indices* to *total* length:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.repeat_sequence_elements_at_indices(range(10), [6, 7, 8], 3)
[0, 1, 2, 3, 4, 5, [6, 6, 6], [7, 7, 7], [8, 8, 8], 9]
```

Return list.

seqtools.repeat_sequence_elements_at_indices_cyclically

`abjad.tools.seqtools.repeat_sequence_elements_at_indices_cyclically(sequence, cycle_token, total)`

New in version 2.0. Repeat *sequence* elements at indices specified by *cycle_token* to *total* length:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.repeat_sequence_elements_at_indices_cyclically(range(10), (5, [1, 2]), 3)
[0, [1, 1, 1], [2, 2, 2], 3, 4, 5, [6, 6, 6], [7, 7, 7], 8, 9]
```

The *cycle_token* may be a sieve:

```
abjad> from abjad.tools import sievetools

abjad> sieve = sievetools.cycle_tokens_to_sieve((5, [1, 2]))
abjad> seqtools.repeat_sequence_elements_at_indices_cyclically(range(10), sieve, 3)
[0, [1, 1, 1], [2, 2, 2], 3, 4, 5, [6, 6, 6], [7, 7, 7], 8, 9]
```

Return list.

seqtools.repeat_sequence_elements_n_times_each

`abjad.tools.seqtools.repeat_sequence_elements_n_times_each(sequence, n)`

New in version 1.1. Repeat *sequence* elements *n* times each:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.repeat_sequence_elements_n_times_each((1, -1, 2, -3, 5, -5, 6), 2)
(1, 1, -1, -1, 2, 2, -3, -3, 5, 5, -5, -5, 6, 6)
```

Return newly constructed *sequence* object with copied *sequence* elements. Changed in version 2.0: renamed `listtools.repeat_elements_to_count()` to `seqtools.repeat_sequence_elements_n_times_each()`.

seqtools.repeat_sequence_n_times

`abjad.tools.seqtools.repeat_sequence_n_times(sequence, n)`

New in version 2.0. Repeat *sequence* *n* times:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.repeat_sequence_n_times((1, 2, 3, 4, 5), 3)
(1, 2, 3, 4, 5, 1, 2, 3, 4, 5, 1, 2, 3, 4, 5)
```

Repeat *sequence* 0 times:

```
abjad> seqtools.repeat_sequence_n_times((1, 2, 3, 4, 5), 0)
()
```

Return newly constructed *sequence* object of copied *sequence* elements.

seqtools.repeat_sequence_to_length

`abjad.tools.seqtools.repeat_sequence_to_length(sequence, length, start=0)`

New in version 1.1. Repeat *sequence* to nonnegative integer *length*:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.repeat_sequence_to_length(range(5), 11)
[0, 1, 2, 3, 4, 0, 1, 2, 3, 4, 0]
```

Repeat *sequence* to nonnegative integer *length* from *start*:

```
abjad> seqtools.repeat_sequence_to_length(range(5), 11, start = 2)
[2, 3, 4, 0, 1, 2, 3, 4, 0, 1, 2]
```

Return newly constructed *sequence* object. Changed in version 2.0: renamed `listtools.repeat_list_to_length()` to `seqtools.repeat_sequence_to_length()`.

seqtools.repeat_sequence_to_weight_at_least

`abjad.tools.seqtools.repeat_sequence_to_weight_at_least(sequence, weight)`

New in version 1.1. Repeat *sequence* to *weight* at least:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.repeat_sequence_to_weight_at_least((5, -5, -5), 23)
(5, -5, -5, 5, -5)
```

Return newly constructed *sequence* object.

seqtools.repeat_sequence_to_weight_at_most

`abjad.tools.seqtools.repeat_sequence_to_weight_at_most(sequence, weight)`

New in version 1.1. Repeat *sequence* to *weight* at most:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.repeat_sequence_to_weight_at_most((5, -5, -5), 23)
(5, -5, -5, 5)
```

Return newly constructed *sequence* object.

seqtools.repeat_sequence_to_weight_exactly

abjad.tools.seqtools.**repeat_sequence_to_weight_exactly**(*sequence*, *weight*)

New in version 1.1. Repeat *sequence* to *weight* exactly:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.repeat_sequence_to_weight_exactly((5, -5, -5), 23)
(5, -5, -5, 5, -3)
```

Return newly constructed *sequence* object.

seqtools.replace_sequence_elements_cyclically_with_new_material

abjad.tools.seqtools.**replace_sequence_elements_cyclically_with_new_material**(*sequence*,
indices,
new_material)

New in version 1.1. Replace *sequence* elements cyclically at *indices* with *new_material*:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.replace_sequence_elements_cyclically_with_new_material(range(20), ([0], 2), (['A', 1, 'B', 3, 4, 5, 'A', 7, 'B', 9, 10, 11, 'A', 13, 'B', 15, 16, 17, 'A', 19])

abjad> seqtools.replace_sequence_elements_cyclically_with_new_material(range(20), ([0], 2), (['*', 1, '*', 3, '*', 5, '*', 7, '*', 9, '*', 11, '*', 13, '*', 15, '*', 17, '*', 19])

abjad> seqtools.replace_sequence_elements_cyclically_with_new_material(range(20), ([0], 2), (['A', 1, 'B', 3, 'C', 5, 'D', 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19])

abjad> seqtools.replace_sequence_elements_cyclically_with_new_material(range(20), ([0, 1, 8, 13], 2), (['A', 'B', 2, 3, 4, 5, 6, 7, 'C', 9, 10, 11, 12, 'D', 14, 15, 16, 17, 18, 19])
```

Raise type error when *sequence* not a list.

Return newly constructed list. Changed in version 2.0: renamed `seqtools.replace_elements_cyclic()` to `seqtools.replace_sequence_elements_cyclically_with`.

seqtools.retain_sequence_elements_at_indices

abjad.tools.seqtools.**retain_sequence_elements_at_indices**(*sequence*, *indices*)

New in version 2.0. Retain *sequence* elements at *indices*:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.retain_sequence_elements_at_indices(range(20), [1, 16, 17, 18])
[1, 16, 17, 18]
```

Ignore negative indices.

Return list.

seqtools.retain_sequence_elements_at_indices_cyclically

`abjad.tools.seqtools.retain_sequence_elements_at_indices_cyclically` (*sequence*,
indices,
period,
off-
set=0)

New in version 2.0. Retain *sequence* elements at *indices* mod *period* plus *offset*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.retain_sequence_elements_at_indices_cyclically(range(20), [0, 1], 5, 3)
[3, 4, 8, 9, 13, 14, 18, 19]
```

Ignore negative values in *indices*.

Return list.

seqtools.reverse_sequence

`abjad.tools.seqtools.reverse_sequence` (*sequence*)

New in version 2.0. Reverse *sequence*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.reverse_sequence((1, 2, 3, 4, 5))
(5, 4, 3, 2, 1)
```

Return new *sequence* object.

seqtools.reverse_sequence_elements

`abjad.tools.seqtools.reverse_sequence_elements` (*sequence*)

New in version 2.0. Reverse *sequence* elements:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.reverse_sequence_elements([1, (2, 3, 4), 5, (6, 7)])
[1, (4, 3, 2), 5, (7, 6)]
```

Return new *sequence* object.

seqtools.rotate_sequence

`abjad.tools.seqtools.rotate_sequence` (*sequence*, *n*)

New in version 1.1. Rotate *sequence* to the right:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.rotate_sequence(range(10), 4)
[6, 7, 8, 9, 0, 1, 2, 3, 4, 5]
```

Rotate *sequence* to the left:

```
abjad> seqtools.rotate_sequence(range(10), -3)
[3, 4, 5, 6, 7, 8, 9, 0, 1, 2]
```

Rotate *sequence* neither to the right nor the left:

```
abjad> seqtools.rotate_sequence(range(10), 0)
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
```

Return newly created *sequence* object. Changed in version 2.0: renamed `seqtools.rotate()` to `seqtools.rotate_sequence()`.

seqtools.splice_new_elements_between_sequence_elements

```
abjad.tools.seqtools.splice_new_elements_between_sequence_elements(sequence,
                                                                    new_elements,
                                                                    over-
                                                                    hang=(0,
                                                                    0))
```

New in version 1.1. Splice copies of *new_elements* between each of the elements of *sequence*:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [0, 1, 2, 3, 4]
abjad> new_elements = ['A', 'B']

abjad> seqtools.splice_new_elements_between_sequence_elements(sequence, new_elements)
[0, 'A', 'B', 1, 'A', 'B', 2, 'A', 'B', 3, 'A', 'B', 4]
```

Splice copies of *new_elements* between each of the elements of *sequence* and after the last element of *sequence*:

```
abjad> seqtools.splice_new_elements_between_sequence_elements(sequence, new_elements, overhang =
[0, 'A', 'B', 1, 'A', 'B', 2, 'A', 'B', 3, 'A', 'B', 4, 'A', 'B']
```

Splice copies of *new_elements* before the first element of *sequence* and between each of the other elements of *sequence*:

```
abjad> seqtools.splice_new_elements_between_sequence_elements(sequence, new_elements, overhang =
['A', 'B', 0, 'A', 'B', 1, 'A', 'B', 2, 'A', 'B', 3, 'A', 'B', 4]
```

Splice copies of *new_elements* before the first element of *sequence*, after the last element of *sequence* and between each of the other elements of *sequence*:

```
abjad> seqtools.splice_new_elements_between_sequence_elements(sequence, new_elements, overhang =
['A', 'B', 0, 'A', 'B', 1, 'A', 'B', 2, 'A', 'B', 3, 'A', 'B', 4, 'A', 'B']
```

Return newly constructed list. Changed in version 2.0: renamed `seqtools.insert_slice_cyclic()` to `seqtools.splice_new_elements_between_sequence_elements()`.

seqtools.split_sequence_cyclically_by_weights_with_overhang

```
abjad.tools.seqtools.split_sequence_cyclically_by_weights_with_overhang(sequence,
                                                                    weights)
```

New in version 2.0. Split *sequence* cyclically by *weights* with overhang:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.split_sequence_cyclically_by_weights_with_overhang((10, -10, 10, -10), [3, 15, 3,
[(3,), (7, -8), (-2, 1), (3,), (6, -9), (-1,)]
```

Return list of *sequence* objects.

seqtools.split_sequence_cyclically_by_weights_without_overhang

abjad.tools.seqtools.**split_sequence_cyclically_by_weights_without_overhang**(*sequence*,
weights)

New in version 2.0. Split *sequence* cyclically by *weights* without overhang:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.split_sequence_cyclically_by_weights_without_overhang((10, -10, 10, -10), [3, 15, 3, 15])
[(3,), (7, -8), (-2, 1), (3,), (6, -9)]
```

Return list of *sequence* objects.

seqtools.split_sequence_extended_to_weights_with_overhang

abjad.tools.seqtools.**split_sequence_extended_to_weights_with_overhang**(*sequence*,
weights)

New in version 2.0. Split *sequence* extended to *weights* with overhang:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.split_sequence_extended_to_weights_with_overhang([1, 2, 3, 4, 5], [7, 7, 7])
[[1, 2, 3, 1], [3, 4], [1, 1, 2, 3], [4, 5]]
```

Return new object of *sequence* type.

seqtools.split_sequence_extended_to_weights_without_overhang

abjad.tools.seqtools.**split_sequence_extended_to_weights_without_overhang**(*sequence*,
weights)

New in version 2.0. Split *sequence* extended to *weights* without overhang:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.split_sequence_extended_to_weights_without_overhang([1, 2, 3, 4, 5], [7, 7, 7])
[[1, 2, 3, 1], [3, 4], [1, 1, 2, 3]]
```

Return new object of *sequence* type.

seqtools.split_sequence_once_by_weights_with_overhang

abjad.tools.seqtools.**split_sequence_once_by_weights_with_overhang**(*sequence*,
weights)

New in version 2.0. Split *sequence* once by *weights* with overhang:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.split_sequence_once_by_weights_with_overhang((10, -10, 10, -10), [3, 15, 3])
[(3,), (7, -8), (-2, 1), (9, -10)]
```

Return list of *sequence* objects.

seqtools.split_sequence_once_by_weights_without_overhang

abjad.tools.seqtools.**split_sequence_once_by_weights_without_overhang**(*sequence*,
weights)

New in version 2.0. Split *sequence* once by *weights* without overhang:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.split_sequence_once_by_weights_without_overhang((10, -10, 10, -10), [3, 15, 3])
[(3,), (7, -8), (-2, 1)]
```

Return list of *sequence* objects.

seqtools.sum_consecutive_sequence_elements_by_sign

abjad.tools.seqtools.**sum_consecutive_sequence_elements_by_sign**(*sequence*,
sign=[-1, 0, 1])

New in version 1.1. Sum consecutive *sequence* elements by *sign*:

```
abjad> from abjad.tools import seqtools

abjad> sequence = [0, 0, -1, -1, 2, 3, -5, 1, 2, 5, -5, -6]

abjad> seqtools.sum_consecutive_sequence_elements_by_sign(sequence)
[0, -2, 5, -5, 8, -11]

abjad> seqtools.sum_consecutive_sequence_elements_by_sign(sequence, sign = [-1])
[0, 0, -2, 2, 3, -5, 1, 2, 5, -11]

abjad> seqtools.sum_consecutive_sequence_elements_by_sign(sequence, sign = [0])
[0, -1, -1, 2, 3, -5, 1, 2, 5, -5, -6]

abjad> seqtools.sum_consecutive_sequence_elements_by_sign(sequence, sign = [1])
[0, 0, -1, -1, 5, -5, 8, -5, -6]

abjad> seqtools.sum_consecutive_sequence_elements_by_sign(sequence, sign = [-1, 0])
[0, -2, 2, 3, -5, 1, 2, 5, -11]

abjad> seqtools.sum_consecutive_sequence_elements_by_sign(sequence, sign = [-1, 1])
[0, 0, -2, 5, -5, 8, -11]

abjad> seqtools.sum_consecutive_sequence_elements_by_sign(sequence, sign = [0, 1])
[0, -1, -1, 5, -5, 8, -5, -6]

abjad> seqtools.sum_consecutive_sequence_elements_by_sign(sequence, sign = [-1, 0, 1])
[0, -2, 5, -5, 8, -11]
```

When -1 in *sign*, sum consecutive negative elements.

When 0 in *sign*, sum consecutive 0 elements.

When 1 in *sign*, sum consecutive positive elements.

Return list. Changed in version 2.0: renamed `seqtools.sum_by_sign()` to `seqtools.sum_consecutive_sequence_elements_by_sign()`.

seqtools.sum_sequence_elements_at_indices

`abjad.tools.seqtools.sum_sequence_elements_at_indices(sequence, pairs, period=None, overhang=True)`

New in version 1.1. Sum *sequence* elements at indices according to *pairs*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.sum_sequence_elements_at_indices(range(10), [(0, 3)])
[3, 3, 4, 5, 6, 7, 8, 9]
```

Sum *sequence* elements cyclically at indices according to *pairs* and *period*:

```
abjad> seqtools.sum_sequence_elements_at_indices(range(10), [(0, 3)], period = 4)
[3, 3, 15, 7, 17]
```

Sum *sequence* elements cyclically at indices according to *pairs* and *period* and do not return incomplete final sum:

```
abjad> seqtools.sum_sequence_elements_at_indices(range(10), [(0, 3)], period = 4, overhang = False)
[3, 3, 15, 7]
```

Replace `sequence[i:i+count]` with `sum(sequence[i:i+count])` for each `(i, count)` in *pairs*.

Indices in *pairs* must be less than *period* when *period* is not none.

Return new list. Changed in version 2.0: renamed `seqtools.sum_slices_at()` to `seqtools.sum_sequence_elements_at_indices()`.

seqtools.truncate_runs_in_sequence

`abjad.tools.seqtools.truncate_runs_in_sequence(sequence)`

New in version 1.1. Truncate subruns of like elements in *sequence* to length 1:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.truncate_runs_in_sequence([1, 1, 2, 3, 3, 3, 9, 4, 4, 4])
[1, 2, 3, 9, 4]
```

Return empty list when *sequence* is empty:

```
abjad> seqtools.truncate_runs_in_sequence([ ])
[]
```

Raise type error when *sequence* is not a list.

Return new list. Changed in version 2.0: renamed `seqtools.truncate_subruns()` to `seqtools.truncate_runs_in_sequence()`.

seqtools.truncate_sequence_to_sum

`abjad.tools.seqtools.truncate_sequence_to_sum(sequence, sum)`

New in version 1.1. Truncate *sequence* to *sum*:

```
abjad> from abjad.tools import seqtools
```



```

abjad> for n in range(10):
...     print n, seqtools.truncate_sequence_to_sum([-1, 2, -3, 4, -5, 6, -7, 8, -9, 10], n)
...
0 []
1 [-1, 2]
2 [-1, 2, -3, 4]
3 [-1, 2, -3, 4, -5, 6]
4 [-1, 2, -3, 4, -5, 6, -7, 8]
5 [-1, 2, -3, 4, -5, 6, -7, 8, -9, 10]
6 [-1, 2, -3, 4, -5, 6, -7, 8, -9, 10]
7 [-1, 2, -3, 4, -5, 6, -7, 8, -9, 10]
8 [-1, 2, -3, 4, -5, 6, -7, 8, -9, 10]
9 [-1, 2, -3, 4, -5, 6, -7, 8, -9, 10]

```

Return empty list when *sum* is 0:

```

abjad> seqtools.truncate_sequence_to_sum([1, 2, 3, 4, 5], 0)
[]

```

Raise type error when *sequence* is not a list.

Raise value error on negative *sum*.

Return new list. Changed in version 2.0: renamed `seqtools.truncate_to_sum()` to `seqtools.truncate_sequence_to_sum()`.

seqtools.truncate_sequence_to_weight

`abjad.tools.seqtools.truncate_sequence_to_weight(sequence, weight)`

New in version 1.1. Truncate *sequence* to *weight*:

```

abjad> from abjad.tools import seqtools

abjad> l = [-1, 2, -3, 4, -5, 6, -7, 8, -9, 10]
abjad> for x in range(10):
...     print x, seqtools.truncate_sequence_to_weight(l, x)
...
0 []
1 [-1]
2 [-1, 1]
3 [-1, 2]
4 [-1, 2, -1]
5 [-1, 2, -2]
6 [-1, 2, -3]
7 [-1, 2, -3, 1]
8 [-1, 2, -3, 2]
9 [-1, 2, -3, 3]

```

Return empty list when *weight* is 0:

```

abjad> seqtools.truncate_sequence_to_weight([1, 2, 3, 4, 5], 0)
[]

```

Raise type error when *sequence* is not a list.

Raise value error on negative *weight*.

Return new list. Changed in version 2.0: renamed `seqtools.truncate_to_weight()` to `seqtools.truncate_sequence_to_weight()`.

seqtools.yield_all_combinations_of_sequence_elements

abjad.tools.seqtools.**yield_all_combinations_of_sequence_elements**(*sequence*,
min_length=None,
max_length=None)

New in version 2.0. Yield all combinations of *sequence* in binary string order:

```
abjad> from abjad.tools import seqtools

abjad> list(seqtools.yield_all_combinations_of_sequence_elements([1, 2, 3, 4]))
[[], [1], [2], [1, 2], [3], [1, 3], [2, 3], [1, 2, 3], [4], [1, 4],
 [2, 4], [1, 2, 4], [3, 4], [1, 3, 4], [2, 3, 4], [1, 2, 3, 4]]
```

Yield all combinations of *sequence* greater than or equal to *min_length* in binary string order:

```
abjad> list(seqtools.yield_all_combinations_of_sequence_elements([1, 2, 3, 4], min_length = 3))
[[1, 2, 3], [1, 2, 4], [1, 3, 4], [2, 3, 4], [1, 2, 3, 4]]
```

Yield all combinations of *sequence* less than or equal to *max_length* in binary string order:

```
abjad> list(seqtools.yield_all_combinations_of_sequence_elements([1, 2, 3, 4], max_length = 2))
[[], [1], [2], [1, 2], [3], [1, 3], [2, 3], [4], [1, 4], [2, 4], [3, 4]]
```

Yield all combinations of *sequence* greater than or equal to *min_length* and less than or equal to *max_length* in lex order:

```
abjad> list(seqtools.yield_all_combinations_of_sequence_elements([1, 2, 3, 4], min_length = 2, max_length = 3))
[[1, 2], [1, 3], [2, 3], [1, 4], [2, 4], [3, 4]]
```

Return generator of newly created *sequence* objects. Changed in version 2.0: renamed `seqtools.sublists()` to `seqtools.yield_all_combinations_of_sequence_elements()`.

seqtools.yield_all_k_ary_sequences_of_length

abjad.tools.seqtools.**yield_all_k_ary_sequences_of_length**(*k*, *length*)

New in version 2.0. Generate all *k*-ary sequences of *length*:

```
abjad> from abjad.tools import seqtools

abjad> for sequence in seqtools.yield_all_k_ary_sequences_of_length(2, 3):
...     sequence
...
(0, 0, 0)
(0, 0, 1)
(0, 1, 0)
(0, 1, 1)
(1, 0, 0)
(1, 0, 1)
(1, 1, 0)
(1, 1, 1)
```

Return generator of tuples.

seqtools.yield_all_pairs_between_sequences

abjad.tools.seqtools.**yield_all_pairs_between_sequences**(*l*, *m*)

New in version 2.0. Yield all pairs between sequences *l* and *m*:

```

abjad> from abjad.tools import seqtools

abjad> for pair in seqtools.yield_all_pairs_between_sequences([1, 2, 3], [4, 5]):
...     pair
...
(1, 4)
(1, 5)
(2, 4)
(2, 5)
(3, 4)
(3, 5)

```

Return pair generator.

seqtools.yield_all_partitions_of_sequence

`abjad.tools.seqtools.yield_all_partitions_of_sequence(sequence)`

New in version 2.0. Yield all partitions of *sequence*:

```

abjad> from abjad.tools import seqtools

abjad> for partition in seqtools.yield_all_partitions_of_sequence([0, 1, 2, 3]):
...     partition
...
[[0, 1, 2, 3]]
[[0, 1, 2], [3]]
[[0, 1], [2, 3]]
[[0, 1], [2], [3]]
[[0], [1, 2, 3]]
[[0], [1, 2], [3]]
[[0], [1], [2, 3]]
[[0], [1], [2], [3]]

```

Return generator of newly created lists.

seqtools.yield_all_permutations_of_sequence

`abjad.tools.seqtools.yield_all_permutations_of_sequence(sequence)`

New in version 1.1. Yield all permutations of *sequence* in lex order:

```

abjad> from abjad.tools import seqtools

abjad> list(seqtools.yield_all_permutations_of_sequence((1, 2, 3)))
[(1, 2, 3), (1, 3, 2), (2, 1, 3), (2, 3, 1), (3, 1, 2), (3, 2, 1)]

```

Return generator of *sequence* objects. Changed in version 2.0: renamed `listtools.permutations()` to `seqtools.yield_all_permutations_of_sequence()`.

seqtools.yield_all_permutations_of_sequence_in_orbit

`abjad.tools.seqtools.yield_all_permutations_of_sequence_in_orbit(sequence, permutation)`

New in version 2.0. Yield all permutations of *sequence* in orbit of *permutation* in lex order:

```
abjad> from abjad.tools import seqtools
```

```
abjad> list(seqtools.yield_all_permutations_of_sequence_in_orbit((1, 2, 3, 4), [1, 2, 3, 0]))
[(1, 2, 3, 4), (2, 3, 4, 1), (3, 4, 1, 2), (4, 1, 2, 3)]
```

Return generator of *sequence* objects.

seqtools.yield_all_restricted_growth_functions_of_length

`abjad.tools.seqtools.yield_all_restricted_growth_functions_of_length(length)`

New in version 2.0. Generate all restricted growth functions of *length* in lex order:

```
abjad> from abjad.tools import seqtools
```

```
abjad> for rgf in seqtools.yield_all_restricted_growth_functions_of_length(4):
...     rgf
...
(1, 1, 1, 1)
(1, 1, 1, 2)
(1, 1, 2, 1)
(1, 1, 2, 2)
(1, 1, 2, 3)
(1, 2, 1, 1)
(1, 2, 1, 2)
(1, 2, 1, 3)
(1, 2, 2, 1)
(1, 2, 2, 2)
(1, 2, 2, 3)
(1, 2, 3, 1)
(1, 2, 3, 2)
(1, 2, 3, 3)
(1, 2, 3, 4)
```

Return generator of tuples.

seqtools.yield_all_rotations_of_sequence

`abjad.tools.seqtools.yield_all_rotations_of_sequence(sequence, n=1)`

New in version 2.0. Yield all *n*-rotations of *sequence* up to identity:

```
abjad> from abjad.tools import seqtools
```

```
abjad> list(seqtools.yield_all_rotations_of_sequence([1, 2, 3, 4], -1))
[[1, 2, 3, 4], [2, 3, 4, 1], [3, 4, 1, 2], [4, 1, 2, 3]]
```

Return generator of *sequence* objects.

seqtools.yield_all_set_partitions_of_sequence

`abjad.tools.seqtools.yield_all_set_partitions_of_sequence(sequence)`

New in version 2.0. Yield all set partitions of *sequence* in restricted growth function order:

```
abjad> from abjad.tools import seqtools
```

```

abjad> for set_partition in seqtools.yield_all_set_partitions_of_sequence([21, 22, 23, 24]):
...     set_partition
...
[[21, 22, 23, 24]]
[[21, 22, 23], [24]]
[[21, 22, 24], [23]]
[[21, 22], [23, 24]]
[[21, 22], [23], [24]]
[[21, 23, 24], [22]]
[[21, 23], [22, 24]]
[[21, 23], [22], [24]]
[[21, 24], [22, 23]]
[[21], [22, 23, 24]]
[[21], [22, 23], [24]]
[[21, 24], [22], [23]]
[[21], [22, 24], [23]]
[[21], [22], [23, 24]]
[[21], [22], [23], [24]]

```

Return generator of list of lists.

seqtools.yield_all_subsequences_of_sequence

`abjad.tools.seqtools.yield_all_subsequences_of_sequence(sequence, min_length=0, max_length=None)`

New in version 2.0. Yield all subsequences of *sequence* in lex order:

```

abjad> from abjad.tools import seqtools

abjad> list(seqtools.yield_all_subsequences_of_sequence([0, 1, 2]))
[[], [0], [0, 1], [0, 1, 2], [1], [1, 2], [2]]

```

Yield all subsequences of *sequence* greater than or equal to *min_length* in lex order:

```

abjad> list(seqtools.yield_all_subsequences_of_sequence([0, 1, 2, 3, 4], min_length = 3))
[[0, 1, 2], [0, 1, 2, 3], [0, 1, 2, 3, 4], [1, 2, 3], [1, 2, 3, 4], [2, 3, 4]]

```

Yield all subsequences of *sequence* less than or equal to *max_length* in lex order:

```

abjad> list(seqtools.yield_all_subsequences_of_sequence([0, 1, 2, 3, 4], max_length = 3))
[[], [0], [0, 1], [0, 1, 2], [1], [1, 2], [1, 2, 3], [2], [2, 3], [2, 3, 4], [3], [3, 4], [4]]

```

Yield all subsequences of *sequence* greater than or equal to *min_length* and less than or equal to *max_length* in lex order:

```

abjad> list(seqtools.yield_all_subsequences_of_sequence([0, 1, 2, 3, 4], min_length = 3, max_length = 3))
[[0, 1, 2], [1, 2, 3], [2, 3, 4]]

```

Return generator of newly created *sequence* slices.

seqtools.yield_all_unordered_pairs_of_sequence

`abjad.tools.seqtools.yield_all_unordered_pairs_of_sequence(sequence)`

New in version 2.0. Yield all unordered pairs of *sequence*:

```

abjad> from abjad.tools import seqtools

```

```
abjad> list(seqtools.yield_all_unordered_pairs_of_sequence([1, 2, 3, 4]))
[(1, 2), (1, 3), (1, 4), (2, 3), (2, 4), (3, 4)]
```

Yield all unordered pairs of length-1 *sequence*:

```
abjad> list(seqtools.yield_all_unordered_pairs_of_sequence([1]))
[]
```

Yield all unordered pairs of empty *sequence*:

```
abjad> list(seqtools.yield_all_unordered_pairs_of_sequence([ ]))
[]
```

Yield all unordered pairs of *sequence* with duplicate elements:

```
abjad> list(seqtools.yield_all_unordered_pairs_of_sequence([1, 1, 1]))
[(1, 1), (1, 1), (1, 1)]
```

Pairs are tuples instead of sets to accommodate duplicate *sequence* elements.

Return generator.

seqtools.yield_outer_product_of_sequences

abjad.tools.seqtools.**yield_outer_product_of_sequences**(*sequences*)

New in version 1.1. Yield outer product of *sequences*:

```
abjad> from abjad.tools import seqtools
```

```
abjad> list(seqtools.yield_outer_product_of_sequences([[1, 2, 3], ['a', 'b']]))
[[1, 'a'], [1, 'b'], [2, 'a'], [2, 'b'], [3, 'a'], [3, 'b']]
```

```
abjad> list(seqtools.yield_outer_product_of_sequences([[1, 2, 3], ['a', 'b'], ['X', 'Y']]))
[[1, 'a', 'X'], [1, 'a', 'Y'], [1, 'b', 'X'], [1, 'b', 'Y'],
 [2, 'a', 'X'], [2, 'a', 'Y'], [2, 'b', 'X'], [2, 'b', 'Y'],
 [3, 'a', 'X'], [3, 'a', 'Y'], [3, 'b', 'X'], [3, 'b', 'Y']]
```

```
abjad> list(seqtools.yield_outer_product_of_sequences([[1, 2, 3], [4, 5], [6, 7, 8]]))
[[1, 4, 6], [1, 4, 7], [1, 4, 8], [1, 5, 6], [1, 5, 7], [1, 5, 8],
 [2, 4, 6], [2, 4, 7], [2, 4, 8], [2, 5, 6], [2, 5, 7], [2, 5, 8],
 [3, 4, 6], [3, 4, 7], [3, 4, 8], [3, 5, 6], [3, 5, 7], [3, 5, 8]]
```

Return generator. Changed in version 2.0: renamed `seqtools.outer_product()` to `seqtools.yield_outer_product_of_sequences()`.

seqtools.zip_sequences_cyclically

abjad.tools.seqtools.**zip_sequences_cyclically**(**sequences*)

New in version 1.1. Zip *sequences* cyclically:

```
abjad> from abjad.tools import seqtools
```

```
abjad> seqtools.zip_sequences_cyclically([1, 2, 3], ['a', 'b'])
[(1, 'a'), (2, 'b'), (3, 'a')]
```

New in version 1.1: Arbitrary number of input sequences now allowed.

```
abjad> seqtools.zip_sequences_cyclically([10, 11, 12], [20, 21], [30, 31, 32, 33])
[(10, 20, 30), (11, 21, 31), (12, 20, 32), (10, 21, 33)]
```

Cycle over the elements of the sequences of shorter length.

Return list of length equal to sequence of greatest length in *sequences*. Changed in version 2.0: renamed `seqtools.zip_cyclic()` to `seqtools.zip_sequences_cyclically()`.

seqtools.zip_sequences_without_truncation

```
abjad.tools.seqtools.zip_sequences_without_truncation(*sequences)
```

New in version 1.1. Zip *sequences* nontruncating:

```
abjad> from abjad.tools import seqtools

abjad> seqtools.zip_sequences_without_truncation([1, 2, 3, 4], [11, 12, 13], [21, 22, 23])
[(1, 11, 21), (2, 12, 22), (3, 13, 23), (4,)]
```

Lengths of the tuples returned may differ but will always be greater than or equal to 1.

Return list of tuples. Changed in version 2.0: renamed `seqtools.zip_nontruncating()` to `seqtools.zip_sequences_without_truncation()`.

sievetools

sievetools.ResidueClass

```
class abjad.tools.sievetools.ResidueClass(*args)
```

Bases: `abjad.tools.sievetools._BaseResidueClass`, `_BaseResidueClass`, `_BaseResidueClass`, `abjad.core._Immutable`, `_Immutable`, `_Immutable`

Residue class (or congruence class). Residue classes form the basis of Xenakis sieves. They can be used to construct any complex periodic integer (or boolean) sequence as a combination of simple periodic sequences.

Example from the opening of Xenakis's *Psappha* for solo percussion:

```
abjad> from abjad.tools.sievetools import ResidueClass as RC

abjad> s1 = (RC(8, 0) | RC(8, 1) | RC(8, 7)) & (RC(5, 1) | RC(5, 3))
abjad> s2 = (RC(8, 0) | RC(8, 1) | RC(8, 2)) & RC(5, 0)
abjad> s3 = RC(8, 3)
abjad> s4 = RC(8, 4)
abjad> s5 = (RC(8, 5) | RC(8, 6)) & (RC(5, 2) | RC(5, 3) | RC(5, 4))
abjad> s6 = (RC(8, 1) & RC(5, 2))
abjad> s7 = (RC(8, 6) & RC(5, 1))

abjad> y = s1 | s2 | s3 | s4 | s5 | s6 | s7
abjad> y
{{ResidueClass(8, 0) | ResidueClass(8, 1) | ResidueClass(8, 7)} & {ResidueClass(5, 1) | ResidueClass(5, 3)}

abjad> y.get_congruent_bases(40)
[0, 1, 3, 4, 6, 8, 10, 11, 12, 13, 14, 16, 17, 19, 20, 22, 23, 25, 27,
 28, 29, 31, 33, 35, 36, 37, 38, 40]
abjad> y.get_boolean_train(40)
[1, 1, 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 0, 1, 1, 0, 1, 1, 0,
 1, 1, 0, 1, 0, 1, 1, 1, 0, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 0]
```

Return residue class.

get_boolean_train (*min_max)

Returns a boolean train with 0s mapped to the integers that are not congruent bases of the residue class and 1s mapped to those that are. The method takes one or two integer arguments. If only one is given, it is taken as the max range and the min is assumed to be 0.

Example:

```
abjad> from abjad.tools.sievetools import ResidueClass as RC

abjad> r = RC(3, 0)
abjad> r.get_boolean_train(6)
[1, 0, 0, 1, 0, 0]
abjad> r.get_congruent_bases(-6, 6)
[-6, -3, 0, 3, 6]
```

Return list.

get_congruent_bases (*min_max)

Returns all the congruent bases of this residue class within the given range. The method takes one or two integer arguments. If only one is given, it is taken as the max range and the min is assumed to be 0.

Example:

```
abjad> from abjad.tools.sievetools import ResidueClass as RC

abjad> r = RC(3, 0)
abjad> r.get_congruent_bases(6)
[0, 3, 6]
abjad> r.get_congruent_bases(-6, 6)
[-6, -3, 0, 3, 6]
```

Return list.

modulo

Period of residue class.

residue

Residue of residue class.

sievetools.ResidueClassExpression

class abjad.tools.sievetools.**ResidueClassExpression** (rcs, operator='or')

Bases: abjad.tools.sievetools._BaseResidueClass._BaseResidueClass._BaseResidueClass, abjad.core._Immutable._Immutable._Immutable

get_boolean_train (*min_max)

Returns a boolean train with 0s mapped to the integers that are not congruent bases of the RC expression and 1s mapped to those that are. The method takes one or two integer arguments. If only one is given, it is taken as the max range and min is assumed to be 0.

Example:

```
abjad> from abjad.tools.sievetools import ResidueClass as RC

abjad> e = RC(3, 0) | RC(2, 0)
abjad> e.get_boolean_train(6)
[1, 0, 1, 1, 1, 0]
abjad> e.get_congruent_bases(-6, 6)
[-6, -4, -3, -2, 0, 2, 3, 4, 6]
```


Return list.

get_congruent_bases (*min_max)

Returns all the congruent bases of this RC expression within the given range. The method takes one or two integer arguments. If only one it given, it is taken as the max range and min is assumed to be 0.

Example:

```
abjad> from abjad.tools.sievetools import ResidueClass as RC
```

```
abjad> e = RC(3, 0) | RC(2, 0)
abjad> e.get_congruent_bases(6)
[0, 2, 3, 4, 6]
abjad> e.get_congruent_bases(-6, 6)
[-6, -4, -3, -2, 0, 2, 3, 4, 6]
```

Return list.

is_congruent_base (integer)

operator

Operator of residue class expression.

period

rcls

Residue classes of expression.

representative_boolean_train

representative_congruent_bases

sievetools.cycle_tokens_to_sieve

abjad.tools.sievetools.**cycle_tokens_to_sieve** (*cycle_tokens)

New in version 2.0. Make Xenakis sieve from arbitrarily many *cycle_tokens*.

```
abjad> from abjad.tools import sievetools
```

```
abjad> cycle_token_1 = (6, [0, 4, 5])
abjad> cycle_token_2 = (10, [0, 1, 2], 6)
abjad> sievetools.cycle_tokens_to_sieve(cycle_token_1, cycle_token_2)
{ResidueClass(6, 0) | ResidueClass(6, 4) | ResidueClass(6, 5) | ResidueClass(10, 6) | ResidueClass(10, 2)}
```

Cycle token comprises mandatory *modulo*, mandatory *residues* and optional *offset*.

tempotools

tempotools.integer_tempo_to_multiplier_tempo_pairs

abjad.tools.tempotools.**integer_tempo_to_multiplier_tempo_pairs** (integer_tempo,

maxi-
mum_numerator=None,
maxi-
mum_denominator=None)

New in version 2.0. Return all multiplier, tempo pairs possible from *integer_tempo*.

Tempi must be no less than $\text{integer_tempo} / 2$ and not greater than $2 * \text{integer_tempo}$:

```
abjad> from abjad.tools import tempotools

abjad> pairs = tempotools.integer_tempo_to_multiplier_tempo_pairs(58, 8, 8)
abjad> for pair in pairs:
...     pair
...
(Fraction(1, 2), Fraction(29, 1))
(Fraction(1, 1), Fraction(58, 1))
(Fraction(3, 2), Fraction(87, 1))
(Fraction(2, 1), Fraction(116, 1))
```

Return list.

tempotools.integer_tempo_to_multiplier_tempo_pairs_report

```
abjad.tools.tempotools.integer_tempo_to_multiplier_tempo_pairs_report(integer_tempo,
                                                                    maxi-
                                                                    mum_numerator=None,
                                                                    maxi-
                                                                    mum_denominator=None)
```

New in version 2.0. Print all multiplier, tempo pairs possible from *integer_tempo*.

Allow no tempi less than $\text{integer_tempo} / 2$ nor greater than $2 * \text{integer_tempo}$:

```
abjad> from abjad.tools import tempotools

abjad> tempotools.integer_tempo_to_multiplier_tempo_pairs_report(58, 8, 8)
2:1      29
1:1      58
2:3      87
1:2     116
```

With more lenient numerator and denominator.

```
abjad> tempotools.integer_tempo_to_multiplier_tempo_pairs_report(58, 30, 30)
2:1      29
29:15    30
29:16    32
29:17    34
29:18    36
29:19    38
29:20    40
29:21    42
29:22    44
29:23    46
29:24    48
29:25    50
29:26    52
29:27    54
29:28    56
1:1      58
29:30    60
2:3      87
1:2     116
```

Return none.

threadtools

threadtools.component_to_thread_signature

`abjad.tools.threadtools.component_to_thread_signature` (*component*)

Return `_ContainmentSignature` giving the root and first voice, staff and score in parentage of *component*.

threadtools.iterate_thread_backward_from_component

`abjad.tools.threadtools.iterate_thread_backward_from_component` (*component*,
klass=None)

New in version 2.0. Yield right-to-left components in the thread of *component* starting from *component*.

When `klass = None` return all components in the thread of *component*.

When *klass* is set to some other Abjad class, yield only *klass* instances in the thread of *component*:

```
abjad> from abjad.tools import threadtools
```

```
abjad> container = Container(Voice(notetools.make_repeated_notes(2)) * 2)
abjad> container.is_parallel = True
abjad> container[0].name = 'voice 1'
abjad> container[1].name = 'voice 2'
abjad> staff = Staff(container * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> print staff.format
\new Staff {
  <<
    \context Voice = "voice 1" {
      c'8
      d'8
    }
    \context Voice = "voice 2" {
      e'8
      f'8
    }
  >>
  <<
    \context Voice = "voice 1" {
      g'8
      a'8
    }
    \context Voice = "voice 2" {
      b'8
      c''8
    }
  >>
}
```

Starting from the last leaf in score.

```
abjad> for x in threadtools.iterate_thread_backward_from_component(staff.leaves[-1], Note):
...     x
Note("c'8")
Note("b'8")
Note("f'8")
Note("e'8")
```

Yield all components in thread:

```
abjad> for x in threadtools.iterate_thread_backward_from_component(staff.leaves[-1]):
...     x
Note("c'8")
Voice="voice 2"{2}
Note("b'8")
Voice="voice 2"{2}
Note("f'8")
Note("e'8")
```

Note that this function is a special type of depth-first search.

Compare	with	<code>threadtools.iterate_thread_backward_in_expr()</code> .
Changed in version 2.0:	renamed	<code>iterate.thread_backward_from()</code> to
		<code>threadtools.iterate_thread_backward_from_component()</code> .
Changed in version 2.0:	renamed	<code>iterate.thread_backward_from_component()</code> to
		<code>threadtools.iterate_thread_backward_from_component()</code> .

`threadtools.iterate_thread_backward_in_expr`

`abjad.tools.threadtools.iterate_thread_backward_in_expr(expr, class, thread_signature)`

New in version 2.0. Yield right-to-left instances of *class* in *expr* with *thread_signature*:

```
abjad> from abjad.tools import threadtools

abjad> container = Container(Voice(notetools.make_repeated_notes(2)) * 2)
abjad> container.is_parallel = True
abjad> container[0].name = 'voice 1'
abjad> container[1].name = 'vocie 2'
abjad> staff = Staff(container * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> f(staff)
\new Staff {
    <<
        \context Voice = "voice 1" {
            c'8
            d'8
        }
        \context Voice = "vocie 2" {
            e'8
            f'8
        }
    >>
    <<
        \context Voice = "voice 1" {
            g'8
            a'8
        }
        \context Voice = "vocie 2" {
            b'8
            c''8
        }
    >>
}

abjad> signature = threadtools.component_to_thread_signature(staff[0])
abjad> for x in threadtools.iterate_thread_backward_in_expr(staff, Note, signature): # doctest:
```

```
...      x
Note("c'8")
Note("b'8")
Note("f'8")
Note("e'8")
```

The important thing to note is that the function yields only those leaves that sit in the same thread.

Compare with `componenttools.iterate_components_backward_in_expr()`.
 Changed in version 2.0: renamed `iterate.thread_backward_in()` to `threadtools.iterate_thread_backward_in_expr()`.

threadtools.iterate_thread_forward_from_component

`abjad.tools.threadtools.iterate_thread_forward_from_component` (*component*,
klass=None)

New in version 1.1. Yield left-to-right components in the thread of *component* starting from *component*.

When `klass = None` return all components in the thread of *component*.

When *klass* is set to some other Abjad class, yield only *klass* instances in the thread of *component*:

```
abjad> from abjad.tools import threadtools

abjad> container = Container(Voice(notetools.make_repeated_notes(2)) * 2)
abjad> container.is_parallel = True
abjad> container[0].name = 'voice 1'
abjad> container[1].name = 'voice 2'
abjad> staff = Staff(container * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> print staff.format
\new Staff {
    <<
        \context Voice = "voice 1" {
            c'8
            d'8
        }
        \context Voice = "voice 2" {
            e'8
            f'8
        }
    >>
    <<
        \context Voice = "voice 1" {
            g'8
            a'8
        }
        \context Voice = "voice 2" {
            b'8
            c''8
        }
    >>
}
```

Starting from the first leaf in score.

```
abjad> for x in threadtools.iterate_thread_forward_from_component(staff.leaves[0], Note):
...     x
...
```

```
Note("c'8")
Note("d'8")
Note("g'8")
Note("a'8")
```

Starting from the second leaf in score.

```
abjad> for x in threadtools.iterate_thread_forward_from_component(staff.leaves[1], Note):
...     x
...
Note("d'8")
Note("g'8")
Note("a'8")
```

Yield all components in thread.

```
abjad> for x in threadtools.iterate_thread_forward_from_component(staff.leaves[0]):
...     x
...
Note("c'8")
Voice-"voice 1"{2}
Note("d'8")
Voice-"voice 1"{2}
Note("g'8")
Note("a'8")
```

Note that this function is a special type of depth-first search.

Compare	with	<code>threadtools.iterate_thread_forward_in_expr()</code> .
Changed in version 2.0:	renamed	<code>iterate.thread_forward_from()</code> to
		<code>threadtools.iterate_thread_forward_from_component()</code> .
Changed in version 2.0:	renamed	<code>iterate.thread_forward_from_component()</code> to
		<code>threadtools.iterate_thread_forward_from_component()</code> .

`threadtools.iterate_thread_forward_in_expr`

`abjad.tools.threadtools.iterate_thread_forward_in_expr(expr, class, thread_signature)`

New in version 1.1. Yield left-to-right instances of *class* in *expr* with *thread_signature*:

```
abjad> from abjad.tools import threadtools

abjad> container = Container(Voice(notetools.make_repeated_notes(2)) * 2)
abjad> container.is_parallel = True
abjad> container[0].name = 'voice 1'
abjad> container[1].name = 'voice 2'
abjad> staff = Staff(container * 2)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(staff)
abjad> print staff.format
\new Staff {
  <<
    \context Voice = "voice 1" {
      c'8
      d'8
    }
    \context Voice = "voice 2" {
      e'8
      f'8
    }
  >>
}
```

```

    }
    >>
    <<
        \context Voice = "voice 1" {
            g'8
            a'8
        }
        \context Voice = "voice 2" {
            b'8
            c''8
        }
    >>
}

abjad> signature = threadtools.component_to_thread_signature(staff.leaves[0])
abjad> for x in threadtools.iterate_thread_forward_in_expr(staff, Note, signature):
...     x
...
Note("c'8")
Note("d'8")
Note("g'8")
Note("a'8")

```

The important thing to note is that the function yields only those leaves that sit in the same thread.

Compare with `componenttools.iterate_components_forward_in_expr()`.
 Changed in version 2.0: renamed `iterate.thread_forward_in()`
 to `threadtools.iterate_thread_forward_in_expr()`. Changed in
 version 2.0: renamed `iterate.thread_forward_in_expr()` to
`threadtools.iterate_thread_forward_in_expr()`.

tonalitytools

tonalitytools.ChordClass

class `abjad.tools.tonalitytools.ChordClass`

Bases: `abjad.tools.pitchtools.NamedChromaticPitchClassSet`, `NamedChromaticPitchClassSet`, `Nar`
 New in version 2.0. Abjad model of tonal chords like G 7, G 6/5, G half-diminished 6/5, etc.

Note that notions like G 7 represent an entire *class of* chords because there are many different spacings and registrations of a G 7 chord.

bass

cardinality

extent

figured_bass

inversion

markup

quality_indicator

quality_pair

root

root_string

transpose (*mdi*)

tonalitytools.ChordQualityIndicator

class abjad.tools.tonalitytools.**ChordQualityIndicator**

Bases: abjad.tools.pitchtools.HarmonicDiatonicIntervalSegment.HarmonicDiatonicIntervalSegment

New in version 2.0. Chord quality indicator.

cardinality

extent

extent_name

inversion

position

quality_string

rotation

tonalitytools.DoublingIndicator

class abjad.tools.tonalitytools.**DoublingIndicator** (*doublings*)

Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Indicator of chord doubling.

Value object that can not be changed after instantiation.

doublings

tonalitytools.ExtentIndicator

class abjad.tools.tonalitytools.**ExtentIndicator** (*arg*)

Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Indicator of chord extent, such as triad, seventh chord, ninth chord, etc.

Value object that can not be changed after instantiation.

name

number

tonalitytools.InversionIndicator

class abjad.tools.tonalitytools.**InversionIndicator** (*arg=0*)

Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Indicator of the inversion of tertian chords: 5, 63, 64 and also 7, 65, 43, 42, etc. Also root position, first, second, third inversions, etc.

Value object that can not be changed once initialized.

extent_to_figured_bass_string (*extent*)

name

number

title

tonalitytools.Mode

class abjad.tools.tonalitytools.**Mode** (*arg*)

Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Diatonic mode.
Can be extended for nondiatonic mode.

Modes with different ascending and descending forms not yet implemented.

melodic_diatonic_interval_segment

mode_name_string

tonalitytools.OmissionIndicator

class abjad.tools.tonalitytools.**OmissionIndicator**

Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Indicator of missing chord tones.

Value object that can not be changed after instantiation.

tonalitytools.QualityIndicator

class abjad.tools.tonalitytools.**QualityIndicator** (*quality_string*)

Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Indicator of chord quality, such as major, minor, dominant, diminished, etc.

Value object that can not be changed after instantiation.

is_uppercase

quality_string

tonalitytools.Scale

class abjad.tools.tonalitytools.**Scale**

Bases: abjad.tools.pitchtools.NamedChromaticPitchClassSegment.NamedChromaticPitchClassSegment New in version 2.0. Abjad model of diatonic scale.

diatonic_interval_class_segment

dominant

key_signature

leading_tone

mediant

named_chromatic_pitch_class_to_scale_degree (**args*)

scale_degree_to_named_chromatic_pitch_class (**args*)

subdominant

submediant

superdominant

tonic

tonalitytools.ScaleDegree

```
class abjad.tools.tonalitytools.ScaleDegree(*args)
    Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Abjad model of
    diatonic scale degrees 1, 2, 3, 4, 5, 6, 7 and also chromatic alterations including flat-2, flat-3, flat-6, etc.

    accidental
        Read-only accidental applied to scale degree.

    apply_accidental(accidental)
        Apply accidental to self and emit new instance.

    name
        Read-only name of scale degree.

    number
        Read-only number of diatonic scale degree from 1 to 7, inclusive.

    roman_numeral_string

    symbolic_string

    title_string
```

tonalitytools.SuspensionIndicator

```
class abjad.tools.tonalitytools.SuspensionIndicator(*args)
    Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Indicator of 9-8,
    7-6, 4-3, 2-1 and other types of suspension typical of, for example, the Bach chorales.

    Value object that can not be changed after instantiation.

    chord_name_string

    figured_bass_pair

    figured_bass_string

    is_empty

    start

    stop

    title_string
```

tonalitytools.TonalFunction

```
class abjad.tools.tonalitytools.TonalFunction(*args)
    Bases: abjad.core._Immutable._Immutable._Immutable New in version 2.0. Abjad model of
    functions in tonal harmony: I, I6, I64, V, V7, V43, V42, bII, bII6, etc., also i, i6, i64, v, v7, etc.

    Value object that can not be cahnged after instantiation.

    bass_scale_degree

    extent

    figured_bass_string

    inversion

    markup
```

quality
root_scale_degree
scale_degree
suspension
symbolic_string

tonalitytools.analyze_chord

abjad.tools.tonalitytools.**analyze_chord**(*expr*)

New in version 2.0. Analyze *expr* and return chord class.

```
abjad> from abjad.tools import tonalitytools
```

```
abjad> chord = Chord([7, 10, 12, 16], (1, 4))
abjad> tonalitytools.analyze_chord(chord)
CDominantSeventhInSecondInversion
```

Return none when no tonal chord is understood.

```
abjad> chord = Chord(['c', 'cs', 'd'], (1, 4))
abjad> tonalitytools.analyze_chord(chord) is None
True
```

Raise tonal harmony error when chord can not analyze.

tonalitytools.analyze_incomplete_chord

abjad.tools.tonalitytools.**analyze_incomplete_chord**(*expr*)

New in version 2.0. Analyze *expr* and return chord class based on incomplete pitches.

```
abjad> from abjad.tools import tonalitytools
```

```
abjad> tonalitytools.analyze_incomplete_chord(Chord([7, 11], (1, 4)))
GMajorTriadInRootPosition
```

```
abjad> tonalitytools.analyze_incomplete_chord(Chord(['fs', 'g', 'b'], (1, 4)))
GMajorSeventhInSecondInversion
```

Return chord class.

tonalitytools.analyze_incomplete_tonal_function

abjad.tools.tonalitytools.**analyze_incomplete_tonal_function**(*expr*, *key_signature*)

New in version 2.0. Analyze tonal function of *expr* according to *key_signature*:

```
abjad> from abjad.tools import tonalitytools
```

```
abjad> chord = Chord("<c' e'>4")
abjad> key_signature = contexttools.KeySignatureMark('g', 'major')
abjad> tonalitytools.analyze_incomplete_tonal_function(chord, key_signature)
IVMajorTriadInRootPosition
```

Return tonal function.

tonalitytools.analyze_tonal_function

`abjad.tools.tonalitytools.analyze_tonal_function(expr, key_signature)`
 New in version 2.0. Analyze *expr* and return tonal function according to *key_signature*.

```
abjad> from abjad.tools import tonalitytools

abjad> chord = Chord(['ef', 'g', 'bf'], (1, 4))
abjad> key_signature = contexttools.KeySignatureMark('c', 'major')
abjad> tonalitytools.analyze_tonal_function(chord, key_signature)
FlatIIIMajorTriadInRootPosition
```

Return none when no tonal function is understood.

```
abjad> chord = Chord(['c', 'cs', 'd'], (1, 4))
abjad> key_signature = contexttools.KeySignatureMark('c', 'major')
abjad> tonalitytools.analyze_tonal_function(chord, key_signature) is None
True
```

Return tonal function or none.

tonalitytools.are_scalar_notes

`abjad.tools.tonalitytools.are_scalar_notes(*expr)`
 New in version 2.0. True when notes in *expr* are scalar.

```
abjad> from abjad.tools import tonalitytools

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> tonalitytools.are_scalar_notes(t[:])
True
```

Otherwise false.

```
abjad> tonalitytools.are_scalar_notes(Note("c'4"), Note("c'4"))
False
```

Changed in version 2.0: renamed `tonalitytools.are_scalar()` to `tonalitytools.are_scalar_notes()`.

tonalitytools.are_stepwise_ascending_notes

`abjad.tools.tonalitytools.are_stepwise_ascending_notes(*expr)`
 New in version 2.0. True when notes in *expr* are stepwise ascending.

```
abjad> from abjad.tools import tonalitytools

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> tonalitytools.are_stepwise_ascending_notes(t[:])
True
```

Otherwise false.

```
abjad> tonalitytools.are_stepwise_ascending_notes(Note("c'4"), Note("c'4"))
False
```

Changed in version 2.0: renamed `tonalitytools.are_stepwise_ascending()` to `tonalitytools.are_stepwise_ascending_notes()`.

tonalitytools.are_stepwise_descending_notes

`abjad.tools.tonalitytools.are_stepwise_descending_notes(*expr)`

New in version 2.0. True when notes in *expr* are stepwise descending:

```
abjad> from abjad.tools import tonalitytools

abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]
abjad> t = Staff(list(reversed(notes)))
abjad> tonalitytools.are_stepwise_descending_notes(t[:])
True
```

Otherwise false:

```
abjad> tonalitytools.are_stepwise_descending_notes(Note("c'4"), Note("c'4"))
False
```

Changed in version 2.0: renamed `tonalitytools.are_stepwise_descending()` to `tonalitytools.are_stepwise_descending_notes()`.

tonalitytools.are_stepwise_notes

`abjad.tools.tonalitytools.are_stepwise_notes(*expr)`

New in version 2.0. True when notes in *expr* are stepwise.

```
abjad> from abjad.tools import tonalitytools

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> tonalitytools.are_stepwise_notes(t[:])
True
```

Otherwise false.

```
abjad> tonalitytools.are_stepwise_notes(Note("c'4"), Note("c'4"))
False
```

Changed in version 2.0: renamed `tonalitytools.are_stepwise()` to `tonalitytools.are_stepwise_notes()`.

tonalitytools.chord_class_cardinality_to_extent

`abjad.tools.tonalitytools.chord_class_cardinality_to_extent(cardinality)`

..versionadded:: 2.0

Change integer chord class *cardinality* to integer chord class extent:

```
abjad> from abjad.tools import tonalitytools

abjad> tonalitytools.chord_class_cardinality_to_extent(4)
7
```

The function above indicates that a tertian chord with 4 unique pitches qualifies as a seventh chord.

tonalitytools.chord_class_extent_to_cardinality

`abjad.tools.tonalitytools.chord_class_extent_to_cardinality(extent)`

..versionadded:: 2.0

Change integer chord class *extent* to integer chord class cardinality:

```
abjad> from abjad.tools import tonalitytools

abjad> tonalitytools.chord_class_extent_to_cardinality(7)
4
```

The call above shows that a seventh chord comprises 4 unique pitch-classes.

tonalitytools.chord_class_extent_to_extent_name

`abjad.tools.tonalitytools.chord_class_extent_to_extent_name` (*extent*)

New in version 2.0. Change integer chord class *extent* to extent name string.

```
abjad> from abjad.tools import tonalitytools

abjad> tonalitytools.chord_class_extent_to_extent_name(7)
'seventh'
```

The call above shows that a tertian chord subtending 7 staff spaces qualifies as a seventh chord.

tonalitytools.diatonic_interval_class_segment_to_chord_quality_string

`abjad.tools.tonalitytools.diatonic_interval_class_segment_to_chord_quality_string` (*dic_seg*)

New in version 2.0. Change diatonic interval-class segment *dic_seg* to chord quality string:

```
abjad> from abjad.tools import tonalitytools

abjad> dic_seg = pitchtools.InversionEquivalentDiatonicIntervalClassSegment([
...     pitchtools.InversionEquivalentDiatonicIntervalClass('major', 3),
...     pitchtools.InversionEquivalentDiatonicIntervalClass('minor', 3),])
abjad> tonalitytools.diatonic_interval_class_segment_to_chord_quality_string(dic_seg)
'major'
```

Todo

Implement `diatonic_interval_class_set_to_chord_quality_string()`.

tonalitytools.is_neighbor_note

`abjad.tools.tonalitytools.is_neighbor_note` (*note*)

New in version 2.0. True when *note* is preceded by a stepwise interval in one direction and followed by a stepwise interval in the other direction. Otherwise false.

```
abjad> from abjad.tools import tonalitytools

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> for note in t:
...     print '%s\t%s' % (note, tonalitytools.is_neighbor_note(note))
...
c'8      False
d'8      False
e'8      False
f'8      False
```

Return boolean.

tonalitytools.is_passing_tone

`abjad.tools.tonalitytools.is_passing_tone(note)`

New in version 2.0. True when *note* is both preceeded and followed by scalewise sibling notes. Otherwise false.

```

abjad> from abjad.tools import tonalitytools

abjad> t = Staff("c'8 d'8 e'8 f'8")
abjad> for note in t:
...     print '%s\t%s' % (note, tonalitytools.is_passing_tone(note))
...
c'8      False
d'8      True
e'8      True
f'8      False

```

Return boolean.

tonalitytools.is_unlikely_melodic_diatonic_interval_in_chorale

`abjad.tools.tonalitytools.is_unlikely_melodic_diatonic_interval_in_chorale(mdi)`

New in version 2.0. True when *mdi* is unlikely melodic diatonic interval in JSB chorale.

```

abjad> from abjad.tools import tonalitytools

abjad> mdi = pitchtools.MelodicDiatonicInterval('major', 7)
abjad> tonalitytools.is_unlikely_melodic_diatonic_interval_in_chorale(mdi)
True

```

Otherwise False.

```

abjad> mdi = pitchtools.MelodicDiatonicInterval('major', 2)
abjad> tonalitytools.is_unlikely_melodic_diatonic_interval_in_chorale(mdi)
False

```

Return boolean.

tonalitytools.make_all_notes_in_ascending_and_descending_diatonic_scale

`abjad.tools.tonalitytools.make_all_notes_in_ascending_and_descending_diatonic_scale(key_signature)`

New in version 2.0. Construct one up-down period of scale according to *key_signature*:

```

abjad> from abjad.tools import tonalitytools

abjad> score = tonalitytools.make_all_notes_in_ascending_and_descending_diatonic_scale(contextttt
abjad> f(score)
\new Score \with {
    tempoWholesPerMinute = #(ly:make-moment 30 1)
} <<
    \new Staff {
        \key e \major
        e'8
        fs'8
        gs'8
        a'8
        b'8
        cs''8
    }

```

```

        ds''8
        e''8
        ds''8
        cs''8
        b'8
        a'8
        gs'8
        fs'8
        e'4
    }
>>

```

Changed in version 2.0: renamed `construct.scale_period()` to `tonalitytools.make_all_notes_in_ascending_and_descending_diatonic_scale()`. Changed in version 2.0: renamed `leaftools.make_all_notes_in_ascending_and_descending_diatonic_scale()` to `tonalitytools.make_all_notes_in_ascending_and_descending_diatonic_scale()`.

tonalitytools.make_first_n_notes_in_ascending_diatonic_scale

```

abjad.tools.tonalitytools.make_first_n_notes_in_ascending_diatonic_scale(count,
                                                                           writ-
                                                                           ten_duration=Duration(1,
                                                                           8),
                                                                           key_signature=None)

```

Construct *count* notes with *written_duration* according to *key_signature*:

```
abjad> from abjad.tools import tonalitytools
```

```

abjad> tonalitytools.make_first_n_notes_in_ascending_diatonic_scale(4)
[Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]

```

Allow nonassignable *written_duration*:

```

abjad> staff = Staff(tonalitytools.make_first_n_notes_in_ascending_diatonic_scale(2, (5, 16)))
abjad> f(staff)
\new Staff {
    c'4 ~
    c'16
    d'4 ~
    d'16
}

```

New in version 2.0: Optional *key_signature* keyword parameter. Changed in version 2.0: renamed `leaftools.make_first_n_notes_in_ascending_diatonic_scale()` to `tonalitytools.make_first_n_notes_in_ascending_diatonic_scale()`.

verticalitytools

verticalitytools.VerticalMoment

```

class abjad.tools.verticalitytools.VerticalMoment(prolated_offset, governors, compo-
nents)
    Bases: abjad.core._Immutable._Immutable._Immutable
    Everything happening at a single moment in musical time:

```



```

abjad> from abjad.tools import verticalitytools

abjad> score = Score([scoretools.PianoStaff([Staff("c'4 e'4 d'4 f'4"), Staff('g2 f2'))]])
abjad> contexttools.ClefMark('bass')(score[0][1])
ClefMark('bass')(Staff{2})

f(score)
\new Score <<
  \new PianoStaff <<
    \new Staff {
      c'4
      e'4
      d'4
      f'4
    }
    \new Staff {
      \clef "bass"
      g2
      f2
    }
  >>
>>

abjad> for vertical_moment in verticalitytools.iterate_vertical_moments_forward_in_expr(score):
...     vertical_moment
...
VerticalMoment(0, <<2>>)
VerticalMoment(1/4, <<2>>)
VerticalMoment(1/2, <<2>>)
VerticalMoment(3/4, <<2>>)

```

Create vertical moments with the getters and iterators implemented in the `verticalitytools` module.

Vertical moments are immutable.

attack_count

Positive integer number of pitch carriers starting at vertical moment.

components

Read-only tuple of zero or more components happening at vertical moment.

It is always the case that `self.components = self.overlap_components + self.start_components`.

governors

Read-only tuple of one or more containers in which vertical moment is evaluated.

leaves

Read-only tuple of zero or more leaves at vertical moment.

measures

Read-only tuplet of zero or more measures at vertical moment.

next_vertical_moment

Read-only reference to next vertical moment forward in time.

notes

Read-only tuple of zero or more notes at vertical moment.

overlap_components

Read-only tuple of components in vertical moment starting before vertical moment, ordered by score index.

overlap_leaves

Read-only tuple of leaves in vertical moment starting before vertical moment, ordered by score index.

overlap_measures

Read-only tuple of measures in vertical moment starting before vertical moment, ordered by score index.

overlap_notes

Read-only tuple of notes in vertical moment starting before vertical moment, ordered by score index.

prev_vertical_moment

Read-only reference to prev vertical moment backward in time.

prolated_offset

Read-only rational-valued score offset at which vertical moment is evaluated.

start_components

Read-only tuple of components in vertical moment starting with at vertical moment, ordered by score index.

start_leaves

Read-only tuple of leaves in vertical moment starting with vertical moment, ordered by score index.

start_notes

Read-only tuple of notes in vertical moment starting with vertical moment, ordered by score index.

verticalitytools.get_vertical_moment_at_prolated_offset_in_expr

abjad.tools.verticalitytools.get_vertical_moment_at_prolated_offset_in_expr(*governor*,
pro-
lated_offset)

New in version 2.0. Get vertical moment at *prolated_offset* in *governor*:

```
abjad> from abjad.tools import verticalitytools

abjad> score = Score([ ])
abjad> score.append(Staff([tuplettools.FixedDurationTuplet(Duration(4, 8), notetools.make_repeat
abjad> piano_staff = scoretools.PianoStaff([ ])
abjad> piano_staff.append(Staff(notetools.make_repeated_notes(2, Duration(1, 4))))
abjad> piano_staff.append(Staff(notetools.make_repeated_notes(4)))
abjad> contexttools.ClefMark('bass')(piano_staff[1])
ClefMark('bass')(Staff{4})
abjad> score.append(piano_staff)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(lis
abjad> f(score)
\new Score <<
  \new Staff {
    \fraction \times 4/3 {
      d''8
      c''8
      b'8
    }
  }
  \new PianoStaff <<
    \new Staff {
      a'4
      g'4
    }
    \new Staff {
      \clef "bass"
```

```

        f'8
        e'8
        d'8
        c'8
    }
>>
>>
abjad> vertical_moment = verticalitytools.get_vertical_moment_at_prolated_offset_in_expr(piano_s
abjad> vertical_moment.leaves
(Note("a'4"), Note("e'8"))

```

Todo

optimize without full-component traversal.

Changed in version 2.0: renamed `iterate.get_vertical_moment_at_prolated_offset_in()` to `verticalitytools.get_vertical_moment_at_prolated_offset_in_expr()`.

verticalitytools.get_vertical_moment_starting_with_component

`abjad.tools.verticalitytools.get_vertical_moment_starting_with_component` (*expr*, *gov-*
er-
nor=None)

New in version 2.0. When *governor* is none, get vertical moment at `expr._offset.start` in score root of *expr*:

```

abjad> from abjad.tools import verticalitytools

abjad> score = Score([ ])
abjad> score.append(Staff([tuplettools.FixedDurationTuplet(Duration(4, 8), notetools.make_repeat
abjad> piano_staff = scoretools.PianoStaff([ ])
abjad> piano_staff.append(Staff(notetools.make_repeated_notes(2, Duration(1, 4))))
abjad> piano_staff.append(Staff(notetools.make_repeated_notes(4)))
abjad> contexttools.ClefMark('bass')(piano_staff[1])
ClefMark('bass')(Staff{4})
abjad> score.append(piano_staff)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(lis
abjad> f(score)
\new Score <<
  \new Staff {
    \fraction \times 4/3 {
      d''8
      c''8
      b'8
    }
  }
  \new PianoStaff <<
    \new Staff {
      a'4
      g'4
    }
    \new Staff {
      \clef "bass"
      f'8
      e'8
    }
  }

```

```

        d'8
        c'8
    }
>>
>>
abjad> verticalitytools.get_vertical_moment_starting_with_component(piano_staff[1][1])
VerticalMoment(1/8, <<3>>)

```

When *governor* is not none, get vertical moment at `expr._offset.start` in *governor*.

```

abjad> verticalitytools.get_vertical_moment_starting_with_component(piano_staff[1][1], piano_staff[1])
VerticalMoment(1/8, <<2>>)

```

Todo

optimize without full-component traversal.

Changed in version 2.0: renamed `iterate.get_vertical_moment_starting_with()` to `verticalitytools.get_vertical_moment_starting_with_component()`. Changed in version 2.0: renamed `iterate.get_vertical_moment_starting_with_component()` to `verticalitytools.get_vertical_moment_starting_with_component()`.

verticalitytools.iterate_vertical_moments_backward_in_expr

`abjad.tools.verticalitytools.iterate_vertical_moments_backward_in_expr(governor)`

New in version 2.0. Yield vertical moments forward in *governor*:

```

abjad> from abjad.tools import verticalitytools

abjad> score = Score([ ])
abjad> score.append(Staff([tuplettools.FixedDurationTuplet(Duration(4, 8), notetools.make_repeat_note('d', 8))]))
abjad> piano_staff = scoretools.PianoStaff([ ])
abjad> piano_staff.append(Staff(notetools.make_repeated_notes(2, Duration(1, 4))))
abjad> piano_staff.append(Staff(notetools.make_repeated_notes(4)))
abjad> contexttools.ClefMark('bass')(piano_staff[1])
ClefMark('bass')(Staff{4})
abjad> score.append(piano_staff)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(list(score))
abjad> f(score)
\new Score <<
  \new Staff {
    \fraction \times 4/3 {
      d''8
      c''8
      b'8
    }
  }
  \new PianoStaff <<
    \new Staff {
      a'4
      g'4
    }
    \new Staff {
      \clef "bass"
      f'8
      e'8
    }
  }
>>

```

```

        d'8
        c'8
    }
>>
>>
abjad> for vertical_moment in verticalitytools.iterate_vertical_moments_backward_in_expr(score):
...     vertical_moment.leaves
...
(Note("b'8"), Note("g'4"), Note("c'8"))
(Note("b'8"), Note("g'4"), Note("d'8"))
(Note("c''8"), Note("g'4"), Note("d'8"))
(Note("c''8"), Note("a'4"), Note("e'8"))
(Note("d''8"), Note("a'4"), Note("e'8"))
(Note("d''8"), Note("a'4"), Note("f'8"))
abjad> for vertical_moment in verticalitytools.iterate_vertical_moments_backward_in_expr(piano_score):
...     vertical_moment.leaves
...
(Note("g'4"), Note("c'8"))
(Note("g'4"), Note("d'8"))
(Note("a'4"), Note("e'8"))
(Note("a'4"), Note("f'8"))

```

Todo

optimize without multiple full-component traversal.

Changed in version 2.0: renamed `iterate.vertical_moments_backward_in()` to `verticalitytools.iterate_vertical_moments_backward_in_expr()`.
 Changed in version 2.0: renamed `iterate.vertical_moments_backward_in_expr()` to `verticalitytools.iterate_vertical_moments_backward_in_expr()`.

verticalitytools.iterate_vertical_moments_forward_in_expr

`abjad.tools.verticalitytools.iterate_vertical_moments_forward_in_expr(governor)`

New in version 2.0. Yield vertical moments forward in *governor*:

```

abjad> from abjad.tools import verticalitytools

abjad> score = Score([ ])
abjad> score.append(Staff([tuplettools.FixedDurationTuplet(Duration(4, 8), notetools.make_repeat_note("d'8", 4))]))
abjad> piano_staff = scoretools.PianoStaff([ ])
abjad> piano_staff.append(Staff(notetools.make_repeated_notes(2, Duration(1, 4))))
abjad> piano_staff.append(Staff(notetools.make_repeated_notes(4)))
abjad> contexttools.ClefMark('bass')(piano_staff[1])
ClefMark('bass')(Staff{4})
abjad> score.append(piano_staff)
abjad> pitchtools.set_ascending_named_diatonic_pitches_on_nontied_pitched_components_in_expr(list(score))
abjad> f(score)
\new Score <<
  \new Staff {
    \fraction \times 4/3 {
      d''8
      c''8
      b'8
    }
  }

```

```

\new PianoStaff <<
  \new Staff {
    a'4
    g'4
  }
  \new Staff {
    \clef "bass"
    f'8
    e'8
    d'8
    c'8
  }
>>
>>
abjad> for vertical_moment in verticalitytools.iterate_vertical_moments_forward_in_expr(score):
...     vertical_moment.leaves
...
(Note("d''8"), Note("a'4"), Note("f'8"))
(Note("d''8"), Note("a'4"), Note("e'8"))
(Note("c''8"), Note("a'4"), Note("e'8"))
(Note("c''8"), Note("g'4"), Note("d'8"))
(Note("b'8"), Note("g'4"), Note("d'8"))
(Note("b'8"), Note("g'4"), Note("c'8"))
abjad> for vertical_moment in verticalitytools.iterate_vertical_moments_forward_in_expr(piano_staff):
...     vertical_moment.leaves
...
(Note("a'4"), Note("f'8"))
(Note("a'4"), Note("e'8"))
(Note("g'4"), Note("d'8"))
(Note("g'4"), Note("c'8"))

```

Todo

optimize without multiple full-component traversal.

Changed in version 2.0: renamed `iterate.vertical_moments_forward_in()` to `verticalitytools.iterate_vertical_moments_forward_in_expr()`. Changed in version 2.0: renamed `iterate.vertical_moments_forward_in_expr()` to `verticalitytools.iterate_vertical_moments_forward_in_expr()`.

verticalitytools.label_vertical_moments_in_expr_with_chromatic_interval_classes

`abjad.tools.verticalitytools.label_vertical_moments_in_expr_with_chromatic_interval_classes`

New in version 2.0. Label harmonic chromatic interval-classes of every vertical moment in *expr*:

```

abjad> from abjad.tools import verticalitytools

abjad> score = Score(Staff([ ]) * 3)
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]
abjad> score[0].extend(notes)
abjad> contexttools.ClefMark('alto')(score[1])
ClefMark('alto')(Staff{})
abjad> score[1].extend([Note(-5, (1, 4)), Note(-7, (1, 4))])
abjad> contexttools.ClefMark('bass')(score[2])
ClefMark('bass')(Staff{})

```

```

abjad> score[2].append(Note(-24, (1, 2)))
abjad> verticalitytools.label_vertical_moments_in_expr_with_chromatic_interval_classes(score)
abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8 _ \markup { \small { \column { 2 7 } } }
    e'8
    f'8 _ \markup { \small { \column { 5 5 } } }
  }
  \new Staff {
    \clef "alto"
    g4
    f4 _ \markup { \small { \column { 4 5 } } }
  }
  \new Staff {
    \clef "bass"
    c,2 _ \markup { \small { \column { 12 7 } } }
  }
>>

```

Changed in version 2.0: renamed `label.vertical_moment_chromatic_interval_classes()` to `verticalitytools.label_vertical_moments_in_expr_with_chromatic_interval_classes()`.

verticalitytools.label_vertical_moments_in_expr_with_chromatic_intervals

`abjad.tools.verticalitytools.label_vertical_moments_in_expr_with_chromatic_intervals` (*expr*, *markup*)

New in version 2.0. Label harmonic chromatic intervals of every vertical moment in *expr*:

```

abjad> from abjad.tools import verticalitytools

abjad> score = Score(Staff([ ]) * 3)
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]
abjad> score[0].extend(notes)
abjad> contexttools.ClefMark('alto')(score[1])
ClefMark('alto')(Staff{})
abjad> score[1].extend([Note(-5, (1, 4)), Note(-7, (1, 4))])
abjad> contexttools.ClefMark('bass')(score[2])
ClefMark('bass')(Staff{})
abjad> score[2].append(Note(-24, (1, 2)))
abjad> verticalitytools.label_vertical_moments_in_expr_with_chromatic_intervals(score)
abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8 _ \markup { \small { \column { 26 19 } } }
    e'8
    f'8 _ \markup { \small { \column { 29 17 } } }
  }
  \new Staff {
    \clef "alto"
    g4
    f4 _ \markup { \small { \column { 28 17 } } }
  }
  \new Staff {
    \clef "bass"

```

```

        c,2 _ \markup { \small { \column { 24 19 } } }
    }
>>

```

Changed in version 2.0: renamed `label.vertical_moment_chromatic_intervals()` to `verticalitytools.label_vertical_moments_in_expr_with_chromatic_intervals()`.

verticalitytools.label_vertical_moments_in_expr_with_counterpoint_intervals

`abjad.tools.verticalitytools.label_vertical_moments_in_expr_with_counterpoint_intervals` (*expr*, *markup_c*)

New in version 2.0. Label counterpoint interval of every vertical moment in *expr*:

```

abjad> from abjad.tools import verticalitytools

abjad> score = Score(Staff([ ]) * 3)
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]
abjad> score[0].extend(notes)
abjad> contexttools.ClefMark('alto')(score[1])
ClefMark('alto')(Staff{})
abjad> score[1].extend([Note(-5, (1, 4)), Note(-7, (1, 4))])
abjad> contexttools.ClefMark('bass')(score[2])
ClefMark('bass')(Staff{})
abjad> score[2].append(Note(-24, (1, 2)))
abjad> verticalitytools.label_vertical_moments_in_expr_with_counterpoint_intervals(score)
abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8 _ \markup { \small { \column { 2 5 } } }
    e'8
    f'8 _ \markup { \small { \column { 4 4 } } }
  }
  \new Staff {
    \clef "alto"
    g4
    f4 _ \markup { \small { \column { 3 4 } } }
  }
  \new Staff {
    \clef "bass"
    c,2 _ \markup { \small { \column { 8 5 } } }
  }
>>

```

Changed in version 2.0: renamed `label.vertical_moment_counterpoint_intervals()` to `verticalitytools.label_vertical_moments_in_expr_with_counterpoint_intervals()`.

verticalitytools.label_vertical_moments_in_expr_with_diatonic_intervals

`abjad.tools.verticalitytools.label_vertical_moments_in_expr_with_diatonic_intervals` (*expr*, *markup_c*)

New in version 2.0. Label diatonic intervals of every vertical moment in *expr*:

```

abjad> from abjad.tools import verticalitytools

```



```

abjad> score = Score(Staff([ ]) * 3)
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]
abjad> score[0].extend(notes)
abjad> contexttools.ClefMark('alto')(score[1])
ClefMark('alto')(Staff{})
abjad> score[1].extend([Note(-5, (1, 4)), Note(-7, (1, 4))])
abjad> contexttools.ClefMark('bass')(score[2])
ClefMark('bass')(Staff{})
abjad> score[2].append(Note(-24, (1, 2)))
abjad> verticalitytools.label_vertical_moments_in_expr_with_diatonic_intervals(score)
abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8 _ \markup { \small { \column { 16 12 } } }
    e'8
    f'8 _ \markup { \small { \column { 18 11 } } }
  }
  \new Staff {
    \clef "alto"
    g4
    f4 _ \markup { \small { \column { 17 11 } } }
  }
  \new Staff {
    \clef "bass"
    c,2 _ \markup { \small { \column { 15 12 } } }
  }
>>

```

Changed in version 2.0: renamed `label.vertical_moment_diatonic_intervals()` to `verticalitytools.label_vertical_moments_in_expr_with_diatonic_intervals()`.

verticalitytools.label_vertical_moments_in_expr_with_interval_class_vectors

`abjad.tools.verticalitytools.label_vertical_moments_in_expr_with_interval_class_vectors` (*expr*, *man*)

New in version 2.0. Label interval-class vector of every vertical moment in *expr*:

```

abjad> from abjad.tools import verticalitytools

abjad> score = Score(Staff([ ]) * 3)
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]
abjad> score[0].extend(notes)
abjad> contexttools.ClefMark('alto')(score[1])
ClefMark('alto')(Staff{})
abjad> score[1].extend([Note(-5, (1, 4)), Note(-7, (1, 4))])
abjad> contexttools.ClefMark('bass')(score[2])
ClefMark('bass')(Staff{})
abjad> score[2].append(Note(-24, (1, 2)))
abjad> verticalitytools.label_vertical_moments_in_expr_with_interval_class_vectors(score)
abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8 _ \markup { \tiny { 0010020 } }
    e'8
    f'8 _ \markup { \tiny { 1000020 } }
  }
>>

```

```

    }
    \new Staff {
      \clef "alto"
      g4
      f4 _ \markup { \tiny { 0100110 } }
    }
    \new Staff {
      \clef "bass"
      c,2 _ \markup { \tiny { 1000020 } }
    }
  >>

```

Changed in version 2.0: renamed `label.vertical_moment_interval_class_vectors()` to `verticalitytools.label_vertical_moments_in_expr_with_interval_class_vectors()`.

verticalitytools.label_vertical_moments_in_expr_with_numbered_chromatic_pitch_classes

`abjad.tools.verticalitytools.label_vertical_moments_in_expr_with_numbered_chromatic_pitch_classes`

New in version 2.0. Label pitch-classes of every vertical moment in *expr*:

```

abjad> from abjad.tools import verticalitytools

abjad> score = Score(Staff([ ]) * 3)
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]
abjad> score[0].extend(notes)
abjad> contexttools.ClefMark('alto')(score[1])
ClefMark('alto')(Staff{})
abjad> score[1].extend([Note(-5, (1, 4)), Note(-7, (1, 4))])
abjad> contexttools.ClefMark('bass')(score[2])
ClefMark('bass')(Staff{})
abjad> score[2].append(Note(-24, (1, 2)))
abjad> verticalitytools.label_vertical_moments_in_expr_with_numbered_chromatic_pitch_classes(score)
abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8 _ \markup { \small { \column { 7 2 0 } } }
    e'8
    f'8 _ \markup { \small { \column { 5 0 } } }
  }
  \new Staff {
    \clef "alto"
    g4
    f4 _ \markup { \small { \column { 5 4 0 } } }
  }
  \new Staff {
    \clef "bass"
    c,2 _ \markup { \small { \column { 7 0 } } }
  }
>>

```

Changed in version 2.0: renamed `label.vertical_moment_pitch_classes()` to `verticalitytools.label_vertical_moments_in_expr_with_numbered_chromatic_pitch_classes()`.

verticalitytools.label_vertical_moments_in_expr_with_pitch_numbers

abjad.tools.verticalitytools.label_vertical_moments_in_expr_with_pitch_numbers(*expr*, *markup_direction*)

New in version 2.0. Label pitch numbers of every vertical moment in *expr*:

```
abjad> from abjad.tools import verticalitytools

abjad> score = Score(Staff([ ]) * 3)
abjad> notes = [Note("c'8"), Note("d'8"), Note("e'8"), Note("f'8")]
abjad> score[0].extend(notes)
abjad> contexttools.ClefMark('alto')(score[1])
ClefMark('alto')(Staff{})
abjad> score[1].extend([Note(-5, (1, 4)), Note(-7, (1, 4))])
abjad> contexttools.ClefMark('bass')(score[2])
ClefMark('bass')(Staff{})
abjad> score[2].append(Note(-24, (1, 2)))
abjad> verticalitytools.label_vertical_moments_in_expr_with_pitch_numbers(score)
abjad> f(score)
\new Score <<
  \new Staff {
    c'8
    d'8 _ \markup { \small { \column { 2 -5 -24 } } }
    e'8
    f'8 _ \markup { \small { \column { 5 -7 -24 } } }
  }
  \new Staff {
    \clef "alto"
    g4
    f4 _ \markup { \small { \column { 4 -7 -24 } } }
  }
  \new Staff {
    \clef "bass"
    c,2 _ \markup { \small { \column { 0 -5 -24 } } }
  }
>>
```

Changed in version 2.0: renamed `label.vertical_moment_pitch_numbers()` to `verticalitytools.label_vertical_moments_in_expr_with_pitch_numbers()`.

57.1.3 Unstable Abjad composition packages (load manually)

quantizationtools

quantizationtools.QEvent

class abjad.tools.quantizationtools.QEvent

Bases: abjad.core._Immutable._Immutable._Immutable

A utility class for quantization comprising an offset time in milliseconds, and some pitch information: a Number representing a single pitch, None representing silence, or an Iterable comprised of Numbers representing a chord.

QEvents are immutable.

offset

The offset in milliseconds of the event.

value

The pitch information of the event.

quantizationtools.QGrid

class abjad.tools.quantizationtools.QGrid

Bases: abjad.core._Immutable._Immutable._Immutable

Abjad model of a QGrid, a nesting division structure which assists certain quantization algorithms.

QGrids are defined by a list, which must be prime in length, whose members are either Numbers or tuples of Numbers (useful for representing timepoint or pitch information), a [QEvent](#) or tuple of [QEvent](#) objects, or None (representing silence), or other lists which must recursively obey the same rules.

QGrids also have a *next* attribute, representing the downbeat of not “this” *QGrid*, but the next *QGrid* in a list of grids. This is useful as timepoints must often be quantized not to any internal division of a the “current” beat, but to the next beat.

```
abjad> from abjad.tools.quantizationtools import QGrid
abjad> q = QGrid([0, 0, [0, 0]], 0)
```

The values in the grid can be access via subscript, as though the grid were a flat list.

```
abjad> q[0] = 1
abjad> q[2] = 3
abjad> q[4] = 5
abjad> q
QGrid([1, 0, [3, 0]], 5)
```

QGrids are quasi-immutable.

definition

The nested list which defines the *QGrid*’s structure.

```
abjad> from abjad.tools.quantizationtools import QGrid
abjad> q = QGrid([0, 0, [0, 0]], 0)
abjad> q.definition
[0, 0, [0, 0]]
```

Read-only.

find_divisible_indices(*points*)

Given a list of numbers $0 \leq n \leq 1$, return a list of indices in self which countain those points, as though they were segments.

```
abjad> from abjad.tools.quantizationtools import QGrid
abjad> q = QGrid([0, [0, 0]], 0)
abjad> q.offsets
(Offset(0, 1), Offset(1, 2), Offset(3, 4), Offset(1, 1))
abjad> points = [0.1, 0.9]
abjad> q.find_divisible_indices(points)
[0, 2]
```

Returns a list.

find_parentage_of_index(*index*)

Return a tuple of the lengths of each container containing *index*, from the topmost to the bottommost.

```
abjad> from abjad.tools.quantizationtools import QGrid
abjad> q = QGrid([0, [0, [0, 0], 0], 0, 0, 0], 0)
```

```

abjad> q.find_parentage_of_index(0)
(5,)
abjad> q.find_parentage_of_index(1)
(5, 3)
abjad> q.find_parentage_of_index(2)
(5, 3, 2)
abjad> q.find_parentage_of_index(7)
(5,)

```

Returns a tuple.

format_for_beatspan (*beatspan*=*Fraction(1, 4)*)

Return an Abjad container, whose structure mirrors the division structure of the *QGrid*. The values of the items in the *QGrid* have no effect on the output.

```

abjad> from abjad.tools.quantizationtools import QGrid
abjad> q = QGrid([0, [0, 0], 0], 0)
abjad> q.format_for_beatspan()
Tuplet(2/3, [c'8, c'16, c'16, c'8])

```

Returns a *Tuplet* or *Container*, depending on structure.

next

The contents of the final offset in the *QGrid*.

```

abjad> from abjad.tools.quantizationtools import QGrid
abjad> q = QGrid([0, 0, [0, 0]], 0)
abjad> q[-1] = 9
abjad> q
QGrid([0, 0, [0, 0]], 9)
abjad> q.next
9

```

Read-only.

offsets

An ordered tuple of those *Offset* objects generated by the division structure of a *QGrid*.

```

abjad> from abjad.tools.quantizationtools import QGrid
abjad> q = QGrid([0, [0, 0], 0], 0)
abjad> q.offsets
(Offset(0, 1), Offset(1, 3), Offset(1, 2), Offset(2, 3), Offset(1, 1))

```

Read-only.

subdivide_indices (*pairs*)

Given a list of 2-tuples, where for each tuple *t*, *t*[0] is a valid index into self, and *t*[1] is a prime integer greater than 1, return a new *QGrid* with those indices subdivided.

```

abjad> from abjad.tools.quantizationtools import QGrid
abjad> q = QGrid([0, 0], 0)
abjad> q.subdivide_indices([(0, 2), (1, 3)])
QGrid([[0, 0], [0, 0, 0]], 0)

```

Returns a new *QGrid*.

quantizationtools.QGridQuantizer

```
class abjad.tools.quantizationtools.QGridQuantizer (search_tree=None,          beat-
                                                    span=Fraction(1,          4),
                                                    tempo=TempoMark(4, 60), thresh-
                                                    old=None)
```

Bases: abjad.tools.quantizationtools._Quantizer._Quantizer._Quantizer

An Abjad implementation of Paul Nauert's Q-grid quantization algorithm.

Input is converted into timepoints, which are grouped according to which beat - or *beatspan* - they fall in, given a target tempo. Each beatspan is then divided into grids called Q-grids, which are based upon a nesting division structure (similar to nested tuplets). The Q-grids generated for each beatspan are then tested against the timepoints falling within that beatspan, and the grid with least deviation is chosen to represent the rhythmic skeleton for that beat.

```
abjad> from abjad.tools.quantizationtools import QGridQuantizer
abjad> q = QGridQuantizer()
```

QGridQuantizer is immutable, but cheap to instantiate. Various attributes can be defined on instantiation. Please consult the documentation for each attribute respectively, for proper usage.

```
abjad> from abjad.tools.quantizationtools import QGridSearchTree
abjad> target_tempo = contexttools.TempoMark((1, 8), 73)
abjad> beatspan = Fraction(1, 4)
abjad> search_tree = QGridSearchTree({2: {2: None, 3: None}, 5: None})
abjad> threshold = 250
abjad> q = QGridQuantizer(tempo = target_tempo, beatspan = beatspan, search_tree = search_tree,
```

QGridQuantizer can quantize lists of leaves. If the source leaves have no effective tempo, one must be provided with the *tempo* keyword.

```
abjad> q = QGridQuantizer()
abjad> source = Staff("c'4 d'4 e'4. r'8 <c' e' g'>2. <d' g' b'>4")
abjad> source_tempo = contexttools.TempoMark((1, 4), 54)
abjad> result = q(source[:], tempo = source_tempo)
```

```
abjad> q = QGridQuantizer()
abjad> source = Staff("c'4 d'4 e'4. r'8 <c' e' g'>2. <d' g' b'>4")
abjad> t = contexttools.TempoMark((1, 8), 34, target_context = Staff)(source)
abjad> t = contexttools.TempoMark((1, 4), 135, target_context = Staff)(source[3])
abjad> result = q(source[:])
```

QGridQuantizer can quantize lists of millisecond durations. Negative values can be used to indicate silences.

```
abjad> q = QGridQuantizer()
abjad> milliseconds = [100, 120, -133, 500, -1003, 125]
abjad> result = q(milliseconds)
```

QGridQuantizer can also quantize lists of rationals, if a tempo is provided. As with quantizing millisecond durations, negative values can be used to indicate silences.

```
abjad> q = QGridQuantizer()
abjad> rationals = [1, Fraction(1, 2), Fraction(-1, 4), 3, Fraction(-1, 3), 2]
abjad> tempo = contexttools.TempoMark((1, 4), 45)
abjad> result = q(rationals, tempo = tempo)
```

Lastly, *QGridQuantizer* can quantize lists of pairs, where the first value in each pair is a millisecond duration, and the second value is an int or float - indicating a single pitch -, None - indicating silence, or a list of ints or

floats - indicating a chord. This is probably most useful for assisting in the importation of audio analyses from other tools.

```
abjad> q = QGridQuantizer()
abjad> pairs = [(130, 0), (250, 2), (500, None), (1303, [0, 1, 4])]
abjad> result = q(pairs)
```

Todo

Write a documentation chapter on quantization.

Todo

Implement multiprocessing-based QGrid comparison

beatspan

The basic division of the beat for quantization.

Read-only, defaults to *Duration(1, 4)*.

beatspan_ms

The duration of *beatspan* in milliseconds, as determined by *tempo*.

Read-only, defaults to *Duration(1000)*.

search_tree

Reference to a *QGridSearchTree* object, which defines the permissible divisions for each *QGrid* comprising a quantization attempt.

Read-only, defaults to *QGridSearchTree()*.

Please consult the documentation for *QGrid* and *QGridSearchTree* for more information.

tempo

Reference to a *TempoMark*, defining the target tempo for all quantization results.

Read-only, defaults to *TempoMark((1, 4), 60)*.

tempo_lookup

Reference to a *QGridTempoLookup* object, a utility class for mapping rational divisions of a beat into milliseconds.

Read-only.

threshold

Millisecond duration, which if specified at instantiation will be used to call the quantizer's *QGridSearchTree*'s *prune()* method, in order to generate a pruned search tree for the quantizer, instead of either the user-provided or default search trees.

Read-only, defaults to None. See the documentation for *QGridSearchTree* for more information on pruning.

quantizationtools.QGridSearchTree

class abjad.tools.quantizationtools.*QGridSearchTree*

Bases: abjad.core._Immutable._Immutable._Immutable, abjad.core._ImmutableDictionary._Immutable

A utility class for defining the permissible divisions of a collection of *QGrid* objects.

The search tree is defined by a nested dictionary structure, whose keys must be prime integers, and whose values must be `None` (indicating no further possible divisions) or another dictionary following the same rules.

```
abjad> from abjad.tools.quantizationtools import QGridSearchTree
```

For example, In the following tree, the beat may be divided into 2 or into 5. If divided into 2, it may be divided again into 2 or into 3.

```
abjad> search_tree = QGridSearchTree({2: {2: None, 3: None}, 5: None})
```

Return a new *QGridSearchTree*.

find_subtree_divisibility (*parentage*)

Given a parentage signature, defining some subtree of a *QGridSearchTree*, return a tuple of permitted divisions of that subtree.

```
abjad> from abjad.tools.quantizationtools import QGridSearchTree
abjad> qst = QGridSearchTree({2: {2: None, 3: {7: None, 11: None}}, 5: None})
abjad> qst.find_subtree_divisibility((2,))
(2, 3)
abjad> qst.find_subtree_divisibility((2, 2))
()
abjad> qst.find_subtree_divisibility((2, 3))
(7, 11)
abjad> qst.find_subtree_divisibility((2, 3, 7))
()
```

Returns a tuple.

offsets

An ordered tuple of all *Offset* objects which those *QGrid* objects governed by a specific *QGridSearchTree* can contain.

```
abjad> from abjad.tools.quantizationtools import QGridSearchTree
abjad> qst = QGridSearchTree({2: {3: None}})
abjad> qst.offsets
(Offset(0, 1), Offset(1, 6), Offset(1, 3), Offset(1, 2), Offset(2, 3), Offset(5, 6), Offset(
```

Returns a tuple.

prune (*beatspan, tempo, threshold*)

Prune those subtrees of a *QGridSearchTree* whose divisions in milliseconds, given *beatspan* and *tempo*, would be less than *threshold*.

This allows a composer to specify the maximum speed any quantization operation will permit.

```
abjad> from abjad.tools.quantizationtools import QGridSearchTree
abjad> qst = QGridSearchTree({2: {2: {2: {2: None}}}}})
abjad> beatspan = Fraction(1, 4)
abjad> tempo = contexttools.TempoMark((1, 4), 60)
abjad> qst.prune(beatspan, tempo, 100)
{2: {2: {2: None}}}
abjad> qst.prune(beatspan, tempo, 200)
{2: {2: None}}
abjad> qst.prune(beatspan, tempo, 400)
{2: None}
```

Returns a new *QGridSearchTree*.

quantizationtools.QGridTempoLookup

class abjad.tools.quantizationtools.**QGridTempoLookup** (*offsets, beatspan, tempo*)

Bases: abjad.core._Immutable._Immutable._Immutable, abjad.core._ImmutableDictionary._Immutable

A utility class for matching fractional offsets within a beat to their tempo-scaled (real-time) millisecond values.

QGridTempoLookup objects are immutable.

beatspan

The duration which the *Offset* objects comprising the keys of the *QGridTempoLookup* are offsets into.

tempo

The *TempoMark* used to generate the lookup.

quantizationtools.is_valid_beatspan

abjad.tools.quantizationtools.**is_valid_beatspan** (*beatspan*)

True if *beatspan* is a valid beatspan.

- 1.A beatspan must be an int or Fraction.
- 2.It must be a binary rational.
- 3.If it is greater than zero, it must be a power of two.
- 4.If it is less than zero, it must be Fraction, whose numerator is 1 and whose denominator is a power of two.

quantizationtools.millisecond_pitch_pairs_to_q_events

abjad.tools.quantizationtools.**millisecond_pitch_pairs_to_q_events** (*pairs*)

Convert a list of pairs of millisecond durations and pitches to a list of *QEvent* instances.

Pitch values must be one of the following:

- 1.A single chromatic pitch number, indicating a note,
- 2.None, indicating a silence, or
- 3.An iterable of chromatic pitch numbers, indicating a chord.

```

abjad> from abjad.tools.quantizationtools import millisecond_pitch_pairs_to_q_events
abjad> durations = [1001, 503, 230, 1340]
abjad> pitches = [None, 0, (1, 2, 3), 4.5]
abjad> pairs = zip(durations, pitches)
abjad> millisecond_pitch_pairs_to_q_events(pairs)
[QEvent(Offset(0, 1), None), QEvent(Offset(1001, 1), 0), QEvent(Offset(1504, 1), (1, 2, 3)), QEvent(Offset(2007, 1), 4.5)]

```

Return a list of *QEvent* instances.

quantizationtools.milliseconds_to_q_events

abjad.tools.quantizationtools.**milliseconds_to_q_events** (*milliseconds*)

Convert a list of millisecond durations to a list of *QEvent* objects.

Negative duration values can be used to indicate silence. Any resulting pitched *QEvent* objects will default to using middle-C.

```
abjad> from abjad.tools.quantizationtools import milliseconds_to_q_events
abjad> durations = [100, -250, 500]
abjad> milliseconds_to_q_events(durations)
[QEvent(Offset(0, 1), 0), QEvent(Offset(100, 1), None), QEvent(Offset(350, 1), 0), QEvent(Offset(
```

Return a list of `QEvent` objects.

quantizationtools.tempo_scaled_leaves_to_q_events

`abjad.tools.quantizationtools.tempo_scaled_leaves_to_q_events` (*leaves*,
tempo=None)

Convert *leaves* to a list of `QEvent` objects. If the leaves have no effective tempo, *tempo* must be a `TempoMark`.

```
abjad> from abjad.tools.quantizationtools import tempo_scaled_leaves_to_q_events
abjad> source = Staff("c'4 r'4. e'8 <g' b' d'' fs''>2")
abjad> source_tempo = contexttools.TempoMark((1, 4), 55)
abjad> tempo_scaled_leaves_to_q_events(source[:], tempo = source_tempo)
[QEvent(Offset(0, 1), 0), QEvent(Offset(12000, 11), None), QEvent(Offset(30000, 11), 4), QEvent(
```

Return a list of `QEvent` objects.

quantizationtools.tempo_scaled_rational_to_milliseconds

`abjad.tools.quantizationtools.tempo_scaled_rational_to_milliseconds` (*rational*,
tempo)

Return the millisecond value of *rational* at *tempo*.

```
abjad> from abjad.tools.quantizationtools import tempo_scaled_rational_to_milliseconds
abjad> tempo = contexttools.TempoMark((1, 4), 60)
abjad> tempo_scaled_rational_to_milliseconds(Fraction(1, 4), tempo)
Duration(1000, 1)
```

Return a `Duration`.

quantizationtools.tempo_scaled_rationals_to_q_events

`abjad.tools.quantizationtools.tempo_scaled_rationals_to_q_events` (*durations*,
tempo)

Convert a list of rational durations to a list of `QEvent` objects.

Negative duration values can be used to indicate silence. Any resulting pitched `QEvent` objects will default to using middle-C.

```
abjad> from abjad.tools.quantizationtools import tempo_scaled_rationals_to_q_events
abjad> durations = [Duration(-1, 2), Duration(1, 4), Duration(1, 6)]
abjad> tempo = contexttools.TempoMark((1, 4), 55)
abjad> tempo_scaled_rationals_to_q_events(durations, tempo)
[QEvent(Offset(0, 1), None), QEvent(Offset(24000, 11), 0), QEvent(Offset(36000, 11), 0), QEvent(
```

Return a list of `QEvent` objects.

BIBLIOGRAPHY

- [Adan2006] Víctor Adán. Music <-> Geometry <-> Meta-Music. Draft February 12, 2006.
- [AgonHaddadAssayag2002] Carlos Agon, Karim Haddad & Gerard Assayag. Représentation et rendu de structures rythmiques. Journées d'Informatique Musicale, 9th ed., Marseille, 29 - 31 May 2002.
- [Alegant1993] Brian Alegant. The seventy-seven partitions of the aggregate: Analytical and theoretical implications. Doctoral Dissertation. The University of Rochester, Eastman School of Music. 1993.
- [Ariza2005] Christopher Ariza. An Open Design for Computer-Aided Algorithmic Music Composition: athenaCL. Dissertation.com, Boca Raton. 2005.
- [BacaAdan2007] Trevor Bača & Víctor Adán. Cuepatlahto and Lascaux: two approaches to the formalized control of musical score. Draft June 7, 2007.
- [BressonAgonAssayag2008] Jean Bresson, Carlos Agon, Gérard Assayag. The OM Composer's Book 2. Éditions Delatour, Paris. 2008
- [Carter2002] Eliot Carter. Harmony Book. Nicholas Hopkins and John F. Link, eds. Carl Fischer, New York. 2002.
- [Haddad] Karim Haddad. Le Temps comme Territoire: pour une géographie temporelle.
- [Kampela1998] Arthur Kampela. Uma Faca Só Lâmina. Doctoral Dissertation. Columbia University, NY, NY. 1998.
- [Malt2008] Mikhaïl Malt. Some Considerations on Brian Ferneyhough's Musical Language Through His Use of CAC – Part I: Time and Rhythmic Structures. In [BressonAgonAssayag2008].
- [Morris1987] Robert Morris. Composition with Pitch-Classes. Yale University Press, New Haven. 1987.
- [Nauert1997] Paul Nauert. Timespan Formation in Nonmetric, Posttonal Music. Doctoral Dissertation. Columbia University, NY, NY. 1997.
- [NienhuysNieuwenhuizen2003] Han-Wen Nienhuys & Jan Nieuwenhuizen. Lilypond: A system for automated music engraving. Proceedings of the XIV Colloquium on Musical Informatics. Firenze, Italy. May 8 - 10, 2003.
- [Ross1987] Ted Ross. Teach Yourself The Art of Music Engraving and Processing. Hansen House, Miami Beach. 1987.
- [Selfridge-Field1997] Eleanor Selfridge-Field, ed. Beyond MIDI: The Handbook of Musical Codes. The MIT Press. Cambridge, Massachusetts. 1997.
- [Valle] Andrea Valle. GeoGraphy: Notazione musicale e composizione algoritmica. Centro Interdipartimentale di Ricerca sulla Multimedialità e l'Audiovisivo. Università degli Studi di Torino.
- [WulfsonBarrettWinter] Harris Wulfson, G. Douglas Barrett & Michael Winter. Automatic Notation Generators.

INDEX

A

- AbjadRevisionToken (class in abjad.tools.lilyfiletools), 370
- accidental (abjad.tools.tonalitytools.ScaleDegree attribute), 712
- Accidental (class in abjad.tools.pitchtools), 437
- Accordion (class in abjad.tools.instrumenttools), 321
- add_artificial_harmonic_to_note() (in module abjad.tools.notetools), 427
- add_double_bar_to_end_of_score() (in module abjad.tools.scoretools), 508
- add_markup_to_end_of_score() (in module abjad.tools.scoretools), 508
- add_or_remove_tie_chain_notes_to_achieve_scaled_written_duration() (in module abjad.tools.tietools), 556
- add_or_remove_tie_chain_notes_to_achieve_written_duration() (in module abjad.tools.tietools), 556
- all_are_assignable_integers() (in module abjad.tools.seqttools), 660
- all_are_chromatic_pitch_class_name_octave_number_pairs() (in module abjad.tools.pitchtools), 464
- all_are_components() (in module abjad.tools.componenttools), 209
- all_are_components_in_same_parent() (in module abjad.tools.componenttools), 209
- all_are_components_in_same_score() (in module abjad.tools.componenttools), 210
- all_are_components_in_same_thread() (in module abjad.tools.componenttools), 210
- all_are_components_scalable_by_multiplier() (in module abjad.tools.componenttools), 210
- all_are_contiguous_components() (in module abjad.tools.componenttools), 211
- all_are_contiguous_components_in_same_parent() (in module abjad.tools.componenttools), 211
- all_are_contiguous_components_in_same_score() (in module abjad.tools.componenttools), 211
- all_are_contiguous_components_in_same_thread() (in module abjad.tools.componenttools), 212
- all_are_equal() (in module abjad.tools.seqttools), 660
- all_are_integer_equivalent_numbers() (in module abjad.tools.seqttools), 661
- all_are_intervals_or_trees_or_empty() (in module abjad.tools.intervaltreetools), 606
- all_are_nonnegative_integer_equivalent_numbers() (in module abjad.tools.seqttools), 661
- all_are_nonnegative_integer_powers_of_two() (in module abjad.tools.seqttools), 661
- all_are_nonnegative_integers() (in module abjad.tools.seqttools), 662
- all_are_numbers() (in module abjad.tools.seqttools), 662
- all_are_orphan_components() (in module abjad.tools.componenttools), 212
- all_are_positive_integer_equivalent_numbers() (in module abjad.tools.seqttools), 662
- all_are_positive_integers() (in module abjad.tools.seqttools), 662
- all_are_thread_contiguous_components() (in module abjad.tools.componenttools), 212
- all_are_unequal() (in module abjad.tools.seqttools), 663
- all_intervals_are_contiguous() (in module abjad.tools.intervaltreetools), 606
- all_intervals_are_nonoverlapping() (in module abjad.tools.intervaltreetools), 606
- alpha() (abjad.tools.pitchtools.NumberedChromaticPitchClassSegment method), 458
- alphabetic_string (abjad.tools.pitchtools.Accidental attribute), 437
- AltoFlute (class in abjad.tools.instrumenttools), 322
- analyze_chord() (in module abjad.tools.tonalitytools), 713
- analyze_incomplete_chord() (in module abjad.tools.tonalitytools), 713
- analyze_incomplete_tonal_function() (in module abjad.tools.tonalitytools), 713
- analyze_tonal_function() (in module abjad.tools.tonalitytools), 714
- Annotation (class in abjad.tools.marktools), 374
- AnonymousMeasure (class in abjad.tools.measuretools), 393
- append() (abjad.tools.chordtools.Chord method), 201

- ul style="list-style-type: none; padding-left: 0;">
- append() (abjad.tools.containertools.Container method), 264
- append() (abjad.tools.pitcharraytools.PitchArrayColumn method), 652
- append() (abjad.tools.pitcharraytools.PitchArrayRow method), 653
- append() (abjad.tools.spannertools.Spanner method), 532
- append_column() (abjad.tools.pitcharraytools.PitchArray method), 649
- append_left() (abjad.tools.spannertools.Spanner method), 532
- append_row() (abjad.tools.pitcharraytools.PitchArray method), 649
- append Spacer skip to underfull measure() (in module abjad.tools.measuretools), 396
- append Spacer skips to underfull measures in expr() (in module abjad.tools.measuretools), 397
- apply_accidental() (abjad.tools.pitchtools.NamedChromaticPitchClass method), 450
- apply_accidental() (abjad.tools.pitchtools.NumberedChromaticPitch method), 456
- apply_accidental() (abjad.tools.pitchtools.NumberedChromaticPitchClass method), 457
- apply_accidental() (abjad.tools.tonalitytools.ScaleDegree method), 712
- apply_accidental_to_named_chromatic_pitch() (in module abjad.tools.pitchtools), 464
- apply_articulations_to_notes_and_chords_in_expr() (in module abjad.tools.marktools), 379
- apply_beam_spanner_to_measure() (in module abjad.tools.measuretools), 397
- apply_beam_spanners_to_measures_in_expr() (in module abjad.tools.measuretools), 398
- apply_complex_beam_spanner_to_measure() (in module abjad.tools.measuretools), 399
- apply_complex_beam_spanners_to_measures_in_expr() (in module abjad.tools.measuretools), 399
- apply_durated_complex_beam_spanner_to_measures() (in module abjad.tools.measuretools), 400
- apply_full_measure_tuplets_to_contents_of_measures_in_expr() (in module abjad.tools.measuretools), 401
- apply_octavation_spanner_to_pitched_components() (in module abjad.tools.pitchtools), 464
- apply_pitches() (abjad.tools.pitcharraytools.PitchArrayRow method), 653
- apply_pitches_by_row() (abjad.tools.pitcharraytools.PitchArray method), 649
- apply_tie_spanner_to_leaf_pair() (in module abjad.tools.tietools), 557
- are_components_in_same_tie_spanner() (in module abjad.tools.tietools), 557
- are_scalar_notes() (in module abjad.tools.tonalitytools), 714
- are_stepwise_ascending_notes() (in module abjad.tools.tonalitytools), 714
- are_stepwise_descending_notes() (in module abjad.tools.tonalitytools), 715
- are_stepwise_notes() (in module abjad.tools.tonalitytools), 715
- arg (abjad.tools.schemetools.SchemeBoolean attribute), 502
- args (abjad.tools.markuptools.MarkupCommand attribute), 389
- arithmetic_mean() (in module abjad.tools.mathtools), 627
- arpeggiate_chord() (in module abjad.tools.chordtools), 203
- Articulation (class in abjad.tools.marktools), 375
- assignable_rational_to_dot_count() (in module abjad.tools.durtools), 587
- assignable_rational_to_lilypond_duration_string() (in module abjad.tools.durtools), 587
- attach_mark() (abjad.tools.contexttools.ContextMark method), 298
- attach_mark() (abjad.tools.marktools.Mark method), 378
- attack_count (abjad.tools.verticalitytools.VerticalMoment attribute), 719
- ## B
- bass (abjad.tools.tonalitytools.ChordClass attribute), 709
 - bass_scale_degree (abjad.tools.tonalitytools.TonalFunction attribute), 712
 - BassClarinet (class in abjad.tools.instrumenttools), 322
 - BassFlute (class in abjad.tools.instrumenttools), 323
 - Bassoon (class in abjad.tools.instrumenttools), 323
 - beam_bottommost_tuplets_in_expr() (in module abjad.tools.tuplettools), 571
 - BeamSpanner (class in abjad.tools.spannertools), 516
 - beatspan (abjad.tools.quantizationtools.QGridQuantizer attribute), 733
 - beatspan (abjad.tools.quantizationtools.QGridTempoLookup attribute), 735
 - beatspan_ms (abjad.tools.quantizationtools.QGridQuantizer attribute), 733
 - binomial_coefficient() (in module abjad.tools.mathtools), 628
 - BookBlock (class in abjad.tools.lilyfiletools), 370
 - BookpartBlock (class in abjad.tools.lilyfiletools), 370
 - BoundedInterval (class in abjad.tools.intervalreetools), 604
 - bounds (abjad.tools.intervalreetools.IntervalTree attribute), 605
 - BracketSpanner (class in abjad.tools.spannertools), 516

C

- `calculate_density_of_attacks_in_interval()` (in module `abjad.tools.intervaltreetools`), 606
- `calculate_density_of_releases_in_interval()` (in module `abjad.tools.intervaltreetools`), 606
- `calculate_depth_centroid_of_intervals()` (in module `abjad.tools.intervaltreetools`), 606
- `calculate_depth_centroid_of_intervals_in_interval()` (in module `abjad.tools.intervaltreetools`), 607
- `calculate_depth_density_of_intervals()` (in module `abjad.tools.intervaltreetools`), 607
- `calculate_depth_density_of_intervals_in_interval()` (in module `abjad.tools.intervaltreetools`), 607
- `calculate_harmonic_chromatic_interval_class_from_pitch_carrier_to_pitch_carrier()` (in module `abjad.tools.pitchtools`), 465
- `calculate_harmonic_chromatic_interval_from_pitch_carrier_to_pitch_carrier()` (in module `abjad.tools.pitchtools`), 465
- `calculate_harmonic_counterpoint_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch()` (in module `abjad.tools.pitchtools`), 465
- `calculate_harmonic_counterpoint_interval_from_named_chromatic_pitch_to_named_chromatic_pitch()` (in module `abjad.tools.pitchtools`), 465
- `calculate_harmonic_diatonic_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch()` (in module `abjad.tools.pitchtools`), 465
- `calculate_harmonic_diatonic_interval_from_named_chromatic_pitch_to_named_chromatic_pitch()` (in module `abjad.tools.pitchtools`), 466
- `calculate_mean_attack_of_intervals()` (in module `abjad.tools.intervaltreetools`), 607
- `calculate_mean_release_of_intervals()` (in module `abjad.tools.intervaltreetools`), 607
- `calculate_melodic_chromatic_interval_class_from_pitch_carrier_to_pitch_carrier()` (in module `abjad.tools.pitchtools`), 466
- `calculate_melodic_chromatic_interval_from_pitch_carrier_to_pitch_carrier()` (in module `abjad.tools.pitchtools`), 466
- `calculate_melodic_counterpoint_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch()` (in module `abjad.tools.pitchtools`), 466
- `calculate_melodic_counterpoint_interval_from_named_chromatic_pitch_to_named_chromatic_pitch()` (in module `abjad.tools.pitchtools`), 466
- `calculate_melodic_diatonic_interval_class_from_named_chromatic_pitch_to_named_chromatic_pitch()` (in module `abjad.tools.pitchtools`), 467
- `calculate_melodic_diatonic_interval_from_named_chromatic_pitch_to_named_chromatic_pitch()` (in module `abjad.tools.pitchtools`), 467
- `calculate_min_mean_and_max_depth_of_intervals()` (in module `abjad.tools.intervaltreetools`), 608
- `calculate_min_mean_and_max_magnitude_of_intervals()` (in module `abjad.tools.intervaltreetools`), 608
- `calculate_sustain_centroid_of_intervals()` (in module `abjad.tools.intervaltreetools`), 608
- `cardinality` (`abjad.tools.tonalitytools.ChordClass` attribute), 709
- `cardinality` (`abjad.tools.tonalitytools.ChordQualityIndicator` attribute), 710
- `cell_tokens` (`abjad.tools.pitcharraytools.PitchArrayColumn` attribute), 652
- `cell_tokens` (`abjad.tools.pitcharraytools.PitchArrayRow` attribute), 653
- `cell_tokens_by_row` (`abjad.tools.pitcharraytools.PitchArray` attribute), 649
- `cell_widths` (`abjad.tools.pitcharraytools.PitchArrayColumn` attribute), 652
- `cell_widths` (`abjad.tools.pitcharraytools.PitchArrayRow` attribute), 653
- `cell_widths_by_row` (`abjad.tools.pitcharraytools.PitchArray` attribute), 649
- `Cello` (class in `abjad.tools.instrumenttools`), 324
- `calls` (`abjad.tools.pitcharraytools.PitchArray` attribute), 649
- `calls` (`abjad.tools.pitcharraytools.PitchArrayColumn` attribute), 652
- `calls` (`abjad.tools.pitcharraytools.PitchArrayRow` attribute), 653
- `centroid` (`abjad.tools.intervaltreetools.BoundedInterval` attribute), 604
- `change_augmented_tuplets_in_expr_to_diminished()` (in module `abjad.tools.tuplettools`), 571
- `change_defective_chord_to_note_or_rest()` (in module `abjad.tools.chordtools`), 204
- `change_diminished_tuplets_in_expr_to_augmented()` (in module `abjad.tools.tuplettools`), 572
- `change_written_leaf_duration_and_preserve_preprolated_leaf_duration()` (in module `abjad.tools.leaftools`), 338
- `Chord` (class in `abjad.tools.chordtools`), 201
- `chord_class_cardinality_to_extent()` (in module `abjad.tools.tonalitytools`), 715
- `chord_class_extent_to_cardinality()` (in module `abjad.tools.tonalitytools`), 715
- `chord_class_extent_to_named_chromatic_pitch()` (in module `abjad.tools.tonalitytools`), 716
- `chord_class_extent_to_extent_name()` (in module `abjad.tools.tonalitytools`), 716
- `chord_name_string` (`abjad.tools.tonalitytools.SuspensionIndicator` attribute), 712
- `ChordClass` (class in `abjad.tools.tonalitytools`), 709
- `ChordQualityIndicator` (class in `abjad.tools.tonalitytools`), 710
- `chromatic_interval_number` (`abjad.tools.pitchtools.MelodicChromaticInterval` attribute), 443
- `chromatic_pitch_class_name` (`abjad.tools.pitchtools.NamedChromaticPitch` attribute), 447
- `chromatic_pitch_class_name` (`abjad.tools.pitchtools.NamedDiatonicPitch` attribute), 454
- `chromatic_pitch_class_name_to_chromatic_pitch_class_number()` (in module `abjad.tools.pitchtools`), 467

chromatic_pitch_class_name_to_diatonic_pitch_class_name() (in module abjad.tools.pitchtools), 467

chromatic_pitch_class_name_to_diatonic_pitch_class_name_alphabetic_accidental_abbreviation_pair() (in module abjad.tools.pitchtools), 467

chromatic_pitch_class_number (abjad.tools.pitchtools.NamedChromaticPitch attribute), 448

chromatic_pitch_class_number (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 454

chromatic_pitch_class_number_to_chromatic_pitch_class_name() (in module abjad.tools.pitchtools), 468

chromatic_pitch_class_number_to_chromatic_pitch_class_name_with flats() (in module abjad.tools.pitchtools), 468

chromatic_pitch_class_number_to_chromatic_pitch_class_name_with sharps() (in module abjad.tools.pitchtools), 469

chromatic_pitch_class_number_to_diatonic_pitch_class_number() (in module abjad.tools.pitchtools), 469

chromatic_pitch_class_numbers (abjad.tools.pitchtools.NumberedChromaticPitchClassVector attribute), 461

chromatic_pitch_name (abjad.tools.pitchtools.NamedChromaticPitch attribute), 448

chromatic_pitch_name (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 454

chromatic_pitch_name_to_chromatic_pitch_class_name() (in module abjad.tools.pitchtools), 469

chromatic_pitch_name_to_chromatic_pitch_class_number() (in module abjad.tools.pitchtools), 469

chromatic_pitch_name_to_chromatic_pitch_number() (in module abjad.tools.pitchtools), 470

chromatic_pitch_name_to_diatonic_pitch_class_name() (in module abjad.tools.pitchtools), 470

chromatic_pitch_name_to_diatonic_pitch_class_number() (in module abjad.tools.pitchtools), 470

chromatic_pitch_name_to_diatonic_pitch_name() (in module abjad.tools.pitchtools), 470

chromatic_pitch_name_to_diatonic_pitch_number() (in module abjad.tools.pitchtools), 470

chromatic_pitch_name_to_octave_number() (in module abjad.tools.pitchtools), 470

chromatic_pitch_names_string_to_named_chromatic_pitch_list() (in module abjad.tools.pitchtools), 471

chromatic_pitch_number (abjad.tools.pitchtools.NamedChromaticPitch attribute), 448

chromatic_pitch_number (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 454

chromatic_pitch_number (abjad.tools.pitchtools.NumberedChromaticPitch attribute), 456

chromatic_pitch_number (abjad.tools.pitchtools.NumberedDiatonicPitch attribute), 461

chromatic_pitch_number_and_accidental_semitones_to_octave_number() (in module abjad.tools.pitchtools), 471

chromatic_pitch_number_diatonic_pitch_class_name_to_alphabetic_accidental_abbreviation_pair() (in module abjad.tools.pitchtools), 471

chromatic_pitch_number_to_chromatic_pitch_class_number() (in module abjad.tools.pitchtools), 471

chromatic_pitch_number_to_chromatic_pitch_name() (in module abjad.tools.pitchtools), 472

chromatic_pitch_number_to_diatonic_pitch_class_name_alphabetic_accidental_abbreviation_pair() (in module abjad.tools.pitchtools), 472

chromatic_pitch_number_to_diatonic_pitch_class_number() (in module abjad.tools.pitchtools), 472

chromatic_pitch_number_to_diatonic_pitch_number() (in module abjad.tools.pitchtools), 472

chromatic_pitch_number_to_octave_number() (in module abjad.tools.pitchtools), 472

chromatic_pitch_numbers (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452

chromatic_pitch_numbers (abjad.tools.pitchtools.NamedChromaticPitchSet attribute), 453

chromatic_pitch_numbers (abjad.tools.pitchtools.NamedChromaticPitchVector attribute), 453

Clarinet (class in abjad.tools.instrumenttools), 324

clear() (abjad.tools.chordtools.Chord method), 201

clear() (abjad.tools.spannertools.Spanner method), 532

clear_terminal() (in module abjad.tools.iotools), 617

clef_and_staff_position_number_to_named_chromatic_pitch() (in module abjad.tools.pitchtools), 473

clef_name_string (abjad.tools.contexttools.ClefMark attribute), 297

ClefMark (class in abjad.tools.contexttools), 296

clip_interval_magnitudes_to_range() (in module abjad.tools.intervaltreetools), 608

Cluster (class in abjad.tools.containertools), 263

color_chord_note_heads_by_pitch_class_color_map() (in module abjad.tools.chordtools), 205

color_contents_of_container() (in module abjad.tools.containertools), 267

color_leaf() (in module abjad.tools.leaftools), 338

color_leaves_in_expr() (in module abjad.tools.leaftools), 339

color_measure() (in module abjad.tools.measuretools), 402

color_name (abjad.tools.schemetools.SchemeColor attribute), 502

color_nonbinary_measures_in_expr() (in module abjad.tools.measuretools), 402

`color_note_head_by_numbered_chromatic_pitch_class_color` (in module `abjad.tools.nottetools`), 428

`colors` (`abjad.tools.pitchtools.NumberedChromaticPitchClassColorMap` attribute), 457

`column_index` (`abjad.tools.pitcharraytools.PitchArrayColumn` attribute), 652

`column_indices` (`abjad.tools.pitcharraytools.PitchArrayCell` attribute), 651

`columns` (`abjad.tools.pitcharraytools.PitchArray` attribute), 649

`columns` (`abjad.tools.seqtools.CyclicMatrix` attribute), 658

`columns` (`abjad.tools.seqtools.Matrix` attribute), 659

`combine_markup_commands()` (in module `abjad.tools.markuptools`), 390

`command` (`abjad.tools.markuptools.MarkupCommand` attribute), 389

`command_name_string` (`abjad.tools.marktools.LilyPondCommandMark` attribute), 377

`Comment` (class in `abjad.tools.marktools`), 376

`comment_measures_in_container_with_measure_numbers()` (in module `abjad.tools.measuretools`), 403

`ComplexBeamSpanner` (class in `abjad.tools.spannertools`), 517

`component_to_parentage_signature()` (in module `abjad.tools.componenttools`), 213

`component_to_pitch_and_rhythm_skeleton()` (in module `abjad.tools.componenttools`), 213

`component_to_score_depth()` (in module `abjad.tools.componenttools`), 214

`component_to_score_index()` (in module `abjad.tools.componenttools`), 214

`component_to_score_root()` (in module `abjad.tools.componenttools`), 215

`component_to_thread_signature()` (in module `abjad.tools.threadtools`), 705

`component_to_tuplet_depth()` (in module `abjad.tools.componenttools`), 215

`components` (`abjad.tools.spannertools.Spanner` attribute), 533

`components` (`abjad.tools.verticalitytools.VerticalMoment` attribute), 719

`composite_dynamic_name_to_steady_state_dynamic_name()` (`abjad.tools.contexttools.DynamicMark` static method), 299

`compute_depth_of_intervals()` (in module `abjad.tools.intervaltreetools`), 608

`compute_depth_of_intervals_in_interval()` (in module `abjad.tools.intervaltreetools`), 608

`compute_logical_and_of_intervals()` (in module `abjad.tools.intervaltreetools`), 609

`compute_logical_and_of_intervals_in_interval()` (in module `abjad.tools.intervaltreetools`), 609

`compute_logical_not_of_intervals()` (in module `abjad.tools.intervaltreetools`), 609

`compute_logical_not_of_intervals_in_interval()` (in module `abjad.tools.intervaltreetools`), 609

`compute_logical_or_of_intervals()` (in module `abjad.tools.intervaltreetools`), 609

`compute_logical_or_of_intervals_in_interval()` (in module `abjad.tools.intervaltreetools`), 610

`compute_logical_xor_of_intervals()` (in module `abjad.tools.intervaltreetools`), 610

`compute_logical_xor_of_intervals_in_interval()` (in module `abjad.tools.intervaltreetools`), 610

`concatenate_pitch_arrays()` (in module `abjad.tools.pitcharraytools`), 654

`concatenate_trees()` (in module `abjad.tools.intervaltreetools`), 610

`Container` (class in `abjad.tools.containertools`), 263

`contents_duration` (`abjad.tools.containertools.Container` attribute), 264

`contents_string` (`abjad.tools.marktools.Comment` attribute), 377

`ContextMark` (class in `abjad.tools.contexttools`), 297

`contexts` (`abjad.tools.lilyfiletools.LayoutBlock` attribute), 371

`Contrabass` (class in `abjad.tools.instrumenttools`), 325

`ContrabassFlute` (class in `abjad.tools.instrumenttools`), 325

`Contrabassoon` (class in `abjad.tools.instrumenttools`), 326

`copy_and_partition_governed_component_subtree_by_leaf_counts()` (in module `abjad.tools.componenttools`), 216

`copy_components_and_covered_spanners()` (in module `abjad.tools.componenttools`), 217

`copy_components_and_fracture_crossing_spanners()` (in module `abjad.tools.componenttools`), 218

`copy_components_and_immediate_parent_of_first_component()` (in module `abjad.tools.componenttools`), 219

`copy_components_and_remove_all_spanners()` (in module `abjad.tools.componenttools`), 221

`copy_governed_component_subtree_by_leaf_range()` (in module `abjad.tools.componenttools`), 222

`copy_governed_component_subtree_from_prolated_offset_to()` (in module `abjad.tools.componenttools`), 223

`copy_subarray()` (`abjad.tools.pitcharraytools.PitchArray` method), 649

`copy_subrow()` (`abjad.tools.pitcharraytools.PitchArrayRow` method), 653

`copy_written_duration_and_multiplier_from_leaf_to_leaf()` (in module `abjad.tools.leaftools`), 340

`count_length_two_runs_in_sequence()` (in module `abjad.tools.seqtools`), 663

`CrescendoSpanner` (class in `abjad.tools.spannertools`), 519

`cumulative_products()` (in module `abjad.tools.mathtools`), 628

- `cumulative_signed_weights()` (in module `abjad.tools.mathtools`), 628
 - `cumulative_sums()` (in module `abjad.tools.mathtools`), 629
 - `cumulative_sums_zero()` (in module `abjad.tools.mathtools`), 629
 - `cumulative_sums_zero_pairwise()` (in module `abjad.tools.mathtools`), 629
 - `cut_component_at_prolated_duration()` (in module `abjad.tools.componenttools`), 224
 - `cycle_tokens_to_sieve()` (in module `abjad.tools.sievetools`), 703
 - `CyclicList` (class in `abjad.tools.seqtools`), 657
 - `CyclicMatrix` (class in `abjad.tools.seqtools`), 657
 - `CyclicTuple` (class in `abjad.tools.seqtools`), 658
- ## D
- `DateTimeToken` (class in `abjad.tools.lilyfiletools`), 370
 - `DecrescendoSpanner` (class in `abjad.tools.spannertools`), 520
 - `default_paper_size` (`abjad.tools.lilyfiletools.LilyFile` attribute), 372
 - `definition` (`abjad.tools.quantizationtools.QGrid` attribute), 730
 - `delete_contents_of_container()` (in module `abjad.tools.containertools`), 268
 - `delete_contents_of_container_starting_at_or_after_prolated_offset()` (in module `abjad.tools.containertools`), 268
 - `delete_contents_of_container_starting_before_or_at_prolated_offset()` (in module `abjad.tools.containertools`), 269
 - `delete_contents_of_container_starting_strictly_after_prolated_offset()` (in module `abjad.tools.containertools`), 269
 - `delete_contents_of_container_starting_strictly_before_prolated_offset()` (in module `abjad.tools.containertools`), 270
 - `denominator` (`abjad.tools.contexttools.TimeSignatureMark` attribute), 305
 - `denominator` (`abjad.tools.measuretools.DynamicMeasure` attribute), 394
 - `depth` (`abjad.tools.pitcharraytools.PitchArray` attribute), 650
 - `depth` (`abjad.tools.pitcharraytools.PitchArrayColumn` attribute), 652
 - `depth` (`abjad.tools.pitcharraytools.PitchArrayRow` attribute), 653
 - `destroy_all_spanners_attached_to_component()` (in module `abjad.tools.spannertools`), 539
 - `detach()` (`abjad.tools.gracetools.Grace` method), 318
 - `detach_all_context_marks_attached_to_component()` (in module `abjad.tools.contexttools`), 306
 - `detach_annotations_attached_to_component()` (in module `abjad.tools.marktools`), 380
 - `detach_articulations_attached_to_component()` (in module `abjad.tools.marktools`), 380
 - `detach_comments_attached_to_component()` (in module `abjad.tools.marktools`), 381
 - `detach_grace_containers_attached_to_leaf()` (in module `abjad.tools.gracetools`), 319
 - `detach_instrument_mark_attached_to_component()` (in module `abjad.tools.contexttools`), 307
 - `detach_lilypond_command_marks_attached_to_component()` (in module `abjad.tools.marktools`), 382
 - `detach_mark()` (`abjad.tools.contexttools.ContextMark` method), 298
 - `detach_mark()` (`abjad.tools.marktools.Mark` method), 378
 - `detach_marks_attached_to_component()` (in module `abjad.tools.marktools`), 382
 - `detach_stem_tremolos_attached_to_component()` (in module `abjad.tools.marktools`), 383
 - `detach_time_signature_mark_attached_to_component()` (in module `abjad.tools.contexttools`), 307
 - `deviation_in_cents` (`abjad.tools.pitchtools.NamedChromaticPitch` attribute), 448
 - `diatonic_interval_class_segment` (`abjad.tools.tonalitytools.Scale` attribute), 711
 - `diatonic_interval_class_segment_to_chord_quality_string()` (in module `abjad.tools.tonalitytools`), 716
 - `diatonic_interval_number_and_chromatic_interval_number_to_melodic_diatonic_pitch_class_name()` (in module `abjad.tools.pitchtools`), 473
 - `diatonic_pitch_class_name` (`abjad.tools.pitchtools.NamedChromaticPitch` attribute), 448
 - `diatonic_pitch_class_name` (`abjad.tools.pitchtools.NamedDiatonicPitch` attribute), 454
 - `diatonic_pitch_class_name_to_chromatic_pitch_class_number()` (in module `abjad.tools.pitchtools`), 473
 - `diatonic_pitch_class_name_to_diatonic_pitch_class_number()` (in module `abjad.tools.pitchtools`), 474
 - `diatonic_pitch_class_number` (`abjad.tools.pitchtools.NamedChromaticPitch` attribute), 448
 - `diatonic_pitch_class_number` (`abjad.tools.pitchtools.NamedDiatonicPitch` attribute), 454
 - `diatonic_pitch_class_number` (`abjad.tools.pitchtools.NumberedChromaticPitch` attribute), 456
 - `diatonic_pitch_class_number_to_chromatic_pitch_class_number()` (in module `abjad.tools.pitchtools`), 474
 - `diatonic_pitch_class_number_to_diatonic_pitch_class_name()` (in module `abjad.tools.pitchtools`), 474
 - `diatonic_pitch_name` (`abjad.tools.pitchtools.NamedChromaticPitch` attribute), 448
 - `diatonic_pitch_name` (`abjad.tools.pitchtools.NamedDiatonicPitch` attribute), 454

- attribute), 454
- diatonic_pitch_name_to_chromatic_pitch_class_name() (in module abjad.tools.pitchtools), 474
- diatonic_pitch_name_to_chromatic_pitch_class_number() (in module abjad.tools.pitchtools), 474
- diatonic_pitch_name_to_chromatic_pitch_name() (in module abjad.tools.pitchtools), 474
- diatonic_pitch_name_to_chromatic_pitch_number() (in module abjad.tools.pitchtools), 475
- diatonic_pitch_name_to_diatonic_pitch_class_name() (in module abjad.tools.pitchtools), 475
- diatonic_pitch_name_to_diatonic_pitch_class_number() (in module abjad.tools.pitchtools), 475
- diatonic_pitch_name_to_diatonic_pitch_number() (in module abjad.tools.pitchtools), 475
- diatonic_pitch_number (abjad.tools.pitchtools.NamedChromaticPitch attribute), 449
- diatonic_pitch_number (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 454
- diatonic_pitch_number (abjad.tools.pitchtools.NumberedChromaticPitch attribute), 457
- diatonic_pitch_number (abjad.tools.pitchtools.NumberedDiatonicPitch attribute), 461
- diatonic_pitch_number_to_chromatic_pitch_number() (in module abjad.tools.pitchtools), 475
- diatonic_pitch_number_to_diatonic_pitch_class_name() (in module abjad.tools.pitchtools), 476
- diatonic_pitch_number_to_diatonic_pitch_class_number() (in module abjad.tools.pitchtools), 476
- diatonic_pitch_number_to_diatonic_pitch_name() (in module abjad.tools.pitchtools), 476
- difference_series() (in module abjad.tools.mathtools), 630
- dimensions (abjad.tools.pitcharraytools.PitchArray attribute), 650
- dimensions (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652
- dimensions (abjad.tools.pitcharraytools.PitchArrayRow attribute), 653
- direction_number (abjad.tools.pitchtools.MelodicChromaticInterval attribute), 443
- direction_number (abjad.tools.pitchtools.MelodicCounterpointInterval attribute), 445
- direction_number (abjad.tools.pitchtools.MelodicDiatonicInterval attribute), 446
- direction_number (abjad.tools.pitchtools.MelodicDiatonicIntervalClass attribute), 447
- direction_string (abjad.tools.marktools.Articulation attribute), 376
- direction_string (abjad.tools.pitchtools.MelodicDiatonicInterval attribute), 446
- direction_symbol (abjad.tools.pitchtools.MelodicDiatonicIntervalClass attribute), 447
- direction_word (abjad.tools.pitchtools.MelodicDiatonicIntervalClass attribute), 447
- divide_chord_by_chromatic_pitch_number() (in module abjad.tools.chordtools), 205
- divide_chord_by_diatonic_pitch_number() (in module abjad.tools.chordtools), 206
- divide_leaf_meiotically() (in module abjad.tools.leaftools), 340
- divide_leaves_in_expr_meiotically() (in module abjad.tools.leaftools), 341
- divide_number_by_ratio() (in module abjad.tools.mathtools), 630
- divide_sequence_elements_by_greatest_common_divisor() (in module abjad.tools.seqttools), 663
- divisors() (in module abjad.tools.mathtools), 630
- dominant (abjad.tools.tonalitytools.Scale attribute), 711
- DoublingIndicator (class in abjad.tools.tonalitytools), 710
- doublings (abjad.tools.tonalitytools.DoublingIndicator attribute), 710
- duplicate_pitch_classes (abjad.tools.pitchtools.NamedChromaticPitchSet attribute), 453
- DuratedComplexBeamSpanner (class in abjad.tools.spannertools), 521
- duration (abjad.tools.contexttools.TempoMark attribute), 303
- duration (abjad.tools.contexttools.TimeSignatureMark attribute), 305
- duration (abjad.tools.schemetools.SchemeMoment attribute), 503
- Duration (class in abjad.tools.durtools), 587
- duration_and_possible_denominators_to_meter() (in module abjad.tools.metertools), 648
- duration_in_seconds (abjad.tools.containertools.Container attribute), 264
- duration_in_seconds (abjad.tools.spannertools.Spanner attribute), 533
- duration_pair_to_prolation_string() (in module abjad.tools.durtools), 588
- duration_token_to_big_endian_list_of_assignable_duration_pairs() (in module abjad.tools.durtools), 588
- duration_token_to_duration_pair() (in module abjad.tools.durtools), 588
- duration_token_to_rational() (in module abjad.tools.durtools), 589
- duration_tokens_to_duration_pairs() (in module abjad.tools.durtools), 589
- duration_tokens_to_duration_pairs_with_least_common_denominator() (in module abjad.tools.durtools), 589

- duration_tokens_to_least_common_denominator() (in module abjad.tools.durtools), 589
- duration_tokens_to_rationals() (in module abjad.tools.durtools), 590
- durations (abjad.tools.spannertools.DuratedComplexBeamSpanner attribute), 521
- dynamic_name_string (abjad.tools.contexttools.DynamicMark attribute), 299
- dynamic_name_to_dynamic_ordinal() (abjad.tools.contexttools.DynamicMark static method), 299
- dynamic_ordinal_to_dynamic_name() (abjad.tools.contexttools.DynamicMark static method), 299
- DynamicMark (class in abjad.tools.contexttools), 298
- DynamicMeasure (class in abjad.tools.measuretools), 393
- DynamicTextSpanner (class in abjad.tools.spannertools), 522
- ## E
- effective_context (abjad.tools.contexttools.ContextMark attribute), 298
- EFlatClarinet (class in abjad.tools.instrumenttools), 326
- eject_contents_of_container() (in module abjad.tools.containertools), 271
- empty_pitches() (abjad.tools.pitcharraytools.PitchArrayRow method), 653
- EnglishHorn (class in abjad.tools.instrumenttools), 327
- explode_intervals_compactly() (in module abjad.tools.intervaltreetools), 610
- explode_intervals_into_n_trees_heuristically() (in module abjad.tools.intervaltreetools), 610
- explode_intervals_uncompactly() (in module abjad.tools.intervaltreetools), 610
- expr_has_duplicate_named_chromatic_pitch() (in module abjad.tools.pitchtools), 476
- expr_has_duplicate_numbered_chromatic_pitch_class() (in module abjad.tools.pitchtools), 476
- expr_has_leaf_with_dotted_written_duration() (in module abjad.tools.leaftools), 341
- expr_to_melodic_chromatic_interval_segment() (in module abjad.tools.pitchtools), 477
- extend() (abjad.tools.chordtools.Chord method), 202
- extend() (abjad.tools.containertools.Container method), 264
- extend() (abjad.tools.measuretools.DynamicMeasure method), 394
- extend() (abjad.tools.pitcharraytools.PitchArrayColumn method), 652
- extend() (abjad.tools.pitcharraytools.PitchArrayRow method), 653
- extend() (abjad.tools.spannertools.Spanner method), 533
- extend_in_parent_of_component_and_do_not_grow_spanners() (in module abjad.tools.componenttools), 225
- extend_in_parent_of_component_and_grow_spanners() (in module abjad.tools.componenttools), 226
- extent_left() (abjad.tools.spannertools.Spanner method), 533
- extend_left_in_parent_of_component_and_do_not_grow_spanners() (in module abjad.tools.componenttools), 226
- extend_left_in_parent_of_component_and_grow_spanners() (in module abjad.tools.componenttools), 227
- extend_measures_in_expr_and_apply_full_measure_tuplets_to_measure_co (in module abjad.tools.measuretools), 404
- extent (abjad.tools.tonalitytools.ChordClass attribute), 709
- extent (abjad.tools.tonalitytools.ChordQualityIndicator attribute), 710
- extent (abjad.tools.tonalitytools.TonalFunction attribute), 712
- extent_name (abjad.tools.tonalitytools.ChordQualityIndicator attribute), 710
- extent_to_figured_bass_string() (abjad.tools.tonalitytools.InversionIndicator method), 710
- ExtentIndicator (class in abjad.tools.tonalitytools), 710
- ## F
- factors() (in module abjad.tools.iotools), 617
- factors() (in module abjad.tools.mathtools), 631
- figured_bass (abjad.tools.tonalitytools.ChordClass attribute), 709
- figured_bass_pair (abjad.tools.tonalitytools.SuspensionIndicator attribute), 712
- figured_bass_string (abjad.tools.tonalitytools.SuspensionIndicator attribute), 712
- figured_bass_string (abjad.tools.tonalitytools.TonalFunction attribute), 712
- file_initial_system_comments (abjad.tools.lilyfiletools.LilyFile attribute), 372
- file_initial_system_includes (abjad.tools.lilyfiletools.LilyFile attribute), 372
- file_initial_user_comments (abjad.tools.lilyfiletools.LilyFile attribute), 372
- file_initial_user_includes (abjad.tools.lilyfiletools.LilyFile attribute), 372
- fill_measures_in_expr_with_big_endian_notes() (in module abjad.tools.measuretools), 405
- fill_measures_in_expr_with_full_measure_spacer_skips() (in module abjad.tools.measuretools), 405

- `fill_measures_in_expr_with_little_endian_notes()` (in module `abjad.tools.measuretools`), 405
- `fill_measures_in_expr_with_meter_denominator_notes()` (in module `abjad.tools.measuretools`), 406
- `fill_measures_in_expr_with_repeated_notes()` (in module `abjad.tools.measuretools`), 406
- `find_divisible_indices()` (`abjad.tools.quantizationtools.QGrid` method), 730
- `find_index_of_spanner_component_at_score_offset()` (in module `abjad.tools.spannertools`), 539
- `find_intervals_intersecting_or_tangent_to_interval()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_intersecting_or_tangent_to_offset()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_starting_after_offset()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_starting_and_stopping_within_interval()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_starting_at_offset()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_starting_before_offset()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_starting_or_stopping_at_offset()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_starting_within_interval()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_stopping_after_offset()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_stopping_at_offset()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_stopping_before_offset()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_intervals_stopping_within_interval()` (`abjad.tools.intervaltreetools.IntervalTree` method), 605
- `find_parentage_of_index()` (`abjad.tools.quantizationtools.QGrid` method), 730
- `find_spanner_component_starting_at_exactly_score_offset()` (in module `abjad.tools.spannertools`), 540
- `find_subtree_divisibility()` (`abjad.tools.quantizationtools.QGridSearchTree` method), 734
- `fingered_pitch` (`abjad.tools.notetools.Note` attribute), 425
- `fingered_pitches` (`abjad.tools.chordtools.Chord` attribute), 202
- `fix_contents_of_tuplets_in_expr()` (in module `abjad.tools.tuplettools`), 572
- `FixedDurationTuplet` (class in `abjad.tools.tuplettools`), 569
- `flatten_sequence()` (in module `abjad.tools.seqttools`), 664
- `flatten_sequence_at_indices()` (in module `abjad.tools.seqttools`), 664
- `Flute` (class in `abjad.tools.instrumenttools`), 327
- `force_fraction` (`abjad.tools.tuplettools.Tuplet` attribute), 570
- `format` (`abjad.tools.contexttools.ClefMark` attribute), 297
- `format` (`abjad.tools.contexttools.DynamicMark` attribute), 299
- `format` (`abjad.tools.contexttools.InstrumentMark` attribute), 300
- `format` (`abjad.tools.contexttools.KeySignatureMark` attribute), 301
- `format` (`abjad.tools.contexttools.StaffChangeMark` attribute), 302
- `format` (`abjad.tools.contexttools.TempoMark` attribute), 304
- `format` (`abjad.tools.contexttools.TimeSignatureMark` attribute), 305
- `format` (`abjad.tools.lilyfiletools.AbjadRevisionToken` attribute), 370
- `format` (`abjad.tools.lilyfiletools.DateTimeToken` attribute), 370
- `format` (`abjad.tools.lilyfiletools.LilyFile` attribute), 372
- `format` (`abjad.tools.lilyfiletools.LilyPondLanguageToken` attribute), 373
- `format` (`abjad.tools.lilyfiletools.LilyPondVersionToken` attribute), 373
- `format` (`abjad.tools.marktools.Articulation` attribute), 376
- `format` (`abjad.tools.marktools.Comment` attribute), 377
- `format` (`abjad.tools.marktools.LilyPondCommandMark` attribute), 378
- `format` (`abjad.tools.marktools.StemTremolo` attribute), 379
- `format` (`abjad.tools.markuptools.Markup` attribute), 389
- `format` (`abjad.tools.markuptools.MarkupCommand` attribute), 390
- `format` (`abjad.tools.notetools.NoteHead` attribute), 427
- `format` (`abjad.tools.pitchtools.Accidental` attribute), 437
- `format` (`abjad.tools.pitchtools.NamedChromaticPitch` attribute), 449
- `format` (`abjad.tools.pitchtools.NamedDiatonicPitch` attribute), 455
- `format` (`abjad.tools.schemetools.SchemeAssociativeList` attribute), 501

- ul style="list-style-type: none; padding-left: 0;">
- format (abjad.tools.schemetools.SchemeBoolean attribute), 502
- format (abjad.tools.schemetools.SchemeColor attribute), 502
- format (abjad.tools.schemetools.SchemeFunction attribute), 503
- format (abjad.tools.schemetools.SchemeMoment attribute), 503
- format (abjad.tools.schemetools.SchemeNumber attribute), 504
- format (abjad.tools.schemetools.SchemePair attribute), 504
- format (abjad.tools.schemetools.SchemeString attribute), 504
- format (abjad.tools.schemetools.SchemeVariable attribute), 505
- format (abjad.tools.schemetools.SchemeVector attribute), 505
- format (abjad.tools.schemetools.SchemeVectorConstant attribute), 505
- format_for_beatspan() (abjad.tools.quantizationtools.QGrid method), 731
- format_input_lines_as_doc_string() (in module abjad.tools.iotools), 617
- format_input_lines_as_regression_test() (in module abjad.tools.iotools), 617
- fracture() (abjad.tools.spannertools.Spanner method), 533
- fracture_all_spanners_attached_to_component() (in module abjad.tools.spannertools), 540
- fracture_spanners_that_cross_components() (in module abjad.tools.spannertools), 541
- FrenchHorn (class in abjad.tools.instrumenttools), 327
- fuse() (abjad.tools.spannertools.Spanner method), 534
- fuse_contiguous_measures_in_container_cyclically_by_counts() (in module abjad.tools.measuretools), 406
- fuse_leaves_big_endian() (in module abjad.tools.leaftools), 342
- fuse_leaves_in_container_once_by_counts_into_big_endian_notes() (in module abjad.tools.leaftools), 342
- fuse_leaves_in_container_once_by_counts_into_big_endian_rests() (in module abjad.tools.leaftools), 342
- fuse_leaves_in_container_once_by_counts_into_little_endian_notes() (in module abjad.tools.leaftools), 342
- fuse_leaves_in_container_once_by_counts_into_little_endian_rests() (in module abjad.tools.leaftools), 342
- fuse_leaves_in_tie_chain_by_immediate_parent_big_endian() (in module abjad.tools.leaftools), 343
- fuse_like_named_contiguous_containers_in_expr() (in module abjad.tools.containertools), 271
- fuse_measures() (in module abjad.tools.measuretools), 408
- fuse_overlapping_intervals() (in module abjad.tools.intervaltreetools), 611
- fuse_tangent_or_overlapping_intervals() (in module abjad.tools.intervaltreetools), 611
- fuse_tied_leaves_in_components_once_by_prolated_durations_without_overlap() (in module abjad.tools.leaftools), 343
- fuse_tuplets() (in module abjad.tools.tuplettools), 572
- ## G
- get() (abjad.tools.pitchtools.NumberedChromaticPitchClassColorMap method), 457
 - get_abjad_revision_string() (in module abjad.tools.cfgtools), 585
 - get_abjad_version_string() (in module abjad.tools.cfgtools), 585
 - get_all_unique_bounds_in_intervals() (in module abjad.tools.intervaltreetools), 611
 - get_annotation_attached_to_component() (in module abjad.tools.marktools), 383
 - get_annotations_attached_to_component() (in module abjad.tools.marktools), 384
 - get_arithmetic_mean_of_chord() (in module abjad.tools.chordtools), 206
 - get_articulations_attached_to_component() (in module abjad.tools.marktools), 384
 - get_beam_spanner_attached_to_component() (in module abjad.tools.spannertools), 541
 - get_boolean_train() (abjad.tools.sievetools.ResidueClass method), 701
 - get_boolean_train() (abjad.tools.sievetools.ResidueClassExpression method), 702
 - get_comments_attached_to_component() (in module abjad.tools.marktools), 385
 - get_component_start_offset() (in module abjad.tools.componenttools), 227
 - get_component_start_offset_in_seconds() (in module abjad.tools.componenttools), 228
 - get_component_stop_offset() (in module abjad.tools.componenttools), 228
 - get_component_stop_offset_in_seconds() (in module abjad.tools.componenttools), 228
 - get_composite_offset_difference_series_from_leaves_in_expr() (in module abjad.tools.leaftools), 344
 - get_composite_offset_series_from_leaves_in_expr() (in module abjad.tools.leaftools), 344
 - get_congruent_bases() (abjad.tools.sievetools.ResidueClass method), 702
 - get_congruent_bases() (abjad.tools.sievetools.ResidueClassExpression method), 703
 - get_context_marks_attached_to_any_improper_parent_of_component() (in module abjad.tools.contexttools), 308
 - get_context_marks_attached_to_component() (in module abjad.tools.contexttools), 309

- `get_down_markup_attached_to_component()` (in module `abjad.tools.markuptools`), 390
- `get_dynamic_marks_attached_to_component()` (in module `abjad.tools.contexttools`), 309
- `get_effective_clef()` (in module `abjad.tools.contexttools`), 309
- `get_effective_context_mark()` (in module `abjad.tools.contexttools`), 310
- `get_effective_dynamic()` (in module `abjad.tools.contexttools`), 310
- `get_effective_instrument()` (in module `abjad.tools.contexttools`), 311
- `get_effective_key_signature()` (in module `abjad.tools.contexttools`), 311
- `get_effective_staff()` (in module `abjad.tools.contexttools`), 312
- `get_effective_tempo()` (in module `abjad.tools.contexttools`), 312
- `get_effective_time_signature()` (in module `abjad.tools.contexttools`), 313
- `get_element_starting_at_exactly_prolated_offset()` (in module `abjad.tools.containertools`), 272
- `get_first_component_in_expr_with_name()` (in module `abjad.tools.componenttools`), 229
- `get_first_component_with_name_in_improper_parentage_of_component()` (in module `abjad.tools.componenttools`), 229
- `get_first_component_with_name_in_proper_parentage_of_component()` (in module `abjad.tools.componenttools`), 230
- `get_first_container_in_improper_parentage_of_component()` (in module `abjad.tools.containertools`), 272
- `get_first_container_in_proper_parentage_of_component()` (in module `abjad.tools.containertools`), 272
- `get_first_element_starting_at_or_after_prolated_offset()` (in module `abjad.tools.containertools`), 273
- `get_first_element_starting_before_or_at_prolated_offset()` (in module `abjad.tools.containertools`), 273
- `get_first_element_starting_strictly_after_prolated_offset()` (in module `abjad.tools.containertools`), 273
- `get_first_element_starting_strictly_before_prolated_offset()` (in module `abjad.tools.containertools`), 274
- `get_first_instance_of_klass_in_improper_parentage_of_component()` (in module `abjad.tools.componenttools`), 230
- `get_first_instance_of_klass_in_proper_parentage_of_component()` (in module `abjad.tools.componenttools`), 231
- `get_first_measure_in_improper_parentage_of_component()` (in module `abjad.tools.measuretools`), 409
- `get_first_measure_in_proper_parentage_of_component()` (in module `abjad.tools.measuretools`), 409
- `get_first_score_in_improper_parentage_of_component()` (in module `abjad.tools.scoretools`), 509
- `get_first_score_in_proper_parentage_of_component()` (in module `abjad.tools.scoretools`), 509
- `get_first_staff_in_improper_parentage_of_component()` (in module `abjad.tools.stafftools`), 554
- `get_first_staff_in_proper_parentage_of_component()` (in module `abjad.tools.stafftools`), 554
- `get_first_tuplet_in_improper_parentage_of_component()` (in module `abjad.tools.tuplettools`), 573
- `get_first_tuplet_in_proper_parentage_of_component()` (in module `abjad.tools.tuplettools`), 574
- `get_first_voice_in_improper_parentage_of_component()` (in module `abjad.tools.voicetools`), 581
- `get_first_voice_in_proper_parentage_of_component()` (in module `abjad.tools.voicetools`), 582
- `get_grace_containers_attached_to_leaf()` (in module `abjad.tools.gracetools`), 320
- `get_improper_parentage_of_component()` (in module `abjad.tools.componenttools`), 231
- `get_indices_of_sequence_elements_equal_to_true()` (in module `abjad.tools.seqtools`), 665
- `get_instrument_mark_attached_to_component()` (in module `abjad.tools.contexttools`), 313
- `get_last_output_file_name()` (in module `abjad.tools.iotools`), 618
- `get_leaf_at_index_in_measure_number_in_expr()` (in module `abjad.tools.leaftools`), 345
- `get_leaves_in_tie_chain()` (in module `abjad.tools.tietools`), 557
- `get_lilypond_multiplier_of_components()` (in module `abjad.tools.componenttools`), 231
- `get_lilypond_command_marks_attached_to_component()` (in module `abjad.tools.marktools`), 385
- `get_lilypond_version_string()` (in module `abjad.tools.cfgtools`), 585
- `get_marks_attached_to_component()` (in module `abjad.tools.marktools`), 386
- `get_markup_attached_to_component()` (in module `abjad.tools.markuptools`), 391
- `get_named_chromatic_pitch_from_pitch_carrier()` (in module `abjad.tools.pitchtools`), 477
- `get_next_measure_from_component()` (in module `abjad.tools.measuretools`), 409
- `get_next_output_file_name()` (in module `abjad.tools.iotools`), 618
- `get_nth_binary_factor_from_meter_denominator()` (in module `abjad.tools.metertools`), 648
- `get_nth_context_marks_attached_to_component()` (in module `abjad.tools.marktools`), 386
- `get_note_head_from_chord_by_pitch()` (in module `abjad.tools.chordtools`), 206
- `get_nth_component_in_expr()` (in module `abjad.tools.componenttools`), 232
- `get_nth_leaf_in_expr()` (in module `abjad.tools.leaftools`), 346
- `get_nth_leaf_in_spanner()` (in module `abjad.tools.spannertools`), 542
- `get_nth_leaf_in_thread_from_leaf()` (in module `abjad.tools.leaftools`), 346

[get_nth_measure_in_expr\(\)](#) (in module `abjad.tools.measuretools`), 410
[get_nth_namesake_from_component\(\)](#) (in module `abjad.tools.componenttools`), 233
[get_numbered_chromatic_pitch_class_from_pitch_carrier\(\)](#) (in module `abjad.tools.pitchtools`), 477
[get_one_indexed_measure_number_in_expr\(\)](#) (in module `abjad.tools.measuretools`), 411
[get_overlap_with_interval\(\)](#) (`abjad.tools.intervaltreetools.BoundedInterval` method), 604
[get_parent_and_start_stop_indices_of_components\(\)](#) (in module `abjad.tools.componenttools`), 233
[get_preprolated_tie_chain_duration\(\)](#) (in module `abjad.tools.tietools`), 557
[get_prev_measure_from_component\(\)](#) (in module `abjad.tools.measuretools`), 412
[get_prolated_tie_chain_duration\(\)](#) (in module `abjad.tools.tietools`), 558
[get_proper_parentage_of_component\(\)](#) (in module `abjad.tools.componenttools`), 234
[get_python_version_string\(\)](#) (in module `abjad.tools.cfgtools`), 585
[get_sequence_degree_of_rotational_symmetry\(\)](#) (in module `abjad.tools.seqtools`), 665
[get_sequence_element_at_cyclic_index\(\)](#) (in module `abjad.tools.seqtools`), 665
[get_sequence_elements_at_indices\(\)](#) (in module `abjad.tools.seqtools`), 666
[get_sequence_elements_frequency_distribution\(\)](#) (in module `abjad.tools.seqtools`), 666
[get_sequence_period_of_rotation\(\)](#) (in module `abjad.tools.seqtools`), 666
[get_shared_numeric_sign\(\)](#) (in module `abjad.tools.mathtools`), 631
[get_spanners_attached_to_any_improper_child_of_component\(\)](#) (in module `abjad.tools.spannertools`), 542
[get_spanners_attached_to_any_improper_parent_of_component\(\)](#) (in module `abjad.tools.spannertools`), 543
[get_spanners_attached_to_any_proper_child_of_component\(\)](#) (in module `abjad.tools.spannertools`), 543
[get_spanners_attached_to_any_proper_parent_of_component\(\)](#) (in module `abjad.tools.spannertools`), 544
[get_spanners_attached_to_component\(\)](#) (in module `abjad.tools.spannertools`), 544
[get_spanners_contained_by_components\(\)](#) (in module `abjad.tools.spannertools`), 545
[get_spanners_covered_by_components\(\)](#) (in module `abjad.tools.spannertools`), 545
[get_spanners_on_components_or_component_children\(\)](#) (in module `abjad.tools.spannertools`), 545
[get_spanners_that_cross_components\(\)](#) (in module `abjad.tools.spannertools`), 546
[get_spanners_that_dominate_component_pair\(\)](#) (in module `abjad.tools.spannertools`), 546
[get_spanners_that_dominate_components\(\)](#) (in module `abjad.tools.spannertools`), 546
[get_spanners_that_dominate_container_components_from_to\(\)](#) (in module `abjad.tools.spannertools`), 546
[get_stem_tremolos_attached_to_component\(\)](#) (in module `abjad.tools.marktools`), 387
[get_the_only_spanner_attached_to_any_improper_parent_of_component\(\)](#) (in module `abjad.tools.spannertools`), 547
[get_the_only_spanner_attached_to_component\(\)](#) (in module `abjad.tools.spannertools`), 547
[get_tie_chain\(\)](#) (in module `abjad.tools.tietools`), 558
[get_tie_chain_duration_in_seconds\(\)](#) (in module `abjad.tools.tietools`), 558
[get_tie_chains_in_expr\(\)](#) (in module `abjad.tools.tietools`), 558
[get_time_signature_mark_attached_to_component\(\)](#) (in module `abjad.tools.contexttools`), 314
[get_up_markup_attached_to_component\(\)](#) (in module `abjad.tools.markuptools`), 391
[get_value_of_annotation_attached_to_component\(\)](#) (in module `abjad.tools.marktools`), 387
[get_vertical_moment_at_prolated_offset_in_expr\(\)](#) (in module `abjad.tools.verticalitytools`), 720
[get_vertical_moment_starting_with_component\(\)](#) (in module `abjad.tools.verticalitytools`), 721
[get_written_tie_chain_duration\(\)](#) (in module `abjad.tools.tietools`), 558
[GlissandoSpanner](#) (class in `abjad.tools.spannertools`), 523
[global_staff_size](#) (`abjad.tools.lilyfiletools.LilyFile` attribute), 372
[Glockenspiel](#) (class in `abjad.tools.instrumenttools`), 328
[governors](#) (`abjad.tools.verticalitytools.VerticalMoment` attribute), 719
[GraceNote](#) (class in `abjad.tools.gracetools`), 317
[GrandStaff](#) (class in `abjad.tools.scoretools`), 506
[gcd\(\)](#) (`abjad.tools.mathtools` method), 632
[greatest_common_divisor\(\)](#) (in module `abjad.tools.mathtools`), 632
[greatest_multiple_less_equal\(\)](#) (in module `abjad.tools.mathtools`), 632
[greatest_power_of_two_less_equal\(\)](#) (in module `abjad.tools.mathtools`), 633
[group_duration_tokens_by_implied_prolation\(\)](#) (in module `abjad.tools.durtools`), 590
[group_leaves_in_tie_chain_by_immediate_parents\(\)](#) (in module `abjad.tools.tietools`), 558
[group_overlapping_intervals_and_yield_groups\(\)](#) (in module `abjad.tools.intervaltreetools`), 611
[group_tangent_or_overlapping_intervals_and_yield_groups\(\)](#) (in module `abjad.tools.intervaltreetools`), 611
[Guitar](#) (class in `abjad.tools.instrumenttools`), 328

H

- HairpinSpanner (class in abjad.tools.spannertools), 523
- harmonic_chromatic_interval (abjad.tools.pitchtools.MelodicChromaticInterval attribute), 443
- harmonic_chromatic_interval (abjad.tools.pitchtools.MelodicDiatonicInterval attribute), 446
- harmonic_chromatic_interval_class (abjad.tools.pitchtools.HarmonicChromaticInterval attribute), 438
- harmonic_chromatic_interval_class_segment (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- harmonic_chromatic_interval_numbers (abjad.tools.pitchtools.HarmonicChromaticIntervalSet attribute), 439
- harmonic_chromatic_interval_segment (abjad.tools.pitchtools.HarmonicDiatonicIntervalSegment attribute), 441
- harmonic_chromatic_interval_segment (abjad.tools.pitchtools.MelodicChromaticIntervalSegment attribute), 445
- harmonic_chromatic_interval_segment (abjad.tools.pitchtools.MelodicDiatonicIntervalSegment attribute), 447
- harmonic_chromatic_interval_segment (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- harmonic_chromatic_interval_set (abjad.tools.pitchtools.HarmonicDiatonicIntervalSet attribute), 441
- harmonic_chromatic_interval_set (abjad.tools.pitchtools.MelodicChromaticIntervalSet attribute), 445
- harmonic_chromatic_interval_set (abjad.tools.pitchtools.MelodicDiatonicIntervalSet attribute), 447
- harmonic_chromatic_intervals (abjad.tools.pitchtools.HarmonicChromaticIntervalSet attribute), 439
- harmonic_counterpoint_interval (abjad.tools.pitchtools.HarmonicDiatonicInterval attribute), 440
- harmonic_counterpoint_interval (abjad.tools.pitchtools.MelodicDiatonicInterval attribute), 446
- harmonic_counterpoint_interval_class (abjad.tools.pitchtools.HarmonicCounterpointInterval attribute), 439
- harmonic_diatonic_interval (abjad.tools.pitchtools.MelodicDiatonicInterval attribute), 446
- harmonic_diatonic_interval_class (abjad.tools.pitchtools.HarmonicDiatonicInterval attribute), 440
- harmonic_diatonic_interval_class_segment (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- harmonic_diatonic_interval_classes (abjad.tools.pitchtools.HarmonicDiatonicIntervalClassSet attribute), 441
- harmonic_diatonic_interval_numbers (abjad.tools.pitchtools.HarmonicDiatonicIntervalSet attribute), 441
- harmonic_diatonic_interval_segment (abjad.tools.pitchtools.MelodicDiatonicIntervalSegment attribute), 447
- harmonic_diatonic_interval_segment (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- harmonic_diatonic_interval_set (abjad.tools.pitchtools.MelodicDiatonicIntervalSet attribute), 447
- harmonic_diatonic_intervals (abjad.tools.pitchtools.HarmonicDiatonicIntervalSet attribute), 441
- HarmonicChromaticInterval (class in abjad.tools.pitchtools), 438
- HarmonicChromaticIntervalClass (class in abjad.tools.pitchtools), 438
- HarmonicChromaticIntervalClassVector (class in abjad.tools.pitchtools), 438
- HarmonicChromaticIntervalSegment (class in abjad.tools.pitchtools), 439
- HarmonicChromaticIntervalSet (class in abjad.tools.pitchtools), 439
- HarmonicCounterpointInterval (class in abjad.tools.pitchtools), 439
- HarmonicCounterpointIntervalClass (class in abjad.tools.pitchtools), 439
- HarmonicDiatonicInterval (class in abjad.tools.pitchtools), 440
- HarmonicDiatonicIntervalClass (class in abjad.tools.pitchtools), 440
- HarmonicDiatonicIntervalClassSet (class in abjad.tools.pitchtools), 440
- HarmonicDiatonicIntervalSegment (class in abjad.tools.pitchtools), 441
- HarmonicDiatonicIntervalSet (class in abjad.tools.pitchtools), 441
- Harp (class in abjad.tools.instrumenttools), 329
- has_none_of() (abjad.tools.pitchtools.HarmonicChromaticIntervalClassVector method), 438
- has_spanning_cell_over_index() (abjad.tools.pitcharraytools.PitchArray method), 650

- `has_spanning_cell_over_index()` (abjad.tools.pitcharraytools.PitchArrayRow method), 653
- `has_voice_crossing` (abjad.tools.pitcharraytools.PitchArray attribute), 650
- `has_voice_crossing` (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652
- `HeaderBlock` (class in abjad.tools.lilyfiletools), 371
- `HiddenStaffSpanner` (class in abjad.tools.spannertools), 526
- `high` (abjad.tools.intervaltreetools.BoundedInterval attribute), 604
- `high` (abjad.tools.intervaltreetools.IntervalTree attribute), 605
- `high_max` (abjad.tools.intervaltreetools.IntervalTree attribute), 605
- `high_min` (abjad.tools.intervaltreetools.IntervalTree attribute), 605
- I**
- `include_rests` (abjad.tools.spannertools.HairpinSpanner attribute), 524
- `increase_sequence_elements_at_indices_by_addenda()` (in module abjad.tools.seqttools), 667
- `increase_sequence_elements_cyclically_by_addenda()` (in module abjad.tools.seqttools), 667
- `index()` (abjad.tools.containertools.Container method), 265
- `index()` (abjad.tools.pitcharraytools.PitchArrayRow method), 653
- `index()` (abjad.tools.spannertools.Spanner method), 534
- `indices` (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651
- `inflection_point_count` (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- `insert()` (abjad.tools.containertools.Container method), 265
- `insert_and_transpose_nested_subruns_in_chromatic_pitch_class_number_set()` (in module abjad.tools.pitchtools), 478
- `insert_component_and_do_not_fracture_crossing_spanners()` (in module abjad.tools.containertools), 274
- `insert_component_and_fracture_crossing_spanners()` (in module abjad.tools.containertools), 275
- `instantiate_pitch_and_interval_test_collection()` (in module abjad.tools.pitchtools), 478
- `instrument_name` (abjad.tools.contexttools.InstrumentMark attribute), 300
- `InstrumentMark` (class in abjad.tools.contexttools), 300
- `integer_equivalent_number_to_integer()` (in module abjad.tools.mathtools), 634
- `integer_tempo_to_multiplier_tempo_pairs()` (in module abjad.tools.tempotools), 703
- `integer_tempo_to_multiplier_tempo_pairs_report()` (in module abjad.tools.tempotools), 704
- `integer_to_base_k_tuple()` (in module abjad.tools.mathtools), 634
- `integer_to_binary_string()` (in module abjad.tools.mathtools), 634
- `interlace_sequences()` (in module abjad.tools.seqttools), 667
- `interpolate_cosine()` (in module abjad.tools.mathtools), 635
- `interpolate_divide()` (in module abjad.tools.mathtools), 635
- `interpolate_divide_multiple()` (in module abjad.tools.mathtools), 635
- `interpolate_exponential()` (in module abjad.tools.mathtools), 636
- `interpolate_linear()` (in module abjad.tools.mathtools), 636
- `IntervalTree` (class in abjad.tools.intervaltreetools), 605
- `inventory_aggregate_subsets()` (in module abjad.tools.pitchtools), 479
- `inventory_inversion_equivalent_diatonic_interval_classes()` (in module abjad.tools.pitchtools), 480
- `inversion` (abjad.tools.tonalitytools.ChordClass attribute), 709
- `inversion` (abjad.tools.tonalitytools.ChordQualityIndicator attribute), 710
- `inversion` (abjad.tools.tonalitytools.TonalFunction attribute), 712
- `inversion_equivalent_chromatic_interval_class` (abjad.tools.pitchtools.MelodicDiatonicInterval attribute), 446
- `inversion_equivalent_chromatic_interval_class_numbers` (abjad.tools.pitchtools.InversionEquivalentChromaticIntervalClass attribute), 442
- `inversion_equivalent_chromatic_interval_class_segment` (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- `inversion_equivalent_chromatic_interval_class_segment` (abjad.tools.pitchtools.NumberedChromaticPitchClassSegment attribute), 458
- `inversion_equivalent_chromatic_interval_class_set` (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- `inversion_equivalent_chromatic_interval_class_set` (abjad.tools.pitchtools.NumberedChromaticPitchClassSet attribute), 459
- `inversion_equivalent_chromatic_interval_class_vector` (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- `inversion_equivalent_chromatic_interval_class_vector` (abjad.tools.pitchtools.NumberedChromaticPitchClassSet attribute), 459

- attribute), 459
- inversion_equivalent_chromatic_interval_classes (abjad.tools.pitchtools.InversionEquivalentChromaticIntervalClasses attribute), 442
- inversion_equivalent_chromatic_interval_number (abjad.tools.pitchtools.InversionEquivalentChromaticIntervalClasses attribute), 441
- inversion_equivalent_diatonic_interval_class_segment (abjad.tools.pitchtools.NamedChromaticPitchClassSegment attribute), 451
- inversion_equivalent_diatonic_interval_class_vector (abjad.tools.pitchtools.NamedChromaticPitchClassSet attribute), 451
- InversionEquivalentChromaticIntervalClass (class in abjad.tools.pitchtools), 441
- InversionEquivalentChromaticIntervalClassSegment (class in abjad.tools.pitchtools), 441
- InversionEquivalentChromaticIntervalClassSet (class in abjad.tools.pitchtools), 442
- InversionEquivalentChromaticIntervalClassVector (class in abjad.tools.pitchtools), 442
- InversionEquivalentDiatonicIntervalClass (class in abjad.tools.pitchtools), 442
- InversionEquivalentDiatonicIntervalClassSegment (class in abjad.tools.pitchtools), 442
- InversionEquivalentDiatonicIntervalClassVector (class in abjad.tools.pitchtools), 443
- InversionIndicator (class in abjad.tools.tonalitytools), 710
- invert() (abjad.tools.pitchtools.HarmonicDiatonicIntervalClass method), 440
- invert() (abjad.tools.pitchtools.NumberedChromaticPitchClass method), 457
- invert() (abjad.tools.pitchtools.NumberedChromaticPitchClassSegment method), 458
- invert() (abjad.tools.pitchtools.NumberedChromaticPitchClassSet method), 460
- is_adjusted (abjad.tools.pitchtools.Accidental attribute), 437
- is_alphabetic_accidental_abbreviation() (in module abjad.tools.pitchtools), 480
- is_assignable_integer() (in module abjad.tools.mathtools), 636
- is_assignable_rational() (in module abjad.tools.durtools), 590
- is_augmentation (abjad.tools.tuplettools.Tuplet attribute), 570
- is_bar_line_crossing_leaf() (in module abjad.tools.leaftools), 347
- is_beamable_component() (in module abjad.tools.componenttools), 234
- is_binary (abjad.tools.measuretools.Measure attribute), 395
- is_binary (abjad.tools.tuplettools.Tuplet attribute), 570
- is_binary_rational() (in module abjad.tools.durtools), 591
- is_braced (abjad.tools.markuptools.MarkupCommand attribute), 390
- IntervalClassSet.pitch_class_name() (in module abjad.tools.pitchtools), 480
- is_chromatic_pitch_class_name_octave_number_pair() (in module abjad.tools.pitchtools), 481
- is_chromatic_pitch_class_number() (in module abjad.tools.pitchtools), 481
- is_chromatic_pitch_name() (in module abjad.tools.pitchtools), 481
- is_chromatic_pitch_number() (in module abjad.tools.pitchtools), 481
- is_component_with_beam_spanner_attached() (in module abjad.tools.spannertools), 548
- is_component_with_context_mark_attached() (in module abjad.tools.contexttools), 314
- is_component_with_lilypond_command_mark_attached() (in module abjad.tools.marktools), 387
- is_component_with_spanner_attached() (in module abjad.tools.spannertools), 548
- is_component_with_tie_spanner_attached() (in module abjad.tools.tietools), 559
- is_component_with_time_signature_mark_attached() (in module abjad.tools.contexttools), 315
- is_congruent_base() (abjad.tools.sievetools.ResidueClassExpression method), 703
- is_contained_by_interval() (abjad.tools.intervaltreetools.BoundedInterval method), 604
- is_container_of_interval() (abjad.tools.intervaltreetools.BoundedInterval method), 604
- is_defective (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652
- is_defective (abjad.tools.pitcharraytools.PitchArrayRow attribute), 653
- is_diatonic_pitch_class_name() (in module abjad.tools.pitchtools), 481
- is_diatonic_pitch_class_number() (in module abjad.tools.pitchtools), 482
- is_diatonic_pitch_name() (in module abjad.tools.pitchtools), 482
- is_diatonic_pitch_number() (in module abjad.tools.pitchtools), 482
- is_diatonic_quality_abbreviation() (in module abjad.tools.pitchtools), 482
- is_diminution (abjad.tools.tuplettools.Tuplet attribute), 570
- is_dotted_integer() (in module abjad.tools.mathtools), 637
- is_duration_pair() (in module abjad.tools.durtools), 591
- is_duration_token() (in module abjad.tools.durtools), 592

- `is_dynamic_name()` (abjad.tools.contexttools.DynamicMark static method), 299
- `is_empty` (abjad.tools.tonalitytools.SuspensionIndicator attribute), 712
- `is_equivalent_under_transposition()` (abjad.tools.pitchtools.NamedChromaticPitchClassSet static method), 451
- `is_first_in_row` (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651
- `is_full` (abjad.tools.measuretools.Measure attribute), 395
- `is_hairpin_shape_string()` (abjad.tools.spannertools.HairpinSpanner static method), 525
- `is_harmonic_diatonic_interval_abbreviation()` (in module abjad.tools.pitchtools), 483
- `is_in_range` (abjad.tools.pitcharraytools.PitchArrayRow attribute), 653
- `is_integer_equivalent_number()` (in module abjad.tools.mathtools), 638
- `is_invisible` (abjad.tools.tuplettools.Tuplet attribute), 570
- `is_last_in_row` (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651
- `is_lilypond_duration_name()` (in module abjad.tools.durtools), 592
- `is_lilypond_duration_string()` (in module abjad.tools.durtools), 592
- `is_lilypond_rest_string()` (in module abjad.tools.resttools), 498
- `is_melodic_diatonic_interval_abbreviation()` (in module abjad.tools.pitchtools), 483
- `is_meter_with_equivalent_binary_representation()` (in module abjad.tools.metertools), 649
- `is_monotonically_decreasing_sequence()` (in module abjad.tools.seqtools), 668
- `is_monotonically_increasing_sequence()` (in module abjad.tools.seqtools), 668
- `is_named_chromatic_pitch_token()` (in module abjad.tools.pitchtools), 483
- `is_negative_integer()` (in module abjad.tools.mathtools), 638
- `is_neighbor_note()` (in module abjad.tools.tonalitytools), 716
- `is_nonbinary` (abjad.tools.contexttools.TimeSignatureMark attribute), 305
- `is_nonbinary` (abjad.tools.measuretools.Measure attribute), 396
- `is_nonbinary` (abjad.tools.tuplettools.Tuplet attribute), 570
- `is_nonnegative_integer()` (in module abjad.tools.mathtools), 638
- `is_nonnegative_integer_equivalent_number()` (in module abjad.tools.mathtools), 639
- `is_nonnegative_integer_power_of_two()` (in module abjad.tools.mathtools), 639
- `is_octave_tick_string()` (in module abjad.tools.pitchtools), 483
- `is_orphan_component()` (in module abjad.tools.componenttools), 234
- `is_overfull` (abjad.tools.measuretools.Measure attribute), 396
- `is_overlapped_by_interval()` (abjad.tools.intervaltreetools.BoundedInterval method), 604
- `is_parallel` (abjad.tools.containertools.Container attribute), 265
- `is_passing_tone()` (in module abjad.tools.tonalitytools), 717
- `is_permutation()` (in module abjad.tools.seqtools), 669
- `is_pitch_carrier()` (in module abjad.tools.pitchtools), 483
- `is_pitch_class_unique` (abjad.tools.pitchtools.NamedChromaticPitchSet attribute), 453
- `is_positive_integer()` (in module abjad.tools.mathtools), 639
- `is_positive_integer_equivalent_number()` (in module abjad.tools.mathtools), 640
- `is_proper_tuplet_multiplier()` (in module abjad.tools.tuplettools), 574
- `is_rectangular` (abjad.tools.pitcharraytools.PitchArray attribute), 650
- `is_repetition_free_sequence()` (in module abjad.tools.seqtools), 669
- `is_restricted_growth_function()` (in module abjad.tools.seqtools), 670
- `is_strictly_decreasing_sequence()` (in module abjad.tools.seqtools), 670
- `is_strictly_increasing_sequence()` (in module abjad.tools.seqtools), 671
- `is_tangent_to_interval()` (abjad.tools.intervaltreetools.BoundedInterval method), 604
- `is_tertian` (abjad.tools.pitchtools.InversionEquivalentDiatonicIntervalClassSet attribute), 443
- `is_tie_chain()` (in module abjad.tools.tietools), 560
- `is_tie_chain_with_all_leaves_in_same_parent()` (in module abjad.tools.tietools), 560
- `is_transposed_subset()` (abjad.tools.pitchtools.NumberedChromaticPitchClassSet method), 460
- `is_transposed_superset()` (abjad.tools.pitchtools.NumberedChromaticPitchClassSet method), 460
- `is_trivial` (abjad.tools.tuplettools.Tuplet attribute), 570
- `is_underfull` (abjad.tools.measuretools.Measure attribute), 396

<code>is_unlikely_melodic_diatonic_interval_in_chorale()</code> (in module <code>abjad.tools.tonalitytools</code>), 717	<code>iterate_notes_backward_in_expr()</code> (in module <code>abjad.tools.notetools</code>), 429
<code>is_uppercase</code> (<code>abjad.tools.tonalitytools.QualityIndicator</code> attribute), 711	<code>iterate_notes_forward_in_expr()</code> (in module <code>abjad.tools.notetools</code>), 430
<code>is_valid_beatspan()</code> (in module <code>abjad.tools.quantizationtools</code>), 735	<code>iterate_rests_backward_in_expr()</code> (in module <code>abjad.tools.resttools</code>), 498
<code>is_well_formed_component()</code> (in module <code>abjad.tools.componenttools</code>), 234	<code>iterate_rests_forward_in_expr()</code> (in module <code>abjad.tools.resttools</code>), 499
<code>iterate_chords_backward_in_expr()</code> (in module <code>abjad.tools.chordtools</code>), 207	<code>iterate_scores_backward_in_expr()</code> (in module <code>abjad.tools.scoretools</code>), 509
<code>iterate_chords_forward_in_expr()</code> (in module <code>abjad.tools.chordtools</code>), 207	<code>iterate_scores_forward_in_expr()</code> (in module <code>abjad.tools.scoretools</code>), 510
<code>iterate_components_and_grace_containers_forward_in_expr()</code> (in module <code>abjad.tools.gracetools</code>), 320	<code>iterate_semantic_voices_backward_in_expr()</code> (in module <code>abjad.tools.voicetools</code>), 582
<code>iterate_components_backward_in_expr()</code> (in module <code>abjad.tools.componenttools</code>), 235	<code>iterate_semantic_voices_forward_in_expr()</code> (in module <code>abjad.tools.voicetools</code>), 583
<code>iterate_components_backward_in_spanner()</code> (in module <code>abjad.tools.spannertools</code>), 548	<code>iterate_sequence_cyclically()</code> (in module <code>abjad.tools.seqtools</code>), 672
<code>iterate_components_depth_first()</code> (in module <code>abjad.tools.componenttools</code>), 236	<code>iterate_sequence_cyclically_from_start_to_stop()</code> (in module <code>abjad.tools.seqtools</code>), 672
<code>iterate_components_forward_in_expr()</code> (in module <code>abjad.tools.componenttools</code>), 236	<code>iterate_sequence_forward_and_backward_nonoverlapping()</code> (in module <code>abjad.tools.seqtools</code>), 673
<code>iterate_components_forward_in_spanner()</code> (in module <code>abjad.tools.spannertools</code>), 549	<code>iterate_sequence_forward_and_backward_overlapping()</code> (in module <code>abjad.tools.seqtools</code>), 673
<code>iterate_containers_backward_in_expr()</code> (in module <code>abjad.tools.containertools</code>), 275	<code>iterate_sequence_nwise_cyclic()</code> (in module <code>abjad.tools.seqtools</code>), 673
<code>iterate_containers_forward_in_expr()</code> (in module <code>abjad.tools.containertools</code>), 276	<code>iterate_sequence_nwise_strict()</code> (in module <code>abjad.tools.seqtools</code>), 674
<code>iterate_contexts_backward_in_expr()</code> (in module <code>abjad.tools.contexttools</code>), 315	<code>iterate_sequence_nwise_wrapped()</code> (in module <code>abjad.tools.seqtools</code>), 674
<code>iterate_contexts_forward_in_expr()</code> (in module <code>abjad.tools.contexttools</code>), 316	<code>iterate_sequence_pairwise_cyclic()</code> (in module <code>abjad.tools.seqtools</code>), 674
<code>iterate_leaf_pairs_forward_in_expr()</code> (in module <code>abjad.tools.leaftools</code>), 348	<code>iterate_sequence_pairwise_strict()</code> (in module <code>abjad.tools.seqtools</code>), 674
<code>iterate_leaves_backward_in_expr()</code> (in module <code>abjad.tools.leaftools</code>), 349	<code>iterate_sequence_pairwise_wrapped()</code> (in module <code>abjad.tools.seqtools</code>), 675
<code>iterate_leaves_forward_in_expr()</code> (in module <code>abjad.tools.leaftools</code>), 350	<code>iterate_skips_backward_in_expr()</code> (in module <code>abjad.tools.skiptools</code>), 513
<code>iterate_measures_backward_in_expr()</code> (in module <code>abjad.tools.measuretools</code>), 412	<code>iterate_skips_forward_in_expr()</code> (in module <code>abjad.tools.skiptools</code>), 514
<code>iterate_measures_forward_in_expr()</code> (in module <code>abjad.tools.measuretools</code>), 413	<code>iterate_staves_backward_in_expr()</code> (in module <code>abjad.tools.stafftools</code>), 555
<code>iterate_named_chromatic_pitch_pairs_forward_in_expr()</code> (in module <code>abjad.tools.pitchtools</code>), 484	<code>iterate_staves_forward_in_expr()</code> (in module <code>abjad.tools.stafftools</code>), 555
<code>iterate_namesakes_backward_from_component()</code> (in module <code>abjad.tools.componenttools</code>), 237	<code>iterate_thread_backward_from_component()</code> (in module <code>abjad.tools.threadtools</code>), 705
<code>iterate_namesakes_forward_from_component()</code> (in module <code>abjad.tools.componenttools</code>), 238	<code>iterate_thread_backward_in_expr()</code> (in module <code>abjad.tools.threadtools</code>), 706
<code>iterate_notes_and_chords_backward_in_expr()</code> (in module <code>abjad.tools.leaftools</code>), 351	<code>iterate_thread_forward_from_component()</code> (in module <code>abjad.tools.threadtools</code>), 707
<code>iterate_notes_and_chords_forward_in_expr()</code> (in module <code>abjad.tools.leaftools</code>), 351	<code>iterate_thread_forward_in_expr()</code> (in module <code>abjad.tools.threadtools</code>), 708
<code>iterate_notes_and_chords_in_expr_outside_traditional_instrument_ranges()</code> (in module <code>abjad.tools.instrumenttools</code>), 335	<code>iterate_ties_backward_in_expr()</code> (in module <code>abjad.tools.tietools</code>), 560

- `iterate_tie_chains_forward_in_expr()` (in module `abjad.tools.tietools`), 561
 - `iterate_timeline_backward_from_component()` (in module `abjad.tools.componenttools`), 239
 - `iterate_timeline_backward_in_expr()` (in module `abjad.tools.componenttools`), 240
 - `iterate_timeline_forward_from_component()` (in module `abjad.tools.componenttools`), 241
 - `iterate_timeline_forward_in_expr()` (in module `abjad.tools.componenttools`), 241
 - `iterate_topmost_tie_chains_and_components_forward_in_expr()` (in module `abjad.tools.tietools`), 562
 - `iterate_tuplets_backward_in_expr()` (in module `abjad.tools.tuplettools`), 575
 - `iterate_tuplets_forward_in_expr()` (in module `abjad.tools.tuplettools`), 575
 - `iterate_vertical_moments_backward_in_expr()` (in module `abjad.tools.verticalitytools`), 722
 - `iterate_vertical_moments_forward_in_expr()` (in module `abjad.tools.verticalitytools`), 723
 - `iterate_voices_backward_in_expr()` (in module `abjad.tools.voicetools`), 584
 - `iterate_voices_forward_in_expr()` (in module `abjad.tools.voicetools`), 584
- J**
- `join_subsequences_by_sign_of_subsequence_elements()` (in module `abjad.tools.seqttools`), 675
- K**
- `key_signature` (`abjad.tools.tonalitytools.Scale` attribute), 711
 - `KeySignatureMark` (class in `abjad.tools.contexttools`), 301
 - `kind` (`abjad.tools.gracetools.Grace` attribute), 319
 - `kind` (`abjad.tools.spannertools.PianoPedalSpanner` attribute), 531
- L**
- `label_leaves_in_expr_with_inversion_equivalent_chromatic_interval_classes()` (in module `abjad.tools.leaftools`), 352
 - `label_leaves_in_expr_with_leaf_depth()` (in module `abjad.tools.leaftools`), 352
 - `label_leaves_in_expr_with_leaf_durations()` (in module `abjad.tools.leaftools`), 353
 - `label_leaves_in_expr_with_leaf_indices()` (in module `abjad.tools.leaftools`), 353
 - `label_leaves_in_expr_with_leaf_numbers()` (in module `abjad.tools.leaftools`), 353
 - `label_leaves_in_expr_with_melodic_chromatic_interval_classes()` (in module `abjad.tools.leaftools`), 354
 - `label_leaves_in_expr_with_melodic_chromatic_intervals()` (in module `abjad.tools.leaftools`), 354
 - `label_leaves_in_expr_with_melodic_counterpoint_interval_classes()` (in module `abjad.tools.leaftools`), 354
 - `label_leaves_in_expr_with_melodic_counterpoint_intervals()` (in module `abjad.tools.leaftools`), 355
 - `label_leaves_in_expr_with_melodic_diatonic_interval_classes()` (in module `abjad.tools.leaftools`), 355
 - `label_leaves_in_expr_with_melodic_diatonic_intervals()` (in module `abjad.tools.leaftools`), 356
 - `label_leaves_in_expr_with_pitch_class_numbers()` (in module `abjad.tools.leaftools`), 356
 - `label_leaves_in_expr_with_pitch_numbers()` (in module `abjad.tools.leaftools`), 357
 - `label_leaves_in_expr_with_prolated_leaf_duration()` (in module `abjad.tools.leaftools`), 357
 - `label_leaves_in_expr_with_tuplet_depth()` (in module `abjad.tools.leaftools`), 357
 - `label_leaves_in_expr_with_written_leaf_duration()` (in module `abjad.tools.leaftools`), 358
 - `label_notes_in_expr_with_note_indices()` (in module `abjad.tools.notetools`), 431
 - `label_tie_chains_in_expr_with_prolated_tie_chain_duration()` (in module `abjad.tools.tietools`), 562
 - `label_tie_chains_in_expr_with_tie_chain_durations()` (in module `abjad.tools.tietools`), 563
 - `label_tie_chains_in_expr_with_written_tie_chain_duration()` (in module `abjad.tools.tietools`), 563
 - `label_vertical_moments_in_expr_with_chromatic_interval_classes()` (in module `abjad.tools.verticalitytools`), 724
 - `label_vertical_moments_in_expr_with_chromatic_intervals()` (in module `abjad.tools.verticalitytools`), 725
 - `label_vertical_moments_in_expr_with_counterpoint_intervals()` (in module `abjad.tools.verticalitytools`), 726
 - `label_vertical_moments_in_expr_with_diatonic_intervals()` (in module `abjad.tools.verticalitytools`), 726
 - `label_vertical_moments_in_expr_with_interval_class_vectors()` (in module `abjad.tools.verticalitytools`), 727
 - `label_vertical_moments_in_expr_with_numbered_chromatic_pitch_classes()` (in module `abjad.tools.verticalitytools`), 728
 - `label_vertical_moments_in_expr_with_pitch_numbers()` (in module `abjad.tools.verticalitytools`), 729
 - `LayoutBlock` (class in `abjad.tools.lilyfiletools`), 371
 - `leading_tone` (`abjad.tools.tonalitytools.Scale` attribute), 711
 - `leaf_to_augmented_tuplet_with_n_notes_of_equal_written_duration()` (in module `abjad.tools.leaftools`), 358
 - `leaf_to_augmented_tuplet_with_proportions()` (in module `abjad.tools.leaftools`), 359
 - `leaf_to_diminished_tuplet_with_n_notes_of_equal_written_duration()` (in module `abjad.tools.leaftools`), 359
 - `leaf_to_diminished_tuplet_with_proportions()` (in module `abjad.tools.leaftools`), 359
 - `least_common_multiple()` (in module `abjad.tools.mathtools`), 640

- least_multiple_greater_equal() (in module abjad.tools.mathtools), 640
- least_power_of_two_greater_equal() (in module abjad.tools.mathtools), 641
- leaves (abjad.tools.containertools.Container attribute), 266
- leaves (abjad.tools.spannertools.Spanner attribute), 535
- leaves (abjad.tools.verticalitytools.VerticalMoment attribute), 719
- LilyFile (class in abjad.tools.lilyfiletools), 371
- lilypond_duration_string_to_rational() (in module abjad.tools.durtools), 593
- lilypond_duration_string_to_rational_list() (in module abjad.tools.durtools), 593
- LilyPondCommandMark (class in abjad.tools.marktools), 377
- LilyPondLanguageToken (class in abjad.tools.lilyfiletools), 373
- LilyPondVersionToken (class in abjad.tools.lilyfiletools), 373
- lines (abjad.tools.spannertools.StaffLinesSpanner attribute), 536
- list_abjad_environment_variables() (in module abjad.tools.cfgtools), 586
- list_abjad_templates() (in module abjad.tools.cfgtools), 586
- list_badly_formed_components_in_expr() (in module abjad.tools.componenttools), 242
- list_chromatic_pitch_numbers_in_expr() (in module abjad.tools.pitchtools), 485
- list_harmonic_chromatic_intervals_in_expr() (in module abjad.tools.pitchtools), 485
- list_harmonic_diatonic_intervals_in_expr() (in module abjad.tools.pitchtools), 485
- list_improper_contents_of_component_that_cross_prolated_offset() (in module abjad.tools.componenttools), 243
- list_inversion_equivalent_chromatic_interval_classes_pairwise_between_pitch_carriers() (in module abjad.tools.pitchtools), 486
- list_leftmost_components_with_prolated_duration_at_most() (in module abjad.tools.componenttools), 244
- list_melodic_chromatic_interval_numbers_pairwise_between_pitch_carriers() (in module abjad.tools.pitchtools), 487
- list_named_chromatic_pitch_carriers_in_expr_sorted_by_numbered_chromatic_pitch_class() (in module abjad.tools.pitchtools), 487
- list_named_chromatic_pitches_in_expr() (in module abjad.tools.pitchtools), 488
- list_nonspanning_subarrays_of_pitch_array() (in module abjad.tools.pitcharraytools), 654
- list_numbered_chromatic_pitch_classes_in_expr() (in module abjad.tools.pitchtools), 488
- list_octave_transpositions_of_pitch_carrier_within_pitch_range() (in module abjad.tools.pitchtools), 488
- list_ordered_named_chromatic_pitch_pairs_from_expr_1_to_expr_2() (in module abjad.tools.pitchtools), 488
- list_prolated_durations_of_leaves_in_expr() (in module abjad.tools.leaftools), 360
- list_time_signatures_of_measures_in_expr() (in module abjad.tools.measuretools), 414
- list_unordered_named_chromatic_pitch_pairs_in_expr() (in module abjad.tools.pitchtools), 489
- list_written_durations_of_leaves_in_expr() (in module abjad.tools.leaftools), 360
- local_maxima (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- local_minima (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- log() (in module abjad.tools.iotools), 619
- lone (abjad.tools.spannertools.ComplexBeamSpanner attribute), 518
- low (abjad.tools.intervaltreetools.BoundedInterval attribute), 604
- low (abjad.tools.intervaltreetools.IntervalTree attribute), 605
- low_max (abjad.tools.intervaltreetools.IntervalTree attribute), 605
- low_min (abjad.tools.intervaltreetools.IntervalTree attribute), 606
- ly() (in module abjad.tools.iotools), 619
- ## M
- magnitude (abjad.tools.intervaltreetools.BoundedInterval attribute), 604
- magnitude (abjad.tools.intervaltreetools.IntervalTree attribute), 606
- make_accelerating_notes_with_lilypond_multipliers() (in module abjad.tools.notetools), 432
- make_all_notes_in_ascending_and_descending_diatonic_scale() (in module abjad.tools.tonalitytools), 717
- make_augmented_tuplet_from_duration_and_proportions_and_avoid_dots() (in module abjad.tools.tuplettools), 576
- make_augmented_tuplet_from_duration_and_proportions_and_encourage_dots() (in module abjad.tools.tuplettools), 577
- make_basic_lily_file() (in module abjad.tools.lilyfiletools), 374
- make_big_centered_page_number_markup() (in module abjad.tools.markuptools), 391
- make_chromatic_pitch_class() (in module abjad.tools.spannertools), 549
- make_diminished_tuplet_from_duration_and_proportions_and_avoid_dots() (in module abjad.tools.tuplettools), 577
- make_diminished_tuplet_from_duration_and_proportions_and_encourage_dots() (in module abjad.tools.tuplettools), 578
- make_dynamic_spanner_below_with_nib_at_right() (in module abjad.tools.spannertools), 550
- make_empty_piano_score() (in module abjad.tools.scoretools), 510
- make_empty_pitch_array_from_list_of_pitch_lists() (in module abjad.tools.pitcharraytools), 655

- `make_first_n_notes_in_ascending_diatonic_scale()` (in module `abjad.tools.tonalitytools`), 718
- `make_invisible_staff()` (in module `abjad.tools.stafftools`), 556
- `make_leaves()` (in module `abjad.tools.leaftools`), 360
- `make_leaves_from_note_value_signal()` (in module `abjad.tools.leaftools`), 361
- `make_measures_with_full_measure_spacer_skips()` (in module `abjad.tools.measuretools`), 415
- `make_monophonic_percussion_score_from_nonoverlapping_intervals()` (in module `abjad.tools.intervaltreetools`), 612
- `make_multi_measure_rests()` (in module `abjad.tools.resttools`), 499
- `make_n_middle_c_centered_pitches()` (in module `abjad.tools.pitchtools`), 489
- `make_notes()` (in module `abjad.tools.notetools`), 432
- `make_notes_with_multiplied_durations()` (in module `abjad.tools.notetools`), 433
- `make_percussion_note()` (in module `abjad.tools.notetools`), 433
- `make_piano_score_from_leaves()` (in module `abjad.tools.scoretools`), 510
- `make_piano_sketch_score_from_leaves()` (in module `abjad.tools.scoretools`), 511
- `make_pitch_array_score_from_pitch_arrays()` (in module `abjad.tools.scoretools`), 512
- `make_polyphonic_percussion_score_from_nonoverlapping_intervals()` (in module `abjad.tools.intervaltreetools`), 612
- `make_populated_pitch_array_from_list_of_pitch_lists()` (in module `abjad.tools.pitcharraytools`), 656
- `make_quarter_notes_with_lilypond_multipliers()` (in module `abjad.tools.notetools`), 433
- `make_repeated_notes()` (in module `abjad.tools.notetools`), 434
- `make_repeated_notes_from_time_signature()` (in module `abjad.tools.notetools`), 434
- `make_repeated_notes_from_time_signatures()` (in module `abjad.tools.notetools`), 435
- `make_repeated_notes_with_shorter_notes_at_end()` (in module `abjad.tools.notetools`), 435
- `make_repeated_rests_from_time_signature()` (in module `abjad.tools.resttools`), 500
- `make_repeated_rests_from_time_signatures()` (in module `abjad.tools.resttools`), 500
- `make_repeated_skips_from_time_signature()` (in module `abjad.tools.skiptools`), 514
- `make_repeated_skips_from_time_signatures()` (in module `abjad.tools.skiptools`), 514
- `make_rests()` (in module `abjad.tools.resttools`), 500
- `make_rhythmic_sketch_staff()` (in module `abjad.tools.stafftools`), 556
- `make_skips_with_multiplied_durations()` (in module `abjad.tools.skiptools`), 515
- `make_solid_text_spanner_above_with_nib_at_right()` (in module `abjad.tools.spannertools`), 550
- `make_solid_text_spanner_below_with_nib_at_right()` (in module `abjad.tools.spannertools`), 551
- `make_spacing_vector()` (in module `abjad.tools.layouttools`), 624
- `make_spanner_schema()` (in module `abjad.tools.spannertools`), 552
- `make_tuplet_from_proportions_and_pair()` (in module `abjad.tools.tuplettools`), 578
- `map_sequence_elements_to_canonic_tuples()` (in module `abjad.tools.seqttools`), 675
- `map_sequence_elements_to_numbered_sublists()` (in module `abjad.tools.seqttools`), 676
- `Marimba` (class in `abjad.tools.instrumenttools`), 329
- `mark` (`abjad.tools.spannertools.DynamicTextSpanner` attribute), 522
- `Mark` (class in `abjad.tools.marktools`), 378
- `markup` (`abjad.tools.markuptools.MarkupCommand` attribute), 390
- `markup` (`abjad.tools.tonalitytools.ChordClass` attribute), 709
- `markup` (`abjad.tools.tonalitytools.TonalFunction` attribute), 712
- `Markup` (class in `abjad.tools.markuptools`), 388
- `MarkupCommand` (class in `abjad.tools.markuptools`), 389
- `mask_intervals_with_intervals()` (in module `abjad.tools.intervaltreetools`), 612
- `matches_cell()` (`abjad.tools.pitcharraytools.PitchArrayCell` method), 651
- `Matrix` (class in `abjad.tools.seqttools`), 659
- `Measure` (class in `abjad.tools.measuretools`), 395
- `measure_number` (`abjad.tools.measuretools.Measure` attribute), 396
- `MeasuredComplexBeamSpanner` (class in `abjad.tools.spannertools`), 526
- `measures` (`abjad.tools.verticalitytools.VerticalMoment` attribute), 719
- `mediant` (`abjad.tools.tonalitytools.Scale` attribute), 711
- `melodic_chromatic_interval` (`abjad.tools.pitchtools.MelodicDiatonicInterval` attribute), 446
- `melodic_chromatic_interval_class` (`abjad.tools.pitchtools.MelodicChromaticInterval` attribute), 444
- `melodic_chromatic_interval_class_segment` (`abjad.tools.pitchtools.MelodicChromaticIntervalSegment` attribute), 445
- `melodic_chromatic_interval_class_segment` (`abjad.tools.pitchtools.NamedChromaticPitchSegment` attribute), 452
- `melodic_chromatic_interval_class_vector` (`abjad.tools.pitchtools.MelodicChromaticIntervalSegment` attribute), 445

melodic_chromatic_interval_numbers	(abjad.tools.pitchtools.MelodicChromaticIntervalSegment attribute), 445	MelodicChromaticInterval (class in abjad.tools.pitchtools), 443	
melodic_chromatic_interval_numbers	(abjad.tools.pitchtools.MelodicChromaticIntervalSet attribute), 445	MelodicChromaticIntervalClass (class in abjad.tools.pitchtools), 444	
melodic_chromatic_interval_segment	(abjad.tools.pitchtools.HarmonicDiatonicIntervalSegment attribute), 441	MelodicChromaticIntervalClassVector (class in abjad.tools.pitchtools), 444	
melodic_chromatic_interval_segment	(abjad.tools.pitchtools.MelodicDiatonicIntervalSegment attribute), 447	MelodicChromaticIntervalSegment (class in abjad.tools.pitchtools), 444	
melodic_chromatic_interval_segment	(abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452	MelodicChromaticIntervalSet (class in abjad.tools.pitchtools), 445	
melodic_chromatic_interval_set	(abjad.tools.pitchtools.MelodicDiatonicIntervalSet attribute), 447	MelodicCounterpointInterval (class in abjad.tools.pitchtools), 445	
melodic_chromatic_intervals	(abjad.tools.pitchtools.MelodicChromaticIntervalSet attribute), 445	MelodicCounterpointIntervalClass (class in abjad.tools.pitchtools), 446	
melodic_counterpoint_interval	(abjad.tools.pitchtools.MelodicDiatonicInterval attribute), 446	MelodicDiatonicInterval (class in abjad.tools.pitchtools), 446	
melodic_counterpoint_interval_class	(abjad.tools.pitchtools.MelodicCounterpointInterval attribute), 446	MelodicDiatonicIntervalClass (class in abjad.tools.pitchtools), 446	
melodic_diatonic_interval_ascending	(abjad.tools.pitchtools.HarmonicDiatonicInterval attribute), 440	MelodicDiatonicIntervalSegment (class in abjad.tools.pitchtools), 447	
melodic_diatonic_interval_class	(abjad.tools.pitchtools.MelodicDiatonicInterval attribute), 446	MelodicDiatonicIntervalSet (class in abjad.tools.pitchtools), 447	
melodic_diatonic_interval_class_segment	(abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452	merge() (abjad.tools.pitcharraytools.PitchArrayRow method), 653	
melodic_diatonic_interval_descending	(abjad.tools.pitchtools.HarmonicDiatonicInterval attribute), 440	meter_to_binary_meter() (in module abjad.tools.metertools), 649	
melodic_diatonic_interval_numbers	(abjad.tools.pitchtools.MelodicDiatonicIntervalSet attribute), 447	meters (abjad.tools.spannertools.MetricGridSpanner attribute), 528	
melodic_diatonic_interval_segment	(abjad.tools.pitchtools.HarmonicDiatonicIntervalSegment attribute), 441	MetricGridSpanner (class in abjad.tools.spannertools), 527	
melodic_diatonic_interval_segment	(abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452	middle_c_position (abjad.tools.contexttools.ClefMark attribute), 297	
melodic_diatonic_interval_segment	(abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452	MidiBlock (class in abjad.tools.lilyfiletools), 373	
melodic_diatonic_interval_segment	(abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452	millisecond_pitch_pairs_to_q_events() (in module abjad.tools.quantizationtools), 735	
melodic_diatonic_interval_segment	(abjad.tools.pitchtools.HarmonicDiatonicInterval attribute), 440	milliseconds_to_q_events() (in module abjad.tools.quantizationtools), 735	
melodic_diatonic_interval_numbers	(abjad.tools.pitchtools.MelodicDiatonicIntervalSet attribute), 447	minimal_page_breaking (abjad.tools.lilyfiletools.PaperBlock attribute), 373	
melodic_diatonic_interval_segment	(abjad.tools.pitchtools.HarmonicDiatonicIntervalSegment attribute), 441	mode (abjad.tools.contexttools.KeySignatureMark attribute), 301	
melodic_diatonic_interval_segment	(abjad.tools.pitchtools.HarmonicDiatonicIntervalSegment attribute), 441	Mode (class in abjad.tools.tonalitytools), 711	
melodic_diatonic_interval_segment	(abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452	mode_name_string (abjad.tools.tonalitytools.Mode attribute), 711	
melodic_diatonic_interval_segment	(abjad.tools.tonalitytools.Mode attribute), 711	modulo (abjad.tools.sievetools.ResidueClass attribute), 702	
melodic_diatonic_intervals	(abjad.tools.pitchtools.MelodicDiatonicIntervalSet attribute), 447	move_component_subtree_to_right_in_immediate_parent_of_component() (in module abjad.tools.componenttools), 244	
		move_measure_prolation_to_full_measure_tuplet() (in module abjad.tools.measuretools), 415	

move_parentage_and_spanners_from_components_to_components() (in module abjad.tools.componenttools), 245
 move_parentage_children_and_spanners_from_components_to_components() (in module abjad.tools.containertools), 277
 move_prolation_of_full_measure_tuplet_to_meter_of_measures() (in module abjad.tools.measuretools), 416
 move_prolation_of_tuplet_to_contents_of_tuplet_and_remove_tuplet() (in module abjad.tools.tuplettools), 579
 move_spanners_from_component_to_children_of_component() (in module abjad.tools.spannertools), 552
 MultiMeasureRest (class in abjad.tools.resttools), 498
 MultipartBeamSpanner (class in abjad.tools.spannertools), 529
 multiplied_duration (abjad.tools.tuplettools.FixedDurationTuplet attribute), 569
 multiplied_duration (abjad.tools.tuplettools.Tuplet attribute), 570
 multiplier (abjad.tools.contexttools.TimeSignatureMark attribute), 305
 multiplier (abjad.tools.measuretools.Measure attribute), 396
 multiplier (abjad.tools.tuplettools.FixedDurationTuplet attribute), 569
 multiplier (abjad.tools.tuplettools.Tuplet attribute), 570
 multiply() (abjad.tools.pitchtools.NumberedChromaticPitchClass method), 457
 multiply() (abjad.tools.pitchtools.NumberedChromaticPitchClassSegment method), 458
 multiply() (abjad.tools.pitchtools.NumberedChromaticPitchClassSet method), 460
 multiply_contents_of_measures_in_expr() (in module abjad.tools.measuretools), 416
 multiply_contents_of_measures_in_expr_and_scale_meter_denominators() (in module abjad.tools.measuretools), 417
 multiply_duration_pair() (in module abjad.tools.durtools), 593
 multiply_duration_pair_and_reduce_factors() (in module abjad.tools.durtools), 593
 multiply_duration_pair_and_try_to_preserve_numerator() (in module abjad.tools.durtools), 594
 music (abjad.tools.containertools.Container attribute), 266

N

name (abjad.tools.contexttools.KeySignatureMark attribute), 301
 name (abjad.tools.marktools.Annotation attribute), 375
 name (abjad.tools.tonalitytools.ExtentIndicator attribute), 710
 name (abjad.tools.tonalitytools.InversionIndicator attribute), 710
 name (abjad.tools.tonalitytools.ScaleDegree attribute), 712
 named_chromatic_pitch (abjad.tools.marktools.Articulation attribute), 376
 named_chromatic_pitch (abjad.tools.pitchtools.Accidental attribute), 437
 named_chromatic_pitch (abjad.tools.notetools.NoteHead attribute), 427
 named_chromatic_pitch (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 455
 named_chromatic_pitch_and_clef_to_staff_position_number() (in module abjad.tools.pitchtools), 489
 named_chromatic_pitch_class (abjad.tools.pitchtools.NamedChromaticPitch attribute), 449
 named_chromatic_pitch_class (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 455
 named_chromatic_pitch_class_set (abjad.tools.pitchtools.NamedChromaticPitchClassSegment attribute), 451
 named_chromatic_pitch_class_to_scale_degree() (abjad.tools.tonalitytools.Scale method), 711
 named_chromatic_pitch_class_vector (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
 named_chromatic_pitch_classes (abjad.tools.pitchtools.NamedChromaticPitchClassSegment attribute), 451
 named_chromatic_pitch_classes (abjad.tools.pitchtools.NamedChromaticPitchClassSet attribute), 451
 named_chromatic_pitch_set (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
 named_chromatic_pitch_tokens_to_named_chromatic_pitches() (in module abjad.tools.pitchtools), 490
 named_chromatic_pitch_vector (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
 named_chromatic_pitches (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
 named_chromatic_pitches (abjad.tools.pitchtools.NamedChromaticPitchSet attribute), 453
 named_chromatic_pitches (abjad.tools.pitchtools.NamedChromaticPitchVector attribute), 453
 named_chromatic_pitches_to_harmonic_chromatic_interval_class_number() (in module abjad.tools.pitchtools), 490
 named_chromatic_pitches_to_inversion_equivalent_chromatic_interval_class_number() (in module abjad.tools.pitchtools), 490
 named_diatonic_pitch (abjad.tools.pitchtools.NamedChromaticPitch attribute), 453

- attribute), 449
- named_diatonic_pitch (abjad.tools.pitchtools.NumberedDiatonicPitch attribute), 462
- named_diatonic_pitch_class (abjad.tools.pitchtools.NamedChromaticPitch attribute), 449
- named_diatonic_pitch_class (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 455
- named_diatonic_pitch_class (abjad.tools.pitchtools.NumberedDiatonicPitch attribute), 462
- named_diatonic_pitch_class (abjad.tools.pitchtools.NumberedDiatonicPitchClass attribute), 462
- NamedChromaticPitch (class in abjad.tools.pitchtools), 447
- NamedChromaticPitchClass (class in abjad.tools.pitchtools), 450
- NamedChromaticPitchClassSegment (class in abjad.tools.pitchtools), 451
- NamedChromaticPitchClassSet (class in abjad.tools.pitchtools), 451
- NamedChromaticPitchSegment (class in abjad.tools.pitchtools), 452
- NamedChromaticPitchSet (class in abjad.tools.pitchtools), 453
- NamedChromaticPitchVector (class in abjad.tools.pitchtools), 453
- NamedDiatonicPitch (class in abjad.tools.pitchtools), 453
- NamedDiatonicPitchClass (class in abjad.tools.pitchtools), 456
- NaturalHarmonic (class in abjad.tools.notetools), 425
- negate_absolute_value_of_sequence_elements_at_indices() (in module abjad.tools.seqtools), 676
- negate_absolute_value_of_sequence_elements_cyclically() (in module abjad.tools.seqtools), 676
- negate_sequence_elements_at_indices() (in module abjad.tools.seqtools), 677
- negate_sequence_elements_cyclically() (in module abjad.tools.seqtools), 677
- next (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651
- next (abjad.tools.quantizationtools.QGrid attribute), 731
- next_integer_partition() (in module abjad.tools.mathtools), 642
- next_vertical_moment (abjad.tools.verticalitytools.VerticalMoment attribute), 719
- normalized_spacing_duration (abjad.tools.layouttools.SpacingIndication attribute), 624
- Note (class in abjad.tools.notetools), 425
- note_head (abjad.tools.notetools.Note attribute), 426
- note_heads (abjad.tools.chordtools.Chord attribute), 202
- NoteHead (class in abjad.tools.notetools), 427
- notes (abjad.tools.verticalitytools.VerticalMoment attribute), 719
- notes_and_chords_in_expr_are_on_expected_clefs() (in module abjad.tools.instrumenttools), 335
- notes_and_chords_in_expr_are_within_traditional_instrument_ranges() (in module abjad.tools.instrumenttools), 336
- number (abjad.tools.schemetools.SchemeNumber attribute), 504
- number (abjad.tools.tonalitytools.ExtentIndicator attribute), 710
- number (abjad.tools.tonalitytools.InversionIndicator attribute), 710
- number (abjad.tools.tonalitytools.ScaleDegree attribute), 712
- number_is_between_prolated_start_and_stop_offsets_of_component() (in module abjad.tools.componenttools), 246
- number_is_between_start_and_stop_offsets_of_component_in_seconds() (in module abjad.tools.componenttools), 246
- numbered_chromatic_pitch (abjad.tools.pitchtools.NamedChromaticPitch attribute), 449
- numbered_chromatic_pitch (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 455
- numbered_chromatic_pitch_class (abjad.tools.pitchtools.NamedChromaticPitch attribute), 449
- numbered_chromatic_pitch_class (abjad.tools.pitchtools.NamedChromaticPitchClass attribute), 450
- numbered_chromatic_pitch_class (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 455
- numbered_chromatic_pitch_class_segment (abjad.tools.pitchtools.NamedChromaticPitchClassSegment attribute), 451
- numbered_chromatic_pitch_class_segment (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- numbered_chromatic_pitch_class_set (abjad.tools.pitchtools.NamedChromaticPitchClassSegment attribute), 451
- numbered_chromatic_pitch_class_set (abjad.tools.pitchtools.NamedChromaticPitchClassSet attribute), 452
- numbered_chromatic_pitch_class_set (abjad.tools.pitchtools.NamedChromaticPitchSegment attribute), 452
- numbered_chromatic_pitch_class_set (abjad.tools.pitchtools.NamedChromaticPitchSet attribute), 453

- p
numbered_chromatic_pitch_class_set (abjad.tools.pitchtools.NumberedChromaticPitchClassSegment attribute), 458
numbered_chromatic_pitch_classes (abjad.tools.pitchtools.NamedChromaticPitchClassSegment attribute), 451
numbered_chromatic_pitch_classes (abjad.tools.pitchtools.NamedChromaticPitchSet attribute), 453
numbered_chromatic_pitch_classes (abjad.tools.pitchtools.NumberedChromaticPitchClassSet attribute), 460
numbered_chromatic_pitch_classes (abjad.tools.pitchtools.NumberedChromaticPitchClassVector attribute), 461
numbered_diatonic_pitch (abjad.tools.pitchtools.NamedChromaticPitch attribute), 450
numbered_diatonic_pitch (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 455
numbered_diatonic_pitch_class (abjad.tools.pitchtools.NamedChromaticPitch attribute), 450
numbered_diatonic_pitch_class (abjad.tools.pitchtools.NamedDiatonicPitch attribute), 455
numbered_diatonic_pitch_class (abjad.tools.pitchtools.NamedDiatonicPitchClass attribute), 456
numbered_diatonic_pitch_class (abjad.tools.pitchtools.NumberedDiatonicPitch attribute), 462
NumberedChromaticPitch (class in abjad.tools.pitchtools), 456
NumberedChromaticPitchClass (class in abjad.tools.pitchtools), 457
NumberedChromaticPitchClassColorMap (class in abjad.tools.pitchtools), 457
NumberedChromaticPitchClassSegment (class in abjad.tools.pitchtools), 458
NumberedChromaticPitchClassSet (class in abjad.tools.pitchtools), 459
NumberedChromaticPitchClassVector (class in abjad.tools.pitchtools), 461
NumberedDiatonicPitch (class in abjad.tools.pitchtools), 461
NumberedDiatonicPitchClass (class in abjad.tools.pitchtools), 462
numerator (abjad.tools.contexttools.TimeSignatureMark attribute), 306
numeric_seconds_to_clock_string() (in module abjad.tools.durtools), 594
numeric_seconds_to_escaped_clock_string() (in module abjad.tools.durtools), 594
O
OctaveSpanner (class in abjad.tools.spannertools), 529
octave_number (abjad.tools.pitchtools.NamedChromaticPitch attribute), 450
octave_number_to_octave_tick_string() (in module abjad.tools.pitchtools), 491
octave_tick_string_to_octave_number() (in module abjad.tools.pitchtools), 491
Offset (class in abjad.tools.quantizationtools.QEvent attribute), 729
offset (abjad.tools.spannertools.Spanner attribute), 535
Offset (class in abjad.tools.durtools), 587
offsets (abjad.tools.quantizationtools.QGrid attribute), 731
offsets (abjad.tools.quantizationtools.QGridSearchTree attribute), 734
OmissionIndicator (class in abjad.tools.tonalitytools), 711
operator (abjad.tools.sievetools.ResidueClassExpression attribute), 703
order_by() (abjad.tools.pitchtools.NamedChromaticPitchClassSet method), 452
ordered_chromatic_pitch_class_numbers_are_within_ordered_chromatic_pitch_class_numbers() (in module abjad.tools.pitchtools), 491
overlap_components (abjad.tools.verticalitytools.VerticalMoment attribute), 719
overlap_leaves (abjad.tools.verticalitytools.VerticalMoment attribute), 719
overlap_measures (abjad.tools.verticalitytools.VerticalMoment attribute), 720
overlap_notes (abjad.tools.verticalitytools.VerticalMoment attribute), 720
override (abjad.tools.spannertools.Spanner attribute), 535
overwrite_sequence_elements_at_indices() (in module abjad.tools.seqtools), 677
P
pad_measures_in_expr_with_rests() (in module abjad.tools.measuretools), 417
pad_measures_in_expr_with_skips() (in module abjad.tools.measuretools), 419
pad_to_depth() (abjad.tools.pitcharraytools.PitchArray method), 650
pad_to_width() (abjad.tools.pitcharraytools.PitchArray method), 650
pad_to_width() (abjad.tools.pitcharraytools.PitchArrayRow method), 653
pairs (abjad.tools.pitchtools.NumberedChromaticPitchClassColorMap attribute), 458

PaperBlock (class in abjad.tools.lilyfiletools), 373

parent_array (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651

parent_array (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652

parent_array (abjad.tools.pitcharraytools.PitchArrayRow attribute), 653

parent_column (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651

parent_row (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651

parse_lilypond_input_string() (in module abjad.tools.iotools), 619

partial (abjad.tools.contexttools.TimeSignatureMark attribute), 306

partition_components_cyclically_by_durations_in_seconds_exactly_with_overhang() (in module abjad.tools.componenttools), 246

partition_components_cyclically_by_durations_in_seconds_exactly_without_overhang() (in module abjad.tools.componenttools), 247

partition_components_cyclically_by_durations_in_seconds_ge_with_overhang() (in module abjad.tools.componenttools), 247

partition_components_cyclically_by_durations_in_seconds_ge_without_overhang() (in module abjad.tools.componenttools), 247

partition_components_cyclically_by_durations_in_seconds_le_with_overhang() (in module abjad.tools.componenttools), 247

partition_components_cyclically_by_durations_in_seconds_le_without_overhang() (in module abjad.tools.componenttools), 247

partition_components_cyclically_by_prolated_durations_exactly_with_overhang() (in module abjad.tools.componenttools), 247

partition_components_cyclically_by_prolated_durations_exactly_without_overhang() (in module abjad.tools.componenttools), 248

partition_components_cyclically_by_prolated_durations_ge_with_overhang() (in module abjad.tools.componenttools), 248

partition_components_cyclically_by_prolated_durations_ge_without_overhang() (in module abjad.tools.componenttools), 249

partition_components_cyclically_by_prolated_durations_le_with_overhang() (in module abjad.tools.componenttools), 249

partition_components_cyclically_by_prolated_durations_le_without_overhang() (in module abjad.tools.componenttools), 249

partition_components_once_by_durations_in_seconds_exactly_with_overhang() (in module abjad.tools.componenttools), 249

partition_components_once_by_durations_in_seconds_exactly_without_overhang() (in module abjad.tools.componenttools), 249

partition_components_once_by_durations_in_seconds_ge_with_overhang() (in module abjad.tools.componenttools), 249

partition_components_once_by_durations_in_seconds_ge_without_overhang() (in module abjad.tools.componenttools), 250

partition_components_once_by_durations_in_seconds_le_with_overhang() (in module abjad.tools.componenttools), 250

partition_components_once_by_durations_in_seconds_le_without_overhang() (in module abjad.tools.componenttools), 250

partition_components_once_by_prolated_durations_exactly_with_overhang() (in module abjad.tools.componenttools), 250

partition_components_once_by_prolated_durations_exactly_without_overhang() (in module abjad.tools.componenttools), 250

partition_components_once_by_prolated_durations_ge_with_overhang() (in module abjad.tools.componenttools), 250

partition_components_once_by_prolated_durations_ge_without_overhang() (in module abjad.tools.componenttools), 251

partition_components_once_by_prolated_durations_le_with_overhang() (in module abjad.tools.componenttools), 251

partition_components_once_by_prolated_durations_le_without_overhang() (in module abjad.tools.componenttools), 251

partition_integer_by_ratio() (in module abjad.tools.mathtools), 642

partition_integer_into_canonic_parts() (in module abjad.tools.mathtools), 642

partition_integer_into_halves() (in module abjad.tools.mathtools), 644

partition_integer_into thirds() (in module abjad.tools.mathtools), 644

partition_integer_into_units() (in module abjad.tools.mathtools), 645

partition_sequence_by_ratio_of_lengths() (in module abjad.tools.seqttools), 677

partition_sequence_by_ratio_of_weights() (in module abjad.tools.seqttools), 678

partition_sequence_by_restricted_growth_function() (in module abjad.tools.seqttools), 678

partition_sequence_by_sign_of_elements() (in module abjad.tools.seqttools), 679

partition_sequence_by_value_of_elements() (in module abjad.tools.seqttools), 679

partition_sequence_cyclically_by_counts_with_overhang() (in module abjad.tools.seqttools), 680

partition_sequence_cyclically_by_counts_without_overhang() (in module abjad.tools.seqttools), 680

partition_sequence_cyclically_by_weights_at_least_with_overhang() (in module abjad.tools.seqttools), 680

partition_sequence_cyclically_by_weights_at_least_without_overhang() (in module abjad.tools.seqttools), 680

partition_sequence_cyclically_by_weights_at_most_with_overhang() (in module abjad.tools.seqttools), 681

partition_sequence_cyclically_by_weights_at_most_without_overhang() (in module abjad.tools.seqttools), 681

partition_sequence_cyclically_by_weights_exactly_with_overhang() (in module abjad.tools.seqttools), 681

partition_sequence_cyclically_by_weights_exactly_without_overhang() (in module abjad.tools.seqttools), 682

partition_sequence_extended_to_counts_with_overhang() (in module abjad.tools.seqttools), 682

partition_sequence_extended_to_counts_without_overhang() (in module abjad.tools.seqttools), 682

partition_sequence_once_by_counts_with_overhang() (in module abjad.tools.seqttools), 682

partition_sequence_once_by_counts_without_overhang() (in module abjad.tools.seqttools), 683

- ul style="list-style-type: none; padding-left: 0;">
- partition_sequence_once_by_weights_at_least_with_overhang() (in module abjad.tools.seqttools), 683
- partition_sequence_once_by_weights_at_least_without_overhang() (in module abjad.tools.seqttools), 683
- partition_sequence_once_by_weights_at_most_with_overhang() (in module abjad.tools.seqttools), 683
- partition_sequence_once_by_weights_at_most_without_overhang() (in module abjad.tools.seqttools), 684
- partition_sequence_once_by_weights_exactly_with_overhang() (in module abjad.tools.seqttools), 684
- partition_sequence_once_by_weights_exactly_without_overhang() (in module abjad.tools.seqttools), 684
- pdf() (in module abjad.tools.iotools), 620
- pentatonic_pitch_number_to_chromatic_pitch_number() (in module abjad.tools.pitchtools), 492
- period (abjad.tools.sievetools.ResidueClassExpression attribute), 703
- permute_named_chromatic_pitch_carrier_list_by_twelve_tones() (in module abjad.tools.pitchtools), 492
- permute_sequence() (in module abjad.tools.seqttools), 685
- PhrasingSlurSpanner (class in abjad.tools.spannertools), 530
- Piano (class in abjad.tools.instrumenttools), 330
- PianoPedalSpanner (class in abjad.tools.spannertools), 530
- PianoStaff (class in abjad.tools.scoretools), 506
- Piccolo (class in abjad.tools.instrumenttools), 331
- pitch (abjad.tools.spannertools.TrillSpanner attribute), 538
- pitch_array_row_to_measure() (in module abjad.tools.measuretools), 421
- pitch_array_to_measures() (in module abjad.tools.measuretools), 421
- pitch_iterables (abjad.tools.pitchtools.NumberedChromaticPitchClassOrderMap attribute), 458
- pitch_range (abjad.tools.pitcharraytools.PitchArrayRow attribute), 653
- PitchArray (class in abjad.tools.pitcharraytools), 649
- PitchArrayCell (class in abjad.tools.pitcharraytools), 650
- PitchArrayColumn (class in abjad.tools.pitcharraytools), 652
- PitchArrayRow (class in abjad.tools.pitcharraytools), 653
- pitches (abjad.tools.pitcharraytools.PitchArray attribute), 650
- pitches (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651
- pitches (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652
- pitches (abjad.tools.pitcharraytools.PitchArrayRow attribute), 653
- pitches_by_row (abjad.tools.pitcharraytools.PitchArray attribute), 650
- PitchRange (class in abjad.tools.pitchtools), 462
- play() (in module abjad.tools.iotools), 620
- pop() (abjad.tools.chordtools.Chord method), 202
- pop() (abjad.tools.containertools.Container method), 266
- pop() (abjad.tools.pitcharraytools.PitchArrayRow method), 654
- pop() (abjad.tools.spannertools.Spanner method), 535
- pop_column() (abjad.tools.pitcharraytools.PitchArray method), 650
- pop_left() (abjad.tools.spannertools.Spanner method), 535
- pop_row() (abjad.tools.pitcharraytools.PitchArray method), 650
- position (abjad.tools.tonalitytools.ChordQualityIndicator attribute), 710
- positive_integer_to_implied_prolation_multiplier() (in module abjad.tools.durtools), 594
- preferred_denominator (abjad.tools.tuplettools.Tuplet attribute), 570
- preprolated_duration (abjad.tools.containertools.Container attribute), 267
- preprolated_duration (abjad.tools.measuretools.DynamicMeasure attribute), 394
- preprolated_duration (abjad.tools.measuretools.Measure attribute), 396
- preprolated_duration (abjad.tools.spannertools.Spanner attribute), 536
- preprolated_duration (abjad.tools.tuplettools.Tuplet attribute), 570
- prev (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651
- prev_vertical_moment (abjad.tools.verticalitytools.VerticalMoment attribute), 720
- prime_form (abjad.tools.pitchtools.NumberedChromaticPitchClassSet attribute), 460
- profile_expr() (in module abjad.tools.iotools), 620
- prolated_duration (abjad.tools.spannertools.Spanner attribute), 536
- prolated_offset (abjad.tools.verticalitytools.VerticalMoment attribute), 720
- proportional_notation_duration (abjad.tools.layouttools.SpacingIndication attribute), 624
- prune() (abjad.tools.quantizationtools.QGridSearchTree method), 734
- ## Q
- QEvent (class in abjad.tools.quantizationtools), 729
 - QGrid (class in abjad.tools.quantizationtools), 730
 - QGridQuantizer (class in abjad.tools.quantizationtools), 732
 - QGridSearchTree (class in abjad.tools.quantizationtools), 733

QGridTempoLookup (class in abjad.tools.quantizationtools), 735

quality (abjad.tools.tonalitytools.TonalFunction attribute), 712

quality_indicator (abjad.tools.tonalitytools.ChordClass attribute), 709

quality_pair (abjad.tools.tonalitytools.ChordClass attribute), 709

quality_string (abjad.tools.tonalitytools.ChordQualityIndicator attribute), 710

quality_string (abjad.tools.tonalitytools.QualityIndicator attribute), 711

QualityIndicator (class in abjad.tools.tonalitytools), 711

quarters_per_minute (abjad.tools.contexttools.TempoMark attribute), 304

R

ratio (abjad.tools.tuplettools.Tuplet attribute), 570

rational_to_duration_pair_with_multiple_of_specified_integer_denominator() (in module abjad.tools.durtools), 595

rational_to_duration_pair_with_specified_integer_denominator() (in module abjad.tools.durtools), 596

rational_to_equal_or_greater_assignable_rational() (in module abjad.tools.durtools), 596

rational_to_equal_or_greater_binary_rational() (in module abjad.tools.durtools), 597

rational_to_equal_or_lesser_assignable_rational() (in module abjad.tools.durtools), 598

rational_to_equal_or_lesser_binary_rational() (in module abjad.tools.durtools), 598

rational_to_flag_count() (in module abjad.tools.durtools), 599

rational_to_fraction_string() (in module abjad.tools.durtools), 599

rational_to_prolation_string() (in module abjad.tools.durtools), 599

rational_to_proper_fraction() (in module abjad.tools.durtools), 600

rcs (abjad.tools.sievetools.ResidueClassExpression attribute), 703

redo() (in module abjad.tools.iotools), 621

register_chromatic_pitch_class_numbers_by_chromatic_pitch_class_numbers() (in module abjad.tools.pitchtools), 493

remove() (abjad.tools.chordtools.Chord method), 202

remove() (abjad.tools.containertools.Container method), 267

remove() (abjad.tools.pitcharraytools.PitchArrayRow method), 654

remove_abjad_pyc_files() (in module abjad.tools.iotools), 621

remove_all_leaves_in_tie_chain_except_first() (in module abjad.tools.tietools), 564

remove_component_subtree_from_score_and_spanners() (in module abjad.tools.componenttools), 251

remove_empty_containers_in_expr() (in module abjad.tools.containertools), 277

remove_initial_rests_from_sequence() (in module abjad.tools.leaftools), 362

remove_leaf_and_shrink_durated_parent_containers() (in module abjad.tools.leaftools), 362

remove_markup_attached_to_component() (in module abjad.tools.markuptools), 392

remove_markup_from_leaves_in_expr() (in module abjad.tools.markuptools), 392

remove_outer_rests_from_sequence() (in module abjad.tools.leaftools), 363

remove_pitches() (abjad.tools.pitcharraytools.PitchArrayColumn method), 652

remove_powers_of_two() (in module abjad.tools.mathtools), 645

remove_row() (abjad.tools.pitcharraytools.PitchArray method), 650

remove_sequence_elements_at_indices() (in module abjad.tools.seqtools), 685

remove_sequence_elements_at_indices_cyclically() (in module abjad.tools.seqtools), 685

remove_subsequence_of_weight_at_index() (in module abjad.tools.seqtools), 685

remove_terminal_rests_from_sequence() (in module abjad.tools.leaftools), 364

remove_tie_spanners_from_components_in_expr() (in module abjad.tools.tietools), 564

remove_trivial_tuplets_in_expr() (in module abjad.tools.tuplettools), 579

repeat_contents_of_container() (in module abjad.tools.containertools), 278

repeat_last_n_elements_of_container() (in module abjad.tools.containertools), 279

repeat_leaf_and_extend_spanners() (in module abjad.tools.leaftools), 364

repeat_leaves_in_expr_and_extend_spanners() (in module abjad.tools.leaftools), 365

repeat_runs_in_sequence_to_count() (in module abjad.tools.seqtools), 686

repeat_sequence_elements_at_indices() (in module abjad.tools.seqtools), 687

repeat_sequence_elements_at_indices_cyclically() (in module abjad.tools.seqtools), 687

repeat_sequence_elements_n_times_each() (in module abjad.tools.seqtools), 687

repeat_sequence_n_times() (in module abjad.tools.seqtools), 688

repeat_sequence_to_length() (in module abjad.tools.seqtools), 688

repeat_sequence_to_weight_at_least() (in module abjad.tools.seqtools), 688

- ul style="list-style-type: none; padding-left: 0;">
- repeat_sequence_to_weight_at_most() (in module abjad.tools.seqttools), 688
- repeat_sequence_to_weight_exactly() (in module abjad.tools.seqttools), 689
- replace_components_with_children_of_components() (in module abjad.tools.componenttools), 253
- replace_contents_of_measures_in_expr() (in module abjad.tools.measuretools), 422
- replace_contents_of_target_container_with_contents_of_source_container() (in module abjad.tools.containertools), 279
- replace_larger_left_half_of_elements_in_container_with_big_endian_ints() (in module abjad.tools.containertools), 281
- replace_larger_left_half_of_elements_in_container_with_little_endian_ints() (in module abjad.tools.containertools), 281
- replace_larger_right_half_of_elements_in_container_with_big_endian_ints() (in module abjad.tools.containertools), 282
- replace_larger_right_half_of_elements_in_container_with_little_endian_ints() (in module abjad.tools.containertools), 283
- replace_leaves_in_expr_with_skips() (in module abjad.tools.skiptools), 515
- replace_n_edge_elements_in_container_with_big_endian_ints() (in module abjad.tools.containertools), 283
- replace_n_edge_elements_in_container_with_little_endian_ints() (in module abjad.tools.containertools), 284
- replace_n_edge_elements_in_container_with_rests() (in module abjad.tools.containertools), 284
- replace_sequence_elements_cyclically_with_new_material() (in module abjad.tools.seqttools), 689
- replace_smaller_left_half_of_elements_in_container_with_big_endian_ints() (in module abjad.tools.containertools), 285
- replace_smaller_left_half_of_elements_in_container_with_little_endian_ints() (in module abjad.tools.containertools), 286
- replace_smaller_right_half_of_elements_in_container_with_big_endian_ints() (in module abjad.tools.containertools), 287
- replace_smaller_right_half_of_elements_in_container_with_little_endian_ints() (in module abjad.tools.containertools), 287
- report() (abjad.tools.markuptools.MarkupCommand method), 390
- report_as_string_format_contributions_of_all_spanners_attached_to_measures() (in module abjad.tools.spannertools), 552
- report_as_string_format_contributions_of_all_spanners_attached_to_measures_cyclically() (in module abjad.tools.spannertools), 553
- report_component_format_contributions_as_string() (in module abjad.tools.componenttools), 253
- report_container_modifications_as_string() (in module abjad.tools.containertools), 288
- report_meter_distribution_as_string() (in module abjad.tools.measuretools), 423
- representative_boolean_train (abjad.tools.sievetools.ResidueClassExpression attribute), 703
- representative_congruent_bases (abjad.tools.sievetools.ResidueClassExpression attribute), 703
- residue (abjad.tools.sievetools.ResidueClass attribute), 702
- ResidueClass (class in abjad.tools.sievetools), 701
- ResidueClassExpression (class in abjad.tools.sievetools), 702
- resolve_overlaps_between_nonoverlapping_trees() (in module abjad.tools.intervaltreetools), 612
- resolve_overlaps_between_nonoverlapping_trees_excluding_remainders_left() (in module abjad.tools.intervaltreetools), 613
- respell_named_chromatic_pitches_in_expr_with_flats() (in module abjad.tools.pitchtools), 493
- respell_named_chromatic_pitches_in_expr_with_sharps() (in module abjad.tools.pitchtools), 493
- Rest (class in abjad.tools.resttools), 498
- retain_disjuncts(elements_at_indices) (in module abjad.tools.seqttools), 689
- retain_disjuncts(elements_at_indices_cyclically) (in module abjad.tools.seqttools), 690
- retrograde() (abjad.tools.pitchtools.NamedChromaticPitchClassSegment method), 451
- restgrade() (abjad.tools.pitchtools.NumberedChromaticPitchClassSegment method), 459
- reverse_contents_of_container() (in module abjad.tools.containertools), 289
- reverse_sequence() (in module abjad.tools.seqttools), 690
- reverse_sequence_elements() (in module abjad.tools.seqttools), 690
- rewrite_rational_under_new_tempo() (in module abjad.tools.durtools), 600
- RhythmicStaff (class in abjad.tools.stafftools), 553
- rotational_degrees (abjad.tools.tonalitytools.ScaleDegree attribute), 712
- root (abjad.tools.tonalitytools.ChordClass attribute), 709
- root_candidate_degrees (abjad.tools.tonalitytools.TonalFunction attribute), 713
- root_string (abjad.tools.tonalitytools.ChordClass attribute), 709
- rotate() (abjad.tools.pitchtools.NamedChromaticPitchClassSegment method), 451
- rotate() (abjad.tools.pitchtools.NumberedChromaticPitchClassSegment method), 459
- rotate_sequence() (in module abjad.tools.seqttools), 690
- rotation (abjad.tools.tonalitytools.ChordQualityIndicator attribute), 710
- round_interval_bounds_to_nearest_multiple_of_rational() (in module abjad.tools.intervaltreetools), 613
- row_index (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651
- row_index (abjad.tools.pitcharraytools.PitchArrayRow attribute), 654
- rows (abjad.tools.pitcharraytools.PitchArray attribute), 650
- rows (abjad.tools.seqttools.CyclicMatrix attribute), 658

rows (abjad.tools.seqttools.Matrix attribute), 660

S

save_last_ly_as() (in module abjad.tools.iotools), 621

save_last_pdf_as() (in module abjad.tools.iotools), 622

Scale (class in abjad.tools.tonalitytools), 711

scale_aggregate_magnitude_by_rational() (in module abjad.tools.intervaltreetools), 613

scale_aggregate_magnitude_to_rational() (in module abjad.tools.intervaltreetools), 614

scale_by_rational() (abjad.tools.intervaltreetools.BoundedInterval method), 604

scale_contents_of_container() (in module abjad.tools.containertools), 289

scale_contents_of_measures_in_expr() (in module abjad.tools.measuretools), 423

scale_contents_of_tuplets_in_expr_by_multiplier() (in module abjad.tools.tuplettools), 580

scale_degree (abjad.tools.tonalitytools.TonalFunction attribute), 713

scale_degree_to_named_chromatic_pitch_class() (abjad.tools.tonalitytools.Scale method), 711

scale_interval_magnitudes_by_rational() (in module abjad.tools.intervaltreetools), 614

scale_interval_magnitudes_to_rational() (in module abjad.tools.intervaltreetools), 615

scale_interval_offsets_by_rational() (in module abjad.tools.intervaltreetools), 615

scale_measure_by_multiplier_and_adjust_meter() (in module abjad.tools.measuretools), 423

scale_measure_denominator_and_adjust_measure_contents() (in module abjad.tools.measuretools), 423

scale_preprolated_leaf_duration() (in module abjad.tools.leaftools), 365

scale_to_rational() (abjad.tools.intervaltreetools.BoundedInterval method), 604

ScaleDegree (class in abjad.tools.tonalitytools), 712

SchemeAssociativeList (class in abjad.tools.schemetools), 501

SchemeBoolean (class in abjad.tools.schemetools), 502

SchemeColor (class in abjad.tools.schemetools), 502

SchemeFunction (class in abjad.tools.schemetools), 503

SchemeMoment (class in abjad.tools.schemetools), 503

SchemeNumber (class in abjad.tools.schemetools), 503

SchemePair (class in abjad.tools.schemetools), 504

SchemeString (class in abjad.tools.schemetools), 504

SchemeVariable (class in abjad.tools.schemetools), 505

SchemeVector (class in abjad.tools.schemetools), 505

SchemeVectorConstant (class in abjad.tools.schemetools), 505

Score (class in abjad.tools.scoretools), 507

ScoreBlock (class in abjad.tools.lilyfiletools), 374

search_tree (abjad.tools.quantizationtools.QGridQuantizer attribute), 733

semitones (abjad.tools.pitchtools.Accidental attribute), 437

semitones (abjad.tools.pitchtools.HarmonicDiatonicInterval attribute), 440

semitones (abjad.tools.pitchtools.MelodicDiatonicInterval attribute), 446

set (abjad.tools.spannertools.Spanner attribute), 536

set_accidental_style_on_sequential_contexts_in_expr() (in module abjad.tools.contexttools), 317

set_ascending_named_chromatic_pitches_on_nontied_pitched_components() (in module abjad.tools.pitchtools), 494

set_ascending_named_diatonic_pitches_on_nontied_pitched_components() (in module abjad.tools.pitchtools), 494

set_container_multiplier() (in module abjad.tools.containertools), 290

set_default_accidental_spelling() (in module abjad.tools.cfgtools), 586

set_denominator_of_tuplets_in_expr_to_at_least() (in module abjad.tools.tuplettools), 580

set_line_breaks_cyclically_by_line_duration_ge() (in module abjad.tools.layouttools), 625

set_line_breaks_cyclically_by_line_duration_in_seconds_ge() (in module abjad.tools.layouttools), 626

set_measure_denominator_and_adjust_numerator() (in module abjad.tools.measuretools), 424

set_preprolated_leaf_duration() (in module abjad.tools.leaftools), 367

set_vertical_positioning_pitch_on_rest() (in module abjad.tools.resttools), 500

shape_string (abjad.tools.spannertools.HairpinSpanner attribute), 525

shift_aggregate_offset_by_rational() (in module abjad.tools.intervaltreetools), 615

shift_aggregate_offset_to_rational() (in module abjad.tools.intervaltreetools), 616

shift_by_rational() (abjad.tools.intervaltreetools.BoundedInterval method), 604

shift_to_rational() (abjad.tools.intervaltreetools.BoundedInterval method), 604

short_instrument_name (abjad.tools.contexttools.InstrumentMark attribute), 300

show() (in module abjad.tools.iotools), 622

show_leaves() (in module abjad.tools.leaftools), 368

sign() (in module abjad.tools.mathtools), 646

signature (abjad.tools.intervaltreetools.BoundedInterval attribute), 605

size (abjad.tools.pitcharraytools.PitchArray attribute), 650

Skip (class in abjad.tools.skiptools), 513

slope (abjad.tools.pitchtools.MelodicChromaticIntervalSegment attribute), 445
 SlurSpanner (class in abjad.tools.spannertools), 531
 sounding_pitch (abjad.tools.notetools.Note attribute), 426
 sounding_pitches (abjad.tools.chordtools.Chord attribute), 203
 SpacingIndication (class in abjad.tools.layouttools), 624
 span (abjad.tools.spannertools.DuratedComplexBeamSpanner attribute), 522
 span (abjad.tools.spannertools.MeasuredComplexBeamSpanner attribute), 527
 Spanner (class in abjad.tools.spannertools), 532
 splice_new_elements_between_sequence_elements() (in module abjad.tools.seqttools), 691
 split_at_rational() (abjad.tools.intervaltreetools.BoundedInterval attribute), 605
 split_component_at_prolated_duration_and_do_not_fracture_crossing_spanners() (in module abjad.tools.componenttools), 254
 split_component_at_prolated_duration_and_fracture_crossing_spanners() (in module abjad.tools.componenttools), 255
 split_components_cyclically_by_prolated_durations_and_do_not_fracture_crossing_spanners() (in module abjad.tools.componenttools), 255
 split_components_cyclically_by_prolated_durations_and_fracture_crossing_spanners() (in module abjad.tools.componenttools), 256
 split_components_once_by_prolated_durations_and_do_not_fracture_crossing_spanners() (in module abjad.tools.componenttools), 257
 split_components_once_by_prolated_durations_and_fracture_crossing_spanners() (in module abjad.tools.componenttools), 258
 split_container_at_index_and_do_not_fracture_crossing_spanners() (in module abjad.tools.containertools), 291
 split_container_at_index_and_fracture_crossing_spanners() (in module abjad.tools.containertools), 292
 split_container_cyclically_by_counts_and_do_not_fracture_crossing_spanners() (in module abjad.tools.containertools), 293
 split_container_cyclically_by_counts_and_fracture_crossing_spanners() (in module abjad.tools.containertools), 294
 split_container_once_by_counts_and_do_not_fracture_crossing_spanners() (in module abjad.tools.containertools), 295
 split_container_once_by_counts_and_fracture_crossing_spanners() (in module abjad.tools.containertools), 296
 split_intervals_at_rationals() (in module abjad.tools.intervaltreetools), 616
 split_leaf_at_prolated_duration_and_rest_right_half() (in module abjad.tools.leaftools), 369
 split_on_bar() (abjad.tools.spannertools.MetricGridSpanner method), 528
 split_sequence_cyclically_by_weights_with_overhang() (in module abjad.tools.seqttools), 691
 split_sequence_cyclically_by_weights_without_overhang() (in module abjad.tools.seqttools), 692
 split_sequence_extended_to_weights_with_overhang() (in module abjad.tools.seqttools), 692
 split_sequence_extended_to_weights_without_overhang() (in module abjad.tools.seqttools), 692
 split_sequence_once_by_weights_with_overhang() (in module abjad.tools.seqttools), 692
 split_sequence_once_by_weights_without_overhang() (in module abjad.tools.seqttools), 693
 splitting_condition() (abjad.tools.spannertools.MetricGridSpanner method), 528
 spread (abjad.tools.pitchtools.MelodicChromaticIntervalSegment attribute), 445
 staff (abjad.tools.contexttools.StaffChangeMark attribute), 303
 Staff (class in abjad.tools.stafftools), 554
 staff_spaces (abjad.tools.pitchtools.HarmonicDiatonicInterval attribute), 440
 staff_spaces (abjad.tools.pitchtools.MelodicDiatonicInterval attribute), 446
 StaffChangeMark (class in abjad.tools.contexttools), 302
 StaffGroup (class in abjad.tools.scoretools), 507
 StaffSpanner (class in abjad.tools.spannertools), 536
 stafftools (abjad.tools.pitchtools module), 440
 start_cells (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652
 start_crossing_spanners() (abjad.tools.marktools.Mark attribute), 378
 start_components (abjad.tools.verticalitytools.VerticalMoment attribute), 720
 start_dynamic_string (abjad.tools.spannertools.HairpinSpanner attribute), 525
 start_leaves (abjad.tools.verticalitytools.VerticalMoment attribute), 720
 start_notes (abjad.tools.verticalitytools.VerticalMoment attribute), 720
 start_pitch (abjad.tools.pitchtools.PitchRange attribute), 463
 start_pitch_is_included_in_range (abjad.tools.pitchtools.PitchRange attribute), 463
 start_pitches (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652
 StemTremolo (class in abjad.tools.marktools), 379
 stop (abjad.tools.spannertools.OctavationSpanner attribute), 530
 stop (abjad.tools.tonalitytools.SuspensionIndicator attribute), 712
 stop_cells (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652
 stop_dynamic_string (abjad.tools.spannertools.HairpinSpanner attribute), 525

- stop_pitch (abjad.tools.pitchtools.PitchRange attribute), 463
- stop_pitch_is_included_in_range (abjad.tools.pitchtools.PitchRange attribute), 463
- stop_pitches (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652
- style (abjad.tools.spannertools.PianoPedalSpanner attribute), 531
- subdivide_indices() (abjad.tools.quantizationtools.QGrid method), 731
- subdominant (abjad.tools.tonalitytools.Scale attribute), 711
- submediant (abjad.tools.tonalitytools.Scale attribute), 711
- suggest_clef_for_named_chromatic_pitches() (in module abjad.tools.pitchtools), 495
- sum_consecutive_sequence_elements_by_sign() (in module abjad.tools.seqttools), 693
- sum_duration_of_components_in_seconds() (in module abjad.tools.componenttools), 259
- sum_preprolated_duration_of_components() (in module abjad.tools.componenttools), 260
- sum_prolated_duration_of_components() (in module abjad.tools.componenttools), 260
- sum_sequence_elements_at_indices() (in module abjad.tools.seqttools), 694
- superdominant (abjad.tools.tonalitytools.Scale attribute), 711
- suppress_meter (abjad.tools.measuretools.DynamicMeasure attribute), 394
- suspension (abjad.tools.tonalitytools.TonalFunction attribute), 713
- SuspensionIndicator (class in abjad.tools.tonalitytools), 712
- symbolic_string (abjad.tools.pitchtools.Accidental attribute), 437
- symbolic_string (abjad.tools.tonalitytools.ScaleDegree attribute), 712
- symbolic_string (abjad.tools.tonalitytools.TonalFunction attribute), 713
- ## T
- tabulate_well_formedness_violations_in_expr() (in module abjad.tools.componenttools), 261
- target_context (abjad.tools.contexttools.ContextMark attribute), 298
- target_duration (abjad.tools.tuplettools.FixedDurationTuplet attribute), 569
- tempo (abjad.tools.quantizationtools.QGridQuantizer attribute), 733
- tempo (abjad.tools.quantizationtools.QGridTempoLookup attribute), 735
- tempo_indication (abjad.tools.layouttools.SpacingIndication attribute), 624
- tempo_lookup (abjad.tools.quantizationtools.QGridQuantizer attribute), 733
- tempo_scaled_leaves_to_q_events() (in module abjad.tools.quantizationtools), 736
- tempo_scaled_rational_to_milliseconds() (in module abjad.tools.quantizationtools), 736
- tempo_scaled_rationals_to_q_events() (in module abjad.tools.quantizationtools), 736
- TempoMark (class in abjad.tools.contexttools), 303
- TextScriptSpanner (class in abjad.tools.spannertools), 537
- TextSpanner (class in abjad.tools.spannertools), 537
- threshold (abjad.tools.quantizationtools.QGridQuantizer attribute), 733
- tie_chain_to_augmented_tuplet_with_proportions_and_avoid_dots() (in module abjad.tools.tietools), 564
- tie_chain_to_augmented_tuplet_with_proportions_and_encourage_dots() (in module abjad.tools.tietools), 565
- tie_chain_to_diminished_tuplet_with_proportions_and_avoid_dots() (in module abjad.tools.tietools), 567
- tie_chain_to_diminished_tuplet_with_proportions_and_encourage_dots() (in module abjad.tools.tietools), 568
- TieSpanner (class in abjad.tools.tietools), 556
- TimeSignatureMark (class in abjad.tools.contexttools), 304
- title (abjad.tools.tonalitytools.InversionIndicator attribute), 710
- title_string (abjad.tools.tonalitytools.ScaleDegree attribute), 712
- title_string (abjad.tools.tonalitytools.SuspensionIndicator attribute), 712
- token (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651
- TonalFunction (class in abjad.tools.tonalitytools), 712
- tonic (abjad.tools.contexttools.KeySignatureMark attribute), 301
- tonic (abjad.tools.tonalitytools.Scale attribute), 711
- transpose() (abjad.tools.pitchtools.NamedChromaticPitchClass method), 451
- transpose() (abjad.tools.pitchtools.NamedChromaticPitchClassSegment method), 451
- transpose() (abjad.tools.pitchtools.NamedChromaticPitchClassSet method), 452
- transpose() (abjad.tools.pitchtools.NamedChromaticPitchSegment method), 452
- transpose() (abjad.tools.pitchtools.NamedChromaticPitchSet method), 453
- transpose() (abjad.tools.pitchtools.NumberedChromaticPitch method), 457
- transpose() (abjad.tools.pitchtools.NumberedChromaticPitchClass method), 457
- transpose() (abjad.tools.pitchtools.NumberedChromaticPitchClassSegment method), 459

- transpose() (abjad.tools.pitchtools.NumberedChromaticPitchClassSet method), 460
- transpose() (abjad.tools.tonalitytools.ChordClass method), 709
- transpose_chromatic_pitch_by_melodic_chromatic_interval_segment() (in module abjad.tools.pitchtools), 495
- transpose_chromatic_pitch_class_number_by_octaves_to_nearest_neighbor_of_chromatic_pitch_number() (in module abjad.tools.pitchtools), 496
- transpose_chromatic_pitch_number_by_octave_transposition_mapping() (in module abjad.tools.pitchtools), 496
- transpose_named_chromatic_pitch_by_melodic_chromatic_interval_and_respell() (in module abjad.tools.pitchtools), 497
- transpose_notes_and_chords_in_expr_from_fingered_pitch_to_sounding_pitch() (in module abjad.tools.instrumenttools), 337
- transpose_notes_and_chords_in_expr_from_sounding_pitch_to_fingered_pitch() (in module abjad.tools.instrumenttools), 337
- transpose_pitch_carrier_by_melodic_interval() (in module abjad.tools.pitchtools), 497
- transpose_pitch_expr_into_pitch_range() (in module abjad.tools.pitchtools), 498
- tremolo_flags (abjad.tools.marktools.StemTremolo attribute), 379
- TrillSpanner (class in abjad.tools.spannertools), 538
- trim() (abjad.tools.tuplettools.FixedDurationTuplet method), 569
- Trombone (class in abjad.tools.instrumenttools), 331
- Trumpet (class in abjad.tools.instrumenttools), 332
- truncate_runs_in_sequence() (in module abjad.tools.seqttools), 694
- truncate_sequence_to_sum() (in module abjad.tools.seqttools), 694
- truncate_sequence_to_weight() (in module abjad.tools.seqttools), 695
- Tuba (class in abjad.tools.instrumenttools), 332
- Tuplet (class in abjad.tools.tuplettools), 569
- tweak (abjad.tools.notetools.NoteHead attribute), 427
- twelve_tone_complete (abjad.tools.pitchtools.NumberedChromaticPitchClassColorMap attribute), 458
- TwelveToneRow (class in abjad.tools.pitchtools), 463
- twenty_four_tone_complete (abjad.tools.pitchtools.NumberedChromaticPitchClassColorMap attribute), 458
- ## U
- underscore_delimited_lowercase_to_lowercamelcase() (in module abjad.tools.iotools), 622
- underscore_delimited_lowercase_to_uppercamelcase() (in module abjad.tools.iotools), 622
- units_per_minute (abjad.tools.contexttools.TempoMark attribute), 304
- UntunedPercussion (class in abjad.tools.instrumenttools), 333
- value (abjad.tools.marktools.Annotation attribute), 375
- value (abjad.tools.quantizationtools.QEvent attribute), 729
- VerticalMoment (class in abjad.tools.verticalitytools), 718
- Vibraphone (class in abjad.tools.instrumenttools), 333
- Viola (class in abjad.tools.instrumenttools), 334
- Violin (class in abjad.tools.instrumenttools), 334
- Voice (class in abjad.tools.voicetools), 581
- voice_crossing_count (abjad.tools.pitcharraytools.PitchArray attribute), 639
- ## V
- weight (abjad.tools.pitcharraytools.PitchArray attribute), 650
- weight (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651
- weight (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652
- weight (abjad.tools.pitcharraytools.PitchArrayRow attribute), 654
- weight() (in module abjad.tools.mathtools), 646
- width (abjad.tools.pitcharraytools.PitchArray attribute), 650
- width (abjad.tools.pitcharraytools.PitchArrayCell attribute), 651
- width (abjad.tools.pitcharraytools.PitchArrayColumn attribute), 652
- width (abjad.tools.pitcharraytools.PitchArrayRow attribute), 654
- withdraw() (abjad.tools.pitcharraytools.PitchArrayRow method), 654
- withdraw_components_from_spanners_covered_by_components() (in module abjad.tools.spannertools), 553
- write_expr_to_ly() (in module abjad.tools.iotools), 623
- write_expr_to_ly_and_to_pdf_and_show() (in module abjad.tools.iotools), 623
- write_expr_to_pdf() (in module abjad.tools.iotools), 623
- written_duration (abjad.tools.spannertools.Spanner attribute), 536
- written_pitch (abjad.tools.notetools.Note attribute), 426
- written_pitch (abjad.tools.notetools.NoteHead attribute), 427
- written_pitch (abjad.tools.spannertools.TrillSpanner attribute), 538
- written_pitches (abjad.tools.chordtools.Chord attribute), 203
- ## X
- Xylophone (class in abjad.tools.instrumenttools), 335

Y

- `yield_all_assignable_rationals_in_cantor_diagonalized_order()` (in module `abjad.tools.durtools`), 601
- `yield_all_combinations_of_sequence_elements()` (in module `abjad.tools.seqtools`), 696
- `yield_all_compositions_of_integer()` (in module `abjad.tools.mathtools`), 646
- `yield_all_k_ary_sequences_of_length()` (in module `abjad.tools.seqtools`), 696
- `yield_all_pairs_between_sequences()` (in module `abjad.tools.seqtools`), 696
- `yield_all_partitions_of_integer()` (in module `abjad.tools.mathtools`), 647
- `yield_all_partitions_of_sequence()` (in module `abjad.tools.seqtools`), 697
- `yield_all_permutations_of_sequence()` (in module `abjad.tools.seqtools`), 697
- `yield_all_permutations_of_sequence_in_orbit()` (in module `abjad.tools.seqtools`), 697
- `yield_all_positive_integer_pairs_in_cantor_diagonalized_order()` (in module `abjad.tools.durtools`), 601
- `yield_all_positive_rationals_in_cantor_diagonalized_order()` (in module `abjad.tools.durtools`), 602
- `yield_all_positive_rationals_in_cantor_diagonalized_order_uniquely()` (in module `abjad.tools.durtools`), 602
- `yield_all_prolation_rewrite_pairs_of_rational_in_cantor_diagonalized_order()` (in module `abjad.tools.durtools`), 603
- `yield_all_restricted_growth_functions_of_length()` (in module `abjad.tools.seqtools`), 698
- `yield_all_rotations_of_sequence()` (in module `abjad.tools.seqtools`), 698
- `yield_all_set_partitions_of_sequence()` (in module `abjad.tools.seqtools`), 698
- `yield_all_subchords_of_chord()` (in module `abjad.tools.chordtools`), 208
- `yield_all_subsequences_of_sequence()` (in module `abjad.tools.seqtools`), 699
- `yield_all_unordered_pairs_of_sequence()` (in module `abjad.tools.seqtools`), 699
- `yield_components_grouped_by_preprolated_duration()` (in module `abjad.tools.componenttools`), 261
- `yield_components_grouped_by_prolated_duration()` (in module `abjad.tools.componenttools`), 262
- `yield_groups_of_chords_in_sequence()` (in module `abjad.tools.chordtools`), 208
- `yield_groups_of_mixed_klasses_in_sequence()` (in module `abjad.tools.componenttools`), 262
- `yield_groups_of_mixed_notes_and_chords_in_sequence()` (in module `abjad.tools.leaftools`), 369
- `yield_groups_of_notes_in_sequence()` (in module `abjad.tools.notetools`), 436
- `yield_groups_of_rests_in_sequence()` (in module `abjad.tools.resttools`), 501
- `yield_groups_of_skips_in_sequence()` (in module `abjad.tools.skiptools`), 515
- `yield_outer_product_of_sequences()` (in module `abjad.tools.seqtools`), 700
- `yield_topmost_components_grouped_by_type()` (in module `abjad.tools.componenttools`), 263
- `yield_topmost_components_of_class_grouped_by_type()` (in module `abjad.tools.componenttools`), 263

Z

- `zip_sequences_cyclically()` (in module `abjad.tools.seqtools`), 700
- `zip_sequences_without_truncation()` (in module `abjad.tools.seqtools`), 701